Thermodiffusion and Thermoelectricity in Electrolyte Solutions

Miikka Jokinen

Thermodiffusion and Thermoelectricity in Electrolyte Solutions

Miikka Jokinen

A doctoral dissertation completed for the degree of Doctor of Science (Technology) to be defended, with the permission of the Aalto University School of Chemical Engineering, at a public examination held at the lecture hall KE1 (Kemistintie 1) of the school on 15 October 2021 at 12.

Aalto University
School of Chemical Engineering
Department of Chemistry and Materials Science
Research group of Physical Chemistry and Electrochemistry

Supervising professor

Professor Lasse Murtomäki, Aalto University, Finland

Thesis advisor

Professor Lasse Murtomäki, Aalto University, Finland

Preliminary examiners

Professor Vladimir Garcia-Morales, University of Valencia, Spain

Professor Aliaksei Boika, University of Akron, USA

Opponent

Professor Dr. Simone Wiegand, Forschungszentrum Jülich, Germany

Aalto University publication series

DOCTORAL DISSERTATIONS 128/2021

© 2021 Miikka Jokinen

ISBN 978-952-64-0516-2 (printed)

ISBN 978-952-64-0517-9 (pdf)

ISSN 1799-4934 (printed)

ISSN 1799-4942 (pdf)

<http://urn.fi/URN:ISBN:978-952-64-0517-9>

Unigrafia Oy

Helsinki 2021

Finland

Author

Miikka Jokinen

Name of the doctoral dissertation

Thermoelectricity and Thermoelectricity in Electrolyte Solutions

Publisher School of Chemical Engineering

Unit Department of Chemistry and Materials Science

Series Aalto University publication series DOCTORAL DISSERTATIONS 128/2021

Field of research Physical chemistry

Manuscript submitted 24 August 2021

Date of the defence 15 October 2021

Permission for public defence granted (date) 15 September 2021

Language English

☐ **Monograph**

☒ **Article dissertation**

☐ **Essay dissertation**

Abstract

Thermoelectricity and thermoelectricity are transport phenomena driven by the coupling of heat and mass fluxes. This coupling creates and maintains concentration gradients in the presence of temperature gradients, a process known as thermoelectricity or the Soret effect. If the thermally transported particles are charged, a thermoelectric effect known as the Seebeck effect can be observed: the temperature gradient creates also an electric potential gradient to the system.

The coupling of heat with other fluxes could offer interesting applications and insight into various fields of science. The on-going climate crisis increases the appeal of heat harvesting, and advances in biochemistry are looking to exploit thermoelectricity as a purification and analysis method. However, to unlock the full potential of these applications, the fundamentals of non-isothermal transport processes need to be thoroughly understood.

The theory of irreversible thermodynamics can explain these effects and the coupling of heat, mass and electricity fluxes. By formulating the entropy balance for the system it is understood that in electrolyte systems, the ionic heats of transport determine, to a large extent, the extent and direction of the Soret and the Seebeck effects. However, the non-isothermal transport processes of electrolytes are complicated by the fact that the transport of positively and negatively charged particles is coupled through electrostatic interactions. The thesis investigates this dynamics in three different experimental cases, and advances methods for measuring these effects in electrolyte mixtures.

Heat harvesting with ion-exchange membranes and salt solutions was shown to be possible in practice. The system successfully converted heat into electric power, and the performance could be well explained with the theory – electrolytes with small or negative heat of transport generated largest cell potentials. The results also suggested potential ways to improve the electric power output from the cell.

The Soret effect can be measured and understood in simple electrolyte solutions with existing methods, but experiments in mixtures are more challenging. A new method based on electrochemical impedance spectroscopy (EIS) was developed to measure the Soret effect and the heats of transport of red/ox active electrolytes in a mixture. A theory for the impedance response was developed and verified with measurements in a thin cell. The transport in a mixture was measured also in the case of electrochemically inactive trace electrolyte. It was shown that the supporting salt strongly affects the thermoelectricity of the trace electrolyte: in extreme cases, thermophobic behavior (enriches in cold regions) could potentially be reversed to thermophilic (enriches in hot regions).

Keywords Thermoelectricity, thermoelectricity, Seebeck effect, Soret effect, non-isothermal transport, thermal membrane potential, heat harvesting, impedance, polyelectrolyte transport

ISBN (printed) 978-952-64-0516-2

ISBN (pdf) 978-952-64-0517-9

ISSN (printed) 1799-4934

ISSN (pdf) 1799-4942

Location of publisher Helsinki

Location of printing Helsinki **Year** 2021

Pages 103

urn <http://urn.fi/URN:ISBN:978-952-64-0517-9>

Tekijä

Miikka Jokinen

Väitöskirjan nimi

Termodiffuusio ja termosähköisyys elektrolyyttiliuoksissa

Julkaisija Kemian tekniikan korkeakoulu

Yksikkö Kemian ja materiaalitieteen laitos

Sarja Aalto University publication series DOCTORAL DISSERTATIONS 128/2021

Tutkimusala Fysikaalinen kemia ja sähkökemian

Käsikirjoituksen pvm 24.08.2021

Väitöspäivä 15.10.2021

Väittelyluvan myöntämispäivä 15.09.2021

Kieli Englanti

☐ **Monografia**

☒ **Artikkeliväitöskirja**

☐ **Esseeväitöskirja**

Tiivistelmä

Termodiffuusio ja termosähköisyys ovat kuljetusilmiöitä, joissa havaitaan lämpövuon ja ainevuon kytkeytyminen. Kytkeytymisen avulla lämpötilagradientteja voidaan hyödyntää pitoisuuserojen luomisessa, jolloin puhutaan termodiffusiosta tai Soret-ilmiöstä. Jos lämpövuon avulla kuljetetut partikkelit ovat sähköisesti varautuneita, systeemiin syntyy sähköinen jännite, jolloin puhutaan Seebeck-ilmiöstä.

Ilmiöitä voidaan hyödyntää monilla eri tavoilla. Seebeck-ilmiö mahdollistaa hukkalämmön talteenoton ja muuntamisen sähköksi, mikä on kiinnostava lisä ilmastokriisin vastaisessa taistelussa. Termodiffuusiota voidaan puolestaan hyödyntää esimerkiksi biokemian saralla mm. analyysi- ja erotusmenetelmänä. Käyttökohteiden tehokas kehittäminen vaatii kuitenkin ilmiöiden perusteiden, ei-isotermisten kuljetusprosessien, vahvaa ymmärrystä.

Irreversiibelien prosessien termodynamiikan avulla eri voiden kytkeytymisen syyt ja seuraukset voidaan ymmärtää. Analysoimalla tutkittavien systeemien entropiatasetta huomataan, että parametri nimeltä ioninen kuljetuslämpö selittää suurelta osin sekä Soret- että Seebeck-ilmiön suunnan ja voimakkuuden elektrolyttisysteemeissä. Elektrolyttien kuljetusta kuitenkin monimutkaistaa positiivisesti ja negatiivisesti varautuneiden ionien kytkeytyminen sähköstaattisten vuorovaikutusten vuoksi. Tässä väitöskirjassa tutkitaan tätä dynamiikkaa kokeellisesti kolmesta hieman eri näkökulmasta. Tutkimus myös edistää näiden ilmiöiden parempaa mittaamista ja ymmärrystä erityisesti elektrolyttiseoksissa.

Väitöskirjassa näytettiin, kuinka hukkalämmön talteenotto on käytännössä mahdollista ioninvaihtomembraaneihin ja suolaliuokseen perustuvassa kennossa ja millä tavoin talteenottoa olisi mahdollista entisestään tehostaa. Kennon toimintaa kuvaavan teorian avulla mittaustulokset voitiin yhdistää ilmiötä selittäviin parametreihin, ja näytettiin, että voimakkain Seebeck-ilmiö aikaansaatiin elektrolyyteillä, joilla oli pieni tai negatiivinen kuljetuslämpö.

Nykyisen tiedon ja menetelmien avulla Soret-ilmiön käsittely yksinkertaisissa suolaliuoksissa on melko suoraviivaista, mutta monimutkaisempien suolaseosten kohdalla ymmärrystä tulee kehittää. Väitöskirjassa kehitettiin uusi sähkökemialliseen impedanssispektroskopiaan perustuva menetelmä, jonka avulla sähkökemiallisesti aktiivisten ionien termodiffuusiota olisi mahdollista mitata seoksessa. Mittausvasteesta kehitettiin matemaattinen malli, joka validoitiin mittauksilla ohutkennossa. Väitöskirjassa tutkittiin myös sähkökemiallisesti epäaktiivisen polyelektrolyytin kuljetusta suolaseoksessa. Kokeiden perusteella seoksen kantava elektrolyytti vaikuttaa merkittävästi tutkittavan polyelektrolyytin termodiffuusioon, ja äärimmäisissä tapauksissa kantavaa elektrolyyttiä vaihtamalla olisi mahdollista jopa kokonaan kääntää polyelektrolyytin

Avainsanat Termosähköisyys, termodiffuusio, Seebeck-ilmiö, Soret-ilmiö, ei-isotermiset

kuljetusyhtälöt, membraanin termojännite, hukkalämmön talteenotto, impedanssi, polyelektrolyytin kuljetus

ISBN (painettu) 978-952-64-0516-2

ISBN (pdf) 978-952-64-0517-9

ISSN (painettu) 1799-4934

ISSN (pdf) 1799-4942

Julkaisupaikka Helsinki

Painopaikka Helsinki

Vuosi 2021

Sivumäärä 103

urn <http://urn.fi/URN:ISBN:978-952-64-0517-9>

Acknowledgements

The work for this doctoral thesis was conducted at the Laboratory of Physical Chemistry and Electrochemistry at the Aalto University School of Chemical Engineering. The research was funded by Aalto Energy Efficiency Research Programme under the project Heat-Harvest, Aalto University School of Chemical Engineering, Emil Aaltonen Foundation (grant number 180066), Waldemar von Frenckells Foundation, and Kaute Foundation. All funding parties are gratefully acknowledged – without them, this research would not have been possible.

Besides the funding, equally as significant enabler for this thesis has been the amazing support from those close to me and my work. I would like to thank Professor Lasse Murtomäki for patiently guiding the thesis work to the very end, and for being the supportive voice-of-reason through the many ups and downs of the journey. Also, I wish to express my gratitude towards Professor José A. Manzanares for sharing his wisdom and for being an ever-present coauthor and source of support. His impact on this thesis has been immense. I also wish to thank the late Professor Emeritus Kyösti Kontturi, who offered me the chance to pursue a doctoral degree with a topic I knew nothing about beforehand – what a ride it turned out to be. Another very important person in my academic journey whom I would like to thank is Professor Tanja Kallio. She first offered me the chance to work in science and really sparked my interest towards electrochemistry.

My fellow doctoral students, especially at FyKe: Thank you for being awesome colleagues and friends, both at work and during our numerous after-work events. Special shoutout to my brothers-in-arms; Sampsa Vierros and Nico Holmberg, with whom I had the pleasure of sharing the journey all the way from freshman courses to the very end of postgraduate studies in physical chemistry; to #C239's Lauri Viitala and Olli Sorsa for the great office spirit and friendship, and finally to Sami Tuomi, who first showed me how fun it could be to work in a laboratory.

Finally, I cannot thank my family enough for being there, every day, showing love, support and interest in what I do. You are my reason for everything.

Helsinki, August 24, 2021

Miikka Jokinen

Contents

List of Abbreviations and Symbols	i
List of Publications	v
Author's Contribution.....	vi
1. Introduction.....	1
2. Non-isothermal transport processes	4
2.1 The dissipation function	4
2.2 Phenomenological transport equations	8
2.3 Coupling of ion transport in multi-ionic systems	10
2.4 The observed Soret coefficient in a mixture	11
3. The Seebeck effect in electrolytes	14
3.1 Thermal membrane potential	16
3.2 Thermoelectric membrane cell	20
3.2.1 Measured cell potential	21
3.2.2 Thermoelectric power	23
4. The Soret effect in electrolytes	25
4.1 Thermodiffusion impedance.....	26
4.1.1 Impedance spectroscopy.....	26
4.1.2 Theoretical modelling of the thermodiffusion impedance..	27
4.1.3 Experimental thin-layer impedance cell	30
4.1.4 Simulated and measured spectra	31
4.2 Polyelectrolyte thermodiffusion	35
4.2.1 Polyelectrolyte flux equations	36
4.2.2 Thermal separation of the polyelectrolyte	38
4.2.3 Thermodiffusion in different supporting electrolytes.....	42
5. Conclusions and outlook	44
References.....	47

List of Abbreviations and Symbols

List of abbreviations

CE	Counter electrode
CPE	Constant phase element
EIS	Electrochemical impedance spectroscopy
OCP	Open circuit potential
TDFRS	Thermal diffusion forced Rayleigh scattering
TD _{ox/red}	Thermodiffusion element of oxidized/reduced species
UV	Ultraviolet light
Vis	Visible light

List of symbols

A	Surface area [cm ²]
c_i	Concentration of species i [mol L ⁻¹]
c_i^s	Surface concentration [mol L ⁻¹]
$\bar{c}$	Average concentration [mol L ⁻¹]
C_{dl}	Double layer capacitance [F]
D_i	Diffusion coefficient of species i [cm ² s ⁻¹]
E	Electric potential [V]
$\vec{E}$	Electric field [V m ⁻¹]
$\hat{E}$	Amplitude of the potential perturbation [V]
$E_{T,i}$	Thermophoretic enhancement factor [1]

F	Faraday's constant [C mol^{-1}]
G	Gibbs free energy [J]
g	Gibbs free energy density [J m^{-3}]
h	Thickness of cell/membrane [m]
$\vec{i}$	Electric current density [A m^{-2}]
i_{sc}	Short-circuit current density [A m^{-2}]
i_0	Exchange current density [A m^{-2}]
I	Electric current [A]
$\hat{I}$	Amplitude of electric current response [A]
j	Imaginary unit
$\vec{j}_i$	Flux density of species i [$\text{mol m}^{-2} \text{s}^{-1}$]
$\vec{j}_u$	Internal energy flux density [$\text{J m}^{-2} \text{s}^{-1}$]
$\vec{j}_s$	Entropy flux density [$\text{J K}^{-1} \text{m}^{-2} \text{s}^{-1}$]
$\vec{j}_q$	Heat flux density [$\text{J m}^{-2} \text{s}^{-1}$]
k	Proportionality coefficient [1]
k_{ox}	Rate constant of the oxidation reaction [$\text{mol L}^{-1} \text{s}^{-1}$]
k_{red}	Rate constant of the reduction reaction [$\text{mol L}^{-1} \text{s}^{-1}$]
k^0	Standard rate constant of a reaction [$\text{mol L}^{-1} \text{s}^{-1}$]
$l_{i,j}$	Ionic phenomenological transport coefficient [$\text{mol}^2 \text{J}^{-1} \text{m}^{-1} \text{s}^{-1}$]
$L_{i,j}$	Component phenomenological coefficient [$\text{mol}^2 \text{J}^{-1} \text{m}^{-1} \text{s}^{-1}$]
$L(x) = \coth(x) - 1/x$	Langevin function
n	Parameter of CPE, amount of substance (mol), number of electrons in a reaction, polyelectrolyte charge
p	Pressure [Pa]
P_{max}	Maximum power output [W]
Q_i^*	Heat of transport of species i [J mol^{-1}]
$\bar{Q}_i^*$	Average heat of transport of species i [J mol^{-1}]
R	Molar gas constant [$\text{J mol}^{-1} \text{K}^{-1}$]
R_{ct}	Charge transfer resistance [Ω]

$R_{i,\text{eq}}^s$	Ohmic resistance associated to species i [Ω]
S_e	Seebeck coefficient [V K^{-1}]
S	Entropy [J K^{-1}]
s	Entropy density [$\text{J K}^{-1} \text{m}^{-3}$], complex frequency
$\bar{s}_i$	Partial molar entropy of species i [$\text{J K}^{-1} \text{mol}^{-1}$]
t	Time [s]
t_i	Transport number of ionic species i [1]
$t_{D,i} = h^2/D_i$	Diffusional time of species i [s]
T	Temperature [K]
U	Internal energy [J]
u	Internal energy density [J m^{-3}]
V	Volume [m^3]
$\dot{V}$	Volume flow [$\text{m}^3 \text{s}^{-1}$]
X	Fixed charge density (ion-exchange membrane) [mol L^{-1}]
x	Position [m]
Z	Impedance [Ω]
$\hat{Z}$	Modulus of the complex impedance [Ω]
α	Charge-transfer coefficient [1], cold side, electrode
β	Fitting parameter [1], hot side
δ	Thickness of boundary layer [m], change in variable
κ	Electrical conductivity [$\Omega^{-1} \text{m}^{-1}$]
κ_T	Thermal conductivity [$\text{W K}^{-1} \text{m}^{-1}$]
μ_i	Chemical potential [J mol^{-1}]
$\tilde{\mu}_i$	Electrochemical potential [J mol^{-1}]
ν_i	Stoichiometric coefficient [1]
ω	Angular frequency [rad s^{-1}], reduced evaporation rate [s^{-1}], electrode
π_s	Density of entropy production rate [$\text{J K}^{-1} \text{m}^{-3} \text{s}^{-1}$]
ϕ	Electric potential [V]
ϕ_{dif}	Diffusion potential [V]

ϕ_{oc}	Open-circuit potential [V]
ϕ_{ohm}	Ohmic potential [V]
ϕ_{th}	Thermodiffusion potential [V]
ϕ_{D}	Donnan potential [V]
φ	Phase shift [1]
$\varphi_{\text{D}} = \text{arcsinh}[X/(2\bar{c})]$	Reduced Donnan potential [1]
ρ_i	Parameter of thermodiffusion impedance [1]
$\sigma_{T,i}$	Soret coefficient of species i at temperature T [K ⁻¹]
$\sigma_{T,i}^*$	Observed Soret coefficient in a mixture [K ⁻¹]
$\theta_i = \sigma_{T,i} \Delta T / 2$	Parameter of thermophoretic factor [1]
θ	Dissipation function [J m ⁻³ s ⁻¹]

List of Publications

This doctoral dissertation consists of a summary and of the following publications which are referred to in the text by their numerals

- I.** Miikka Jokinen, José A. Manzanares, Kyösti Kontturi, Lasse Murtomäki. Thermal potential of ion-exchange membranes and its application to thermoelectric power generation. *Journal of Membrane Science*, **2016**, 499, 234-244. DOI: 10.1016/j.memsci.2015.10.042.
- II.** Miikka Jokinen, José A. Manzanares, Lasse Murtomäki. Soret coefficient of trace ions determined with electrochemical impedance spectroscopy in a thin cell. Theory and measurement. *Journal of Electroanalytical Chemistry*, **2018**, 820, 67-73. DOI: 10.1016/j.jelechem.2018.04.054.
- III.** Miikka Jokinen, José A. Manzanares, Lasse Murtomäki. Thermodiffusion of sodium polystyrene sulfonate in a supporting electrolyte. *Electrochimica Acta*, **2019**, 317, 542-550. DOI: 10.1016/j.electacta.2019.05.155.

Author's Contribution

Publication I: Thermal potential of ion-exchange membranes and its application to thermoelectric power generation.

MJ planned the experiments and designed the experimental setup with KK and LM. MJ and JAM developed the theory together. MJ surveyed the literature, conducted the experiments and analysed the results. KK and LM supervised the research, reviewed the results and provided feedback to MJ. MJ wrote the manuscript in collaboration with JAM and LM.

Publication II: Soret coefficient of trace ions determined with electrochemical impedance spectroscopy in a thin cell. Theory and measurement.

MJ planned the experiments together with LM. MJ, LM and JAM developed the theory together. MJ surveyed the literature, designed the experimental setup, ran the simulations, conducted the experiments and analysed the results. LM supervised the research, reviewed the results and provided feedback to MJ. MJ wrote the manuscript in collaboration with JAM and LM.

Publication III: Thermodiffusion of sodium polystyrene sulfonate in a supporting electrolyte.

MJ planned the experiments, designed the experimental setup, conducted the experiments and analysed the results. MJ, LM and JAM developed the theory together. LM supervised the research, reviewed the results and provided feedback to MJ. MJ wrote the manuscript in collaboration with JAM and LM.

1. Introduction

Thermodiffusion is a process which occurs in non-isothermal systems, when a temperature gradient drives not only a flux of heat in the system, but also a flux of matter [1]. This coupling of heat and mass fluxes allows concentration gradients to build-up and be maintained by temperature gradients. The phenomenon plays a role in natural transport processes with temperature gradients, e.g. thermohaline convection process in oceans and component segregation in Earth's mantle [2,3]. Also, as it is one of the few known mechanisms which allows the accumulation of substance against diffusion, it is believed to have been essential for the development of conditions which might have led to the natural synthesis of macromolecules such as RNA. Therefore, some argue that it could have played a role in the origin of life [4–6]. Perhaps more ordinary applications of thermodiffusion can be found from biomolecule analytics [7,8] and molecule separation and purification [9,10]. Therefore, studies of non-isothermal transport in different, especially biologically relevant systems are gathering interest.

If thermally transported particles are charged, e.g. ions or electrons, thermodiffusion can become more difficult to analyse and predict [11], but more importantly, it can lead to a build-up of voltage and electric current in certain systems, facilitating the generation of electric power directly from heat transport [1,12]. This phenomenon, thermoelectricity or the Seebeck effect, can be applied to heat harvesting, i.e. utilizing (waste) heat in power generation. Thermoelectric devices allow off-grid power generation where heat sources and temperature differences are available. Small medical devices and wearable sensors, which require constant but low electric power, could be powered by body heat, especially in cases where batteries are impractical [13]. Powering up deep space probes with a radioactive heat source is common already today [14]. More generally, the Seebeck effect could be used to increase the efficiency of different devices and processes which require cooling and generate waste heat, ranging from computer CPUs to automobile engines or even power plants [13].

The theory of the Seebeck effect is well known in solid systems such as metals and semiconductors [15], and the development of more complex materials has resulted in a significant improvement in the thermal-to-electrical conversion efficiency [14,16]. The thermoelectric performance of the material is usually evaluated [14] through the dimensionless thermoelectric figure-of-merit:

$$ZT = \frac{\kappa S_e^2}{\kappa_T} T \quad (1)$$

which depends on the temperature T , and three material properties; the electrical conductivity κ , the Seebeck coefficient S_e , i.e. the ratio between the induced voltage and the temperature difference, and the thermal conductivity κ_T . In simple terms, one enhances the performance by increasing ZT by [14,16]:

- i. Increasing the Seebeck coefficient S_e . This increases the electrical driving force induced by the temperature difference.
- ii. Increasing the electrical conductivity κ . This enhances the electric current driven by the voltage.
- iii. Decreasing the thermal conductivity κ_T . This decreases the heat flow, resulting in higher temperature difference and induced voltage.

Metalloids like antimony, bismuth, and tellurium have provided the largest ZT values so far [16,17], due to their good electrical conductivities and high Seebeck coefficients; in the elevated temperatures used for maximizing ZT , their thermal conductivities are relatively large [18]. Moreover, the state-of-the-art semiconductor-based thermoelectric materials could be inherently too expensive for the performance they provide, especially in near-ambient temperatures [19,20]. Therefore, alternative routes for higher ZT values with a more affordable cost are being sought with increasing activity. Such alternatives include organic thermoelectrics [21] and thermoelectric electrolyte systems [20,22,23]. The former materials are appealing due to their potentially low cost and low thermal conductivity, but usually suffer from low Seebeck coefficients and low electrical conductivities. The latter, studied in this thesis, are found appealing due to their potentially high Seebeck coefficients and lower thermal conductivities associated with liquid media but suffer from lower electrical conductivities which might restrict their applicability. Therefore, the determination of the key parameters affecting ZT , understanding their codependence and optimizing them to reach high ZT values is still essential.

The purpose of this thesis is to investigate the applicability of non-isothermal transport processes in electrolyte solutions to heat harvesting. Key questions addressed in this thesis are:

1. How non-isothermal transport can be applied to thermoelectric power generation in electrolyte solutions, and what are the experimentally relevant parameters therein?
2. Based on these parameters, is it possible to predict the behavior of some electrolytes and improve their performance in applications?
3. How can these parameters be measured most conveniently?

Question 1 laid the foundations for the work in Publication [I], a proof-of-concept of the application of ion-exchange membranes to thermoelectric power

generation. This highlighted several parameters which could be optimized to improve the heat harvesting performance. Questions 2 and 3 were addressed in Publications [II] and [III], where thermodiffusion of electrolyte mixtures were investigated and methods for measuring the phenomenon were introduced.

In the next chapters, the work around these three publications is summarized. The relevant thermodynamic theory for understanding the phenomena is introduced in Chapter 2. Chapter 3 focuses on the Seebeck effect in electrolytes, particularly on the thermal membrane potential generated in the thermoelectric membrane cell. In Chapter 4 the attention is shifted to the Soret effect and the measurement of the Soret coefficient in different systems. Finally, Chapter 5 presents the conclusions, and suggests how the research could be continued in the future.

2. Non-isothermal transport processes

The first experimental reports of thermoelectricity and thermodiffusion were published already in the 19th century. Thomas J. Seebeck discovered in 1823 that a system of two different electronic conductors whose two phase boundaries are held at different temperatures without current flow shows an electric potential difference [1]. In 1834 J. Peltier observed that when current flows through the isothermal junction between two different electronic conductors, it can heat up or cool down [1]. Few decades later, W. Thomson discovered that these two thermoelectric phenomena (now known as the Seebeck effect and the Peltier effect, respectively) are related, and predicted the existence of a third one, the Thomson effect: the current flow through a conductor in the presence of a temperature gradient has an associated contribution to the local density of internal energy production rate that can be positive or negative, depending on the direction of current flow – relative to the direction of the temperature gradient. [1,24]. Furthermore, C. Soret and C. Ludwig independently published several reports on thermally-induced mass transport during the same century [1,25].

At the time, these discoveries could not be explained properly, because the foundations of thermodynamics and electromagnetism were still under development. Thermoelectric and thermodiffusion phenomena sparked the development of the thermodynamics of irreversible processes [26]. The following few subsections provide a brief description of the approach relevant for this thesis. A more thorough presentation can be found from the seminal works by De Groot and Mazur [26] and Haase [1].

2.1 The dissipation function

The thermodynamics of irreversible processes (also known as non-equilibrium thermodynamics) provides a framework for the study of non-equilibrium processes. The entropy balance plays a crucial role because it determines the transport equations, i.e. the relations between the thermodynamic driving forces and the flux densities [27]. Therefore, in order to understand how the

system evolves towards equilibrium, the entropy production rate needs to be determined.

Two hypotheses, the continuum hypothesis and the local equilibrium hypothesis, are crucial for the approach. In non-equilibrium thermodynamics, the system can be thought to consist of volume elements [1,27]. Each volume element is so small that the condition of internal equilibrium can be safely assumed and infinitesimal calculus can be applied to the spatial changes of the thermodynamic quantities, yet so large that it is macroscopic (i.e. it contains a large number of molecules) [1,27]. Then, the intensive state variables and the densities of the extensive state variables are continuous functions of space and time. Therefore, local formulations of the Gibbs, Euler and Gibbs-Duhem equations are needed. The Gibbs energy of a volume element is

$$dG = \sum_i \mu_i dn_i = dU - TdS + pdV \quad (2)$$

where dU , dS , and dV are the internal energy, entropy and volume of the volume element, μ_i and dn_i are the chemical potential and the amount of component i in the volume element, respectively, T is the temperature, and p is the pressure. If equation (2) is divided with dV , the local form of the Euler equation

$$g = \sum_i \mu_i c_i = u - Ts + p \quad (3)$$

is obtained, where $g = dG/dV$ is the local Gibbs energy density, $c_i = dn_i/dV$ is the molar concentration of component i , $u = dU/dV$ is the internal energy density, and $s = dS/dV$ is the entropy density. The local equilibrium hypothesis amounts to the validity of the local Gibbs equation

$$\delta u = T\delta s + \sum_i \mu_i \delta c_i \quad (4)$$

where the symbol δ refers to change in a variable. Accordingly, the relation between the flux densities of internal energy, entropy, and the amounts of components is

$$\vec{j}_u = T\vec{j}_s + \sum_i \mu_i \vec{j}_i. \quad (5)$$

The application of eq. (4) to the time variation of u , s , and c_i at any position implies

$$T \frac{\partial s}{\partial t} = \frac{\partial u}{\partial t} - \sum_i \mu_i \frac{\partial c_i}{\partial t}. \quad (6)$$

Combining eq. (6) with the balance equations of entropy, internal energy and amount of component i , the expressions of the local density of the entropy production rate and of the dissipation function can be determined.

The local form of the entropy balance equation is [27]

$$\frac{\partial s}{\partial t} + \vec{\nabla} \cdot \vec{j}_s = \pi_s \quad (7)$$

where π_s is the local density of the entropy production rate. The integration of eq. (7) over any control volume implies that the time variation of the entropy of the control volume is the difference between the rate of entropy production inside the control volume and the outward flux of entropy through the boundaries of the control volume. In the absence of convection and chemical reactions, the balance equations of the internal energy and amount of component i are [26,27]

$$\frac{\partial u}{\partial t} + \vec{\nabla} \cdot \vec{j}_u = \vec{i} \cdot \vec{E}, \quad (8)$$

$$\frac{\partial c_i}{\partial t} + \vec{\nabla} \cdot \vec{j}_i = 0 \quad (9)$$

where $\vec{i}$ is the electric current density and $\vec{E}$ is the electric field. The Joule term $\vec{i} \cdot \vec{E}$ is the local density of internal energy production rate, i.e. the conversion rate of electric potential energy into internal energy per unit volume of solution. By combining eqs. (5) and (9) it is possible to eliminate the time derivatives of u , s , and c_i , and solve for π_s . The dissipation function $\theta \equiv T\pi_s$ can then be expressed as

$$\begin{aligned} \theta &= -\vec{\nabla} \cdot \vec{j}_u + T \vec{\nabla} \cdot \vec{j}_s + \sum_i \mu_i \vec{\nabla} \cdot \vec{j}_i + \vec{i} \cdot \vec{E} \\ &= -\vec{j}_s \cdot \vec{\nabla} T - \sum_i \vec{j}_i \cdot \vec{\nabla} \mu_i + \vec{i} \cdot \vec{E}. \end{aligned} \quad (10)$$

Using the definition $\vec{i} \equiv F \sum_i z_i \vec{j}_i$ of the electric current density, where F is the Faraday constant and z_i is the charge number of species i , and introducing the electrochemical potential $\tilde{\mu}_i = \mu_i + z_i F \phi$, where ϕ is the electric potential, and the relation $\vec{E} = -\vec{\nabla} \phi$, eq. (10) can be transformed to [26,28]

$$\theta = -\vec{j}_s \cdot \vec{\nabla} T - \sum_i \vec{j}_i \cdot \vec{\nabla} \tilde{\mu}_i. \quad (11)$$

If present, the sum also runs over neutral components with $z_i = 0$.

Since the electrochemical potential can be considered to be a function of temperature, the gradient $\vec{\nabla}\tilde{\mu}_i$ has a contribution proportional to $\vec{\nabla}T$. Thus, the driving forces $\vec{\nabla}\tilde{\mu}_i$ and $\vec{\nabla}T$ are not independent of each another. However, it is possible to transform eq. (11) so that the expression of the dissipation function θ only involves independent driving forces. The gradient of electrochemical potential of component i is

$$\vec{\nabla}\tilde{\mu}_i = \left(\frac{\partial\mu_i}{\partial T}\right)_{p,c_j} \vec{\nabla}T + (\vec{\nabla}\mu_i)_T + z_i F \vec{\nabla}\phi = -S_i \vec{\nabla}T + (\vec{\nabla}\tilde{\mu}_i)_T \quad (12)$$

where $S_i = -(\partial\mu_i/\partial T)_{p,c_j}$ is the partial molar entropy of component i and the subscripts p, c_j and T refer to constant pressure, concentration of all species, and temperature. Elimination of $\vec{\nabla}\tilde{\mu}_i$ from eqs. (11) and (12) leads to

$$\theta = -\frac{\vec{J}_q}{T} \cdot \vec{\nabla}T - \sum_i \vec{J}_i \cdot (\vec{\nabla}\tilde{\mu}_i)_T \quad (13)$$

where

$$\vec{J}_q = T\vec{J}_s - \sum_i S_i \vec{J}_i = \vec{J}_u - \sum_i H_i \vec{J}_i \quad (14)$$

is the so-called reduced heat flux density [1] and $H_i = \mu_i + TS_i$ is the partial molar enthalpy of component i . Equation (14) is equivalent to

$$\vec{J}_s = -\frac{1}{T}\vec{J}_q + \sum_i S_i \vec{J}_i. \quad (15)$$

which expresses the entropy flux density as a sum of contributions from heat transport and mass transport. The conclusion is that, in the absence of convection and chemical reactions, eq. (13) shows that the transport processes are driven by independent driving forces: the temperature gradient and the isothermal gradients of the electrochemical potentials of the components. The contribution to θ from each independent transport process is positive [28].

In ionic systems, the contribution of electrodiffusion to the dissipation function can be written in terms of charged species or in terms of neutral components. In most cases it is reasonable to assume that the system is locally electroneutral, i.e. $F \sum_i z_i c_i = 0$, for the energy required to charge a macroscopic system is high [27]. This means that ionic concentrations cannot be changed independently from one another, and therefore they cannot be considered as components of the system. Rather, it is the concentration of an electrolyte (electroneutral combination of ionic species) which can be changed independently, making the chemical potential of an electrolyte $\mu_{12} = (\partial g / \partial c_{12})_{T,p,c_0}$, as the measurable variable instead of the chemical potential of an ionic species; c_0 is the solvent

concentration. However, the ionic formalism and the local electric potential are important in cases where the transport equations of charged species are more conveniently described separately, e.g. the trace ion case in electrochemical systems [27].

2.2 Phenomenological transport equations

In chapter 2.1 the dissipation function was derived specifically for a non-isothermal system in the absence of chemical reactions and convection. In the simplest of cases of one neutral solute in a solvent, the dissipation function is the sum of two scalar products, heat flux density times negative temperature gradient plus solute flux density times negative gradient of chemical potential of the solute. This result can be generalized: The dissipation function of any system can be expressed as the sum of products of all the conjugate pairs flux density-driving force [26]. Because transport processes produce entropy, the dissipation function is positive [1,27] – although some products could be negative, the sum of scalar products of flux densities and driving forces is positive.

When the fluctuations from equilibrium are small, the assumption of local equilibrium and microscopic reversibility holds, and the transport equations can be linearized so that the fluxes are linear functions of the driving forces, with different proportionality coefficients [26]. Although discovered before the emergence of irreversible thermodynamics, the Fourier law of heat conduction

$$-\vec{j}_q = \kappa_T \vec{\nabla} T, \quad (16)$$

and the Fick law of diffusion for a single solute,

$$-\vec{j}_1 = D_1 \vec{\nabla} c_1, \quad (17)$$

can be considered as simple examples¹ of such linearized transport equations [1]; the transport coefficients are the thermal conductivity κ_T and the diffusion coefficient D_1 .

In 1931 Lars Onsager showed that cross-phenomena can be described by linear phenomenological transport equations [26]. Thus, each flux is linearly dependent not only on its conjugate driving force, but also on all the other forces present in the system. Thermoelectric effects are the result of the coupling of electric current and heat flux, driven by the negative gradients of electric potential and temperature, respectively [1]. For example, the Peltier effect is a linear relation between the heat flux density and the electric current under isothermal

¹ Note that the Fick law of diffusion in a more general case is not a phenomenological equation.

conditions which amounts to consider that the negative gradient of electric potential is a driving force for heat transport. More generally, in a non-isothermal system with K species, the phenomenological transport equations can be presented in matrix form as

$$\begin{bmatrix} \vec{j}_q \\ \vec{j}_1 \\ \vdots \\ \vec{j}_K \end{bmatrix} = - \begin{bmatrix} l_{q,q} & l_{q,1} & \dots & l_{q,K} \\ l_{q,1} & l_{1,1} & \dots & l_{K,1} \\ \vdots & \vdots & \ddots & \vdots \\ l_{q,K} & \dots & \dots & l_{K,K} \end{bmatrix} \begin{bmatrix} (1/T)\vec{\nabla}T \\ (\vec{\nabla}\tilde{\mu}_1)_T \\ \vdots \\ (\vec{\nabla}\tilde{\mu}_K)_T \end{bmatrix} \quad (18)$$

where $l_{i,j}$ are the phenomenological transport coefficients. The requirement for the dissipation function, $\theta > 0$, imposes conditions on these coefficients. Thus, the heat flux density is proportional to the temperature gradient and to the isothermal gradients of the electrochemical potentials of all the components. Because linear dependency is observed, the transport coefficients can be dependent on the local state variables of the system, but not on the fluxes and forces. Therefore, they can be measured independently from one another [26]. Moreover, the so called cross-coefficients satisfy Onsager's reciprocal theorem $l_{i,k} = l_{k,i}$ [1,26].

As an example, for a neutral solute in a non-isothermal solution the transport equations are

$$\begin{aligned} -\vec{j}_q &= L_{q,q} \frac{1}{T} \vec{\nabla}T + L_{q,1} (\vec{\nabla}\mu_1)_T \\ -\vec{j}_1 &= L_{q,1} \frac{1}{T} \vec{\nabla}T + L_{1,1} (\vec{\nabla}\mu_1)_T \end{aligned} \quad (19)$$

where capital letters L are used for the symbols of the transport coefficients to emphasize that a neutral solute (instead of ionic species) is considered; note also the use of symbol $\vec{j}_1$ for the solute flux density. If the solution is dilute, it is possible to approximate $(\vec{\nabla}\mu_1)_T = RT\vec{\nabla} \ln c_1$. With the help of experimental observations/relations such as eqs. (16) and (17), $L_{q,q}/T = \kappa_T$ can be identified as the thermal conductivity, and similarly $D_1 = L_{1,1}RT/c_1$ as the diffusion coefficient. Similarly, from the transport equations for thermodiffusion the cross coefficients can be written as $L_{q,1} = TD_1c_1\sigma_{T,1}$, or as $L_{q,1} = Q_1^*L_{1,1}$, where $\sigma_{T,1}$ is the Soret coefficient and $Q_1^* = RT^2\sigma_{T,1}$ is the heat of transport of the solute. Thus, eq. (19) can be expressed as

$$\begin{aligned} -\vec{j}_q &= \kappa_T \vec{\nabla}T + Q_1^*D_1\vec{\nabla}c_1 = [\kappa_T - L_{1,1}(Q_1^*)^2/T] + Q_1^*\vec{j}_1 \\ -\vec{j}_1 &= D_1c_1\sigma_{T,1}\vec{\nabla}T + D_1\vec{\nabla}c_1. \end{aligned} \quad (20)$$

The solute flux is the combination of thermodiffusion and diffusion, driven by the two gradients. The reduced heat flux $\vec{j}_q$ is also driven by the two gradients,

and it can be described as a sum of a heat conduction contribution and $Q_1^* \vec{J}_1$, the heat transported by the solute.

2.3 Coupling of ion transport in multi-ionic systems

In a multi-ionic system, the flux equations are obtainable from eq. (18). The number of phenomenological coefficients grows quickly with the number of ionic fluxes, even after the Onsager reciprocity theorem is applied. However, the ionic flux equations can be simplified with the Nernst-Planck approximation. The Nernst-Planck approximation assumes that the ionic cross-phenomenological coefficients are negligible, $l_{i,j} = 0$ when $i \neq j$ [27]. The assumption can be interpreted as neglecting the short-range ionic interactions, which is reasonable in dilute solutions where the number of ions with respect to the number of solvent molecules is small and the probability for two ions being close to each other is low [27]. Applying the Nernst-Planck approximation to eq. (18), along with the identities $l_{q,q}/T = \kappa_T$, $l_{q,i} = D_i c_i T \sigma_{T,i}$, and $l_{i,i} = D_i c_i / (RT)$, and the approximation $(\vec{\nabla} \tilde{\mu}_i)_T = RT \vec{\nabla} \ln c_i + z_i F \vec{\nabla} \phi$ leads to

$$\begin{aligned} -\vec{J}_q &= \kappa_T \vec{\nabla} T + \sum_i Q_i^* D_i \vec{\nabla} c_i + \sum_i Q_i^* D_i c_i z_i \frac{F}{RT} \vec{\nabla} \phi \\ -\vec{J}_i &= D_i c_i \sigma_{T,i} \vec{\nabla} T + D_i \vec{\nabla} c_i + D_i c_i z_i \frac{F}{RT} \vec{\nabla} \phi \end{aligned} \quad (21)$$

where $Q_i^* = RT^2 \sigma_{T,i}$ is the ionic heat of transport, and $\sigma_{T,i}$ is the ionic Soret coefficient. The electric potential gradient can be expressed as a sum of different contributions:

$$\vec{\nabla} \phi = \vec{\nabla} \phi_{\text{ohm}} + \vec{\nabla} \phi_{\text{dif}} + \vec{\nabla} \phi_{\text{th}}. \quad (22)$$

The ohmic potential gradient is defined as

$$\vec{\nabla} \phi_{\text{ohm}} = -\frac{\vec{t}}{\kappa} = -\frac{F}{\kappa} \sum_i z_i \vec{J}_i \quad (23)$$

where $\kappa = \sum_i \kappa_i = (F^2/RT) \sum_i z_i D_i c_i$ is the electric conductivity. The diffusion potential gradient is

$$\vec{\nabla} \phi_{\text{dif}} = -\frac{RT}{F} \sum_i \frac{t_i}{z_i} \vec{\nabla} \ln c_i \quad (24)$$

where $t_i = z_i^2 D_i c_i / \sum_k z_k^2 D_k c_k$ is the ionic transport number. The thermodiffusion potential gradient is

$$\vec{\nabla}\phi_{\text{th}} = - \sum_i \frac{t_i Q_i^*}{z_i F} \frac{1}{T} \vec{\nabla}T = -S_e \vec{\nabla}T, \quad (25)$$

where S_e is the ionic Seebeck coefficient. Just like in the case of electronic conductors, the measurable electric potential drops in non-isothermal systems have contributions from the Seebeck coefficients of different phases.

The key message of this section is that although the ionic phenomenological transport -cross-coefficients are assumed to be zero within the Nernst-Planck approximation, the transport of all ionic species is still coupled through the electric potential gradient and the requirement for electroneutrality [27]. This coupling is essential when considering non-isothermal transport in multi-ionic solutions.

2.4 The observed Soret coefficient in a mixture

In the simplest of cases, eq. (20) shows that a temperature gradient is a driving force for solute flux in a system with a neutral solute and a solvent. As alluded to earlier, this process is known as thermodiffusion, or the Soret effect. When a temperature gradient is imposed to a solution with uniform solute concentration, a solute redistribution is observed. The redistribution occurs until the induced concentration gradient cancels out the effect of the temperature gradient, $c_1 \sigma_{T,1} \vec{\nabla}T + \vec{\nabla}c_1 = \vec{0}$. The solute flux density then vanishes, and the system is in a steady state known as the Soret equilibrium [1]; that is, equilibrium with respect to solute transport and nonequilibrium with respect to heat transport. The Soret coefficient determined the magnitude and direction of the concentration gradient in this state [29]:

$$\sigma_{T,1} = - \left(\frac{d \ln c_1}{dT} \right)_{J_1=0}. \quad (26)$$

A solute with positive Soret coefficient depletes from high temperature regions and accumulates in low temperature regions, and vice versa for negative $\sigma_{T,1}$ ².

In a multi-ionic system, the study of thermodiffusion is complicated by the coupling of the ionic fluxes through the electric potential gradient and the local electroneutrality condition, eqs. (22)-(25). The temperature gradient tends to drive the ionic fluxes at different rates, but electrostatic interactions bind them together through a thermally-induced electric potential gradient. In the Soret equilibrium, $\vec{j}_i = \vec{0}$, the electric potential gradient is [30]

² Note that the opposite sign convention is sometimes used in the literature.

$$-\frac{F}{RT} \vec{\nabla} \phi_{ji=0} = \frac{\sum_j z_j c_j \sigma_{T,j}}{\sum_k z_k^2 c_k} \vec{\nabla} T, \quad (27)$$

and the concentration gradient is

$$\vec{\nabla} \ln c_i = - \left(\sigma_{T,i} - z_i \frac{\sum_j z_j c_j \sigma_{T,j}}{\sum_k z_k^2 c_k} \right) \vec{\nabla} T. \quad (28)$$

Usually in an experiment on the Soret effect, the aim is to measure the concentration difference (gradient) achieved with a certain temperature difference (gradient), and the term inside the parenthesis of eq. (28) can be identified as the observed Soret coefficient of the ions

$$\sigma_{T,i}^* = \sigma_{T,i} - z_i \frac{\sum_j z_j c_j \sigma_{T,j}}{\sum_k z_k^2 c_k}. \quad (29)$$

For an aqueous solution of a strong electrolyte $A_{\nu_1} C_{\nu_{3,1}}$, the observed Soret coefficient of the electrolyte (denoted by the index 13) is the observed Soret coefficients of the ions, $\sigma_{T,13} = \sigma_{T,1}^* = \sigma_{T,3}^* = (\nu_1 \sigma_{T,1} + \nu_{3,1} \sigma_{T,3}) / (\nu_1 + \nu_{3,1})$, that is, an average of the actual Soret coefficients of the ions weighted by their stoichiometric coefficients ν_1 and $\nu_{3,1}$ in the electrolyte. In a mixture of electrolytes $A_{\nu_1} C_{\nu_{3,1}}$ and $B_{\nu_2} C_{\nu_{3,2}}$ with a common ion, the observed Soret coefficient of the electrolytes are **[III]**

$$\sigma_{T,13}^* = \sigma_{T,1}^* = \sigma_{T,13} + \frac{\sigma_{T,13} - \sigma_{T,23}}{\frac{\nu_1}{\nu_{3,1}} + \frac{\nu_2}{\nu_{3,2}} \frac{\nu_1 + \nu_{3,1}}{\nu_2 + \nu_{3,2}} \frac{c_{13}}{c_{23}}}, \quad (30)$$

$$\sigma_{T,23}^* = \sigma_{T,2}^* = \sigma_{T,23} + \frac{\sigma_{T,23} - \sigma_{T,13}}{\frac{\nu_2}{\nu_{3,2}} + \frac{\nu_1}{\nu_{3,1}} \frac{\nu_2 + \nu_{3,2}}{\nu_1 + \nu_{3,1}} \frac{c_{23}}{c_{13}}}. \quad (31)$$

where $\sigma_{T,13}$ and $\sigma_{T,23}$ are the Soret coefficients of the electrolytes in the absence of the second electrolyte, c_{13} and c_{23} are the electrolyte concentrations in the mixture. For a mixture of monovalent electrolytes (e.g. NaCl and KCl), the stoichiometric coefficients are all unity and the equations simplify to

$$\sigma_{T,\text{NaCl}}^* = \sigma_{T,\text{Na}^+}^* = \sigma_{T,\text{NaCl}} + \frac{\sigma_{T,\text{NaCl}} - \sigma_{T,\text{KCl}}}{1 + \frac{c_{\text{NaCl}}}{c_{\text{KCl}}}}, \quad (32)$$

$$\sigma_{T,\text{KCl}}^* = \sigma_{T,\text{K}^+}^* = \sigma_{T,\text{KCl}} + \frac{\sigma_{T,\text{KCl}} - \sigma_{T,\text{NaCl}}}{1 + \frac{c_{\text{KCl}}}{c_{\text{NaCl}}}}. \quad (33)$$

Equations (32) and (33) describe the cross thermodiffusion effects in the mixture. If NaCl alone has a higher Soret coefficient than KCl alone, then the observed Soret coefficient of NaCl in the mixture is higher than it would be alone. Respectively, the observed Soret coefficient of KCl in the mixture is lower than it would be alone.

3. The Seebeck effect in electrolytes

The Seebeck effect in an electrolyte solution can be studied in a thermogalvanic cell, where two (identical) electrodes A are placed in an electrolyte AX of uniform composition which dissociates into ions A^+ and X^- . The electrodes are set at different temperatures. The following presents only a brief introduction of such systems with the general features. A more complete description of thermogalvanic cells can be found in Refs. [29,31].

Typically, the cell potential is measured for different temperature differences, and the slope $d\Delta\phi/d\Delta T$ is determined. This slope is known as the thermoelectric power of the cell [1]. The schematic of a thermogalvanic cell is shown in Figure 1, which also highlights the analogy between electrolyte systems and thermocouples: the potential difference $\phi_{VI'} - \phi_{I'}$ is measured between two wires of the same metal at the same temperature T_0 and it has contributions from either metal/electrolyte or metal/metal interfaces, as well as from the conductors with internal temperature gradients [29].

Figure 1. The principle of a thermogalvanic cell is analogous to a thermocouple. In a thermogalvanic cell, two electrodes of metal A (capable of a redox reaction A/A^+) are set at different temperatures and the temperature gradient lies in the electrolyte AX and in the wires of metal M. In a thermocouple, the electrolyte is replaced by a metal B, and the two metal junctions (M/B and B/M) are then at different temperatures (T_1 and T_2).

The measured electric potential difference of a thermogalvanic cell has contributions from [1,29]:

1. thermal diffusion potential of electrons in the metal wire (drops between VI' and VI, and between I and I'),
2. junction potentials between the wire and metal A,
3. difference in the electrode potentials, and

4. thermodiffusion potential in the electrolyte (drop between IV and III).

Usually, the contributions from the wire (1 and 2) are negligible and can be omitted [1,32], and the cell e.m.f. ΔE is a sum of the electrode potential differences arising from the temperature difference (3), and the thermodiffusion potential of the electrolyte (4). Because thermodiffusion potential difference drives the redistribution of the electrolyte, the e.m.f. is a function of time. Initially, the concentration in the cell is uniform, and the cell e.m.f. $\Delta\phi$ can be expressed as a sum of the thermal diffusion potential difference and the temperature dependence of the redox-potential difference [33]:

$$\Delta\phi = \frac{\partial\phi_{\text{el}}}{\partial T} \Delta T - \sum_i \frac{t_i Q_i^*}{z_i F} \frac{1}{T} \Delta T. \quad (34)$$

The e.m.f. and its time dependence, sometimes supported with other measurements, can be used to determine different thermodynamic parameters of the system. For example, the ionic Seebeck coefficient of the electrolyte can be determined from the initial e.m.f. if the electrode contribution is known from other measurements [29,33]. Sometimes, the steady-state e.m.f. is used, but special care should be used in such experiments: the time required to reach the steady-state e.m.f. can be long, and convection easily disturbs such measurements [31]. Different approaches can be used to minimize the effect of convection, such as careful cell design and handling, and setting the temperature gradient vertically with the hot electrode above the cold one also helps in this regard [25,34].

To measure the ionic Seebeck coefficient successfully the two electrodes must be identical to minimize the inherent electric potential difference between them [29]. Furthermore, the electrodes must be stable, as changes in their chemical composition or even physical structure might cause the measured electric potential difference to drift [29]. Therefore, each electrode pair must be prepared carefully. Also, the temperature is also an important experimental parameter which needs to be measured and controlled carefully. Ideally, the mean temperature of the experiment needs to be controlled, as the relevant transport parameters, such as diffusion coefficients and heats of transport, are sensitive to temperature changes [1]. Moreover, the applied temperature difference can also play a role. It should be large enough to create a reliably measurable effect in the system, but small enough so that the system does not deviate from the equilibrium value too violently [29]. Too large a temperature gradient might render the assumption of microscopic reversibility invalid and break down the linear relationship between forces and fluxes [1,29].

Non-isothermal setups can also be set up with the electrodes at identical temperatures by adding liquid junctions to the thermocell. The electrodes are placed

in identical electrolyte solutions at identical temperatures, and these are separated by another electrolyte solution with a common ion and a temperature gradient. Then, the usual thermogalvanic cell

will be replaced by a cell

where A is the electrode reversible to the ion A^+ , AX and BX are electrolytes, T_0 , T_1 and T_2 are the temperatures at different interfaces. As the (identical) electrodes are in identical environments both in terms of temperature and concentration, the electrode potentials do not contribute to the measured cell potential. Instead, the contributions from the liquid junctions and thermal diffusion potential are measured. This approach allows the estimation of entropies of transfer of single ions transferred over the interface [35,36].

A similar approach to liquid/liquid junctions is to introduce ion-exchange membranes to the cell. Then, the thermally induced potential difference is usually called thermal membrane potential [37].

3.1 Thermal membrane potential

When an ion-exchange membrane is introduced to a thermogalvanic cell with a 1-1 electrolyte, the interfaces between the solution and membrane, and the thermodiffusion inside the membrane contribute to the measured potential difference over the cell.

Figure 2. A temperature difference over an ion-exchange membrane (thickness h) in an electrolyte solution creates an electric potential difference to the system. The potential difference is the sum of the thermodiffusion potential in the thermal polarization layers, Donnan potential drops at the membrane/electrolyte interfaces, and thermodiffusion and diffusion potential drops inside the membrane. The green line indicates the potential drops (not in scale), and the blue-to-red line indicates the temperature profile.

When a temperature difference $\Delta T = T^\beta - T^\alpha$ is set over the membrane, a part of the temperature difference always resides in the electrolyte solutions on both sides of the membrane [38]. Therefore, the temperature difference over the membrane, $\Delta T^M = T(h) - T(0)$, is always a fraction k ($k < 1$) of the applied temperature difference:

$$\Delta T^M = k \Delta T \quad (35)$$

Enhanced mixing increases the share of ΔT over the membrane and thus increases k towards unity, but the boundary layers can never be fully eliminated. Thus, these stagnant layers on both sides of the membrane ($-\delta < x < 0$ and $h < x < h + \delta$) create a small thermal diffusion potential gradient, contributions 1 and 5 in Figure 2, which can be evaluated from eq. (25) as [I]

$$\Delta \phi_{\text{th}}^\alpha = \frac{t_1 Q_1^* - t_2 Q_2^*}{z_2 F} \ln \frac{T(0)}{T^\alpha} \quad (36)$$

$$\Delta \phi_{\text{th}}^\beta = \frac{t_1 Q_1^* - t_2 Q_2^*}{z_2 F} \ln \frac{T^\beta}{T(h)} \quad (37)$$

where t_i is the transport number of ionic species i , Q_i^* is the heat of transport of ionic species i , z_2 is the charge number of the co-ion with respect to the ion-exchange membrane, i.e. $z_2 < 0$ for cation exchange membrane. The temperature dependence of the transport number and of the ionic heats of transport has been neglected.

At the membrane/electrolyte interface, the Donnan equilibrium condition implies that the electrochemical potential of the ion i is the same in the external solution and inside the membrane [27]. Thus, the Donnan potential drop over the membrane interface is [I]:

$$\Delta\phi_D(x) = \frac{RT(x)}{z_2 F} \operatorname{arsinh} \frac{X}{2c(x)} \quad (38)$$

where X is the concentration of the fixed charge groups in the membrane and $c(x)$ is the concentration of the electrolyte in the external solution. Being a function of both temperature and concentration, the drop has different values on either side of the membrane, and the potential drop over the membrane extending from $x = 0$ to $x = h$ is [I]

$$\begin{aligned} \Delta\phi_D(0) - \Delta\phi_D(h) &\approx \frac{R\bar{T}}{z_2 F} \left[\tanh \varphi_D \frac{c(h) - c(0)}{\bar{c}} - \varphi_D \frac{T(h) - T(0)}{\bar{T}} \right] \\ &\approx -\frac{R}{z_2 F} \varphi_D k \Delta T \end{aligned} \quad (39)$$

where $\bar{c}$ and $\bar{T}$ is the average concentration and temperature inside the membrane, respectively, $\varphi_D = \operatorname{arsinh}[X/(2\bar{c})]$, and the last approximation applies to a case where the concentration difference in the membrane is negligible. This accounts for the contributions 2 and 4 in Figure 2.

Equation (22) inside the membrane phase shows that the electric potential gradient (contribution 3 in Figure 2) is a sum of the ohmic, diffusion and thermodiffusion potential gradients:

$$\frac{d\phi^M}{dx} = \frac{d\phi_{\text{ohm}}^M}{dx} + \frac{d\phi_{\text{dif}}^M}{dx} + \frac{d\phi_{\text{th}}^M}{dx} \quad (40)$$

where [I]

$$\frac{d\phi_{\text{ohm}}^M}{dx} = -\frac{R\bar{T}}{F^2} \frac{I}{D_1^M c_1^M + D_2^M c_2^M}, \quad (41)$$

$$\frac{d\phi_{\text{dif}}^M}{dx} = -\frac{RT}{z_2 F} \frac{D_2^M - D_1^M}{D_1^M c_1^M + D_2^M c_2^M} \frac{dc_2^M}{dx}, \quad (42)$$

$$\frac{d\phi_{\text{th}}^M}{dx} = -\frac{t_1^M Q_1^{*,M} - t_2^M Q_2^{*,M}}{z_2 F} \frac{d \ln T}{dx} \quad (43)$$

hold inside the membrane.

Under open circuit conditions $I = 0$ and $d\phi_{\text{ohm}}^M/dx = 0$. The diffusion potential gradient is negligible in strongly charged membranes separating two identical solutions [1]. Furthermore, as $t_2^M \approx 0$ in strongly charged membranes [27], contribution from eq. (43) can be simplified and the membrane contribution to the open circuit potential is

$$\Delta\phi^M \approx \Delta\phi_{\text{th}}^M \approx \frac{\bar{Q}_1^{*,M}}{z_2 F} \ln \frac{T(h)}{T(0)} \approx \frac{\bar{Q}_1^{*,M}}{z_2 F} \frac{\Delta T}{\bar{T}} \quad (44)$$

where the bar signifies values in average temperature and concentration.

The thermal membrane potential of one ion-exchange membrane can be evaluated as the sum of eqs. (35)-(37), (39), and (44):

$$\Delta\phi = \left[-\frac{R}{z_2 F} \varphi_D k + \frac{2(t_1 Q_1^* - t_2 Q_2^*)(1-k)}{z_2 F} \frac{\bar{T}}{T^{\alpha T \beta}} + \frac{Q_1^{*,M} k}{z_2 F \bar{T}} \right] \Delta T \quad (45)$$

where $\bar{c}$ and $\bar{T}$ is the average concentration and temperature inside the membrane, respectively, and $\varphi_D = \text{arcsinh}[X/(2\bar{c})]$. If the transport numbers of the negatively and positively charged species are very similar, the second term inside the square brackets is negligible. Furthermore, if the Donnan potential drop is approximated as $\varphi_D = \text{arsinh}[X/(2\bar{c})] \approx X/(2\bar{c})$, the thermal membrane potential is

$$\Delta\phi = \left[-\frac{R}{z_2 F} \frac{X}{2\bar{c}} + \frac{Q_1^{*,M}}{z_2 F \bar{T}} \right] k \Delta T. \quad (46)$$

Equation (46) predicts that two effects are affecting the thermal membrane potential – the membrane charge density (vs. electrolyte concentration) and the counter-ion heat of transport inside the membrane. Studies on the thermal membrane potential for common chloride electrolytes, such as LiCl, KCl, NaCl, and HCl, can be found in the literature, considering the effects of the electrolyte and its concentration [39–44], the thermal polarization [38], the mean temperature [45], and the hydrophobicity of the ion-exchange groups [46]. Generally, the absolute value of the thermal membrane potential decreases with increasing concentration [37], in agreement with eq. (46). The contribution from thermodiffusion inside the membrane could explain the observed differences between different electrolytes (or counter-ions).

3.2 Thermoelectric membrane cell

In publication [I] the thermal membrane potential was measured in a cell containing several cation- and anion-exchange membranes in an electrolyte solution, to mimic the structure of a conventional thermoelectric generator. The cell consisted of four narrow compartments with solutions of the same 1:1 electrolyte of uniform concentration. All solutions were pumped through the cell to larger containers, which provided mixing and maintained the desired temperature and composition of the solutions. The cell design would have made it possible to change the temperature of the two centremost solutions while keeping the electrode compartments at identical temperatures. However, the arrangement was deemed impractical and, in the experiments, the temperature of only one of the solutions (hot), was varied while the other three solutions had fixed temperature. While this approach did not keep the average temperature of the cell constant, it did not produce significant error to the results as no deviation from linear behaviour was observed [I].

The electrode compartments were separated by means of anion-exchange membranes and a cation-exchange membrane separated the hot solution from the cold one. Thus, temperature gradients existed across the cation-exchange and one of the anion-exchange membranes (Figure 3).

Figure 3. Diagram of the (single-module) experimental setup. H and C stand for hot and cold solutions, A and K for anion- and cation-exchange membrane, and α and ω for the electrode compartments. The solutions in all compartments are circulated. The inlet and outlet flow rates are $\dot{V}_{in}$ and $\dot{V}_{out}$, respectively. The inlet and outlet electrolyte fluxes are $J_{12,in} = c_{12,in}\dot{V}_{in}$ and $J_{12,out} = c_{12,out}\dot{V}_{out}$. The temperature and electrostatic potential distributions are indicated. Originally published in [I].

The used cell was modular, so that more anion- and cation-exchange membrane pairs (with hot and cold electrolyte streams) could be introduced in series to the

cell. This would increase the measured potential difference, in analogy with solid thermoelectric generators.

The electrodes were specially prepared from high-purity silver wire according to the procedure described in [I]. The commercial ion-exchange membranes were analysed in terms of their thermal conductivities and counterion transport properties, validating assumptions and enabling the evaluation of some parameters used in the analysis. Further details of the experiment can be found from PUB1 and the Supporting Information therein.

The e.m.f. of the cell with the single-module setup is obtained with equation (46) by combining the contributions from the anion- and cation-exchange membranes [I]:

$$\Delta\phi_{oc} = \left[k \frac{2R}{F} \operatorname{arcsinh} \frac{X}{2c} - \beta \frac{Q_{12}^{*,w}}{FT_C} \right] (T_H - T_C) \quad (47)$$

where k is the parameter describing the effective temperature difference in the membrane, R is the universal gas constant, F is the Faraday constant, c is the concentration of the electrolyte, T_C is the temperature of the cold stream and T_H is the temperature of the hot steam. The single parameter X was introduced as the geometric average fixed charge concentration of both the anion and cation membranes, a good approximation taking into consideration the similar characteristics of the membranes. The fitting parameter β considers the effective temperature difference combined with the difference between the electrolyte heat of transport in the aqueous phase and in the membrane phase.

3.2.1 Measured cell potential

Equation (47) predicts that the open circuit potential is proportional to the temperature difference between the two membrane boundaries, which is a fraction of the applied temperature difference. The inset of Figure 4a shows a typical measurement (0.1 mol/L NaCl). Although the heat of transport term is negative in eq. (47) the measured potential difference is positive with positive temperature difference. Thus, the measurement confirms that the Donnan term is larger than the negative electrolyte heat of transport term. Furthermore, the measured potential difference shows a linear dependence within the studied temperature difference interval, as predicted for one membrane configurations for both anion and cation-exchange membranes [37,42]. The slope of this line is the Seebeck coefficient of the cell, specific to this electrolyte and concentration. Figure 4a shows the dependence of the Seebeck coefficient with electrolyte concentration for KCl and NaCl. The solid lines are the best fits to the eq. (47) with β as the fitting parameter. The concentration dependence of $Q_{12}^{*,w}$ is obtained from

literature values of Soret coefficients, $Q_{12}^{*,w} = 2\sigma_{T,12}RT^2$ shown in Figure 4b and Figure 4c.

The Seebeck coefficient decreases with increasing concentration, mainly driven by the concentration dependence of the Donnan potential drops. This is illustrated by the dashed line in Figure 4a, which shows eq. (47) without the heat of transport contribution, i.e. $Q_{12}^{*,w} = 0$, and gives qualitative agreement with the measurements. However, the Seebeck coefficients are systematically larger for KCl than they are for NaCl, and the Donnan term alone cannot explain this difference, and the heat of transport term can be used to explain the difference. The agreement between the theoretical prediction and experimental measurements is deemed acceptable given the large dispersion in the heat of transport values reported for these two electrolytes in different concentrations (Figure 4b and Figure 4c).

Figure 4. (a) Variation of the Seebeck coefficient of the membrane cell with NaCl and KCl concentration. The solid lines represent eq. (47) with the electrolyte heats of transport estimated from the trend lines in panels (b) and (c), $X = 3$ mol/L and $k = 1/3$ fixed, and β as the only fitting parameter ($\beta = 0.6 \pm 0.3$ for KCl and 0.89 ± 0.16 for NaCl). The dashed line corresponds to $Q_{12}^{*,w} = 0$, $X = 3$ mol/L, and $k = 1/4$. The inset shows the potential difference measured in 0.10 mol/L NaCl. The full symbols are open-circuit measurements (slope 0.131 mV/K) and the open symbols are extrapolations of the closed-circuit measurements in the limit of infinite external load (slope 0.120 mV/K). (b and c) Concentration dependence of the Soret coefficient of NaCl and KCl aqueous solutions at 25 °C. The symbols are experimental data from the literature: Snowdon [47], Price [48], Römer [49], Chanu [50], Leaist [51], Agar st (steady-state values) and Agar in (initial values) [52], and Gaeta [53] (data corresponding to 30 °C). Originally published in [1].

The fitting parameter β can be interpreted to show the difference between the heat of transport of the electrolyte inside the membrane and in the bulk solution. Such difference would be expected, as the chemical environment inside the membrane is different from that of the bulk solution. For example, changes in

ionic strength reportedly affect the value [31]. Despite this, the measured Seebeck coefficients showed a clear correlation with the heats of transport of different electrolytes, although potassium electrolytes showed some deviation [I]. It should be noted that the theory presented here neglected the effect of water thermo-osmosis – including it could provide an even better agreement between experiments and theory.

3.2.2 Thermoelectric power

When the cell is connected to an external resistance, the thermally induced potential can be used to produce power. Figure 5a shows the voltage-current dependence of the cell in 0.10 mol/L NaCl and different ΔT . The very similar slopes indicate that the inner resistance of the cell R_{int} is independent of ΔT . The resulting peak power $P_{\text{max}} = (\Delta\phi_{\text{oc}})^2 / (4R_{\text{int}})$ is thus a function of $(\Delta T)^2$, and with $\Delta T \approx 20$ K, $P_{\text{max}} = 5$ nW cm⁻² (Figure 5b). Figure 5c shows the measured open circuit potentials in different concentrations of NaCl. Although the Seebeck coefficient of the cell is higher with lower concentration of the electrolyte, the lower conductivity of the electrolyte results in suboptimal power output. Increasing the concentration by a factor of 5 (0.02 mol/L to 0.10 mol/L) increases the power output significantly, whereas a further increase by a factor of 5 (0.10 mol/L to 0.50 mol/L) results in only slight improvement in the power output. The maximum power increases linearly with number of ion-exchange membrane pairs (anion+cation) connected in series.

Figure 5. (a and b) Thermally generated voltage $\Delta\phi$ and power output P/A in 0.10 mol/L NaCl solutions vs. electric current density through the external load for different ΔT . The practically identical slopes of the $\Delta\phi - i$ curves indicate that R_{int} is independent of ΔT . The power output is parabolic in the current density and its maximum value is $P_{\text{max}}/A = i_{\text{sc}}\Delta\phi_{\text{oc}}/4$, where $i_{\text{sc}} = \Delta\phi_{\text{oc}}/(AR_{\text{int}})$ is the short-circuit current density; P_{max}/A is given by the area of the largest rectangle under the $\Delta\phi - i$ curve. (c and d) Open-circuit voltage $\Delta\phi_{\text{oc}}$ and maximum power output P_{max}/A vs. the temperature difference. Symbols are experimental results, lines are theoretical curves. Originally published in [I].

The proposed cell design outlined how a thermoelectric generator can be built with ion-exchange membranes. The linear dependence of the thermal membrane potential on the temperature difference means that the power output scales with the temperature difference squared. The Seebeck coefficient could be increased by selecting electrolytes with low or negative heat of transport, which should also increase the power, if the conductivity does not decrease. Figure 5 showed that a high electrical conductivity of the membrane system is critical for high power output from the cell. However, in the studied system, it was shown that an increase of the electrolyte concentration beyond 0.1 mol/L did not produce significant increase in the maximum power. While the increasing concentration increases conductivity (decreases R_{int}), it simultaneously decreases the Seebeck coefficient (decreases the ratio $X/2c$). This suggests that the optimal electrolyte concentration for an optimized application is relatively dilute and depends on the charge density of the ion-exchange membranes. It is possible to increase the thermoelectric cell output with more membranes in series, as the Seebeck coefficient increases linearly with the number of membrane pairs.

The power produced by the system with NaCl is obviously low, not to mention the expected efficiency. However, it is of the same order of magnitude than obtained with other emerging thermoelectric technologies, such as organic thermoelectrics [21,54]. Further optimization of the cell and the electrolyte could naturally lead to some improvements in performance. Firstly, the effective temperature difference across the membrane was only about one third of the applied temperature difference. As the thermal conductivity of the membranes is close to that of water [1], the magnitude of parameter k suggests that the temperature polarization layers are of the same thickness as the membranes. With enhanced mixing, k could be increased – Barragán and Ruiz-Bauzá achieved over 200% increase to the Seebeck coefficient by controlling the mixing in their experiment [38]. This, with further optimization of the cell resistance could result in three orders of magnitude increase in the maximum power at 0.10 mol/L concentration. Increasing the membrane charge density also increases the Seebeck coefficient as dictated by eq. (47), and thus enables the use of more concentrated electrolyte solutions. The efficiency of the system could be further enhanced by decreasing the thermal conductivity of the membranes. These improvements could make electrolyte heat harvesting more appealing.

4. The Soret effect in electrolytes

The measurement of the Soret coefficient has some similarities with the measurement of the Seebeck coefficient. Both rely on establishing a well-defined temperature gradient to the system, but when measuring the Soret coefficient, the changes in local concentration are to be measured without disturbing the system. Again, a major source of error in many types of experimental setups is convective mixing. Convection can be fully eliminated only by conducting experiments in microgravity conditions [25], but similar to the Seebeck coefficient measurement, its effect can be minimized in normal gravity conditions by careful cell design and experimental approach, or it can be incorporated in the analysis of thermodiffusion [25,55].

Recently, optical methods have been among the most common ways for measuring the Soret effect [25,34]. One of the most popular examples is Thermal Diffusion Forced Rayleigh Scattering (TDFRS), where chemically inert dye is used to convert light into heat in the cell. Two lasers are used to create a grating of light intensity in the sample, which then interacts with the dye and transforms into heat grating. A third laser is used to measure the refractive index grating, and if the dependence of refractive index on concentration and temperature is known, this information gives the rate of thermodiffusion. Typical experiments are very short (few ms) but repeated many times. [25,34,56,57] Ideally, the dyes used in the experiments should be fully inert. In practice, they contribute typically a small error (0.5%) in organic solutions but in aqueous systems, dyes' spectroscopic properties usually vary more [57], potentially generating a larger error. Therefore, the technique can be used to study thermodiffusion of organic liquids and liquid mixtures, polymers and concentrated (aqueous) electrolyte solutions [25,56,57], yet when more diluted electrolyte solutions are used, conductivity measurements are usually more sensitive [58].

Pioneering work of Agar, Snowdon and Turner in the 1960s showed that by measuring changes in conductivity separately in cold and hot regions of a cell, the thermally-driven transport of electrolyte can be measured with good accuracy [47,52,59]. However, when electrolyte mixtures are studied, the different ionic concentrations cannot be measured by conductivity, and other methods must be used.

4.1 Thermodiffusion impedance

In publication [II] it was shown that when the system consists of an electrochemically active ion in an inert electrolyte, electrochemical impedance spectroscopy (EIS) is a practical technique to study thermodiffusion. The use of a thin cell, where the distance between the working electrode and the counter electrode is very small, enhances the effect of thermodiffusion.

4.1.1 Impedance spectroscopy

EIS is a technique based on the perturbation of the electrochemical system with a low-amplitude periodic signal and the measurement of the system response as a function of the frequency of the excitation signal [60]. If the excitation signal is a sine-wave potential signal $E = \hat{E} \exp(j\omega t)$, the response will be a current signal $I = \hat{I} \exp(j\omega t + j\varphi)$, where j is the imaginary unit, $\omega = 2\pi f$ is the angular frequency and f is the frequency of the signal, t is time, φ is the phase shift of the response and the caret represents the amplitude of the signals. The impedance Z is a complex number, defined as the ratio of potential E and current I :

$$Z = \frac{E}{I} = \frac{\hat{E}}{\hat{I}} \exp(-j\varphi) = \hat{Z} \exp(-j\varphi). \quad (48)$$

EIS offers several advantages over other techniques commonly used in electrochemistry. As the alternating perturbation does not depend on time, the response can be recorded several times and averaged over many observations, increasing the precision of the result. Because the perturbation signal is small, the current-potential dependence of the reaction can be linearized, which simplifies the analysis considerably [60]. Moreover, as the system response is a function of frequency, the analysis of the relevant (differential) equations can be done in the Laplace domain³, making them easier to solve analytically.

The drawback with EIS is its unselectiveness. The excitation draws a response from all electrochemical processes and reactions in the system simultaneously, and it might be difficult to know the individual contribution of a particular process. However, because different processes occur at different rates, they have different frequency dependence [60]. In general, this means that the amplitude and phase shift of the complex impedance change with frequency, depending on the characteristics of the system, and different processes can be identified and quantified based on this frequency dependence. For example, at high frequencies, fast processes such as ohmic resistance, charging of the electrode double layer, and resistance associated to the electrochemical reaction dominate the

³ Laplace transform of a function $f(x, t)$ is $\mathcal{L}\{f(x, t)\} = F(x, s) = \int_0^\infty f(x, t) e^{-st} dt$.

response, and at lower frequencies, mass transport processes begin to affect the response [60,61]. Therefore, measurements at different frequencies can uncover all the electrochemically relevant information about the system, if the frequency dependence of the response can be understood e.g. through a mathematical model [61]. However, due to the unselectivity and sensitivity of the measurement, the system needs to be carefully designed so that the error from unwanted reactions and processes is minimized. The more accurate the model employed to describe the processes occurring in the system, the clearer the interpretation of the experimental observations.

4.1.2 Theoretical modelling of the thermodiffusion impedance

In an electrochemical system, a temperature gradient and the Soret effect change the concentrations and ionic fluxes observed, for example, at the working electrode surface. The temperature gradient thus affects the electrode kinetics and the rate of mass transport in an electrochemical measurement, and both these phenomena can be seen with impedance spectroscopy. Therefore, by measuring the impedance of a redox reaction in a non-isothermal system, and formulating a relevant mathematical model of the process, it is possible to determine the Soret coefficient of an electrochemically active ion or redox couple.

In a general electron transfer reaction taking place at the electrode/solution interface, an oxidized species O accepts n electrons e and becomes a reduced species R,

The rates of the reduction and oxidation reactions are k_{red} and k_{ox} , respectively. In a one-dimensional description, the flux densities of species O and R at the interface ($x = 0$) are

$$j_{\text{O}}(x = 0, t) = -j_{\text{R}}(x = 0, t) = \frac{i(t)}{nF}. \quad (49)$$

From Chapter 2.3 we can deduce that in the presence of a temperature gradient, the flux of species i has contributions from electrodiffusion and thermodiffusion, and the driving forces are the isothermal gradients of the electrochemical potentials of the redox species and the temperature gradient. If an electrochemically inert electrolyte is added to the system so that its concentration is much larger than the concentration of the redox-pair species, the former is known as

the supporting electrolyte and the latter as the trace ions. The supporting electrolyte is added so that it carries the current in the bulk electrolyte, but at the electrodes, only the trace ions react. This means that the migration term is negligible for the trace ions, and their flux equations can be simplified

$$-j_i = D_i \left(c_i \sigma_{T,i} \frac{\partial T}{\partial x} + \frac{\partial c_i}{\partial x} \right). \quad (50)$$

This standard approach in electrochemistry considerably simplifies the analysis also in the non-isothermal case.

The reaction takes place in a thin cell, extending from the working electrode (WE) at $x = 0$ to the counter electrode (CE) at $x = h$, with $\Delta T = T(h) - T(0)$. Before measuring the electrochemical impedance, the system is allowed to reach Soret equilibrium ($j_i = 0$). Then, the surface concentrations at the WE are

$$c_{i,\text{eq}}^s = c_i^b E_{\theta,i} \quad (51)$$

where c_i^b is the average (bulk) concentration and $E_{T,i} = 2\theta_i / (1 - \exp[-2\theta_i])$ is the thermophoretic enhancement factor of species i ; $\theta_i = \sigma_{T,i} \Delta T / 2$. The impedance of the system can be evaluated by taking the Laplace transform of the continuity equation (eq. 9) and eq. (50) with the boundary condition that the flux density at the CE is equal to the flux density at the WE. The rather long derivation is shown in [II], and the resulting impedance is

$$\begin{aligned} Z(s) = R_{\text{ct}} + R_{\text{O},\text{eq}}^s \left(\rho_{\text{O}} \tanh \rho_{\text{O}} + \frac{\theta_{\text{O}}}{2} - \rho_{\text{O}} \frac{e^{\theta_{\text{O}}} - 1}{\sinh 2\rho_{\text{O}}} \right) \frac{1}{t_{\text{D},\text{O}} s} \\ + R_{\text{R},\text{eq}}^s \left(\rho_{\text{R}} \tanh \rho_{\text{R}} + \frac{\theta_{\text{R}}}{2} - \rho_{\text{R}} \frac{e^{\theta_{\text{R}}} - 1}{\sinh 2\rho_{\text{R}}} \right) \frac{1}{t_{\text{D},\text{R}} s} \end{aligned} \quad (52)$$

where

$$R_{\text{ct}} = \frac{R \left(\bar{T} - \frac{\Delta T}{2} \right)}{FA i_0} \quad (53)$$

is the charge-transfer resistance, $\bar{T} = T(0) + \Delta T / 2$ is the average temperature of the cell, A is the electrode surface area, $i_0 = F k^0 (c_{\text{O}}^s)^\alpha (c_{\text{R}}^s)^{1-\alpha}$ is the exchange current density, k^0 is the standard rate constant and α is the charge-transfer coefficient;

$$R_{i,\text{eq}}^s = \frac{RT(0)h}{2F^2 A D_i c_i^s}, \quad (54)$$

is the ohmic charge associated to species i ,

$$\rho_i(s) = \left(t_{D,i}s + \frac{\theta_i^2}{4} \right)^{\frac{1}{2}} \quad (55)$$

and

$$t_{D,i} = \frac{h^2}{4D_i}. \quad (56)$$

The zero-frequency ($t_{D,i}s \rightarrow 0$) limit of eq. (52) is

$$Z(\omega \rightarrow 0) = R_{ct} + R_{O,eq}^s [1 + L(\theta_O)] + R_{R,eq}^s [1 + L(\theta_R)] \quad (57)$$

where $L(x) = \coth(x) - 1/x$ is the Langevin function.

Eqs. (51)-(57), especially Eq. (52), show that it is possible to obtain the Soret coefficients of the reduced and oxidized species by analyzing the low-frequency impedance of a non-isothermal system, either by fitting the theoretical equation for $Z(\omega)$ to the measured data, or by extrapolating the EIS measurement to the real axis in the Nyquist plot. For the EIS measurement of the Soret coefficient, the thickness of the cell h , the diffusion coefficients D_i , and the surface area A need to be obtained somehow. They might be fitted to the same measurement, but a better option is to use the isothermal case as a reference point to the non-isothermal measurement. If $\Delta T = 0$, $\theta_i = 0$ and $\rho_i = \sqrt{t_{D,i}s}$, and the electrochemical impedance reduces to the tanh-type elements describing isothermal diffusion in a thin-layer cell [62,63]:

$$Z(\omega) = \lim_{s \rightarrow j\omega} Z(s) = R_{ct}^b + R_O^b \frac{\tanh(\sqrt{j\omega t_{D,O}})}{\sqrt{j\omega t_{D,O}}} + R_R^b \frac{\tanh(\sqrt{j\omega t_{D,R}})}{\sqrt{j\omega t_{D,R}}}, \quad (58)$$

the low frequency limit of which is

$$\lim_{\omega \rightarrow 0} Z(\omega) = R_{ct}^b + R_O^b + R_R^b \quad (59)$$

where $R_i^b = RT\bar{h}/(2F^2AD_i c_i^b)$ ($i = O, R$). Thus, the isothermal measurement can be used to obtain $t_{D,i}$.

The key message of the theory above is that in an electrochemical system, a temperature gradient has two effects. Firstly, the Soret effect changes the equilibrium concentrations at the electrodes. This has an effect to the equilibrium potential (through the Nernst equation) and to the reaction kinetics through the concentration dependence of the exchange current density. Secondly, the tem-

perature gradient drives mass transport by thermodiffusion, and the low-frequency response of the impedance deviates from the isothermal case and normal diffusion.

In addition to the electrode reaction and mass transport, the Ohmic resistance of the system, and the charging of the electrical double layer of the electrode also contribute to the impedance. Then, the total impedance of the system can be described with an equivalent circuit, which is shown in Figure 6. As explained earlier, the measurement is based on different processes, represented as different elements of the equivalent circuit, having different frequency dependencies. Fast processes dominate the response in higher frequencies, and slow processes become visible in lower frequencies. There are different ways to represent the impedance data, but in electrochemistry, the Nyquist plot is perhaps the most common one [60]. In the Nyquist plot, the negative of the imaginary part of the impedance is represented in the ordinate axis and its real part in the abscissa. Then, for the equivalent circuit in Figure 6, the impedance shows the response from the Ohmic resistance at high frequencies, and the imaginary part of the impedance is zero. When the frequency decreases, the simultaneous charging of the electric double layer of the WE, and the charge transfer reaction increase both the real and the imaginary parts, and a semicircle-like shape forms in the Nyquist plot. After this, mass transfer begins to be visible from the response. In macroscopic cells it is seen as a straight line rising in a 45° angle [60], but in a thin-layer cell, the confined space causes the mass transfer impedance to bend towards the real axis, forming another semicircle-like shape when $f \rightarrow 0$ [62].

Figure 6. The thermodiffusion impedance equivalent circuit. R_Ω is the Ohmic resistance, C_{dl} is the double layer capacitance, R_{ct} is the charge transfer resistance, and $TD_{ox,red}$ are the thermodiffusion elements of the oxidized and the reduced species, respectively. Originally published in [II].

4.1.3 Experimental thin-layer impedance cell

The impedance measurements in [II] were conducted in a thin-layer cell, shown in Figure 7, with platinum WE and CE, and Ag/AgCl reference electrode. The average temperature $\bar{T} = 298$ K of the cell was kept constant, and ΔT was changed by heating the CE at the top and cooling down the WE at the bottom. EIS was measured at open circuit potential (OCP) from 100 kHz to 1 mHz. The

redox pair was $\text{K}_3\text{Fe}(\text{CN})_6$ (O) and $\text{K}_4\text{Fe}(\text{CN})_6$ (R), the supporting electrolyte was 0.5 mol/L KCl. Other experimental details can be found from [II].

Figure 7. Left: Schematic of the measurement setup. The WE and CE, both from platinum, are clamped together and a 260 μm glass fiber separator and a thin Ag/AgCl wire are placed in the middle. Two copper blocks are used as the heat sink and source. The temperatures of the electrodes are measured with K-type thermocouples 1 mm away from the electrode surface and controlled with a Peltier element and a heating wire. The temperature gradient runs vertically through the cell, with the colder side at the bottom to reduce convection in the cell. Right: 3D-sketch of the cell. Originally published in [II].

4.1.4 Simulated and measured spectra

To understand how sensitive the different parameters are to the measured impedance spectrum, eq. (52) and the thermodiffusion impedance equivalent circuit were simulated. Figure 8 shows a selection of these simulations, where the effect of the Soret coefficient value, temperature difference and cell thickness are varied. In Figure 8a, the Soret coefficient $\sigma_{T,0} = \sigma_{T,R}$ is changed from 0.001 K^{-1} to 0.1 K^{-1} while $\Delta T = 30 \text{ K}$ and $h = 500 \mu\text{m}$. The observed sensitivity is enough to distinguish differences at the 0.001 K^{-1} range, but differences much below that would be difficult to observe and verify, given the expected precision of the low frequency impedance measurement. In Figure 8b, the temperature difference is changed when the Soret coefficient and thickness remain constant. With positive temperature differences (temperature of the WE is lower than the CE), the impedance decreases. Measuring the same system with different temperature differences would be an obvious way to improve the precision of the Soret coefficient determination. Finally, in Figure 8c, the thickness was changed while the Soret coefficient and the temperature difference are kept constant. Comparing this sensitivity to the others in the figure, it is evident that controlling the cell thickness, i.e. the distance between the two electrodes, is crucial. Decreasing the distance between the electrodes while maintaining constant ΔT increases the temperature gradient and enhances thermodiffusion.

Simulations also highlighted that when $c_0^b = c_R^b$, any difference in the Soret coefficients for the oxidized and reduced species would be difficult to observe,

whereas a possible difference in diffusion coefficients between the two species would cause a significant difference to the low-frequency impedance. Hence, the measurement is much more sensitive to the diffusion coefficient than to the Soret coefficient. Thus, $\sigma_{T,O} = \sigma_{T,R}$ and $D_R/D_O = 0.81$, obtained from the diffusion coefficient values in infinite dilution, were assumed in the analysis of the experimental measurements.

Figure 8. Simulated thermodiffusion impedance with different parameters. (a) The thickness h and the temperature difference ΔT are fixed, and the Soret coefficient $\sigma_{T,O=R}$ changes. (b) The thickness h and the Soret coefficient $\sigma_{T,O=R}$ are fixed, and the temperature difference ΔT changes. (c) The Soret coefficient $\sigma_{T,O=R}$ and the temperature difference ΔT are fixed, and the thickness h changes. To help comparison, the black line in all figures corresponds to the case $\Delta T = 30$ K, $\sigma_{T,O=R} = 10 \times 10^{-3} \text{ K}^{-1}$, $h = 500 \text{ } \mu\text{m}$. Other simulation parameters kept constant: the bulk concentrations $c_O^b = c_R^b = 5 \text{ mmol/L}$, electrode diameter $d = 5 \text{ mm}$, average temperature of the system $\bar{T} = 298 \text{ K}$, solution resistance $R_\Omega = 1 \text{ } \Omega$, double layer capacitance $C_{dl} = 5 \text{ } \mu\text{F}$, charge transfer resistance $R_{ct} = 5 \text{ } \Omega$, and diffusion coefficients $D_O = D_R = 10^{-5} \text{ cm}^2/\text{s}$. Originally published in [11].

The Soret coefficient of the redox-pair was experimentally measured in four different concentrations. In each concentration, the isothermal EIS measurement was used to obtain the electrode surface area A and the diffusional time for the reduced species, $t_{D,R}$ and $t_{D,O} = 0.81t_{D,R}$ with a fit to an isothermal equivalent circuit. Directly after the isothermal measurement, a temperature difference

was applied to the cell, and once the OCP of the cell stabilized, another EIS measurement was performed. These results were then fitted to the thermodiffusion equivalent circuit, with the values for A , $t_{D,R}$, and $t_{D,O}$ fixed from the isothermal measurement. This left five free parameters for the fit: Ohmic resistance, charge transfer resistance, double layer capacitance approximated as a constant phase element (two parameters n and Q , $1/Z_{CPE} = (j\omega)^n Q$, where $n \leq 1$), and the Soret coefficient. Figure 9 shows the measurements in $c_0^b = c_R^b = 10 \text{ mmol/L}$.

Figure 9. EIS measurement in $c_0^b = c_R^b = 10 \text{ mmol/L}$ in 0.5 mol/L KCl from $f = 100 \text{ kHz} - 1 \text{ mHz}$ at OCP and $\bar{T} = 298 \text{ K}$. Top panel shows the isothermal measurement and bottom panel the non-isothermal measurement with $\Delta T = 10 \text{ K}$. Symbols represent the measured impedance, solid line is the best fit. (a) The isothermal measurement, dashed lines show how the impedance changes if h is changed $\pm 5 \%$ (b) The high-frequency data fit of the isothermal case. (c) The non-isothermal measurement, dashed lines show how the impedance changes if $\sigma_{T,O=R}$ is changed $\pm 50 \%$. (d) The high-frequency data fit of the non-isothermal case. Originally published in [II].

The circles in Figure 9 represent measured values, the solid line is the best fit to the equivalent circuit. For all four concentrations, the fitted parameters are shown in Table 1. The isothermal measurement proved to be an effective way to determine the thickness and the surface area of the cell. The dashed line shown in Figure 9a highlights this sensitivity, as it represents $\pm 5 \%$ changes to the thickness, corresponding to $\pm 10 \%$ change in $t_{D,R}$. The surface area shows similar sensitivity. Fixing the values for these parameters for the non-isothermal case was essential, as the sensitivity of the impedance towards the Soret coefficient was much lower. In Figure 9c, the measurement with a 10 K temperature difference and its fit to the equivalent circuit is shown, together with the cases where the Soret coefficient $\sigma_{T,O=R}$ changes $\pm 50 \%$. Figure 9b and Figure 9d show the high frequency data for both cases in more detail.

Table 1. Best fit parameter values for different concentrations and temperature differences. In the isothermal measurements, A and $t_{D,R}$ were the only fitting

parameters for the whole frequency range. In the non-isothermal measurements, σ_T was the only fitting parameter for the whole frequency range. In both cases, R_Ω , Q , n and R_{ct} were obtained from the analysis of the high frequency data.

c [mmol L ⁻¹]	ΔT [K]	R_Ω [Ω]	R_{ct} [Ω]	Q [μF]	n	A [cm ²]	$t_{D,R}$ [s]	$10^3 \sigma_T$ [K ⁻¹]
50	0	0.54	0.47	2900	0.64	0.20	51.6	-
	10	0.53	0.48	1800	0.67			1.8
10	0	0.50	1.1	70	0.87	0.20	49.5	-
	10	0.37	2.0	69	0.87			6.0
5.0	0	0.50	3.2	71	0.83	0.26	50.8	-
	10	0.45	2.8	62	0.85			6.6
1.0	0	0.60	66	54	0.84	0.19	56.2	-
	10	0.70	71	100	0.78			4.2
	10	0.73	110	68	0.82			7.1
	20	0.57	77	150	0.72			9.1

The Soret coefficients are graphically presented as a function of the square root of the ionic strength in Figure 10a. The three measurement points at 1.0 mmol/L concentration (circles) indicate that $\sigma_T = (7 \pm 3) \times 10^{-3} \text{ K}^{-1}$. The measurements in slightly more concentrated solutions show similar results, but the measurement point at 50 mmol/L concentration resulted in a lower value. With the obtained precision, it might be premature to discuss how the Soret coefficient changes with concentration or ionic strength – taking the results as they are, it might be possible to observe a declining Soret coefficient as a function of the ionic strength. However, to make more far-reaching conclusions on this would require more measurements, perhaps with an optimized measurement setup where the obtained precision would be better. Furthermore, the assumption of negligible migration for the trace ions should be critically examined. The ions are in an electrolyte mixture, and as section 2.4 explained, this affects the observed Soret coefficients. An improved theory on thermodiffusion impedance should take this into consideration.

Figure 10. (a) The Soret coefficient of the reacting species decreases with increasing ionic strength. The symbols represent measurements in different concentrations of the ferro/ferri couple: 50 mmol/L (triangle), 10 mmol/L (diamond), 5 mmol/L (square), 1 mmol/L (open circles are different measurements and filled circle is their average); note the 0.5 mol/L KCl supporting electrolyte. The solid line shows the best fit for a linear decrease with increasing square root of the ionic strength, in agreement with the theoretical predictions and experimental observations in Ref. [15]. Our results, however, are not conclusive as to the dependence on I . The dashed line shows the best fit for a linear decrease with increasing I , which could also be consistent with our results. (b) The resistance associated with the oxidized species, $R_{O,eq}^S = RT(0)h/(2F^2AD_0c_0^bE_{\theta,0})$, calculated with the parameters in Table 1 and the diffusion coefficient corresponding to infinite dilution at 298 K. The resistance increases linearly with the reciprocal surface concentration in Soret equilibrium. Originally published in [II].

4.2 Polyelectrolyte thermodiffusion

The use of the impedance method for a trace electrolyte relies on the fact that the studied species are electrochemically active, whereas the supporting electrolyte is not. Should the studied species be electrochemically inactive, another approach should be used. As alluded to in the beginning of Chapter 4, one option then would of course then be TDFRS, were it not for its limited sensitivity in dilute electrolyte mixtures.

In publication [III], a diffusion cell was used together with UV/Vis absorption spectroscopy to combine the high sensitivity of the adsorption to the thermodiffusion experiment in a non-isothermal cell. The two sides of the diffusion cell were set at different temperatures and the cell compartments were separated by a porous fritted glass disc with a pore size range 40 – 100 μm . The low porosity of the disc, together with the pore size, effectively prevented mixing through the membrane, but created a stagnant layer of liquid where the mass transport through thermodiffusion could take place. The solution on the cold side was

constantly pumped through a spectrophotometer (Cary 60 UV-Vis, Agilent USA), which was used to measure the absorption spectrum periodically. The experimental setup is shown in Figure 11.

For the studied polyelectrolyte poly(sodium-4-styrenesulfonate, $M = 500$ kg/mol), the absorption spectrum showed two peaks in the UV-range, a highly sensitive one at 225 nm and another at 262 nm. The former was used in the analysis by calibrating the absorbance with a series polyelectrolyte samples of different concentrations. In the thermodiffusion measurement, the spectrum was measured every 5 min for time $t = 0-120$ min, every 15 min for $t = 120-360$ min, and every 30 min for $t = 360-7999$ min, after which a new procedure had to be manually started. The baseline was measured for each supporting electrolyte in the correct concentration beforehand. The approach provided the required sensitivity already in the nmol/L concentration range for the studied electrolyte, together with the possibility to study its behaviour in a supporting electrolyte, but the slow rate of thermodiffusion through the disc meant that each experiment took up to several days to complete.

Figure 11. The Side-bi-Side diffusion cell consists of two compartments of 3 mL, which can be set to different temperatures. Magnetic bars stir both sides, which are separated by a porous glass disc. The total volume of the cold side (α) when connected to a flow-through cuvette is 5 mL. Modified with permission from [64], originally published in [III].

4.2.1 Polyelectrolyte flux equations

The studied system consists of a polyelectrolyte (Na_nPSS , $n = 2400$), present as a trace electrolyte in a supporting electrolyte (e.g. NaCl), diluted in water. To make the derivation more general, the ions are indexed, so that Cl^- is 1, Na^+ is

3, and PSS^{n-} is 2, and ν_i are their stoichiometric coefficients in the electrolytes. Then c_{13} refers to the supporting electrolyte concentration, c_{23} to the polyelectrolyte concentration, and $c_{13} \gg c_{23}$. The ionic concentrations are

$$\begin{aligned} c_1 &= \nu_1 c_{13} \\ c_2 &= \nu_2 c_{23} \\ c_3 &= \nu_{3,1} c_{13} + \nu_{3,2} c_{23}. \end{aligned} \quad (60)$$

Naturally for NaCl $\nu_1 = \nu_{3,1} = 1$, but for the Na^+ in the polyelectrolyte, $\nu_{3,2} = 2400$. As the polyelectrolyte concentration is very low, it can be assumed that it does not affect the transport of the supporting electrolyte. The supporting electrolyte flux density $\vec{j}_{13}$ is then [III]

$$-\vec{j}_{13} = D_{13}(\vec{\nabla} c_{13} + \sigma_{T,13} c_{13} \vec{\nabla} T) \quad (61)$$

where T is the temperature, D_{13} is the diffusion coefficient and $\sigma_{T,13}$ is the Soret coefficient of the supporting electrolyte. The supporting electrolyte does, however, greatly affect the transport of the trace electrolyte. Because there are no electrodes in the system, current density $\vec{I} = F \sum_i z_i \vec{j}_i = \vec{0}$, where F is the Faraday constant and z_i the charge of the ion, the ionic fluxes $\vec{j}_i$ are coupled through the thermodiffusion electric potential gradient. With eq. (21) and the zero current condition, the electric potential gradient is

$$-\frac{F}{RT} \vec{\nabla} \phi_{I=0} = \sum_i \frac{t_i}{z_i} (\sigma_{T,i} \vec{\nabla} T + \vec{\nabla} \ln c_i) \quad (62)$$

where R is the gas constant and t_i is the transport number. Then, the polyelectrolyte flux density is

$$\vec{j}_{23} = \frac{\vec{j}_2}{\nu_2} = \frac{D_2 c_2}{\nu_2} \left(\vec{\nabla} \ln c_2 + \sigma_{T,2} \vec{\nabla} T - z_2 \sum_{i=1}^3 \frac{t_i}{z_i} (\sigma_{T,i} \vec{\nabla} T + \vec{\nabla} \ln c_i) \right) \quad (63)$$

which can be simplified by replacing the ionic concentrations with the electrolyte concentrations in eq. (60), and by introducing $D_{23,13} = \alpha D_2 c_{23} / c_{13}$, $D_{23,23} = D_2$, $D_{T,23}^* = D_2 \sigma_{T,23}^* + \alpha D_2 \sigma_{T,13}$, and $\alpha = (\nu_1 \nu_{3,2} / \nu_2) (D_3 - D_1) / (\nu_{3,1} D_1 + \nu_1 D_3)$, into [III]

$$-\vec{j}_{23} = D_{23,13} \vec{\nabla} c_{13} + D_{23,23} \vec{\nabla} c_{23} + D_{T,23}^* c_{23} \vec{\nabla} T \quad (64)$$

Here $D_{T,23}^*$ is the thermodiffusion coefficient and $\sigma_{T,23}^*$ is the observed Soret coefficient of the polyelectrolyte in the mixture,

$$\sigma_{T,23}^* = \sigma_{T,23} + \frac{\sigma_{T,23} - \sigma_{T,13}}{\frac{1}{v_{3,2}} + \frac{1 + v_{3,2} \frac{c_{23}}{c_{13}}}{2}} \approx \sigma_{T,23} + v_{3,2}(\sigma_{T,23} - \sigma_{T,13}). \quad (65)$$

Because the supporting electrolyte diffuses much faster than the polyelectrolyte, it can be assumed that the supporting electrolyte has reached Soret equilibrium distribution when the polyelectrolyte thermodiffusion is still ongoing. Equation (64) then simplifies into

$$-\vec{J}_{23} \approx D_2(\vec{\nabla}c_{23} + \sigma_{T,23}^*c_{23}\vec{\nabla}T) \quad (66)$$

The time dependence of the polyelectrolyte concentration can be solved from eq. (66) by using the quasi-steady state approximation⁴ [27]. The concentration in the cold side α is then

$$c^\alpha(t) = \frac{c_\infty^\alpha + (c_0 - c_\infty^\alpha)(1 - \omega t)^{1/(\omega\tau_{23})}}{1 - \omega t} \quad (67)$$

where

$$c_\infty^\alpha = \frac{V_0^\alpha + V_0^\beta}{V_0^\alpha + V_0^\beta e^{-\sigma_{T,23}^* \Delta T}} c_0, \quad (68)$$

and

$$\frac{1}{\tau_{23}} = \frac{AD_2 E_{T,23}}{h} \left(\frac{e^{-\sigma_{T,23}^* \Delta T}}{V_0^\alpha} + \frac{1}{V_0^\beta} \right) \quad (69)$$

is the inverse of relaxation time, $E_{T,23} = \sigma_{T,23}^* \Delta T / (1 - e^{-\sigma_{T,23}^* \Delta T})$ is the thermophoretic enhancement factor and the parameter $\omega = (1 - V^\alpha(t)/V_0^\alpha)/t$ takes into account the slow evaporation of water. Although extremely slow, when the experiment lasts for several days, the water evaporation should be considered as it can be easily misunderstood as the system being still out of Soret equilibrium.

4.2.2 Thermal separation of the polyelectrolyte

Equation (65) suggests that the Soret coefficient of the electrolyte in the mixture depends not only of its value in the absence of the supporting electrolyte, but also on the stoichiometric number (or charge) of the electrolyte, and the Soret

⁴ The approximation assumes that the volume of the disc is much smaller than the volume of the chambers, so that the transport through the membrane is fast compared to the rate of concentration change in the half cell chambers. Then, the flux is independent of position inside the disc.

coefficient of the supporting electrolyte. Interestingly, the same polyelectrolyte might show completely different thermodiffusion behavior in a mixture with one type of supporting electrolyte when compared to the behavior with another type of supporting electrolyte, given they had different $\sigma_{T,13}$ values. This behavior is perhaps evident from Figure 12 where eq. (67) is simulated with different observed polyelectrolyte Soret coefficient values, $\sigma_{T,23}^* = -0.2 \text{ K}^{-1} \dots 0.2 \text{ K}^{-1}$. With positive values, the cold side polyelectrolyte concentration increases, and with negative values, the concentration in the cold side decreases.

Figure 12. Simulated thermodiffusion of $\text{Na}_{2400}\text{PSS}$. The concentration on the cold side (α) changes when a temperature difference $\Delta T = 20 \text{ K}$ is applied. Depending on its effective Soret coefficient $\sigma_{T,23}^* = 0.2 \text{ K}^{-1} \dots -0.2 \text{ K}^{-1}$, the polyelectrolyte either accumulates at the cold side (thermophobic behavior, blue), or is depleted from the cold side (thermophilic behavior, red). Time is normalized with relaxation time τ_{23} to help comparison, $\omega = 0$. Originally published in [III].

The thermal separation of $\text{Na}_{2400}\text{PSS}$ was measured in $0.1 \text{ mol L}^{-1} \text{ NaCl}$ supporting electrolyte at $T_{\text{avg}} = 308 \text{ K}$ with $\Delta T = 20 \text{ K}$. In all studied concentrations, the polyelectrolyte concentration increased with time in the cold α -side, which indicates that $\sigma_{T,23}^*$ is positive. Figure 13 shows the measured concentration profiles for 12 nmol L^{-1} , 18 nmol L^{-1} , and 68 nmol L^{-1} . The thermal separation is almost complete in the 12 nmol L^{-1} case, but becomes weaker already in 18 nmol L^{-1} concentration. In 68 nmol L^{-1} the separation is almost zero. The blue lines in Figure 13 represent best fits to eq 11 with parameters $\sigma_{T,23}^*$, ω and τ_{23} (Table 2). The values for ω range between $(0.3 - 1) \times 10^{-3} \text{ h}^{-1}$, which results in a maximum of $1 \mu\text{L}$ loss of water per hour or $0.2 - 0.9 \text{ mL}$ in a week. Although the end volume of the system was not measured, this qualitatively agrees with observations, as in a week-long measurement, the volume change could sometimes be noticed. The route for water evaporation was not clear, but it could have had taken place either from between the hand-made silicon seals which were around the glass disc and between the half-cells, or through the

connections between the tubing from the cell and the flow-through absorbance cuvette.

Figure 13. Thermodiffusion of $\text{Na}_{2400}\text{PSS}$ in $0.1 \text{ mol L}^{-1} \text{ NaCl}$ at $T_{\text{avg}} = 308 \text{ K}$ with $\Delta T = 20 \text{ K}$ and a) $c_0 = 12 \text{ nmol L}^{-1}$ (6 mg L^{-1}), b) $c_0 = 18 \text{ nmol L}^{-1}$ (9 mg L^{-1}), and c) $c_0 = 68 \text{ nmol L}^{-1}$ (34 mg L^{-1}). Symbols represent experimental values. Blue lines (cold α -side) are best fits to eq 11 with the parameters shown in Table 1 and red lines represent eq 10 (hot β -side). The effect of a larger evaporation rate is noticeable in panel b), as the concentration in both chambers increase with time at larger times; note that the relaxation time τ_{23} depends on c_0 . Originally published in [III].

Figure 14 shows the fitted values for $\sigma_{T,23}^*$ in the studied concentrations. These results suggest that the observed Soret coefficient of the polyelectrolyte in the mixture, $\sigma_{T,23}^*$, is strongly dependent on the polyelectrolyte concentration. shows the fitted values In the measured concentrations $c_0 < 20 \text{ nmol L}^{-1}$, $\sigma_{T,23}^*$ increases sharply with decreasing c_0 , from values close to zero to values resulting in almost complete depletion of the polyelectrolyte from the hot β -side and enrichment in the cold α -side. However, negative values for $\sigma_{T,23}^*$ were not observed. From the value of the Soret coefficient observed in the mixture, the Soret coefficient in the absence of the supporting electrolyte can be evaluated with eq. (65), if $v_{3,2}$ and $\sigma_{T,13}$ are known. Figure 14c shows the resulting values for $\sigma_{T,23}$ with $\sigma_{T,13} = 2.3 \times 10^{-3} \text{ K}^{-1}$ and assuming $v_{3,2} = 240$, which corresponds to a case where 10% of the sodium in the sulfonate groups of the polyelectrolyte would be dissociated. However, the values for $\sigma_{T,23}$ in the more concentrated polyelectrolyte solutions are perhaps unrealistically close to $\sigma_{T,13}$. Still, there is a clear difference between the observed value in the mixture and the value in the absence of the supporting electrolyte, and $\sigma_{T,23}^* \gg \sigma_{T,23}$, which is in agreement with [65].

Table 2. Fitting parameters for thermodiffusion of Na₂₄₀₀PSS in 0.1 mol L⁻¹ NaCl at $T_{\text{avg}} = 308$ K with $\Delta T = 20$ K in various concentrations.

c_0 [nmol L ⁻¹]	$10^3 \sigma_{T,23}^*$ [K ⁻¹]	$10^7 \omega$ [s ⁻¹]	τ_{23} [h]
7	200	2.01	40.9
12	130	1.26	20.4
15	13	2.01	28.8
18	25	2.98	16.1
22	8.0	1.12	9.35
31	5.5	2.61	15.0
43	12	0.835	71.4
46	1.7	0.876	13.3
68	8.1	0.365	43.7
102	-0.10	0.865	4.92

Figure 14. a) $\sigma_{T,23}^*$ as a function of the initial concentration of the polyelectrolyte in 0.1 mol L⁻¹ NaCl (circles), black line an exponential fit to guide the eye. b) Theoretical steady-state concentration of the (cold) α -side as a function of $\sigma_{T,23}^* \Delta T$ (line) and the values (circles) calculated from $\sigma_{T,23}^*$ in panel a. c) Estimated Soret coefficient for the polyelectrolyte in the absence of supporting electrolyte. Originally published in [III].

4.2.3 Thermodiffusion in different supporting electrolytes

To verify the role of the supporting electrolyte in the observed Soret coefficient of the polyelectrolyte, similar thermodiffusion measurements were carried out in supporting electrolytes with different $\sigma_{T,13}$. Figure 15 compares the results in NaCl, NaClO₄, Na₂SO₄ and LiCl. Although the theory is made only for a ternary electrolyte case (three different ionic species present in the system), and thus does not strictly apply to the case in LiCl, it was chosen to the analysis as its Soret coefficient is reportedly close to zero or negative in dilute solutions [59,66].

Figure 15. Thermodiffusion of Na₂₄₀₀PSS ($c_{23} \approx 10 \text{ nmol L}^{-1}$, $T_{\text{avg}} = 308 \text{ K}$, $\Delta T = 20 \text{ K}$) in different 0.1 mol L^{-1} supporting electrolytes. a) Experimental results are represented with symbols and dash lines are the best fits: NaCl (circles and blue), LiCl (squares and orange), Na₂SO₄ (triangles and green), and NaClO₄ (diamonds and red). b) Theoretical predictions without the effect of evaporation, i.e. $\omega = 0$. Note that the difference between NaCl and LiCl is small and the curves practically overlap. Originally published in [III].

Figure 15a shows the measured data and the best fits to equation (67), and in Figure 15b, the effect of evaporation has been removed from the curves. The experiments confirm that the supporting electrolyte can significantly influence the thermodiffusion of the polyelectrolyte. Lowest values for the observed Soret coefficient (and thus weakest thermal separation) is achieved with NaClO₄, then with Na₂SO₄, and the highest values are obtained with NaCl and LiCl, which practically overlap. The results suggest that for all the Na-salts, $\sigma_{T,13} < \sigma_{T,23}$.

The observed Soret coefficient of the polyelectrolyte in NaCl and LiCl is nearly the same $\sigma_{T,23}^* \approx 0.130 \text{ K}^{-1}$. In Na_2SO_4 the value is 0.060 K^{-1} and in NaClO_4 it is 0.030 K^{-1} . For all studied cases $\sigma_{T,23}^*$ is larger than the estimated values $\sigma_{T,23}$ shown in Figure 14c, which, in light with the presented theory, suggests that $\sigma_{T,13} < \sigma_{T,23}$.

5. Conclusions and outlook

The temperature gradient affects the mass transport in solutions, in some cases to an extreme extent. In electrolyte solutions, this effect can be applied in fields ranging from heat harvesting and development in energy technology to biochemistry and membrane science. However, to better understand the possibilities in applications, the phenomenon itself must be more thoroughly understood. The interactions, especially in electrolyte mixtures, are complex and often difficult to predict, as this thesis and previous research have highlighted.

The thesis provided the proof-of-concept for an electrolytic thermoelectric generator and highlighted the parameters most critical to its performance. The achieved power densities were modest, but the study highlighted a clear path for improvement. The key issues were conductivity and enhanced mixing – these can be improved by optimizing the design of the cell and were projected to significantly increase the performance. The validation of these projections should be prioritized when moving forward. Also, advances in membrane technology, strongly driven by the everincreasing interest towards hydrogen, electrolyzers and fuel cells, is likely to decrease the cost and improve the performance of ion-exchange membranes in a way which is relevant also for the heat harvesting applications. Lastly, the fact that the membranes used are soft and flexible could open new avenues for applications, although here they were used in a rigid cell. If these points will be enough to spur wider interest, time will tell.

The research on membrane thermoelectricity raised a more fundamental question of how ions behave inside the membrane when exposed to a temperature gradient. It was hypothesized that the Soret coefficient inside the membrane is likely to be different from the Soret coefficient in the bulk solution. The membrane system can be regarded as a ternary mixture of aqueous electrolyte and the charged groups of the membrane – with the difference that the membrane groups are more rigid and the transport occurs through narrow channels. Understanding of such a system could be built and accumulated first through the study of slightly simplified systems: aqueous ternary mixtures, or solutions with polyelectrolytes. Suitable methods for measuring thermodiffusion in electrolyte mixtures are somewhat lacking, and the impedance method was developed to help in this regard. The method relied on the studied ions being electrochemically active and the supporting electrolyte being inactive. This feature allowed the probing of the thermodiffusion rate with the rate of reaction. The measurement and its fit to the impedance model yielded values for the Soret coefficient

which agreed with literature values. However, the impedance was very sensitive to the diffusional times $t_{D,i} = h^2/4D_i$, even more so than for the Soret coefficients. The results highlighted that it would be possible to study the differences of the Soret coefficients of the reduced and oxidized species, and to see how the change in the oxidation state (and structure of the ion) this way by changing concentration ratios of O and R. However, the early results highlight the need for improving the obtained precision, and to validate the results with other redox-pairs with known Soret coefficients in the next phase of study. Another interesting application of the thin-layer cell would be to directly study thermodiffusion in ion-exchange membranes by placing the membrane between the electrodes. From an experimental standpoint, an automated temperature control for setting the temperature difference would decrease the measurement time, and a more precise control over the distance between the two electrodes would eliminate the cell thickness as a parameter in the fit.

Lastly, the question of thermodiffusion in electrolyte mixtures was approached with more scrutiny in the context of polyelectrolyte thermodiffusion through a neutral fritted glass membrane. Our experimental observations confirm that the supporting electrolyte facilitates the thermodiffusion of the polyelectrolyte. The theory predicts that this effect is particularly important for a trace electrolyte. Most importantly, it was experimentally shown that the supporting electrolyte clearly influences the Soret effect of a polyelectrolyte. The theory suggested that it would be possible to observe thermophobic behaviour in one electrolyte and thermophilic behaviour in another electrolyte, but such stark differences were not experimentally verified. Still, the effect of supporting electrolyte is an important feature that should be considered in new studies conducted in multi-component systems, e.g. thermodiffusion and thermophoresis in biologically relevant solutions. Another interesting point observed was the nearly perfect thermal separation in dilute polyelectrolyte solutions. Although no convection was observed, it would be extremely interesting to see the result validated with another type of cell and polyelectrolyte.

References

- [1] R. Haase, Thermodynamics of irreversible processes, Dover, Mineola, 1990.
- [2] D.R. Caldwell, S.A. Eide, Separation of seawater by Soret diffusion, Deep Sea Res. Part A, Oceanogr. Res. Pap. 32 (1985) 965–982.
[https://doi.org/10.1016/0198-0149\(85\)90039-1](https://doi.org/10.1016/0198-0149(85)90039-1).
- [3] S. Iacopini, R. Piazza, Thermophoresis in protein solutions, Europhys. Lett. 63 (2003) 247–253. <https://doi.org/10.1209/epl/i2003-00520-y>.
- [4] D. Braun, A. Libchaber, Trapping of DNA by Thermophoretic Depletion and Convection, Phys. Rev. Lett. 89 (2002) 2–5.
<https://doi.org/10.1103/PhysRevLett.89.188103>.
- [5] M. Kreysing, L. Keil, S. Lanzmich, D. Braun, Heat flux across an open pore enables the continuous replication and selection of oligonucleotides towards increasing length, Nat. Chem. 7 (2015) 203–208.
<https://doi.org/10.1038/nchem.2155>.
- [6] I. Budin, R.J. Bruckner, J.W. Szostak, Formation of protocell-like vesicles in a thermal diffusion column, J. Am. Chem. Soc. 131 (2009) 9628–9629.
<https://doi.org/10.1021/ja9029818>.
- [7] R.A. Sperling, T. Liedl, S. Duhr, S. Kudera, M. Zanella, C.A.J. Lin, W.H. Chang, D. Braun, W.J. Parak, Size determination of (bio)conjugated water-soluble colloidal nanoparticles: A comparison of different techniques, J. Phys. Chem. C. 111 (2007) 11552–11559. <https://doi.org/10.1021/jp070999d>.
- [8] R. Piazza, A. Parola, Thermophoresis in colloidal suspensions, J. Phys. Condens. Matter. 20 (2008). <https://doi.org/10.1088/0953-8984/20/15/153102>.
- [9] S. Duhr, D. Braun, Why molecules move along a temperature gradient, Proc. Natl. Acad. Sci. U. S. A. 103 (2006) 19678–19682.
<https://doi.org/10.1073/pnas.0603873103>.
- [10] S. Iacopini, R. Rusconi, R. Piazza, The “macromolecular tourist”: Universal temperature dependence of thermal diffusion in aqueous colloidal suspensions, Eur. Phys. J. E. 19 (2006) 59–67. <https://doi.org/10.1140/epje/e2006-00012-9>.
- [11] A. Hammack, Y.L. Chen, J.K. Pearce, Role of dissolved salts in thermophoresis of DNA: Lattice-Boltzmann-based simulations, Phys. Rev. E - Stat. Nonlinear, Soft Matter Phys. 83 (2011) 1–7. <https://doi.org/10.1103/PhysRevE.83.031915>.
- [12] T.I. Quickenden, Y. Mua, A Review of Power Generation in Aqueous Thermogalvanic Cells, J. Electrochem. Soc. 142 (1995) 3985–3994.
<https://doi.org/10.1149/1.2048446>.
- [13] N. Jaziri, A. Boughamoura, J. Müller, B. Mezghani, F. Tounsi, M. Ismail, A comprehensive review of Thermoelectric Generators: Technologies and common applications, Energy Reports. 6 (2020) 264–287.

<https://doi.org/10.1016/j.egy.2019.12.011>.

- [14] T.M. Tritt, Thermoelectric phenomena, materials, and applications, *Annu. Rev. Mater. Res.* 41 (2011) 433–448. <https://doi.org/10.1146/annurev-matsci-062910-100453>.
- [15] J.A. Manzanares, M. Jokinen, J. Cervera, On the different formalisms for the transport equations of thermoelectricity: A review, *J. Non-Equilibrium Thermodyn.* 40 (2015) 211–227. <https://doi.org/10.1515/jnet-2015-0026>.
- [16] R. Moshwan, L. Yang, J. Zou, Z.G. Chen, Eco-Friendly SnTe Thermoelectric Materials: Progress and Future Challenges, *Adv. Funct. Mater.* 27 (2017) 30–44. <https://doi.org/10.1002/adfm.201703278>.
- [17] X.F. Zheng, C.X. Liu, Y.Y. Yan, Q. Wang, A review of thermoelectrics research - Recent developments and potentials for sustainable and renewable energy applications, *Renew. Sustain. Energy Rev.* 32 (2014) 486–503. <https://doi.org/10.1016/j.rser.2013.12.053>.
- [18] H. Jin, G. Marin, A. Giri, T. Tynell, M. Gestranus, B.P. Wilson, E. Kontturi, T. Tammelin, P.E. Hopkins, M. Karppinen, Strongly reduced thermal conductivity in hybrid ZnO/nanocellulose thin films, *J. Mater. Sci.* 52 (2017) 6093–6099. <https://doi.org/10.1007/s10853-017-0848-5>.
- [19] J. Wüsten, K. Potje-Kamloth, Organic thermogenerators for energy autarkic systems on flexible substrates, *J. Phys. D. Appl. Phys.* 41 (2008). <https://doi.org/10.1088/0022-3727/41/13/135113>.
- [20] K.D. Sandbakk, A. Bentien, S. Kjelstrup, Thermoelectric effects in ion conducting membranes and perspectives for thermoelectric energy conversion, *J. Memb. Sci.* 434 (2013) 10–17. <https://doi.org/10.1016/j.memsci.2013.01.032>.
- [21] O. Bubnova, X. Crispin, Towards polymer-based organic thermoelectric generators, *Energy Environ. Sci.* 5 (2012) 9345–9362. <https://doi.org/10.1039/c2ee22777k>.
- [22] T.J. Abraham, D.R. Macfarlane, J.M. Pringle, High Seebeck coefficient redox ionic liquid electrolytes for thermal energy harvesting, *Energy Environ. Sci.* 6 (2013) 2639–2645. <https://doi.org/10.1039/c3ee41608a>.
- [23] M. Bonetti, S. Nakamae, M. Roger, P. Guenoun, Huge Seebeck coefficients in nonaqueous electrolytes, *J. Chem. Phys.* 134 (2011). <https://doi.org/10.1063/1.3561735>.
- [24] I.B. Cadoff, E. Miller, eds., *Thermoelectric materials and devices*, Reinhold Publishing Corporation, New York, 1960.
- [25] M.A. Rahman, M.Z. Saghir, Thermodiffusion or Soret effect: Historical review, *Int. J. Heat Mass Transf.* 73 (2014) 693–705. <https://doi.org/10.1016/j.ijheatmasstransfer.2014.02.057>.
- [26] S.R. De Groot, P. Mazur, *Non-equilibrium thermodynamics*, North-Holland Publisching Co., Amsterdam, 1962.
- [27] K. Kontturi, L. Murtomäki, J.A. Manzanares, *Ionic transport processes*, Oxford University Press, Oxford, 2008.
- [28] J.A. Manzanares, *Thermodynamics of irreversible processes - revised version of Chapter 1*, unpublished manuscript, 2013.
- [29] J.N. Agar, Thermogalvanic cells, in: P. Delahay (Ed.), *Adv. Electrochem. Electrochem. Eng.*, Interscience, New York, 1963: pp. 31–120.
- [30] G. Guthrie, J.N. Wilson, V. Schomaker, Theory of the thermal diffusion of electrolytes in a clusius column, *J. Chem. Phys.* 17 (1949) 310–313. <https://doi.org/10.1063/1.1747244>.
- [31] J.N. Agar, Thermal diffusion and related effects in solutions of electrolytes, in:

W.J. Hamer (Ed.), *Struct. Electrolyte Solut.*, John Wiley & Sons, New York, 1959: p. 200.

- [32] B.E. Conway, D.P. Wilkinson, Non-isothermal cell potentials and evaluation of entropies of ions and of activation for single electrode processes in non-aqueous media, *Electrochim. Acta.* 38 (1993) 997–1013. [https://doi.org/10.1016/0013-4686\(93\)87020-E](https://doi.org/10.1016/0013-4686(93)87020-E).
- [33] J. Josseland, V. Devaud, G. Lager, H. Jensen, H.H. Girault, Hydrovoltaic cells. Part II: Thermogalvanic cells and numerical simulations of thermal diffusion potentials, *J. Electroanal. Chem.* 565 (2004) 65–75. <https://doi.org/10.1016/j.jelechem.2003.09.033>.
- [34] J.K. Platten, The Soret effect: A review of recent experimental results, *J. Appl. Mech. Trans. ASME.* 73 (2006) 5–15. <https://doi.org/10.1115/1.1992517>.
- [35] E.D. Eastman, Electromotive force of electrolytic thermocouples and thermocells and the entropy of transfer and absolute entropy of ions, *J. Am. Chem. Soc.* 50 (1928) 292–297. <https://doi.org/10.1021/ja01389a008>.
- [36] H.H. Girault, The water/oil/water thermocouple and the ionic seebeck effect, *J. Chem. Soc. Faraday Trans. 1 Phys. Chem. Condens. Phases.* 84 (1988) 2147–2154. <https://doi.org/10.1039/F19888402147>.
- [37] M. Tasaka, S. Morita, M. Nagasawa, Membrane Potential in Nonisothermal Systems, *J. Phys. Chem.* 69 (1965) 4191–4197.
- [38] V.M. Barragán, C. Ruiz-Bauzá, Effect of unstirred solution layers on the thermal membrane potential through cation-exchange membranes, *J. Memb. Sci.* 125 (1997) 219–229. [https://doi.org/10.1016/S0376-7388\(96\)00190-1](https://doi.org/10.1016/S0376-7388(96)00190-1).
- [39] M. Tasaka, K. Hanaoka, Y. Kurosawa, C. Wada, Thermal membrane potential through charged membranes in electrolyte solutions, *Biophys. Chem.* 3 (1975) 331–337.
- [40] M. Tasaka, N. Ichijo, S. Kobayashi, H. Kobayashi, Thermal membrane potential across charged membranes in NaCl-NH₄Cl and LiCl-NH₄Cl solutions, *Biophys. Chem.* 4 (1976) 269–274.
- [41] M. Tasaka, K. Ogawa, T. Yamazaki, Thermal membrane potential across charged membranes in 2-1 and 1-2 electrolyte solutions, *Biophys. Chem.* 7 (1978) 279–283.
- [42] K. Hanaoka, R. Kiyono, M. Tasaka, Thermal membrane potential across anion-exchange membranes in KCl and KIO₃ solutions and the transported entropy of ions, *J. Memb. Sci.* 82 (1993) 255–263. [https://doi.org/10.1016/0376-7388\(93\)85190-8](https://doi.org/10.1016/0376-7388(93)85190-8).
- [43] R. Kiyono, Y. Tanaka, O. Sekiguchi, M. Tasaka, Thermal membrane potential across cation-exchange membranes for various halide solutions, *Colloid Polym. Sci.* 271 (1993) 1183–1190.
- [44] K. Hanaoka, R. Kiyono, M. Tasaka, Nonisothermal membrane phenomena across perfluorosulfonic acid-type membranes, *Flemion S: Part II. Thermal membrane potential and transported entropy of ions*, *Colloid Polym. Sci.* 272 (1994) 979–985. <https://doi.org/10.1007/BF00658896>.
- [45] V.M. Barragán, C. Ruiz-Bauzá, On the dependence of the thermal membrane potential across cation-exchange membranes on the mean temperature, *J. Memb. Sci.* 134 (1997) 75–84.
- [46] M.S. Huda, R. Kiyono, M. Tasaka, T. Yamaguchi, T. Sata, Thermal membrane potential across anion-exchange membranes with different benzyltrialkylammonium groups, *Sep. Purif. Technol.* 14 (1998) 95–106. [https://doi.org/10.1016/S1383-5866\(98\)00064-1](https://doi.org/10.1016/S1383-5866(98)00064-1).
- [47] P.N. Snowden, J.C.R. Turner, The concentration dependence of the Soret effect, *Trans. Faraday Soc.* 56 (1960) 1812–1819.

<https://doi.org/10.1039/tf9605601812>.

- [48] C.D. Price, Thermal diffusion in solutions of electrolytes, Tech. Rep. U.S.A.F., Contract no. AF(052)-99 (AD0276280), 1961.
- [49] F. Römer, Z. Wang, S. Wiegand, F. Bresme, Alkali halide solutions under thermal gradients: Soret coefficients and heat transfer mechanisms, *J. Phys. Chem. B.* 117 (2013) 8209–8222. <https://doi.org/10.1021/jp403862x>.
- [50] J. Chanu, Thermal diffusion of halides in aqueous solution, in: I. Prigogine (Ed.), *Adv. Chem. Physics*, Vol. 13, Hoboken, NJ, 1967: pp. 349–367.
- [51] D.G. Leaist, L. Hui, Conductometric determination of the Soret coefficients of a ternary mixed electrolyte. Reversed thermal diffusion of sodium chloride in aqueous sodium hydroxide solutions, *J. Phys. Chem.* 94 (1990) 447–451.
- [52] J.N. Agar, J.C.R. Turner, Thermal diffusion in solutions of electrolytes, *Proc. R. Soc. London. Ser. A. Math. Phys. Sci.* 255 (1960) 307–330. <https://doi.org/10.1098/rspa.1960.0070>.
- [53] F.S. Gaeta, G. Perna, G. Scala, F. Bellucci, Nonisothermal matter transport in sodium chloride and potassium chloride aqueous solutions, *J. Phys. Chem.* 86 (1982) 2967–2974. <https://doi.org/10.1021/j100212a032>.
- [54] O. Bubnova, Z.U. Khan, A. Malti, S. Braun, M. Fahlman, M. Berggren, X. Crispin, Optimization of the thermoelectric figure of merit in the conducting polymer poly(3,4-ethylenedioxythiophene), *Nat. Mater.* 10 (2011) 429–433. <https://doi.org/10.1038/nmat3012>.
- [55] T.C. Van Vechten, C. Franck, Relative importance of convection and diffusion in binary liquid systems subject to small horizontal temperature gradients, *Phys. Rev. E - Stat. Physics, Plasmas, Fluids, Relat. Interdiscip. Top.* 48 (1993) 3635–3642.
- [56] B.J. De Gans, R. Kita, B. Müller, S. Wiegand, Negative thermodiffusion of polymers and colloids in solvent mixtures, *J. Chem. Phys.* 118 (2003) 8073–8081. <https://doi.org/10.1063/1.1563601>.
- [57] S. Wiegand, H. Ning, H. Kriegs, Thermal diffusion forced Rayleigh scattering Setup optimized for aqueous mixtures, *J. Phys. Chem. B.* 111 (2007) 14169–14174. <https://doi.org/10.1021/jp076913y>.
- [58] A. Boika, Mass transport phenomena at hot microelectrodes, University of Saskatchewan, 2010. <https://harvest.usask.ca/handle/10388/etd-06242010-155233>.
- [59] P.N. Snowden, J.C.R. Turner, The Soret effect in some 0.01 normal aqueous electrolytes, *Trans. Faraday Soc.* 56 (1960) 1409–1418. <https://doi.org/10.1039/TF9605601409>.
- [60] A.J. Bard, L.R. Faulkner, *Electrochemical methods, fundamentals and applications*, 2nd ed., John Wiley & Sons, Hoboken, 2001.
- [61] C.M.A. Brett, A.M.O. Brett, *Electrochemistry. Principles, methods and applications*, Oxford University Press, Oxford, 2005.
- [62] O. Contamin, E. Levart, D. Schuhmann, Étude de l'impédance de concentration sur une cellule à couche mince. I. Diffusion pure ou accompagnée d'une réaction chimique du premier ordre, *J. Electroanal. Chem.* 84 (1977) 271–285.
- [63] O. Contamin, E. Levart, D. Schuhmann, Study of the concentration impedance on a thin-layer cell. Part III. Diffusion coupled to a fast first-order chemical reaction, *J. Electroanal. Chem.* 88 (1978) 49–56. [https://doi.org/10.1016/S0022-0728\(78\)80339-8](https://doi.org/10.1016/S0022-0728(78)80339-8).
- [64] PermeGear, General Catalog, 2018. <https://perme gear.com/wp-content/uploads/2019/02/PermeGear-Catalog.pdf>.
- [65] D.G. Leaist, L. Hao, Very large thermal separations for polyelectrolytes in salt

solutions, J. Chem. Soc. Faraday Trans. 90 (1994) 1909–1911.
<https://doi.org/10.1039/FT9949001909>.

- [66] K.F. Alexander, Zur Theorie der Thermodiffusion in Flüssigkeiten, Zeitschrift Für Phys. Chemie. 203 (1954) 181–368. <https://doi.org/10.1515/zpch-1954-20327>.

Thermoelectricity and thermodiffusion are the result of temperature gradient -driven transport processes. They can be applied in heat harvesting, where waste heat is converted directly into electricity, or in component separation, where temperature gradient creates concentration differences. This thesis investigates how temperature gradients affect transport processes in electrolyte solutions, how the effects can be conveniently observed and predicted, and what kinds of applications they could find.

Cover photo: Valeria Azovskaya.

ISBN 978-952-64-0516-2 (printed)

ISBN 978-952-64-0517-9 (pdf)

ISSN 1799-4934 (printed)

ISSN 1799-4942 (pdf)

Aalto University
School of Chemical Engineering
Department of Chemistry and Materials Science
www.aalto.fi

**BUSINESS +
ECONOMY**

**ART +
DESIGN +
ARCHITECTURE**

**SCIENCE +
TECHNOLOGY**

CROSSOVER

**DOCTORAL
DISSERTATIONS**