Performance and Usage Patterns of Mobile Networks

Ermias Andargie Walelgne

Performance and Usage Patterns of Mobile Networks

Ermias Andargie Walelgne

A doctoral dissertation completed for the degree of Doctor of Science (Technology) to be defended, with the permission of the Aalto University School of Electrical Engineering, at a public examination held at the lecture hall AS1 of the school on 19 November 2021 at 12:00.

Aalto University
School of Electrical Engineering
Department of Communication and Networking

Supervising professor

Professor Jukka Manner, Aalto University, Finland

Thesis advisor

Professor Jörg Ott, Aalto University, Finland

Preliminary examiners

Professor Andreas Kessler, Karlstad University, Sweden

Dr. Narseo Vallina-Rodriguez, IMDEA Networks Institute, Spain

Opponent

Professor Tommi Mikkonen, University of Helsinki, Finland

Aalto University publication series

DOCTORAL DISSERTATIONS 150/2021

© 2021 Ermias Andargie Walelgne

ISBN 978-952-64-0570-4 (printed)

ISBN 978-952-64-0571-1 (pdf)

ISSN 1799-4934 (printed)

ISSN 1799-4942 (pdf)

<http://urn.fi/URN:ISBN:978-952-64-0571-1>

Unigrafia Oy

Helsinki 2021

Finland

Printed matter
4041-0619

Author

Ermas Andargie Walelgne

Name of the doctoral dissertationPerformance and Usage Patterns of
Mobile Networks**Publisher** School of Electrical Engineering**Unit** Department of Communication and Networking**Series** Aalto University publication series DOCTORAL DISSERTATIONS 150/2021**Field of research** Networking technology**Manuscript submitted** 11 August 2021**Date of the defence** 19 November 2021**Permission for public defence granted (date)** 26 August 2021**Language** English☐ **Monograph**☒ **Article dissertation**☐ **Essay dissertation****Abstract**

The popularity of mobile devices and the availability of various services over mobile cellular networks has increased over the past twenty years. Over time, mobile cellular network technologies have evolved, and the performance of wireless links from mobile devices to the core networks is increasing. Mobile applications and services require different network qualities to meet users' expectations and increase the Quality of Experience (QoE). To support the increased number of users, and to deliver the capacity required by applications, mobile networks have become complex systems. The demand for high-quality experience in mobile cellular networks is in the interest of both end-users and providers. However, mobile network performance is affected by a multitude of network features. This includes radio technology, network bandwidth and coverage, signal strength, mobility, throughput, latency, and data usage patterns of users.

This thesis analyzes mobile cellular network performance and usage patterns. We apply different data analysis methods and use various datasets collected through crowdsourcing and testbeds. We study various features of mobile networks and their effect on mobile network performance. We propose an estimation method for QoE in web browsing and discuss factors affecting web-flows performance in mobile networks. We present different models based on machine learning that predict network throughput, cluster, and classify mobile users' data usage patterns.

This thesis contributes to the evolving mobile networks by studying various network features that determine the performance of mobile networks and the data usage patterns of mobile users. The large-scale crowdsourced mobile network measurement datasets provide valuable input for understanding factors affecting the performance and quality of mobile networks. The study on the data usage patterns of mobile users provides significant input for understanding mobile users' data usage patterns and behavior across different countries. The classification model on network stability and data usage patterns can be valuable input for network resource optimization. The study conducted on the feasibility of teleoperated driving and correlation-based network feature mapping shows how crowd-sourced datasets can be used to analyze different use cases in mobile networks.

Keywords mobile networks, data usage, performance measurement, QoE**ISBN (printed)** 978-952-64-0570-4**ISBN (pdf)** 978-952-64-0571-1**ISSN (printed)** 1799-4934**ISSN (pdf)** 1799-4942**Location of publisher** Helsinki**Location of printing** Helsinki**Year** 2021**Pages** 233**urn** <http://urn.fi/URN:ISBN:978-952-64-0571-1>

Preface

“ፍጻሜና ተስፋ እስጣችሁ ዘንድ” ት.አ. ፳፱፡፲፩

Throughout my doctoral study I have received a great support and assistance. First and foremost, I would like to thank my supervising professor, Jukka Manner, who helped me a lot in all circumstances. Thank you so much for the unwavering support and patience. Your continuous guidance and encouragement helped me finalize my final thesis. I would not be here without you.

My special thanks also go to thesis advisor (ex-supervisor) professor Jörg Ott to trust me and give me the chance to start my doctoral studies. Your positive energy is very contagious. I want to say that I was lucky to be mentored with two excellent professors. Both professor Jukka Manner and Professor Jörg Ott have been excellent supervisors that I could not have asked for more. Your continuous support, practical approach, and constructive feedback brought me to where I am today. You both believed in me even in times I have not. I am so grateful for the consistent support and mentorship that you provided throughout my Ph.D.

I also could not have done all the work without these excellent other co-authors: Vibhav Bajpai, Alemnew Sheferaw Asrese, Stefan Neumeier, Kasper Apajalahti, Kim Setälä, Eero Hyvönen, Christian Facchi, Andra Lutu, Özgu Alay. It has been my honor to work with you.

I want to thank my colleagues, IT support, and all HR staff at the ComNet department, who have always been supportive. During my study, I had a chance to do a research visit at Elisa and TUM. I want to thank the personnel at Elisa, especially Kim Setälä. My gratitude to all members Chair of Connected Mobility at the TU Munich for your warm welcome and valuable feedbacks on multiple occasions. Your feedback was valuable input to this thesis.

Part of this thesis was funded by the European Union METRICS project. I thank all of the project partners and METRICS students for their valuable feedback and suggestions during the course of the project. Especially to my

METRICS colleagues, I am so grateful for all the good times we had during the project and wish you the best of luck in your future endeavor.

I want to thank the pre-examiners, Professor Andreas Kassler, Dr. Narseo Vallina-Rodriguez for reviewing my thesis and their valuable feedbacks. I am also grateful to Beneyam Haile for proofreading part of this manuscript.

A special thanks to Alemnew Sheferaw Asrese and Vaibhav Bajpai, without whom this thesis would have taken a lot longer. Alex, in all challenging and happy moments, in all ups and downs we went through, you have always been one call away whenever I asked. I could not ask more, so thank you.

I thank my family and friends, who have been the energy and motivation factor in finishing my Ph.D. Your prayer and continued support held me through this: Primarily, I want to extend my gratefulness to my mother, Yeajebnesh Miku, and my father, Andargie Walelgne, to my Brothers (Belachew (Tilaye and Woini), Henok) and sisters (Yeshe and Elsa). Your prayer, relentless encouragement, love, and thoughtfulness always give me a reason to breathe with joy. My brother Tilaye and my family gave me everything they had, sometimes beyond what they could. I am so happy, humble, and lucky to have you all as my family. I always adore and cherish you!

I have several people that I would like to thank. I believe you all know who you are, and I thank you so much for making this journey easy and joyful in one way or another. These are the ones who have been continuously supporting me during my Ph.D. career – whom I call friends and brothers with confidence. Tadele Worku – I always found humor, strength, and reason to live, Tsehay Wasihun – the iron man with heartwarming genuineness, Kasahun Zewudie – the motivator, and Yehenew Abere – the thoughtful soul. I also want to thank Kaisa Kettunen at Ericsson, who has encouraged me to complete my final thesis.

Last but not least, my thanks go to my beautiful wife Netsanet Ergetie. Especially the last couple of years of my Ph.D. was full of cumbersome. Thank you for brightening those challenging days with love, compassion, and laughter – apologies for taking some of your lovely moments while writing this thesis. For sure, we are going to have many more lovely moments ahead – Love you. Our new baby queen, Tinbite Ermias, blessed our life with joy – May God bless you.

Espoo, October 14, 2021,

Ermias Andargie Walelgne

Contents

Preface	1
List of Publications	7
Author's Contribution	9
List of Figures	11
1. Introduction	17
1.1 Research problem	18
1.2 Research methodology	20
1.3 Contributions of the thesis	21
1.4 Structure of the thesis	22
2. Mobile network measurements and performance analysis	23
2.1 Mobile networks	23
2.1.1 Evolution of mobile networks	24
2.2 Network measurement techniques and metrics	26
2.2.1 Network measurement approaches	28
2.2.2 Measurement metrics	29
2.3 Measurement platforms	33
2.3.1 Platforms in fixed line networks	33
2.3.2 Platforms in mobile networks	34
2.3.3 Tools and datasets	36
2.3.4 Challenges and limitations of crowdsourcing data . .	40
2.3.5 Ethical considerations	40
2.4 Related work	41
2.4.1 Mobility related measurements and analysis	42
2.4.2 Latency and packet loss	44
2.4.3 Throughput and network performance	45
2.4.4 Quality of experience in mobile networks	47
2.4.5 User behavior and data usage patterns	48
2.5 Summary	49
3. Network throughput and stability	51
3.1 Network throughput	51
3.2 Methodology and dataset	52

3.3	Network throughput	54
3.3.1	Radio technology and device model	54
3.3.2	Mobile network operator and subscribers' locations	55
3.3.3	Subscribers' locations and time of day	57
3.3.4	Predicting network throughput	58
3.4	Network stability	59
3.4.1	Received data per recording interval	60
3.4.2	Sudden dropout by network technology	60
3.4.3	Feature selection and classification model	61
3.5	Summary	63
4.	Web latency and quality of experience	65
4.1	Performance of web-flows	65
4.1.1	Methodology and dataset	67
4.1.2	DNS look-ups and failures	68
4.1.3	Packet loss	69
4.1.4	Radio technology type	70
4.1.5	Cache entries	72
4.2	Web browsing Quality of Experience (QoE) in mobile network	73
4.2.1	Methodology and dataset	74
4.2.2	Web latency and QoE	74
4.3	Summary	77
5.	Data usage patterns and user behavior in mobile networks	79
5.1	Methodology and dataset	79
5.2	Data usage patterns	80
5.2.1	User mobility and location dynamics	81
5.2.2	Device model and OS version	81
5.3	Data usage pattern across countries	83
5.3.1	Service Level Scores (SLS) and network congestion	85
5.4	Clustering mobile users data usage patterns	87
5.4.1	Types of mobile users	87
5.4.2	App categories	90
5.4.3	Data usage prediction	91
5.5	Summary	92
6.	Opportunities and challenges of mobile network measurements	95
6.1	Teleoperated driving	96
6.1.1	Methodology and dataset	96

6.1.2	Feasibility of Teleoperated driving in existing mobile networks	97
6.1.3	Latency	98
6.1.4	Throughput	99
6.2	Aggregating network measurement data	100
6.2.1	Methodology and dataset	101
6.2.2	Evaluating feature mapping	103
6.3	Summary	105
7.	Conclusions	107
7.1	Discussion	107
7.2	Limitations and future work	109
	References	113
	Errata	135
	Publications	137

List of Publications

This thesis consists of an overview, and of the following publications, which are referred to in the text by their Roman numerals.

- I** E. A. Walelgne, J. Manner, V. Bajpai and J. Ott. Analyzing Throughput and Stability in Cellular Networks. In *30th IEEE/International Federation for Information Processing (IFIP) Network Operations and Management Symposium*, Taipei, Taiwan, pp. 1–9 , 2018.
- II** E. A. Walelgne, K. Setälä, V. Bajpai, S. Neumeier, J. Manner, J. Ott. Factors Affecting Performance of Web Flows in Cellular Networks. In *17th International Federation for Information Processing (IFIP)/IEEE Networking Conference*, Zurich, Switzerland, pp. 73–81, 2018.
- III** A. S. Asrese, E. A. Walelgne, V. Bajpai, A. Lutu, Ö. Alay, J. Ott. Measuring Web Quality of Experience in Cellular Networks. In *Springer Passive and Active Measurement Conference (PAM)*, Puerto Varas, Chile, pp. 18–33, 2019.
- IV** E. A. Walelgne, A. S. Asrese, J. Manner, V. Bajpai, J. Ott. Understanding Mobile Data Usage Patterns and User Behavior Across Countries from the Edge. *Transactions on Network and Service Management (TNSM) (Accepted)* , pp. 1–14, xx 2020.
- V** E. A. Walelgne, A. S. Asrese, J. Manner, V. Bajpai, J. Ott. Clustering and Predicting the Data Usage Patterns of Geographically Diverse Mobile Users. *Computer Networks: The International Journal of Computer and Telecommunications Networking (Submitted)*, pp. 1–11, xx 2021.

- VI** S. Neumeier, E. A. Walelgne, V. Bajpai, J. Ott, C. Facchi. Measuring the Feasibility of Teleoperated Driving in Mobile Networks. In *2019 Network Traffic Measurement and Analysis (TMA)*, Paris, France, pp. 113–120, 2019.
- VII** K. Apajalahti, E. A. Walelgne, J. Manner, E. Hyvönen. Correlation-Based Feature Mapping of Crowdsourced LTE Data. In *2018 IEEE 29th Annual International Symposium on Personal, Indoor and Mobile Radio Communications (PIMRC)*, Bologna, Italy, pp. 1–7, 2018.

Author's Contribution

Publication I: “Analyzing Throughput and Stability in Cellular Networks”

The publication is a joint work between the authors. The author of this dissertation was the primary author of this paper and was responsible for data processing, machine learning-based model designing, and analysis. The author drafted and led the paper.

Publication II: “Factors Affecting Performance of Web Flows in Cellular Networks”

The publication is a joint work between the authors. The author of this dissertation was the primary author of this paper and was responsible for the main idea, including data processing, statistical analysis, and result compilation. The author drafted and led the paper.

Publication III: “Measuring Web Quality of Experience in Cellular Networks”

The publication is a joint work between the authors. The author of this dissertation was one of the co-authors of this paper and was responsible for parts of scripts for data processing, statistical data analysis, and paper writing.

Publication IV: “Understanding Mobile Data Usage Patterns and User Behavior Across Countries from the Edge”

The publication is a joint work between the authors. The author of this dissertation was the primary author of this paper and was responsible for the main idea including data processing, statistical data analysis and comparison of data usage patterns of mobile users across countries. The author drafted and led the paper.

Publication V: “Clustering and Predicting the Data Usage Patterns of Geographically Diverse Mobile Users”

The publication is a joint work between the authors. The author of this dissertation was the primary author of this paper and was responsible for the main idea including developing machine learning based models, data processing and analysis. The author drafted and led the paper.

Publication VI: “Measuring the Feasibility of Teleoperated Driving in Mobile Networks”

The publication is a joint work between the authors. The author of this dissertation was one of the co-authors of this paper and was responsible for parts of data collection, processing, analysis, paper writing, and concepts used in the paper.

Publication VII: “Correlation-Based Feature Mapping of Crowdsourced LTE Data”

The publication is a joint work between the authors. The author of this dissertation was one of the co-authors of this paper and was responsible for parts of algorithm design, data processing, and paper writing.

List of Figures

List of Figures

3.1	Distribution of downlink in 4G network technology over the years in Finland.	52
3.2	TCP download speed of different device models per network technology	55
3.3	The average downlink and uplink speeds of three different MNO's under LTE networks	56
3.4	Average TCP throughput of three MNO in Finland by area using LTE networks	56
3.5	Average of the first 3 bit rates samples before and after a <i>sudden dropout</i>	60
3.6	Bytes downloaded during each 50 ms sample time span	61
3.7	<i>Sudden dropout</i> occurrences per network technology over time of a day	61
3.8	Importance of network features used for the classification model	62
4.1	Distribution of 4G network latency (over UDP) in Finland over the years.	66
4.2	Percentage packets loss across the number of packets sent. . .	69
4.3	DNS response times by radio technology	71
4.4	TCP connect time towards <code>www.youtube.com</code> and <code>www.google.fi</code> by radio technology.	71
4.5	TCP connect time towards <code>www.google.fi</code> showing the latency difference between ISP cache and CDN	73

4.6	The distribution of (a) DNS lookup time, TCP connect time, Time To First Byte (TTFB), Page Load Time (PLT) and ATF . . .	75
4.7	The CDF of the PLT and the Above The Fold (ATF) time of the different websites.	76
5.1	Distribution of total download bytes per user during a month period.	81
5.2	Total download bytes per user categorized by price level and OS version of the devices	82
5.3	Total download bytes per user categorized by device Operating System (OS) version name and devices year of release.	83
5.4	Total download bytes per mobile users over WiFi and cellular in six countries	84
5.5	SLS distribution and variation over time of a day in six countries	85
5.6	Number of congested sessions on stationary and movable users.	86
5.7	Median distribution per cluster for users in Finland.	89
5.8	Proportion of application category per user within each cluster label.	90
6.1	CDF of ping latency based on the destination server in Munich/Frankfurt	98
6.2	Distribution of ping latency based on destination: Munich/Frankfurt. Figure from Publication VI.	98
6.3	CDF of Netradar uplink measurements	99
6.4	Variance of Netradar uplink measurements	99
6.5	Steps in the mapping procedure	103
6.6	Average mapping scores when mapping from RTR Nettest to Netradar	104
6.7	Average mapping scores when mapping from Netradar to RTR Nettest.	104

List of abbreviations

1G	First Generation
2G	Second Generation
3G	Third Generation
3GPP	3rd Generation Partnership Project
4G	Fourth Generation
5G	Fifth Generation
ACK	Acknowledgment
ADASYN	Adaptive Synthetic
ASU	Arbitrary Strength Unit
ATF	Above The Fold
CAIDA	Cooperative Association for Internet Data Analysis
CDMA	Code Division Multiple Access
CDMA-2000	CDMA-2000
CDN	Content Delivery Network
CID	Cell ID
CQI	Channel Quality Indicator
CRC	Cyclic Redundancy Check
CSP	Constraint Satisfaction Problem
Dig	Domain Information Groper
DNS	Domain Name System
EDGE	Enhanced Data rates for GSM Evolution
EDNS	Extension Mechanisms for DNS
5G	Fifth Generation
FDD	Frequency Division Duplex
FQDN	Fully Qualified Domain Name

GPRS	General Packet Radio Service
GPS	Global Positioning System
GSM	Global System for Mobile Communications
HSDPA	High Speed Downlink Packet Access
HSPA	High Speed Packet Access
HSPA+	Evolved High Speed Packet Access
HSUPA	High Speed Uplink Packet Access
HTTP	HyperText Transfer Protocol
HTTPS	HyperText Transfer Protocol Secure
ICMP	Internet Control Message Protocol
IDC	International Data Corporation
IP	Internet Protocol
IPTV	Internet Protocol Television
ISP	Internet Service Provider
ITU	International Telecommunication Union
IXP	Internet Exchange Point
KPI	Key Performance Indicator
LAC	Location Area Code
LTE	Long Term Evolution
LTE-A	LTE Advanced
MAC	Medium Access Control
MBB	Mobile Broadband
MCC	Mobile Country Code
M-Lab	Measurement Lab
MMS	Multimedia Messaging Service
MNC	Mobile Network Code
MNO	Mobile Network Operator
MOS	Mean Opinion Score
MPTCP	Multipath TCP
NDT	Network Diagnostic Tool
NNE	NorNet Edge
NSA	Non-standalone
OONI	Open Observatory of Network Interference
OS	Operating Systems

PDC	Personal Digital Cellular
PLT	Page Load Time
PRTP	Partial Reliability Transport Protocol
QoE	Quality of Experience
QoS	Quality of Service
RAN	Radio Access Network
RAT	Radio Access Technology
RF	Random Forest
RMSE	Root Mean Square Error
ROC	Receiver Operating Characteristic
RRC	Radio Resource Control
RSRP	Reference Signal Received Power
RSRQ	Reference Signal Received Quality
RSSI	Received Signal Strength Indicator
RSSNR	Reference Signal Signal to Noise Ratio
RTO	Retransmission Timeouts
RTT	Round Trip Time
SCTP	Stream Control Transmission Protocol
SINR	Signal-to-Interference-plus-Noise Ratio
SLS	Service Level Scores
SMOTE	Synthetic Minority Over-sampling Technique
SMS	Short Messaging System
SNR	Signal to Noise Ratio
SA	standalone
SYN	SYNchronize
SYN-ACK	SYNchronize-ACKnowledgment
TCP	Transport Control Protocol
TDD	Time Division Duplex
TDMA	Time-Division Multiple Access
TFVR	Time for Full Visual Rendering
TTFB	Time To First Byte
UDP	User Datagram Protocol
UMTS	Universal Mobile Telecommunications System
UE	User Equipment

List of abbreviations

VoD	Video-on-Demand
VoIP	Voice over IP
WCDMA	Wideband Code Division Multiple Access
WCSS	Within Cluster Sum of Squares
WWW	World Wide Wireless Web
WebLAR	Web Latency And Rendering

1. Introduction

The ubiquity of the mobile device, combined with the availability of mobile networks with Internet access, significantly impacts today's society. Internet access over mobile devices has become an integral part of everyday life. Mobile users are now accustomed to performing different activities using their mobile devices wherever they go. Some of the activities include performing business tasks, following news and entertainment, playing games, and fetching information from the Internet. Support for mobility, ease of use, and availability of mobile devices makes mobile networks widely used communication methods [1, 2, 3, 4, 5].

Since the first introduction of the Global System for Mobile Communications (GSM) network, recent years have witnessed the overwhelming growth of accessing the Internet via mobile devices. This growth is a combined effect of the abundance of reasonably cheap smartphones, improvement in radio technologies [6, 7], increasing number of mobile-based services, flexible pricing on mobile data plans [8, 9], and availability of different spectrum aggregation methods [10, 11]. According to the GSM Association report, in 2018, more than 3.5 billion people (~47% of the global population) are connected to the Internet [12]. A Cisco Annual Internet Report estimation shows that more than 70% of the global population will have mobile connectivity in 2023 [13].

Over time, various mobile Internet applications and services, including multimedia streaming, mobile games, web browsing, instant messaging, and voice-based apps, are evolving. As a result, the amount of traffic generated from mobile devices is increasing. For instance, more than 2.9 million Android apps were just on the Google Play store by May 2020 [14]. This also shows the fast growth of the mobile app economy in generating revenues [15, 16] in the order of billions of dollars [17]. The majority of them are driven by multimedia content [18, 19, 20] and web traffic [21].

Over the past years, there has been an improvement in mobile network technology, network coverage, bit-rate enhancement, and device hardware (e.g.,

chipsets, antennae). However, mobile users' demand for high-quality of services and data consumption is still growing [12, 13, 18, 21]. As various mobile-based services are introduced and the number of mobile users increases, there is a need to efficiently manage the limited network resources.

Mobile networks have evolved to be complex and heterogeneous in order to support the requirements of high-speed demand, user mobility, and the growing number of users [22, 23, 24]. The added complexity increases the challenge of quantifying and understanding network factors that are affecting mobile network performance.

1.1 Research problem

In an effort to understand the complexity of mobile cellular networks and their performance, quantifying and conducting measurements is required. The goal of measuring mobile networks and analyzing the dataset is to provide an input that can eventually help to improve the network performance and to deliver network connectivity with an enhanced quality of user experience. However, due to the complex nature of the mobile network such as dependence on user mobility [24, 25, 26], environmental conditions [27], device model [28, 29, 30], middleboxes [31, 32], core network inefficiencies [33], access technologies, and location [34, 35], multiple factors affect its performance and user satisfaction. As a result, mobile network data analysis and understanding its performance require a systematic and comprehensive study that considers the aforementioned factors.

Generally, we can categorize factors affecting mobile network performance and Quality of Experience (QoE) into three major groups of metrics. 1) Bit-rate related parameters, such as uplink, and downlink speed, signal strength, and handover; 2) Latency related metrics such as Domain Name System (DNS) [36] lookup time and Transport Control Protocol (TCP) [37] connection establishment time; and 3) Mobile users data usage patterns, such as mobility, location, heavy users and light user, device type, radio access technology (e.g., Fourth Generation (4G) [38, 39] and Third Generation (3G) [40, 41]) networks).

This thesis studies the performance and data usage patterns of mobile networks using measurement datasets collected from the crowd and dedicated testbeds. It investigates the aforementioned factors using real-world measurement datasets collected from end-user devices. The primary research question of this thesis is:

- How can we use mobile measurement data to understand better mobile networks in general and the performance of mobile-cellular networks in particular?

This thesis investigates the main challenges of today’s mobile network connectivity using crowd-sourced measurement datasets collected from end-user devices and from dedicated test-beds. In order to address the aforementioned research question, the thesis focuses on the following objectives.

- First, it investigates a mechanism for understanding network performance in terms of throughput, latency, mobility, device model, network coverage, location, etc. It studies how to classify the stability of TCP download bit rate using minimal information. It also studies how to estimate QoE in mobile networks and how the performance of short web-flow is affected by different factors, such as the presence of cache entries. The thesis address these objectives in Publications I, II and, III.
- Second, the thesis asks whether similar data usage patterns emerge among mobile users by studying factors such as total data consumption, network technology coverage, and mobility. Moreover, it investigates whether it is possible to build a model that predicts a cluster of data usage patterns (if it exists) using machine learning methods. It addresses these questions in Publications IV and V, where we study and characterize data usage patterns and behaviors of mobile users across five different countries.
- Third, the thesis studies how to use exiting measurement datasets to study different research topics. Within this research question, we demonstrate the importance of evaluating how well mobile networks can meet emerging technologies and applications’ performance needs. In this regard, we investigate whether Teleoperated driving is feasible in an existing mobile network by conducting measurements while driving. We also seek a methodology that aggregates network measurement data by mapping similar network features collected from two different measurement platforms. The research output can be used, for instance, to enhance the design of new applications and tackle technical challenges in a timely manner. Publications VI and VII address these research questions.

The primary goal of this thesis is to provide a data-driven based mobile network

performance analysis using real-world measurement datasets collected across different locations. It helps to advance the state-of-the-art by identifying factors affecting mobile network performance and mobile users' data usage patterns. As a result, Internet service providers and application designers can use the outputs of this type of empirical research to enhance user QoE.

1.2 Research methodology

In the thesis, a variety of research methodologies have been applied to address a number of research objectives. The detailed methods are described in each chapter. We used measurement data collected through crowdsourced platforms (e.g., Nettitutka [42] and Netradar [43]) and dedicated testbeds (e.g., MON-ROE [44]). We leverage vast amounts of measurement datasets (ranging from several thousand to millions of records) collected through different mobile network measurement platforms. The majority of the datasets used in this thesis are collected through pre-built crowdsourced-based mobile network measurement platforms. Some of the measurement platforms have been running for several years. The datasets cover a wide range of geographical areas, Mobile Network Operators (MNOs), radio technology types, and mobile users.

Most of the measurement data have been collected using two primary types of measurement methods, known as active and passive measurement. One of the measurement platforms used (i.e., Netradar) uses a hybrid measurement method, combining both active and passive measurements. We use a dataset collected through active measurement for network performance-related analysis, such as throughput, latency, and web QoE. To study users' data usage patterns and behavior, we used datasets that were collected using passive measurement methods, as these are more natural for capturing the actual data usage behavior of mobile users.

We applied different statistical methodologies and techniques to analyze the datasets, including data preparation, validation, cleaning, anonymization, and interpretation. We applied correlation and statistical analysis to understand the influence of different factors such as latency, throughput, radio technology, device hardware limitations, and user mobility in a mobile network. We applied machine learning-based algorithms and methods to predict the network throughput, classify the mobile network's stability based on the user's data reception characteristics, and understand and model mobile users' data usage patterns across different locations. A supervised machine learning approach has been applied for classification and prediction models. An unsupervised machine learn-

ing method was used to study mobile users' data usage patterns and behavior across countries.

We conducted mobile network measurements while driving a vehicle using three measurement tools (Netitutka, Ping, and iperf3). This study helps to evaluate whether the current mobile network meets the emerging technology demands such as teleoperated driving. For correlation-based feature mapping, we use the Pearson and Spearman correlation coefficient by solving the maximum Constraint Satisfaction Problem (CSP). The detailed dataset metrics, along with measurement collection methods, are described in Chapter 2.

1.3 Contributions of the thesis

This thesis is composed of seven research publications based on the original work by the author. The contribution of each publication investigates a part of this thesis, focusing on characterizing mobile network performance, data usage patterns, and performance prediction from the edge.

In Publication I, we study the throughput of a cellular network by applying a machine learning approach to identify the important features and to understand the relationship between different ones. These features are then used to build a model to classify the stability of cellular networks based on the data reception characteristics of the user. We show that it is possible to classify networks instability using minimal cellular network metrics with up to 90% accuracy.

In Publication II, we use a month-long DNS-lookup time and TCP connection time measured towards popular websites from 25K subscribers of a network operator in Finland. Using this dataset, we present and discuss factors affecting web-flow performance in a mobile network. A method of estimating web Quality of Experience (web QoE) in mobile networks is presented in Publication III. We develop two different approaches to measuring web QoE, known as pixel-wise comparison and browser heuristics, using the web ATF time as a metric.

Publications IV and V focus on studying mobile users' data usage patterns in different countries. In Publication IV, we use a month-long dataset of 340 million measurement sessions across six countries to investigate the data usage patterns of mobile users. We study different factors such as time of day, user mobility, location, and the frequency of users accessing the data traffic over cellular or WiFi network. In Publication V, we investigate mobile users' data usage patterns across countries. We apply unsupervised and supervised machine learning-based models that help cluster and classify mobile users' data usage patterns, respectively.

In Publication VI, we investigate the feasibility of Teleoperated driving on the current mobile network. Publication VII presents a correlation-based feature mapping method. We present a method of correlating related features in the LTE network using datasets collected from two different crowdsourcing-based mobile network measurement platforms.

1.4 Structure of the thesis

Each chapter consists of materials and knowledge gained from one or more of the included publications. The thesis is organized as follows.

Chapter 2 outlines the background information for the whole thesis. It provides insights into the evolution of mobile networks, the different approaches of network measurement techniques, and measurement platforms used on both fixed-line and mobile networks. Specifically, this chapter describes the different measurement platforms and tools that we have used the datasets in one or more of the included publications. After describing the measurement platforms, this chapter turns to a discussion of related work focusing on mobile network performance and analysis, QoE, and data usage patterns.

Despite several studies on mobile network measurement and performance analysis, there are still gaps in adequately understanding and characterizing mobile network performance in a way that reflects end-users' perceived network performance and data usage. Crowd-based data measurement and analysis is one good way to get the actual network performance as experienced by mobile users, as the metrics are collected from the end-user device.

Chapter 3 discusses mobile network performance based on TCP throughput. It presents different factors affecting the stability of throughput, including radio technology, mobility, as well as a prediction model of the average TCP throughput. It also presents a model that classifies the stability of TCP throughput based on sudden dropouts observed during a measurement session.

Chapter 4 focuses on the latency and factors that affect short web-flows in mobile networks. It also presents web browsing QoE in mobile networks. Chapter 5 presents mobile users' data usage patterns and behavior by leveraging a measurement dataset (more than 113M records) collected across five countries. It presents a clustering and classification model of data usage in mobile networks.

Chapter 6 discusses mobile network measurement opportunities and challenges by considering two use-cases, focusing on crowdsourced datasets. Finally, Chapter 7 concludes the thesis with a discussion on this research's impact, limitations, and future research prospects.

2. Mobile network measurements and performance analysis

This chapter starts by discussing mobile networks, including how they evolve and their significance. It briefly discusses network (Internet) measurements at the high-level, such as the importance of conducting network measurements, how they are performed, and what are the metrics that we can measure. It also discusses how mobile networks in general, and mobile network measurements in particular, are different from fixed-line networks. Next, it introduces some of the measurement platforms and frameworks that are known in both fixed-line and mobile network research areas. Following that, it describes the measurement platforms and tools used in this thesis. Finally, it covers previous research results related to the thesis topic, focusing on mobile network performance and analysis.

2.1 Mobile networks

A mobile network refers to the whole process of accessing Internet data through any kind of radio communication, as well as support for network mobility. A mobile user can access the Internet using different radio technologies, such as cellular radio technologies (Long Term Evolution (LTE), Universal Mobile Telecommunications System (UMTS)) or WiFi hotspots. This thesis focuses on Internet data communication on mobile networks using cellular radio technologies; we refer to them here as mobile networks. In this thesis, the term mobile network is also used interchangeably with cellular network. In the later chapters, we study data usage patterns of mobile users on WiFi and mobile networks.

A mobile network communication system can be built on several radio technologies. In order to have seamless communication both at the local and global levels, standards and requirements for radio technologies must be agreed internationally. The International Telecommunication Union (ITU) specifies the technical standards of different radio technologies used in mobile networks. The

ITU standards (recommendations) are important guidelines that specify the scope and high-level requirement of radio technologies by which the 3rd Generation Partnership Project (3GPP) must abide. The 3GPP is a global collaboration between various telecommunication companies, service providers, and device manufacturers [45]. The 3GPP follows the requirements set by the ITU and it studies, defines, develops, and maintains the technical standards of radio technologies. Each new version of the standards defined by 3GPP are known as ‘releases’. The next section briefly discusses the evolution of mobile networks, along with the releases of radio technology standards.

2.1.1 Evolution of mobile networks

Following the introduction of digital radio technologies, the evolution of mobile networks gets its momentum in the early 1990s after the Second Generation (2G) wireless telephone was introduced. GSM is one of the most widely used standards of 2G radio technology families. GSM uses Frequency Division Duplex (FDD) and Time-Division Multiple Access (TDMA) techniques. TDMA is a technique for dividing signals into different time slots, which allows multiple users to share the same frequency channel. On the other hand, FDD uses two separate frequency channels for simultaneously transmitting and receiving data. The GSM network was primarily designed to provide only a voice communication service. However, later, it was enhanced to provide limited data communication using a Short Messaging System (SMS).

Later at the beginning of the 2000s, improved variants of the GSM network were developed to enhance its limited data service. The General Packet Radio Service (GPRS) and Enhanced Data rates for GSM Evolution (EDGE) improved the performance of GSM by incorporating packet-switched connectivity and adaptive coding and modulation techniques. As a result, peak download data rates were enhanced to 171 kbps and 473 kbps for GPRS and EDGE, respectively [46]. The requirements of GPRS and EDGE were set by the European Telecommunications Standards Institute (ETSI). The release of GPRS/EDGE provides different services including text messages, Multimedia Messaging Service (MMS), and circuit-switched data transfer. Note that, although GPRS and EDGE are sometimes regarded as 2.5G and 2.7G, respectively, we include them here as 2G families. Throughput capacity and latency were improved in the later evolution of the EDGE technology through multi-carrier and higher-order modulation based transmissions.

During the 2G period, different regions such as the USA, EU, and Japan, have adopted different standards. For instance, GSM, Personal Digital Cellular (PDC),

and CDMAone (IS-95) have been widely used in Europe, Japan, and the USA, respectively [47]. Later, a joint standardization effort focuses on 3G technology under the 3GPP consortium, which helps to achieve similar specifications and equipment compatibility globally.

Demand for high data rates, such as for multimedia services and the ITU new IMT-200 band recommendation, led to the development of the joint 3G technology. UMTS is one of the 3G technologies that evolved from GSM, providing higher data rates and more advanced services than its predecessors. Wideband Code Division Multiple Access (WCDMA) is one of the popular 3G technologies that UMTS uses as its air-interface technology. WCDMA comes with advanced capabilities as it uses FDD and Time Division Duplex (TDD) techniques. It also supports both voice and data transmission using circuit-switched and data packet-switched, respectively. UMTS/WCDMA provides a theoretical peak data rate from 384 kbps to 2 Mbps [6]. The first release of the UMTS/WCDMA standard was 3GPP Release 99 [48]. Later, 3GPP adjusted its naming system, and Release 4 [49] came out with minor adjustments to Release 99.

Due to the proliferation of mobile devices in the mid-2000s, the capacity of UMTS/WCDMA became a bottleneck in the delivery of quality network connectivity with a high data rate. As a result, WCDMA upgraded to High Speed Packet Access (HSPA), improving the peak data rate through the new modulation scheme (64-QAM) and multiple carriers. HSPA consists of two separate improvements on download and upload speeds. The improvements are known as High Speed Downlink Packet Access (HSDPA) (in release 5 [40]) and High Speed Uplink Packet Access (HSUPA) (in release 6 [41]). HSDPA increases the peak download data rate up to 14.4 Mbps, while HSUPA increases the peak upload data rate to 5.4 Mbps [3]. Later, the evolution of Evolved High Speed Packet Access (HSPA+) (since Release 7 [50]) with higher-order modulation 64QAM (for download) and 16QAM (for upload) increase peak download and upload data rates to 42 Mbps and 11 Mbps, respectively. As a result, new services such as video streaming, web browsing with high speed, video conferencing, Internet Protocol Television (IPTV), and World Wide Wireless Web (WWWW) services become available.

User demand for higher data rates and quality of service are some of the main driving forces for the development of LTE technology, also known as 4G networks. The development of the LTE network started in early 2004. Its development targeted high user throughput, lower latency, high level of mobility, optimal power usage, and flexible frequency allocation (1.5 MHz to 20 MHz) compared with HSPA variants. The initial release of LTE (release

Table 2.1. Release and evolution of mobile technologies along with the peak download (DL) and upload (UL) data rates they support.

Generation	Requirement	3GPP				Year
		Release	Technology name	Peak data rate	Radio Access Network (RAN)	
2G	ETSI GSM standard	R97/R98/R99	GSM /GPRS	DL: 171 kbps UL: 14 kbps	GSM EDGE Radio Access Network (GERAN)	1997-1999
		R98-99	GSM/EDGE	DL: 384 kbps	GERAN	1997-1999
3G	ITU IMT-2000	R4 minor adjusted version of R99	UMTS/WCDMA	DL:384 kbps to 2Mbps	UMTS Terrestrial Radio Access Network (UTRAN)	1999
		R5	HSPA/HSDPA	DL:1.2 Mbps to 14.4 Mbps	UTRAN	2002
		R6	HSPA/HSUPA	UL: 5.4 Mbps	UTRAN	2005
		R7/8	HSPA/HSPA+	DL:21 Mbps to 42 Mbps UL:11 Mbps	UTRAN	2008
4G	ITU IMT-2000	R8/R9	LTE	DL: 150 Mbps - 300 Mbps UL:75 Mbps	Evolved Universal Terrestrial Access Network (E-UTRAN)	2008/2009
	ITU IMT Advanced	R10	LTE-Advanced	DL: 1 Gbps, UL: 0.5 Gbps	E-UTRAN	2010/11
5G	IMT-2020	R15	5G	DL: 1Gbps UL: 50Mbps	3GPP 5G New Radio (NR)	2016

8 [38]) has 300 Mbps and 75 Mbps in downlink and uplink, respectively [6]. Similarly, to fully address the requirements set by ITU and further improve LTE networks' capacity, LTE Advanced (LTE-A) has been developed since Release 10. LTE-A achieves peak data rates up to 1 Gbps and 500 Mbps in downlink and uplink, respectively [6]. The LTE network is a fully packet-switched and Internet Protocol (IP) based system with an increasing number of subscribers around the globe [51]. The ITU report shows that access to LTE network in 2015 for developing and developed countries are more than 53% and 88%, respectively [52].

The Fifth Generation (5G), which is the most recent network technology, is designed to have a peak data rate of 1 Gbps and 50Mbps for download and upload speeds, respectively [53, 54]. The first version of the 5G system was specified in Release 15. This specification presents the 5G Core (5GC) and 5G New Radio (NR) with 5G User Equipment (UE) [55]. The 5G has two deployment tracks, Non-standalone (NSA) and standalone (SA). In the NSA NR, 5G networks are supported by existing 4G infrastructures. The SA mode of 5G NR will use the new 3GPP 5GC architecture instead of relying on the existing 4G networks. Table 2.1 summarizes the release and evolution of mobile network technologies with the theoretical maximum speed they support.

2.2 Network measurement techniques and metrics

In today's mobile network, the type and number of provided services are ever-increasing. The number of users accessing the Internet over their mobile devices is also increasing. Ericsson's mobility report shows that the yearly global mobile broadband subscription number is still growing by more than 15% [51]. Ac-

According to the ITU report, global mobile-cellular subscriptions in developed and developing countries have continuously increased since 2005 [52].

The current mobile network is increasingly becoming composed of heterogeneous networks in terms of network elements. One reason for this is to address the increasing demand for mobile traffic data, reduce network cost, and improve service quality [23]. However, heterogeneous networks composed of multiple layers and radio technologies can create additional complexity, such as interference management on top of the existing mobile networks [56, 57]. Moreover, the increasing number of mobile users and the increasing traffic demand create a challenge to deliver a good quality of services to mobile users.

As the performance of a mobile network is a factor of multiple network features, so does user satisfaction and QoE. Analyzing the performance and capabilities of mobile networks provides input to network operators on how to improve the efficiency of the network with optimal cost. For instance, Mobile Network Operators (MNOs) can use the results of mobile network analysis to find the number of customers that can be served with better quality and to identify customers' demand for better data transfer rate per a given area and time. From the end user-side, service and application performance depends on various factors, including seamless mobility handling, latency, and available throughput (bit rate) [6].

Given the ongoing importance and the expected increase of mobile traffic, there is ample need to understand and characterize the performance of mobile networks and various mobile-based applications. Mobile network measurements help to understand, quantify, mitigate, and identify bottlenecks in mobile network performance. Performing network measurements and data analysis are also useful for studying end-users' actual data usage patterns and user experience. In addition, it can be used to model and predict network throughput, which could eventually help to improve network performance and end-user quality of experience.

Measurements of mobile networks have their own additional challenges compared to fixed-line network measurements. These challenges include frequent user mobility, environmental conditions such as weather and snow [27], connectivity, technology support, and lack of proper radio network coverage. In addition, most concepts widely studied and used in fixed-line networks are difficult to directly interpret, evaluate, and quantify in the context of mobile networks [58]. Studies also show that protocols (e.g., TCP) and applications initially designed for fixed-line network communication faces performance degradation in mobile networks [19, 59, 60]. For instance, Huang *et al.* [19] show that

TCP under-utilizes the available capacity of mobile networks. Mobile network measurements also implicitly consider the fixed-line network part, as content sent from mobile networks eventually passes through a fixed-line network infrastructure.

2.2.1 Network measurement approaches

Network measurements can be conducted in various ways from the vantage points of different network elements. How we measure the network and how we record different samples can be different too. For instance, measuring network speed (e.g., throughput) can be done either by reading multiple TCP flows at the same time in the network, by only using a single TCP stream [61], or by using multiple HTTP flows [62]. User Datagram Protocol (UDP) can also be used to measure throughput if the focus of measurement is not congestion control and reliability. However, throughput measurement over UDP can be subject to traffic throttling policies by operators [63]. In addition, there can be different places and vantage points to measure network performance. Measurement metrics can also be collected by reading data streams and traffic flows at different levels, such as at the interface, the IP, or the transport layer. Depending on where and how the measurement data is collected, the way we analyze and interpret the measurement dataset could also differ [64]. As a result, understanding the measurement and sample taking methods is essential for analyzing and interpreting the result correctly. Generally, there are three main types of Internet measurements - active, passive, and hybrid or fused [65].

1. **Passive measurement:** This is performed by silently observing the normal incoming and outgoing network traffic flows without imposing any synthetic traffic. This type of measurement is important for understanding traffic properties and users' data consumption patterns or behavior while accessing the network. Though passive measurement has an advantage as it does not impose additional traffic, it also has limitations. For instance, since traffic flows can only be observed, it is challenging to control and reproduce the generated traffic through passive monitoring. In addition, it also requires a large amount of storage space and data processing to store all the traffic [66].
2. **Active measurement:** This is performed by actively sending test data (from a file or randomly generated) to the target destination. Active traffic measurement needs the involvement of additional test data traffic on the regular network. Hence, the measurement results can be affected as imposing extra

traffic onto a network might bias the traffic behavior [67]. Active measurement provides the advantage of reproducing the desired scenario to be tested in a controlled environment. Hence, using active testing, it is possible, for instance, to verify whether certain quality agreements are met or not [68]. Active measurement tools for network performance include iPerf [69], Domain Information Groper (Dig), ping, and traceroute. iPerf is a speed test tool for TCP, UDP, and Stream Control Transmission Protocol (SCTP) protocols. Dig is a DNS query tool used to measure DNS query time by collecting data about DNS Servers. Similarly, ping and traceroute are the most common active measurement tools installed by default [70] with most OSs (Linux, macOS).

3. Hybrid measurement: This is a combination of passive and active measurement, where passively listing the traffic flow is combined with active testing. For instance, in a hybrid approach, a probe at a given vantage point might send test data towards the destination to measure the latency while passively listing the incoming and outgoing traffic flows. Hybrid measurement can be used to record new metrics derived from prior knowledge [71] or conduct measurement based on observed phenomena [72]. For instance, Allman *et al.* [72] proposed a reactive measurement framework that combines active and passive measurement techniques that helps to conduct additional measurements based on observed behavior.

2.2.2 Measurement metrics

One of the primary purposes of conducting Internet measurements is to measure the performance of the network and the application over fixed, mobile networks. While conducting measurements, different metrics relevant to the network performance need to be collected and stored for further analysis. Some of the commonly used metrics are:

Latency: In a communication network, latency can be defined as the waiting time until a given packet or group of packets sent from a source arrives at its destination. Latency can be expressed by measuring Round Trip Time (RTT) values. The RTT is the delay time measure for a packet to arrive at its destination and back to the source.

In mobile networks, different network components can be sources of latency. Some of the sources of latency include transport time of physical links, queuing and transmission time between the paths (e.g., at routers), processing time (e.g., request processing time at client-side and response processing time at the

server), and crossing traffics [65, 73].

Throughput: This can be defined as the rate at which the total amount of data transferred through the network per a given time. The transfer rate of the data through the network can be measured by counting the number of bits, bytes or packets transferred per second, expressed as bits per second (bps), bytes per second (Bps) or packets per second (pps), respectively. As the throughput can be processed and measured at different protocol layers such as IP [74], TCP [75], and Medium Access Control (MAC), etc., the value of throughput differs when it is measured at different layers of the protocols [76].

In mobile communication, the terms downlink and uplink are commonly used to refer to the direction of communication and data flow. The uplink communication process refers to when users are transmitting or sending data from their mobile device to the Internet through one of the base station towers. The uplink throughput or the uploading speed stands for the amount of data transferred from the mobile user's device to the destination (server). The downlink is the inverse of uplink communication. That is, data transmission from the Internet to user's mobile device. Downlink throughput or download speed is the rate at which data is transferred from source (e.g., Internet server) to the device of mobile user.

Goodput: It is the rate at which total amount of useful data (payload) is transferred over the network to the destination per a given time interval. Here, the amount of useful data (payloads) refers to the total amount of data transferred to its destination per given time, excluding the control messages, protocol overheads, and packets retransmitted or dropped due to corrupted data (e.g., due to Cyclic Redundancy Check (CRC) errors) [76].

DNS lookup time: Domain Name System (DNS) [77, 36, 78] is a hierarchical database system containing the IP address of the network elements and their human-readable format. The databases are distributed across the global DNS servers dedicated to resolving domain names and IP addresses. In most Internet communications, resolving the domain name by sending a DNS query to the DNS server is often the first step, especially for services that require name resolution such as web browsing.

DNS lookup time is the delay between sending a DNS query from the client until getting the response back from the DNS server. The DNS lookup time can differ significantly depending on the proximity of the DNS server from which the DNS response comes. Local DNS servers can keep a cache entry of DNS replies (both successful and unsuccessful replies) with associated time-to-live information for later use. A cached DNS response has a much faster DNS lookup

time than a non-cached DNS response [65].

TCP connect time: TCP [75] is one of the most widely used Internet protocol at the transport layer. It is commonly used for applications that require reliable data transmission, such as web browsing. Before the actual data exchange starts, the TCP connection establishment process has to be performed. For applications such as web browsing, the TCP connection establishment phase is executed immediately after the DNS lookup time. The TCP connect time is the processing time that it takes to establish the TCP connection. It is the delay measured between a client sending a SYNchronize (SYN) message request to the server to their receiving a SYNchronize-ACKnowledgment (SYN-ACK) message.

Transport Layer Security (TLS) handshake time: The TLS [79] handshake is the process it takes when the browser (client) and the server verifies each other for secure communication. TLS handshake could take two round trips (e.g., if the verification happens for the first time) or one round trip time (e.g., using TLS session resumptions [80]).

Packet loss: Packets might get dropped or lost in transit from source to destination. A packet loss can happen when it is dropped or rejected by a network component due to various reasons such as congestion, high latency, presence of jitter, bandwidth limitation, or a problem with the network connection [81]. Counting the number of packets lost during a given time interval is one measure of network performance. A congested network component (e.g., router) might start dropping packets when its egress link (output link) is busy. Packet loss measurement can be expressed either by counting the number or the percentage of packets lost during a specified time interval. It can also be expressed by calculating the loss rate of packets per given time. As a result, the packet loss rate can range from 0% when no single packet is lost to 100% when all packets in transit are lost before being delivered to their destination.

Quality of Experience (QoE) and Quality of Service (QoS): In communication networks, QoS is a measure of users' satisfaction level with a given service. As initially defined by ITU [82], the end-to-end QoS is a combined effect of both network-related performance such as throughput and non-network related performance such as service price and repair time. However, the evaluation of QoS mainly focuses on parameters of network-related performance, including latency, packet loss, and throughput [83].

Different QoS-based metrics such as packet delay, jitter, packet loss rates, latency, and throughput, indicate more about the impact of network performance on applications. These metrics do not directly reflect users' perceptions while using the applications; instead, they are mostly used to quantify the perfor-

mance of different services. As such, one can study how different values of the aforementioned metrics would impact the quality of various services such as video streaming and web browsing.

QoE has different definitions depending on the number of specifications. It is closely related to users' judgment and evaluation scores after accessing services and applications. The evaluation scores reflect how users experience a system when using a service. In other words, they measure the satisfaction or annoyance level of the users when accessing the service [84]. Broadly speaking, quality measurement methodologies can be both subjective and objective based approaches. The QoS assessment is mostly performed using objective metrics, whereas QoE measurement is predominantly subjective. Note that, there are also studies that propose to capture web QoE by approximating different objective based metrics such as ATF [85], Time for Full Visual Rendering (TFVR) [86], and Speed Index [87].

There are different approaches for measuring and inferring QoE using both subjective and objective assessment techniques [88, 89, 90]. The Mean Opinion Score (MOS) is the most commonly used method of measuring QoE subjectively. It is also part of the standardized ITU recommendation [91]. MOS scores are defined as a number ranging from 1 to 5, representing poor to excellent QoE, respectively.

Time To First Byte (TTFB): It refers to the time it takes for a user's browser to receive the first byte of page content from the server. TTFB represents the minimum delay the user will experience before the actual application starts rendering the requested content [92].

Above The Fold (ATF): This measures the time it takes to fully download and render all the objects within the browser's visible portion (viewport) [93].

Page Load Time (PLT): The PLT is a time between the initial request until the website has been fully loaded, i.e., until the onLoad event fires [94].

Different architectural or core network aspects can have implications on mobile network performance. As a result, in addition to the aforementioned metrics, other network characteristics such as the presence of TCP splitting proxies [95, 96], path inflation [97, 98], or DNS proxies [96], CDN caches and peering relationships [32, 99] can also have implications on the performance of a mobile network.

2.3 Measurement platforms

Different measurement platforms are designed to measure fixed-line and mobile networks. This section briefly describes some commonly known and used measurement platforms for fixed-line networks, followed by measurement platforms in mobile networks.

2.3.1 Platforms in fixed line networks

Several platforms are predominately designed to measure fixed-line networks or to provide infrastructure support for conducting internet measurement. Examples of these platforms include Samknows [100], Cooperative Association for Internet Data Analysis (CAIDA) [101], and Réseaux IP Européens Network Coordination Centre (RIPE NCC) [102]. Even though these platforms are not exclusively designed for measuring mobile networks, some of them, such as CAIDA, can also be used to capture different traffic coming from both fixed-line and mobile networks.

CAIDA: The measurement platform introduced by CAIDA is one of the measurement platforms and data archives for fixed-line networks [101]. It is a passive measurement software platform that monitors and analyzes traffic flows. The traffic flows are collected from high-speed backbone links, one from Equinix-San Jose and another from Equinix-Chicago. CAIDA releases the anonymized Internet passive traffic dataset for free. The dataset has been used to study the characteristics and performance of Internet traffic, including security analysis [103], distribution of applications, traffic volume, congestion [104], and duration. Other studies have also performed analyses on the topological and geographical distributions of different traffic [105] using the CAIDA measurement platform and datasets.

CAIDA Archipelago (Ark): This is another active measurement infrastructure introduced by CAIDA [106]. The measurement metrics are collected using IPv4 and IPv6 probes that are distributed in different geographical areas. Through the probes, it is possible to collect different network performance related metrics such as traceroute-based measurements, which are useful for Internet topology discovery. The dataset is freely available as open-source upon request. Gharaibeh *et al.* [107] use the CAIDA's Ark dataset to investigate whether geolocating routers is possible using geolocation databases. They show that infrastructure IP addresses of routers have inconsistent geolocation addresses.

SamKnows: This measurement platform is designed to perform active performance measurements on broadband networks by collecting different metrics

such as the DNS resolution time, throughput, latency, and packet loss [100]. It collects the measurements using measurement probes deployed across countries including different Internet Service Provider (ISP) networks and regulators. Research outputs using the SamKnows measurement platform and datasets include [108, 109, 110].

RIPE Atlas: RIPE NCC provides a platform that measures Internet connectivity and reachability using its measurement probes distributed across the globe [102]. RIPE Atlas probes are configurable measurement probes that can collect information including the RTT, current, and total uptime history. Using the measurement probes, one can send different queries and perform active measurements. The measurement queries include ping tests, DNS lookup, and traceroute towards different root or user-defined destination servers. Examples of the research outputs using the RIPE Atlas platform include [111, 112, 113].

In addition, globally distributed network research testbeds such as Open Observatory of Network Interference (OONI) [114], PlanetLab [115], Measurement Lab (M-Lab) [116] have been used for network infrastructure measurements and for deploying and evaluating network services. OONI is an open-source measurement platform for measuring network infrastructure and internet censorship. The datasets collected by OONI probes are freely available. PlanetLab constituted a group of servers hosted across several countries. Network researchers had used PlanetLab Internet development and research before it had officially shut down in May 2020. M-Lab is another open distributed server platform for researchers to measure the Internet. It hosts more than 500 servers strategically located around the globe. M-Lab servers are placed next to data centers or outside of access networks. This helps to measure the full route from user to content and to understand the last-mile user experience. M-Lab measurements are active measurements and datasets are open to access.

2.3.2 Platforms in mobile networks

Several measurement platforms have been used to measure mobile networks [117]. Mobile measurement platforms such as OpenSignal [117], Nettiutka [42], Ciqua [118], RTR-NetTest [119, 120], and Netradar [43], MobiPerf [121], Mobilyzer [122], Netalyzr [123, 124], and FCC Speed Test [125] are mostly crowdsourced tools. These tools are used to collect measurement data from end-user devices in mobile networks. Dedicated mobile network measurements platforms such as MONROE [44] and NorNet Edge (NNE) [126] are useful to conduct network measurements in a controlled environment. In this section, we

first briefly describe some of these measurement platforms in mobile networks. Later, we discuss the measurement platforms and the corresponding datasets that we have used for this thesis work.

MONROE: This is a large-scale, configurable, and open access Mobile Broadband (MBB) network performance measurement platform. The platform has measurement nodes distributed in different locations. The MONROE measurement nodes are deployed on public transport, residential homes, and offices in Norway, Italy, Spain, and Sweden. The nodes support more than one commercial level SIM-card based cellular connectivity and access to WiFi networks. The nodes enable experiments to run different measurement trials of different applications such as video streaming and browsing.

It is possible to conduct the measurement from both stationary (installed with the residential area) and mobile (installed on public trains and buses) measurement nodes. In addition to collecting measurement performance metrics such as throughput, latency, and DNS lookup time, it is also possible to collect contextual information about mobile networks. The contextual information includes the type of radio network (LTE, HSPA), GPS coordinates, information about the base station, and signal strength [127].

NorNet Edge (NNE): The NNE [126] is a dedicated measurement infrastructure in Norway that is designed to conduct network measurements of MBB networks. The measurement is performed using nodes distributed across different places (schools, long-distance trains, and offices) and server-side infrastructures. The nodes are small computers with a Linux distribution and are equipped with a modem capable of hosting up to four different radio networks with data subscriptions. These nodes are configurable for conducting different test metrics such as throughput, DNS lookup time, and latency [128]. In parallel to the test metrics, other meta-information about the network, such as radio network types, signal strength, and location, can also be inferred.

OpenSignal: OpenSignal [117] is a crowd-sourced network measurement platform available to be installed on iOS and Android devices. The platform has similarities with other measurement platforms such as SpeedChecker [129], Speedtest [62], and Nettitutka [42]. It also has a web-based measurement interface so that users can actively trigger the measurement from their computer (desktop, laptop) and get information about the network, such as download/upload speed and latency. It provides both speed measurements (by downloading a file (~108Mb) from a Content Delivery Network (CDN) distributed in different locations) and other detailed meta-information about the network, including signal strength, user location, and end-users' device features.

Table 2.2. Summary of measurement datasets used in this thesis.

Tools	Time period	Geography	# of records	Measurement type	Publication
Netradar	One month (Jul., 2018)	FI, UK, DE, JP, BR, IN	340M, 113M	Hybrid (Crowd-sourced)	IV, V
MONROE	Two weeks (May 19-26 & Jul. 2-9, 2018)	SE, NR	18K	Active (Dedicated)	III
RTR-NetTest & Nettitutka	Six months (Jun - Nov. 2017)	FI	43K & 10K	Active (Crowd-sourced)	VII
Ciqua	One month (Oct., 2016)	FI	14M	Hybrid (Crowd-sourced)	II
Nettitutka	One year (2015)	FI	768K	Active (Crowd-sourced)	I, VI*

*Nettitutka and other tools used in 2017 while driving a car in DE for >354 km.

2.3.3 Tools and datasets

This section explains the five mobile measurement tools that we used in this thesis in more detail. We describe the measurement methodology along with descriptions of the metrics that have been collected during the measurements. Table 2.2 shows the summary of measurement datasets used in this thesis.

(i) Nettitutka

This dataset is used for mobile network link stability prediction and analysis (Publication I), for correlation based feature mapping (Publication VII), and for GPS location error analysis (Publication VIII).

Measurement setup: Nettitutka [42] (previously also known as Netradar) is a crowd-sourced mobile measurement platform that measures and collects metrics related to cellular network performance across mobile users' devices. It has been running actively worldwide since March 2013. The Nettitutka mobile measurement platform works based on a client-server architecture. The server to which it connects is hosted in Amazon Cloud and distributed globally, so clients' devices can be anywhere in the world. The platform mainly focuses on measurements of different bitrate values (over TCP), latency (over UDP), and context information related to each measurement, such as signal strength and network technology type.

Measurement metrics: The Nettitutka measurement platform collects different active-based measurement metrics and context or meta-information about the network during a 10-second session. It performs an active test to measure the throughput (uplink and downlink speed over TCP) and the latency (over UDP). Each measurement session also records detailed information about download and upload bytes sampled at 50-millisecond intervals. The information recorded during each session includes signal strength, OS information (OS version, OS

type), device model and vendor information, and radio technology types (e.g., LTE, HSPA+, and UMTS network). It also records Global Positioning System (GPS) based location (latitude and longitude), user mobility speed, and base station information (e.g., Cell ID (CID) and Location Area Code (LAC)).

(ii) Ciqua

One of the datasets that we used in our study for Publication II is collected by a carriers' mobile network measurement platform based in Finland. It is a mobile application for iOS and Android installed on subscribers' mobile devices [118] that conducts measurement tests on DNS lookup, TCP connection establishment, and connectivity tests using ping.

Measurement setup: The tests are active measurements; each measurement test is executed inside a session. A session starts when a network interface that provides access to the Internet is available, and there is no interface claiming to yield a default route. The session ends in situations when the interface that was providing the default route to the Internet becomes unavailable, or the client loses the assigned IP endpoint. Sessions are not periodic, but they are repeated when network conditions change. That is, when multiple interfaces claim to provide a default route to the Internet and the 'best interface' changes, the current session is terminated, and a new session starts.

Measurement metrics: There are three active measurement tests performed, with different metric values collected under each test. 1) *DNS Lookup time:* This test measures the time it takes to look up a Fully Qualified Domain Name (FQDN) from a DNS server and resolve it into an IPv4 address. The test allows one to specify a set of DNS servers and target DNS names. The DNS servers can either be statically configured or automatically assigned by the DHCP server. In this work, we measure the DNS lookup time of four popular websites over UDP: `www.google.fi`, `www.youtube.com`, `www.facebook.com`, and `www.elisa.net`, as most of them are commonly known. Note that, as shown by Bajpai *et al.* [130], `www.google.*` websites are served by the same CDN and therefore exhibit similar latency behavior. In light of this, we use `www.google.fi` for our measurement study. 2) *TCP connect time:* This test measures the time it takes to establish a TCP connection (over IPv4) to a target website (over port 80) from the client device. The test starts when the client sends a SYN packet to a destination identified by a FQDN. It then subtracts this time value from the time of receiving a SYN+ACK packet from the server. Note that, the TCP connect time does not include the DNS resolution time. 3) *RTT and packet loss:* This test uses the ping measurement tool to measure the RTT and packet loss

towards `www.google.fi` using Internet Control Message Protocol (ICMP) [37] echo request packets. Each ping test sends an average of five to nine ICMP echo requests from clients to the target. The payload for each ICMP echo request is configured to be 16 bytes in size.

(iii) **RTR-NetTest**

This measurement dataset RTR-NetTest, in combination with the Nettitutka dataset, was used for Publication VII.

Measurement setup: The RTR NetTest [119, 120] is a mobile application that collects information from end users with open dataset access. It is available for Android and iOS devices. The web browser version is also used to conduct the measurement from desktop and mobile devices where their operating system is different from iOS and Android.

Measurement metrics: The platform records features including the downlink and uplink throughput, signal strength, Key Performance Indicator (KPI) values of the mobile network such as Reference Signal Received Power (RSRP) and Reference Signal Received Quality (RSRQ) for LTE, connection error and IP packet loss, ping based latency, testing time, IP address, and hostname of the computer. RTR NetTest provides more than 60 network-related features. In this thesis, we only focus on metrics collected under LTE networks. These are the TCP-based downlink and uplink throughput, TCP-based ping latency test, LTE RSRQ, and LTE RSRP.

(iv) **Netradar**

The dataset collected through the Netradar measurement [43] was used for Publication IV and Publication V. In these publications, we study data usage behavior and patterns of mobile users across countries.

(i) *Measurement setup:* The measurement app passively listens to the incoming and outgoing traffic flow without generating any additional traffic for measurement. The app is a crowd-based application that is freely available to install on Android devices. It is a session-based traffic flow measurement method based on a client application installed at end users' mobile devices. The measurement session starts whenever there is active traffic flow in either an incoming or outgoing direction. The session stops when no active traffic flow is observed in both the uplink and downlink direction for about two seconds. The threshold for starting the session is 100 Kbps and 200 Kbps for uplink and downlink

direction, respectively. The duration of the session can be from milliseconds to minutes long. Sessions that have very few bytes transferred are not recorded. The application does not have any visibility on the content.

(ii) *Measurement metrics*: Each measurement session consists of several pieces of meta-information. This information includes device information (model and vendor names of the device) and information about the subscriber's MNO, location, and user mobility speed. It also contains information about network type (WiFi or cellular) and accessed radio technologies (2G, 3G, 4G) with detailed radio QoS values and signal strength. The constrained and unconstrained speeds for both download and upload speeds with respective session length is also recorded. Note that, constrained speed reflects the maximum speed offered by the network to the user. Constrained speed is the network maximum speed recorded when the network was a limiting factor. It is inferred based on the queuing delay of packets, the available bandwidth, and the latency information. The constrained speed is not recorded when there is no latency information or users never hit the network maximum speed. Unconstrained speed reflects the speed that the user needs from the network to use mobile apps on his/her device suitably. This is the maximum speed recorded during the session when the network speed did not limit users. Furthermore, every session also contains the average download and upload speeds, total upload (bytes), total download (bytes), latency, battery level, and information about the base station (e.g., CID, and LAC). The sessions have associated tile information (e.g., tile-ID, country, city, population density, postal code), where the tile-ID is the area coverage of 100 by 100 map square meters.

(v) **Web Latency And Rendering (WebLAR)**

The WebLAR measurement and the corresponding dataset has been used for Publication III – where we study QoE by conducting measurements on different websites in mobile networks.

(i) *Measurement setup*: WebLAR [131] is a tool that measures end-users web QoE over operational MNOs. It quantifies web QoE by approximating the ATF time of a website. The ATF time is a measure of the required time to load the visible portion of the web content that is displayed at first glance without scrolling the web page [85]

The QoE metric (i.e., ATF time) is measured using two ATF time approximating approaches: pixel-wise comparison (ATF_p), and browser heuristic (ATF_b). The (ATF_p) approach calculates the ATF time using pixel-wise comparison [132].

This has three major steps. First, it records a video of browsing sessions in pre-defined screen sizes. Second, it converts the recorded video into bitmap images at every 100 ms intervals using FFmpeg [133] tools. Finally, it compares the pixel difference between consecutive images using ImageMagick [134]. The ATF_p time is the calculated value where there is no more pixel difference between X successive images. Here, X is the value for different thresholds in seconds (tested with 3, 10, and 14 seconds thresholds). The thresholds are the time used to determine whether or not a given webpage has loaded and stabilized. ATF_b approximates the ATF times using the Google Chrome browser API [135]. Calculating the ATF_b is a heuristic-based approach, in which values are calculated by integrating the downloading time of website elements (e.g., HTML, CSS, and java-script files) and images that are displayed in the above the fold area.

(i) *Measurement metrics:* Using WebLAR, different metrics related to QoE and web latency are recorded. These include PLT, the ATF time, TCP connect time, and DNS lookup time. It is also possible to capture information about operational networks such as radio network technology type, signal strength, and GPS coordinates. Information about the device (MONROE measurement node) such as CPU and memory usage during measurement can also be recorded.

2.3.4 Challenges and limitations of crowdsourcing data

Crowdsourced measurements provide several advantages. Some of the advantages include representing realistic network performance and user experience, capturing user mobility and ubiquitous scenarios [136], capturing diverse environments in terms of end-user devices, geographical coverage, and MNO.

However, it also comes with challenges and limitations. Some of the challenges and limitations of crowdsourcing-based measurements are the inability to access low-level device and radio information as it requires root access to the device and the challenge of gathering longitudinal and representative data from several users, device type and locations [68].

2.3.5 Ethical considerations

The measurement and data collection follows strict adherence with user privacy defined by Aalto University and retains an anonymized dataset. In all of the datasets we have accessed, there is no personal data collected during network measurement. The study reports only aggregated values, and the analysis does not reveal individual users.

2.4 Related work

The performance of mobile networks is a factor of multiple non-network and network-related features. Some of these features include user mobility, congestion, frequency of packet loss, interference, radio network types and their coverage, network throughput and latency, device specifications, protocols, and application types.

There are different approaches for measuring, analyzing, and modeling the performance of mobile networks and user QoE. Generally, we can categorize them into five groups – mainly based on how the measurement datasets are collected and how the metric trials are conducted. These approaches are: (i) based on measurements data collected from MNOs core-network [20, 137, 92, 138]; (ii) using datasets collected through a dedicated measurement infrastructure [139, 137]; (iii) studying measurement data collected from end-users' devices through crowd-sourced platforms [43, 61, 121, 140]; (iv) using data collected by simulation tools [6, 141]; and (v) studies based on data collected from field tests [142, 143].

The aforementioned measurement approaches have their own pros and cons. For instance, network performance analysis based on a dataset collected from an MNOs' core network has an advantage as it is possible to capture the detailed, fine-grained traffic flows of individual customers. Such datasets can be used to study customers' data usage patterns or to investigate the presence of congestion and the traffic loads in a carrier's base station. However, getting access and collecting data inside an MNOs' core-network is not easily possible for researchers outside the organization. In addition, the analysis results and the measurement data are mostly limited to a single MNO's network infrastructure and customer base.

Similarly, measurement testbeds, simulation tools, and dedicated measurement infrastructure are good for running multiple measurements under a controlled environment. However, these approaches are mostly limited to a particular environment and small numbers of measurement nodes. Crowd-based measurement data are useful for getting the actual perceived end-user experience. However, it has its challenges as it takes time to reach a large number of users in order to collect enough measurement records [88].

These days, MNOs are also moving towards user-centric service performance indicators in order to assess and verify the quality of their network performance [88]. Similarly, 3GPP has defined accessibility, mobility, service availability, integrity, and retainability as service performance indicators. These performance indicators are used to quantify the quality of different services

focusing on end-users [144].

Network measurements and datasets collected from the crowd in combination with geographical data can be used to predict KPI values such as RSRP with a minimal error value, as shown in [145]. As smartphones and other hand-held devices becoming ubiquitous, collecting data from the crowd using end-users' device is relatively cheaper than installing separate measurement platforms [117]. Furthermore, data collected from the end-users device enable to cover more data points, irrespective of which MNO a customer has subscribed to. In this way, the ability to maintain the data collection from a customer even if he/she switches MNO is higher.

In this thesis, we use different datasets that have been collected from end-users' devices through crowd-based measurement platforms. Most of the datasets have been collected over the years. Using these datasets, we study and analyze various factors affecting mobile network performance; we build performance prediction and classification models; we also investigate the data usage patterns of mobile users across countries. In the subsequent chapters, we present the results of these studies and concepts.

There have already been various studies on mobile network performance. These studies have investigated and analyzed the performance of mobile networks by considering different features. Before moving to the subsequent chapters of the thesis, the following subsections present some of the related studies – focusing on mobile network performance analysis.

2.4.1 Mobility related measurements and analysis

Mobile network technologies are designed to provide seamless data communication. Nowadays, it is becoming common for mobile users to access the Internet in most of their day-to-day mobility scenarios, such as while commuting on trains and driving on highways. However, user mobility could create a challenge in delivering seamless network performance, especially for users traveling at high speed. As indicated in the 3GPP specification [146], the LTE network performance worsens and is not guaranteed as user mobility speed surpasses 350 km/h.

Previous studies have investigated TCP-level performance in mobile networks such as connection establishment, packet loss, and re-transmission on high-speed rails' [25, 26, 147, 148, 149]. Most of these studies assert that TCP cannot adapt well (e.g., to frequent handovers) in a high-speed mobility situation in both 3G [147] and 4G [149] networks, which could cause poor network performance.

Li *et al.* [147] use a dataset collected from a single operator to investigate

TCP performance over HSPA+ networks. They show that network performance degrades during high-speed mobility scenarios as TCP fails to adapt very well to high-speed mobility. A related study by Li *et al.* [149] considers different TCP operations, such as TCP connection establishment, packet loss, different TCP congestion and flow control mechanisms, and packet transmission and re-transmission. They show that the presence of high-speed mobility decreases the throughput value but increases latency (RTT) and packet loss rates. Wang *et al.* [26] study the performance of TCP over the LTE network by conducting both active and passive measurements on high-speed rail (> 300 km/h) in China. The authors examine the performance of two TCP variants – TCP CUBIC [150] and BBR [151]. They show that, on high-speed railways, BBR has a lower RTT than CUBIC but no significant difference in terms of throughput performance. The authors also indicate that the performance of TCP on high-speed rails is affected due to a miscommunication with the lower-layer protocols such that TCP is unaware of the presence of frequent handovers. Similarly, Atxutegi *et al.* [148, 152] focused on five TCP variants to study how the protocols utilize the radio resources at different mobility speed scenarios. They show that loss-based TCP variants such, as CUBIC and NewReno [153], have better throughput performance and resource utilization during mobility than other delay-based TCP congestion control protocols such as Westwood+ [154].

The presence of frequent packet loss can affect the performance of mobile networks. Baltrunas *et al.* [155] studied packet loss behavior in MBB. The authors use a dataset collected through NorNet Edge (NNE) measurement infrastructure from six measurement nodes placed in an intercity train in Norway. They find that the magnitude of packet loss for a mobility scenario is higher than stationary cases. The authors found that, in most cases, packet loss is associated with Radio Access Technology (RAT). They suggested the relevance of having a well-planned Radio Access Network (RAN).

The quality of video and voice calls has also been studied under different mobility scenarios. Li *et al.* [156] study the performance of Skype voice and video calls over LTE networks in high speed mobility (> 280 km/h) environments. The authors show that the quality of Skype calls significantly degrades on high-speed mobility. One reason for this is that Skype is not easily adaptable to different network conditions and poorly utilizes the available bandwidth. Another related study by Wuttidittachotti *et al.* [157] measures the quality of Voice over IP (VoIP) under mobility scenarios in LTE networks. They found that call drop rates increase when multiple handovers are observed.

Other studies have also investigated the effect of different network features on

mobile network performance under high mobility scenarios. For instance, Merz *et al.* [158] conducted measurements focusing on physical-layer characteristics of the UE, such as its spectral efficiency, physical layer resource utilization, and the Reference Signal Signal to Noise Ratio (RSSNR) value over an LTE network in an intercity train. The authors show that LTE performance is robust for mobility speeds of up to 200 km/h. They also point out that strong Signal to Noise Ratio (SNR) coverage plays a significant role in good network performance.

2.4.2 Latency and packet loss

The latency of cellular networks is not easily predictable as it can range from a few milliseconds to several seconds, especially during high mobility scenarios [128]. Larson *et al.* [128] apply the ‘triangle events’ approach to investigate the cause of excessive packet delay in mobile networks using a dataset collected through an NNE measurement platform. They measure the latency value by sending UDP datagrams (of 20-byte) from measurement nodes to a dedicated echo server. They found that a long delay value of RTT and consecutive packet loss are strongly correlated with the presence of frequent handovers, radio state changes, and re-transmissions at different layers. Similarly, Baltrunas *et al.* [159] investigate the characteristics of packet loss on a UMTS network based on a dataset collected through active measurement. They showed that most of the packet loss occurred during state transitions in Radio Resource Control (RRC).

Web proxies could be deployed between client and server for different purposes, such as for performance enhancement and access control [160]. Xu *et al.* [161] studied the performance impact and behavior of web proxies that are deployed by carrier networks on mobile users. The authors developed a controlled experimental testbed and captured detailed TCP-level network information for different websites. They showed that web proxies are essential in most scenarios as object caching and redirecting traffic based on proxy’s DNS resolution can enhance network performance. Vallina-Rodriguez *et al.* [95] investigate the impact of in-path proxies using the Netalyzer tool [123]. The authors analyzed HTTP and DNS proxies on mobile networks. They showed that proxy misconfiguration could cause users to have poor service quality and network performance or even potentially could lead to privacy leaks.

2.4.3 Throughput and network performance

Throughput and bandwidth are fundamental features of mobile networks, primarily to satisfy end users' traffic demand. The development of radio network technologies with higher channel bandwidth improves mobile networks' throughput capacity and the overall transmission bandwidth. These days, the downlink throughput of recent radio technologies such as LTE has a theoretical speed that reaches up to 1 Gbps. However, as various high data-traffic demanding services such as real-time video games, high-quality video streaming, and virtual reality are introduced, the demand for high throughput is also growing.

Several previous studies have also focused on characterizing mobile networks' throughput (e.g., download/upload values). These studies conduct measurements from different vantage points such as from end users' devices using crowdsourcing [61, 42, 42, 162, 163, 164, 35]. Most of the aforementioned studies have analyzed the throughput of mobile networks by considering different factors, such as RSRP, RSRQ, RSRQ, Received Signal Strength Indicator (RSSI), Signal-to-Interference-plus-Noise Ratio (SINR), RSSNR, latency, radio technology, location, and downlink and uplink data rates. In this part, we review previous related research results focusing on throughput performance in mobile networks.

Sonntag *et al.* [61, 42] use the Netradar measurement data collected from the crowd over 3G networks. They study the correlation of signal strength with TCP goodput and bandwidth and show that signal strength alone is not a sufficient indicator of cellular network performance. Nikraves *et al.* [35], analyze network performance variability across carriers and locations using performance metrics such as latency, DNS lookup time, and throughput. The authors use measurement data collected through two similar mobile measurement applications - Speedometer¹ and Mobiperf. They show that significant network performance variation across mobile network operators exists, partly due to variance in location and temporal patterns.

Cainey *et al.* [165] focus on modeling the download throughput of LTE networks using measurement data collected from Android devices through the OpenSignal [166] measurement platform. They observe that mobile network operators, LTE signal metrics (such as RSRP, RSRQ, RSSNR), and time of day play an essential role in throughput performance. They also suggest that considering a model that can combine RSRP, RSRQ, and RSSNR could better predict the throughput; however, they did not provide the exact formula.

¹available at <https://storage.cloud.google.com/speedometer>

Throughput while driving a vehicle: As we have discussed in previous sections, mobility could affect the performance of mobile networks. Previous studies [34, 162, 167] investigate throughput and other factors by conducting measurements while driving a vehicle.

Akselrod *et al.* [162] conducted measurements over LTE networks while driving. The authors study how download speed and network availability are affected by parameters such as channel bandwidth and signal quality. They show that bandwidth and signal quality, as they are strongly related to the vehicle's position, have a significant influence on download speed. Huang *et al.* [167] study the impact of mobility speed on LTE networks focusing on downlink and uplink speed, RTT, and time-of-day as network performance metrics. The authors use a dataset collected from Android devices through 4GTest [121]. They show that LTE network throughput outperforms other 3G networks. They also point out that the performance variation of the LTE network remains stable under different user mobility scenarios in the areas they conducted the measurements.

Energy consumption: Characterizing the energy consumption level of different network activities [168] is essential for various reasons. For instance, Balasubramanian *et al.* [169] show that prefetching documents can reduce energy utilization of web searching and browsing applications by decreasing data transfers. The battery power of smartphones could be one factor that affects throughput in cellular networks [170]. Studies have also shown that unplanned use of available network resources has a significant impact on energy consumption by mobile devices' [19]. Tuan *et al.* [171] propose a tool that identifies apps with high energy consumption on Android phones through a testbed measurement. They show that network type, transfer packet size, and link quality impact the battery consumption of smartphones. Similarly, Huang *et al.* [167] characterize the power consumption of the LTE network by comparing it with 3G and WiFi networks. The authors show that the energy consumption of the LTE network is more efficient compared with 3G and WiFi networks.

Network reliability: Baltrunas *et al.* [139] use data collected through NNE measurement infrastructure. The authors investigate the reliability of the 3G network in terms of packet loss and network availability across different MNOs in Norway. The results show that more than 20% of connections from stationary nodes are unavailable for more than 10 minutes per day. The authors identify that network reliability suffers due to poor radio conditions (e.g., lack of dedicated radio resources), connection loss, and network configuration. Similarly, Baltrunas *et al.* [155] also investigate the causes of packet loss in the MBB network under mobility conditions. They show that handover between radio

technologies and network coverage gap is the main reason for packet loss under mobility.

Predicting performance and throughput: There are studies focusing on mobile network performance and throughput prediction [172, 173, 174, 175, 176]. Zou *et al.* [173] showed that it is possible to get accurate throughput predictions (up to 98% accuracy) for short periods by observing network performance on a stationary client device. Michelinakis *et al.* [174] proposed a measurement-based technique that can be used to run on mobile phones as a basis for advanced resource optimization algorithms. A recent study by Elsherbiny *et al.* [176] used an LTE network dataset collected from public transit. The authors showed that network throughput prediction using the random forest algorithm has the highest prediction accuracy than the time series forecasting method.

2.4.4 Quality of experience in mobile networks

Mobile users are concerned about network quality [177]. As a result, Internet service and content providers are always seeking to understand and improve end users' Internet access service quality. Efforts are made to improve web browsing performance, e.g., by reducing PLT, TTFB, SpeedIndex (SI), and other QoE metrics. Some of the efforts include Facebook Instant Articles [178], Opera Mini [179], and Google AMP [180], which are tools designed to enhance the QoE of users in mobile networks.

Several previous studies investigate the effects of different network parameters on end user experience while accessing various applications such as streaming video content [181, 182, 183, 184] and browsing websites [140]. Balachandran *et al.* [140] use measurement data collected from an MNO's core network. The authors investigate how different networking parameters such as handover, throughput, and the number of computing users impact the web browsing experience of mobile users. They show that the QoE of mobile users can be characterized and predicted using a limited set of information about radio networks.

Jun *et al.* [30] measure web QoE metrics to investigate the impact of Google AMP in mobile networks. They show that browsing AMP pages on mobile devices improve the value of SpeedIndex (SI) by 60% on average compared with non-AMP pages. Dasari *et al.* [29] investigate the impact of mobile device computing power and specification on the QoE of different applications. They show that low-end device models affect the quality of web browsing more than they affect video applications. The authors reason that the variation comes from how the application is optimized to use the available resource of the device such that, on multi-core devices, video applications apply more parallelism than web

browsing.

The QoE of voice and video-based services has been studied by Wuttidittachotti *et al.* [157]. The authors study the quality of Skype and Line in both 3G and 4G in different user mobility scenarios. They show that VoIP quality over 3G and 4G networks do not differ significantly for users at a stationary position, while in the mobility case, 4G provides better VoIP quality than 3G networks.

Several studies have been carried out on modeling and predicting QoE from measurements in mobile networks [185, 186, 187]. Casas *et al.* [186] use a combination of device-based passive network measurements in parallel with mobile users' experience feedback to predict the QoE over 2G and 3G networks. The authors propose applying an unsupervised machine learning model to predict the QoE of mobile users with a success rate of more than 90%. Similarly, Boz *et al.* [187] propose a model for predicting the QoE of mobile users based on measurement data collected through the Nettiutka measurement platform over LTE and WiFi networks. The authors show that both network (e.g., throughput and latency) and non-network related features (e.g., device model) play a significant role in predicting the QoE of mobile users in the field.

2.4.5 User behavior and data usage patterns

Understanding mobile users' data usage behavior and traffic consumption patterns is becoming a significant research topic. This is because it can be used to manage network resources and traffic demands properly.

Several studies such as [188], [189], and [190] investigate human mobility patterns and behavior in mobile networks. They show that user mobility has patterns in terms of visited location and time. Yang *et al.* [191] characterize user behavior in terms of mobility, users' data, and application usage pattern based on the data collected from a core network of 2G and 3G in China. Similarly, authors in [192] study the pattern of mobility and temporal activity, as well as how the radio resources are utilized by different applications, using data collected at the core of a 3G network. The authors show that traffic distribution per subscriber is uneven, such that 90% of traffic loads in the 3G networks are generated by 10% of the subscribers. Another work by Oliveira *et al.* [193] studied and characterized mobile users' data usage behavior based on data collected from 3G networks in Mexico. The authors profile mobile users into three classes (Light, Medium, and Heavy users) using the number of sessions, traffic volume, and inter-arrival time as metrics. A recent paper by Lutu *et al.* [194] studies the effects of the COVID-19 emergency on UK MNO to quantify cellular users' mobility, network usage, and performance. Their analysis shows

a decrease in traffic volume and active users in densely populated urban areas compared to rural areas. The decline in traffic volume (uplink and downlink) could attribute to the lockdown as several business and commercial areas in the urban areas have been closed.

As discussed, the evolution of mobile radio technologies has brought improvements such as increasing the throughput rate. However, as witnessed in recent years, there has been growth in mobile devices, applications, and mobile data traffic flow. This leaves room for improvement on the current mobile networks, including an efficient mechanism to decrease the rapid growth of energy consumption by smartphones and network devices [167, 195, 171]. There is also a need for infrastructure and configuration support for emerging technologies such as for Teleoperated and autonomous driving [196, 197].

2.5 Summary

This chapter provided background and motivation for mobile network measurement, metrics quantification, performance analysis, and data usage patterns. Since the introduction of mobile networks, there has been an overwhelming growth in the number of users, traffic demands, and the need to access various services over mobile devices. Since mobile devices are ubiquitous and technologies are improving over time, accessing the Internet over these devices has become part of our daily life. Mobile networks involve large and complex parameter spaces including packet loss, jitter, latency, location, mobility, and user satisfaction. As a result, there is a need to understand and characterize mobile networks. This is important in order to provide quality services and to utilize limited network resources properly. However, enhancing user experience by improving network performance has been a critical research challenge.

In this chapter, we discussed characteristics of mobile networks that make them different from fixed-line networks, including mobility, the presence of frequent handover, and interference. The nature of mobile networks creates an additional challenge that we cannot solve using regular fixed-line based network performance analysis. For this, the research community has proposed different mobile network measurement platforms that help collect network measurement metrics from different vantage points. As a result, several previous research studies have also played their role in improving mobile network performance.

Previous research studies have analyzed and characterized network performance from different angles. Some of them considered the performance of protocols at different protocol layers. Others concentrated on network conges-

tion, energy consumption, mobility, temporal dynamics, and spatial analysis.

Despite several studies on mobile network measurement and performance analysis, there are still gaps in adequately understanding and characterizing mobile network performance in a way that reflects end users' perceived network performance and data usage patterns. Crowd-based data measurement and analysis is one good way to get the actual network performance as experienced by mobile users, as the metrics are collected from the end users' devices. One of the challenges of network performance analysis from the crowd is the lack of enough measurement data. This thesis addresses this gap by using datasets collected from a large crowd of mobile users. Most of the datasets have been collected over several years from various locations.

The subsequent Chapters present the main finding and studies we performed on mobile network performance, including the data set we used, methodology, and results. We started from an understanding of network factors that affect throughput and latency performance, all the way to modeling data usage patterns of mobile users in mobile networks. We characterize mobile network performance by considering different factors, including network throughput, latency, location and time of a day, device model, packet loss, and radio technology types. We also characterize the link performance of the mobile network and model a classifier. Then, we study the data usage patterns of mobile users and cluster them. A discussion and study of the challenges and opportunities of mobile network measurement are also presented.

3. Network throughput and stability

In this chapter, we investigate mobile network performance, focusing on network throughput. This Chapter is based on Publication I. The first part examines key characteristics of cellular networks related to throughput from the perspective of mobile user activity, MNO, smartphone models, link stability, location and time of day. We perform a network-wide correlation and statistical analysis to obtain a basic understanding of the influence of individual factors. The second part uses a machine learning approach to classify the stability of cellular network based on the data reception characteristics of the user.

3.1 Network throughput

Throughput is one important aspect of mobile network performance. Throughput is affected by multiple factors including radio technology type, user mobility, location, antenna design, device position, form factor, and transmission bandwidth. For instance, from the base station side, the performance of radio technologies is one determinant factor in defining how different applications have to perform, and what applications can be used [6]. From end-users perspective, the device type and its processing power could be another critical factor, especially for accessing web-based applications over mobile networks [167].

There have been improvements made on network bandwidth capacity through different evolutions and releases of radio technologies for mobile networks. For instance, the introduction of LTE-Advanced radio technology boosted the target downlink rate upto 100 Mbps and 1 Gbps for high and low-speed mobility, respectively [6]. In addition, the ubiquitousness of hand-held devices supporting advanced radio technologies has played a significant role in increasing the number of users accessing the Internet from mobile devices. Due to the growing demand for mobile data traffic and an increasing number of mobile users, the overall throughput value, when observed by end-users, has decreased over

Figure 3.1. Distribution of downlink in 4G network technology over the years in Finland. Data taken from Nettitutka [61] mobile measurement platform.

the years. Figure 3.1 shows the download trend over time in Finland per network operator over 4G networks. For instance, DNA network operator has a median download speed of 37.7 Mbps and 32.9 Mbps for the first quarter of 2015 and 2018, respectively. This particular example shows a 12.7% decrease in throughput values. Similarly, we observe a decrease in throughput in the other network operators, though the marginal difference might vary.

Therefore, analyzing network throughput and link-level performance of different radio technologies is essential. It helps to investigate factors affecting their performance, including user mobility, device model type, location, time of day, and transmission bandwidth. This chapter illustrates the throughput performance of mobile networks and factors affecting it, especially from the end-users perspective. It also investigates network stability by considering link-level sudden network disruptions.

3.2 Methodology and dataset

As part of our methodology, first, we get a baseline understanding of network features by performing a network-wide correlation and statistical analysis. We cover the impact of radio technologies, device model, location, and time of day for network throughput. Then we develop a machine learning based model that predicts the expected average TCP throughput based on the bit rate values collected during the first five seconds. Second, we investigate the reasons for network instability in mobile networks and build a classification model using minimal cellular network metrics. We apply a random forest algorithm from the R package [198] for classification and regression modeling. For classification, we apply 10-fold cross-validation with class resampling, which helps to avoid over-fitting and unnecessary class imbalance during training the model [199].

Table 3.1. Measurement Distribution per radio Technology for each MNO in Finland

Network Operator	Total # Of Measurements	LTE	HSPA	HSPA+	HSDPA	UMTS	Others
Elisa	373K	45.75%	8.49 %	14.70%	1.12%	25.43%	5%
DNA	235K	63.30%	7.52%	8.17%	10.69%	0.9%	9.42%
TeliaSonera	140K	34.74%	1.04%	14.27%	1.29%	33.60%	15.06%

As described in Chapter 2, we used a dataset collected through Nettiutka [61] – a measurement platform for crowdsourcing information about cellular network performance from mobile devices. In this study, our goal is to study the characteristics of the network when the user is not moving during a ten second measurement session. Therefore, we focus on stationary nodes to minimize the variability that might arise from mobility when we analyze link stability. A node is considered stationary if the user’s moving speed is zero, as inferred from their GPS information. As the accuracy of user movement speed improves over time we took the last record of the ten-second sessions to determine whether a node was moving or not. We further limited the measurement data to the three Finnish mobile network operators, covering one year (2015). Thereby, we could minimize the potential impact of diverse network infrastructures across countries. The resulting data set has a total of about 750K measurements, with more than 13K unique installation IDs (i.e., individual user devices), as shown in Table 3.1.

Our measurement data was collected from mobile users in Finland. As such, some of the results, such as the impact of MNOs on throughput, are more dependent on location, data subscription-price strategy, and the network infrastructure during the measurement period. Moreover, some mobile devices, such as those using Apple iOS, have restrictions on inferring information about the accessed radio technology from a device’s OS. As a result, the impact of mobile device models per radio technology does not take iOS device models into account.

Limitations on the measurement dataset: If the device’s network interface is in a low power state, it needs to be promoted to an intermediary or a dedicated power state before communicating with an online server. The promotion time adds latency, especially for 3G standards [31, 200]. Our result analysis on UMTS does not explicitly analyze this as it is not possible to monitor the state of power-state transition with ordinary mobile apps.

3.3 Network throughput

As described in previous sections, the network throughput is a vital measure of mobile network performance. In this section, we present a study of different features, including radio technology, device model, time, and location, that could impact network throughput in mobile networks.

3.3.1 Radio technology and device model

Improvements in radio technologies provide better throughput in mobile networks. As can be seen in Figure 3.2, the LTE network outperforms all other radio technologies measured. Other recent radio technologies such as HSPA+ and HSPA also have better throughput than the earliest radio technologies.

In mobile networks, as users are moving from place to place, they may access different radio technologies at different times of the day. MNOs also benefit from managing their resources based on the presence of mobile users and traffic demand per given location and time. Resources such as energy can be saved by switching off some base stations with few users. To do that, MNOs might run scheduling algorithms based on the time of the day and the number of users in a specific area.

We study the trend and effect of switching radio technologies per MNO and time of day. We observe that the number of switches from legacy to more advanced technology (e.g., UMTS to HSDPA) increases during peak hours. For instance, observing TeliaSonera subscribers, we note that most HSPA+ network measurements start appearing at 10:00 and increase almost monotonically until 20:00. The actual reason remained open but could be answered with additional datasets from the respective MNO's. A possible reason for such behavior could be that MNOs might schedule base station operations based on traffic demand for optimal resource management. For instance, most mobile users might have left city areas during nighttime to go home (e.g., to suburban areas). As a result, turning off some of the base stations might optimize resource management [201].

These days, a wide variety of mobile devices are available in the market. The difference in chipset design, memory capacity, processor power (number of cores, clock rate), graphics chips, screen resolution, etc., could influence the performance of applications running on the user device. As a result, recent device models may bring network performance improvements to the end user. A previous study shows that the performance of web-based applications could be determined by the processing power of end-user devices [29]. We investigate whether mobile device models impact throughput performance. For that, we

Figure 3.2. TCP download speed of different device models per network technology. Except for the HSPA network, the release year of the device models does not correlate with TCP download speed. (Reproduced from Publication I).

used the year of release and extracted the top device models, for which we collected enough measurement samples per radio technology.

We examine the extent to which new device models improved the performance of TCP downlink speed. Figure 3.2 shows the global TCP download speed distribution of the device models, aggregated per radio technology type, used during the measurement. The figure shows no apparent direct relationship between the year of release and TCP download speed for most of the radio technologies, except for HSPA. We further investigate by limiting the dataset to the same brand (e.g., Samsung) and radio technology type (e.g., LTE). We observe that it is not always the newest device model whose TCP download performance is best, even for the same brand. In some cases, we notice that older device models have better downlink speed than the most recent ones.

3.3.2 Mobile network operator and subscribers' locations

The availability of a quality network and its coverage significantly impact network performance and user satisfaction. Based on their customer base and marketing strategy, different MNOs might place different emphasis on network provisioning and network infrastructure investment in different locations. As a result, the throughput to which subscribers have access might vary based on geographical location and MNOs.

First, let us investigate whether there was a difference in throughput value among MNOs when subscribers accessed the same radio technology types. Figure 3.3 shows the CDF of TCP download and upload rates for LTE. We observe that the LTE network of DNA outperforms the other two MNOs in upload speed. There is also a considerable difference in download speed among MNOs, e.g., the median speed of DNA is 13% and 8% faster than TeliaSonera and Elisa, respectively. We applied the Anova [202] procedure to observe TCP uploading

Figure 3.3. The average downlink (left) and uplink(right) speeds of the three different MNO's in LTE networks. There is a clear difference between upload and download distributions (>1K users in each MNO). (Reproduced from Publication I).

and downloading variance in each operator per radio technology; we filtered equal sample size from each carrier for every radio technology. The Anova result shows that the overall p-value is very small, which allows us to reject the null hypothesis. We observe that not all carriers have identical mean uploading speeds for LTE. The p-value of LTE uploading speed shows that the mobile network operator is of significance for network performance variation. To observe the uploading speed difference across operators, we further analyze the data using a pairwise t-test. The result shows that the difference in means was not significant between Elisa and TeliaSonera (p-value = 1), but both were significantly different from DNA's uploading speed (p-values of $1.6e-05$ and $1.8e-05$, respectively). Hence, we can conclude that the mean uploading speed of LTE was significantly different for DNA. Tukey's [203] multiple comparison tests confirmed that the Elisa-DNA and TeliaSonera-DNA differences are significant (p-values of $1.56e-5$ and $1.81e-5$, respectively), while the TeliaSonera-Elisa difference was not (p-value = $9.994570e-1$). These results suggest that there is an apparent network throughput difference between MNOs. The difference is visible even under similar radio technology types, as the level of support for networks with better infrastructure could vary per MNO across locations.

Figure 3.4. The average TCP throughput distribution of three MNO in Finland by area using LTE networks: Elisa (left), DNA (middle), TeliaSonera (right). The comparison across MNOs shows a higher variation in throughput per location. Note the different scales on the three plots. (Reproduced from Publication I).

3.3.3 Subscribers' locations and time of day

The throughput available to subscribers is impacted by the time of the day and the whereabouts of mobile users. Areas that have better infrastructure provisioning, such as higher base station density (within a short distance of the users), combined with sufficient (core) network capacity, might provide better throughput. We study throughput distribution across different geographical areas for three MNOs in Finland.

The result shows that there is a high variation in throughput by MNO for different locations under LTE networks. In the Uusimaa region (which includes the capital city Helsinki), DNA has the highest median throughput (28.31 Mbps), compared to Elisa and TeliaSonera (21.28 and 19.6 Mbps, respectively). In other areas, such as Pirkanmaa (Tampere), Elisa and TeliaSonera show 12.5% and 8,4 % median throughput improvement over DNA, respectively. We observe such variations in other areas, too. These observations suggest that MNO may provide some locations with better technology and infrastructure based on their subscriber base.

Similarly, we investigate the impact of location and time of day on cellular network performance. For this analysis, we restrict the dataset to measurements collected for three major provinces in Finland: *Uusimaa*, *Pirkanmaa*, and *Pohjois-Pohjanmaa*, which cover central southern Finland (Helsinki, Espoo, and Vantaa), the Tampere sub-region, and central northern Finland, respectively. Each province has more than 94K, 45K, and 24K LTE based measurements, respectively. We observe that the median download speed varies in all areas for the TeliaSonera network, irrespective of the time of the day. Users living in the densest metropolitan area, i.e., the Uusimaa region, and subscribed to DNA or Elisa gets a better download speed than users living in the other two areas. This is likely due to better infrastructure provisioning: higher base station density (within a short distance of the users), combined with sufficient (core) network capacity.

DNA exhibits more stable throughput throughout the day than the other two operators in all of the areas. The download speed decreases starting from 10:00 in the morning in both TeliaSonera and Elisa networks in all three states. The difference between daytime and nighttime for the Elisa network is about 9% in the Uusimaa area. One possible reason for throughput variation between MNO per time of day could be related to the presence of network congestion or to resource management. For instance, based on users' presence in a given area and the traffic demand over the day (including peak and off-peak hours),

operators can switch some base stations off or on to save energy.

3.3.4 Predicting network throughput

An accurate prediction of bit rates is important for different applications. For instance, it can be applied to anticipate the future data rate when using video streaming and thus adapt the streaming quality accordingly. A previous study based on bit rate estimations also demonstrated that an accurate prediction could improve video performance in cellular networks [173].

We trained a model that can predict the average TCP throughput based on the throughput of the first five seconds (mainly in the TCP slow-start phase). For training the model, first, we prepared the dataset. The dataset was split into two, a training dataset (75%) and a validation (testing) data set (25%), using the Caret package [204]. After experimenting with the three different learning algorithms, we found that a random forest with bootstrap aggregation and bagging produces a better prediction, with an accuracy of 90% and an error rate of 10.2%, on the testing dataset. The classification models were trained using the aforementioned network features. The random forest implementation offers some flexibility for improving classification accuracy by combining different sets of classifiers into ensembles. We trained a random forest using a tree size of 5K and by randomly sampling nine variables at each split.

Specifically, we wanted to study how to predict the overall mean bit rate only using the first five seconds of TCP bit rate measurement. We applied the R caret package [204] to train the model. After trying different models, including tree-based, GBM, and bootstrapping, we found that the random forest is (again) the best predictor model. We tested the training model with different variable numbers sampled as candidates at each split point of the random forest trees. It turns out that mtry of 67 is the best predictor model for the mean bit rate with Root Mean Square Error (RMSE) of 0.003 Mbps and $R^2 = 98\%$. The mtry stands for the number of variables randomly sampled as candidates at each tree split. The model is cross-validated with both testing and validating datasets. This was important because we managed to predict the user throughput, using only the download rates of the first five seconds (which would be easily available in practice right after startup). We also observe that a relationship exists between the amount of battery level in the smartphone and the average download rate for an LTE network. Throughput prediction models such as this one could be applied in different areas, such as adjusting the video's streaming quality based on location and quality of the near future throughput value.

3.4 Network stability

The stability of a given network link can be defined as the probability of having persistent connections over a given time interval. We define the stability of a network in terms of the period of time t during which a given measurement session yields receive bit rates of zero in a row. We call this sequence of zero bit rate duration a *sudden dropout*. The longer the *sudden dropout* duration is, the more unstable the network is. The Nettitutka measurement server tests the download speed by sending random data over TCP for 10 seconds. During the measurement session, both the client and the server record the number of bytes transferred every 50 ms.

Different real-time and multimedia applications such as VoIP, online gaming and video-on-Demand (VoD), among others, are very sensitive to bandwidth and latency variation, often entailing strict requirements on throughput. For instance, [205] states that, for proper voice comprehension in VoIP calls, the end-to-end delay should be within 150 – 300 ms. Another previous study [206] on web application response time showed that users feel the delay when the response time is more than 100 ms. Based on these previous studies, we use the 200 ms threshold for analyzing *sudden dropout* analysis. *Sudden dropouts* obviously affect instant throughput, but they will also affect latency (if packets are queued in the network during a dropout) or lead to losses (if they aren't) – the latter of which may cause repair actions at the transport layer, which again turns into delay. In the Nettitutka dataset, we have observed network fluctuations and instability that could potentially affect user experience (e.g., delay in response time) when using delay-sensitive applications.

We take our observation from Nettitutka measurement data and results from previous work as motivation, and study how many of the Nettitutka measurements in our dataset exhibit zero bit rate transmission for at least 200 ms. We choose 200 ms heuristically, also taking into account suggestions from previous work. Since the number of bytes downloaded is recorded at every 50 ms, a zero bit rate transmission for 200 ms means that at least 4 samples were missed or not received by the client. We understand that 200 ms might be relatively small to cause a major performance degradation for many applications. Later on, we will analyze and determine what *sudden dropout* duration would have a major impact on throughput.

Figure 3.5 shows the average of the first 3 bit rate samples before and after the *sudden dropout*. The average throughput of the three samples received after *sudden dropout* is consistently lower than before the *sudden dropout*. This shows

Figure 3.5. Average of the first 3 bit rates samples before and after a *sudden dropout*. (Reproduced from Publication I.)

that the effect of *sudden dropout* is reflected even after the *sudden dropout* (zero bit rate) is over, which may be a result of TCP recovery mechanisms.

3.4.1 Received data per recording interval

We now study the distribution (the variation) of the number of bytes received every 50 ms (on average) within the 10 seconds of the measurement session. For this, we first classify the data into two groups, dropped and non-dropped. The former refers to measurement sessions that experience a sudden dropout for more than 200 ms, the latter refers to sessions without this phenomenon. Then, we compute the number of bytes received every 50 ms. Again, to avoid the effect of the TCP slow start, only the last 5 seconds of the measurement are considered. Figure 3.6 shows that the mean, mode, and median of dropped measurements diverge with a relatively higher standard deviation than the non-dropped measurements. This indicates that more network inconsistency and interruption are present in the dropped measurements than in the non-dropped ones, which increases the likelihood of application disruptions.

3.4.2 Sudden dropout by network technology

We observe that *sudden dropouts* happen mostly in UMTS and HSPA networks, especially during daytime from 11:00 to 19:00 hours, as shown in figure 3.7. The distributions of *sudden dropout* per geographical area are almost similar except for a few island areas that experience more sudden dropouts than the metropolitan region. We observe that the Southwest Finland (Varsinais-Suomi) area and metropolitan (Uusimaa) areas have a median of 0.2 s and 0.15 s *sudden dropout* duration with LTE networks, respectively. Note that both areas have almost the same number of measurements.

Figure 3.6. Bytes downloaded during each 50 ms sample time span. (Reproduced from Publication I.)

Figure 3.7. Sudden dropout occurrences per network technology over time of a day. (Reproduced from Publication I.)

3.4.3 Feature selection and classification model

As we discussed in previous sections, cellular network performance depends on a number of factors. Most of these factors – or features – are (at least partly) related to each other. The relations among these features may not be of simply a linear nature. Therefore, determining the major cause for the effect

Figure 3.8. Importance of network features used for the classification model without using TCP throughput. (Reproduced from Publication I.)

of a *sudden dropout* is non-trivial. In order to address these challenges, we use machine learning to identify the important network features that indicate (upcoming) network interruption. The machine learning approach is also useful for understanding the interdependence of various network features. These identified network features can then be used to build a classification algorithm.

At first, we seek to predict the probability of network stability through classification. We pre-processed the dataset by classifying it into two categories based on the sudden bit rate dropout duration. The two categories are classified in a similar way to the approach we used in section 3.4.1. Measurements that experienced a continuous zero bit rate transmission for at least 200 ms or more in a row were classified as dropped, and the others as non-dropped.

To train the classification model, we split the data into a training dataset (75%) and a validation (testing) data set (25%) using [204]. After experimenting with the three different learning algorithms, we find that a random forest with bootstrap aggregation and bagging produces better prediction, with an accuracy of 90% and an error rate of 10.2% on the testing dataset. These classification models are trained using the network features shown in Figure 3.8. Since throughput directly influences the sudden dropout duration, using throughput as a predictor variable would create a bias. Hence, we trained our model without using the throughput features. The random forest implementation provides some flexibility for improving classification accuracy by combining different sets of classifiers into ensembles. We trained the random forest model using a

tree size of 5K and randomly sampled nine variables at each split. Figure 3.8 shows the ranking of important features. Features such as latency(UDP), signal strength, type of MNO, and time of day played a significant role in classifying the stability of TCP throughput in a cellular network.

3.5 Summary

The application performance for the end user depends on various factors, including the available bit rate, transmission bandwidth, users device model, the infrastructure of MNO, radio technology type, seamless mobility support, and latency. Understanding and predicting the stability of the network is essential. We build a model that helps to classify TCP throughput stability based on *sudden dropouts* only using device model, location, network technology type, time of the day, and latency. This allows inferring network stability using the “minimal information” (e.g., without measuring download and upload rates), which in turn reduces measurement overhead. We also show that it is possible to predict the average TCP throughput based on the first five seconds, which mostly consists of the TCP slow start phases. These types of models are useful for anticipating (near) future performance and for adjusting application demands (e.g., streaming quality).

4. Web latency and quality of experience

This chapter focuses on studying latency of web-flows and user Quality of Experience (QoE) in mobile networks. It is based on Publications II and III and has two main parts. The first part discusses the latency of short web-flows and factors affecting its performance. In this part, we discuss factors affecting web-flow performance by conducting a measurement on TCP connection establishment time, DNS resolution time, and ICMP Ping test. We investigate how different metrics vary across websites, including distribution of packet loss and DNS query failures, as well as the impact of cache entries on both DNS lookup and TCP connect time. We use a real-world crowdsourced measurement dataset collected from end-users mobile devices. In the second part, we discuss web browsing and QoE measurements in mobile networks using a dataset collected through the MONROE measurement platform.

4.1 Performance of web-flows

Latency plays a significant role in the overall mobile network performance and user QoE. The presence of long delay causes performance degradation in cellular networks [207, 208, 209]. Since the early ages of mobile networks, efforts have been made to minimize the latency [210]. Figure 4.1 shows the distribution of UDP based latency measurement values for mobile users in Finland over the years. The measurement is collected from end-users' devices using the Nettiutka mobile network measurement platform. The figure shows that the perceived latency distribution from the end-user devices has a small improvement over the years, despite advancements in radio technologies. This indicates that challenges still need to be explored and studied to understand different factors affecting the latency in mobile networks.

As we discussed in Chapter II, latency can increase at different layers of network protocol stacks. Some of the sources of the latency can be DNS resolution,

TCP connection establishment, load on the server, request and response process on the network components, communication medium, and process required for encryption and decryption. Longer latency in mobile networks is also rooted with legacy infrastructures [128].

TCP and UDP are the two dominant transport layer Internet protocols. Previous studies show that the majority of Internet traffic flows are created using TCP at the transport layer [211, 212]. Most of the TCP sessions generated from web requests consist of short-lived traffic flows [152]. A study by Huang *et al.* [19] also shows that short-lived TCP flows are significant parts of mobile traffic.

Figure 4.1. Distribution of 4G network latency (over UDP) in Finland over the years. Data from Nettitutka measurement.

The latency overheads (e.g., DNS lookup, TCP connection establishment, and HTTP request times) usually incur before any actual data exchange happens. Poor web-browsing quality and high network latency are largely attributed to long DNS lookup [213] and TCP connect times as also reported by content providers [214] and ISPs [215]. However, there have been few studies [216, 217] that quantify the factors that are responsible for higher DNS lookup and TCP connect times. This is mostly due to the lack of datasets with rich metadata information (such as the radio technology type, signal strength, information about mobile device, and carrier network) that can help to identify those factors for mobile users in a cellular network.

Table 4.1. DNS, TCP and ping measurements by website.

Website	DNS (#)	TCP (#)	Ping (#)
www.facebook.com	3,471,440	4,572,298	-
www.google.fi	6,981,348	4,855,516	2,180,700
www.youtube.com	1,628,991	4,075,477	-
www.elisa.net	1,821,334	5,335,350	-

4.1.1 Methodology and dataset

We use a set of measurement datasets collected from end-users mobile devices. The measurement values are collected by conducting a DNS lookup, TCP connection establishment, and ICMP Ping tests towards four websites from end-user devices. These three tests are used to measure the latency of the DNS query response, the time it takes to establish TCP connection, and the packet loss distribution, respectively. The measurement platform and the corresponding metrics that we have used for this part of the study are described in Section 2.3.3.

The datasets are collected from about 25K subscribers of a cellular network provider based in Finland. The dataset consists of about 14M, 19M, 2M records of DNS lookup time, TCP connect time, and Ping test measurements, respectively. The datasets have been collected for one month – October 2016. Table 4.1 provides details of the samples collected towards each target website. Using this dataset, we also study failures in DNS lookup time, packet loss, the impact of cache entries on both DNS resolution and TCP connection establishment. In addition, we investigate latency based performance differences on web-flows by comparing different radio technologies in cellular networks.

Note that, the dataset consists of mobile users based in Finland and that have been using IPv4 [74]. The only measured services are those that were running on port 80 and port 52, for web browsing and DNS resolution, respectively. As such, this study does not cover performance differences that may come using IPv6 [218] and other services running on different port numbers. The tested websites are the most commonly used ones (except `www.elisa.net`) following the Alexa [219] website ranking. Studies show that the three websites (`www.facebook.com`, `www.google.fi`, and `www.youtube.com`) generate considerable network traffic in mobile networks [220]. As such, these websites have a high probability of reflecting the mobile users' experience of web services in terms of the aforementioned metrics. For packet loss analysis, we have used the ping measurements conducted towards `www.google.fi`. As a result, there is a chance that the observation we made on packet loss might vary when it is measured from different client-base and locations towards different websites or services. For instance, operators might completely block or put a rate limitation on the ICMP packet request, which can increase the packet loss rate.

Limitations on the measurement dataset: The measurement data consist of four commonly used websites (except `www.elisa.net`) following the Alexa [219] website ranking. This constitutes a high proportion of mobile traffic volume [220], users only based in Finland, and services that were running on port 80. The

ping measurements are conducted only towards `www.google.fi`. As such, it is not known whether and how the observations would differ from a different client base per country and towards different websites or a different service on the Internet. In addition, the presence of in-path proxies could impact network performance metrics. We have limited visibility on the traffic path between the client and the target end host. Thus, there will be a limitation on our analysis regarding the impact of the middlebox (proxies) for TCP connect time performance.

4.1.2 DNS look-ups and failures

As we have seen in Chapter II, the majority of DNS query-response traffic is sent over the unreliable transport protocol UDP. If the query-response packets are lost in the network or if the DNS server is not responding, the measurement test will time out. The client-side of the Ciqua measurement platform does not retry for failed or timed-out DNS requests. We use the DNS response code to determine the number of successful DNS responses and failures [221]. A DNS query failure can occur due to various reasons including, packet loss and DNS miss-configuration [222, 223, 224].

First, let us study the distribution of DNS lookup failure per radio technologies. We observe that DNS lookup over LTE experiences about 1.9% of DNS failures, while over UMTS, HSPA, and HSPA+ experience 3.4%, 3.9%, and 2.7% DNS failures, respectively. Table 4.2 shows the distribution of DNS lookup failures per website. There is a 2% DNS lookup failure variation between `www.youtube.com` and `www.google.fi` domain names.

Table 4.2. DNS Failures per website using the LTE network.

Website	Failures (%)
<code>www.facebook.com</code>	2.16
<code>www.google.fi</code>	0.96
<code>www.youtube.com</code>	2.99
<code>www.elisa.net</code>	2.74

We investigate the distribution of DNS lookup errors and their probable causes in mobile networks. We observe that about 86% of the DNS failures (which is about 2% from the total DNS lookup tests) are BADSIG or BADVERS [225] (Bad OPT Version or TSIG Signature fails). BADVERS error arises when the DNS server fails to implement the version level of the requester.

The second most frequent DNS failure code observed is YXRRSet [226], which means that a set of resource records exists when it should not. Some other

Figure 4.2. Percentage packets loss across the number of packets sent. Figure from Publication II.

DNS failures, such as BADTIME [227] (out of time windows) and BADMODE [228] (Bad TKEY Mode), are also rarely observed. We noticed that out of all the DNS failures observed, about 67% of the DNS lookup queries were sent towards the AS790 (Elisa mobile operator) DNS resolver. Most of the error codes indicate that most DNS query failures are caused by DNS miss-configuration, including version mismatch between the DNS server and the requester [224]. This type of DNS lookup failure could impact the browsing experience of the mobile user, for instance, when users are requesting censored websites [229].

4.1.3 Packet loss

As mentioned in the previous sections, packets can be lost in transit or rejected by a network element due to different reasons such as presence of congestion, high latency, and network connectivity problems. In mobile networks, due to the mobility scenario, the probability of losing a packet is comparatively higher than in fixed-line networks. Lack of adequate network coverage and frequent handovers are other major causes of packet loss, especially under the mobility scenario [155].

We study packet loss in mobile networks using the data collected through ICMP Ping test towards `www.google.fi` from end-user devices. Before discussing the packet loss, let us observe the distribution of latency (ICMP) per radio technology. The LTE networks have shorter latency than the other radio technology types. From all samples of ping tests recorded as minimum, average, and maximum RTT values, the LTE networks have a median of 27, 38, 51

ms, respectively. We observe that 90% of the average ping test measurements towards `www.google.fi` using LTE has an RTT time of less than 100 ms. In comparison, other legacy 3G technologies are quite slow, with more than 200 ms RTT. Depending on the underlying protocol, higher latency could potentially lead to packet loss.

The Ping test is conducted using the standard ICMP Echo Request for latency and packet loss measurements. Packet loss is calculated from the number of Echo Requests (number of packets sent) and Echo Responses (number of packets received) using the ping test measurement. A packet loss happens if the number of received packets is less than the number of packets sent. This could happen if packets are lost, e.g., during a power state transition of the mobile device from low to high power state (see a limitation on the dataset) [159] or due to a considerable round trip time. Figure 4.2 shows the percentage of packets loss across the number of packets sent at each instance of the ping test. We observe that most packet loss happens if the number of packets sent at every ping test instance exceeds five Echo Requests. The majority of ping tests (about 80%) were conducted by sending five echo requests. Out of these, only 0.33% of the ping tests have lost at least one packet. When we consider ping tests that were conducted by sending seven echo requests, about 19% of them have lost at least one packet. This shows that a packet loss analysis based on the ping test has to consider increasing the number of packets per ping test instance to get a representative result.

4.1.4 Radio technology type

There are different radio technologies such as LTE, HSPA+, HSPA, and UMTS comes with various range of bandwidth performance. Most of today's mobile devices are equipped with all of these radio technology types. We study how DNS lookup and TCP connect time vary across different radio technologies.

As we discussed previously, one of the key performance metrics in communication networks is packet data latency. Mobile network vendors, operators, and end-users are constantly in demand for shorter packet data latency. Improvements in recent radio technologies can minimize packet transmission latency. Figure 4.3 shows that the resolution time of DNS lookup varies between different radio technologies. There is a faster DNS resolution time for recent network technologies such as LTE and HSPA+. However, we observed a considerably long resolution time for anterior technologies such as HSPA and UMTS. The DNS resolutions over the LTE network have faster resolution time on all of the four tested websites. For instance, the median difference between LTE and UMTS

Figure 4.3. DNS response times by radio technology: LTE exhibits significantly lower latency. Figure from Publication II.

Figure 4.4. TCP connect time towards www.youtube.com and www.google.fi by radio technology. The distribution exhibits similar pattern for www.elisa.net and www.facebook.com, too. Figure from Publication II.

network to resolve `www.google.fi` domain name is 370 ms.

TCP incrementally increases the number of segments in flight to fully utilize the communication medium's throughput capacity. The incremental policy is based on the Acknowledgment (ACK) it received after one round trip time. Improving the latency can reduce TCP based data transaction time, bringing shorter data upload and download completion time. Figure 4.4 shows TCP connect times towards `www.youtube.com` and `www.google.fi` websites using different radio technologies. Here also we observe that LTE outperforms all other radio technology types. For instance, the median TCP connect time of `www.youtube.com` under LTE and Legacy technology is 50 ms and 251 ms, respectively. Thus, LTE reduces the TCP connect latency by 80%.

4.1.5 Cache entries

The presence of web proxies in mobile networks can improve network performance in most scenarios [161]. Network operators may deploy proxy servers between the client and the target destination server [123] for better network traffic management and performance optimization. Using the RIPE [230] service, we map the resolved IP address of the websites to an ASN value. We observe that a proxy or a cache server between the client and the true destination host server may acknowledge the TCP socket request first [231, 232]. This has the advantage of decreasing TCP connection time in the order of milliseconds.

Previous studies have shown that caching improves the time to fetch small files [233]. We compare how TCP connect time towards a given website varies by the ASN value under the same radio technology. We observe that clients served by the ISP network have a shorter TCP connection time. For instance, for `www.youtube.com`, we observe that the presence of proxies closer to the subscriber reduces the end-to-end latency by more than 20% compared to the requests sent to YouTube-owned web servers. On the contrary, all TCP connection requests sent to `www.facebook.com` were served by a single Facebook-owned ASN without hitting any cache entries in the ISP network. As a result, the TCP connect time towards `www.facebook.com` is substantially slower than towards `www.youtube.com` and `www.google.fi`.

$$\Delta t(ct) = isp(ct) - cdn(ct) \quad (4.1)$$

We use Equation 4.1 to calculate the TCP connect time difference between an ISP cache and CDN. For this, we created a pair of CDN and ISP per user within a one-hour time frame. First, we grouped the dataset by the user, ASN, and one-hour window. If a given user has more than one measurement in a combination, we take the mean value. Then, we keep the ones that have pairs (in this case, Google and Elisa). Figure 4.5 shows the distribution of the difference in TCP connect times between two destinations, where values on the negative scale indicate that the ISP cache is faster than the other. We observe that about 70% of TCP connect time towards `www.google.fi` achieve lower latency when they hit ISP cache. This is because the proxy installed between the client and the true destination server for improving performance or for traffic controlling [234], may acknowledge the TCP request before passing it to the destination server [235].

Similarly, the latency of DNS resolution can vary depending on the proximity to the client and the number of name servers the DNS resolver has to query [214]. We study the DNS lookup time of different DNS resolvers per website address.

Figure 4.5. TCP connect time towards `www.google.fi` showing the latency difference between ISP cache - Elisa (AS719) and CDN - Google (AS15169) using LTE network. Delta is the TCP connect time difference between Elisa and Google when the same user is getting a reply from the two networks within a one hour time window. Figure from Publication II.

The result shows that some of the cellular network DNS resolvers have a faster DNS lookup time for `www.google.fi` than Google DNS servers. We also notice that there is a significant variation between DNS resolvers belonging to the same ISP. For instance, two DNS resolvers inside AS790, "EUNET.FI" of two different IP entries 195.74.0.47 & 195.197.54.100, have 133 ms and 51 ms (median) time to resolve `www.google.fi` using the LTE network. This variation can happen due to the closer proximity of the DNS resolver to the ISP network [236] and due to IP address mapping inconsistency between client and resolver [217]. We also observe that some of the ISP resolvers we have studied have a longer latency than Google-owned resolvers. This result is consistent with a previous study [223] where they show that latency of DNS resolution does not always depend on aggressive DNS caching.

4.2 Web browsing QoE in mobile network

As we discussed previously, QoE of web browsing (web QoE) can be affected by various factors. Web QoE can vary due to the underlying protocol type (e.g., browsing over TCP or over UDP of QUIC), time taken for DNS resolution, and TCP connection establishment time. Other factors such as website complexity, content type (text, video, and image), the process for encrypting and decrypting contents (e.g., browsing over HyperText Transfer Protocol (HTTP) and HyperText Transfer Protocol Secure (HTTPS)), the type of browser, and the presence of congestion at the server can influence the web browsing experience of mobile users. Most of the factors mentioned above can be a reason for additional latency in one way or another.

Table 4.3. QoE measurement towards websites.

Websites	Number of measurements
www.microsoft.com	3021
www.reddit.com	2246
www.youtube.com	1044
www.facebook.com ¹	1176
www.bbc.com	2929
https://news.google.com	3315
https://en.wikipedia.org ²	3096
https://www.yahoo.com/	1437

4.2.1 Methodology and dataset

As discussed in Chapter II, we use the WebLAR tool to measure web QoE in cellular networks. The test is performed by browsing different websites from the MONROE measurement nodes. While browsing websites, the QoE metrics are conducted using both pixel-wise comparison and browser’s heuristic based approaches. The experiment was running for two weeks (May 19–26, 2018 and July 2–9, 2018) in 128 MONROE nodes located in Norway and Sweden. The nodes were equipped with one or two SIM cards with 4G connectivity. Nine of the nodes deployed in Norway were connected with a Swedish operator roaming [29] in Norway. Our measurement campaign covered a total of six operators. During the campaign, nodes were set to fetch specific pages of eight popular websites. The WebLAR experiment is executed every six hours. Table 4.3 shows the number of measurements per website. The measurement data had a total of ~18K data points. Next, we present some of the factors that affect web QoE in the mobile network using this measurement dataset.

4.2.2 Web latency and QoE

First, let us observe the distribution of TCP connect time and DNS lookup time per MNOs. This helps to compare the latency distribution of TCP connect time and DNS lookup time in different geographical locations and MNO. Figure 4.6 (a) shows the latency of the websites under different MNOs. Note, the Norwegian and Swedish operators are labeled with NO_o and SE_o, respectively, where $o \in \{1, 2, 3\}$. The result shows the MNOs have different performances in terms of DNS lookup time (ranges from 35ms to 60ms, in the median case) and TCP connect time (ranges from 100ms to 200ms, in the median). One of the causes for

the variation in the DNS lookup time across the acpMNO could be the presence of cached DNS entries, as discussed in the previous sections.

As discussed in Chapter II, PLT and ATF metrics help to measure web browsing QoE. We developed two different approaches to measure these metrics. We observe that PLT and ATF time does not significantly differ across operators for most of the websites. Figure 4.6 (b) shows the distribution of the ATF time towards websites across different MNOs as approximated using the two approaches. Figure 4.6 (b, top) shows the approximated ATF_b time. The long tails of the distribution in this result is due to Facebook and BBC, which have a higher number of objects and overlapping images in the above-the-fold area. Figure 4.6 (b, bottom 3) shows the ATF_p with three, ten, and 14 seconds threshold, respectively. From the result, we can see that in the median case, the ATF_b is shorter than the ATF_p time with three seconds threshold. This indicates that three seconds is a sufficient threshold to declare whether the website has stabilized or not.

Figure 4.6. The distribution of (a) DNS lookup time, TCP connect time, TTFB, and PLT and (b) ATF time as approximated using the two approaches. Figure from Publication III.

The ATF time of browsing websites varies by network operators. Figure 4.7 (1) also shows that the ATF time of BBC, Yahoo and Wikipedia exhibits a bimodal distribution. We investigated this aspect further by observing the ATF time of these websites from different operators. For instance, Figure 4.7 (2) shows the distribution of the ATF time of Yahoo across the different MNOs approximated using the two approaches. The result reveals that in the Norwegian MNOs, Yahoo takes longer to show the contents in the above-the-fold area. As such, the bimodal distribution of ATF time is due to the difference observed in the operators across different countries. The impact of the longer download time of the objects in the above-the-fold area is reflected in the ATF_p time of the websites. For the other two websites, we see a difference across the operators. That is, the bimodal distribution happens in all operators.

Figure 4.7. (1)The CDF of the PLT and the ATF time of the different websites. (2) The ATF time of Yahoo across different MNOs. Figure from Publication III.

When approximating the ATF time of web browsing, the design of the website should be taken into account. We analyzed the rendering performance of each website. Figure 4.7 shows the distribution of the ATF time approximated using the two approaches and the PLT of the websites. Through manual inspection, we observed that some of the websites, e.g., Microsoft, have fewer objects and take a shorter time to show the contents of the above-the-fold area. The ATF approximation using both approaches confirms this. On the contrary, websites like Facebook have multiple objects located in the above-the-fold area (confirmed through manual inspection). The objects may overlap where some of the objects may not be visible in the front unless the user takes further action (e.g., clicking the sliding button). In such cases, the browser heuristic based ATF time approximation overestimates the ATF time. Hence, the ATF time approximation based on the browser heuristic does not better represent the end-user experience for these kinds of websites. That is, the missing or delay in the download of those overlapped objects does not affect the visual change of the websites. As a result, the pixel-wise comparison approach is a better estimator for websites with overlapping objects in the above-the-fold area. However, we also noticed that the pixel-wise comparison approach has a drawback of overestimating the ATF time of websites with animating contents.

User mobility has minimal impact on the ATF time of the websites that we have measured. However, we observe that the ATF time of some websites has longer latency than nodes at a stationary position. User mobility creates variable IP path lengths between source and destination. We observe that some of the longer ATF time of mobile nodes was caused by IP path length difference between operators and the Web-content server. By taking Yahoo as an example,

we observed that the nodes hosted in Norwegian operators traverse up to 20 IP hops to reach the Yahoo web server. Instead, other Swedish operators take a maximum of 16 IP hops to reach Yahoo's web server.

4.3 Summary

In this chapter, first, we investigated the factors affecting short web-flows in mobile networks. We showed that there could be different sources of latency in mobile communication, including DNS resolution, TCP connection establishment, radio technology, interference, packet loss, and load on the server. Focusing on DNS resolution and TCP connection establishment time, we studied factors affecting these latencies by conducting measurements towards four websites. Compared to legacy radio technologies, LTE offers considerably lower latency. We showed that DNS lookup time significantly varies for different websites, even when the same radio technology is accessed during the measurement. We observe that the proximity of DNS servers to the subscriber has a higher impact on DNS lookup time performance. We discussed how caches closer to the ISP could significantly improve TCP connect time.

We use ATF time to measure end-user web browsing experience following two different approaches: pixel-wise comparison and the browser heuristics. We have seen that for the websites we have tested, the PLT and ATF time have small differences across MNOs. However, the design of different websites should be considered when approximating user web browsing experience using the two approaches. The impact of user mobility is minimal on the ATF time of the websites. We also discussed that the time for DNS lookup and TCP connection establishment of different websites varies across MNOs due to cache entries.

5. Data usage patterns and user behavior in mobile networks

The number of users and the demand for mobile data traffic are continuously increasing. Mobile networks are becoming heterogeneous in order to keep up with the ever-increasing demand for mobile data traffic [23]. Furthermore, mobile users at various locations and market-places have different data consumption patterns and data usage behavior. These create complexity in managing the network resources and understanding the data usage patterns of mobile users.

Previous studies have shown that data usage and transfer patterns of different applications have a significant impact on the energy consumption of mobile devices [19]. As network resources are finite, different service and content providers need to efficiently manage the available resources based on the data usage behavior of their customers. As a result, understanding the data usage patterns of mobile users at different locations and market prices (e.g., prices for limited and unlimited data usage) becomes increasingly important. In this chapter, we investigate data usage patterns and behavior of mobile users across countries. This chapter is based on Publications IV and V.

5.1 Methodology and dataset

To understand data usage patterns of mobile users, we perform a detail exploratory analysis and comparison on mobile users' data usage patterns and behaviors; first using Finland mobile users as a use case and then across six countries. We cover how the data usage behavior of mobile users varies by factors. Some of these factors include network congestion, user mobility, time of day, market-price, device model, and network performance. We discuss user satisfaction levels, also known as Service Level Scores (SLS) and the data consumption difference over WiFi and cellular networks per country. By defining the data usage patterns of mobile users, we develop a clustering model and identify three different mobile user groups (clusters). We study whether the type

of applications installed by users correlates with data consumption patterns or not. Then, we develop mobile users' data usage classification model using the result of clustered data as a baseline.

We use data collected from mobile users' devices in six different countries (Finland, Germany, the United Kingdom, Japan, India, and Brazil). The dataset has been collected using the Netradar mobile network measurement platform. Mobile users in the respective countries are identified based on the network and subscribers' code (Mobile Network Code (MNC)), and Mobile Country Code (MCC) values. In other words, a user in a given country has to be a subscriber to one of the MNO in that country and accessing the network within the same country. For the sake of simplicity, roaming users are not included. For our analysis, we used a month-long (July 2018) dataset. The number of measurement sessions created per country over cellular networks are in the order of millions. The median session duration per user over cellular and WiFi networks has a marginal difference. For instance, in Finland, the median session duration is seven and six seconds in cellular and WiFi networks, respectively. Table 5.1 summarizes the number of users and sessions created per respective countries in cellular networks.

Table 5.1. Number of users and sessions created in Cellular and WiFi network by country.

Country	# of sessions (M)		# Users		
	Cell	WiFi	Cell	WiFi	Cell & WiFi
Finland (FI)	35.1	26.0	7213	681	15582
Germany (DE)	6.3	17.8	671	504	5877
United Kingdom (UK)	34	90.4	211	569	20358
Japan (JP)	19.8	50.1	369	871	7712
Brazil (BR)	17.8	42.9	279	1483	6885
India (IN)	2.5	5.8	0	121	1665

Note that the measurement data has been collected only from Android devices. Mobile users on other mobile operating system platforms such as iOS and Windows are not included in this study. In addition, our study does not consider the demographics of mobile users as the user information is anonymized.

5.2 Data usage patterns

Mobile users have different data usage patterns and behavior. The variation and the difference come due to various reasons such as access to good network coverage, presence or absence of congestion, user mobility, market-price for mobile data subscription, location, and device model types. In this section, first, let us discuss some of these factors and their impact on mobile data usage

patterns based on the dataset collected from mobile users in Finland. In the later sections, we discuss data usage patterns across different countries.

5.2.1 User mobility and location dynamics

Users access mobile data on different mobility conditions such as while commuting on a train, walking, while driving a car, or from a stationary position. We study data usage patterns in terms of user mobility and investigate at which mobility condition mobile users usually consume data.

Figure 5.1. Distribution of total download bytes per user during a month period. Stationary users consume more data than moving users. Figure from Publication IV.

Figure 5.1 shows the total download bytes per user for stationary and mobile users. We observe that the ratios of cellular users at a fixed location are almost two times greater than users that were moving from place to place (20K users at a stationary location and 13K users on the move). We compared the median download speed the users have got when they are at a stationary place and in mobility. We found that stationary users get a higher download speed (2× faster) than moving users. Similarly, stationary users consume much more data (median download: ~76MB) than users in the move (median download: ~6MB).

5.2.2 Device model and OS version

An interesting question one could ask is whether the choice of the device models impacts the data usage patterns of the users. Device manufacturers set the market price based on the device specification and their target user group. However, the price of the devices might vary in different markets and usually decline over time. The year of release of the device models in the market and their price level can be used as an indicator for the target user group type.

By considering the device model, the OS version, and year of release of the devices, we study if the session length, the number of sessions, and the amount of data transferred vary per user device. To do this, we first grouped device models by their brand name. Then for every brand family, each specific model

Table 5.2. Device group in FI based on market price

Device group	Price range (€)	# users	# devices	#sessions
Low-end	[<=200]	4748	112	6.2M
Mid-end	[200 - 400]	9316	147	11M
High-end	> 400	1200	32	2.1M

has mapped to the devices' year of release and average market price based on the information from the GSMA arena [237]. Note that, the OS version of the devices has already been inferred during the measurement period. After filtering, we found a total of 295 different device models in our measurement dataset from Finland. Table 5.2 shows the three device groups categorized by price range, including the number of users, and the device model per each group.

Figure 5.2. Total download bytes per user categorized by price level and OS version of the devices. The data consumption over high-end device models is twice more than the mid-end and low-end device models. Figure from Publication IV.

By considering the price range of the device, we look at three different groups of users and the per-user total download bytes. We found that users with a high-end device model consume twice the data than mid-end and low-end device model users, as shown in Figure 5.2 (left). The median total download bytes per devices' price level for high-end, mid-end and low-end devices is 50.3MB, 26.3, and 21.8MB, respectively. This is possibly explained by the type of application installed and the data usage behavior of the user. For instance, users with a high-end device might tend to use 'heavy apps' that consume a lot of traffic. One reason for this could be that the economic status of users might allow them to have a good data subscription plan. Besides, high-end devices usually have a larger screen size. As a result, users might use their smartphones for most of their daily activities on the Internet.

Using the associated name of Android OS release versions, we map the version number with the corresponding name based on the Android release information [238]. We observe that the recent OS versions have relatively smaller total download bytes per user than older OS versions. As shown in Figure 5.3 (left), the Oreo OS version has median total download bytes of 167.7 MB per user

Figure 5.3. Total download bytes per user categorized by device OS version name and devices year of release (LTE network). New devices with the latest OS version have relatively lesser total download bytes than similar device models (based on year of release to the market) but with older OS version. Figure from Publication IV.

under LTE network. Oreo is the most recent release of Android OS compared with the other two versions that we have in our measurement. On the other hand, devices based on Nougat and Marshmallow versions have 177.9 MB, 303.3 MB median total download bytes, respectively. One possible reason for the latest OS version to have lesser total download bytes per user is that OSs have come with an improved and an optimized mechanism to avoid bulky downloads from the server for every content the user requests. Similarly, new devices come with higher memory size, storage capacity, and processing power. As a result, some frequently accessed pieces of information can be cached locally to minimize the size of contents to be downloaded directly from the server. This can be observed in Figure 5.3 (right), where the latest devices (based on the year of release) with the latest OS version have relatively smaller total download bytes than older devices with the latest OS version. For instance, devices released from 2016-2018 and running Oreo has smaller total download bytes per user than models released before the year 2016.

5.3 Data usage pattern across countries

In this section, we discuss the variation in mobile data usage patterns across different countries. We have used a large dataset (~ 300 million records) collected from mobile users in six countries. As we have described in previous sections, the dataset is collected using the Netradar mobile network measurement platform.

Mobile networks can be a bottleneck due to different reasons. For instance, if congestion happens at the base station, the session is recorded as constrained. The measurement platform identifies whether sessions created were constrained by the base station or not. Note, the constrained speed (which is related to the maximum network speed and created when the network is a limiting factor) is higher than unconstrained speed (the speed recorded when the network was not

Figure 5.4. Total download bytes per mobile users over WiFi and cellular in 6 countries: July 2018. Figure from Publication IV.

a limiting factor).

Figure 5.4 shows the distribution of data consumption per user over cellular and WiFi networks based on total download bytes across six countries. We observe that, except for users in Finland, mobile users in the other countries prefer WiFi networks for both uploading (the plot not shown) and downloading contents from the Internet. Moreover, we observe that the average daily download (unconstrained) speeds over cellular networks vary per country. For instance, in Japan, average daily download speed is 5.6 Mbps. In comparison, in Finland it is ~ 8 Mbps, which indicates that Finnish mobile users mostly use heavy apps (or apps that demand high data traffic) than Japanese mobile users. The flat-rate based data subscription plan in Finland is one factor for users to use cellular networks for most of their activities on the Internet. The average daily download speed in the UK, Brazil, and India is 6.3 Mbps, 4.2 Mbps, and 4.0 Mbps, respectively.

We observe that the overall download consumption of users per country in the six countries (irrespective of whether users access WiFi or cellular networks) has a similar pattern. The total data consumption per user over both cellular and WiFi network shows that the six countries are comparable. This indicates that mobile users in different countries mostly access the Internet data from their devices in a closely similar trend. However, over which network technology type that mobile users prefer to access the Internet on their device varies across countries, due to different reasons such as network coverage and market price.

We study the ratio of mobile users using cellular and WiFi network across these countries. We observe that except for Japan, mobile users in the other five countries follow a relatively similar pattern. For instance, there is an

Figure 5.5. SLS distribution and variation over time of a day in six countries. Figure from Publication IV.

increasing trend in downloading traffic volume during the evening hours (typical starting from 16:00 up to 20:00). In the afternoon, the number of users who start downloading content over WiFi increase more than the number of users downloading over cellular networks (e.g., in the UK and Germany, after 16:00). This might indicate that users at home or off-work time prefer accessing content from the Internet over WiFi networks. This might also indicate that users start accessing heavy traffic demanding apps over WiFi during that period. For instance, in Germany, the median total download bytes over cellular and WiFi networks at 4:00 AM is 24 and 158 MB, respectively. Whereas at 20:00 hours, it is 58 MB over cellular and 277 MB over the WiFi networks.

5.3.1 Service Level Scores (SLS) and network congestion

SLS measures user satisfaction level based on the number of times that the users have got what they ask for from the network. It is the ratio of the difference between the number of unconstrained and constrained sessions to the number of unconstrained sessions, for every user, as shown in equation 5.1, where α is the number of unconstrained sessions and β is the number of constrained sessions.

$$SLS = \frac{\alpha - \beta}{\alpha} \times 100 \quad (5.1)$$

The overall average SLS score for each country is FI (66.52%), UK (75.75%),

Figure 5.6. Number of congested sessions on stationary and movable users. Stationary users are more likely to access a network with congestion than users at the move. Figure from Publication IV.

JP (76.78%), DE (74.22%), IN (54.73%), and BR (67.74%). Based on user activity and application type, some time of a day tends to be more active in traffic flow than others. We study the temporal traffic dynamics and the service level score of mobile users by time of the day. Figure 5.5 shows the hourly SLS values in a cellular network across six countries. The box plot in black shows the distribution of SLS over time of a day for the whole data. The orange lines are median values per user for every hour. SLS started to deteriorate during peak hours (e.g., starting from 4:00).

Taking Finnish mobile users as a case study, we study how 4G coverage and MNO affects SLS score. We notice that the availability of network coverage (e.g., 4G network) at different locations also varies per MNO. We observe that users subscribed to a given MNO with higher 4G availability, have higher SLS and total download bytes than the MNO's with lower 4G coverage. This indicates that users subscribed to different network operators have different data usage experience and traffic demand.

Figure 5.6 (a) shows the download bytes vs. the number of sessions with constrained speed per user. It depicts that the presence of congestion limits the total download amount users could get, irrespective of the number of times the users are interacting with their device (the bottom of the x-axis). On the other hand, as the number of sessions increases the maximum amount of download bytes are observed. This indicates that users were hitting the maximum network speed as they aggressively access the network. We also study the chance of users running under congestion when they are moving around and when they are stationed at a single place during the measurement period. We found that stationary users access a network with congestion more than users at the move, as shown in Figure 5.6 (b). This result is in-line with the high amount of data consumption by stationary users.

5.4 Clustering mobile users data usage patterns

User clustering can be used to reveal different types of users based on their data traffic consumption and usage patterns. We apply unsupervised K-means clustering method [239] to group mobile users based on their traffic consumption and activity level. First, we present data processing followed by similarity computation to create user clustering. Then we discuss types of users and the app categories they use per cluster.

For a given time T , usage pattern UP is defined by a tuple that consists of the following combination. $UP = (C, F, R, P, D, V, N, B)$ where C is the number of times user runs under congestion (constrained download speeds); F is the number of times the user runs without congestion (unconstrained download speeds); R is the percentage of accessing 4G or 3G network; P is the average population size of the area where the user was accessing the network; V is the throughput (average constrained and unconstrained download speed); D is the average session duration; N is the number of sessions created by the user; B is the total bytes transferred (uplink, and downlink direction) at every time interval t . For our case, the time interval t is set to one hour. The usage pattern for a given user ID i can be defined as: $up^i = up_k^i | 1 \leq k \leq T$. Therefore, the usage pattern for a given user ID i at time k can be defined as: $up_k^i = (c_k^i, f_k^i, r_k^i, p_k^i, d_k^i, v_k^i, n_k^i, b_k^i)$. User ID I is a combination of *installation id*, *device model*, *device brand name*, *subscriber MNO*, and *network country*.

Let $C = c_1, c_2, c_3, \dots, c_k$ be a set of clusters where every c_i is a group of users with ‘similar’ traffic pattern and demand, and k is the number of clusters. In unsupervised learning, the number of clusters (i.e., the number of centroids) has to be specified before doing the clustering. To decide the optimum number of clusters, we use Within Cluster Sum of Squares (WCSS) – elbow method and the dendrogram structure of hierarchical clustering. To measure the quality of the separation of the clusters, we applied three different stopping criteria namely silhouette score (SH) [240], Calinski-Harabasz index (CH) [241] and Davies Bouldin score (DB) [242]. By optimizing the three scores (CH, SH, and DB) we run the K-means clustering algorithm and found that $K = 3$ is the optimum number of clusters.

5.4.1 Types of mobile users

We run the clustering algorithm over the dataset for each country separately and identify group of cellular users belonging together based on their data usage patterns. Accordingly, we found three distinct group of users and named them

Table 5.3. The median data consumption and number of sessions per user group across countries. The three numbers inside the bracket next to each country name show the number of users (%) under Heavy, Regular, and Light clusters, respectively. The numbers under the total Bytes column separated by the pipe represent the download and upload size, respectively.

Country (%)	Total Bytes (MB)			# Sessions		
	Heavy (H)	Regular (R)	Light (L)	H	R	L
FI (3.5, 41.9, 54.6)	309.9 18.8	59.9 4.4	8.5 0.9	389	85	20
DE (2.2, 23, 74)	58.2 5.1	9.9 1.2	2.4 0.3	169	32	10
UK (3.1, 27.2, 69.7)	65.2 5.8	12.1 1.4	2.9 0.4	146	32	11
JP (3.1, 32.9, 64)	98.4 7.7	14.7 1.6	3.4 0.4	211	38	11
BR (4.6, 35.8, 59.6)	186.7 13.8	29.8 2.8	4.8 0.7	277	71	21

as ‘Heavy’, ‘Regular’, and ‘Light’ users. ‘Heavy’ users can be characterized as users that consume the highest volume of data (both in download and upload). They are also who frequently interact with their devices (based on the number of sessions created by users). ‘Light’ users are users with a small amount of download/upload bytes and session number. ‘Regular’ users are found in between the two user groups. Identifying a heavy user from light users can be, for instance, used as an input for optimal resources management based on demands.

Table 5.3 summarizes the number of users under each cluster along with total data consumption and sessions created per every country. It shows that both the number of users and the data consumption grouped together in one country varies compared with the similar group (cluster labels) in another country. For instance, considering the level of data consumption and session creation heavy users in Finland and Brazil consume two times more than heavy users in Germany and the UK. For brevity, we discuss the cluster of two countries (Finland and Brazil) in detail.

Figure 5.7 depicts, the median total download and upload values (left column); the unconstrained and constrained speeds (middle column); the number of sessions and session duration (the right column) per cluster for users in Finland. From the figure, we can observe that cluster 1 consists of a group of users that mostly consume the highest amount of download (309.9 MB) and upload (18.8 MB) values in all times of the day. We refer to these group of users as heavy users. Heavy users cover only 3.5% of the total users from our measurement. Note that, the label assignment as ‘heavy’, ‘regular’, and ‘light’ user is primarily based on the median total download/upload bytes and the number of sessions created per clusters from highest to lowest. These group of users actively engage with their device as can be seen from the number of sessions created by the user

(top right column). These are also users who get higher download speed than the other group of users. Moreover, they constantly hit the maximum network speed of the network (constrained speed) in all time of the day. Under heavy users group, there are more than 3.8M measurements collected from 399 unique users.

Figure 5.7. Median distribution per cluster for users in Finland. Note the scale difference in both X and Y axes. Figure from Publication V.

Users in a cluster 2 can be considered as regular users. They cover $\sim 42\%$ of the total users. Most of the time, regular users do not hit the maximum network speed. In a cluster 2, there are more than 12.3M measurements collected from more than 4.7K unique users. By considering the total measurement sessions from each cluster, we observe that 86% of the sessions were collected over LTE network whereas the remaining 14% over 3G networks (i.e., 12% (HSPA+), and 2% of the time over the other 3G network families). We observed a similar distribution between heavy and regular users in terms of radio technology they accessed (i.e., 3G and 4G).

Cluster 3 consists of the majority of mobile users, which covers $\sim 55\%$ of the users from the measurement dataset. These group of users can be considered as light users. Light users consume lower bytes (in both download and upload). They are less engaged with their device as can be seen from the median number of sessions created per user. There are more than 6.2M sessions generated from $\sim 4K$ unique users. Considering the total measurement session created by light users, we observe that 69% the sessions created over LTE network and the rest 31% over 3G networks (i.e., 27% (HSPA+), and 4% over the other 3G network families).

Figure 5.8. Proportion of application category per user within each cluster label for mobile users in Finland. Heavy users mostly installed apps that demand more traffic than other group of users. Figure from Publication V.

5.4.2 App categories

Data consumption and data usage pattern can be related with the type of mobile application users installed. In the Play Store, individual apps are grouped and tagged under different categories such as Games, Entertainment, and Social. Netradar maintains only the high-level category of installed apps per device using the Android PackageManager. Note that we are focusing only on app categories that users explicitly install from the Google app store. We expect that focusing on the variety of app categories intentionally installed by the user reflects the interest and the data usage pattern of smartphone users. We study whether mobile users' data consumption patterns is related with the type of Apps installed. To estimate the influence of the app category per user within each cluster, we calculate $p(a_i)$ – the proportion of a given app category a being installed by the user i as follows. $p(a_i) = \frac{a_i}{A_i}$ where, a_i is the number of apps installed by user i for the app category type a and A_i is the total number of apps installed by user i , irrespective of the app category.

Different application categories installed on each users' device and their entropy values per cluster for mobile users in Finland is shown in Figures 5.8. We can see that heavy users usually install app categories that generate a lot of data traffics. These categories include entertainment, video player, photography, music and audio, and games. Regular users in Finland focus on entertainment, photography, social media, finance, music & audio, shopping, food & drinking apps than the light users' group. They frequently install apps related to weather, map & navigation, finance, sports, business, library & demo than heavy users.

On the other hand, light users use apps related to productivity, communication, tools, news & magazine, travel & local, education, and business app categories. Light users use these app categories more frequently than the other two groups. Compared to Finnish users, Brazilian heavy users have installed a few app

categories that generate high data traffic. Despite this, Brazilian heavy users still install video players, photography, and productivity apps more frequently than the other groups. Regular users in Brazil use communication, shopping, sports, games, education, finance, professionalization, business, and weather apps more frequently than the other two groups. However, light users use social, map & navigation, lifestyle, entertainment, travel & local, books & reference app categories more often than the other two groups.

5.4.3 Data usage prediction

Predicting data usage patterns and behavior of mobile users can be used to optimally target towards users' data traffic demand and usage patterns. Using labeled clustered dataset as an input, we apply a supervised machine learning algorithm to train a model that classifies user groups based on their group cluster labels. Since the variation between the number of users per cluster is very high, we have an imbalanced dataset. That is, the impact of majority class labels will overwhelm the classification model. Also, the minority cluster labels (e.g., clusters with a few numbers of users) could be missed out, even if the classification accuracy report is higher [243]. For instance, the cluster label imbalance ratio between heavy and regular users in Finland is ~ 14 . As a result, directly performing a general classification model on the existing clustered dataset could lead to a spurious mode that does not consider the impact of the minority class labels. To address this, we first apply the Synthetic Minority Over-sampling Technique (SMOTE) [244] and Adaptive Synthetic (ADASYN) [245] methods. These techniques create new synthetic data points based on the observations of the actual dataset so that all the minority observations are oversampled and balanced. Note that, metrics values such as the accuracy we found by applying both techniques at a different time is closely similar. The reported metrics is based on the SMOTE.

By taking the clustered dataset from Finland as input; first, we split the dataset into two - testing and training datasets. The data split is performed with a ratio of 20% and 80% for the testing and training datasets, respectively. Then we train the classifier on the training dataset. Note that we perform the training with different classifier algorithms, such as the decision tree, gradient boosting classifiers, and random Forest (RF). We found that the RF classifier method gives a better classification result than the other tested algorithms, omitted for brevity. By applying an exhaustive grid search along with ten-fold cross-validation, we found the optimal parameter values of the RF classifier. Accordingly, the model is trained by setting the depth of each tree in the forest

(`max_depth`) to 32, the minimum number of data points allowed in a leaf node (`min_sample_leaf`) to 10, and the number of trees in the forest (`n_estimators`) to 500.

The classification model of the RF model has accuracy of 87.5% and 79.9% on the training and the test, respectively. The precision value of heavy, regular, and light class label are 91%, 77%, and 73%, respectively. On the other hand, the recall values are 90%, 66%, 84% for heavy, regular, and light, respectively. We observe that the number of times the user download contents over unconstrained speeds, the number of tiles visited by users, the number of sessions created per user, and total upload/download traffic contributes more to the classification model. The F1- Score, that is the harmonic mean of precision and recall, is 90.5%, 71.1%, and 78.1% for heavy, regular, and light classes. For instance, the highest F1-score value for the heavy user type shows that the RF model fairly classified the data usage pattern of mobile users with good precision and recall.

5.5 Summary

In this chapter, we observed that Finnish mobile users consume more data using cellular networks than over WiFi. This could be related to the increasing number of unlimited data plan subscribers [246], availability of good mobile network coverage and the flat-rate data-plan [247] encouraging mobile users to stay connected to the Internet for a longer time [248]. In terms of device, we observe that users with high-end devices (based on price range) have the highest total download bytes. Users with recently released devices (based on year of release) have more interaction with their devices. High-end devices with the latest OS version have smaller total download bytes than similar device models (based on devices year of release) with older OS versions. One reason for this could be that high-end devices might come with better capacity to cache frequently accessed contents and thereby avoid bulky downloads from the server [249].

The constrained speed, which is the maximum network speed recorded when the network was a limiting factor, indicates the possible presence of congestion. Such a condition indicates that users and their mobile services need more throughput than what the network can provide. As a result, the highest download speeds are recorded. However, as the mobile network is a limiting factor, the total download bytes is limited to a certain extent, even if users could hit the network maximum. This is partly because downloading with the highest download speed might stay only for a short period. In terms of user mobility, we observe stationary users and users at home consume more data than moving

users and users at working places. We also observe that stationary users have more probability of experiencing congestion in the network than users on the move.

Clustering mobile users can be used to reveal different types of users based on their data traffic consumption and usage patterns. Generally, mobile users' data usage patterns and behavior can be categorized into three distinct user groups – heavy, regular, and light. We have seen that data usage patterns of mobile users are unevenly distributed, where a few percent of heavy users consume the highest volume of the data. The type of apps installed by mobile users is also strongly related with mobile users' data usage patterns. We have seen that heavy mobile user groups installed high data traffic demanding apps more often than the other two groups. We also observed that there is a significant variance in the amount of total data consumption and the number of sessions created across different countries of similar user groups. In other words, a group of mobile users that have been identified as heavy users in one country might not necessarily be categorized as heavy users in another country.

Predicting data usage patterns and behavior of mobile users can be used to optimally target towards users' data traffic demand and usage patterns. In this section, using the labels of the clusters as input features, we develop a classification model that helps to classify mobile users' data usage patterns. From the rank of important features that have been used for classification, we observe that the presence or absence of congested network and user mobility play a role in mobile users' data usage patterns.

6. Opportunities and challenges of mobile network measurements

As the evolution of mobile networks continues, different applications and services have become possible. Especially as the 5G is becoming the next available technology with very low latency and high throughput, new services such as a self-driving cars, machine to machine communication, etc., are going to become apparent. Crowdsourced based performance measurements can be used to quantify, test, and study different use cases on the existing mobile networks.

As discussed in Chapter II, mobile network measurements, mainly crowdsourced based network measurements, come with benefits and challenges. The crowdsourced measurements help to capture a realistic view of the Internet from a diverse environment (e.g., end-user device, location, and MNO). It also has different advantages such as saving costs, representing realistic network performance and user experience, capturing user mobility scenarios, and their ubiquitous [136]. However, it also poses different challenges, such as the diversity of mobile devices, operating systems, and network connections. For instance, gathering signal strength information from iOS or Windows Phone devices is restricted by the OS [61]. The challenges create a practical restriction on reading network-related metrics and differences in sets of reported parameters. As a result, careful considerations of diverse parameters are required to design the crowdsourced measurement and analyze datasets. Policies and issues related to user privacy and their preference, as well as consumption on some resources (e.g., measurements may cause consumption of data volume and battery), etc. are some of the challenges related to crowdsourced measurements [68].

In this chapter, we discuss two different application scenarios that could be possible in the existing and upcoming mobile network technologies. We will also highlight some of the opportunities and challenges of the applications. For that, we present two of our research results as a use-case. First, we present our study on the feasibility of teleoperated driving in the existing cellular network and its challenges. Then, we discuss how to aggregate two different sources of network

measurement data using the correlation method to get a complemented dataset. This chapter is based on Publications VI and VII.

6.1 Teleoperated driving

Controlling vehicles from remote, self-driving, and self-parking are among the evolving services of vehicle management systems, which are becoming the potential application areas using mobile networks. Especially as new and improved radio technologies such as LTE+ and 5G are becoming accessible in the coming years, the relevance of the aforementioned applications becomes prevalent. Following this motivation, in Publication IV, we study the feasibility of teleoperated driving in the current cellular network by conducting network performance measurements while driving through different locations.

Teleoperated Driving provides an autonomous-like behavior of the vehicles where a vehicle is controlled remotely by a human driver when required. Even with fully autonomous vehicles, there will be situations where a system can not handle a situation. In the presence of such situations, human intervention is necessary. For instance, during the presence of complex roadside work [250] or other obstacles [251], Teleoperated Driving can be applicable.

In mobile networks, frequent changes in network quality can be expected due to the mobility of vehicles [252]. The presence of changes in network conditions creates a challenge in performing Teleoperated Driving smoothly. Considering these challenges, we conducted a measurement-based study to investigate whether Teleoperated Driving is feasible with contemporary mobile networks. We investigate latency and throughput values while driving in the real world using three complementary measurement setups. We study the influence of different factors on the usability of the system. These factors include handover effects, the distance between a remote car and the teleoperation station, and the signal strength.

6.1.1 Methodology and dataset

The data for this section is collected while driving a vehicle in rural and urban areas of Germany. The test vehicle equipped with SierraWireless RV50X LTE gateway [253]. The gateway has antennas providing LTE connectivity and GPS signals. It is connected to an Ubuntu computer inside a car using Ethernet. While driving, we measure latency (over UDP and ICMP) and throughput (over TCP) using three different measurement tools Nettitutka, Ping, and iperf3.

Note that to minimize the side effects of reduced throughput or higher latency, the three tools were not running in parallel.

The RTT value and related context information are also gathered by conducting a Ping test from a self-developed Android app. From the computer throughput values (uplink and downlink) are measured using the `iperf3`. Both Ping and `iperf3` based tests are connected to a server hosted in Munich. From the Android device, we run continuous measurements using `Nettutka`, where throughput (over TCP), latency (over UDP), and meta-information related to each measurement have been collected. The server to which `Nettutka` measurement connects to has been hosted at the Amazon cloud servers in Europe.

The measurement data cover the period from May to December 2017. It has a total driving time of ~ 78 hours covering ~ 5200 km. Measurements are split up into 2180 km (1528 minutes) for ping, 2670 km (2940 minutes) for `Nettutka`, and 354 km (191 minutes) for `SierraWireless`. The study and the results we are going to discuss in this section reflect the end-users perspective of the mobile network. Hence, we did not include how network providers treat different packets, or how busy a particular cell tower was during our measurement. In addition, the network infrastructure and coverage could vary by location and country, and this variation will likely impact the measurements we have conducted. Nonetheless, the study approach and results we found can be applied to get the first insight into the feasibility of Teleoperated Driving with contemporary mobile networks.

6.1.2 Feasibility of Teleoperated driving in existing mobile networks

Defining and identifying network parameters that allow to operate Teleoperated Driving safely is done through test measurement and by using previous studies as a reference. Sending a control command to the remote vehicle requires a small amount of data. We observe that controlling the remote vehicle is possible by sending steering commands to the vehicle at every 10 ms with ~ 0.25 Mbit/s. From the test environment, we found that by sending command packets at every 10 ms interval, it is possible to achieve a smooth control stream of steering commands. For smooth Teleoperated driving, uplink speed needs a tighter requirement, as it is required to stream videos. For instance, a minimum of 3 MBit/s of uplink speed is required in order to transmit a view with 150° [254]. Similarly, governmental regulations, such as in Germany, require three cameras (two front and one back) covering 90° with a resolution of 640×480 , where an uplink speed of 3 MBit/s can be enough [255]. Recommendation from YouTube and Adobe for live streaming video also suggests that data transmitted with

Figure 6.1. CDF of ping latency based on the destination server in Munich/Frankfurt (Frankfurt: ~45.3 ms, Munich: ~59.4 ms in median). Figure from Publication VI.

Figure 6.2. Distribution of ping latency based on destination: Munich/Frankfurt. Figure from Publication VI.

1 MBit/s is enough to carry one stream with sufficient resolution [256, 257]. Hence, the uplink speed of 3MBit/s is required to control the remote vehicle with three cameras.

To determine the minimum requirement for latency, we conducted user study with five individuals using a self-developed 3D driving simulator. Users have been driving through pylons with different levels of latency [258]. From the test drive, a threshold of 250 ms and 150 ms for latency and jitter, respectively, are found to be a minimum required critical values. Next, let us discuss the impact of latency and throughput on the feasibility of Teleoperated driving.

6.1.3 Latency

As we discussed in the previous chapters, many applications are impacted by latency; Teleoparted driving is not out of this. If the latency is longer, it can delay the delivery of steering commands and video streams to and from the remote vehicle. ICMP packets may be treated differently [259] than UDP packets on the path towards the destination. Hence, let us discuss separately, the latency values and the results measured using Ping (ICMP) and Nettitutka (over UDP).

There may be multiple teleoperation stations deployed at different places. As a result, investigating whether the location of a teleoperation station influences the latency is essential. We chose two servers in cities with about 300 km of distance between each other. The latency to both servers is roughly comparable, but the one to the server in Frankfurt is lower (~45 ms to ~59 ms), as shown in Figure 6.1. The average distance of the vehicle to the server in Munich and Frankfurt is 119 km and 270 km, respectively. Figure 6.2 shows that Munich has greater maximum distances than Frankfurt. It can be seen that a higher

Figure 6.3. CDF of Netradar uplink measurements with overall median of ~ 12 MBit/s (EDGE: ~ 3.5 MBit/s, HSPA: ~ 15.9 MBit/s, LTE: ~ 16.5 MBit/s, HSPA+: ~ 3.7 MBit/s).

Figure 6.4. Variance of Netradar uplink measurements with overall median of ~ 0.07 MBit/s.

distance between vehicle and teleoperation station does not significantly lead to higher latency, but its variation drastically increases. As both servers are connected to the Internet with identical parameters, this shows that the location of the teleoperation station is important. Note that during the measurements, the vehicle was driven at a varying speeds. However, we do not observe a significant influence of the vehicle's speed on the latency and throughput.

6.1.4 Throughput

For smooth Teleopartor driving the amount of data transmitted per second as well as having stable network connectivity are significant. The quality of transmitted video streams has to be adapted to the available throughput dynamically. Conducting Teleoperated Driving is infeasible if throughput is too low or changes too frequently for algorithms to adjust.

Teleoperated driving is possible based on the view from the remote vehicle. As a result, adequate uplink speed is required to provide qualitative sufficient video streams. The median uplink speed is ~ 12 MBit/s (Figure 6.3). In about 87% of the measurements, the uplink speed is above 3 MBit/s and thus sufficient for Teleoperated Driving. While the median variance is acceptable ~ 0.07 MBit/s, the maximum variance is ~ 70 MBit/s and thus very high (Figure 6.4). In general, these throughput results seem viable for Teleoperated Driving, but there is a high percentage of about 13%, where the uplink speed is insufficient. If only considering LTE connectivity, uplink and downlink are sufficient in about 95% of the time.

We observe that there is a difference in throughput between different measurement platforms on an identical route. For instance, by taking measurements conducted only on LTE networks, the median downlink and uplink speed using

Nettutka measurement platform, is ~ 16 MBit/s and ~ 14 MBit/s, respectively. On a similar route and radio network, the *Sierra Wireless* platform has ~ 32 MBit/s and ~ 20 MBit/s media downlink and uplink speed, respectively. The difference could come due to the position and quality of the antenna installed with *Sierra Wireless* compared with the smartphone. This indicates that provisioning better hardware, such as multiple antennas, can potentially improve Teleoperated Driving.

We observe that distance to the base station was usually less than 5 km. We note that the distance has no apparent influence on the values of throughput (uplink/downlink) and latency. Similarly, the driving speed of the car and signal strength has a minimum impact on Teleoperated Driving. The impact of handover in Teleoperated Driving is not visible when cell switching happens under the same radio technology (e.g., if switching happens from one cell to another under the LTE network). However, if the cell change happens along with switching radio technologies, operating Teleoperated Driving becomes infeasible.

In general, using Teleoperated Driving may be possible with the existing cellular LTE and LTE-Advanced network environment if the areas are whitelisted. In most cases (ping and netradar: 96%), the latency was below 250 ms, the uplink was above 3 MBit/s (*SierraWireless*: 98%, netradar: 87%) and the downlink above 0.25 MBit/s (*SierraWireless*: 99%, netradar: 95%). This shows that in most of the places where we conducted the measurement, Teleoperated Driving could be applicable. With the test drive on a specific route, we showed that the whitelisting routes applicable for Teleoperated Driving can work. However, the basic approach has to be also improved, considering changes in network conditions to provide accurate maps for Teleoperated Driving. For instance, conducting frequent probing and providing results to a cloud-based service can be a helpful approach.

6.2 Aggregating network measurement data

These days there are a plethora of networked devices that generate various signals and information. The presence of 5G network and Internet of Things (IoT) are going to be a trend, where almost all of the devices in a networked environment transmit and receive data. As the number of mobile users and connected devices are prevalent, there is a massive amount of data generated from each of these connected devices. Different measurements are conducted from a different vantage point with various goals and purposes. These measurement data points are found and collected at different times and places. Sometimes, relevant

information about the network might be missed in one measurement data point and recorded on the other measurement data points. This kind of information discrepancy might also lead to a difference in the analysis results [58].

Integrating different measurement data sources will have a chance to provide a piece of resourceful information by complementing the missed information in one data source with the other data source. Different sources of data are widely available in today's network. It is essential to have a mechanism to merge (bring) together with these data sources so that rich information could be found. In motivation to these, our study in Publication VII develops a methodology to integrate different sources of mobile network measurement data points using feature mapping techniques.

6.2.1 Methodology and dataset

For this work, we use two different datasets collected using the Nettitutka [61] and the RTR Nettest [119] measurement platforms. The metrics from Nettitutka are collected from June to the end of November 2017. We further filtered the dataset by radio technology type and location. For this, we select measurements under LTE network, which has been collected from the Helsinki area, Finland. The Nettitutka dataset has a number of measurement metrics related to cellular network performance. For this work, we use 11 of these fields including, TCP based downlink and uplink speed, UDP based latency, signal strength, LTE Arbitrary Strength Unit (ASU), LTE RSRP, LTE Channel Quality Indicator (CQI), LTE RSRQ, and LTE RSSNR.

The second dataset is from RTR Nettest [119]. This platform used to collect a number of measurements metrics including the downlink and uplink speed, signal strength, KPI values of the mobile network such as RSRP and RSRQ for LTE, connection error and IP packet loss, ping based latency, testing time, IP address and host name of the computer. For this work, we only focus on measurement metrics collected under LTE network. These are TCP based downlink and uplink speed tests, TCP based latency test, LTE RSRQ, and LTE RSRP. Based on the measurement description of Nettitutka and RTR Nettest measurement platforms, the following pair of features are assumed to be similar and expected to be mapped to each other through our mapping algorithm. These are: (downlink, download_kbit), (uplink, upload_kbit), (latency, ping_ms), (RSRP, RSRP), (RSRQ, RSRQ).

The feature mapping algorithm maps features from source S to target T dataset based on correlations metrics and by solving a maximum CSP [260]. It follows two main steps. First, we prepare the metrics into correlation coefficient

rankings. To calculate the correlation coefficient ranking, we first split the data into subset by month. Then, for each sub-dataset, the algorithm calculates the correlation metrics (both Pearson and Spearman). The correlation coefficient ranking between features has to be performed for both source and target datasets.

Using the correlation coefficient metrics, we rank the coefficient values and represent every coefficient pair with inequality clauses such that $r(fx, fy) < r(fy, fz)$. The inequality clause represents that the correlation between feature fx and fy is less than the correlation between fy and fz . If such patterns are identified, then it can help to extract a general rule about specific features. For instance, from our results, we observe that the rule $r(latency, downlink) < r(downlink, uplink)$ holds true.

Both source and target datasets consist of their own sets of inequality clauses between correlation coefficients. Before the mapping is applied, the constrained base has to be built from the source dataset. The constrained base consists of coefficient inequalities that are more frequent and regular regarding the whole monthly-divided sub-datasets. An inequality $r(fx, fy) < r(fy, fz)$, which represents the correlation coefficient metrics between fx , fy , and fy, fz , is included into the constraint base, if the inequality clause occurs in more than 50% of the sub-datasets.

In the second step, the algorithm applies the actual mapping using the constrained base from step 1 as input, as shown in Figure 6.5. In this step, the algorithm finds similar patterns from the target to the source dataset by solving maximum CSP. The CSP aims to maximize the similarity of correlation patterns between the features (columns) in the datasets. The notion of CSP is that similar metrics across the two datasets should have a similar correlation between each other. For instance, the correlation between latency and downlink should be less than the correlation between downlink and uplink, irrespective of the network type.

Using the CSP, the algorithm returns a list of possible mappings between the features that have the highest satisfiability count concerning the constrained base. The CSP is adapted to solve the feature mapping problem as follows. First, for every possible mapping combination $Map_i(F_T, F_S)$ between the target (F_T) and source (F_S) dataset, it assigns features F_T to the constraint base wrt. Map_i . Then, for each monthly-based correlation matrix in the target datasets, it counts the number of times the constraints are satisfied in the target dataset with the current assignment. Finally, the algorithm returns a list of possible mappings that have the highest number of truth statements (satisfiability count).

By defining a mapping score, we identify a pair of features that can be mapped together using the returned least. The mapping score is defined as the ratio of feature pairs occurrence in the return list. Let us consider a mapping problem of three features between source $F_s = \{x, y, z\}$ and target $F_T = \{a, b, c\}$ datasets. Then, let the algorithm returns two lists of mappings: $Map_1\{(x, a), (y, b), (z, c)\}$ and $Map_2\{(x, a), (y, c), (z, b)\}$. For this particular example, the mapping scores would be: $(x, a) = 1.0$ and 0.5 for $(y, b), (y, c), (z, b)$ and (z, c) . These scores indicate that x and a could be mapped with each other while other mappings can not be deduced from these results.

Figure 6.5. Steps in the mapping procedure: 1) learning the constraints from the source platform and 2) mapping those to correlation coefficients from the target platform. Figure from Publication VII.

6.2.2 Evaluating feature mapping

To evaluate the feature mapping method, we include all the five features from the RTR Nettest (upload_kbit, download_kbit, ping_ms, lte_rsrp and lte_rsrq) and following eight from the Netradar: uplink, downlink, latency, RSRP, RSRQ, RSSNR, battery_level, and speed. We leave LTE ASU and signal strength out from the evaluation because the correlation matrices clearly indicate that they would give exactly the same results as the RSRP (which is also the desired outcome of the method). The higher number of features in the Netradar dataset allows us to evaluate the mapping in situations when there is not a simple one-to-one mapping between the features, but also some "noisy" features that should be left without a mapping.

For evaluation purposes, we define a mapping score between F_T and F_S for a single mapping case as follows: $\frac{1}{M} \sum_{i=0}^M score(f_{Ti}, f_{Si})$, where M is the number of common features between the sets ($M = |F_T \cap F_S|$), f_{Ti} and f_{Si} are the i th common features from the F_T and F_S . As defined in the previous section, the common feature-pairs are defined as: (uplink, upload_kbit), (downlink, down-

load_kbit), (latency, ping_ms), (RSRP, lte_rsrp), and (RSRQ, lte_rsrq).

Figure 6.6 shows the average scores of the feature mapping while RTR Nettest is the source and Netradar the target platform. The figure shows three subplots separating the mapping results between the mapping of three, four, and five features. From the subplots, we can see an increasing trend of the scores as a function of the common ratio can. The figure shows that the average scores of perfect mappings (common ratio = 1.0) can be distinguished from mappings having more false positives. The false positives include all imperfect mappings that do not refer to the same metric and have the common ratio lower than one.

Figure 6.6. Average mapping scores when mapping from RTR Nettest to Netradar. The score increases as a function of the common ratio. The perfect mappings (ratio of 1.0) outperforms the incomplete mappings. Figure from Publication VII.

Figure 6.7 shows the mapping results when Netradar is the source, and RTR the target platform and the same features are included in the evaluation. Apart from a small variation, the scores are rather equal to the earlier mapping case shown in Figure 6.6.

Figure 6.7. Average mapping scores when mapping from Netradar to RTR Nettest. The score increases as a function of the common ratio. The perfect mappings (ratio of 1.0) outperforms the incomplete mappings. Figure from Publication VII.

Data aggregation methods based on the matching metrics would be helpful to aggregate datasets collected across different platforms. For instance, a European Union project [261], that maps broadband services in Europe was launched in 2016. The project displays different datasets separately as it is challenging to

unify and present various datasets in one mapping application. Such projects could benefit from the metric matching approach presented in this thesis and aggregate datasets collected from different measurement platforms.

6.3 Summary

In this chapter, we explored the visibility of Teleoperator driving in the existing cellular network based on Publication VI. Network performance measurement tests are conducted while driving using three different measurement tools – ping, Nettitutka, and SierraWireless. The first section of this chapter discusses the feasibility of Teleoperated driving in terms of network latency, jitter, throughput, location, mobility, radio technology coverage, and handover.

Based on Publication VII, we discussed the approach we have applied to complement essential network features missed (not recorded) by one measurement platform from another mobile network measurement platform. There is a chance that some network features not measured by one mobile network measurement platform. That means some of the analysis based on a given specific measurement dataset might miss some detailed analysis results and information due to the lack of these missed features.

7. Conclusions

The research presented in this thesis focused on understanding, characterizing, and modeling the performance of mobile networks, QoE, and data usage patterns using measurement datasets collected from end user devices. The previous chapters discussed the motivation of this thesis work, along with the undertaken studies. This chapter will conclude the work. First, we summarize the main points and discuss the takeaways. Then, we discuss some of the limitations and future perspectives in mobile network measurement and performance analysis.

7.1 Discussion

Mobile devices have become the choice for running different Internet-based services. As a result, they have become an integral part of our day-to-day life. However, the performance of different services and applications running on end users' devices can be affected by various factors. Chapter 3 discussed some of these factors, including the available bit rate, transmission bandwidth, device model, the infrastructure of MNOs, radio technology type, seamless mobility support, and latency. Understanding and predicting the stability of the network is essential. We built a model that helps to classify the stability of TCP throughput based on the stability of the network using 'minimal information' (i.e., without measuring download and upload rates), which helps to reduce measurement overhead. We also presented a prediction model of the average TCP throughput based on the first five seconds, which can be useful for anticipating near-future performance in applications such as video streaming.

Browsing web content from mobile devices is an increasing trend. Many applications and services provide mobile-friendly web content. In web browsing, traffic flows generated from short web flows such as TCP connection establishment and DNS lookup time cover the majority of mobile web traffic. As a result, studying and understanding the factors affecting short web flows and

quantifying user QoE in a web is essential. In Chapter 4, we first investigated the factors affecting short web flows in mobile networks. We showed that, in mobile communication, there could be different sources of latency, such as DNS resolution, TCP connection establishment, radio technology, interference, packet loss, and load on the server. Focusing on DNS resolution and TCP connection establishment time, we studied the factors affecting web latency by conducting measurements towards four websites. Compared to legacy radio technologies, LTE offers considerably lower latency. We observe that the proximity of DNS servers to the subscriber has a higher impact on DNS lookup time performance. We also discussed how caches closer to the ISP could significantly improve TCP connect time.

In the second part of Chapter 4, we presented a web QoE approximation method in mobile networks. We discussed that, for the websites tested, the PLT and ATF time have small differences across MNOs. However, the design of different websites should be considered when approximating user web browsing experience using the two approaches. The impact of user mobility is minimal on the ATF time of the websites. We also discussed the fact that the time for DNS lookup and TCP connection establishment of different websites varies across MNOs due to cache entries.

With the presence of limited network resources, despite the enhancement of network technologies, efficient means of resource utilization and management are important. One way of managing resources and providing service on demand is achieved by modeling and understanding mobile users' data usage patterns. Chapter 5 presents a detailed analysis of mobile users' data usage patterns and behavior across six counties. In this chapter, we have seen how good network coverage and flat-rate pricing encourage mobile users to prefer cellular networks over WiFi (as evident from Finnish mobile users). We also discussed how the total data consumption of mobile users is related to factors such as location, device type and pricing, and network coverage. For instance, stationary users and users at home consume more data than moving users and users at places of work.

Grouping and identifying the data usage patterns of mobile users based on their total data volume consumption and usage patterns can be useful for managing network resources and user demand efficiently, for understanding and planning urban dynamics, and for developing data plan products. In the second part of Chapter 5, we apply unsupervised based machine learning methods and identify three data usage patterns – heavy, regular, and light. We discussed the fact that the data usage patterns of mobile users are unevenly distributed, such

that a few percent of heavy users consume the highest volume of the data. The type of apps installed by mobile users is also related to mobile users' data usage patterns (i.e., heavy groups tend to install apps that demand high data traffic). Then, using the labels of the clusters as input features, we develop a model that helps classify mobile users' data usage patterns. Classifying mobile users' data usage patterns and behavior can be used to target users' data traffic demands and usage patterns optimally.

Mobile network measurement data can be applicable for different scenarios, in addition to network performance analysis and modeling. Chapter 6 presented two use cases where crowd-based measurement data can be utilized to test Teleoperated operation and data integration. In this chapter, we explored the visibility of Teleoperator driving in the existing cellular network based on Publication VI. Network performance measurement tests are conducted while driving using three different measurement tools. Publication VI discusses the feasibility of Teleoperated driving in terms of network latency, jitter, throughput, location, mobility, radio technology coverage, and handover. Based on Publication VII, we discussed the approach that we applied to complement essential network features not recorded by one measurement platform with features recorded by another mobile network measurement platform. Mobile network measurement platforms could vary by objective and context. As a result, some network features might not be recorded by one platform while being collected by another platform. That means that some of the analysis based on a given specific measurement dataset might miss some detailed analysis results and information due to the lack of these missed features. Using complementary data sets, which is generated based on our work in Publication VII, could minimize the risk of losing detailed information.

7.2 Limitations and future work

The focus of this work is a mobile network performance study based on measurement data collected from end users. The results and interpretations reflect what the end user will perceive when accessing the mobile networks. We do not have enough visibility from the MNO side, such as how network providers treat different traffic flows and customers, or how much the traffic was congested in a particular base station. Because of this, we treat the network connection as a black box. In our study on mobile users' data usage patterns, the mobile users' demography is not considered since we do not have the information. Since it is a crowd-based measurement, the measurement might be limited to a certain group

of mobile users who are curious and want to monitor their network performance. However, these groups of users are also essential as they are most likely active mobile users and could be affected by the quality of mobile network performance.

If the device's network interface is in a low power state (IDLE), the device needs to get promoted by the base station to an intermediary power state or a dedicated one before communicating with an online server or Internet service. The transition time from IDLE to high power states could incur latency, especially for 3G radio standards. Monitoring the power state transitions of mobile devices with application-layer measurement is not possible with consumer devices. As a result, the network latency analysis, especially on pre-LTE radio technologies, does not consider possible bias caused by the IDLE state's promotion to DCH. MNO's could deploy middle-box (proxies) for different purposes, such as enhancing network performance or controlling their traffic. The presence of in-path proxies could interfere with network performance metrics. We have analyzed the impact of the proxies for TCP connect time performance using the RIPE [89] service to map the websites' resolved IP addresses to an ASN value. However, as we have limited visibility on the traffic path between the client and the target end host, our analysis on proxies has a limitation on fully capturing the impact of middleboxes on network performance metrics.

This thesis focuses mainly on mobile networks up to LTE (4G) networks. According to the Ericsson report, 4G will continue to be the dominant mobile Internet access technology at least until 2022, making it one of the vital access technologies in cellular networks [262]. At the time of writing the thesis, 5G network availability was limited. However, as the availability and network coverage increases, measuring and analyzing the quality of a 5G network will be of paramount significance to understanding its characteristics. In the coming years, it is expected that network coverage and services based on 5G technology will increase. For instance, Cisco forecasts that by 2023 the 5G network will be over 10% of global Internet traffic [263]. We believe that the methods and approaches we have applied in this thesis work can be easily extended to the measurement and analysis of other mobile networks, including 5G networks.

Understanding mobile network performance and mobile users' data usage patterns require continuous research by exploring different dimensions. For instance, in the context of this thesis, it is possible to use the Netradar mobile measurement platform augmented with demographic data in order to get a granular view of data usage patterns for different groups of age, income level, education level, and others. As mobile communication becomes a significant part of our day-to-day activity, ongoing research on mobile networks is essential.

Such research studies can be useful in different areas. For instance, mobile network operators can utilize the information to manage the increasing demand for mobile data usage [264], as well as to plan and optimize telecommunication resources [265, 266]. Similarly, policymakers and content providers will have more information to improve the quality of services and understand urban dynamics [267] for improved urban planning [268].

Teleoperated driving, a mechanism of remotely controlling vehicles located at the operation center, becomes one promising alternative solution when it is compared with autonomous driving [269]. However, there are only a few studies that analyze the feasibility of Teleoperated driving in existing mobile networks. In the future, continuous measurement and investigation of all connection requirements for smooth Teleoperated driving will be essential. Some studies include investigating whether skilled and trained drivers would be able to maneuver a vehicle under different network conditions, such as variable latency, location, and throughput [270, 271].

This thesis also presented a feature mapping method based on crowd-sourced datasets collected from two different mobile network measurement platforms. As we discussed, network measurement metrics can be collected from different vantage points other than the crowd or end-user device. As a result, conducting an additional study is important so that a feature mapping method with more than two sources of measurement datasets could be possible. The methodology presented in this paper could be adapted with other methods such as using the transfer learning paradigm and cross-dataset analysis [272].

References

- [1] I. T. Union, "Mobile Overtakes Fixed: Implications for Policy and Regulation," 2009, Accessed 18.4.2020. [Online]. Available: https://www.itu.int/osg/spu/ni/mobileovertakes/Resources/Mobileovertakes_Paper.pdf
- [2] I. Vogelsang, "The relationship Between mobile and Fixed-Line Communications: A Survey," *Inf. Econ. Policy*, vol. 22, no. 1, pp. 4–17, 2010, Accessed 18.4.2020. [Online]. Available: <https://doi.org/10.1016/j.infoecopol.2009.12.002>
- [3] C. Cox, *An introduction to LTE: LTE, LTE-advanced, SAE and 4G mobile communications*. John Wiley & Sons, 2012. [Online]. Available: <https://onlinelibrary.wiley.com/doi/abs/10.1002/9781119942825>
- [4] J. Macher, J. W. Mayo, O. Ukhaneva, and G. Woroch, "Demand in a Portfolio-choice Environment: The Evolution of Telecommunications," *Georgetown McDonough School of Business Research Paper*, no. 2012-19, 2019, Accessed 18.4.2020. [Online]. Available: <http://dx.doi.org/10.2139/ssrn.2133424>
- [5] D. Quaglione, N. Matteucci, D. Furia, A. Marra, and C. Pozzi, "Are Mobile and Fixed Broadband Substitutes or Complements? New Empirical Evidence From Italy and Implications For The Digital Divide Policies," *Socio-Economic Planning Sciences*, p. 100823, 2020, Accessed 18.4.2020. [Online]. Available: <https://doi.org/10.1016/j.seps.2020.100823>
- [6] H. Holma and A. Toskala, *LTE for UMTS.: Evolution to LTE-Advanced*. John Wiley & Sons, 2011.
- [7] J. Hoydis, S. ten Brink, and M. Debbah, "Massive MIMO in the UL/DL of Cellular Networks: How Many Antennas Do We Need?" *IEEE J. Sel. Areas Commun.*, vol. 31, no. 2, pp. 160–171, 2013. [Online]. Available: <https://doi.org/10.1109/JSAC.2013.130205>
- [8] C. Joe-Wong, S. Ha, S. Sen, and M. Chiang, "Do Mobile Data Plans Affect Usage? Results from a Pricing Trial with ISP Customers," in *Passive and Active Measurement PAM*, vol. 8995. Springer, 2015, pp. 96–108, Accessed 22.4.2020. [Online]. Available: https://doi.org/10.1007/978-3-319-15509-8_8
- [9] Z. Wang, L. Gao, J. Huang, and B. Shou, "Toward Flexible Wireless Data Services," *IEEE Communications Magazine*, vol. 57, no. 12, pp. 25–30, 2019, Accessed 22.4.2020. [Online]. Available: <https://doi.org/10.1109/MCOM.001.1900331>
- [10] H. Lee, S. Vahid, and K. Moessner, "A Survey of Radio Resource Management for Spectrum Aggregation in LTE-Advanced," *IEEE Commun. Surv. Tutorials*,

- vol. 16, no. 2, pp. 745–760, 2014, Accessed 16.4.2020. [Online]. Available: <https://doi.org/10.1109/SURV.2013.101813.00275>
- [11] J. Jia, Y. Deng, J. Chen, A. Aghvami, and A. Nallanathan, “Achieving High Availability in Heterogeneous Cellular Networks via Spectrum Aggregation,” *IEEE Trans. Veh. Technol.*, vol. 66, no. 11, pp. 10 156–10 169, 2017, Accessed 16.4.2020. [Online]. Available: <https://doi.org/10.1109/TVT.2017.2755504>
- [12] GSMA. (2019) Connected Society: The State of Mobile Internet Connectivity 2019. Accessed 10.5.2020. [Online]. Available: <https://bit.ly/3cf2PXX>
- [13] Cisco. (2020) Cisco Annual Internet Report (2018–2023). Accessed 10.5.2020. [Online]. Available: <https://bit.ly/2ztu6ao>
- [14] AppBrain. (2020) Android and Google Play Statistics 2020. Accessed 10.5.2020. [Online]. Available: <https://www.appbrain.com/stats>
- [15] M. Iqbal. (2019) App Revenue Statistics. Accessed 10.4.2020. [Online]. Available: <https://www.businessofapps.com/data/app-revenues/>
- [16] B. Burroughs, “YouTube Kids: The App Economy and Mobile Parenting,” *Social Media+ Society*, vol. 3, no. 2, 2017.
- [17] R. Nelson. (2020) Consumer Spending In Mobile Apps Grew 17% in 2019 to Exceed \$83 Billion Globally. Accessed 10.4.2020. [Online]. Available: <https://sensortower.com/blog/app-revenue-and-downloads-2019>
- [18] Cisco. (2017) Cisco Visual Networking Index: Global Mobile Data Traffic Forecast Update, 2016–2021. Accessed 10.5.2020. [Online]. Available: <https://bit.ly/2SQzADk>
- [19] J. Huang, F. Qian, Y. Guo, Y. Zhou, Q. Xu, Z. M. Mao, S. Sen, and O. Spatscheck, “An in-depth Study of LTE: Effect of Network Protocol and Application Behavior on Performance,” in *ACM SIGCOMM*. ACM, 2013, pp. 363–374. [Online]. Available: <https://doi.org/10.1145/2486001.2486006>
- [20] M. Z. Shafiq, L. Ji, A. X. Liu, and J. Wang, “Characterizing and Modeling Internet Traffic Dynamics of Cellular Devices,” in *ACM SIGMETRICS*. ACM, 2011, pp. 305–316. [Online]. Available: <https://doi.org/10.1145/1993744.1993776>
- [21] InternetSociety. (2019) Internet Society Global Internet Report: Consolidation in the Internet Economy. Accessed 10.5.2020. [Online]. Available: <https://future.internetsociety.org/2019/wp-content/uploads/sites/2/2019/04/InternetSociety-GlobalInternetReport-ConsolidationintheInternetEconomy.pdf>
- [22] Manoj and S. Kumar, “A Survey on Handover in LTE Heterogeneous Networks,” in *Pro. of International Conference on IoT Inclusive Life (ICIIL)*. Singapore: Springer Singapore, 2020, pp. 111–125.
- [23] A. Damjanovic, J. Montojo, Y. Wei, T. Ji, T. Luo, M. Vajapeyam, T. Yoo, O. Song, and D. Malladi, “A Survey on 3GPP Heterogeneous Networks,” *IEEE Wirel. Commun.*, vol. 18, no. 3, pp. 10–21, 2011. [Online]. Available: <https://doi.org/10.1109/MWC.2011.5876496>
- [24] I. Hwang, B. Song, and S. S. Soliman, “A holistic View on Hyper-Dense Heterogeneous and Small Cell Networks,” *IEEE Communications Magazine*, vol. 51, no. 6, 2013. [Online]. Available: <https://doi.org/10.1109/MCOM.2013.6525591>

- [25] L. Li, K. Xu, T. Li, K. Zheng, C. Peng, D. Wang, X. Wang, M. Shen, and R. Mijumbi, "A Measurement Study on Multi-path TCP with Multiple Cellular Carriers on High Speed Rails," in *ACM SIGCOMM Special Interest Group on Data Communication*, 2018, pp. 161–175, Accessed 12.4.2020. [Online]. Available: <https://doi.org/10.1145/3230543.3230556>
- [26] J. Wang, Y. Zheng, Y. Ni, C. Xu, F. Qian, W. Li, W. Jiang, Y. Cheng, Z. Cheng, Y. Li, X. Xie, Y. Sun, and Z. Wang, "An Active-Passive Measurement Study of TCP Performance over LTE on High-speed Rails," in *Mobile Computing and Networking (MobiCom)*, 2019, pp. 1–16, Accessed 25.2.2020. [Online]. Available: <https://doi.org/10.1145/3300061.3300123>
- [27] R. Padmanabhan, A. Schulman, D. Levin, and N. Spring, "Residential Links Under the Weather," in *ACM Special Interest Group on Data Communication, SIGCOMM*, 2019, pp. 145–158. [Online]. Available: <https://doi.org/10.1145/3341302.3342084>
- [28] J. Huang, Q. Xu, B. Tiwana, Z. M. Mao, M. Zhang, and P. Bahl, "Anatomizing Application Performance Differences on Smartphones," in *ACM MobiSys*, S. Banerjee, S. Keshav, and A. Wolman, Eds. ACM, 2010, pp. 165–178. [Online]. Available: <https://doi.org/10.1145/1814433.1814452>
- [29] M. Dasari, S. Vargas, A. Bhattacharya, A. Balasubramanian, S. R. Das, and M. Ferdman, "Impact of Device Performance on Mobile Internet QoE," in *ACM SIGCOMM Internet Measurement Conference, IMC*, 2018, pp. 1–7. [Online]. Available: <https://dl.acm.org/citation.cfm?id=3278533>
- [30] B. Jun, F. E. Bustamante, S. Y. Whang, and Z. S. Bischof, "AMP Up your Mobile Web Experience: Characterizing the Impact of Google's Accelerated Mobile Project," in *Conference on Mobile Computing and Networking, (MobiCom)*, 2019, pp. 1–14, Accessed 23.3.2020. [Online]. Available: <https://doi.org/10.1145/3300061.3300137>
- [31] N. Vallina-Rodriguez, A. Aucinas, M. Almeida, Y. Grunenberger, K. Papagiannaki, and J. Crowcroft, "RILAnalyzer: a Comprehensive 3G Monitor on Your Phone," in *Proceedings Internet Measurement Conference, IMC*. ACM, 2013, pp. 257–264. [Online]. Available: <https://doi.org/10.1145/2504730.2504764>
- [32] U. Goel, M. Steiner, M. P. Wittie, M. Flack, and S. Ludin, "Detecting Cellular Middleboxes Using Passive Measurement Techniques," in *Passive and Active Measurement Conference, PAM*, ser. Lecture Notes in Computer Science, T. Karagiannis and X. A. Dimitropoulos, Eds., vol. 9631. Springer, 2016, pp. 95–107. [Online]. Available: https://doi.org/10.1007/978-3-319-30505-9_8
- [33] A. Aucinas, N. Vallina-Rodriguez, Y. Grunenberger, V. Erramilli, K. Papagiannaki, J. Crowcroft, and D. Wetherall, "Staying online while mobile: The Hidden Costs," in *Conference on Emerging Networking Experiments and Technologies, CoNEXT*. ACM, 2013, pp. 315–320. [Online]. Available: <https://doi.org/10.1145/2535372.2535408>
- [34] L. Schulte, E. Boz, N. Varis, and J. Manner, "On Detecting TCP Path Saturation in LTE Networks," *Int. J. Communication Systems*, vol. 30, no. 16, 2017, Accessed 20.3.2020. [Online]. Available: <https://doi.org/10.1002/dac.3334>
- [35] A. Nikraves, D. R. Choffnes, E. Katz-Bassett, Z. M. Mao, and M. Welsh, "Mobile Network Performance from User Devices: A Longitudinal, Multidimensional

- Analysis,” in *PAM Passive and Active Measurement*, M. Faloutsos and A. Kuzmanovic, Eds., vol. 8362. Springer, 2014, pp. 12–22, Accessed 9.6.2020. [Online]. Available: https://doi.org/10.1007/978-3-319-04918-2_2
- [36] P. V. Mockapetris, “Domain Names - Implementation and Specification,” *RFC*, vol. 1035, pp. 1–55, 1987, Accessed 10.5.2020. [Online]. Available: <https://doi.org/10.17487/RFC1035>
- [37] J. Postel, “Internet Control Message Protocol,” *RFC*, vol. 792, pp. 1–21, 1981. [Online]. Available: <https://doi.org/10.17487/RFC0792>
- [38] 3GPP, “The 3rd Generation Partnership Project (3GPP).The Mobile Broadband Standard - Release 8.” 2008, Accessed 22.4.2020. [Online]. Available: <http://www.3gpp.org/release-8>
- [39] 3GPP, “The 3rd Generation Partnership Project (3GPP). The Mobile Broadband Standard - Release 10.” 2011, Accessed 22.4.2020. [Online]. Available: <http://www.3gpp.org/release-10>
- [40] 3GPP, “The 3rd Generation Partnership Project (3GPP).The Mobile Broadband Standard - Release 5.” 2002, Accessed 22.4.2020. [Online]. Available: <http://www.3gpp.org/release-5>
- [41] 3GPP, “The 3rd Generation Partnership Project (3GPP).The Mobile Broadband Standard - Release 6.” 2004, Accessed 22.4.2020. [Online]. Available: <http://www.3gpp.org/release-6>
- [42] S. Sonntag, L. Schulte, and J. Manner, “Mobile Network Measurements - It's Not All About Signal Strength,” in *IEEE Wireless Communications and Networking Conference (WCNC)*, 2013, pp. 4624–4629, Accessed 18.4.2020. [Online]. Available: <https://doi.org/10.1109/WCNC.2013.6555324>
- [43] Netradar, “Netradar,” Accessed 22.2.2020. [Online]. Available: <https://www.netradar.com/>
- [44] O. Alay, A. Lutu, D. Ros, R. Garcia, V. Mancuso, A. F. Hansen, A. Brunstrom, M. A. Marsan, and H. Lonsethagen, “MONROE: Measuring Mobile Broadband Networks in Europe,” in *Pro. of the IRTF & ISOC Workshop on Research and Applications of Internet Measurements (RAIM)*, 2015, Accessed 22.6.2020. [Online]. Available: <https://bit.ly/2QqqAmx>
- [45] J. Korhonen, T. Savolainen, and J. Soininen, *Deploying IPv6 in 3GPP networks: evolving mobile broadband from 2G to LTE and beyond*. John Wiley & Sons, 2013. [Online]. Available: <https://onlinelibrary.wiley.com/doi/abs/10.1002/9781118398333>
- [46] A. R. Mishra, *Cellular Technologies for Emerging Markets: 2G, 3G and Beyond*. John Wiley & Sons, Ltd, 2010. [Online]. Available: <https://onlinelibrary.wiley.com/doi/book/10.1002/9780470666234>
- [47] H. Holma and A. Toskala, *WCDMA for umts: hspa evolution and lte*. John Wiley & sons, 2007.
- [48] 3GPP, “The 3rd Generation Partnership Project (3GPP).The Mobile Broadband Standard - Release 99.” 2001, Accessed 22.4.2020. [Online]. Available: <https://www.3gpp.org/specifications/releases/77-release-1999>

- [49] 3GPP, “The 3rd Generation Partnership Project (3GPP).The Mobile Broadband Standard - Release 4.” 2016, Accessed 22.4.2020. [Online]. Available: <http://www.3gpp.org/release-4>
- [50] 3GPP, “The 3rd Generation Partnership Project (3GPP).The Mobile Broadband Standard - Release 7.” 2007, Accessed 22.4.2020. [Online]. Available: <http://www.3gpp.org/release-7>
- [51] Ericsson, “Mobile Subscriptions Worldwide Q3 2018,” 2018, Accessed 23.4.2019. [Online]. Available: <https://www.ericsson.com/en/mobility-report/reports/november-2018/mobile-subscriptions-worldwide-q3-2018>
- [52] ITU, “Measuring the Information Society Report Volume 1,” 2018, Accessed 22.4.2020. [Online]. Available: <https://www.itu.int/en/ITU-D/Statistics/Documents/events/wtis2018/MISR-2018-Vol-1-E.PDF>
- [53] 3GPP, “NR - Physical Channels and Modulation - Release 15, Version V15.2.0,” 2018, Accessed 22.4.2020. [Online]. Available: <https://www.3gpp.org/release-15>
- [54] 3GPP, “Service Requirements for the 5G System,” 2016, Accessed 22.4.2020. [Online]. Available: https://www.3gpp.org/news-events/3gpp-news/1831-sa1_5g
- [55] A. Ghosh, A. Mäder, M. Baker, and D. Chandramouli, “5g evolution: A view on 5g cellular technology beyond 3gpp release 15,” *IEEE Access*, vol. 7, pp. 127 639–127 651, 2019, Accessed 10.11.2020. [Online]. Available: <https://doi.org/10.1109/ACCESS.2019.2939938>
- [56] O. Simeone, E. Erkip, and S. Shamai, “Robust transmission and interference management for femtocells with unreliable network access,” *IEEE J. Sel. Areas Commun.*, vol. 28, no. 9, pp. 1469–1478, 2010. [Online]. Available: <https://doi.org/10.1109/JSAC.2010.101208>
- [57] H. Baur, “Heterogeneous networks - meeting mobile broadband expectations with maximum efficiency,” *Elektrotech. Informationstechnik*, vol. 129, no. 6, pp. 416–421, 2012. [Online]. Available: <https://doi.org/10.1007/s00502-012-0050-z>
- [58] A. S. Khatouni, M. Mellia, M. A. Marsan, S. Alfredsson, J. Karlsson, A. Brunström, O. Alay, A. Lutu, C. Midoglu, and V. Mancuso, “Speedtest-Like Measurements in 3G/4G Networks: The MONROE Experience,” in *International Teletraffic Congress*, 2017, pp. 169–177, Accessed 22.3.2020. [Online]. Available: <https://doi.org/10.23919/ITC.2017.8064353>
- [59] N. Becker, A. Rizk, and M. Fidler, “A Measurement Study on the Application-level Performance of LTE,” in *IFIP Networking Conference*, 2014, pp. 1–9, Accessed 23.3.2020. [Online]. Available: <https://doi.org/10.1109/IFIPNetworking.2014.6857113>
- [60] J. Garcia, S. Alfredsson, and A. Brunström, “A Measurement Based Study of TCP Protocol Efficiency in Cellular Networks,” in *Symposium on Modeling and Optimization in Mobile, Ad Hoc, and Wireless Networks, WiOpt*, 2014, pp. 131–136. [Online]. Available: <https://doi.org/10.1109/WIOPT.2014.6850290>
- [61] S. Sonntag, J. Manner, and L. Schulte, “Netradar - Measuring the Wireless World,” in *11th International Symposium and Workshops on Modeling and Optimization in Mobile, Ad Hoc and Wireless Networks, WiOpt*, 2013, pp. 29–34, Accessed 10.5.2020. [Online]. Available: <http://ieeexplore.ieee.org/document/6576402/>

- [62] Ookla , “speedtest.net,” 2006, Accessed 10.4.2020. [Online]. Available: www.speedtest.net
- [63] F. Li and D. Choffnes, “Measuring worldwide traffic differentiation policies,” *Available at SSRN 3142005*, 2018, Accessed 26.2.2021. [Online]. Available: <https://ssrn.com/abstract=3142005>
- [64] S. Bauer, D. D. Clark, and W. Lehr, “Understanding Broadband Speed Measurements.” *TPRC*, 2010, Accessed 23.4.2020. [Online]. Available: <https://ssrn.com/abstract=1988332>
- [65] M. Crovella and B. Krishnamurthy, *Internet Measurement - Infrastructure, Traffic, and Applications*. Wiley, 2006, Accessed 10.5.2020. [Online]. Available: <http://eu.wiley.com/WileyCDA/WileyTitle/productCd-EHEP001029.html>
- [66] C. Chaudet, E. Fleury, I. G. Lassous, H. Rivano, and M. Voge, “Optimal Positioning of Active and Passive Monitoring Devices,” in *Proceedings of the 2005 ACM Conference on Emerging Network Experiment and Technology, CoNEXT*, M. Diaz, A. Azcorra, P. Owezarski, and S. Fdida, Eds. ACM, 2005, pp. 71–82. [Online]. Available: <https://doi.org/10.1145/1095921.1095932>
- [67] A. Ziviani, “An Overview of Internet Measurements: Fundamentals, Techniques, and Trends,” *African J. of Inf. & Commun. Technology*, vol. 2, no. 1, 2006, Accessed 10.5.2020. [Online]. Available: <http://epress.lib.uts.edu.au/ojs/index.php/ajict/article/view/E112122006013>
- [68] C. Midoglu and P. Svoboda, “Opportunities and Challenges of Using Crowdsourced Measurements for Mobile Network Benchmarking a Case Study on RTR Open Data,” in *SAI Computing Conference (SAI)*. IEEE, 2016, pp. 996–1005.
- [69] J. Dugan, S. Elliott, B. Mah, J. Poskanzer, K. Prabhu *et al.*, “iperf-the ultimate speed test tool for tcp, udp and sctp,” 2020. [Online]. Available: <https://iperf.fr>
- [70] W. R. Stevens, *UNIX network programming, 2nd Edition*. Prentice Hall PTR, 1998. [Online]. Available: <http://www.worldcat.org/oclc/312737593>
- [71] A. Morton, “Active and passive metrics and methods (with hybrid types in-between),” *RFC*, vol. 7799, pp. 1–14, 2016. [Online]. Available: <https://doi.org/10.17487/RFC7799>
- [72] M. Allman and V. Paxson, “A reactive measurement framework,” in *Passive and Active Network Measurement, 9th International Conference, PAM 2008, Cleveland, OH, USA, April 29-30, 2008. Proceedings*, ser. Lecture Notes in Computer Science, M. Claypool and S. Uhlig, Eds., vol. 4979. Springer, 2008, pp. 92–101. [Online]. Available: https://doi.org/10.1007/978-3-540-79232-1_10
- [73] Z. Zhang, S. Shi, V. Gupta, and R. Jana, “Analysis of Cellular Network Latency for Edge-Based Remote Rendering Streaming Applications,” in *ACM SIGCOMM Workshop on Networking for Emerging Applications and Technologie*. ACM, 2019, pp. 8–14, Accessed 4.21.2020. [Online]. Available: <https://doi.org/10.1145/3341558.3342199>
- [74] J. Postel, “Internet Protocol,” *RFC*, vol. 791, pp. 1–51, 1981, Accessed 28.4.2020. [Online]. Available: <https://doi.org/10.17487/RFC0791>
- [75] J. Postel, “Transmission Control Protocol,” *RFC*, vol. 793, pp. 1–91, 1981. [Online]. Available: <https://doi.org/10.17487/RFC0793>

- [76] J. Manner and M. Kojo, "Mobility related terminology," *RFC*, vol. 3753, pp. 1–36, 2004. [Online]. Available: <https://doi.org/10.17487/RFC3753>
- [77] P. V. Mockapetris, "Domain Names - Concepts and Facilities," *RFC*, vol. 1034, pp. 1–55, 1987. [Online]. Available: <https://doi.org/10.17487/RFC1034>
- [78] J. Postel, "Domain Name System Structure and Delegation," *RFC*, vol. 1591, pp. 1–7, 1994. [Online]. Available: <https://doi.org/10.17487/RFC1591>
- [79] E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.3," *RFC*, vol. 8446, pp. 1–160, 2018. [Online]. Available: <https://doi.org/10.17487/RFC8446>
- [80] J. Salowey, H. Zhou, P. Eronen, and H. Tschofenig, "Transport layer security (TLS) session resumption without server-side state," *RFC*, vol. 5077, pp. 1–20, 2008. [Online]. Available: <https://doi.org/10.17487/RFC5077>
- [81] G. Almes, S. Kalidindi, and M. J. Zekauskas, "A One-way Packet Loss Metric for IPPM," *RFC*, vol. 2680, pp. 1–15, 1999, Accessed 27.5.2020. [Online]. Available: <https://doi.org/10.17487/RFC2680>
- [82] ITU-T, Telecommunication Standardization Sector of ITU , "Terms and Definitions Related to Quality of Sservice and Network Performance Including Dependability: ITU-T Recommendation E.800," *International Telecommunication Union, Tech. Rep.*, accessed 4.22.2020. [Online]. Available: <https://www.itu.int/rec/T-REC-E.800-199408-S/en>
- [83] M. Fiedler, K. Kilkki, and P. Reichl, Eds., *From Quality of Service to Quality of Experience, 05.05. - 08.05.2009*, vol. 09192. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, Germany, 2009, Accessed 16.4.2020. [Online]. Available: <http://drops.dagstuhl.de/portals/09192/>
- [84] A. Raake and S. Egger, "Quality and Quality of Experience," in *Quality of Experience*, 2014, pp. 11–33, Accessed 16.4.2020. [Online]. Available: https://doi.org/10.1007/978-3-319-02681-7_2
- [85] P. M. Jake Brutlag, Zoe Abrams, "Above the Fold Time, Measuring Web Page Performance Visually," 2011, Accessed 10.4.2020. [Online]. Available: <https://conferences.oreilly.com/velocity/velocity-mar2011>
- [86] A. Saverimoutou, B. Mathieu, and S. Vaton, "Web Browsing Measurements: An Above-the-Fold Browser-Based Technique," in *IEEE Conference on Distributed Computing Systems, ICDCS*, 2018, pp. 1630–1635, Accessed 10.4.2020. [Online]. Available: <https://doi.org/10.1109/ICDCS.2018.00184>
- [87] Google. (1993) Speed Index. Accessed 8.5.2020. [Online]. Available: <https://sites.google.com/a/webpagetest.org/docs/using-webpagetest/metrics/speed-index>
- [88] P. Brooks and B. Hestnes, "User Measures of Quality of Experience: Why Being Objective and Quantitative is Important," *IEEE Network*, vol. 24, no. 2, pp. 8–13, 2010, Accessed 23.5.2020. [Online]. Available: <https://doi.org/10.1109/MNET.2010.5430138>
- [89] D. Pal and V. Vanijja, "Effect of Network QoS on User QoE for a Mobile Video Streaming Service Using H. 265/VP9 Codec," *Procedia computer science*, vol. 111, pp. 214–222, 2017.

- [90] A. Nikraves, Q. A. Chen, S. Haseley, X. Zhu, G. Challen, and Z. M. Mao, "QoE Inference and Improvement Without End-Host Control," in *IEEE/ACM Symposium on Edge Computing, SEC*, 2018, pp. 43–57, Accessed 9.6.2020. [Online]. Available: <https://doi.org/10.1109/SEC.2018.00011>
- [91] ITU, Telecommunication Standardization Sector of ITUE, "ITU-T Recommendation P.800.1: Mean Opinion Score (MOS) Terminology," *International Telecommunication Union, Tech. Rep.*, vol. 800.1, 2016, Accessed 22.4.2020. [Online]. Available: <https://www.itu.int/rec/T-REC-P.800.1/en>
- [92] E. Halepovic, J. Pang, and O. Spatscheck, "Can you GET me now?: estimating the time-to-first-byte of HTTP transactions with passive measurements," in *Proceedings of the 12th ACM SIGCOMM Internet Measurement Conference, IMC*, J. W. Byers, J. Kurose, R. Mahajan, and A. C. Snoeren, Eds. ACM, 2012, pp. 115–122. [Online]. Available: <https://doi.org/10.1145/2398776.2398789>
- [93] J. Brutlag, Z. Abrams, and P. Meenan, "Above the fold time: Measuring web page performance visually," in *Velocity: Web Performance and Operations Conference*, 2011.
- [94] Z. Wang, "Navigation Timing," Tech. Rep., 2012, Accessed 26.5.2020. [Online]. Available: <https://www.w3.org/TR/navigation-timing/>
- [95] N. Vallina-Rodriguez, S. Sundaresan, C. Kreibich, N. Weaver, and V. Paxson, "Beyond the Radio: Illuminating the Higher Layers of Mobile Networks," in *Proceedings of the 13th Annual International Conference on Mobile Systems, Applications, and Services, MobiSys*, G. Borriello, G. Pau, M. Gruteser, and J. I. Hong, Eds. ACM, 2015, pp. 375–387. [Online]. Available: <https://doi.org/10.1145/2742647.2742675>
- [96] F. Michelinakis, H. Doroud, A. Razaghpanah, A. Lutu, N. Vallina-Rodriguez, P. Gill, and J. Widmer, "The Cloud that Runs the Mobile Internet: A Measurement Study of Mobile Cloud Services," in *IEEE Conference on Computer Communications, INFOCOM*. IEEE, 2018, pp. 1619–1627. [Online]. Available: <https://doi.org/10.1109/INFOCOM.2018.8485872>
- [97] N. T. Spring, R. Mahajan, and T. E. Anderson, "The Causes of Path Inflation," in *Proceedings of the ACM SIGCOMM Conference*, A. Feldmann, M. Zitterbart, J. Crowcroft, and D. Wetherall, Eds. ACM, 2003, pp. 113–124. [Online]. Available: <https://doi.org/10.1145/863955.863970>
- [98] K. Zarifis, T. Flach, S. Nori, D. R. Choffnes, R. Govindan, E. Katz-Bassett, Z. M. Mao, and M. Welsh, "Diagnosing path inflation of mobile client traffic," in *Passive and Active Measurement - 15th International Conference, PAM*, ser. Lecture Notes in Computer Science, M. Faloutsos and A. Kuzmanovic, Eds., vol. 8362. Springer, 2014, pp. 23–33. [Online]. Available: https://doi.org/10.1007/978-3-319-04918-2_3
- [99] J. P. Rula, F. E. Bustamante, and M. Steiner, "Cell spotting: Studying the Role of Cellular Networks in the Internet," in *Internet Measurement Conference, IMC*, S. Uhlig and O. Maennel, Eds. ACM, 2017, pp. 191–204. [Online]. Available: <https://doi.org/10.1145/3131365.3131402>
- [100] SamKnows One, "Samknows," Accessed 22.4.2019. [Online]. Available: <https://samknows.com/>

- [101] Cooperative Association for Internet Data Analysis (CAIDA), “Caida,” Accessed 22.4.2019. [Online]. Available: <http://www.caida.org/tools/>
- [102] RIPE, “Ripe ncc,” Accessed 22.4.2019. [Online]. Available: <https://atlas.ripe.net/>
- [103] S. Cho, R. Fontugne, K. Cho, A. Dainotti, and P. Gill, “BGP Hijacking Classification,” in *Network Traffic Measurement and Analysis Conference, TMA*, 2019, pp. 25–32, Accessed 22.6.2020. [Online]. Available: <https://doi.org/10.23919/TMA.2019.8784511>
- [104] A. Dhamdhere, D. D. Clark, A. Gamero-Garrido, M. J. Luckie, R. K. P. Mok, G. Akiwate, K. Gogia, V. Bajpai, A. C. Snoeren, and K. Claffy, “Inferring Persistent Interdomain Congestion,” in *ACM Special Interest Group on Data Communication, SIGCOMM*, 2018, pp. 1–15, Accessed 10.5.2020. [Online]. Available: <https://doi.org/10.1145/3230543.3230549>
- [105] J. Kepner, K. Cho, K. Claffy, V. Gadepally, P. Michaleas, and L. Milechin, “Hypersparse Neural Network Analysis of Large-Scale Internet Traffic,” in *IEEE High Performance Extreme Computing Conference (HPEC)*, 2019. [Online]. Available: https://www.caida.org/publications/papers/2019/hypersparse_neural_network_analysis/
- [106] Archipelago (Ark), “Archipelago (Ark) Measurement Infrastructure,” Accessed 22.4.2019. [Online]. Available: <http://www.caida.org/projects/ark/>
- [107] M. Gharaibeh, A. Shah, B. Huffaker, H. Zhang, R. Ensafi, and C. Papadopoulos, “A Look at Router Geolocation in Public and Commercial Databases,” in *ACM SIGCOMM Internet Measurement Conference, IMC*, 2017, pp. 463–469, Accessed 22.6.2020. [Online]. Available: <https://doi.org/10.1145/3131365.3131380>
- [108] M. A. Sánchez, J. S. Otto, Z. S. Bischof, and F. E. Bustamante, “Trying Broadband Characterization at Home,” in *Passive and Active Measurement Conference, PAM*, 2013, pp. 198–207, Accessed 10.5.2020. [Online]. Available: https://doi.org/10.1007/978-3-642-36516-4_20
- [109] S. Sundaresan, N. Magharei, N. Feamster, R. Teixeira, and S. Crawford, “Web Performance Bottlenecks in Broadband Access Networks,” in *ACM Conference on Measurement and Modeling of Computer Systems (SIGMETRICS)*, 2013, pp. 383–384, Accessed 10.5.2020. [Online]. Available: <https://doi.org/10.1145/2465529.2465745>
- [110] I. Canadi, P. Barford, and J. Sommers, “Revisiting Broadband Performance,” in *Pro. of the 12th ACM SIGCOMM Internet Measurement Conference, IMC*, 2012, pp. 273–286, Accessed 10.5.2020. [Online]. Available: <https://doi.org/10.1145/2398776.2398805>
- [111] T. Sultanov and P. Veselovskiy, “Packet-pair Technique for Available Bandwidth Estimation in IPv6 Network,” *CoRR*, vol. abs/1102.3533, 2011, Accessed 10.5.2020. [Online]. Available: <http://arxiv.org/abs/1102.3533>
- [112] V. Bajpai, S. J. Eravuchira, and J. Schönwälder, “Dissecting Last-mile Latency Characteristics,” *Computer Communication Review*, vol. 47, no. 5, pp. 25–34, 2017, Accessed 10.5.2020. [Online]. Available: <https://doi.org/10.1145/3155055.3155059>
- [113] V. Bajpai, S. J. Eravuchira, J. Schönwälder, R. Kisteleki, and E. Aben, “Vantage Point Selection for IPv6 Measurements: Benefits and Limitations of RIPE

- Atlas tags,” in *IFIP/IEEE Symposium on Integrated Network and Service Management (IM)*, 2017, pp. 37–44, Accessed 20.3.2020. [Online]. Available: <https://doi.org/10.23919/INM.2017.7987262>
- [114] A. Filastò and J. Appelbaum, “OONI: open observatory of network interference,” in *2nd USENIX Workshop on Free and Open Communications on the Internet, FOCI*, R. Dingleline and J. Wright, Eds. USENIX Association, 2012. [Online]. Available: <https://www.usenix.org/conference/foci12/workshop-program/presentation/filast%C3%B2>
- [115] B. N. Chun, D. E. Culler, T. Roscoe, A. C. Bavier, L. L. Peterson, M. Wawrzoniak, and M. Bowman, “Planetlab: an overlay testbed for broad-coverage services,” *Comput. Commun. Rev.*, vol. 33, no. 3, pp. 3–12, 2003. [Online]. Available: <https://doi.org/10.1145/956993.956995>
- [116] C. Dovrolis, P. K. Gummadi, A. Kuzmanovic, and S. D. Meinrath, “Measurement lab: overview and an invitation to the research community,” *Comput. Commun. Rev.*, vol. 40, no. 3, pp. 53–56, 2010. [Online]. Available: <https://doi.org/10.1145/1823844.1823853>
- [117] U. Goel, M. P. Wittie, K. C. Claffy, and A. Le, “Survey of End-to-End Mobile Network Measurement Testbeds, Tools, and Services,” *IEEE Communications Surveys and Tutorials*, vol. 18, no. 1, pp. 105–123, 2016, Accessed 12.4.2020. [Online]. Available: <https://doi.org/10.1109/COMST.2015.2485979>
- [118] E. Oy. (2017) Mobiili OmaElisa. Accessed 26.5.2019. [Online]. Available: <https://verkkoasiointi.elisa.fi/>
- [119] A. R. A. for Broadcasting and Telecommunications, “RTR Nettest Measurement Platform,” Accessed 8.2.2019. [Online]. Available: <https://www.netztest.at/en/>
- [120] C. Sölder, L. Wimmer, D. Zlabinger, U. Latzenhofer, U. Prinzl, and P. Sandner, “RTR Multithreaded Broadband Test (RMBT)–Specification,” 2017, Accessed 2.8.2019. [Online]. Available: <https://www.netztest.at/doc/>
- [121] Google/M-Labs and Dave Choffnes and Michigan, “The M-Lab MobiPerf Data Set,” Accessed 14.4.2020. [Online]. Available: <https://measurementlab.net/tests/mobiperf>
- [122] A. Nikraves, H. Yao, S. Xu, D. R. Choffnes, and Z. M. Mao, “Mobilyzer: An Open Platform for Controllable Mobile Network Measurements,” in *MobiSys Conference on Mobile Systems, Applications, and Services*. ACM, 2015, pp. 389–404, Accessed 22.4.2020. [Online]. Available: <https://doi.org/10.1145/2742647.2742670>
- [123] C. Kreibich, N. Weaver, B. Nechaev, and V. Paxson, “Netalyzr: Illuminating the Edge Network,” in *ACM SIGCOMM Internet Measurement Conference, IMC*, 2010, pp. 246–259, Accessed 10.4.2020. [Online]. Available: <https://doi.org/10.1145/1879141.1879173>
- [124] C. Kreibich, N. Weaver, G. Maier, B. Nechaev, and V. Paxson, “Experiences from Netalyzr with Engaging Users in End-system Measurement,” in *Pro. of the first ACM SIGCOMM workshop on Measurements up the stack, W-MUST@SIGCOMM*, 2011, pp. 25–30, Accessed 10.4.2020. [Online]. Available: <https://doi.org/10.1145/2018602.2018609>
- [125] Speed Test, “Measuring Broadband America,” Accessed 4.15.2020. [Online]. Available: <https://www.fcc.gov/general/measuring-broadband-america>

- [126] A. Kvalbein, D. Baltrunas, K. Evensen, J. Xiang, A. Elmokashfi, and S. F. Oliveira, "The NorNet Edge Platform for Mobile Broadband Measurements," *Computer Networks*, vol. 61, pp. 88–101, 2014, Accessed 10.5.2020. [Online]. Available: <https://doi.org/10.1016/j.bjp.2013.12.036>
- [127] C. Midoglu, L. Wimmer, A. Lutu, O. Alay, and C. Griwodz, "MONROE-Nettest: A Configurable Tool for Dissecting Speed Measurements in Mobile Broadband Networks," in *IEEE INFOCOM Computer Communications Workshops*, 2018, pp. 342–347, Accessed 10.6.2020. [Online]. Available: <https://doi.org/10.1109/INFCOMW.2018.8406836>
- [128] N. Larson, D. Baltrunas, A. Kvalbein, A. Dhamdhere, k. claffy, and A. Elmokashfi, "Investigating excessive delays in mobile broadband networks," in *Proceedings of the 5th Workshop on All Things Cellular: Operations, Applications and Challenges*. Association for Computing Machinery, 2015, p. 51–56, Accessed 10.4.2020. [Online]. Available: <https://doi.org/10.1145/2785971.2785980>
- [129] Speedchecker Limited, "Broadband Speedchecker ," Accessed 21.4.2019. [Online]. Available: <http://www.broadbandspeedchecker.co.uk/>
- [130] V. Bajpai and J. Schönwälder, "IPv4 versus IPv6 - Who Connects Faster?" in *Pro. of the 14th IFIP Networking Conference, Networking*, 2015, pp. 1–9, Accessed 10.4.2020. [Online]. Available: <https://doi.org/10.1109/IFIPNetworking.2015.7145323>
- [131] A. S. Asrese, "WebLAR: A Web Performance Measurement Tool," 2019, Accessed 22.4.2019. [Online]. Available: <https://github.com/alemnew/weblar>
- [132] A. S. Asrese, P. Sarolahti, M. Boye, and J. Ott, "WePR: A Tool for Automated Web Performance Measurement," in *IEEE Globecom Workshops*, 2016, pp. 1–6, Accessed 10.5.2020. [Online]. Available: <https://doi.org/10.1109/GLOCOMW.2016.7849082>
- [133] FFmpeg, "FFmpeg: A Complete, Cross-platform Solution to Record, Convert and Stream Audio and Video," Retrieved October 12, 2018. [Online]. Available: <https://ffmpeg.org>
- [134] ImageMagick, "ImageMagick: Tool to Create, Edit, Compose, or Convert Bitmap Images," 2019, Accessed 22.4.2019. [Online]. Available: <https://imagemagick.org>
- [135] D. N. da Hora, A. S. Asrese, V. Christophides, R. Teixeira, and D. Rossi, "Narrowing the Gap Between QoS Metrics and Web QoE Using Above-the-fold Metrics," in *Passive and Active Measurement Conference, PAM*, 2018, pp. 31–43, Accessed 10.4.2020. [Online]. Available: https://doi.org/10.1007/978-3-319-76481-8_3
- [136] M. Hirth, T. Hoßfeld, M. Mellia, C. Schwartz, and F. Lehrieder, "Crowdsourced Network Measurements: Benefits and Best Practices," *Computer Networks*, vol. 90, pp. 85–98, 2015, Accessed 21.3.2020. [Online]. Available: <https://doi.org/10.1016/j.comnet.2015.07.003>
- [137] S. Sen, J. Yoon, J. Hare, J. Ormont, and S. Banerjee, "Can They Hear Me Now?: A Case for a Client-assisted Approach to Monitoring Wide-area Wireless Networks," in *ACM SIGCOMM Internet Measurement Conference, IMC*, 2011, pp. 99–116. [Online]. Available: <https://doi.org/10.1145/2068816.2068827>

- [138] M. Z. Shafiq, L. Ji, A. X. Liu, J. Pang, S. Venkataraman, and J. Wang, “A First Look at Cellular Network Performance During Crowded Events,” in *ACM Conference on Measurement and Modeling of Computer Systems (SIGMETRICS)*, 2013, pp. 17–28. [Online]. Available: <https://doi.org/10.1145/2465529.2465754>
- [139] D. Baltrunas, A. Elmokashfi, and A. Kvalbein, “Measuring the Reliability of Mobile Broadband Networks,” in *ACM SIGCOMM Internet Measurement Conference, IMC*, 2014, pp. 45–58, Accessed 10.5.2020. [Online]. Available: <https://doi.org/10.1145/2663716.2663725>
- [140] A. Balachandran, V. Aggarwal, E. Halepovic, J. Pang, S. Seshan, S. Venkataraman, and H. Yan, “Modeling Web Quality-of-Experience on Cellular Networks,” in *The 20th Annual International Conference on Mobile Computing and Networking, MobiCom*, 2014, pp. 213–224, Accessed 10.5.2020. [Online]. Available: <https://doi.org/10.1145/2639108.2639137>
- [141] I. Safiulin, S. Schwarz, and M. Rupp, “System Level Simulation of LTE MBSFN Networks with High Mobility Users,” in *International Conference on Systems, Signals and Image Processing, IWSSIP*, 2015, pp. 21–24. [Online]. Available: <https://doi.org/10.1109/IWSSIP.2015.7313927>
- [142] M. P. Wylie-Green and T. Svensson, “Throughput, Capacity, Handover and Latency Performance in a 3GPP LTE FDD Field Trial,” in *Global Communications Conference, GLOBECOM*, 2010, pp. 1–6, Accessed 20.3.2020. [Online]. Available: <https://doi.org/10.1109/GLOCOM.2010.5683398>
- [143] G. Sezgin, Y. Coskun, E. Basar, and G. K. Kurt, “Performance Evaluation of a Live Multi-Site LTE Network,” *IEEE Access*, vol. 6, pp. 49 690–49 704, 2018, Accessed 20.3.2020. [Online]. Available: <https://doi.org/10.1109/ACCESS.2018.2868385>
- [144] ETSI, “Key Performance Indicators (KPI) for Evolved Universal Terrestrial Radio Access Network (E UTRAN): Definitions Release 9,” 2010, Accessed 24.4.2020. [Online]. Available: https://www.etsi.org/deliver/etsi_ts/132400_132499/132450/09.03.00_60/ts_132450v090300p.pdf
- [145] R. Enami, D. Rajan, and J. Camp, “RAIK: Regional Analysis with Geodata and Crowdsourcing to Infer Key Performance Indicators,” in *IEEE Wireless Communications and Networking Conference, WCNC*, 2018, pp. 1–6, Accessed 18.4.2020. [Online]. Available: <https://doi.org/10.1109/WCNC.2018.8377405>
- [146] 3GPP, “Universal Mobile Telecommunications System (UMTS); LTE; Requirements for Evolved UTRA (E-UTRA) and Evolved UTRAN (E-UTRAN),” 2013, Accessed 22.4.2019. [Online]. Available: <http://www.3gpp.org/DynaReport/25913.htm>
- [147] L. Li, K. Xu, D. Wang, C. Peng, Q. Xiao, and R. Mijumbi, “A Measurement Study on TCP Behaviors in HSPA+ Networks on High-Speed Rails,” in *IEEE Conference on Computer Communications, INFOCOM*, 2015, pp. 2731–2739, Accessed 25.2.2020. [Online]. Available: <https://doi.org/10.1109/INFOCOM.2015.7218665>
- [148] E. Atxutegi, F. Liberal, K. Grinnemo, A. Brunström, Å. Arvidsson, and R. Robert, “TCP Behaviour in LTE: Impact of Flow Start-up and Mobility,” in *9th IFIP Wireless and Mobile Networking Conference, WMNC*, 2016, pp. 73–80, Accessed 13.5.2020. [Online]. Available: <https://doi.org/10.1109/WMNC.2016.7543932>

- [149] L. Li, K. Xu, D. Wang, C. Peng, K. Zheng, R. Mijumbi, and Q. Xiao, “A Longitudinal Measurement Study of TCP Performance and Behavior in 3G/4G Networks Over High Speed Rails,” *IEEE/ACM Trans. Netw.*, vol. 25, no. 4, pp. 2195–2208, 2017. [Online]. Available: <https://doi.org/10.1109/TNET.2017.2689824>
- [150] S. Ha, I. Rhee, and L. Xu, “CUBIC: a New TCP-friendly High-speed TCP Variant,” *Operating Systems Review*, vol. 42, no. 5, pp. 64–74, 2008, Accessed 21.5.2020. [Online]. Available: <http://doi.acm.org/10.1145/1400097.1400105>
- [151] N. Cardwell, Y. Cheng, C. S. Gunn, S. H. Yeganeh, and V. Jacobson, “BBR: Congestion-Based Congestion Control,” *ACM Queue*, vol. 14, no. 5, pp. 20–53, 2016, Accessed 21.5.2020. [Online]. Available: <http://doi.acm.org/10.1145/3012426.3022184>
- [152] E. Atxutegi, Å. Arvidsson, F. Liberal, K. Grinnemo, and A. Brunström, “TCP Performance over Current Cellular Access: A Comprehensive Analysis,” in *Autonomous Control for a Reliable Internet of Services - Methods, Models, Approaches, Techniques, Algorithms, and Tools*, 2018, pp. 371–400, Accessed 10.5.2020. [Online]. Available: https://doi.org/10.1007/978-3-319-90415-3_14
- [153] T. R. Henderson, S. Floyd, A. V. Gurtov, and Y. Nishida, “The NewReno Modification to TCP’s Fast Recovery Algorithm,” *RFC*, vol. 6582, pp. 1–16, 2012, Accessed 25.2.2020. [Online]. Available: <https://doi.org/10.17487/RFC6582>
- [154] S. Mascolo, C. Casetti, M. Gerla, M. Y. Sanadidi, and R. Wang, “TCP Westwood: Bandwidth Estimation for Enhanced Transport over Wireless Links,” in *MOBICOM Conference on Mobile Computing and Networking*, 2001, pp. 287–297, Accessed 25.2.2020. [Online]. Available: <https://doi.org/10.1145/381677.381704>
- [155] D. Baltrunas, A. Elmokashfi, A. Kvalbein, and Ö. Alay, “Investigating Packet Loss in Mobile Broadband Networks Under Mobility,” in *IFIP Networking Conference and Workshops*, 2016, pp. 225–233, Accessed 22.4.2020. [Online]. Available: <https://doi.org/10.1109/IFIPNetworking.2016.7497225>
- [156] L. Li, K. Xu, D. Wang, C. Peng, K. Zheng, H. Wang, R. Mijumbi, and X. Wang, “A Measurement Study on Skype Voice and Video Calls in LTE Networks on High Speed Rails,” in *IEEE/ACM Symposium on Quality of Service, IWQoS*, 2017, pp. 1–10, Accessed 12.4.2020. [Online]. Available: <https://doi.org/10.1109/IWQoS.2017.7969110>
- [157] P. Wuttidittachotti and T. Daengsi, “QoE of Social Network Applications: A Study of VoIP Quality from Skype vs LINE over 3G and 4G,” in *International Conference on Ubiquitous and Future Networks*, 2015, pp. 462–464, Accessed 23.3.2020. [Online]. Available: <https://doi.org/10.1109/ICUFN.2015.7182586>
- [158] R. Merz, D. Wenger, D. Scanferla, and S. Mauron, “Performance of LTE in a High-velocity Environment: A Measurement Study,” in *Workshop on All Things Cellular*, 2014, pp. 47–52, Accessed 25.2.2020. [Online]. Available: <https://doi.org/10.1145/2627585.2627589>
- [159] D. Baltrunas, A. Elmokashfi, and A. Kvalbein, “Dissecting Packet Loss in Mobile Broadband Networks from the Edge,” in *IEEE Conference on Computer Communications, INFOCOM*, 2015, pp. 388–396, Accessed 10.5.2020. [Online]. Available: <https://doi.org/10.1109/INFOCOM.2015.7218404>

- [160] N. Weaver, C. Kreibich, M. Dam, and V. Paxson, "Here Be Web Proxies," in *Passive and Active Measurement - 15th International Conference, PAM*, ser. Lecture Notes in Computer Science, M. Faloutsos and A. Kuzmanovic, Eds., vol. 8362. Springer, 2014, pp. 183–192. [Online]. Available: https://doi.org/10.1007/978-3-319-04918-2_18
- [161] X. Xu, Y. Jiang, T. Flach, E. Katz-Bassett, D. R. Choffnes, and R. Govindan, "Investigating Transparent Web Proxies in Cellular Networks," in *Passive and Active Measurement Conference, PAM*, 2015, pp. 262–276, Accessed 22.4.2020. [Online]. Available: https://doi.org/10.1007/978-3-319-15509-8_20
- [162] M. Akselrod, N. Becker, M. Fidler, and R. Lübben, "4G LTE on the Road - What Impacts Download Speeds Most?" in *86th IEEE Vehicular Technology Conference, VTC*, 2017, pp. 1–6, Accessed 25.5.2020. [Online]. Available: <https://doi.org/10.1109/VTCFall.2017.8288296>
- [163] V. Raida, M. Lerch, P. Svoboda, and M. Rupp, "Deriving Cell Load from RSRQ Measurements," in *Network Traffic Measurement and Analysis Conference, TMA*. IEEE, 2018, pp. 1–6, Accessed 18.4.2020. [Online]. Available: <https://doi.org/10.23919/TMA.2018.8506494>
- [164] C. Ide, R. Falkenberg, D. Kaulbars, and C. Wietfeld, "Empirical Analysis of the Impact of LTE Downlink Channel Indicators on the Uplink Connectivity," in *IEEE 83rd Vehicular Technology Conference, VTC*, 2016, pp. 1–5, Accessed 18.4.2020. [Online]. Available: <https://doi.org/10.1109/VTCSpring.2016.7504211>
- [165] J. Caine, B. Gill, S. Johnston, J. Robinson, and S. Westwood, "Modelling Download Throughput of LTE Networks," in *IEEE Conference on Local Computer Networks*, 2014, pp. 623–628, Accessed 10.5.2020. [Online]. Available: <https://doi.org/10.1109/LCNW.2014.6927712>
- [166] OpenSignal, "OpenSignal," 2014, Accessed 22.4.2020. [Online]. Available: <http://opensignal.com/>
- [167] J. Huang, F. Qian, A. Gerber, Z. M. Mao, S. Sen, and O. Spatscheck, "A Close Examination of Performance and Power Characteristics of 4G LTE Networks," in *Mobile Systems, Applications, and Services, MobiSys*, 2012, pp. 225–238, Accessed 25.2.2020. [Online]. Available: <https://doi.org/10.1145/2307636.2307658>
- [168] E. J. Vergara and S. Nadjm-Tehrani, "EnergyBox: A Trace-Driven Tool for Data Transmission Energy Consumption Studies," in *Energy Efficiency in Large Scale Distributed Systems - COST IC0804*, ser. Lecture Notes in Computer Science, J. Pierson, G. D. Costa, and L. Dittmann, Eds., vol. 8046. Springer, 2013, pp. 19–34. [Online]. Available: https://doi.org/10.1007/978-3-642-40517-4_2
- [169] N. Balasubramanian, A. Balasubramanian, and A. Venkataramani, "Energy Consumption in Mobile Phones: a Measurement Study and Implications for Network Applications," in *ACM SIGCOMM Internet Measurement Conference, IMC*, A. Feldmann and L. Mathy, Eds. ACM, 2009, pp. 280–293. [Online]. Available: <https://doi.org/10.1145/1644893.1644927>
- [170] R. Mittal, A. Kansal, and R. Chandra, "Empowering Developers to Estimate App Energy Consumption," in *(MobiCom) Mobile Computing and Networking*, 2012, pp. 317–328, Accessed 20.3.2020. [Online]. Available: <https://doi.org/10.1145/2348543.2348583>

- [171] T. A. Dao, I. Singh, H. V. Madhyastha, S. V. Krishnamurthy, G. Cao, and P. Mohapatra, "TIDE: A User-Centric Tool for Identifying Energy Hungry Applications on Smartphones," *IEEE/ACM Trans. Netw.*, vol. 25, no. 3, pp. 1459–1474, 2017, Accessed 20.3.2020.
- [172] N. Bui, F. Michelinakis, and J. Widmer, "A model for throughput prediction for mobile users," in *European Wireless 2014; 20th European Wireless Conference*, 2014, pp. 1–6.
- [173] X. K. Zou, J. Erman, V. Gopalakrishnan, E. Halepovic, R. Jana, X. Jin, J. Rexford, and R. K. Sinha, "Can Accurate Predictions Improve Video Streaming in Cellular Networks?" in *(HotMobile)Workshop on Mobile Computing Systems and Applications*, 2015, pp. 57–62. [Online]. Available: <https://doi.org/10.1145/2699343.2699359>
- [174] F. Michelinakis, N. Bui, G. Fioravanti, J. Widmer, F. Kaup, and D. Hausheer, "Lightweight mobile bandwidth availability measurement," in *Proceedings of the 14th IFIP Networking Conference*. IEEE Computer Society, 2015, pp. 1–9. [Online]. Available: <https://doi.org/10.1109/IFIPNetworking.2015.7145324>
- [175] F. Kaup, F. Michelinakis, N. Bui, J. Widmer, K. Wac, and D. Hausheer, "Assessing the implications of cellular network performance on mobile content access," *IEEE Trans. Netw. Serv. Manag.*, vol. 13, no. 2, pp. 168–180, 2016. [Online]. Available: <https://doi.org/10.1109/TNSM.2016.2544402>
- [176] H. Elsherbiny, H. M. Abbas, H. Abou-zeid, H. S. Hassanein, and A. Noureldin, "4g LTE network throughput modelling and prediction," in *IEEE Global Communications Conference, GLOBECOM 2020, Virtual Event, Taiwan, December 7-11, 2020*. IEEE, 2020, pp. 1–6. [Online]. Available: <https://doi.org/10.1109/GLOBECOM42002.2020.9322410>
- [177] Y. Cao, J. Nejati, M. Wajahat, A. Balasubramanian, and A. Gandhi, "Deconstructing the Energy Consumption of the Mobile Page Load," *POMACS*, vol. 1, no. 1, pp. 6:1–6:25, 2017, Accessed 23.3.2020. [Online]. Available: <https://doi.org/10.1145/3084443>
- [178] Facebook , "Facebook Instant Articles," 2015, Accessed 22.4.2019. [Online]. Available: <https://instantarticles.fb.com/>
- [179] A. Bovens, "Opera Browsers, Modes and Engines," 2015, Accessed 22.4.2019. [Online]. Available: <https://dev.opera.com/articles/browsers-modes-engines/>
- [180] Christine Chun , " Google AMP Yields 600% Increase on Mobile Site Page Load Speed," 2018, Accessed 22.4.2019. [Online]. Available: <https://tinyurl.com/y7kw3am5>
- [181] A. Balachandran, V. Sekar, A. Akella, S. Seshan, I. Stoica, and H. Zhang, "Developing a Predictive Model of Quality of Experience for Internet Video," in *ACM SIGCOMM Conference*, 2013, pp. 339–350, Accessed 10.5.2020. [Online]. Available: <https://doi.org/10.1145/2486001.2486025>
- [182] P. Casas, M. Seufert, and R. Schatz, "YOUQMON: A System for On-line Monitoring of YouTube QoE in Operational 3G Networks," *SIGMETRICS Perform. Eval. Rev.*, vol. 41, no. 2, pp. 44–46, 2013, Accessed 23.4.2020. [Online]. Available: <http://doi.acm.org/10.1145/2518025.2518033>

- [183] M. Z. Shafiq, J. Erman, L. Ji, A. X. Liu, J. Pang, and J. Wang, "Understanding the Impact of Network Dynamics on Mobile Video User Engagement," in *ACM Conference on Measurement and Modeling of Computer Systems SIGMETRICS*, 2014, pp. 367–379, Accessed 12.4.2020. [Online]. Available: <https://doi.org/10.1145/2591971.2591975>
- [184] F. Wamser, M. Seufert, P. Casas, R. Irmer, P. Tran-Gia, and R. Schatz, "YoMoApp: A Tool for Analyzing QoE of YouTube HTTP Adaptive Streaming in Mobile Networks," in *European Conference on Networks and Communications*, 2015, pp. 239–243, Accessed 23.4.2020. [Online]. Available: <https://doi.org/10.1109/EuCNC.2015.7194076>
- [185] V. Aggarwal, E. Halepovic, J. Pang, S. Venkataraman, and H. Yan, "Prometheus: Toward Quality-of-Experience Estimation for Mobile Apps from Passive Network Measurements," in *15th Workshop on Mobile Computing Systems and Applications, HotMobile*, 2014, pp. 18:1–18:6, Accessed 21.5.2020. [Online]. Available: <https://doi.org/10.1145/2565585.2565600>
- [186] P. Casas, A. D'Alconzo, F. Wamser, M. Seufert, B. Gardlo, A. Schwind, P. Tran-Gia, and R. Schatz, "Predicting QoE in Cellular Networks Using Machine Learning and in-Smartphone Measurements," 2017, pp. 1–6, Accessed 21.5.2020. [Online]. Available: <https://doi.org/10.1109/QoMEX.2017.7965687>
- [187] E. Boz, B. Finley, A. Oulasvirta, K. Kilkki, and J. Manner, "Mobile QoE Prediction in the Field," *Pervasive and Mobile Computing*, vol. 59, p. 101039, 2019, Accessed 23.3.2020. [Online]. Available: <http://www.sciencedirect.com/science/article/pii/S1574119218307673>
- [188] Y. Qiao, Y. Cheng, J. Yang, J. Liu, and N. Kato, "A Mobility Analytical Framework for Big Mobile Data in Densely Populated Area," *IEEE Trans. Vehicular Technology*, vol. 66, no. 2, pp. 1443–1455, 2017. [Online]. Available: <https://doi.org/10.1109/TVT.2016.2553182>
- [189] M. González, C. Hidalgo, and A. Barabási, "Understanding Individual Human Mobility Patterns," *Nature*, vol. 453, no. 7196, pp. 779–782, 2008, Accessed 23.5.2020. [Online]. Available: <https://doi.org/10.1038/nature06958>
- [190] X. Zhou, Z. Zhao, R. Li, Y. Zhou, J. Palicot, and H. Zhang, "Human Mobility Patterns in Cellular Networks," *IEEE Communications Letters*, vol. 17, no. 10, pp. 1877–1880, 2013. [Online]. Available: <https://doi.org/10.1109/LCOMM.2013.090213.130924>
- [191] J. Yang, Y. Qiao, X. Zhang, H. He, F. Liu, and G. Cheng, "Characterizing User Behavior in Mobile Internet," *IEEE Trans. Emerging Topics Comput.*, vol. 3, no. 1, pp. 95–106, 2015. [Online]. Available: <https://doi.org/10.1109/TETC.2014.2381512>
- [192] U. Paul, A. P. Subramanian, M. M. Buddhikot, and S. R. Das, "Understanding Traffic Dynamics in Cellular Data Networks," in *IEEE Computer and Communications Societies (INFOCOM)*, 2011, pp. 882–890. [Online]. Available: <https://doi.org/10.1109/INFOCOM.2011.5935313>
- [193] E. M. R. Oliveira, A. C. Viana, K. P. Naveen, and C. Sarraute, "Measurement-driven Mobile Data Traffic Modeling in a Large Metropolitan Area," in *Pervasive Computing and Communications (PerCom)*, 2015, pp. 230–235. [Online]. Available: <https://doi.org/10.1109/PERCOM.2015.7146533>

- [194] A. Lutu, D. Perino, M. Bagnulo, E. Frías-Martínez, and J. Khangosstar, “A characterization of the COVID-19 pandemic impact on a mobile network operator traffic,” in *IMC '20: ACM Internet Measurement Conference*. ACM, 2020, pp. 19–33, Accessed 10.12.2020. [Online]. Available: <https://doi.org/10.1145/3419394.3423655>
- [195] X. Wang, A. V. Vasilakos, M. Chen, Y. Liu, and T. T. Kwon, “A survey of green mobile networks: Opportunities and challenges,” *Mob. Networks Appl.*, vol. 17, no. 1, pp. 4–20, 2012. [Online]. Available: <https://doi.org/10.1007/s11036-011-0316-4>
- [196] S. Neumeier, E. A. Walelgne, V. Bajpai, J. Ott, and C. Facchi, “Measuring the feasibility of teleoperated driving in mobile networks,” in *Network Traffic Measurement and Analysis Conference, TMA 2019, Paris, France, June 19-21, 2019*, S. Secci, I. Chrisment, M. Fiore, L. Tabourier, and K. Lim, Eds. IEEE, 2019, pp. 113–120. [Online]. Available: <https://doi.org/10.23919/TMA.2019.8784466>
- [197] H. Lundqvist, J. E. Håkegård, and A. Lie, “Mobile Networks for Smart Grid Revisited,” in *2020 6th IEEE International Energy Conference (ENERGYCon)*, 2020, pp. 882–887.
- [198] A. Liaw, M. Wiener *et al.*, “Classification and regression by randomforest,” *R news*, vol. 2, no. 3, pp. 18–22, 2002. [Online]. Available: https://cran.r-project.org/doc/Rnews/Rnews_2002-3.pdf
- [199] I. H. Witten, F. Eibe, and M. A. Hall, *Data mining: practical machine learning tools and techniques, 3rd Edition*. Morgan Kaufmann, Elsevier, 2011. [Online]. Available: <http://www.worldcat.org/oclc/262433473>
- [200] F. Qian, Z. Wang, A. Gerber, Z. M. Mao, S. Sen, and O. Spatscheck, “Characterizing radio resource allocation for 3g networks,” in *Proceedings of the 10th ACM SIGCOMM Internet Measurement Conference, IMC*, M. Allman, Ed. ACM, 2010, pp. 137–150. [Online]. Available: <https://doi.org/10.1145/1879141.1879159>
- [201] V. Mancuso and S. Alouf, “Reducing costs and pollution in cellular networks,” *IEEE Commun. Mag.*, vol. 49, no. 8, pp. 63–71, 2011. [Online]. Available: <https://doi.org/10.1109/MCOM.2011.5978417>
- [202] A. Agresti and M. Kateri, “Categorical Data Analysis,” in *International Encyclopedia of Statistical Science*, 2011, pp. 206–208, Accessed 21.3.2020. [Online]. Available: https://doi.org/10.1007/978-3-642-04898-2_161
- [203] H. Keselman and J. C. Rogan, “The tukey multiple comparison test: 1953–1976,” *Psychological Bulletin*, vol. 84, no. 5, p. 1050, 1977. [Online]. Available: <https://doi.org/10.1037/0033-2909.84.5.1050>
- [204] M. Kuhn, “Building Predictive Models in R Using the caret Package,” *Journal of Statistical Software*, vol. 28, no. 5, pp. 1–26, 2008. [Online]. Available: <https://www.jstatsoft.org/article/view/v028i05>
- [205] M. A. El-Gendy, A. Bose, and K. G. Shin, “Evolution of the Internet QoS and Support for Soft Real-time Applications,” *Pro. of the IEEE*, vol. 91, no. 7, pp. 1086–1104, 2003. [Online]. Available: <http://ieeexplore.ieee.org/abstract/document/1215688/>

- [206] J. NIELSEN. (1993) Response Times: The 3 Important Limits. Accessed 6.9.2020. [Online]. Available: <https://www.nngroup.com/articles/powers-of-10-time-scales-in-ux/>
- [207] H. Jiang, Y. Wang, K. Lee, and I. Rhee, "Tackling Bufferbloat in 3G/4G Networks," in *ACM SIGCOMM Internet Measurement Conference, IMC*, 2012, pp. 329–342, Accessed 10.4.2020. [Online]. Available: <https://doi.org/10.1145/2398776.2398810>
- [208] H. Im, C. Joo, T. Lee, and S. Bahk, "Receiver-Side TCP Countermeasure to Bufferbloat in Wireless Access Networks," *IEEE Trans. Mob. Comput.*, vol. 15, no. 8, pp. 2080–2093, 2016, Accessed 10.4.2020. [Online]. Available: <https://doi.org/10.1109/TMC.2015.2483494>
- [209] S. Abbasloo, T. Li, Y. Xu, and H. J. Chao, "Cellular Controlled Delay TCP (C2TCP)," in *17th International IFIP TC6 Networking Conference, Networking*, 2018, pp. 118–126, Accessed 28.4.2020. [Online]. Available: <https://doi.org/10.23919/IFIPNetworking.2018.8696844>
- [210] T. Blajić, D. Nogulić, and M. Družijanić, "Latency Improvements in 3G Long Term Evolution," in *Proc. Int. Conv. Inf. Commun. Technol., Electron. Microelectron.*, 2006, pp. 1–6.
- [211] K. Thompson, G. J. Miller, and R. Wilder, "Wide-Area Internet Traffic Patterns and Characteristics," *IEEE network*, vol. 11, no. 6, pp. 10–23, 1997.
- [212] M. Mellia, R. L. Cigno, and F. Neri, "Measuring IP and TCP Behavior on Edge Nodes with Tstat," *Computer Networks*, vol. 47, no. 1, pp. 1–21, 2005, Accessed 10.4.2020. [Online]. Available: <https://doi.org/10.1016/j.comnet.2004.06.026>
- [213] X. S. Wang, A. Balasubramanian, A. Krishnamurthy, and D. Wetherall, "Demystifying Page Load Performance with WProf," in *Proceedings of the 10th USENIX Symposium on Networked Systems Design and Implementation, NSDI*, N. Feamster and J. C. Mogul, Eds. USENIX Association, 2013, pp. 473–485. [Online]. Available: https://www.usenix.org/conference/nsdi13/technical-sessions/presentation/wang_xiao
- [214] Google. (2019) Introduction: Causes and Mitigations of DNS Latency. Accessed 18.1.2019. [Online]. Available: <https://developers.google.com/speed/public-dns/docs/performance?csw=>
- [215] J. Hui and K. Lau, "T-Mobile QoE Lab: Making Mobile Browsing Faster and Open Research Problems," in *ACM MobiCom*, 2013, pp. 239–242, Accessed 8.5.2020. [Online]. Available: <http://doi.acm.org/10.1145/2500423.2504585>
- [216] Q. Xu, J. Huang, Z. Wang, F. Qian, A. Gerber, and Z. M. Mao, "Cellular Data Network Infrastructure Characterization and Implication on Mobile Content Placement," in *ACM SIGMETRICS*, 2011, pp. 317–328, Accessed 28.4.2020. [Online]. Available: <http://doi.acm.org/10.1145/1993744.1993777>
- [217] J. P. Rula and F. E. Bustamante, "Behind the Curtain: The Importance of Replica Selection in Next Generation Cellular Networks," in *ACM SIGCOMM*, 2014, pp. 135–136, Accessed 28.4.2020. [Online]. Available: <http://doi.acm.org/10.1145/2619239.2631465>
- [218] S. E. Deering and R. M. Hinden, "Internet Protocol, Version 6 (IPv6) Specification," *RFC*, vol. 2460, pp. 1–39, 1998, Accessed 28.4.2020. [Online]. Available: <https://doi.org/10.17487/RFC2460>

- [219] I. Alexa Internet. (2019) Alexa: The Top 500 Sites on the Web. Accessed 30.10.2019. [Online]. Available: <https://www.alexa.com/topsites>
- [220] C. Marquez, M. Gramaglia, M. Fiore, A. Banchs, C. Ziemlicki, and Z. Smoreda, “Not All Apps Are Created Equal: Analysis of Spatiotemporal Heterogeneity in Nationwide Mobile Service Usage,” in *(CoNEXT) Conference on emerging Networking EXperiments and Technologies*, 2017, pp. 180–186, Accessed 18.1.2019. [Online]. Available: <https://doi.org/10.1145/3143361.3143369>
- [221] M. P. Andrews and R. Bellis, “A Common Operational Problem in DNS Servers - Failure To Communicate.” Internet Engineering Task Force, Internet-Draft, 2019, Work in progress, Accessed 26.5.2020. [Online]. Available: <https://datatracker.ietf.org/doc/html/draft-ietf-dnsop-no-response-issue-14>
- [222] P. B. Danzig, K. Obraczka, and A. Kumar, “An Analysis of Wide-Area Name Server Traffic: A Study of the Internet Domain Name System,” in *ACM SIGCOMM*, 1992, pp. 281–292, Accessed 24.4.2020. [Online]. Available: <https://doi.org/10.1145/144179.144301>
- [223] J. Jung, E. Sit, H. Balakrishnan, and R. T. Morris, “DNS Performance and the Effectiveness of Caching,” *Computer Communication Review*, vol. 32, no. 1, p. 74, 2002, Accessed 24.4.2020. [Online]. Available: <https://doi.org/10.1145/510726.510748>
- [224] V. Pappas, D. Wessels, D. Massey, S. Lu, A. Terzis, and L. Zhang, “Impact of Configuration Errors on DNS Robustness,” *IEEE Journal on Selected Areas in Communications*, vol. 27, no. 3, pp. 275–290, 2009, Accessed 28.4.2020. [Online]. Available: <https://doi.org/10.1109/JSAC.2009.090404>
- [225] P. Vixie, “Extension Mechanisms for DNS (EDNS0),” RFC 2671 (Proposed Standard), RFC Editor, 1999, superseded by RFC 6891. [Online]. Available: <https://www.rfc-editor.org/rfc/rfc2671.txt>
- [226] P. Vixie, S. Thomson, Y. Rekhter, and J. Bound, “Dynamic Updates in the Domain Name System (DNS UPDATE),” RFC 2136 (Proposed Standard), pp. 1–26, 1997, Accessed 18.1.2019. [Online]. Available: <https://www.rfc-editor.org/rfc/rfc2136.txt>
- [227] P. Vixie, O. Gudmundsson, D. Eastlake 3rd, and B. Wellington, “Secret Key Transaction Authentication for DNS (TSIG),” RFC 2845 (Proposed Standard), RFC Editor, 2000, updated by RFCs 3645, 4635, 6895. [Online]. Available: <https://www.rfc-editor.org/rfc/rfc2845.txt>
- [228] D. Eastlake 3rd, “Secret Key Establishment for DNS (TKEY RR),” RFC 2930 (Proposed Standard), RFC Editor, 2000, updated by RFC 6895. [Online]. Available: <https://www.rfc-editor.org/rfc/rfc2930.txt>
- [229] G. Aceto, A. Montieri, and A. Pescapè, “Internet censorship in Italy: An analysis of 3g/4g networks,” in *IEEE International Conference on Communications, ICC 2017, Paris, France, May 21-25, 2017*. IEEE, 2017, pp. 1–6. [Online]. Available: <https://doi.org/10.1109/ICC.2017.7996467>
- [230] RIPE. (2016) RIPE Stat API. [Online]. Available: <https://stat.ripe.net/>
- [231] M.-C. Roşu and D. Roşu, “An Evaluation of TCP Splice Benefits in Web Proxy Servers,” in *Pro. of the Eleventh International World Wide Web Conference(WWW*, 2002, pp. 13–24, Accessed 24.4.2020. [Online]. Available: <http://doi.acm.org/10.1145/511446.511449>

- [232] A. Pathak, A. Wang, C. Huang, A. G. Greenberg, Y. C. Hu, R. Kern, J. Li, and K. W. Ross, "Measuring and Evaluating TCP Splitting for Cloud Services," in *Passive and Active Measurement (PAM)*, 2010, pp. 41–50, Accessed 24.4.2020. [Online]. Available: http://dx.doi.org/10.1007/978-3-642-12334-4_5
- [233] X. Xu, Y. Jiang, T. Flach, E. Katz-Bassett, D. R. Choffnes, and R. Govindan, "Investigating transparent web proxies in cellular networks," in *Passive and Active Measurement (PAM)*, 2015, pp. 262–276, Accessed 24.4.2020. [Online]. Available: https://doi.org/10.1007/978-3-319-15509-8_20
- [234] P. Rodriguez and V. Fridman, "Performance of peps in cellular wireless networks," in *Web Content Caching and Distribution, WCW*, F. Douglass and B. D. Davison, Eds. Kluwer, 2003, pp. 19–38. [Online]. Available: https://doi.org/10.1007/1-4020-2258-1_2
- [235] A. Pathak, A. Wang, C. Huang, A. G. Greenberg, Y. C. Hu, R. Kern, J. Li, and K. W. Ross, "Measuring and evaluating TCP splitting for cloud services," in *Passive and Active Measurement, 11th International Conference, PAM*, ser. Lecture Notes in Computer Science, A. Krishnamurthy and B. Plattner, Eds., vol. 6032. Springer, 2010, pp. 41–50. [Online]. Available: https://doi.org/10.1007/978-3-642-12334-4_5
- [236] B. Ager, W. Mühlbauer, G. Smaragdakis, and S. Uhlig, "Comparing DNS Resolvers in the Wild," in *Pro. of the 10th ACM SIGCOMM Internet Measurement Conference (IMC)*, 2010, pp. 15–21, Accessed 21.4.2020. [Online]. Available: <http://doi.acm.org/10.1145/1879141.1879144>
- [237] GSMarena. (2019) GSMarena.com - Mobile Phone Reviews, News, and Specifications . Accessed 6.9.2020. [Online]. Available: <https://www.gsmarena.com/>
- [238] AndroidDev. (2019) Android Developers Platform. Accessed 29.5.2020. [Online]. Available: <https://developer.android.com/preview>
- [239] J. MacQueen *et al.*, "Some Methods for Classification and Analysis of Multivariate Observations," in *Berkeley Symposium on Mathematical Statistics and Probability*, vol. 1, no. 14, 1967.
- [240] P. J. Rousseeuw, "Silhouettes: a Graphical Aid to the Interpretation and Validation of Cluster Analysis," *Springer CAM*, vol. 20, 1987.
- [241] T. Calinski and J. Harabasz, "A Dendrite Method for Cluster Analysis," *Communications in Statistics*, vol. 3, no. 1, 1974, Accessed 18.1.2019. [Online]. Available: <https://www.tandfonline.com/doi/abs/10.1080/03610927408827101>
- [242] D. L. Davies and D. W. Bouldin, "A Cluster Separation Measure," *IEEE TPAMI*, vol. 1, no. 2, 1979, Accessed 18.1.2019.
- [243] P. Branco, L. Torgo, and R. P. Ribeiro, "A Survey of Predictive Modeling on Imbalanced Domains," *ACM Comput. Surv.*, vol. 49, no. 2, pp. 31:1–31:50, 2016, Accessed 23.4.2020. [Online]. Available: <https://doi.org/10.1145/2907070>
- [244] N. V. Chawla, K. W. Bowyer, L. O. Hall, and W. P. Kegelmeyer, "SMOTE: synthetic minority over-sampling technique," *Journal of Artificial Intelligence Research*, vol. 16, pp. 321–357, 2002, Accessed 18.1.2019. [Online]. Available: <https://doi.org/10.1613/jair.953>

- [245] H. He, Y. Bai, E. A. Garcia, and S. Li, “ADASYN: Adaptive Synthetic Sampling Approach for Imbalanced Learning,” in *IEEE IJCNN*, 2008, Accessed 18.1.2019.
- [246] S. R. Department. (2020) Mobile Phone Internet Data Subscriptions in Finland from 2011 to 2017, by Type. [Online]. Available: <https://www.statista.com/statistics/551000/finland-mobile-phone-internet-data-subscription-by-type/>
- [247] T. Ertiö and P. Räsänen, “Mobile Online Proficiency and Mobile Internet Use - Findings from Finland,” ser. Human Aspects of Information Security, Privacy and Trust HAS, 2017, pp. 45–56. [Online]. Available: https://doi.org/10.1007/978-3-319-58460-7_4
- [248] R. Wei, “Motivations for Using the Mobile Phone for Mass Communications and Entertainment,” *Telematics and Informatics*, vol. 25, no. 1, pp. 36–46, 2008. [Online]. Available: <https://doi.org/10.1016/j.tele.2006.03.001>
- [249] H. Kim, N. Agrawal, and C. Ungureanu, “Revisiting Storage for Smartphones,” *TOS*, vol. 8, no. 4, pp. 14:1–14:25, 2012. [Online]. Available: <https://doi.org/10.1145/2385603.2385607>
- [250] M. Harris, “CES 2018: Phantom Auto Demonstrates First Remote-Controlled Car on Public Roads,” <https://bit.ly/2D26Z87>, 2018, Accessed 28.11.2018.
- [251] L. Kang, W. Zhao, B. Qi, and S. Banerjee, “Augmenting Self-Driving with Remote Control: Challenges and Directions,” in *Workshop on Mobile Computing Systems & Applications*, 2018, pp. 19–24, Accessed 21.3.2020. [Online]. Available: <https://doi.org/10.1145/3177102.3177104>
- [252] Q. Xiao, K. Xu, D. Wang, L. Li, and Y. Zhong, “TCP Performance Over Mobile Networks in High-Speed Mobility Scenarios,” in *IEEE Conference on Network Protocols, ICNP*, 2014, pp. 281–286, Accessed 21.3.2020. [Online]. Available: <https://doi.org/10.1109/ICNP.2014.49>
- [253] SierraWireless, “AirLink RV50 Datasheet,” 2018, Accessed 27.9.2019. [Online]. Available: <https://bit.ly/2W7dkrj>
- [254] F. Chucholowski, T. Tang, and M. Lienkamp, “Teleoperated Driving Robust and Secure Data Connections,” *ATZelektronik Worldwide*, vol. 9, no. 1, pp. 42–45, 2014, Accessed 21.3.2020. [Online]. Available: <https://doi.org/10.1365/s38314-014-0226-x>
- [255] S. Gnatzig, F. Chucholowski, T. Tang, and M. Lienkamp, “A System Design for Teleoperated Road Vehicles.” in *Conference on Informatics in Control, Automation and Robotics*, 2013, pp. 231–238.
- [256] YouTube Help, “Live Encoder Settings, Bitrates and Resolutions,” 2018, Accessed 23.4.2019. [Online]. Available: <https://bit.ly/2oob5w0>
- [257] Adobe Developer Connection, “Recommended Bit Rates for Live Streaming,” Accessed 10.5.2020. [Online]. Available: <https://adobe.ly/2wd8pH7>
- [258] Car2X-Team, “OpenROUTS3D,” 2019, Accessed 22.4.2020. [Online]. Available: <https://git.io/fj8tn>
- [259] H. Guo and J. S. Heidemann, “Detecting ICMP rate limiting in the internet,” in *Passive and Active Measurement - 19th International Conference (PAM)*, vol. 10771. Springer, 2018, pp. 3–17, Accessed 21.3.2020. [Online]. Available: https://doi.org/10.1007/978-3-319-76481-8_1

- [260] S. J. Russell and P. Norvig, *Artificial intelligence: a modern approach*. Prentice Hall, 1995.
- [261] European Union, “Mapping study: Mapping of fixed and mobile broadband services in europe (smart 2014/0016),” 2016, Accessed 26.2.2021. [Online]. Available: <https://www.broadband-mapping.eu/>
- [262] Ericsson, “Ericsson Mobility Report,” 2020, Accessed 9.6.2020. [Online]. Available: <https://bit.ly/3h5kzaj>
- [263] Cisco. (2020) Cisco Annual Internet Report (2018–2023) White Paper. Accessed 9.6.2020. [Online]. Available: <https://bit.ly/30iB1x8>
- [264] C. V. Networking, “Global Mobile Data Traffic Forecast update, 2015–2020,” *Cisco White Paper*, p. 9, 2016, Accessed 9.6.2020.
- [265] J. Guo, C. She, and C. Yang, “Predictive Resource Allocation with Coarse-Grained Mobility Pattern and Traffic Load Information,” in *IEEE ICC*. IEEE, 2018, pp. 1–6, Accessed 9.6.2020. [Online]. Available: <https://doi.org/10.1109/ICC.2018.8422705>
- [266] F. A. Silva, A. C. S. A. Domingues, and T. R. M. B. Silva, “Discovering Mobile Application Usage Patterns from a Large-Scale Dataset,” *ACM Trans. Knowl. Discov. Data*.
- [267] T. Xia and Y. Li, “Revealing Urban Dynamics by Learning Online and Offline Behaviours Together,” *Proc. ACM Interact. Mob. Wearable Ubiquitous Technol.*, vol. 3, no. 1, 2019, Accessed 9.6.2020. [Online]. Available: <https://doi.org/10.1145/3314417>
- [268] J. L. Toole, M. Ulm, M. C. González, and D. Bauer, “Inferring Land Use from Mobile Phone Activity,” in *ACM SIGKDD*, O. E. Wolfson and Y. Zheng, Eds. ACM, 2012, pp. 1–8, Accessed 9.6.2020. [Online]. Available: <https://doi.org/10.1145/2346496.2346498>
- [269] S. Neumeier and C. Facchi, “Towards a Driver Support System for Teleoperated Driving,” in *2019 IEEE Intelligent Transportation Systems Conference, ITSC*. IEEE, 2019, pp. 4190–4196, Accessed 9.6.2020. [Online]. Available: <https://doi.org/10.1109/ITSC.2019.8917244>
- [270] S. Neumeier and C. Facchi, “Towards a Driver Support System for Teleoperated Driving,” in *IEEE Intelligent Transportation Systems Conference, ITSC*, 2019, pp. 4190–4196, Accessed 9.6.2020. [Online]. Available: doi: 10.1109/ITSC.2019.8917244
- [271] A. Gaber, W. Nassar, A. M. Mohamed, and M. K. Mansour, “Feasibility Study of Teleoperated Vehicles Using Multi-Operator LTE Connection,” in *International Conference on Innovative Trends in Communication and Computer Engineering (ITCE)*, 2020, pp. 191–195, Accessed 9.6.2020. [Online]. Available: doi:10.1109/ITCE48509.2020.9047764
- [272] Rich Caruana, “Multitask Learning,” in *Learning to Learn*, S. Thrun and L. Y. Pratt, Eds. Springer, 1998, pp. 95–133, Accessed 9.6.2020. [Online]. Available: https://doi.org/10.1007/978-1-4615-5529-2_5

Errata

Publication I

- Page 1, Section I: ‘minimes’ is spelled incorrectly. It should be ‘minimizes’. The text should read as ‘b) is also important because it minimizes the time each measurement...’.
- Page 1, Section I: ‘throughput’ is spelled incorrectly. It should be ‘throughput’. The text should read as ‘We then present the analysis regarding cellular network throughput as a function of...’.
- Page 1, Section III-A: ‘crowdsourcing’ is spelled incorrectly. It should be ‘crowdsourcing’. The text should read as ‘...a measurement platform for crowdsourcing information...’.
- Page 2, Section IV: ‘manufactures’ is spelled incorrectly. It should be ‘manufacturers’. The text should read as ‘Device manufacturers continuously improve...’.
- Page 5, Section IV-D: ‘descreasing’ is spelled incorrectly. It should be ‘manufacturers’. The text should read as ‘...they start decreasing in number ...’.
- Page 5, Section V : ‘senstive’ is spelled incorrectly. It should be ‘sensitive’. The text should read as ‘...when using delay-sensitive applications...’.
- Page 7, Section V-C : ‘maxim’ is spelled incorrectly. It should be ‘maximum’. The text should read as ‘...can get a maximum bit rate...’.

Publication II

- Page 76, Section IV-C: ‘observer’ is spelled incorrectly. It should be ‘observe’. The text should read as ‘We observe that...’.
- Page 76, Section IV-C: ‘the the ‘ is repeated. It should be ‘the’. The text should read as ‘...of the total ping packet loss...’.

Publication III

- Page 23, Section 2.3: ‘imagemagic’ is spelled incorrectly. It should be `imagemagick`. The text should read as ‘`imagemagick [1]` is used to compare the pixel difference...’.
- Page 25, Section 3.3: ‘NO_2 and NO_2’ is labelled incorrectly. One of them should be labeled as NO_3. The text should read as ‘*e.g.*, 0.46 between NO_2 and NO_3.’

Publication VI

- Page 119, Section V-E: ‘the the ‘ is repeated. It should be ‘the’. The text should read as ‘Fig. 15b shows the uplink speed.’

Publication VII

- Page 1, Section I: ‘crowdsourced’ is spelled incorrectly. It should be ‘crowd-sourced’. The text should read as ‘Various crowdsourced-based platforms...’.

ISBN 978-952-64-0570-4 (printed)

ISBN 978-952-64-0571-1 (pdf)

ISSN 1799-4934 (printed)

ISSN 1799-4942 (pdf)

Aalto University
School of Electrical Engineering
Department of Communication and Networking
www.aalto.fi

**BUSINESS +
ECONOMY**

**ART +
DESIGN +
ARCHITECTURE**

**SCIENCE +
TECHNOLOGY**

CROSSOVER

**DOCTORAL
DISSERTATIONS**