Optimization in Self-Organizing Cellular Networks

Osman Nuri Can Yilmaz

Optimization in Self-Organizing Cellular Networks

Osman Nuri Can Yilmaz

A doctoral dissertation completed for the degree of Doctor of Science (Technology) to be defended, with the permission of the Aalto University School of Electrical Engineering, at a public examination held at the lecture hall AS1 of the school on 14 December 2018 at 12.

Aalto University
School of Electrical Engineering
Department of Communications and Networking

Supervising professor

Prof. Jyri Hämäläinen, Aalto University, Finland

Thesis advisor

Dr. Seppo Hämäläinen, Nokia, Finland

Preliminary examiners

Associate Prof. Mehdi Bennis, University of Oulu, Finland

Dr. Berna Sayrac, Orange Labs, France

Opponent

Prof. Jukka Lempiäinen, Tampere University of Technology, Finland

Aalto University publication series

DOCTORAL DISSERTATIONS 240/2018

© 2018 Osman Nuri Can Yilmaz

ISBN 978-952-60-8327-8 (printed)

ISBN 978-952-60-8328-5 (pdf)

ISSN 1799-4934 (printed)

ISSN 1799-4942 (pdf)

<http://urn.fi/URN:ISBN:978-952-60-8328-5>

Unigrafia Oy

Helsinki 2018

Finland

Author

Osman Nuri Can Yilmaz

Name of the doctoral dissertation

Optimization in Self-Organizing Cellular Networks

Publisher School of Electrical Engineering

Unit Department of Communications and Networking

Series Aalto University publication series DOCTORAL DISSERTATIONS 240/2018

Field of research Communications Engineering

Manuscript submitted 14 August 2018

Date of the defence 14 December 2018

Permission to publish granted (date) 6 November 2018

Language English

☐ **Monograph**

☒ **Article dissertation**

☐ **Essay dissertation**

Abstract

Radio Access Technologies (RATs) continuously evolve as a response to the ever-growing demand for various services ranging from mobile broadband to machine-type communications. On the other hand, the evolution of RATs as in Long Term Evolution (LTE), is not sufficient alone to guarantee the coverage and capacity needs in cellular networks. This is because the overall Radio Access Network (RAN) performance does not only depend on the RAT capabilities but also the RAN parameters adjusted according to the network planning assumptions. Yet these assumptions may change in time, especially due to deployment densification, resulting in suboptimal RAN performance. Furthermore, base station outage or structural changes in the deployment area could impact the RAN performance. Since reacting on these inherent scenarios manually is very expensive and time consuming, automated recovery and optimization of cellular networks, i.e., Self-Organizing Networks (SON), was addressed as an essential technology component within the evolution of LTE standards.

The work presented in this doctoral dissertation contributed to the development of the SON framework by analyzing the potential impact of adaptable RAN parameters on the system performance, designing practical SON algorithms and providing guidelines for SON architecture evolution toward the 5th Generation (5G). To assess the network performance, both analytical and experimental frameworks were developed based on the 3rd Generation Partnership Project (3GPP) guidelines. Whilst the analytical framework simplifies the link-level modeling, the system-level modeling enables the evaluation of overall network performance with a large number of RAN parameters. In the system-level simulations, the recommended 3GPP urban and suburban scenarios (with regular cell layouts) are assumed for the performance evaluations. In addition, the downtown Helsinki scenario is adopted for the SON performance analysis in a deployment model with an irregular cell layout.

Performance evaluations reveal that antenna configuration impacts the coverage and capacity performance significantly. Furthermore, the results obtained for a realistic urban deployment verify that antenna optimization processes can be managed by both centralized and distributed SON architecture options. In addition, the studies demonstrate that cross-channel resource optimization could improve the network capacity in uplink by means of the localized SON architecture. Toward 5G, context-aware SON solutions were also considered. The long-term scheduling of delay-tolerant services in heterogeneous networks was selected as an example. The study assumes a novel SON architecture that is of User Equipment (UE) extension to involve UE context in decision-making. Approximate gains are revealed to address the potential of SON architecture evolution in 5G.

Keywords Optimization, Self-Organizing Networks, Cellular Networks, SON, LTE, 4G, 5G

ISBN (printed) 978-952-60-8327-8

ISBN (pdf) 978-952-60-8328-5

ISSN (printed) 1799-4934

ISSN (pdf) 1799-4942

Location of publisher Helsinki

Location of printing Helsinki **Year** 2018

Pages 197

urn <http://urn.fi/URN:ISBN:978-952-60-8328-5>

In loving memory of my father and my first teacher, Dursun Yılmaz.

Sevgili babam ve ilk öğretmenim Dursun Yılmaz'ın anısına.

Preface

The research work for this doctoral thesis, which is partly funded by Academy of Finland (Grant 284811), was carried out at the Department of Communications and Networking (ComNet) of Aalto University School of Electrical Engineering (formerly known as Helsinki University of Technology), Espoo, Finland, mainly in collaboration with the research units of Nokia Corporation.

First and foremost, I would like to express my utmost gratitude to my supervisor, Prof. Jyri Hämäläinen, for his excellent mentoring, continuous support and fruitful discussions throughout my doctoral research, as well as his guidance at all the phases of my studies and professional career.

I would like to extend my gratitude to my advisor, Dr. Seppo Hämäläinen, who encouraged me for the doctoral research and provided me with the necessary support and guidance especially at the early stage of the doctoral work. My coauthors, Dr. Carl Wijting and Mr. Petteri Lundén, need to be acknowledged for their contributions as well.

I would like to thank the preliminary examiners, Dr. Berna Sayrac and Associate Prof. Mehdi Bennis, for their invaluable feedback. I would also like to thank Prof. Jukka Lempiäinen for accepting to be the opponent.

I would like to extend my thanks to all the colleagues from ComNet, GETA, NSN Research Finland and Nokia Research Center for the wonderful atmosphere for my research and thoughtful discussions. In addition, I would like to thank my line manager, Mr. Johan Torsner, and the colleagues from Ericsson Research Finland for the support and encouragement to finalize my thesis.

Special thanks should be given to the doctoral programme coordinator, Ms. Marja Leppäharju; the school secretary, Ms. Sanna Patana; and the operating engineer, Mr. Viktor Nässi. I would also like to thank my

colleagues and friends, Dr. Ömer Bulakci, Dr. Abdallah Bou Saleh, Dr. Zhong Zheng and Dr. Alexis Dowhuszko, for the good times we had at Aalto University.

The last but definitely not the least, my mom, Emel Yılmaz; my late father, Dursun Yılmaz; my late grandmothers, Seher Çolak and Fatma Yılmaz; and my late grandfathers, Osman Çolak and Nuri Yılmaz; as well as my wife, Valeria Yılmaz, receive my deepest gratitude for their love, inspiration, encouragement and understanding. Indeed, it would not have been possible to achieve this without my family's support.

Helsinki, November 6, 2018,

Osman Nuri Can Yilmaz

Contents

Preface	i
Contents	iii
List of Publications	v
Author's Contribution	vii
List of Abbreviations and Symbols	xi
1. Introduction	1
1.1 Motivation	1
1.2 Scope of the Thesis and Research Questions	4
1.3 Contributions	5
1.4 Structure of the Thesis	8
1.5 Summary of Publications	9
2. Self-Organizing Networks	11
2.1 SON Functions and Use Cases	11
2.1.1 Self-Planning	12
2.1.2 Self-Configuration	12
2.1.3 Self-Optimization	13
2.1.4 Self-Healing	14
2.2 SON Architecture Options	16
2.2.1 Localized SON	17
2.2.2 Distributed SON	17
2.2.3 Centralized SON	18
2.2.4 Hybrid SON	18
3. System Model	21
3.1 Simulation Scenarios	21

3.1.1	Deterministic Deployment Scenarios	21
3.1.2	Semi-Deterministic Deployment Scenarios	22
3.1.3	Non-Deterministic Deployment Scenarios	24
3.2	Channel Access Modeling	25
3.2.1	Random Access Procedures	26
3.2.2	RACH Configuration	27
3.2.3	Stochastic Modeling of Random Access	28
3.3	Channel and Link-Level Modeling	30
3.4	Link-to-System Modeling	33
3.5	Mobility Modeling	36
3.6	Antenna Modeling	38
4.	Self-Optimization Solutions and Performance Assessments	43
4.1	Antenna Parameter Optimization for Downlink	43
4.1.1	Optimization Space	43
4.1.2	Self-Optimization Methodology	46
4.1.3	SON Performance Assessment	49
4.2	Vertical Sectorization Optimization for Downlink	52
4.2.1	Optimization Space	52
4.2.2	Self-Optimization Methodology	53
4.2.3	SON Performance Assessment	55
4.3	Cross-Channel Resource Optimization for Uplink	57
4.3.1	Optimization Space	57
4.3.2	Self-Optimization Methodology	58
4.3.3	SON Performance Assessment	60
4.4	Context-Aware Connectivity Optimization for Downlink and Uplink	61
4.4.1	Optimization Space	62
4.4.2	Self-Optimization Methodology	63
4.4.3	SON Performance Assessment	64
5.	Conclusions	67
5.1	Conclusions	67
5.2	Future Work	69
	References	71
	Errata	83
	Publications	85

List of Publications

This thesis consists of an overview and of the following publications which are referred to in the text by their Roman numerals.

I Osman N. C. Yilmaz, Seppo Hämmäläinen and Jyri Hämmäläinen. Analysis of antenna parameter optimization space for 3GPP LTE. In *IEEE Vehicular Technology Conference (VTC Autumn)*, Anchorage-Alaska, USA, pages 1-5, September 2009.

II Osman N. C. Yilmaz, Seppo Hämmäläinen and Jyri Hämmäläinen. Comparison of remote electrical and mechanical antenna downtilt performance for 3GPP LTE. In *IEEE Vehicular Technology Conference (VTC Autumn)*, Anchorage-Alaska, USA, pages 1-5, September 2009.

III Osman N. C. Yilmaz, Seppo Hämmäläinen and Jyri Hämmäläinen. System level analysis of vertical sectorization for 3GPP LTE. In *International Symposium on Wireless Communication Systems (ISWCS)*, Siena, Italy, pages 453-457, September 2009.

IV Osman N. C. Yilmaz, Seppo Hämmäläinen and Jyri Hämmäläinen. Self-optimization of remote electrical tilt. In *IEEE International Symposium on Personal, Indoor and Mobile Radio Communications (PIMRC)*, Istanbul, Turkey, pages 1128-1132, September 2010.

V Osman N. C. Yilmaz, Jyri Hämmäläinen and Seppo Hämmäläinen. Optimization of adaptive antenna system parameters in self-organizing LTE networks. *Wireless Networks*, Volume 19, Issue 6, pages 1251-1267, Au-

gust 2013.

VI Osman N. C. Yilmaz, Jyri Hämäläinen and Seppo Hämäläinen. Vertical sectorization in self-organizing LTE-advanced networks. *Wireless Networks*, Volume 22, Issue 5, pages 1685-1698, July 2016.

VII Osman N. C. Yilmaz, Jyri Hämäläinen and Seppo Hämäläinen. Self-optimization of random access channel in 3rd Generation Partnership Project Long Term Evolution [Invited Paper]. *Wireless Communications and Mobile Computing*, Volume 11, Issue 12, pages 1507-1517, December 2011.

VIII Osman N. C. Yilmaz, Carl Wijting, Petteri Lundén and Jyri Hämäläinen. Optimized mobile connectivity for bandwidth-hungry, delay-tolerant cloud services toward 5G. In *International Symposium on Wireless Communication Systems (ISWCS)*, Barcelona, Spain, pages 6-10, August 2014.

Author's Contribution

Publication I: “Analysis of antenna parameter optimization space for 3GPP LTE”

The author of the thesis is the main contributor to this paper. The author of the thesis had the lead role in developing and analyzing the techniques provided in the paper. The performance evaluations were carried out via a system-level simulator developed by the author of the thesis. Furthermore, the author of the thesis wrote the entire paper.

Publication II: “Comparison of remote electrical and mechanical antenna downtilt performance for 3GPP LTE”

The author of the thesis is the main contributor to this paper. The author of the thesis had the lead role in developing and analyzing the techniques provided in the paper. The performance evaluations were carried out via a system-level simulator developed by the author of the thesis. Furthermore, the author of the thesis wrote the entire paper.

Publication III: “System level analysis of vertical sectorization for 3GPP LTE”

The author of the thesis is the main contributor to this paper. The author of the thesis had one of the lead roles in developing and analyzing the techniques provided in the paper. The performance evaluations were carried out via a system-level simulator developed by the author of the thesis. Furthermore, the author of the thesis wrote the entire paper.

Publication IV: “Self-optimization of remote electrical tilt”

The author of the thesis is the main contributor to this paper. The author of the thesis had the lead role in developing and analyzing the techniques provided in the paper. The performance evaluations were carried out via a system-level simulator developed by the author of the thesis. Furthermore, the author of the thesis wrote the entire paper.

Publication V: “Optimization of adaptive antenna system parameters in self-organizing LTE networks”

The author of the thesis is the main contributor to this article. The author of the thesis had the lead role in developing and analyzing the techniques provided in the article. The performance evaluations were carried out via a system-level simulator developed by the author of the thesis. Furthermore, the author of the thesis wrote the entire article.

Publication VI: “Vertical sectorization in self-organizing LTE-advanced networks”

The author of the thesis is the main contributor to this article. The author of the thesis had the lead role in developing and analyzing the techniques provided in the article. The performance evaluations were carried out via a system-level simulator developed by the author of the thesis. Furthermore, the author of the thesis wrote the entire article.

Publication VII: “Self-optimization of random access channel in 3rd Generation Partnership Project Long Term Evolution [Invited Paper]”

The author of the thesis is the main contributor to this article. The author of the thesis had the lead role in developing the concepts and derivations as well as analyzing the technique presented in the article. The performance results were produced using an analytical model and a dynamic LTE network simulator that were both developed by the author of the thesis. Furthermore, the author of the thesis wrote the entire article.

Publication VIII: “Optimized mobile connectivity for bandwidth-hungry, delay-tolerant cloud services toward 5G”

The author of the thesis had the lead role in this paper. The techniques provided in this paper was developed in cooperation among the co-authors of the paper. The author of the thesis analyzed the in-house system-level simulation results by using a post-processing tool and an analytical framework that were both developed by the author of the thesis.

Abbreviations and Symbols

Abbreviations

2D	Two Dimensional
3D	Three Dimensional
3G	3 rd Generation
3GPP	3 rd Generation Partnership Project
4G	4 th Generation
5G	5 th Generation
AA	Active Antenna
ANR	Automatic Neighbor Relation
AP	Access Probability
BE	Best-Effort
BLER	Block Error Rate
BP	Blocking Probability
BS	Base Station
BW	Bandwidth
CA	Carrier Aggregation
CAPEX	Capital Expenditure
CBR	Case-Based Reasoning
CBRA	Contention-Based Random Access
CCO	Coverage and Capacity Optimization
CDF	Cumulative Distribution Function
CN	Core Network
COC	Cell Outage Compensation
CoMP	Coordinated Multi-Point
CP	Contention Probability
DL	Downlink

DMP	Detection Miss Probability
EDT	Electrical Downtilt
FB	Full-Buffer
FDD	Frequency Division Duplexing
GBR	Guaranteed Bit Rate
GSM	Global System For Mobile Communications
HetNet	Heterogeneous Network
HO	Handover
HOF	Handover Failure
HPBW	Half Power Beamwidth
ICI	Inter-Cell Interference
ISD	Inter-Site Distance
ITU-R	International Telecommunication Union - Radiocommunications Sector
k-NN	k-Nearest Neighbor
KPI	Key Performance Indicator
L1	Layer 1
L3	Layer 3
LS	Local Search
LTE	Long Term Evolution
LTE-A	LTE-Advanced
MBS	Macro-BS
MCS	Modulation and Coding Scheme
MDT	Mechanical Downtilt
MFTBA	Maximum Front-To-Back Attenuation
MIMO	Multiple-Input Multiple-Output
ML	Machine Learning
MLB	Mobility Load Balancing
MRC	Maximal Ratio Combining
MRO	Mobility Robustness Optimization
NCBRA	Non-Contention-Based Random Access
NGMN	Next Generation Mobile Networks Alliance
NR	New Radio
O&M	Operation and Maintenance
OFDM	Orthogonal Frequency Division Multiplexing
OPEX	Operational Expenditure
PCI	Physical Cell Identity
PDCCH	Physical Downlink Control Channel

PHY	Physical Layer
PRACH	Physical Random Access Channel
PRB	Physical Resource Block
PUSCH	Physical Uplink Shared Channel
QoS	Quality of Service
RA	Random Access
RACH	Random Access Channel
RAN	Radio Access Network
RAT	Radio Access Technology
RBR	Rule-Based Reasoning
RF	Radio Frequency
RFRA	Resource-Fair Resource Allocation
RLF	Radio Link Failure
RLM	Radio Link Monitoring
RRC	Radio Resource Control
RRM	Radio Resource Management
RSRP	Reference Signal Received Power
SBS	Small-BS
SE	Spectral Efficiency
SINR	Signal to Interference plus Noise Ratio
SLA	Side Lobe Attenuation
SON	Self-Organizing Networks
TFRA	Throughput-Fair Resource Allocation
TTT	Time-To-Trigger
UE	User Equipment
UL	Uplink
UMTS	Universal Mobile Telecommunications System
URLLC	Ultra-Reliable Low-Latency Communications
VB	Variable-Buffer
VS	Vertical Sectorization

Latin symbols

A_{3D}^c	Total antenna radiation pattern of BS c
A_g	Antenna gain
A_h^c	Antenna radiation pattern of BS c in the horizontal plane

A_{max}	Maximum front-to-back attenuation
A_u^c	Antenna directivity gain between UE u and BS c
A_v^c	Antenna radiation pattern of BS c in the vertical plane
$AP_{C,m}$	Access probability at the m^{th} CBRA attempt
$AP_{C,t}$	Target access probability in the case of the CBRA procedure
$AP_{NC,m}$	Access probability at the m^{th} NCBRA attempt
$AP_{NC,t}$	Target access probability in the case of the NCBRA procedure
BP	Blocking probability
BW_{all}^s	Average system bandwidth allocated to serving BS s in the evaluated link
BW_{eff}	Bandwidth efficiency
BW_{sys}	Total system bandwidth for the evaluated link
BW_u^s	Average bandwidth allocation per UE u in serving BS s
C	Stored set of successful cases
c_n^q	Stored set of k successful cases that are the most similar to given query q
CF	Connection function
CP	Contention probability
CP_k	Contention probability per preamble period for a set of k CBRA attempts
CR_k	Collision rate per preamble period for a set of k CBRA attempts
d_u^n	Proximity of UE u to target BS n
DMP	Detection miss probability of a random access attempt
DMP_C	Detection miss probability of a CBRA attempt
DMP_{mean}	Mean detection miss probability
DMP_{NC}	Detection miss probability of a NCBRA attempt
EE_{DMP}	Zero-mean normally distributed variable for detection miss probability
GBR	Guaranteed bit rate requirement
K	Filter coefficient
k_{NN}	Number of nearest neighbors
KPI_i	Standard KPI i
KPI_{MR}^s	KPI for the evaluation of the mobility robustness in serving BS s
KPI_{VL}^s	Virtual load in serving BS s
l	Number of NCBRA attempts per preamble period
$L_{DL,u}^c$	Link loss in the downlink between UE u and BS c
$L_{DL,u}^n$	Link loss in the downlink between UE u and interfering BS n

$L_{DL,u}^s$	Link loss in the downlink between UE u and serving BS s
$L_{PL,u}^c$	Path loss between UE u and BS c
$L_{UL,i}^s$	Link loss in the uplink between interfering UE i and BS s
$L_{UL,u}^c$	Link loss in the uplink between UE u and BS c
$L_{UL,u}^s$	Link loss in the uplink between UE u and serving BS s
LF	Link function
MCS_{eff}	Modulation and coding scheme efficiency
MCS_{max}	Maximum spectral efficiency for the highest modulation and coding scheme assumed
$N_{C,d}$	Number of detected CBRA attempts per evaluation period
$n_{C,d}$	Number of detected CBRA attempts per preamble period
$n_{C,pre}$	Number of preamble sequences allocated for CBRA
n_C	Expected number of CBRA attempts per preamble period
N_{DL}	Total thermal noise in downlink
$N_{NC,d}$	Number of detected NCBRA attempts per evaluation period
$n_{NC,d}$	Number of detected NCBRA attempts per preamble period
$n_{NC,pre}$	Number of preamble sequences allocated for NCBRA
n_{NC}	Expected number of NCBRA attempts per preamble period
N_{RA}	Number of preambles per evaluation period
n_{RA}	Expected number of random access attempts per preamble period
N_{SC}	Target BS for offloading
$n_{total,pre}$	Total number of preamble sequences
N_{UL}	Total thermal noise in uplink
P_d	Optimized ratio of signatures that are dedicated for NCBRA
p_d	Ratio of signatures that are dedicated for NCBRA
$P_{C,s}$	Probability of having s CBRA attempts per preamble period
P_i^n	Uplink power of interfering UE i connected to BS n
P_{max}^n	Maximum downlink power of interfering BS n
P_{max}^s	Maximum downlink power of serving BS s
$P_{NC,l}$	Probability of having l NCBRA attempts per preamble period
$p_{off,u}^n$	Offloading probability of UE u to target BS n
$P_{RA,k}$	Probability of having k random access attempts per preamble period
P_u^s	Uplink power of UE u connected to serving BS s
PRB_u^s	Number of PRBs required per UE u in serving BS s
Q_{drop}	90% BLER at hypothetical PDCCH
Q_h^s	Handover hysteresis configured by serving BS s

Q_{in}	2% BLER at hypothetical PDCCH
Q_n^s	Handover offset for neighboring BS n configured by serving BS s
Q_{out}	10% BLER at hypothetical PDCCH
Q_R	Filtered RSRP
Q_R^n	Filtered RSRP of target BS n
Q_R^s	Filtered RSRP of serving BS s
R_{L1}	Latest average RSRP measurement at the physical layer
$S_{c,q}$	Similarity between case c and query q
SC	Small-cell layer
SE_u^s	Spectral efficiency of the evaluated link between UE u and serving BS s
SLA_v	Side lobe attenuation
SPI_i	Normalized KPI i
SPI_i^c	Normalized KPI i for case c
SPI_i^q	Normalized KPI i for query c
SR^s	Satisfied user ratio
t_0	Original time
T_{HO}^s	Time-to-trigger configured by serving BS s
T_{L3}	Measurement period
t_{off}	Offloading time interval
T_{RA}	Optimized preamble period
t_{RA}	Preamble period
T_{RLF1}	First RLF timer
T_{RLF2}	Second RLF timer
TP_u^s	Throughput of the evaluated link between UE u and serving BS s
U_C	CBRA performance function
U_{NC}	NCBRA performance function
U_{total}^s	Total number of UEs connected to serving BS s in the evaluated link
U_{UL}	Uplink performance function
v_u	Velocity of UE u
$\hat{w}_i$	KPI-specific weight for the k-NN classifier
w_C	Weight for the access probability KPI in the case of CBRA
W_i	KPI-specific weight for the LS method
w_i	KPI-specific weight for the rule-based classifier
w_{NC}	Weight for the access probability KPI in the case of NCBRA
w_{VL}	Weight for the virtual load KPI

X Other link losses

Greek symbols

$\Delta_{DL,u}^c$	Channel fading loss in the downlink between UE u and BS c
Δ_t	Time shift tolerance for the data exchange
$\Delta_{UL,u}^c$	Channel fading loss in the uplink between UE u and BS c
$\gamma_{DL,u}^s$	SINR in the downlink between UE u and serving BS s
$\bar{\gamma}_{DL,u}^s$	Mean SINR in the downlink between UE u and serving BS s
γ_{HO}^s	SINR in the downlink of serving BS s when handover is triggered
γ_{max}	SINR at which maximum normalized throughput can be reached
γ_{min}	Minimum SINR that is required for maintaining radio link connection
γ_{RLF1}^s	Mean SINR in the downlink of serving BS s when the first RLF timer is running
γ_{RLF2}^s	Mean SINR in the downlink of serving BS s when the second RLF timer is running
$\gamma_{UL,u}^s$	SINR in the uplink between UE u and serving BS s
$\bar{\gamma}_{UL,u}^s$	Mean SINR in the uplink between UE u and serving BS s
γ_u^s	Mean SINR in the link between UE u and serving BS s
λ	Verified class indicator
$\hat{\lambda}$	Predicted class indicator
μ_i	Mean of the KPI i distribution
ρ^n	Traffic load in interfering BS n in the evaluated link
ρ^s	Traffic load in serving BS s in the evaluated link
$\rho^{m,s}$	Traffic load in BS m which is coordinated with serving BS s in the evaluated link
σ_{DMP}	Standard deviation of the detection miss probability distribution
σ_i	Standard deviation of the KPI i distribution
τ	Measurement time
θ	Angular separation from the main lobe of antenna radiation pattern in elevation
$\hat{\theta}$	Transformed angular separation from the main lobe of antenna radiation pattern in elevation
θ_{3dB}	Vertical half power beamwidth
θ_{EDT}	Electrical downtilt angle
θ_{MDT}	Mechanical downtilt angle

φ	Angular separation from the main lobe of antenna radiation pattern in azimuth
$\hat{\varphi}$	Transformed angular separation from the main lobe of antenna radiation pattern in azimuth
φ_{3dB}	Horizontal half power beamwidth
φ_{AS}	Azimuth steering angle

1. Introduction

1.1 Motivation

In wireless communications, the demand for a wide range of human- and machine- type communication services, as well as radio spectrum scarcity are leading to a rapid increase in the network performance requirements, for instance, in terms of peak data rate, latency, coverage, capacity, spectrum efficiency and energy efficiency. Therefore, the 3rd Generation Partnership Project (3GPP) radio technologies, such as Long Term Evolution (LTE) and New Radio (NR), were designed with these diverse requirements in mind [1, 2, 3, 4, 5, 6, 7].

In LTE [8], the underlying Radio Access Technology (RAT) is based on Orthogonal Frequency Division Multiplexing (OFDM) as specified in [9]. This enables large data rates in combination with higher order modulations, larger Bandwidths (BW) and Multiple-Input Multiple-Output (MIMO) enhancements. Moreover, the network architecture of LTE distributes the Radio Resource Management (RRM) functions among Base Stations (BSs), and thereby a cost-effective and simplified operation with lower control plane latency becomes possible.

Subsequently to the initial releases of LTE specifications, LTE-Advanced (LTE-A) emerged as the continual improvement for the LTE RAT and architecture standards by fulfilling the 4th Generation (4G) requirements [2]. Carrier Aggregation (CA), dual connectivity, advanced relay node communications, MIMO enhancements as well as Coordinated Multi-Point (CoMP) transmission and reception are considered to be the major technical improvements in 4G [10].

The advancements in LTE are not limited to those aforementioned. To minimize both Operational Expenditure (OPEX) and Capital Expenditure

(CAPEX), Self-Organizing Networks (SON), as the essential technology component, was introduced in the 3GPP standards. By means of SON, the major processes of network operation and maintenance can be fully automated and distributed over the LTE Radio Access Network (RAN) minimizing the need for human intervention. These automated functions react dynamically against the negative changes in Key Performance Indicators (KPIs), optimizing the overall RAN performance and Quality of Service (QoS) [11, 12].

From the previous studies conducted on the 3rd Generation (3G) network optimization, it is known that the automated optimization of antenna parameters is an attractive way to extend the network coverage and maximize the network capacity in 3G networks of which the underlying RAT is based on Code Division Multiple Access [13, 14]. This optimization methodology could also be adapted to LTE networks where OFDM is the underlying RAT. As presented in [15, 16, 17, 18], in the case of LTE, the automated antenna optimization also provides notable performance gains. On the other hand, from the SON perspective, the optimization methodology has to tackle with several challenges in order to provide a practical and efficient Coverage and Capacity Optimization (CCO) application for LTE networks as discussed in [19]. It should be recalled that since the underlying technology is also OFDM in NR [20], the SON solutions for NR macro-cellular deployments are expected to be based on those developed for LTE macro-cellular deployments.

In the literature, heuristic approaches are applied in some subfields of communications engineering, such as network planning [21, 22, 23, 24], and antenna design and control [25, 26]. However, exploring a large antenna parameter space during the network's operational phase may be prohibitive, especially in the case of network-wide coverage optimization. That is due to the high risk of negative performance impact on mobility and service continuity. Therefore, the practical applications of Local Search (LS), such as Tabu Search [14], Simulated Annealing [23], Genetic Algorithm [15] and Gradient Method [17], are considered to be quite limited. Furthermore, in [13], a simple algorithm based on Rule-Based Reasoning (RBR) is applied for the network-wide antenna optimization, where predefined optimization policy rules are implemented in order to avoid the exploration of a large parameter space. Yet in this case, an optimal end result may not always be guaranteed since there may not be adequate expert knowledge available for every possible optimization sce-

nario that could emerge in a dynamically changing RAN environment, for instance, due to a BS outage. In order to overcome the human expertise deficiency on these optimization scenarios, Fuzzy Reinforcement Learning approach is proposed by [16, 18]. On the other hand, the total number of rules that needs to be trained and tuned by the mentioned approach may be very large since it depends on both the number of inputs and the membership functions that are defined for each input. In real-world deployments, where the regular hexagonal layout assumption of [16, 18] is not always valid, the time period needed for the training and tuning could be too long for antenna optimization processes. To avoid all these trade-offs, self-optimization methodology needs to effectively combine multiple algorithmic methods.

In order to fully take advantage of SON, antenna parameters need to be flexibly and accurately configurable. To enable this, Radio Frequency (RF) components should be integrated with each radiating element of the antenna. This way, the amplitude and phase control of the signals can be fed into to each radiating element separately [27, 28]. Active Antenna (AA) technology adopts the integration of the RF components and radiating elements, and introduces Vertical Sectorization (VS) [27]. In VS, horizontal sector is divided into two or more (vertical) subsectors. However, to optimize VS in co-channel deployments, the excessive Inter-Cell Interference (ICI) between adjacent subsectors, which were also noted by [29, 30, 31, 32] in the literature, must be alleviated. One way to solve this problem is to use very narrow vertical beam patterns with large Electrical Downtilt (EDT) angles. However, it may not be practical for antenna systems to support a wide range of EDT angles. This is because the narrower the beam pattern is, the more the side lobe level increases, thus resulting in lower antenna gains [30]. Further, CoMP [33, 34, 35], which is an attractive LTE-A feature to mitigate the ICI, can be considered as a technology component to assist VS. Since the subsectors are expected to be controlled by the same controlling unit in the BS, the co-operation of these subsectors in scheduling and transmissions could be managed seamlessly in the case of VS. On the other hand, in order to effectively mitigate the load imbalance and minimize the ICI between the neighbor subsectors [31], it is essential to study EDT optimization (for inner subsectors) under the SON framework, regardless of the use of CoMP.

Since the Downlink (DL) ICI is the main driver for antenna optimization, the performance studies are motivated toward more elaborate DL

modeling and more detailed system-level simulations in DL. However, there are also the CCO applications where Uplink (UL) can take advantage of self-optimization, such as cross-channel resource optimization. That is, in order to obtain better coverage and capacity, as well as shorter channel access latency in UL. The potential gains expected from cross-channel resource optimization are minor in comparison with antenna optimization. However, the fact that the cost of UL resource optimization is negligible makes it an attractive CCO application. This is because it does not require any hardware investment as in antenna optimization. Moreover, UL resource optimization has local and temporal impact on the cell coverage and capacity performance, and there is no need for inter-node message exchange and long-term KPI collection unlike in many other CCO applications.

In LTE and LTE-A networks, User Equipment (UE) data are scheduled based on the instantaneous channel quality measurements so that the BS can exploit the multi-user channel diversity optimizing the radio resource utilization [36]. In addition to the radio resource scheduling mechanism taking place within a single cell, SON is able to balance the network load between different cells using the radio link quality and traffic indicators [37, 38, 39]. In 5th Generation (5G) networks, not only conventional KPIs but also UE context could be potentially utilized for the SON framework [40]. For instance, the long-term scheduling of delay-tolerant services in Heterogeneous Networks (HetNets) could be possible this way. The research study could also address whether UE context and UE itself thereof should be a part of the SON architecture evolution toward 5G.

1.2 Scope of the Thesis and Research Questions

The primary objectives of the doctoral research were to explore the optimization capabilities of LTE and its evolution toward 5G, develop self-optimization solutions adopting low complexity and high intelligibility, and evaluate the effectiveness of the these solutions on the mobile broadband performance.

To assess the network performance, both analytical and experimental frameworks were developed for the simulation studies. Whilst the analytical framework simplifies the link-level modeling, the system-level modeling enables the evaluation of overall network performance with a large number of configurable RAN parameters.

The following research questions are addressed in this doctoral dissertation:

1. How to ensure a reliable CCO performance assessment while enabling longer performance evaluation cycles in comparison with the conventional RRM evaluations?
2. Do antenna techniques, including VS, and antenna parameter settings largely impact the DL coverage and capacity performance in the cellular technologies that employ OFDM, such as LTE?
3. What performance gains are feasible in DL when the antenna techniques and parameters are self-optimized, and what are the typical challenges in the closed-loop antenna optimization?
4. Could cross-channel resource optimization improve the UL capacity, and what performance gains could be obtained in UL by means of self-optimization?
5. How to select the most suitable SON architecture for a given application, and how to design a practical SON algorithm for RAN parameter optimization?
6. What are the potential use cases for the UE context information in the evolution of SON toward 5G?

1.3 Contributions

The doctoral research presented herein contributed to the development of the SON framework by analyzing the potential impact of adaptable RAN parameters on the network performance, designing practical SON algorithms that can autonomously tune these parameters in real-world deployment scenarios and providing further guidelines to the SON architecture evolution toward 5G.

In order to make an assessment on the performance impact of electronically tunable antenna parameters, horizontal and vertical Half Power Beamwidths (HPBW) and EDT are modeled in the LTE DL. Coverage

and capacity performance evaluations were made in accordance with the recommended 3GPP urban and suburban scenarios (i.e., 3GPP case 1 and case 3). The simulation results demonstrate that the ICI-limited deployment scenario (i.e., 3GPP case 1) is more sensitive to the EDT than the noise-limited deployment scenario (i.e., 3GPP case 3). Furthermore, in the case of the ICI-limited deployment scenario - unlike the noise-limited deployment scenario - the optimal EDT angle depends on the other antenna properties, such as horizontal and vertical HPBW. It is also shown that the different coverage and capacity requirements may lead to different optimal antenna parameter values.

Further, the performance evaluation methodology was extended to evaluate the network performance impact of Mechanical Downtilt (MDT) in combination with EDT since large antenna downtilt angles may not be feasible otherwise. Based on the DL performance assessments, EDT provides noticeably better performance in the case of the ICI-limited deployment scenario while the performance difference is insignificant for the noise-limited deployment scenario. In addition, optimal angles for the EDT and MDT parameters are slightly different from each other.

In addition to the performance assessment of the conventional antenna techniques, the performance impact of a novel AA technique - VS - was evaluated for both ICI- and noise- limited deployment scenarios. The simulation results demonstrate that VS could largely improve the network capacity provided that an optimal EDT angle is applied for inner subsector. This is mainly because the ICI between adjacent subsectors may limit the capacity gains when a suboptimal downtilt angle is applied for inner subsector.

As discussed in the remainder of the dissertation, antenna parameter adjustment does not only impact the network coverage and capacity in the serving cell, but also in the neighboring cell(s). On the one hand, this presents a great opportunity to enhance the overall network performance by means of a joint antenna optimization process, on the other hand, it poses a challenge as the interactions among BSs need to be taken into consideration for each parameter adjustment. Hence, the centralized SON architecture becomes a necessity for network-wide antenna parameter optimization. For instance, when a new RAT is deployed, BSs are typically installed to the sites of the preceding RAT. Then, the reuse of the sites requires the optimization of antenna parameters, and this has to be tackled by taking into account the interactions among these BSs in terms

of mobility. Another challenge is that the network coverage and capacity are affected by various dynamic changes in the network environment and deployment, such as urbanization and deployment densification. Reacting on these problems manually is very expensive and time consuming, therefore the antenna optimization solutions should also be responsive to the changes in the network environment and deployment. Considering all these aspects, a novel CCO solution was proposed for the self-optimization of the primary antenna parameters: EDT, antenna azimuth and horizontal HPBW. The solution integrates RBR and Case-Based Reasoning (CBR), and applies these decision-making methods in the training and learning phases, respectively. A dynamic system-level simulator was developed to validate the DL performance of the solution in a realistic macro-cellular deployment. The results show that the self-optimization of these antenna parameters may provide substantial performance improvements with a sufficiently fast convergence rate.

In order to guarantee a reliable and near-optimal operation of VS in a network deployment that applies universal frequency reuse, such as LTE-A, co-channel interference mitigation is essentially needed at least locally i.e, under the coverage of a single BS. A distributed CCO solution was proposed to mitigate the excessive ICI by self-tuning EDT toward the optimal antenna elevation angle. The solution performance was evaluated in DL for both coordinated and uncoordinated multi-point transmission scenarios within the LTE-A framework [35] using a dynamic LTE-A compliant system-level simulator. The extensive performance evaluations demonstrate that the self-optimization of EDT improves the VS performance by reducing the network load significantly. Furthermore, the performance gain is even greater when VS is provided with the dynamic point selection and muting (blanking) that is an LTE-A feature introduced within the CoMP concept [35].

Besides the centralized and distributed CCO solutions, there could also be localized CCO solutions that LTE networks can benefit from. In this respect, the cross-channel resource optimization between Physical Random Access Channel (PRACH) and Physical Uplink Shared Channel (PUSCH) is a prominent example where a localized CCO solution is applied. Based on a semi-analytic performance evaluation, it is shown that LTE PRACH is robust against large changes in the user traffic and mobility. Moreover, the results indicate that the PUSCH capacity in LTE could be improved by the self-optimization of PRACH preamble period, whereas the

performance targets for Contention-Based Random Access (CBRA) and Non-Contention-Based Random Access (NCBRA) are met by adjusting the PRACH preamble split parameter. Although performance gains are not as large as in the aforementioned major CCO applications, improvements are obtained using a simple algorithm, and no additional hardware investment would be required in the network.

In 5G deployments, the co-existence of multiple coverage layers is expected to provide a large selection of connectivity options at the disposal of UEs, each with their own connection characteristics. In these HetNet deployments, UE context could be utilized to offload BW-hungry delay-tolerant services to the optimal connectivity layer, and thus free up resources for delay-critical services in other layer(s). Therefore, toward 5G, it is essential to explore whether UE context can be utilized in addition to existing network KPIs. System-level simulations reveal that both the UE and the network could indeed benefit from the developed context-aware SON solution. The solution enables the UE and the network to proactively interact with each other and optimize the mutual data traffic in both time and connectivity domains.

It should be noted that the doctoral research contributed to the development of SON simulators, demonstrators and products at Nokia Networks (formerly Nokia Siemens Networks). As advertised in [41], SON solutions became commercially available as a result of long-term research and development projects including the one presented in this thesis. In addition, the studies on antenna parameter optimization [PI, PII, PIV, PV] led to a granted patent [42]; and the work on the utilization of UE context [PVIII] resulted in three granted patents [43, 44, 45]. Furthermore, the studies conducted in the scope of this dissertation paved the way for further research toward 5G as demonstrated in the recent literature [46, 47, 48, 49, 50].

1.4 Structure of the Thesis

This thesis consists of five chapters. Chapter 2 discusses the functional and architectural categorizations of SON along with a series of examples that are associated to different SON categories. In Chapter 3, the system model for performance evaluations is presented in detail, including simulation scenarios, channel access modeling, link-to-system mapping, mobility and antenna modeling. Chapter 4 presents the self-optimization

methodology and reports the performance results for the studied SON solutions: antenna parameter optimization, VS optimization, cross-channel resource optimization and context-aware connectivity optimization. The thesis is concluded in Chapter 5.

1.5 Summary of Publications

The dissertation is based on eight publications that are appended at the end of this manuscript. The contribution of each publication is summarized as below.

Publications [PI, PII, PIII] explore the optimization space for a selected set of antenna techniques and parameters by applying both analytical and experimental frameworks that are developed for LTE. Simulations in [PI, PII, PIII] were carried out with a static system-level LTE simulator. Publication [PI] evaluates the network performance impact of horizontal and vertical HPBW, and EDT in the LTE DL. System-level simulation studies were performed for different macro-cellular deployment scenarios to demonstrate the relationship between the deployment scenario and the required antenna parameter setting for optimized network performance. Publication [PII] assumes the same evaluation methodology as in [PI] to study the network performance impact of MDT in combination with EDT. The research work in [PII] addresses the practical limitation in EDT range, and the possible use of MDT to complement EDT. Publication [PIII] extends the previous studies [PI, PII] and analyzes whether AA technology enables further coverage and capacity improvements by means of VS in macro-cellular deployments.

Publications [PIV, PV, PVI] present the CCO studies carried out for the antenna techniques and parameters. The performance evaluations in [PIV, PV, PVI] were performed assuming a non-deterministic deployment scenario with a potential Universal Mobile Telecommunications System (UMTS) site reuse with LTE. Publication [PIV] studies EDT optimization as a part of the CCO use case. The optimization methodology presented in [PIV] adopts CBR in decision-making assuming the centralized SON architecture. The performance evaluations in [PIV] were carried out with a semi-static system-level LTE simulator that generates the Signal to Interference plus Noise Ratio (SINR) and cell throughput results. Publication [PV] advances the performance evaluation methodology studied in [PIV] with the help of a dynamic system-level simulator which enables

the empirical analysis of mobility robustness. It also extends the previous contributions to the SON framework and presents the improved centralized self-optimization methodology. Moreover, it provides the CCO results not only for the EDT parameter but also for the antenna azimuth and HPBW parameters. Publication [PVI] complements the previous studies by presenting a decentralized self-optimization methodology for the VS technique. The performance evaluations in [PVI] were carried out assuming an LTE-A DL scenario with the CoMP capability. The primary goal of the study is to answer whether CCO can mitigate local capacity problems by not altering the handover regions. Mobility Load Balancing (MLB) is also able to respond to local capacity needs. However, in the case of MLB, the handover regions are frequently changed due to the continuous adaptation of mobility parameters [37, 38, 39].

Publication [PVII] presents an analytical framework for the UL channel modeling in LTE on the basis of probability theory and statistics. Then, it uses the deduced mathematical framework and the dynamic system-level LTE simulations in order to examine the cross-channel resource optimization between PRACH and PUSCH.

Publication [PVIII] covers a 5G HetNet scenario where not only conventional KPIs but also UE context could be utilized for the SON framework. It demonstrates the traffic offloading gains through the long-term scheduling of delay-tolerant services in HetNets based on the context information. The performance evaluations were carried out with a dynamic system-level simulator.

2. Self-Organizing Networks

In early Global System For Mobile Communications (GSM) deployments, network maintenance was done mainly on site. Yet along with the evolution of cellular network technologies, nearly all processes regarding the Radio Access Network (RAN) planning, configuration, optimization and healing were managed by centralized remote applications. In the case of Self-Organizing Networks (SON), network maintenance and operations can be fully automated and distributed over RAN. This way, the need for human intervention is minimized and OPEX is further reduced. Moreover, network can be smoothly densified enabling large CAPEX savings.

To guide both network equipment and User Equipment (UE) manufacturers as well as enable interoperability among different manufacturers, SON is specified under 3GPP. Several specification groups study SON use cases to cover both RAN and Operation and Maintenance (O&M) aspects. Accordingly, the agreed functions are specified in multiple series of specifications. The LTE RAN functions that were specified for self-configuration and self-optimization are summarized in [51]. The details of the RAN studies that guided the specification work for the LTE Radio Access Technology (RAT) are reported in [11, 52]. In the case of O&M, SON concepts and requirements are provided in [53]. Furthermore, O&M aspects on self-configuration, self-optimization and self-healing are provided within the 32-series technical specifications [54].

2.1 SON Functions and Use Cases

Based on the functionality, SON solutions can be divided into four categories as suggested by the Next Generation Mobile Networks Alliance (NGMN) [12]: self-planning, self-configuration, self-optimization and self-healing, see Figure 2.1.

Figure 2.1. Main functions and their dependencies in SON during the pre-operational and operational phases.

2.1.1 Self-Planning

Self-planning refers to the dynamic re-computation of the network plan in order to smoothly integrate a newly deployed BS, which is needed for either coverage extension or capacity expansion, into an existing RAN. As a result of this process, a new set of RAN parameter configurations are provided for both the newly deployed BS and its neighbors [24].

Even though in the literature [16], self-planning was considered under the self-configuration category, it can also be categorized as a standalone function as proposed in [12]. This is because the results of the process do not only apply for the newly deployed BS but also for the neighboring BSs affected by the deployment densification or extension.

2.1.2 Self-Configuration

Self-configuration comprises the auto-installation and dynamic configuration of a BS. It takes place typically before the BS radio equipment is switched on. It may also be performed for a BS that is affected by a notable change in the network, for instance, due to a cell outage, as discussed within the self-healing subsection.

By means of self-configuration, the newly deployed BSs can be automatically configured with the required network interfaces and assigned with the suitable operational RAN parameter settings, such as network identities, transmission frequency and power. This is initiated by establishing a

secure auto-connection to the O&M system, Core Network (CN) and RAN.

The dynamically configured network identities for LTE include the Layer 1 (L1) identifier, Physical Cell Identity (PCI) and Cell Global Identity. Due to the fact that there is a limited number of unique cell identifiers available (e.g., 504 PCIs for LTE [11]), the cell identifiers have to be mapped to the newly deployed BSs in a collision and confusion free manner. Otherwise, mobility among the inserted BSs and the neighboring BSs cannot be supported [55]. From the architectural perspective, PCIs for LTE networks can be assigned in a centralized or distributed manner.

Another important function of self-configuration is Automatic Neighbor Relation (ANR). As an essential part of the self-configuration process, it removes the manual effort needed for managing neighbor relations in LTE [55]. ANR configures the neighbor lists before a newly deployed BS becomes operational and continues to optimize the list configuration during the operation. As addressed in [56, 57], emerging technology components of 5G, such as massive beamforming, expand the scope of relations beyond the neighbor relations of LTE.

All in all, the cell planning, roll-out and software upgrade processes are significantly simplified and accelerated by means of self-configuration while the need for on-site commissioning is replaced by the dynamic plug-and-play configuration.

2.1.3 Self-Optimization

Self-optimization is a SON functionality which is responsible for auto-tuning of RAN parameters based on the collected KPIs and the operator policies. It takes place after the auto-integration and dynamic configuration of a newly deployed BS. Self-optimization aims to maximize the network performance in terms of coverage, capacity, mobility robustness, load balancing and interference management while providing greater cost savings in comparison with manually optimized legacy networks.

KPIs are comprised of the statistical information based on the BS and UE performance measurements that are collected as a part of the self-optimization process. KPIs are needed for monitoring the RAN performance, identifying an optimization problem and reacting on this problem by reconfiguring a RAN parameter, such as antenna tilt, transmission power and handover offset. Self-optimization can be further categorized into the following use cases:

- *Coverage and Capacity Optimization (CCO)* is one of the major self-optimization use cases as indicated by 3GPP and NGMN [11, 12]. The SON framework allows the automated control of various RAN parameters for the CCO use case as studied in this dissertation [PIV, PV, PVI, PVII] and in the literature [15, 16, 17, 18, 46, 58]. With reduced human interaction, CCO enables more efficient and dynamic use of network resources in comparison to legacy optimization mechanisms. As a result, both OPEX and CAPEX are minimized.
- *Mobility Load Balancing (MLB)* is another self-optimization use case which allows RAN to transfer the traffic load from the cells suffering congestion to the cells having spare resources. This is achieved by exchanging the information on the load level and the available capacity. In the case of MLB, handover thresholds are adapted according to the data traffic distribution among neighboring cells as discussed in [37, 38, 39], where the handover offset parameter is optimized for each cell pair.
- *Mobility Robustness Optimization (MRO)* refers to the self-optimization use case where the auto detection and correction of errors in the mobility configuration, such as handover hysteresis, handover offset and Time-To-Trigger (TTT), takes place [59, 60]. The errors include those that cause Radio Link Failures (RLFs) due to the handover timing or a handover to an incorrect cell.
- *Energy Saving* is yet another self-optimization use case which optimizes the RAN energy consumption [61, 62]. In this use case, a cell, which is originally deployed for boosting the RAN capacity, is switched off at the times when the additional capacity is not needed and is switched on again when there is a larger capacity demand.

2.1.4 Self-Healing

Self-healing performs the auto-detection of BS faults, for instance, due to a hardware or software malfunction. It may also carry out the auto-healing of a possible cell outage, which is also known as Cell Outage Compensation (COC). The phases leading to COC are illustrated in Figure 2.2 assuming a non-deterministic deployment scenario where the network deployment for the downtown area of Helsinki is simulated.

Figure 2.2. Illustration of COC (from the RAN performance perspective in terms of SINR in decibels) where the cell outage is detected by the self-healing mechanism and the coverage loss is compensated by the neighboring BSs by means of the adaptation of antenna parameters (EDT, antenna azimuth and horizontal HPBW): a) All the BSs are fully operational (marked in red), b) One of the BSs has a malfunction resulting in the cell outages (marked in yellow), c) The neighboring BSs adapt their antenna parameters to compensate the coverage loss (marked in green).

Figure 2.3. Self-optimization use cases in relation to the SON architecture options.

Cell outage typically leads to a sudden loss of coverage and capacity. It may be observed as a drastic increase in the number of call drops. The self-adaptation of transmission power and antenna parameters, such as EDT, are given as the typical means for COC [63]. COC may take place in the operational phase, for instance, in parallel to the CCO process.

Once the COC process is completed, the service area where the cell outage occurs is compensated by the neighboring BSs. Therefore, possible PCI collision or confusion scenarios should be taken into account in the scope of self-configuration when COC is performed. Furthermore, due to the fact that neighbor relations may change, the ANR function needs to self-configure the neighbor lists of the affected BSs to ensure the reliable mobility within the cell outage area.

Minimization of drive tests can also be considered as a part of the self-healing process where regular UEs are enabled to provide the same type of information as those collected in the conventional drive tests. This allows the penetration of drive test information from outdoor to indoor environments.

2.2 SON Architecture Options

In addition to the functional classification, SON can be divided into four categories if an architectural approach is followed. In this case, the SON category depends on where the SON functionality resides. Accordingly, there are centralized SON, distributed SON, localized SON and hybrid SON [19]. Distributed SON and localized SON are also referred to as decentralized SON. Figure 2.3 represents the major self-optimization use

Figure 2.4. Main architecture options in SON where L-SON, D-SON and C-SON denote the localized, distributed and centralized SON architecture options, respectively.

cases in relation to the SON architecture options. In addition, Figure 2.4 depicts the network hierarchy of the SON architecture options.

2.2.1 Localized SON

Localized SON is the preferred architecture option when there is only a single cell involved in a SON process. In the localized SON architecture, SON functions reside at BS, and no SON-related information exchange needs to take place between BSs. Therefore, the use cases associated with the localized SON architecture benefits from the shorter decision times and faster parameter update rates thereof, for instance, in the case of Random Access Channel (RACH) optimization [58] [PVII].

2.2.2 Distributed SON

Distributed SON is needed when only a few cells are involved in a SON use case, for instance, when the mobility parameters are optimized for the adjacent cells by means of MLB [37, 38, 39] or MRO [59, 60]. In this case, the altered parameters could have an impact beyond a single cell, hence the SON algorithm needs to have the knowledge about the effects of potentially conflicting SON decisions.

Distributed SON may also take place to provide coordination between different self-optimization use cases as discussed in [64]. In order to pro-

vide the sufficient information for the SON use cases involving more than one cell, the SON functionality is distributed among adjacent BSs. The inter-BS interface, which is called X2 in the LTE RAN architecture, is used for exchanging the SON-related information among these BSs.

Although the distributed SON architecture allows more complex SON tasks (including the use case coordination) in comparison to the localized SON architecture, the number of cells managed within the distributed SON architecture are limited by the availability of the inter-BS interface. Also, the amount and the timeliness of the information exchanged among those cells depend on the interface capabilities. Therefore, the complexity of the SON tasks managed within the distributed SON architecture cannot be as large as the centralized SON architecture.

2.2.3 Centralized SON

Centralized SON is the architectural category where the SON functionality is located in the O&M system that appears on a higher level in the logical system architecture as illustrated in Figure 2.4. Thus, it allows much more complex SON tasks to be executed including the potential multi-vendor use cases.

Centralized SON is typically needed when a large number of cells is involved in a SON function. For instance, when the self-optimization of EDT takes place for a deployment-wide coverage optimization process, a subset of cells are optimized in parallel as discussed in [PIV, PV].

Due to the use of long-term KPI statistics, the parameter update period in centralized SON is longer than those in the distributed and localized SON architecture options.

2.2.4 Hybrid SON

Hybrid SON is composed of the localized, distributed and centralized SON architecture options. Whilst SON functions using only local information reside at BSs, more complex SON tasks requiring inter-cell information exchange are distributed among BSs or moved to the O&M system.

Due to the fact that network operators aim to run a number of SON solutions with different requirements as well as the ones with the multi-vendor involvement, the hybrid SON architecture has to be adopted in practice for LTE networks and its evolution toward 5G.

In addition to these architecture options, SON architecture may further

evolve in parallel to the advancements in cellular technologies. For instance, the extension of the SON architecture toward UE may enable the utilization of UE context. Whether this is beneficial or not is a research question that needs to be answered in 5G research.

3. System Model

This chapter outlines the key methods and modeling assumptions for a credible and reliable SON performance assessment that requires longer evaluation cycles than those used in the conventional RRM simulations.

While the proposed performance evaluation methodology is mainly targeted for the networks adopting LTE as the underlying Radio Access Technology (RAT), it could also provide valuable guidance for the future networks applying other OFDM-based RATs, such as NR.

3.1 Simulation Scenarios

Both deterministic and non-deterministic deployment models were taken into account for the system-level performance evaluations. While the deterministic deployment modeling allows a comparable analysis to the literature and the 3GPP simulation studies, the non-deterministic deployment modeling enables the simulation of more realistic network topologies and the optimization challenges within these topologies.

3.1.1 Deterministic Deployment Scenarios

The deterministic deployment modeling is mainly based on the recommended 3GPP urban and suburban macro scenarios that are called 3GPP case 1 and 3GPP case 3, respectively [65, 66]. Both deployment scenarios assume a regular cell layout where the Macro-BS (MBS) deployment characteristics are mainly determined by the Inter-Site Distance (ISD). While 3GPP case 1 employs a relatively short ISD that is 500 m, the ISD in 3GPP case 3 is 1732 m.

It is observed from the simulation results that the coverage in 3GPP case 1 is limited by the Inter-Cell Interference (ICI), whereas the coverage in 3GPP case 3 is limited by the background noise. This is because the

Figure 3.1. Coverage maps for a) 3GPP case 1 MBS deployment, b) 3GPP case 3 MBS deployment and c) 3GPP SBS deployment, respectively. The maximal received power level is calculated in dBm for 200 KHz reference BW.

path loss grows exponentially with the distance, and the received signal power decreases near the noise level when the ISD gets longer. Figures 3.1.a and 3.1.b illustrate the coverage maps for 3GPP case 1 and case 3 respectively, where this phenomenon can be clearly observed. Both deployment scenarios were simulated to explore the optimization space for the selected RAN parameters in [PI, PII, PIII, PVII]. The main simulation assumptions used in these studies are given in Table 3.1.

3.1.2 Semi-Deterministic Deployment Scenarios

Semi-deterministic deployment scenarios were modeled based on the simulation guidelines given in [66]. As shown in Figure 3.1.c, Small-BSs (SBSs) are randomly and uniformly distributed over the coverage area of an MBS with a 40 m minimum distance. By means of this random

process, the irregularity of real-world HetNet deployments are simulated while the specified distribution model and parameter values [66] set the boundary conditions for the scenario.

Table 3.1. System-level simulation assumptions for the deterministic and semi-deterministic deployment scenarios modeled for the simulation studies conducted in [PI, PII, PIII, PVII, PVIII].

Parameter	Modeling/Value
Carrier freq.	2 GHz
BW	DL: 10 MHz, UL: 10 MHz
Duplexing	FDD
Monitored link	DL [PI, PII, PIII, PVIII], UL [PVII, PVIII]
MBS ISD	500 m [PI, PII, PIII, PVII], 1732 m [PI, PII, PIII]
SBS ISD	40 m (minimum)
MBS ant. height ¹	32 m [PI, PII, PIII], 25 m [PVIII]
SBS ant. height ¹	10 m
UE ant. height ¹	1.5 m [PI, PII, PIII, PVIII]
Shadowing	MBS: 8 dB [PI, PII, PIII, PVII], 6 dB [PVIII];
stand. deviation	SBS: 4 dB
Shadowing decor.	0.5 (inter-site), 1 (intra-site)
Shadowing decor. distance	MBS: 50 m [PI, PII, PIII, PVII], 40 m [PVIII];
	SBS: 10 m
Thermal noise	-104.5 dBm (for 10 MHz)
Max. DL power	MBS: 46 dBm [PI, PII, PVII, PVIII], 43 dBm [PIII];
	SBS: 30 dBm
UL power control	P_{max} : 21 dBm, P_0 : -54 dBm, α : 0.6 [67, 68]
MBS ant. gain ²	16 dBi [PVII, PVIII]
SBS ant. gain	5 dBi
MBS cable loss	2 dB
SBS cable loss	0 dB
UE ant. gain	UE: 0 dBi
Noise figure	MBS: 5 dB, SBS: 6 dB, UE: 9 dB
MIMO ³	1x2 MRC

¹In [PVIII], antenna height is used as an input only to the path loss models.

²In [PI, PII, PIII], MBS antenna gain depends on the selected horizontal and vertical HPBW.

³Maximal Ratio Combining (MRC) is not the sole but the common MIMO technique used in [PI, PII, PIII, PVII]. In [PVIII], MIMO techniques are not studied.

Figure 3.2. a) LTE network layout for the downtown Helsinki scenario, b) LTE coverage map for the downtown Helsinki deployment where the received power level is calculated in dBm for 200 KHz reference BW.

In [PVIll], the deployment model was applied to simulate the network densification toward 5G. In these simulations, it was assumed that the MBS and the SBSs operate at different frequency bands. Figure 3.1.c illustrates the coverage map obtained for the small-cell layer. Table 3.1 includes the system-level simulation assumptions applied in [PVIll].

3.1.3 Non-Deterministic Deployment Scenarios

The non-deterministic deployment modeling is based on the downtown Helsinki scenario with an irregular network layout where the ISD varies between 500 m and 1750 m [69]. The network layout and the coverage map are depicted in Figures 3.2.a and 3.2.b.

Table 3.2. System-level simulation assumptions for the non-deterministic deployment scenarios modeled for the simulation studies conducted in [PIV, PV, PVI].

Parameter	Modeling/Value
Carrier frequency	2 GHz
BW	10 MHz
Duplexing	FDD
Monitored link	DL
ISD ⁴	[500 m, 1750 m]
BS antenna height	[16 m, 20 m]
Shadowing standard deviation	8 dB
Shadowing decorrelation	0.5 (inter-site), 1 (intra-site)
Shadowing decorrelation distance	50 m
Thermal noise	-104.5 dBm (for 10 MHz)
Max. BS power	46 dBm
BS antenna gain	17 dBi
BS cable loss	2 dB
UE antenna gain	0 dBi
UE noise figure	9 dB
MIMO	1x2 MRC

The co-existence of different types of propagation characteristics due to buildings, streets etc. in a single scenario enables the simulation of real-world problems especially from the mobility perspective, unlike in the specified 3GPP urban and suburban scenarios. The network deployment also presents a potential UMTS site reuse scenario with LTE. These characteristics of the scenario make the downtown Helsinki deployment attractive for the SON performance evaluations that were carried out in [PIV, PV, PVI]. Table 3.2 summarizes the system-level simulation assumptions used in these studies.

3.2 Channel Access Modeling

Prior to the data exchange in OFDM-based RATs, User Equipment (UE) needs to apply a Random Access (RA) procedure to synchronize in UL with BS. In LTE, the RA mechanism is specified in [70] and defines the

⁴ISD is computed for those sites that are included in each other's neighbor list in ANRs.

RA procedures that are used at least for the following events [51]:

- a) initial access of an idle-mode UE,
- b) handover of a connected-mode UE to another cell,
- c) Radio Resource Control (RRC) connection re-establishment after a Radio Link Failure (RLF) event,
- d) UL data arrival for a connected-mode UE when UL synchronization status is non-synchronized,
- e) DL data arrival for a connected-mode UE when UL synchronization status is non-synchronized,
- f) UE positioning requiring the timing advance information.

Based on the events listed above, it is evident that adequate RA performance is essential to guarantee low delays for the channel access and data transmission thereof.

In the remainder of this section, first, the RA procedures and the Random Access Channel (RACH) configuration, where LTE is assumed as the underlying RAT, are outlined. Next, the stochastic modeling of RA is presented in detail. The discussion on the stochastic modeling is based on [PVII].

3.2.1 Random Access Procedures

In LTE, the RA mechanism comprises the Contention-Based Random Access (CBRA) and Non-Contention-Based Random Access (NCBRA) procedures [51]. While CBRA could be applied in both connected and idle modes, NCBRA is used only in the connected mode. As illustrated in Figure 3.3, the NCBRA procedure has less signaling steps and admits shorter delays than the CBRA procedure thereof. This is because the RA resources (i.e., preamble sequences), are reserved per UE for the NCBRA procedure beforehand. In this case, the contention-resolution step is not needed. Inter-node handover is one of typical examples where the NCBRA procedure is applied.

Figure 3.3. Signaling diagrams for a) CBRA and b) NCBRA, respectively.

3.2.2 RACH Configuration

There are a number of ways to configure the Physical Random Access Channel (PRACH) resources in terms of the time-frequency allocation and the transmission power level [70, 71]. The main configuration aspects are summarized as follows:

- *PRACH preamble period* defines the time period where an RA opportunity exists. The longer the periodicity is, the larger the channel access delay is. However, more resources can be used for the control and data signaling when the preamble (sequence allocation) periodicity is longer.
- *PRACH frequency offset* indicates the position of the RA preamble resources in the frequency domain. To avoid overlapping allocations by different cells, the frequency offset used in the serving cell is expected to indicate a different allocation than those used in the neighboring cells.
- *Preamble split* refers to the further allocation of the CBRA and NCBRA resources in a given preamble which comprises 64 unique sequences generated from the cyclic shifts of root Zadoff-Chu sequences [71]. Therefore, it mainly affects the CBRA and NCBRA performance rather than the Physical Uplink Shared Channel (PUSCH) performance.
- *Initial received target power* is the parameter used for estimating the initial preamble transmission power in order to ensure the preamble

detection by the targeted BS. The larger the received power target is, the higher the preamble detection probability is. Yet a large received power target also results in shorter battery lifetime and higher UL interference due to the increased transmission power.

- *Power ramping step* defines the amount of increase in the transmission power level when an RA attempt fails, and a preamble retransmission is needed. A larger power ramping step translates into a higher preamble detection probability in the retransmission. However, if it is configured wrong, larger power consumption and more interference to other UEs are expected.

3.2.3 Stochastic Modeling of Random Access

This subsection describes the stochastic modeling of RA that was originally introduced in [PVII]. The KPIs used in the RA modeling are defined as follows:

- Detection Miss Probability (DMP) refers to the probability that an RA preamble, which is transmitted by UE, is not detected by BS.
- Contention Probability (CP) refers to the probability that a CBRA preamble is collided with another, given that the received power of the preamble is large enough to be detected by BS.
- Blocking Probability (BP) is the probability that an NCBRA preamble is blocked over the dedicated preamble sequences.

Variable DMP is modeled as the sum of the mean DMP, DMP_{mean} , which is assumed to equal 1%, and the zero-mean Gaussian variable, EE_{DMP} ,

$$DMP = DMP_{mean} + EE_{DMP}. \quad (3.1)$$

Here, EE_{DMP} admits the standard deviation, σ_{DMP} , which is assumed to equal 2% in the study carried out for the dissertation [PVII]. The selected values for the distribution are based on the results obtained from the link-level studies and the literature [58].

Poisson distribution is adopted for modeling the RA traffic [72],

$$P_{RA,k} = \frac{n_{RA}^k \cdot e^{-n_{RA}}}{k!}, \quad (3.2)$$

where $P_{RA,k}$ is the probability of k RA attempts per preamble period, and n_{RA} is the expected number of RA attempts per preamble period.

The number of detected RA attempts per preamble period is denoted by $n_{C,d}$ and $n_{NC,d}$ for the CBRA and NCBRA procedures and approximated as follows:

$$n_{C,d} = (1 - DMP_C) \cdot n_C, \quad (3.3)$$

$$n_{NC,d} = (1 - DMP_{NC}) \cdot n_{NC}. \quad (3.4)$$

Here, DMPs for CBRA and NCBRA, which are denoted by DMP_C and DMP_{NC} , are the results of two independent random variables. Yet they follow the same assumptions in terms of DMP. Moreover, n_C and n_{NC} refer to the expected number of the CBRA and NCBRA attempts, and $n_{RA} = n_C + n_{NC}$.

Numbers $n_{C,pre}$ and $n_{NC,pre}$, which can be adaptively tuned, account for the preamble sequences allocated for CBRA and NCBRA respectively,

$$n_{C,pre} = \left(\frac{1}{t_{RA}} \right) \cdot (1 - p_d) \cdot n_{total,pre}, \quad (3.5)$$

$$n_{NC,pre} = \left(\frac{1}{t_{RA}} \right) \cdot p_d \cdot n_{total,pre}, \quad (3.6)$$

where t_{RA} is the preamble period, $n_{total,pre}$ is the total number of preamble sequences, and p_d is the preamble split which refers to the ratio of RACH signatures that are dedicated for NCBRA.

In the case of CBRA, an RA attempt might collide with another, unlike NCBRA. In this regard, collision rate, CR_k , is defined per preamble period for a set of k CBRA attempts,

$$CR_k = \binom{N_{C,d} - 1}{k - 1} \cdot (n_{C,pre} \cdot N_{RA})^{-(k-1)} \cdot \sum_{s=k}^{N_{C,d}} P_{C,s}, \quad (3.7)$$

where $N_{C,d}$ denotes the number of detected CBRA attempts per system-level evaluation period, $P_{C,s}$ is the probability of having s CBRA attempts per preamble period, and N_{RA} is the number of preambles per system-level evaluation period.

If CR_k is greater than or equal to 1, $k - 1$ contentions occur. In this case, the contention probability per preamble period for a set of k CBRA attempts, CP_k , is biased at 1,

$$CP_k = \begin{cases} CR_k, & CR_k \leq 1, \\ 1, & CR_k > 1. \end{cases} \quad (3.8)$$

CP - denoted by CP - is the sum of the unique event probabilities,

$$CP = \sum_{k=2}^{N_{C,d}} CP_k \cdot \left(\frac{k-1}{k} - \frac{k-2}{k-1} \right). \quad (3.9)$$

In the case of NCBRA, a dedicated preamble sequence is assigned to UE for RA, such as in the case of handover, so that no contention occurs. However, dedicated access is available only if there is a sufficient number of dedicated preamble sequences. In practice, this means the CBRA procedure replaces the NCBRA procedure if there is no dedicated RACH signature allocated. In the performance evaluation methodology, it refers to BP (a.k.a. Blocking Rate), which is defined for NCBRA and denoted by BP ,

$$BP = \sum_{l=n_{NC,pre}+1}^{N_{NC,d}} P_{NC,l} \cdot \frac{l - n_{NC,pre}}{l}, \quad (3.10)$$

where l is the number of NCBRA attempts per preamble period, $N_{NC,d}$ is the number of detected NCBRA attempts per evaluation period, and $P_{NC,l}$ is the probability of having l NCBRA attempts per preamble period.

Based on the CBRA and NCBRA performance metrics that are DMP , CP and BP , Access Probabilities (APs) for CBRA and NCBRA at the m^{th} RA attempt - denoted by $AP_{C,m}$ and $AP_{NC,m}$ respectively - are given as follows:

$$AP_{C,m} = 1 - \prod_{i=1}^m (DMP_{C,i} + (1 - DMP_{C,i}) \cdot CP), \quad (3.11)$$

$$AP_{NC,m} = 1 - \prod_{i=1}^m (DMP_{NC,i} + (1 - DMP_{NC,i}) \cdot BP). \quad (3.12)$$

3.3 Channel and Link-Level Modeling

In the system-level simulations, the modeling of wireless channel and the implementation of link-level RAT capabilities are simplified in comparison with the link-level evaluations. This is because the typical simulation length of a system level evaluation could be at least two orders of magnitude larger than the typical simulation length of a link-level evaluation. Another reason why the simulator reduces the Physical Layer (PHY) complexity is to minimize the computational overhead. Simplified modeling also helps the simulator remove the effects of suboptimally configured PHY parameters on the system-level performance results. Even though, the PHY modeling needs to be abstracted as such, the performance evaluation methodology should still model the fundamental phenomena ob-

served in the wireless channel, such as slow fading (and fast fading if mobility is modeled in detail) as described in this section. Furthermore, it should take the link-level limitations of the underlying RAT into consideration. In this respect, the section discusses how the link loss and the SINR are calculated in [PI-PVIII].

Path loss - denoted by $L_{PL,u}^c$ in Equations (3.13) and (3.14) - is modeled based on [65, 66] for the deterministic [PI, PII, PIII, PVII] and semi-deterministic [PVIII] deployment scenarios. In the evaluations of the non-deterministic deployment scenarios [PIV, PV, PVI], the path loss is adopted from [69]. In [69], the path loss was calculated using a ray-tracing program for the micro-cell scenario and the Okumura-Hata model for the macro-cell scenario. The simulations of the deterministic deployment scenarios follow the macro-cell system simulation baseline parameters given in [65], including the distant-dependent path loss. In the case of the semi-deterministic deployment scenario, the International Telecommunication Union - Radiocommunication Sector (ITU-R) M.2135 urban macro- and urban micro- models [73] are adopted from [66]. However, only the non-line-of-sight propagation characteristics of the ITU-R M.2135 models are taken into account in the simulations. Furthermore, additional 20 dB loss is included in the path loss calculation when a UE is located indoors and the serving BS is located outdoors in the case of both deterministic and semi-deterministic deployment scenarios.

Link loss accounts for the product of path loss, antenna directivity gain, channel fading, and other losses, such as connector or cable loss. In this regard, $L_{DL,u}^c$ and $L_{UL,u}^c$, both of which are on a linear scale, refer to the link loss in DL and UL respectively,

$$L_{DL,u}^c = L_{PL,u}^c \cdot A_u^{c-1} \cdot \Delta_{DL,u}^c \cdot X, \quad (3.13)$$

$$L_{UL,u}^c = L_{PL,u}^c \cdot A_u^{c-1} \cdot \Delta_{UL,u}^c \cdot X. \quad (3.14)$$

Here, A_u^c denotes the antenna directivity gain which is the product of maximum antenna gain and antenna radiation pattern. X refers to other link losses, such as cable/connector loss. Furthermore, the channel fading loss in DL, $\Delta_{DL,u}^c$, and the channel fading loss in UL, $\Delta_{UL,u}^c$, are taken into account in the DL and UL link loss calculations, respectively. Channel fading accounts for both the spatially correlated shadowing (a.k.a. slow fading) that captures the large-scale effects (e.g., buildings, hills and foliage) along the path profile and the fast fading that models the effects of small-scale channel variations. Shadowing follows Gaussian distribu-

tion on a logarithmic scale where the spatial correlation depends on the antenna location. Fast fading follows the (user velocity-dependent) time-correlated Rayleigh distribution (i.e., the exponential distribution in the case of power loss) for which the samples are generated by using a statistical sum-of-sinusoids method as described in [74]. Fast fading and Layer 3 (L3) filtering thereof are only modeled for the studies in [PV, PVI] where the impact of CCO on the mobility robustness is evaluated in DL.

Signal to Interference plus Noise Ratio (SINR) is a signal quality indicator that can be used for approximating how many bits can be reliably carried over the air interface, and how many Physical Resource Blocks (PRBs) need to be assigned per UE in the case of the Guaranteed Bit Rate (GBR) service. In the HetNet scenarios where MBSs and SBSs operate at different frequency layers, SINR is calculated for each layer separately. Hereinafter, BS may refer to either SBS, MBS, or a certain cell of MBS if it employs more than one logical cell.

The SINR in DL, $\gamma_{DL,u}^s$, is defined by

$$\gamma_{DL,u}^s = \frac{P_{max}^s \cdot L_{DL,u}^s{}^{-1}}{\sum_{n \neq s} \rho^n \cdot P_{max}^n \cdot L_{DL,u}^n{}^{-1} + N_{DL}}. \quad (3.15)$$

Here, P_{max}^s refers to the maximum DL power of serving BS s , P_{max}^n is the maximum DL power of interfering BS n , $L_{DL,u}^s$ is the link loss in DL between UE u and serving BS s , and $L_{DL,u}^n$ is the link loss in DL between UE u and interfering BS n . Moreover, N_{DL} is the total noise in DL that accounts for both the thermal noise and the noise figure in the receiver, and ρ^n denotes the traffic load in the interfering cell. It should be noted that in the case of the coordinated scheduling [35], which models the dynamic point selection and muting feature for the Vertical Sectorization (VS) studies in [PVI], interfering cell cannot be the adjacent (vertical) subsector since adjacent subsectors form a cooperating set.

The SINR in UL, $\gamma_{UL,u}^s$ is given by

$$\gamma_{UL,u}^s = \frac{P_u^s \cdot L_{UL,u}^s{}^{-1}}{\sum_{n \neq s} \sum_{i \neq u} P_i^n \cdot L_{UL,i}^s{}^{-1} + N_{UL}}, \quad (3.16)$$

where P_u^s refers to the UL power of UE u connected to serving BS s , P_i^n is the UL power of interfering UE i , $L_{UL,u}^s$ is the link loss in UL between UE u and serving BS s , and $L_{UL,i}^s$ is the link loss in UL between interfering UE i and BS s . In addition, N_{UL} is the total noise in UL that accounts for both the thermal noise and the noise figure in the receiver.

3.4 Link-to-System Modeling

In this section, the link-to-system mapping methodology developed within the doctoral studies [PI-PVIII] is recalled and summarized.

Based on the methodology proposed in [75] and the 3GPP guidelines given in [76], the radio link performance in terms of Spectral Efficiency (SE), SE_u^s , is approximated by using a weighted and truncated form of Shannon capacity bound,

$$SE_u^s = \begin{cases} 0, & \gamma_u^s < \gamma_{min}, \\ BW_{eff} \cdot MCS_{eff} \cdot \log_2(1 + \gamma_u^s), & \gamma_{min} \leq \gamma_u^s \leq \gamma_{max}, \\ BW_{eff} \cdot MCS_{max}, & \gamma_u^s > \gamma_{max}. \end{cases}, \quad (3.17)$$

with

$$\gamma_u^s = \begin{cases} \bar{\gamma}_{DL,u}^s, & LF(u, s) = DL, \\ \bar{\gamma}_{UL,u}^s, & LF(u, s) = UL. \end{cases}.$$

Here, LF refers to the link function, which indicates the evaluated radio link (i.e., either DL or UL), and γ_u^s denotes the SINR of the evaluated link over the evaluation period (i.e., $\bar{\gamma}_{DL,u}^s$ or $\bar{\gamma}_{UL,u}^s$). γ_u^s - together with the PHY properties of the radio link - translates into the SE. Accordingly, BW_{eff} refers to the product of adjacent channel leakage ratio efficiency, cyclic prefix efficiency and reference symbol efficiency. Furthermore, MCS_{eff} adjusts the Modulation and Coding Scheme (MCS) efficiency with respect to the Shannon capacity bound, γ_{min} refers to the minimum SINR that is required for maintaining the radio link connection with the serving cell, γ_{max} denotes the maximal SINR at which the maximum SE can be reached, and MCS_{max} refers to the maximum SE for the highest MCS assumed in the performance evaluation methodology. The numerical values for these parameters are given in Table 3.3.

It should be noted that for the studies conducted in [PVIII], MCS_{max} , MCS_{eff} and BW_{eff} are assumed to be ideal for the underlying OFDM-based RAT since the 5G PHY design parameters were still under discussion at the time when the performance evaluations took place. Furthermore, the Physical Downlink Control Channel (PDCCH) overhead for both common and dedicated signaling is taken into account in the initial studies that addresses the LTE capacity [PI, PII, PIII, PIV, PVII]. Yet in order to keep the performance evaluation methodology unaffected by the the possible changes in the evolution of 3GPP specifications, the PDCCH overhead is neglected in the later studies [PV, PVI, PVIII]. It is also noteworthy that the link-level scheduler gains in time and frequency domains

Table 3.3. Link adaptation parameters used in the link-to-system modeling.

Parameter	Modeling/Value
Max. SE	4.80 bit/symbol (64-QAM 4/5) [PI, PII, PIII, PIV, PVII], 5.55 bit/symbol (64-QAM 948/1024) [PV, PVI], 9.97 bit/symbol [PVIII]
MCS eff.	0.75 [PI, PII, PIII, PIV, PV, PVI, PVII], 1.0 [PVIII]
BW eff.	0.80 [PI, PII, PIII, PIV, PV, PVI, PVII], 1.0 [PVIII]
PDCCH rate	0.285 [PI, PII, PIII, PIV, PVII], 0.0 [PV, PVI, PVIII]
Min. SINR	-10 dB
PRB alloc.	RFRA [PI, PII, PIII, PIV, PV, PVIII], TFRA [PV, PVI, PVII]

are not included in the throughput calculations. In other words, round-robin scheduler is assumed in the studies.

The radio link performance in terms of UE throughput, TP_u^s , is given by

$$TP_u^s = BW_u^s \cdot SE_u^s, \quad (3.18)$$

where BW_u^s refers to the average BW allocation per UE (per evaluation period in the case of dynamic simulations) in the serving BS including the BW overhead. The assignment of BW_u^s depends on the service modeling as defined in Equations (3.19) and (3.20).

In the studies conducted for the dissertation, both Best-Effort (BE) and GBR types of services are considered in the system-level performance evaluation methodology by modeling Resource-Fair Resource Allocation (RFRA) and Throughput-Fair Resource Allocation (TFRA), respectively. The evaluations where the RFRA method is applied assumes only the Full-Buffer (FB) traffic. However, the evaluations in which the TFRA method is applied assumes both FB and Variable-Buffer (VB) utilization of PRBs. The modeling of VB traffic is essential for the research work, such as in [PVI], where the relationship between the traffic load and the ICI is studied.

In the performance evaluations that assume the BE service type and model the RFRA method thereof, BW_u^s , which refers to the average BW allocation per UE (for the evaluated link), is given by

$$BW_u^s = \frac{BW_{all}^s}{U_{total}^s}. \quad (3.19)$$

Here, BW_u^s , is assumed to include the BW overhead which occupies 10%

of the total system BW in LTE due to the guard bands. This is because BW_{eff} accounts for the the link-level BW efficiency in the throughput calculations associated to the underlying OFDM-based RAT. As can be seen in Equation (3.19), in the case of RFRA, BW_u^s depends on the total number of UEs that are connected to the serving BS (per evaluation period), U_{total}^s , and the average system BW that is allocated (per evaluation period) to the serving BS (in the evaluated link), BW_{all}^s .

In the performance evaluations that assume the GBR service type and model the TFRA method thereof, BW_u^s , in order to satisfy the GBR requirement, is calculated by

$$BW_u^s = \frac{GBR}{SE_u^s}, \quad (3.20)$$

where BW_u^s depends on the GBR requirement, GBR , and the link quality that is indicated in terms of SE_u^s .

In the case of both RFRA and TFRA methods, the BS load (in the evaluated link), ρ^s , becomes maximum if the FB traffic is assumed. When RFRA is modeled with the VB utilization of PRBs, ρ^s is directly proportional to the total BW demand in the BS and defined by

$$\rho^s = \begin{cases} \min \left(1, \frac{\sum_{u \in s} BW_u^s}{BW_{all}^s} \right), & \text{VB,} \\ 1, & \text{FB.} \end{cases} \quad (3.21)$$

When assuming the coordinated scheduling, which models the dynamic point selection and muting feature, for a cell pair as studied in [PVI], BW_{all}^s is given by

$$BW_{all}^s = BW_{sys} \cdot \frac{\rho^s}{\rho^s + \rho^{m,s}}. \quad (3.22)$$

Here, BW_{sys} refers to the total system BW (for the evaluated link), and $\rho^{m,s}$ denotes the traffic load in BS m that is coordinated with serving BS s (in the evaluated link). In this case, BS m is not allowed to perform transmission/reception simultaneously (i.e., muted) in the same PRBs as serving BS s transmits/receives (in the evaluated link).

In the performance evaluations where VB utilization of PRBs is assumed, the aforementioned BW allocation and traffic load parameters - BW_u^s , BW_{all}^s , ρ^s , ρ^n and $\rho^{m,s}$ - should be iteratively re-computed, starting from the FB traffic assumption, until the computational convergence is ensured as proposed in [77]. Thereby, the satisfied user ratio in the serving BS, SR^s , is approximated by

$$SR^s = \min \left(1, \frac{BW_{all}^s}{\sum_{u \in s} BW_u^s} \right). \quad (3.23)$$

Figure 3.4. Illustration of a handover execution scenario and the parameters used in the mobility modeling.

3.5 Mobility Modeling

Mobility modeling is comprised of two parts: handover and Radio Link Monitoring (RLM). While handover modeling applies to the studies presented in [PV, PVI, PVII, PVIII], RLM modeling applies only to the performance evaluations carried out in [PV, PVI] where the impact of CCO on the mobility robustness is studied in DL.

Handover modeling is based on the evaluation of filtered Reference Signal Received Power (RSRP) measurements. According to the L3 filtering described in the LTE RRC specification [68], the filtered RSRP of a detectable cell, Q_R , at time instance t , is given by

$$Q_R(t) = \left(1 - (1/2)^{K/4}\right) \cdot Q_R(t - T_{L3}) + (1/2)^{K/4} \cdot R_{L1}(t), \quad (3.24)$$

where R_{L1} is the latest average L1 RSRP measurement at the PHY, T_{L3} is the L3 measurement period, and K is the filter coefficient. If K is set to 0, no L3 filtering is applicable.

As shown in Figure 3.4, a handover from the serving BS to the target BS is triggered provided that following two conditions are fulfilled i) the sum of the filtered RSRP of the target BS, Q_R^n , and the handover offset, Q_n^s , exceeds the filtered RSRP of the serving BS, Q_R^s , by a number of decibels equal to the handover hysteresis, Q_h^s ; ii) condition i) is met along the Time-To-Trigger (TTT) period, T_{HO}^s , configured by the serving BS. Thus, the handover event is defined by

$$Q_R^s(t) + Q_h^s < Q_R^n(t) + Q_n^s, \quad \tau \leq t \leq \tau + T_{HO}^s, \quad (3.25)$$

Table 3.4. Handover and RLM parameters for [PV, PVI, PVII, PVIII].

Parameter	Modeling/Value
Evaluation period	200 ms [PV, PVI], 1000 ms [PVII], 1 ms [PVIII]
TTT	250 ms [PV, PVI], 850 ms [PVII], 100 ms [PVIII]
Max. HO delay	150 ms [PV, PVI, PVII], 0 ms [PVIII]
HO hysteresis	4 dB [PV, PVI, PVII], 3 dB [PVIII]
HO offset	b/w sectors/sites: 0 dB, b/w subsectors: 4 dB [PVI]
SINR thresholds	$Q_{in} = -6$ dB, $Q_{out} = -8$ dB, $Q_{drop} = -9$ dB
Meas. interval (L1)	50 ms (fast-fading sampling)
Meas. period (L3)	200 ms
Filter coefficient	4 [PV, PVI], 0 [PVII, PVIII]
RLF timer 1 ⁵	0.5 s
RLF timer 2	1 s

where τ denotes the measurement time. The numerical values for the handover modeling parameters used in Equation (3.25) are given in Table 3.4.

The handover delay - denoted by Δt in Figure 3.4 - occurs due to the time period needed for handover preparation and execution. In [PV, PVI, PVII], the maximum handover delay assumption, which is based on [78, 79], is shorter than the evaluation period. Therefore, in the system-level simulator implementation, the handover delay is added on top of TTT. The TTT assumption follows the typical range of values applied in the literature [59, 64, 78, 79]. For the 5G HetNet evaluations presented in [PVIII], the potential handover delay is neglected because the simulation scenario assumes a low-latency handover mechanism with 0 ms interruption in the user plane. This assumption is aligned with the 5G design requirements set by ITU-R [7]. Since the user plane interruption is not a threat to the mobility performance in [PVIII], the TTT and handover hysteresis values are assumed to be smaller than the ones applied in the LTE studies [PV, PVI, PVII].

The RLF and Handover Failure (HOF) event statistics are used for the mobility robustness assessments. The modeling of the events is based on the evaluation of time-varying SINR measurements (in DL) in compari-

⁵In the simulator implementation, the effective value for the RLF timer 1 is 0.6 s because the evaluation period is 200 ms.

son to the signal quality thresholds. Accordingly, Q_{in} , Q_{out} and Q_{drop} refer to the SINR thresholds that indicate 2%, 10% and 90% Block Error Rates (BLERs) at a hypothetical PDCCH, respectively. In the light of the RLF description in [68], the mobility robustness KPIs (from the serving BS perspective), KPI_{MR}^s , are RLF, call drop, successful handover, late handover and handover drop respectively,

$$KPI_{MR}^s = \begin{cases} \text{RLF,} & \gamma_{RLF1}^s < Q_{out}, \\ \text{call drop,} & \gamma_{RLF1}^s < Q_{out} \text{ and } \gamma_{RLF2}^s < Q_{in}, \\ \text{successful handover,} & \gamma_{HO}^s \geq Q_{out}, \\ \text{late handover,} & \gamma_{HO}^s < Q_{out}, \\ \text{handover drop,} & \gamma_{HO}^s < Q_{drop}. \end{cases} \quad (3.26)$$

Here, γ_{HO}^s is the SINR in the DL of the serving BS when the handover is triggered, and it is used for assessing the probability of a successfully received handover command. Performance metrics γ_{RLF1}^s and γ_{RLF2}^s refer to the mean SINR in the DL of the serving BS, which is measured during the first (a.k.a. radio problem detection) and the second (a.k.a. radio link recovery) timers, T_{RLF1} and T_{RLF2} , respectively. A typical setting for the radio problem detection timer is in the range of [500 ms, 1000 ms] as discussed in [80].

3.6 Antenna Modeling

Antenna radiation pattern modeling (of an MBS) is an essential component of the performance evaluation methodology. This is because the signal quality indicator, SINR, largely depends on the link loss which is mainly the product of path loss and antenna directivity gain as can be seen in Equations (3.13) and (3.14). Publications [PVII, PVIII] assume the Two Dimensional (2D) modeling of the antenna radiation pattern by abstracting the elevation-plane pattern. Publications [PI, PII, PIII, PIV, PV, PVI], where the antenna optimization scenarios are evaluated, takes into account both azimuth- and elevation- plane patterns. This way, the antenna radiation pattern is constructed in Three Dimensional (3D). Table 3.5 defines the main antenna parameters that are used in the system-level performance evaluations.

Based on the 3GPP simulation guidelines given in [65, 66], antenna radiation (gain) patterns (in decibels) are modeled for the horizontal- and

Table 3.5. Antenna parameters and value ranges used (for MBSs) in the system-level performance evaluations.

Parameter	Value/Range
Hor. HPBW	[45°, 85°] [PI], 70° [PII, PVII, PVIII], 65° [PIII, PIV, PVI], [35°, 135°] [PV]
MFTBA	25 dB
Ver. HBPW	{4.4°, 6.8°, 9.4°, 10.0°, 13.5°} [PI], 10° [PII], {3.0°, 4.4°, 6.8°} [PIII], 8.5° [PIV, PV, PVI]
SLA	20 dB
EDT	[0°, 20°] [PI, PII, PIII], [0°, 10°] [PIV, PV, PVI]
MDT	0° [PI, PIII, PIV, PV], [0°, 20°] [PII], [0°, 2.5°] [PVI]
Azimuth	0° [PI, PII, PIII, PIV, PVI], [-40°, 40°] [PV]

vertical- planes, A_h^c and A_v^c respectively,

$$A_h^c(\varphi) = -\min \left[12 \left(\frac{\varphi - \varphi_{AS}}{\varphi_{3dB}} \right)^2, A_{max} \right], \quad (3.27)$$

$$A_v^c(\theta) = -\min \left[12 \left(\frac{\theta - \theta_{EDT}}{\theta_{3dB}} \right)^2, SLA_v \right]. \quad (3.28)$$

Here, φ and θ refer to the angular separation from the main lobe of the antenna radiation pattern in the azimuth- and elevation- planes, respectively. The directivity of the antenna is characterized by the horizontal Half Power Beamwidth (HPBW), φ_{3dB} , and the vertical HPBW, θ_{3dB} . As illustrated in Figures 3.5.a and 3.5.b, HPBW defines the angular width within which the antenna has at most 3 dB directivity loss. In the studies where the deterministic 3GPP deployment scenarios are assumed, the default (unoptimized) values for φ_{3dB} and θ_{3dB} follow those introduced in [66], which are 70° and 10°, respectively. Antenna radiation loss is limited by the Maximum Front-To-Back Attenuation (MFTBA), A_{max} , in the horizontal-plane and by the Side Lobe Attenuation (SLA), SLA_v , in the vertical-plane. This is because the antenna model takes the realistic antenna design effects into account as shown in Figure 3.5 and corresponds better to the limited isolation of co-sited sectors. Furthermore, the antenna radiation pattern is subject to the Electrical Downtilt (EDT), Mechanical Downtilt (MDT) and azimuth steering angles, which are denoted by θ_{EDT} , θ_{MDT} and φ_{AS} , respectively. As presented in [PV, PVI], antenna radiation loss pattern, which is the reciprocal of antenna gain pattern, can also be used in the antenna modeling terminology.

Figure 3.5. Comparison of the 3GPP antenna modeling [66] and the antenna product data [81]: a) Antenna radiation pattern in the azimuth plane, b) Antenna radiation pattern in the elevation plane (with 0° tilt). In the 3GPP model, the horizontal and vertical HPBWs are assumed to be 70° and 10° respectively, whereas the antenna product of which the data are visualized in the figure employs 65° horizontal HPBW and 9.4° vertical HPBW.

In the case of EDT, the main, side and back lobes of the antenna radiation pattern are downtilted uniformly by adjusting the phases of antenna elements. However, in the case of MDT, the main lobe is lowered on one side, and the back lobe is raised on the other side because the antenna elements are physically directed toward the ground [22]. In real-world deployments, MDT is required in combination with EDT. This is because the larger the EDT angle is, the less effective the antenna directivity becomes [30]. On the other hand, the adaptive adjustment of MDT may be slow, inaccurate and costly due to the need for manual effort when adjusting the MBS antenna [82]. Hence, MDT is assumed to be statically configured in the performance evaluation methodology.

In the earlier studies [PII] [83], it is shown that the system performance in the case of the combined tilt technique (with both EDT and MDT configurations) is not notably different from the single EDT configuration provided that the EDT contribution in the combined tilt technique is maximized. Due to the fact that the 3D antenna radiation is affected by the mechanical tilt configuration asymmetrically, the angular transformation in both horizontal- and vertical- planes needs to be applied for the performance evaluations that adopt MDT [PII, PVI]. Figure 3.6 represents the EDT and MDT techniques, and the elevation-plane geometry that is applied in Equation (3.27) - Equation (3.31).

Publication [PVI] follows the latest 3GPP model given in [66], which pre-

Figure 3.6. Antenna elevation angles - θ , θ_{EDT} and θ_{MDT} - are illustrated.

serves the radiation pattern shape and obeys the conservation of energy in comparison to the previous MDT model [84], as follows:

$$\hat{\varphi} = \arg \left(\cos \varphi \cdot \sin \left(\theta + \frac{\pi}{2} \right) \cdot \cos \theta_{MDT} - \cos \left(\theta + \frac{\pi}{2} \right) \cdot \sin \theta_{MDT} + j \sin \varphi \cdot \sin \left(\theta + \frac{\pi}{2} \right) \right), \quad (3.29)$$

and

$$\hat{\theta} = \frac{\pi}{2} - \arccos \left(\cos \varphi \cdot \sin \left(\theta + \frac{\pi}{2} \right) \cdot \sin \theta_{MDT} + \cos \left(\theta + \frac{\pi}{2} \right) \cdot \cos \theta_{MDT} \right). \quad (3.30)$$

Here, $\hat{\varphi}$ and $\hat{\theta}$ refer to the transformed angular separation from the main lobe of the antenna radiation pattern in the azimuth- and elevation- planes respectively when the MBS antenna is mechanically tilted.

In [PII], which studies the MDT performance in the LTE DL, the previous MDT model given in [84] is adopted. Yet the calibration studies revealed that the difference is negligible (around 0.1 dB) for both 3GPP case 1 and case 3 in terms of system-level KPIs, such as the 5th and 50th percentiles of SINR Cumulative Distribution Function (CDF).

Given A_h^c and A_v^c , the corresponding 3D radiation loss pattern, A_{3D}^c , is defined by

$$A_{3D}^c(\varphi, \theta) = \max \{ [A_h^c(\varphi) + A_v^c(\theta)], -A_{max} \} + A_g, \quad (3.31)$$

where A_g accounts for the maximum antenna (directivity) gain (in decibels), which is subject to the horizontal and vertical antenna pattern modeling, in comparison with an isotropic radiator. Angles φ and θ in Equations (3.27) and (3.28) are replaced by $\hat{\varphi}$ and $\hat{\theta}$ respectively when the MBS antenna is mechanically tilted.

In the case of Vertical Sectorization (VS), horizontal sector is divided into two or more subsectors in the elevation-plane. From the performance evaluation methodology perspective, it means that these subsectors will have the identical horizontal radiation loss pattern, A_h^c , but each one will have its own vertical radiation loss pattern, A_v^c , with a distinct θ_{EDT} . In practice, A_v^c and θ_{EDT} are formed for each subsector by the electronic adaptation of the phase delays and the amplitude weights of the signals emitted from the vertically aligned Active Antenna (AA) elements.

4. Self-Optimization Solutions and Performance Assessments

In this chapter, each self-optimization study is presented along with the discussion on optimization space (i.e., Radio Access Network (RAN) parameters and their value ranges), self-optimization methodology (i.e., SON architecture, Key Performance Indicators (KPIs) and optimization methods) and SON performance assessment (i.e., simulation results with a brief analysis). The discussion in this chapter is based on [PI-PVIII].

4.1 Antenna Parameter Optimization for Downlink

In this section, first, the impact of antenna parameters on the LTE DL performance is analyzed in terms of SINR. Next, the section summarizes the methodology for the self-optimization of the primary antenna parameters: Electrical Downtilt (EDT), antenna azimuth and horizontal Half Power Beamwidth (HPBW). Finally, the discussion on the SON performance results takes place. Here, the SON performance is evaluated for the LTE DL according to the SINR, cell throughput and mobility robustness metrics. The section is based on the methodology and the results discussed in [PI, PII, PIV, PV].

4.1.1 Optimization Space

Before developing the self-optimization solution, it is essential to first understand the impact of antenna parameters on the network performance. In this respect, the research work carried out in [PI, PII] explores the optimization space and sensitivity for Mechanical Downtilt (MDT), EDT, and horizontal and vertical HPBWs in the LTE DL by means of a static system-level simulator. These simulation studies were repeatedly performed for 3GPP case 1 and case 3, which are described in Section 3.1.1, so as to demonstrate the relationship between the deployment scenario and

Figure 4.1. Box-and-whisker plots for the optimization space of EDT, MDT and horizontal HPBW in terms of: a) the 5th percentile of SINR CDF and b) the 50th percentile of SINR CDF. The values in the blue and red boxes refer to the optimal parameter values for 3GPP case 1 and case 3, respectively. The figures are based on the results discussed in [PI, PII].

the optimized antenna parameter setting. The 5th and 50th percentiles of SINR CDF refer to the coverage and capacity performance indicators, respectively.

The box-and-whisker plots given in Figure 4.1 represent the parameter optimization space and sensitivity in terms of the selected coverage and capacity metrics. In Figure 4.1, combined tilt refers to the configuration of both EDT and MDT in equal parts. The default values for the horizontal and vertical HPBWs are assumed to be 70° and 10°. The downtilt angle range is [10°, 20°] for 3GPP case 1 and [0°, 10°] for 3GPP case 3. In both deployment scenarios, the downtilt step size is assumed to be 1°. The HPBW sets are {45°, 55°, 65°, 75°, 85°} and {4.4°, 6.8°, 9.4°, 10.0°, 13.5°} for the horizontal and vertical sections of the antenna radiation pattern,

respectively. For the HPBW analysis, the EDT configuration is assumed to be optimal so as to depict the combined optimization gain.

As shown in Figure 4.1, when the deployment scenario is ICI-limited (i.e., 3GPP case 1), EDT has a larger impact on the capacity performance than the coverage. Furthermore, in 3GPP case 1, EDT could offer around 0.5 dB better coverage and 1 dB better capacity (in terms of SINR metrics) in comparison to the MDT and combined tilt techniques. Figure 4.1 also indicates that the noise-limited deployment scenario (i.e., 3GPP case 3) is less sensitive to the EDT parameter adjustment than 3GPP case 1 in terms of both coverage and capacity metrics. No significant performance difference is identified between the EDT and MDT techniques in 3GPP case 3.

Horizontal HPBW is of limited impact on the coverage performance, especially when the network deployment is noise-limited as shown in Figure 4.1.a. This is because antenna gain non-uniformly changes on the cell edge. However, Figure 4.1 indicates that horizontal HPBW improves the capacity performance around 1 dB in comparison to the mean SINR in both 3GPP case 1 and case 3. Vertical HPBW affects both coverage and capacity performance notably in the noise-limited scenario. The reason is that antenna gain changes uniformly on the cell edge in the case of vertical HPBW adjustment.

As observed from Figure 4.1, the interval between the third quantile level and the maximum level is less than 0.3 dB for all the parameters and deployment scenarios. It means that antenna parameter optimization is not too sensitive to the parameter adjustment provided that the antenna parameter setting is one or two adjustment steps away from the optimal setting. Furthermore, coverage optimization is even less sensitive to the parameter adjustment than the capacity optimization as can be seen in Figure 4.1.

Whilst EDT optimization provides the largest gains in both ICI- and noise-limited deployment scenarios, for the maximal performance all the antenna parameters need to be tuned according to the performance needs. On the other hand, very narrow vertical HPBWs may not be feasible in real-world LTE deployments since the larger number of antenna elements are needed in the elevation plane. This results in taller antenna panels which are not practical to be installed on the rooftops in low-frequency deployments. In addition, EDT range is quite limited for BS antennas with narrow vertical HPBWs.

Table 4.1. Selected KPIs for the antenna self-optimization algorithm.

Notation	Definition
KPI_1	Mean of SE^1 CDF
KPI_2	10 th percentile of SE^1 CDF
KPI_3	50 th percentile of SE^1 CDF
KPI_4	90 th percentile of SE^1 CDF
KPI_5	Mean of RSRP CDF
KPI_6	Normalized late handover rate (per source cell)

4.1.2 Self-Optimization Methodology

The results obtained from [PI, PII] provide the necessary information to develop the self-optimization methodology for antenna parameter optimization. Accordingly, the first self-optimization solution - applicable to EDT - is given in [PIV]. Following the same design principles, the evolved solution - applicable to EDT, antenna azimuth and horizontal HPBW - is given in [PV].

In this subsection, the core components of the SON methodology [PV] are presented. First, the discussion on the selected SON architecture option and KPIs is provided. Next, the decision-making methods adopted in the SON algorithm are summarized. In this regard, the SON algorithm consists of the following decision-making methods: Rule-Based Reasoning (RBR) for the classification during the training period, Case-Based Reasoning (CBR) for the classification during the learning period, and an LS method for the corrective actions.

SON Architecture and KPIs

Centralized SON is the most suitable architecture option for the network-wide self-optimization of antenna parameters. This is because a large number of interacting cells are involved in this process, and those need to be coordinated to maximize the Coverage and Capacity Optimization (CCO) gains as discussed in [PIV, PV].

The KPIs listed in Table 4.1 are used in the decision-making process. Since these KPIs may be on different scales, all the numeric values of these KPIs need to be normalized before being fed into the decision-making

¹In practical implementation, SE distribution can be estimated by monitoring Channel Quality Indicator samples and corresponding BLERs.

process as follows:

$$SPI_i = \frac{KPI_i - \mu_i}{\sigma_i}, \quad (4.1)$$

where KPI_i and SPI_i refer to the original and normalized KPI values, respectively. μ_i and σ_i denote the mean and the standard deviation of the KPI distribution. Since the simultaneous optimization of antenna parameters in neighboring cells may result in noisy performance measures, optimization actions should be restricted by means of a centralized SON coordination mechanism that takes into account the neighbor relations as suggested in [PV].

Rule-Based Reasoning

A Rule-Based Reasoning (RBR) is needed for the decision-making process until the minimum number of successful cases (classifications) is stored for CBR. In [PV], the rule-based decision-making simply refers to the classifier defined in Equation (4.2). The classification for the given query, $\hat{\lambda}$, can take three different values: 1 when the cell is ICI-limited (class 1), -1 when the cell is noise-limited (class 2), and 0 when there is no classification available. However, in practice, the rule-based classifier is modeled as a binominal classifier of which the output is (forced to be) either 1 or -1. In this regard, each class - representing an optimization problem - is mapped to a self-optimization action, such as downtilt for class 1 and up-tilt for class 2. KPI_2 and KPI_3 are used as the inputs to the rule-based classifier as given below,

$$\hat{\lambda}(q) = \text{sign}(w_2 \cdot SPI_2^q - w_3 \cdot SPI_3^q), \quad (4.2)$$

where SPI_i^q refers to the normalized KPI value for the given query. The weights for the KPIs - denoted by w_i - are assumed to be equal in [PV], but they might be assigned with different values in practice, for instance, due to the varying operator preferences and needs.

Case-Based Reasoning

Case-Based Reasoning (CBR) is a non-parametric Machine Learning (ML) technique where the cases are stored and later retrieved to solve a new problem [85, 86, 87]. The k-Nearest Neighbor (k-NN) is a typical CBR algorithm, and it is selected as the decision-making method for the learning period in [PIV, PV]. This is because k-NN admits low complexity in the implementation, intelligibility in the operational phase, and high accuracy when there are small number of training samples and limited number of features [85].

To initiate the k-NN based decision-making, at least two previous cases for each class should be available in the memory of the k-NN classifier. $KPI_2, KPI_3, KPI_4, KPI_5$ and KPI_6 - defined in Table 4.1 - are used as the inputs by the binominal k-NN classifier in which $k_{NN} = 3$ is used as a prediction tool. A set of previous k_{NN} successful cases that are the most similar to given query, c_n^q , are accessed from the stored set of previous successful cases, C . c_n^q is defined by

$$c_n^q = \arg \max_{c \in C} S_{c,q}, \quad n = 1, 2, \dots, k_{NN}, \quad (4.3)$$

where similarity $S_{c,q}$ between c and q is computed by

$$S_{c,q} = \frac{1}{\sqrt{\sum_{i=2}^6 [\hat{w}_i \cdot (SPI_i^c - SPI_i^q)]^2}}. \quad (4.4)$$

Here, SPI_i^c and SPI_i^q denote the normalized KPI values for the case and query, respectively. In addition, $\hat{w}_i$ refers to the KPI-specific weight (in the case of CBR). Leave-One-Out Cross Validation [88] is applied for the recomputation of $\hat{w}_i$ in each self-optimization cycle. The classification for the given query, $\hat{\lambda}$, is predicted based on the previously verified classifications, λ , of the most similar cases,

$$\hat{\lambda}(q) = \text{sign} \left(\sum_{n=1}^{k_{NN}} \lambda(c_n^q) \right). \quad (4.5)$$

As in the rule-based classifier, each class - representing an optimization problem - is mapped to a self-optimization action. Yet even if one-to-one mapping is erroneous in the training phase, CBR is able to learn and adapt the classifications accordingly.

Local Search

Subsequent to the self-optimization action, which is the result of the classification step, a Local Search (LS) method is applied for the corrective actions in the given parameter search space. To assess whether a corrective action is needed, the change in the network performance has to be measured. In this respect, a corrective action is not needed if the following condition is met,

$$W_1 \cdot \frac{KPI_1^{new}}{KPI_1^{pre}} + W_2 \cdot \frac{KPI_2^{new}}{KPI_2^{pre}} \geq W_1 + W_2, \quad (4.6)$$

Here, W_i refers to the KPI weightings of the selected KPIs - KPI_1 and KPI_2 - for the LS method. In [PV], these weights are assumed to be

equal. However, they might be assigned with different values in practice. Each successful action is repeated locally (since the classification is valid), and the case is stored as an input to the k-NN classifier for future queries. If the condition is not met, the latest self-optimization action is retrieved and the antenna parameter is altered within a smaller search space (under the assumption of wrong classification). If the condition is not fulfilled for two consecutive attempts, the erroneous configuration is retrieved for the second time and the self-optimization of the parameter is suspended locally until the re-optimization is triggered, for instance, due to Cell Outage Compensation (COC).

4.1.3 SON Performance Assessment

In the case of antenna parameter optimization, the system-level SON simulations were performed for the downtown Helsinki scenario, which is described in Section 3.1.3. To evaluate the robustness of antenna parameter optimization against the changes in mobility behavior, the modeled deployment scenario, which had been originally optimized for the 10 km/h User Equipment (UE) speed, was also simulated for the 60 km/h UE speed [PV]. Figure 4.2 represents the self-optimization results for both mobility scenarios. The results shown in Figure 4.2 assume that the self-optimization takes places first for the azimuth parameter, secondly for the EDT parameter and finally for the horizontal HPBW parameter. It is also possible to obtain similar gains in case the self-optimization takes place in a different order (e.g., first for the horizontal HPBW parameter, secondly for the EDT parameter and thirdly for the azimuth parameter) as discussed in [PVII]. However, the optimal sequence starts with the optimization of the azimuth parameter and ends with the horizontal HPBW parameter at least for the given simulation scenario.

In Figure 4.2.a, the cumulative performance gains obtained from the self-optimization are given in terms of a coverage metric - the 10th percentile of SINR CDF) - and a pair of capacity metrics that are the 50th percentile of SINR CDF and the cell throughput. Unlike the earlier studies [PI, PII, PIV], [PV] adopts the 10th percentile of SINR CDF as the coverage metric instead of the 5th percentile. This is because the 10th percentile is seen as a more reliable metric when the sample size is limited as in the downtown Helsinki simulations. As shown in Figure 4.2.a, the network capacity is expanded 25% and 22% in terms of cell throughput for the 10 km/h and 60 km/h UE speeds, respectively. Although the capacity

Figure 4.2. Performance of antenna self-optimization (per mobility scenario) in terms of: a) SINR and capacity metrics, b) Mobility robustness metrics. The figures are based on the results discussed in [PV].

improvement is significant for both mobility scenarios, the coverage gain is limited, especially when the UE speed is high (e.g., 60 km/h). Based on the results given in [PV], this is mainly due to the suboptimal handover parameter (i.e., TTT, handover hysteresis and handover offset) values as indicated by the larger number of RLF and HOF events at the 60 km/h UE speed. To maximize the benefits of the presented CCO solution, mobility state-specific parameter values should be used per UE, which could be considered in the future CCO studies.

Figure 4.2.b represents the mobility robustness performance according to the RLF, call drop and handover statistics. It is shown that antenna parameter optimization improves the mobility robustness in the down-

Figure 4.3. The statistical performance results of the RBR and CBR classifiers are given in terms of correct and incorrect prediction rates (per antenna parameter optimization).

town Helsinki scenario. For instance, the number of call drops is reduced by 58% and 68% at the 10 km/h and 60 km/h UE speeds, respectively. In addition, the self-optimization solution reduces the number of handover attempts in both mobility scenarios, and thus minimizes the handover signaling.

While this subsection summarizes the cumulative gains obtained from the self-optimization of the selected antenna parameters, the results given in [PV] further show the gains obtained from each antenna parameter. Accordingly, the self-optimization of the EDT parameter provides larger gains in terms of the selected coverage and capacity metrics in comparison to the horizontal pattern parameters, azimuth and horizontal HPBW. Moreover, [PV] shows that the self-optimization of the horizontal pattern parameters roughly doubles the coverage and capacity gains if applied in combination with the self-optimization of the EDT parameter. It is noteworthy that these observations are aligned with the conclusions made in the earlier studies that assume the deterministic 3GPP deployment scenarios [PI, PII].

Figure 4.3 illustrates the performance results of the RBR and CBR classifiers. The statistical data given in Figure 4.3 is based on the extensive simulations that also include the evaluations presented in [PV]. To provide a fair assessment, when the simulations were carried for the performance analysis of the RBR and CBR classifiers, all the simulation parameters and the starting conditions for the antenna settings were assumed to be the same. Furthermore, the statistical figures do not include

the classification cases that resulted in a too small change in the parameter configuration (i.e., a smaller value change than the parameter step size). To analyze the results given in Figure 4.3, the Wilson score interval [89] is applied. Based on the analysis, the CBR classifier outperforms the RBR classifier in the case of the EDT and horizontal HPBW optimization tasks with the 99% and 98% confidence intervals, respectively. Although it may be statistically inconclusive (due to the limited data set for the azimuth optimization), Figure 4.3 shows that the CBR classifier outperforms the RBR classifier in the case of the azimuth optimization task as well. However, the CBR gain - in terms of classification error rate - is not obvious as the azimuth adaptation has a less homogenous impact on cell borders than the EDT and horizontal HPBW adaptation. It is noteworthy that with a larger set of training data, the CBR classifier may even perform better, whereas in [PIV, PV] the CBR classifier was initiated only with a set of two samples per class due to the limited number of optimization cases.

4.2 Vertical Sectorization Optimization for Downlink

In this section, first, the impact of Vertical Sectorization (VS) on the LTE DL performance is shown in terms of UE throughput. Next, the self-optimization methodology is introduced for the VS deployment. Finally, the section presents the performance results for the self-optimization in the LTE DL. Here, the self-optimization solution, which tunes the EDT parameter at each inner subsector, is evaluated according to the BS load and mobility robustness metrics. The section is based on the methodology and the results discussed in [PIII, PVI].

4.2.1 Optimization Space

The research work presented in [PIII] shows the performance impact of the Vertical Sectorization (VS) deployment and the antenna parameters associated with it (i.e., EDT and vertical HPBW). The performance evaluations were carried out for the LTE DL by means of a static system-level simulator. The main simulation assumptions in [PIII] were kept the same as those recommended by the 3GPP simulation guidelines [65, 66], thus allowing a comparable analysis to the earlier studies. The simulated deployment scenarios include both 3GPP case 1 and case 3, which

Figure 4.4. Relative UE throughput gain when the VS deployment is provided with optimal antenna parameter settings. 3GPP case 1 with three sectors is assumed to be the benchmark scenario when analyzing the relative change in each metric. The figure is based on the results discussed in [PIII].

are described in Section 3.1.1. The 5th and 50th percentiles of the UE throughput CDF refer to the coverage and capacity performance indicators, respectively.

Figure 4.4 represents the relative UE throughput gains when VS is provided with optimal antenna parameter settings. 3GPP case 1 with three sectors is assumed to be the benchmark scenario when analyzing the relative change in each metric. The simulations assumed the Best-Effort (BE) service type in the DL traffic. As shown in Figure 4.4, the median UE performance is improved by 58% and 85% when VS is adopted within 3GPP case 1 and case 3, respectively. On the other hand, SINR deteriorates - due to the excessive Inter-Cell Interference (ICI) between adjacent subsectors - in the case of the VS deployment with full-frequency reuse [PIII]. Hence, it may not be possible to achieve similar gains without a self-optimization mechanism in place when the GBR service type is assumed. Furthermore, as discussed in [PIII], narrow vertical HPBW (i.e., less than 5°) would help maximizing the network capacity. However, the required EDT range for these HPBW (i.e., larger than 10°) may not be practical for the BS antenna systems.

4.2.2 Self-Optimization Methodology

The selected SON architecture option and Key Performance Indicators (KPIs), and the decision-making methods adopted in the self-optimization

are summarized in this subsection. As introduced by the SON methodology given in [PVI], Local Search (LS) is the core component of the decision-making process in the case of VS.

SON Architecture and KPIs

In VS, the Inter-Cell Interference (ICI) between adjacent subsectors deteriorates the SINR performance in DL compared to the standard three-sectorized setup as noted in [PIII]. Since the ICI is correlated with the traffic load distribution, it is of utmost importance to have an optimization solution that is responsive to the local changes in the traffic load. In the case of centralized SON, the parameter update period may be too long to respond to these local changes in time. Thus, decentralized SON - more specifically the distributed SON architecture option - is more suitable to the self-optimization of VS as discussed in [PVI]. In distributed SON, the decision-making process has to admit low design complexity in comparison to centralized SON. This is because a large number of decisions made in each BS may not be otherwise feasible to be monitored and interpreted by the network's operator.

Virtual load - denoted by KPI_{VL}^s - is used as the self-optimization metric in the decision-making process. This KPI refers to the total Physical Resource Block (PRB) demand in a subsector by all the UEs within the subsector coverage in terms of the target UE throughput,

$$KPI_{VL}^s = \sum_{u \in s} PRB_u^s, \quad (4.7)$$

where PRB_u^s denotes the number of PRBs required per UE to meet the target UE throughput. KPI_{VL}^s is averaged over a period of one second so as to filter out the temporary changes in the wireless channel. However, the simultaneous optimization of immediate neighbor cells may also result in noisy KPI data. Therefore, the self-optimization of EDT has to be restricted to one inner subsector at a time in each site as described in [PVI].

Local Search

In the self-optimization of VS, an LS method is applied to optimize the EDT parameter at each inner subsector in a given search space. To decide whether an EDT optimization attempt is successful or not, the change in the virtual load of the site is measured. In this respect, an optimization attempt has to fulfill the following condition to be assessed as an improve-

ment,

$$\sum_{s \in S}^{t=t_2} KPI_{VL}^s \leq \sum_{s \in S}^{t=t_1} KPI_{VL}^s. \quad (4.8)$$

Here, S refers to the site in which the self-optimization takes place, and s denotes each co-sited subsector in this site. In addition, t_1 and t_2 refer to the time instances before and after a self-optimization attempt is made, respectively. To minimize the ICI from inner subsectors toward the outer subsectors and other sites, LS starts with a downtilt action (as the candidate solution), and the action is reversed at each failed attempt. It should also be noted that the LS method initially applies the maximal EDT step size, yet the step size is reduced at each failed attempt until the EDT adaptation converges to the minimal EDT step size.

4.2.3 SON Performance Assessment

In the case of VS optimization, the system-level SON simulations were performed for the downtown Helsinki scenario, which is described in Section 3.1.3. In the evaluations, the GBR service type was assumed in the traffic modeling [PVI]. This is because the GBR service requirements are more challenging to meet in high ICI (and low SINR) conditions than the BE service requirements. Furthermore, network traffic is spatially distributed as a) background traffic (54 UE/site) where the mobile UEs randomly move at the speed of 3 km/h or 30 km/h, and b) hotspot traffic (42 UE/hotspot) where the stationary UEs are randomly and uniformly distributed over hotspots of which the diameter is 200 m [PVI].

In both Figures 4.5.a and 4.5.b, VS, C and S denote vertical sectorization, coordinated scheduling and self-optimization features respectively; and 1 and 0 refer to whether each feature is enabled or disabled. For instance, "VS-0 C-0 S-0" refers to the standard three-sectorized deployment scenario where VS, coordinated scheduling and self-optimization are not applied. Illustrated results are averaged over 30-min simulations including the convergence time of the SON solution that is around 200 s.

In Figure 4.5.a, the average load in the case of the three-sectorized deployment is assumed to be the benchmark for each mobility scenario. As shown in Figure 4.5.a, when the self-optimization solution is performed for the VS deployment, the BS load is reduced by 16% and 12% at the 3 km/h and 30 km/h UE speeds, respectively. When the self-optimization solution is applied along with the coordinated scheduling, then the BS load is reduced by 25% at the 3 km/h UE speed and 23% at the 30 km/h

Figure 4.5. a) Relative BS load. The average load in the case of the three-sectorized deployment is assumed to be the benchmark for each mobility scenario. b) Radio link robustness. The figures are based on the results discussed in [PVI].

UE speed. Hence, the maximal capacity performance is achieved when all these complementary features are simultaneously used.

In Figure 4.5.b, the radio link performance indicators (i.e., RLF recovery and call drop counts), indicate that the network performance with respect to all these metrics mainly depends on the UE speed assumption. For instance, it is possible to zero out all the RLF events at the 3 km/h UE speed when the coordinated scheduling is applied within the VS deployment. However, this improvement is not viable at the 30 km/h UE speed given the fact that the handover parameters are not optimized for the 30 km/h UE speed. The best performance for the 30 km/h UE speed is achieved when the self-optimization is applied together with the coordinated scheduling. Yet the self-optimization gain is negligible compared to the case where only the coordinated scheduling is applied.

Based on these simulation results, it is evident that the self-optimization solution could effectively mitigate the co-channel interference between ad-

jacent subsectors and reduce the BS load in hotspots without a need of additional BS deployment. It is also noted in [PVI] that the convergence rate of the solution is sufficiently fast for the given optimization problem.

4.3 Cross-Channel Resource Optimization for Uplink

The goal of the cross-channel resource optimization solution is to meet the Random Access Channel (RACH) performance targets while maximizing the BS capacity. Therefore, in this section, first, the impact of RACH configuration on the network performance is discussed in terms of Access Probability (AP) and Physical Random Access Channel (PRACH) overhead. Next, the SON methodology is presented for the multi-objective UL optimization. Finally, the section presents the performance results for the cross-channel resource optimization in the LTE UL. Here, the SON performance is discussed in terms of the BS load and AP metrics. The section is based on the methodology and the results discussed in [PVII].

4.3.1 Optimization Space

The optimization space for PRACH was explored by means of a semi-analytic approach as discussed in [PVII]. In this regard, Figure 4.6.a represents the AP metric as a function of the number of Contention-Based Random Access (CBRA) attempts and the preamble period (assuming that the preamble split is 0.5). In Figure 4.6.b, the PRACH overhead is shown as a function of the preamble period. Here, the preamble period parameter defines the time period where a Random Access (RA) opportunity exists, and the preamble split parameter refers to the ratio of RACH signatures that are dedicated for Non-Contention-Based Random Access (NCBRA) in a PRACH preamble. Since NCBRA is a channel access method where no contention resolution mechanism is needed, it admits a higher AP target than CBRA. Therefore, the optimization space for the NCBRA method is rather limited in comparison to the CBRA method.

As shown in Figure 4.6.a, AP is approximately a linear function of the number of CBRA attempts regardless of the preamble period setting. However, the steepness of this function is directly proportional to the configured preamble period. Thus, in the case of longer preamble periods, AP becomes more sensitive to the changes in the network traffic. However, in the case of shorter preamble periods, Figure 4.6.b indicates that the

Figure 4.6. a) AP at the initial CBRA attempt (when the preamble split is 0.5). The legend indicates the preamble period length. b) PRACH overhead vs. preamble period. The figures are based on the results discussed in [PVII].

BS capacity shrinks due to larger PRACH overhead. Therefore, the goal of the self-optimization task is not only to minimize the access delay, but also to maximize the BS capacity.

4.3.2 Self-Optimization Methodology

This subsection discusses the selected SON architecture and Key Performance Indicators (KPIs), as well as the decision-making methods adopted in the cross-channel resource optimization solution. As introduced by the SON methodology given in [PVII], the decision-making process can be expressed as a utility function.

SON Architecture and KPIs

The cross-channel resource optimization between PRACH and PUSCH is a prominent example for which the localized SON architecture is more preferable than the other architecture options. In the case of cross-channel

resource optimization, the impact of the parameter adaptation is local, thus no coordination is needed between BSs. Furthermore, a localized SON solution benefits from the shorter decision times resulting in larger self-optimization gains - especially in the case of RACH optimization - as stated in [PVII].

The Access Probabilities (APs) for CBRA and NCBRA, and the BS load are the main KPIs used in the decision-making process. Whereas the AP metric was calculated by using an analytic approach in the RACH performance evaluations [PVII], it is expected to be measured in practice by means of the collected statistics at the network.

Utility Function

RACH resource allocation is a multi-objective optimization problem as the RACH parameter configuration - particularly the preamble period, t_{RA} - impacts both PRACH and PUSCH performance. However, to optimize the UL in terms of both CBRA and NCBRA performance metrics, not only the preamble period, but also the preamble split - denoted by p_d - should be tuned depending on the network performance targets. In this regard, $AP_{C,t}$ and $AP_{NC,t}$ - given in the utility function - refer to the target APs for the CBRA and NCBRA procedures.

Since handover latency is the primary measure for service continuity, the utility function prioritizes the optimization of NCBRA over the optimization of CBRA and PUSCH, respectively. Accordingly, at each self-optimization iteration, the optimized preamble period, T_{RA} , and the optimized preamble split (i.e., dedicated signature ratio), P_d , are the outputs of the utility function,

$$\{T_{RA}, P_d\} = \begin{cases} \arg \max_{\{t_{RA}, p_d\}} U_{UL}, & (U_C < 1) \vee (U_{NC} < 1), \\ \arg \min_{\{t_{RA}, p_d\}} KPI_{VL}^s, & (U_C = 1) \wedge (U_{NC} = 1). \end{cases}, \quad (4.9)$$

with

$$U_{NC}(t_{RA}, p_d) = \begin{cases} \frac{AP_{NC,1}}{AP_{NC,t}}, & AP_{NC,1} < AP_{NC,t}, \\ 1, & \text{otherwise.} \end{cases},$$

$$U_C(t_{RA}, p_d) = \begin{cases} \frac{AP_{C,1}}{AP_{C,t}}, & (AP_{C,1} < AP_{C,t}) \wedge (U_{NC} = 1) \\ 1, & (AP_{C,1} \geq AP_{C,t}) \wedge (U_{NC} = 1), \\ 0, & \text{otherwise.} \end{cases},$$

and

$$U_{UL}(t_{RA}, p_d) = (w_{NC} \cdot U_{NC} + w_C \cdot U_C + w_{VL} \cdot KPI_{VL}^s)^{-1}.$$

Figure 4.7. a) Preamble period adaptation, b) Preamble split adaptation, c) BS load optimization, d) RACH optimization. The target AP values for CBRA and NCBRA (at the first RA attempt) are assumed to be 97% and 99%, respectively. The figures are based on the results discussed in [PVII].

Here, U_C , U_{NC} and U_{UL} refer to the CBRA, NCBRA and UL performance functions, respectively. In addition, KPI_{VL}^s denotes the average virtual load. The utility function could be tuned by the weighting parameters, w_C , w_{NC} and w_{VL} , which are assumed equal in the studies [PVII]. Each UE is assumed to report the number of previously failed RA attempts to the target BS so as to enable the calculation of the APs (at the first RA attempt) for the CBRA and NCBRA procedures, $AP_{C,1}$ and $AP_{NC,1}$.

4.3.3 SON Performance Assessment

SON performance analysis for cross-channel resource optimization follows a semi-analytic approach [PVII]. First, the RACH performance results are produced using the analytical model. Next, the analytical results are fed into the the dynamic system-level LTE simulator in which the simulation time interval (i.e., 1 s) is larger than the LTE transmission time interval (i.e., 1 ms). 3GPP case 1, which is described in Section 3.1.1, was selected as the deployment scenario for the SON performance assessment.

Based on the results of the semi-analytic simulations, which are partly captured in Figure 4.7, it is shown that LTE PRACH is mostly robust

against the changes in the network traffic and the UE mobility [PVII]. Hence, there is greater potential to optimize the BS capacity than the access delay. Furthermore, the PUSCH capacity - see Figure 4.7.c - could be indeed improved by the adaptation of the preamble period parameter which is shown in Figure 4.7.a. Yet the CBRA and NCBRA performance targets - see Figure 4.7.d - are met by adjusting the preamble split parameter as shown in Figure 4.7.b. The target AP values for CBRA and NCBRA (at the first RA attempt) are assumed to be 97% and 99%, respectively.

In Figure 4.7.c, the virtual load metric indicates that the number of unsatisfied UEs could be decreased around 2%. It should be noted that the gain would be 13% if the initial preamble period would have been configured to 1 ms. The expected capacity improvement is smaller than the antenna optimization gains [PV, PVI]. However, there are some advantages of the cross-channel resource optimization solution that make it attractive to implement:

- i) There is no need for any additional hardware investment to enable the solution.
- ii) No inter-node coordination and signaling thereof are needed.
- iii) The response time of the solution to the capacity problems is very quick (e.g., in seconds).

4.4 Context-Aware Connectivity Optimization for Downlink and Uplink

In 5G networks, where a large number of Small-BSs (SBSs) are expected to be deployed for capacity extension, not only conventional Key Performance Indicators (KPIs) but also UE context could be potentially utilized for the SON framework [40]. Therefore, in this section, first, the impact of SBS densification on the coverage and capacity performance is discussed in relation to UE context. Next, the section summarizes the methodology for the context-aware connectivity optimization solution. Finally, the SON performance results are discussed according to relative offloading gain and UL power change. The section is based on the methodology and the results discussed in [PVIll].

Figure 4.8. Offered coverage and capacity by the small-cell layer in comparison to the macro-cell layer in the case of the network densification scenarios with 12, 36 and 60 SBSs per macro-site, respectively. The traffic demand per area is assumed to be the same in both macro- and small- cell layers. The UE speed is 6 km/h. The figure is based on the results discussed in [PVIII].

4.4.1 Optimization Space

The performance evaluations given in [PVIII] studies the impact of the network densification toward 5G assuming the HetNet deployment scenario that is described in Section 3.1.2. In this respect, Figure 4.8 shows the coverage and capacity results in the case of the network densification scenarios with 12, 36 and 60 SBSs per macro-site, respectively. Here, it is assumed that both macro- and small- cell layers have the same amount of system bandwidth available for the mobile traffic.

As shown in Figure 4.8, when there are 60 SBSs per macro-site, the small-cell layer provides coverage to 58% of the mobile UEs. However, for the optimal load balancing performance, 92% of the total data traffic should be offloaded to the small-cell layer - assuming the Best-Effort (BE) service type - in both DL and UL directions. In order to take advantage of this offloading potential, BW-hungry, delay-tolerant services - originated in the macro-cell layer - could be moved to the small-cell layer provided that the QoS requirement in terms of service delay is fulfilled. The results given in [PVIII] indicate that the continuous connection time that is not interrupted by an inter-layer handover may be too long to offload those services to the small-cell layer at low SBS density scenarios. Therefore, at high SBS density scenarios, the amount of offloaded data could be max-

imized especially for the moderate- and high- speed UEs. As discussed in [PVIII], another advantage of the data offloading would be to lower the UE power consumption in the UL. Based on the analysis given in [PVIII], the median power consumption decreases around 9 dB when the UE is served within the small-cell layer instead of the macro-cell layer.

4.4.2 Self-Optimization Methodology

This subsection discusses the potential SON evolution toward 5G and the use of context information in the decision-making process. The methodology presented here is based on the framework given in [PVIII].

SON Architecture and KPIs

Future networks are designed to learn the UE behavior and optimize the long-term connectivity based on both network context (e.g., KPIs and operator policies) and UE context (e.g., UE velocity, UE proximity to SBS, and battery level) [40]. As noted in [PVIII], in the case of the context-aware SON architecture, the context information is foreseen to be mutually transparent to the UE and the network for the optimal connectivity performance. Therefore, the context information can be further categorized into the following: mobility-context (e.g., UE velocity and UE proximity to SBS), traffic-context (e.g., QoS profile, KPIs and operator policies), energy-context (e.g., battery level) as well as the user preferences. It is noted that the context-aware connectivity optimization solution [PVIII] takes only the subset of the context information into account: UE velocity and UE proximity information. The BS load metric is used for the evaluation of this solution.

Thanks to the mutually transparent context information, delay-tolerant services (e.g., a cloud synchronization task) could be managed in the time domain. In this regard, the network could reserve dedicated resources for the service in advance by proactively adapting the traffic steering and load balancing mechanisms. Thus, even if the mobile UE gets connected to the small-cell layer for a very short time, the small-cell layer would be able to manage heavy data exchange tasks by means of the early resource reservation and prioritization capabilities of the context-aware SON.

Utility Function

In the case of the context-aware connectivity optimization solution, the target BS for offloading, N_{SC} , can be determined based on the mobility-

context information and the existing mobility statistics,

$$N_{SC} = \arg \max_n p_{off,u}^n, \quad n \in SC, \quad (4.10)$$

with

$$p_{off,u}^n = P[u \mid CF(v_u, d_u^n) = n, t_0 - \Delta_t \leq t_{off} \leq t_0 + \Delta_t].$$

Here, $p_{off,u}^n$ refers to the offloading probability of UE u to target BS n within the small-cell layer, SC , given the UE velocity, v_u , and the UE proximity to target BS n , d_u^n . v_u and d_u^n are the inputs to the connection function, CF . In addition, t_0 , t_{off} and Δ_t denote the original time, the offloading time interval and the time shift tolerance for data exchange, respectively. It is noteworthy that there should be sufficient statistics and accurate context information available in order to decide whether the data exchange task should be delayed/advanced or executed at the original time. Otherwise, an inaccurate prediction may force the UE to initiate the data exchange closer to the macro cell-edge, thus even more network resources may be consumed in the macro-cell layer. To avoid such consequences in real-world implementations, data offloading to N_{SC} may only be suggested if $p_{off,u}^n$ is above a certain threshold set by the network operator. Since the target SBS, N_{SC} , is deployed at a different frequency layer than the serving cell, it is also more energy-efficient for the UE receiver to start an inter-frequency cell search when the UE is in the close proximity of N_{SC} .

4.4.3 SON Performance Assessment

The SON performance evaluations were carried out for the HetNet deployment scenario that is described in Section 3.1.2. In this scenario, 60 SBSs (per macro-site) are assumed to be randomly and uniformly distributed over the coverage area of a Macro-BS (MBS) with a 40 m minimum distance [PVIII]. In the performance evaluations, it was assumed that the mobility (i.e., the UE speed and route) are correlated during the time shift tolerance for data exchange.

Figure 4.9 illustrates the potential gains in terms of both offloading gain and transmission power metrics. Based on the results, when the time shift tolerance for data exchange is short, noteworthy offloading gains (i.e., 2% or above) could only be observed for the UEs moving faster than the 6 km/h speed. However, when the time shift tolerance is longer than 5 s, significant improvements could also be observed for the UEs at lower speeds. Thanks to offloading, the network could also free up resources

Figure 4.9. Relative data offloading gain and UL transmission power change in the case of the context-aware connectivity optimization solution. The figure is based on the results discussed in [PVIII].

for delay-critical services, such as Ultra-Reliable Low-Latency Communications (URLLC) in the macro-cell layer. Furthermore, the average UL transmission power decreases proportionally to the offloading gain as shown in Figure 4.9. This may potentially enable energy saving on the UE transmitter, thus resulting in longer battery lifetime.

5. Conclusions

5.1 Conclusions

Self-Organizing Networks (SON) allows the automated control of various Radio Access Network (RAN) parameters. With minimal human interaction, SON aims to provide greater performance gains in comparison to legacy optimization solutions. As a result of more efficient and dynamic use of network resources, it is expected that both OPEX and CAPEX are reduced. In this regard, the doctoral dissertation contributed to the ongoing SON research by exploring self-optimization capabilities in LTE and its evolution toward 5G. To assess the SON performance, both analytical and experimental frameworks were developed.

As discussed in the doctoral dissertation, network-wide antenna parameter optimization is essential to maximize the coverage and capacity performance in the LTE Downlink (DL). Therefore, in the self-optimization studies, a centralized SON solution was introduced for the optimization of the Electrical Downtilt (EDT), antenna azimuth and horizontal Half Power Beamwidth (HPBW) parameters. The simulation results showed that the solution could provide 25% capacity improvement and 58% call drop reduction when the UMTS site reuse scenario is assumed. Furthermore, the algorithm analysis indicated that the Case-Based Reasoning (CBR) classifier reduces the risk of erroneous decisions - especially for the EDT and horizontal HPBW parameters - in comparison with the Rule-Based Reasoning (RBR) classifier.

In macro-cellular deployments with Vertical Sectorization (VS), there is even greater potential to optimize the capacity performance in the LTE DL when antenna parameters are optimally adjusted. For instance, the median User Equipment (UE) performance - assuming the Best-Effort

(BE) type service - could be improved by 58% and 85% when VS is adopted within 3GPP case 1 and case 3, respectively. On the other hand, the excessive Inter-Cell Interference (ICI) between adjacent subsectors poses a potential threat to the Guaranteed Bit Rate (GBR) service type. Hence, a decentralized SON solution was developed to optimize the EDT parameter at inner subsectors. The SON simulations were performed by assuming the GBR type service. These simulations showed that when the self-optimization is performed for the VS deployment, the BS load could be reduced by 16% and 12% - in comparison to the standard three-sectorized deployment - at the 3 km/h and 30 km/h UE speeds, respectively. Furthermore, it was observed that the BS load could be reduced by 25% at the 3 km/h UE speed and 23% at the 30 km/h UE speed when the self-optimization is applied along with the coordinated scheduling.

In Uplink (UL), cross-channel resource optimization was considered as the primary Coverage and Capacity Optimization (CCO) application which can be adopted within the localized SON architecture. The UL evaluations showed that in the case of longer Physical Random Access Channel (PRACH) preamble periods, Access Probability (AP) becomes more sensitive to the changes in the network traffic. However, in the case of shorter preamble periods, BS capacity shrinks due to larger PRACH overhead. Therefore, the goal of the self-optimization task was not only to minimize the access delay, but also to maximize the BS capacity. In the SON evaluations, it was shown that LTE PRACH is mostly robust against the changes in the network traffic and the UE mobility, hence there is greater potential to optimize the BS capacity than the access delay. The results suggested that the Physical Uplink Shared Channel (PUSCH) capacity may be indeed improved by self-tuning the preamble period parameter, whereas the Contention-Based Random Access (CBRA) and Non-Contention-Based Random Access (NCBRA) performance targets could be met by adjusting the preamble split parameter that defines the allocation of CBRA and NCBRA resources within a PRACH preamble.

In 5G networks, where a large number of Small-BSs (SBSs) are expected to be deployed for capacity extension, not only conventional Key Performance Indicators (KPIs) but also UE context could be potentially utilized for the SON framework. Therefore, the impact of SBS densification on the network performance, in relation to UE context, was analyzed. Based on the simulation results, the small-cell layer could provide coverage to 58% of the mobile UEs when there are 60 SBSs per macro-site. Yet to

maximize the overall throughput performance, 92% of the total BE data traffic needs to be offloaded to the small-cell layer in both DL and UL directions when the macro- and small- cell layers have the same amount of system bandwidth available for the mobile traffic. It was shown that at high SBS density scenarios, the amount of offloaded data could be maximized especially for the moderate- and high- speed UEs while the UE power consumption could be significantly reduced in the UL. In this respect, it was proposed that the SON architecture should evolve such that UE and UE context thereof should be part of the future SON architecture. In the SON evaluations, it was observed that when the time shift tolerance for data exchange is short, noteworthy offloading gains (i.e., 2% or above) could only be observed for the UEs moving faster than the 6 km/h speed. However, when the time shift tolerance is longer than 5 s, significant improvements could also be observed for the UEs at lower speeds. Thanks to offloading, the network could free up resources for delay-critical services, such as Ultra-Reliable Low-Latency Communications (URLLC) in the macro-cell layer. Furthermore, battery lifetime within the UE could be extended as the average UL transmission power could be reduced proportionally to the offloading gain.

5.2 Future Work

The primary focus of this doctoral thesis is on the DL performance optimization in SON. To complement the studies presented in the thesis, future work could address further SON studies on the UL performance optimization, for instance, in the case of Vertical Sectorization (VS). Moreover, the SON framework should also be revisited in order to address the new design paradigms emerged in 5G, such as millimeter wave based radio access, beam-based mobility management, URLLC and split RAN architecture. The conventional SON framework enables the automated control of various RAN parameters that will also exist in 5G networks. However, as partly discussed in this thesis, due to its reactive design approach and lack of end-to-end knowledge, it may not always meet the stringent requirements of 5G, for instance, in terms of data rate, latency and availability [4, 5, 6, 7]. In this respect, Machine Learning (ML) could play a key role in 5G networks enabling big-data-driven analytics which could transform the SON design from reactive to proactive and maximize the network performance and the operational efficiency in 5G [90, 91, 92].

References

- [1] 3GPP TR 25.913 V7.3.0, *Requirements for Evolved UTRA (E-UTRA) and Evolved UTRAN (E-UTRAN)*.
Available: www.3gpp.org/dynareport/25913.htm
- [2] ITU-R Report M.2134-0 (2008), *Requirements related to technical performance for IMT-Advanced radio interface(s)*.
Available: https://www.itu.int/dms_pub/itu-r/opb/rep/R-REP-M.2134-2008-PDF-E.pdf
- [3] 3GPP TR 36.913 V8.0.1, *Requirements for further advancements for Evolved Universal Terrestrial Radio Access (E-UTRA) (LTE-Advanced)*.
Available: <http://www.3gpp.org/dynareport/36913.htm>
- [4] A. Osseiran, et al., "The foundation of the Mobile and Wireless Communications System for 2020 and beyond Challenges, Enablers and Technology Solutions," In Proceedings of IEEE Vehicular Technology Conference (VTC Spring), Dresden, Germany, June 2013, pp. 1-5.
- [5] METIS, Deliverable D1.1, *Scenarios, requirements and KPIs for 5G mobile and wireless system*, May 2013.
Available: https://www.metis2020.com/wp-content/uploads/deliverables/METIS_D1.1_v1.pdf
- [6] 3GPP TR 38.913 V14.3.0, *Study on Scenarios and Requirements for Next Generation Access Technologies*.
Available: <http://www.3gpp.org/dynareport/38913.htm>
- [7] ITU-R Report M.2410-0 (11/2017), *Minimum requirements related to technical performance for IMT-2020 radio interface(s)*.
Available: https://www.itu.int/dms_pub/itu-r/opb/rep/R-REP-M.2410-2017-PDF-E.pdf

- [8] 3GPP, *Overview of 3GPP LTE*.
Available: <http://www.3gpp.org/LTE>
- [9] 3GPP TS 36.201 V11.1.0, *Evolved Universal Terrestrial Radio Access (E-UTRA); LTE physical layer; General description*.
Available: <http://www.3gpp.org/dynareport/36201.htm>
- [10] 3GPP, *Overview of 3GPP LTE-Advanced*.
Available: <http://www.3gpp.org/LTE-Advanced>
- [11] 3GPP TR 36.902 V9.3.1, *Self-configuring and self-optimizing network use cases and solutions*.
Available: <http://www.3gpp.org/dynareport/36902.htm>
- [12] Next Generation Mobile Networks, *Use Cases related to Self Organising Network, Overall Description*, Version 2.02, April 2007.
Available: https://www.ngmn.org/fileadmin/user_upload/NGMN_Use_Cases_related_to_Self_Organising_Network__Overall_Description.pdf
- [13] M. Pettersen, L. E. Bråten and A. G. Spilling, "Automatic antenna tilt control for capacity enhancement in UMTS FDD," In Proceedings of IEEE Vehicular Technology Conference (VTC Fall), Los Angeles, California, USA, September 2004, pp. 280-284.
- [14] M. N. ul Islam, R. Abou-Jaoude, C. Hartmann and A. Mitschele-Thiel, "Self-optimization of antenna tilt and pilot power for dedicated channels," In Proceedings of the International Symposium Modeling and Optimization in Mobile, Ad Hoc and Wireless Networks (WiOpt), Avignon, France, June 2010, pp. 196-203.
- [15] Y. Wang, X. Yang, A. Ma and L. Cuthbert, "Intelligent resource optimisation using semi-smart antennas in LTE OFDMA systems," In Proceedings of IEEE International Conference on Communications Technology and Applications (ICCTA), Beijing, P.R. China, October 2009, pp. 173-179.
- [16] R. Razavi, S. Klein and H. Claussen, "A fuzzy reinforcement learning approach for self-optimization of coverage in LTE networks," Bell Labs Technical Journal, 2010, Vol. 15, No. 3, pp. 153-175.
- [17] H. Eckhardt, S. Klein and M. Gruber, "Vertical antenna tilt optimization for LTE base stations," In Proceedings of IEEE Vehicular Tech-

- nology Conference (VTC Spring), Budapest, Hungary, May 2011, pp. 1-5.
- [18] M. N. ul Islam and A. Mitschele-Thiel, "Reinforcement learning strategies for self-organized coverage and capacity optimization," In Proceedings of IEEE Wireless Communications and Networking Conference (WCNC), Paris, France, April 2012, pp. 2818-2823.
 - [19] M. Döttling and I. Viering, "Challenges in mobile network operation: Towards self-optimizing networks," In Proceedings of IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), Taipei, Taiwan, April 2009, pp. 3609-3612.
 - [20] 3GPP TS 38.201 V2.0.0, *NR; Physical layer; General description*. Available: <http://www.3gpp.org/dynareport/38201.htm>
 - [21] U. Turke and M. Koonert, "Advanced site configuration techniques for automatic UMTS radio network design," In Proceedings of IEEE Vehicular Technology Conference (VTC Spring), Stockholm, Sweden, May 2005, pp. 1960-1964.
 - [22] I. Siomina, P. Värbrand and D. Yuan, "Automated optimization of service coverage and base station antenna configuration in UMTS networks," *IEEE Wireless Communications*, 2006, Vol. 13, No. 6, pp. 16-25.
 - [23] I. Siomina and D. Yuan, "Enhancing HSDPA performance via automated and large-scale optimization of radio base station antenna configuration," In Proceedings of IEEE Vehicular Technology Conference (VTC Spring), Marina Bay, Singapore, May 2008, pp. 2061-2065.
 - [24] A. Awada, B. Wegmann, I. Viering and A. Klein, "Optimizing the radio network parameters of the Long Term Evolution system using Taguchi's method," *IEEE Transactions on Vehicular Technology*, 2011, Vol. 60, No. 8, pp. 3825-3839.
 - [25] M. Donelli, S. Caorsi, F. G. B. De Natale, D. Franceschini and A. Massa, "A versatile enhanced genetic algorithm for planar array design," *Journal of Electromagnetic Waves and Applications*, 2004, Vol. 18, No. 11, pp. 1533-1548.
 - [26] A. Massa, M. Donelli, F. G. B. De Natale, S. Caorsi and A. Lommi, "Planar antenna array control with genetic algorithms and adap-

- tive array theory," *IEEE Transactions on Antennas and Propagation*, 2004, Vol. 52, No. 11, pp. 2919-2924.
- [27] 4G Americas, *MIMO and Smart Antennas for Mobile Broadband Systems*.
Available: http://www.5gamericas.org/files/4614/0622/2152/MIMO_and_Smart_Antennas_July_2013_FINAL.pdf
- [28] Nokia Networks, *Active Antenna Systems A step-change in base station site performance*.
Available: https://onestore.nokia.com/asset/200016/Nokia_Active_Antenna_Systems_White_Paper_EN.pdf
- [29] W. Guo and T. O'Farrell, "Green cellular network: Deployment solutions, sensitivity and tradeoffs," In *Proceedings of Wireless Advanced*, London, UK, June 2011, pp. 42-47.
- [30] E. P. Tsakalaki, L. A. M. R. de Temino, T. Haapala; J. L. Roman and M. A. Arauzo, "Deterministic beamforming for enhanced vertical sectorization and array pattern compensation," In *Proceedings of European Conference on Antennas and Propagation (EuCAP)*, Prague, Czech Republic, March 2012, pp. 2789-2793.
- [31] D. W. Kifle, B. Wegmann, I. Viering, A. Klein, "Mathematical model for vertical sectorization (VS) in AAS based LTE deployment," In *Proceedings of International Symposium on Wireless Communication Systems (ISWCS)*, Barcelona, Spain, August 2014, pp. 100-105.
- [32] F. Yang, J. Zhang, W. Xie, X. Zhu, "Field trial results for vertical sectorization in LTE network using Active Antenna System," In *Proceedings of IEEE International Conference on Communications*, Sydney, Australia, June 2014, pp. 2508-2512.
- [33] S. Sun, Q. Gao, Y. Peng, Y. Wang and Lingyang Song, "Interference management through CoMP in 3GPP LTE-advanced networks," *IEEE Wireless Communications*, 2013, Vol. 20, No. 1, pp. 59-66.
- [34] H. L. Määtinen, et al., "System-level performance of LTE-Advanced with joint transmission and dynamic point selection schemes," *EURASIP Journal on Advances in Signal Processing*, 2012, No. 1, pp.1-18.
- [35] 3GPP TR 36.819 V11.2.0, *Technical Specification Group Radio Access Network; Coordinated multi-point operation for LTE physical layer*

aspects.

Available: <http://www.3gpp.org/dynareport/36819.htm>

- [36] R. Kwan, C. Leung and J. Zhang, "Multiuser scheduling on the down-link of an LTE cellular system," *Research Letters in Communications*, vol. 2008, Article ID 323048, 2008.
- [37] A. Lobinger, S. Stefanski, T. Jansen and I. Balan, "Load balancing in downlink LTE self-optimizing networks," In *Proceedings of IEEE Vehicular Technology Conference (VTC Spring)*, Taipei, Taiwan, May 2010, pp. 1-5.
- [38] R. Kwan, R. Arnott, R. Paterson, R. Trivisonno and M. Kubota, "On Mobility Load Balancing for LTE Systems," In *Proceedings of IEEE Vehicular Technology Conference (VTC Fall)*, Ottawa, Ontario, Canada, September 2010, pp. 1-5.
- [39] M. M. Hasan, S. Kwon and J. H. Na, "Adaptive Mobility Load Balancing Algorithm for LTE Small-Cell Networks," *IEEE Transactions on Wireless Communications*, 2018, Vol. PP, No. 99, pp. 1-1.
- [40] T. Ihalainen, et al., "Flexible scalable solutions for dense small cell networks," *Wireless World Research Forum (WWRF)*, Oulu, Finland, April 2013, pp. 1-4.
- [41] Nokia Networks, *Self organizing networks*.
Available: <https://networks.nokia.com/portfolio/self-organizing-networks>
- [42] S. Härmäläinen, H. Tang, A. Wacker and O. N. C. Yilmaz, "Method of improving coverage and optimisation in communication networks," *International Patent Application PCT/EP2008/065001* filed November 5, 2008 (Granted by US).
- [43] O. N. C. Yilmaz, C. Wijting and P. Lundén, "Cloud services in mobile heterogeneous networks," *International Patent Application PCT/US2012/042296* filed June 13, 2012 (Granted by EP).
- [44] P. Lundén, O. N. C. Yilmaz and C. Wijting, "Method and apparatus for network assisted data transfer scheduling," *International Patent Application PCT/IB2012/054052* filed August 8, 2012 (Granted by US, JP).

- [45] P. Lundén, O. N. C. Yilmaz and C. Wijting, "Methods, apparatuses and computer program products for providing a protocol to resolve synchronization conflicts when synchronizing between multiple devices," International Patent Application PCT/IB2012/054949 filed September 18, 2012 (Granted by JP).
- [46] Y. Khan, B. Sayrac and E. Moulines, "Active antenna systems for centralized self-optimization of capacity in LTE-A," In Proceedings of IEEE Wireless Communications and Networking Conference Workshops (WCNCW), Istanbul, Turkey, May 2014, pp. 166-171.
- [47] S. E. Nai, Z. Lei, S. H. Wong and Y. H. Chew, "Optimizing Radio Network Parameters for Vertical Sectorization via Taguchi's Method," IEEE Transactions on Vehicular Technology, 2016, Vol. 65, No. 2, pp. 860-869.
- [48] D. W. Kifle, B. Wegmann, I. Viering and A. Klein, "Self optimizing network (SON) framework for automated vertical sectorization," In Proceedings of IEEE International Symposium on Personal, Indoor and Mobile Radio Communications (PIMRC), Valencia, Spain, September 2016, pp. 1-6.
- [49] M. Vilgelm, H. M. Gürsu, W. Kellerer and M. Reisslein, "LATMAPA: Load-Adaptive Throughput- MAXimizing Preamble Allocation for Prioritization in 5G Random Access," IEEE Access, 2017, Vol. 5, pp. 1103-1116.
- [50] A. Prasad, P. Lundén, M. Moisio, M. A. Uusitalo and Z. Li, "Efficient mobility and traffic management for delay tolerant cloud data in 5G networks," In Proceedings of IEEE International Symposium on Personal, Indoor and Mobile Radio Communications (PIMRC), Hong Kong, P.R. China, August-September 2015, pp. 1740-1745.
- [51] 3GPP TS 36.300 V15.3.0, *Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description*.
Available: <http://www.3gpp.org/dynareport/36300.htm>
- [52] 3GPP TR 36.742 V15.0.0, *Study on Self-Organizing Networks (SON) for enhanced Coordinated Multi-Point (eCoMP)*.
Available: <http://www.3gpp.org/dynareport/36742.htm>

- [53] 3GPP TS 32.500 V12.1.0, *Telecommunication Management; Self-Organizing Networks (SON); Concepts and requirements*.
Available: <http://www.3gpp.org/dynareport/32500.htm>
- [54] 3GPP, *32 series*.
Available: <http://www.3gpp.org/DynaReport/32-series.htm>
- [55] M. Amirijoo, et al., "Neighbor cell relation list and physical cell identity self-organization in LTE," In Proceedings of IEEE International Conference on Communications (ICC) Workshops, Beijing, P.R. China, May 2008, pp. 37-41.
- [56] P. Ramachandra et al., "On automatic establishment of relations in 5G radio networks," In Proceedings of IEEE International Symposium on Personal, Indoor and Mobile Radio Communications (PIMRC), Valencia, Spain, September 2016, pp. 1-6.
- [57] M. Huang and X. Zhang, "Enhanced automatic neighbor relation function for 5G cellular systems with massive MIMO," In Proceedings of IEEE International Conference on Communications (ICC) Workshops, Paris, France, May 2017, pp. 1-6.
- [58] M. Amirijoo, P. Frenger, F. Gunnarsson, J. Moe and K. Zetterberg, "On self-optimization of the random access procedure in 3G long term evolution," In Proceedings of IFIP/IEEE International Symposium on Integrated Network Management (IM)-Workshops, Long Island, New York, USA, June 2009, pp. 177-184.
- [59] K. Kitagawa, T. Komine, T. Yamamoto and S. Konishi, "A handover optimization algorithm with mobility robustness for LTE systems," In Proceedings of IEEE International Symposium on Personal, Indoor and Mobile Radio Communications (PIMRC), Toronto, Ontario, Canada, September 2011, pp. 1647-1651.
- [60] A. Awada, B. Wegmann, D. Rose, I. Viering and A. Klein, "Towards self-organizing mobility robustness optimization in inter-RAT scenario," In Proceedings of IEEE Vehicular Technology Conference (VTC Spring), Dresden, Germany, June 2013, pp. 1-5.
- [61] O. Blume, H. Eckhardt, S. Klein, E. Kuehn and W. M. Wajda, "Energy savings in mobile networks based on adaptation to traffic statistics," Bell Labs Technical Journal, 2010, Vol. 15, No. 2, pp. 77-94.

- [62] M. Amirijoo, Z. Chai, P. Frenger, B. Olin and J. Moe, "Self-optimizing antenna muting - energy consumption and user throughput analysis," In Proceedings of International Symposium on Wireless Communication Systems (ISWCS), Paris, France, August 2012, pp. 46-50.
- [63] S. Nováczki, V. Wille, O. N. C. Yilmaz, S. Hämäläinen and H. Sanneck, Self-Healing, LTE Self-Organising Networks (SON): Network Management Automation for Operational Efficiency (eds. S. Hämäläinen, H. Sanneck and C. Sartori), John Wiley & Sons, December 2011.
- [64] Z. Liu, P. Hong, K. Xue and M. Peng, "Conflict Avoidance between Mobility Robustness Optimization and Mobility Load Balancing," In Proceedings of IEEE Global Telecommunications Conference (GLOBECOM), Miami, Florida, USA, December 2010, pp. 1-5.
- [65] 3GPP TR 25.814 V7.1.0, *Physical layer aspects for evolved Universal Terrestrial Radio Access (UTRA)*.
Available: <http://www.3gpp.org/dynareport/25814.htm>
- [66] 3GPP TR 36.814 V9.0.0, *Evolved Universal Terrestrial Radio Access (E-UTRA); Further advancements for E-UTRA Physical layer aspects*.
Available: <http://www.3gpp.org/dynareport/36814.htm>
- [67] 3GPP TS 36.213 V11.13.0, *Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer procedures*.
Available: <http://www.3gpp.org/dynareport/36213.htm>
- [68] 3GPP TS 36.331 V11.18.0, *Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Resource Control (RRC); Protocol specification*.
Available: <http://www.3gpp.org/dynareport/36331.htm>
- [69] J. Laiho, A. Wacker and T. Novasad, *Static radio network simulator (Radio Network Planning and Optimization for UMTS, John Wiley & Sons Inc., 2nd Edition)*, 2006.
- [70] 3GPP TS 36.321 V11.6.0, *Evolved Universal Terrestrial Radio Access (E-UTRA); Medium Access Control (MAC) protocol specification*.
Available: <http://www.3gpp.org/dynareport/36321.htm>
- [71] 3GPP TS 36.211 V11.7.0, *Evolved Universal Terrestrial Radio Access (E-UTRA); Physical channels and modulation*.
Available: <http://www.3gpp.org/dynareport/36211.htm>

- [72] 3GPP, R2-062160, *RACH Contention and Retry Cases*, NTT DoCoMo, NEC, RAN2#54, Tallinn, Estonia, August 2006.
- [73] ITU-R Report M.2135 (2008), *Guidelines for evaluation of radio interface technologies for IMT-Advanced*.
Available: https://www.itu.int/dms_pub/itu-r/opb/rep/R-REP-M.2135-2008-PDF-E.pdf
- [74] Y. R. Zheng and C. Xiao, "Improved models for the generation of multiple uncorrelated Rayleigh fading waveforms," *IEEE Communications Letters*, 2002, Vol. 6, No. 6, pp. 256-258.
- [75] P. Mogensen, et al., "LTE capacity compared to the Shannon bound," In *Proceedings of IEEE Vehicular Technology Conference (VTC Spring)*, Dublin, Ireland, April 2007, pp. 1234-1238.
- [76] 3GPP TR 36.942 V11.0.0, *Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Frequency (RF) system scenarios*.
Available: <http://www.3gpp.org/dynareport/36942.htm>
- [77] I. Viering, M. Döttling and A. Lobinger, "A Mathematical Perspective of Self-Optimizing Wireless Networks," In *Proceedings of IEEE International Conference on Communications (ICC)*, Dresden, Germany, June 2009, pp. 1-6.
- [78] A. Prasad, P. Lundén, O. Tirkkonen and C. Wijting, "Mobility state based flexible inter-frequency small cell discovery for heterogeneous networks," In *Proceedings of IEEE International Symposium on Personal, Indoor and Mobile Radio Communications (PIMRC)*, London, UK, September 2013, pp. 2057-2061.
- [79] S. Barbera, et al., "Synchronized RACH-less handover solution for LTE heterogeneous networks," In *Proceedings of International Symposium on Wireless Communication Systems (ISWCS)*, Brussels, Belgium, August 2015, pp. 755-759.
- [80] Qualcomm Incorporated, *LTE Mobility Enhancements*, February 2010.
Available: <https://www.qualcomm.com/media/documents/files/lte-mobility-enhancements.pdf>
- [81] Powerwave, *Antenna product data sheets*, 2009.
Source: <http://www.powerwave.com/antennaproducts.asp>

- [82] J. Niemelä and J. Lempiäinen, "Impact of mechanical antenna down-tilt on performance of WCDMA cellular network," In Proceedings of IEEE Vehicular Technology Conference (VTC Spring), Milan, Italy, May 2004, pp. 2091-2095.
- [83] F. Athley and M. N. Johansson, "Impact of Electrical and Mechanical Antenna Tilt on LTE Downlink System Performance," In Proceedings of IEEE Vehicular Technology Conference (VTC Spring), Taipei, Taiwan, May 2010, pp. 1-5.
- [84] 3GPP TS 36.814 V0.4.1, *Evolved Universal Terrestrial Radio Access (E-UTRA); Further advancements for E-UTRA Physical layer aspects*. Available: <http://www.3gpp.org/dynareport/36814.htm>
- [85] K. Uehara, "Random Case Analysis of Inductive Learning Algorithms," In Proceedings of the International Conference on Discovery Science (DS), Fukuoka, Japan, December 1998, pp. 60-71.
- [86] D. W. Aha, "Case-Based Learning Algorithms," In Proceedings of the DARPA Case-Based Reasoning Workshop, Washington, D.C., USA, 1991, pp. 147-158.
- [87] P. Langley and W. Iba, "Average-Case Analysis of a Nearest Neighbor Algorithm," In Proceedings of the International Joint Conference on Artificial Intelligence (IJCAI), Chambéry, France, August-September 1993, pp. 889-894.
- [88] E. Alpaydin, *Introduction to Machine Learning (Second Edition)*, the MIT Press, 2010, pp. 486-489.
- [89] E. B. Wilson, "Probable inference, the law of succession, and statistical inference", *Journal of the American Statistical Association*, 1927 Vol. 22, No. 158, pp. 209-212.
- [90] A. Imran, A. Zoha and A. Abu-Dayya, "Challenges in 5G: how to empower SON with big data for enabling 5G," *IEEE Network*, 2014, Vol. 28, No. 6, pp. 27-33.
- [91] Y. He, et al., "Big data analytics in mobile cellular networks," *IEEE Access*, 2016, Vol. 4, pp. 1985–1996.
- [92] P. Chiu, J. Reunanen, R. Luostari and H. Holma, "Big Data Analytics for 4.9G and 5G Mobile Network Optimization," In Proceedings of

IEEE Vehicular Technology Conference (VTC Spring), Sydney, Australia, June 2017, pp. 1-4.

Errata

Publications I, II, III

- The antenna radiation loss equations should be corrected as $A_H(\varphi) = -\min \left[12 \left(\frac{\varphi}{\varphi_{3dB}} \right)^2, A_{\max} \right]$ and $A_V(\theta) = -\min \left[12 \left(\frac{\theta}{\theta_{3dB}} \right)^2, SLA_v \right]$. The error consists of sub/superscript typos and does not affect the results.
- The transmit diversity term, STTD, refers to the space-frequency equivalence of STTD in LTE FDD. This does not have any effect on the results.

Publication III

- In Figures 9 and 10, the shadowing decorrelation is 0 between the vertical sectors. This illustration error does not affect the numerical results.

Publication IV

- The handover condition should be corrected as $SINR_{source\ cell} \geq -6\ dB$. The typo - due to the missing minus sign - has no effect on the results.
- The similarity equation should be corrected as $Similarity(C, Q) = \frac{1}{\sqrt{\sum_{k=1}^M \sum_{j=1}^N [W_{i,j} \cdot (KPI_{i,j}^C - KPI_{i,j}^Q)]^2}}$. The error is comprised of missing brackets and does not affect the results.

Publications V, VI, VIII

- The SINR equations should be corrected as $\gamma = \frac{P_{tx,s} \cdot L_s^{-1}}{\sum_{n \neq s} \rho_n \cdot P_{tx,n} \cdot L_n^{-1} + N}$ in [PV], $\gamma_s^{\text{UE}} = \frac{P_{tx,s}^{\text{PRB}} \cdot L_s^{\text{UE}-1}}{\sum_{n \neq s} \rho_n \cdot P_{tx,n}^{\text{PRB}} \cdot L_n^{\text{UE}-1} + N^{\text{PRB}}}$ in [PVI], and $\gamma_{u,DL}^c = \frac{P_u^c \cdot L_u^{c-1}}{\sum_{k \neq c} P_k \cdot L_u^{k-1} + N}$, $c = X(u)$ for DL and $\gamma_{u,UL}^c = \frac{P_u \cdot L_u^{c-1}}{\sum_{k \neq c} \sum_{i \neq u} P_i \cdot L_i^{c-1} + N}$, $c = X(u)$ for UL in [PVIII]. The errors are comprised of superscript typos and do not affect the results.

Publication VI

- The PRB BW parameter, BW_{PRB} , is assumed to be 200 KHz in the simulations as the BW efficiency addresses the guard band overhead. This does not have any effect on the results.
- The equations used in the self-optimization methodology should be corrected as $s_p = \arg \max_{s \in I} \left[\sum_{\text{UE} \in s} \text{PRB}_{\text{req},s}^{\text{UE}} + \sum_{\text{UE} \in s^*} \text{PRB}_{\text{req},s^*}^{\text{UE}} \right]$ and $\sum_{s \in S} \sum_{\text{UE} \in s} \text{PRB}_{\text{req},s}^{\text{UE}} \leq \sum_{s \in S} \sum_{\text{UE} \in s} \text{PRB}_{\text{req},s}^{\text{UE}}$. The equation descriptions are correct in the text, but the satisfied UE ratio erroneously replaces the virtual load in the equations. These typos do not affect the results.

Publication VII

- Self-optimization period, which is given as 300 s in Table I [PVII], should be corrected as 60 s. It is a typo and do not have any effect on the results.
- The following equations regarding CBRA and NCBRA should be corrected as $n_{C,d} = (1 - \text{DMP}_C) \cdot n_C$ and $n_{NC,d} = (1 - \text{DMP}_{NC}) \cdot n_{NC}$. The error is comprised of subscript typos and does not affect the results.
- The AP equations should be corrected as $AP_{C,m} = 1 - \prod_{i=1}^m (\text{DMP}_{C,i} + (1 - \text{DMP}_{C,i}) \cdot CP)$ and $AP_{NC,m} = 1 - \prod_{i=1}^m (\text{DMP}_{NC,i} + (1 - \text{DMP}_{NC,i}) \cdot BR)$. The error is comprised of subscript typos and does not affect the results.

Self-Organizing Networks (SON) allows the automated control of various network parameters. With minimal human interaction, SON aims to provide greater performance gains in comparison to legacy optimization solutions. As a result of more efficient and dynamic use of network resources, it is expected that both operational and capital expenditures are minimized. In this regard, the doctoral dissertation contributed to the ongoing SON research by exploring self-optimization capabilities in LTE and its evolution toward 5G. Furthermore, practical solutions were developed for SON use cases and analyzed by means of both analytical and experimental frameworks. System-level simulation results revealed that the network performance could be improved significantly in terms of coverage, capacity, mobility robustness and load balancing.

ISBN 978-952-60-8327-8 (printed)
ISBN 978-952-60-8328-5 (pdf)
ISSN 1799-4934 (printed)
ISSN 1799-4942 (pdf)

Aalto University
School of Electrical Engineering
Department of Communications and Networking
www.aalto.fi

**BUSINESS +
ECONOMY**

**ART +
DESIGN +
ARCHITECTURE**

**SCIENCE +
TECHNOLOGY**

CROSSOVER

**DOCTORAL
DISSERTATIONS**