Untangling the Application of Text-mining Methods in Information Systems Domain

Bikesh Raj Upreti

Untangling the Application of Text-mining Methods in Information Systems Domain

Bikesh Raj Upreti

Supervising professor

Associate. Professor, Pekka Malo, Aalto University school of Business, Finland

Thesis advisor

Professor, Matti Rossi, Aalto University school of Business, Finland

Preliminary examiners

Professor, J.P. Shim, Georgia State University, USA

Professor, Teero Vartiainen, University of Vaasa, Finland

Opponent

Professor, Oliver Müller, Universität Paderborn, Germany

Aalto University publication series

DOCTORAL DISSERTATIONS 89/2019

© 2019 Bikesh Raj Upreti

ISBN 978-952-60-8545-6 (printed)

ISBN 978-952-60-8548-7 (pdf)

ISSN 1799-4934 (printed)

ISSN 1799-4942 (pdf)

<http://urn.fi/URN:ISBN:978-952-60-8548-7>

Unigrafia Oy

Helsinki 2019

Finland

Publication orders (printed book):

bikesh.upreti@gmail.com

julkaisut@aalto.fi

Supported by: HSE-Foundation, Plauo Foundation, Matti Lehti Foundation

Author

Bikesh Raj Upreti

Name of the doctoral dissertation

Untangling the Application of Text-mining Methods in Information Systems Domain

Publisher School of Business

Unit Department of Information and Service Management

Series Aalto University publication series DOCTORAL DISSERTATIONS 89/2019

Field of research

Date of the defence 17 May 2019

Language English

☐ **Monograph**

☐ **Article dissertation**

☒ **Essay dissertation**

Abstract

The advent of digitalization has brought a massive proliferation of unstructured data, producing vast repositories of textual data, from various sources, such as Web sites, academic publications, news articles, blog posts, e-mail, corporate communication platforms, reports, and social media feeds. This proliferation coupled with the upsurge in mobile and Web technologies alongside ever-improving connectivity has led to various digital platforms and applications rapidly achieving mass-market penetration. With the production of textual and other forms of unstructured data certain to continue at unprecedented rates for the foreseeable future, this availability on massive scale presents both opportunities and challenges that researchers and practitioners must address.

Ability to utilize text data on a large scale not only provides better coverage in terms of sample size but also opens opportunities to build a deeper understanding of phenomena that otherwise are simply unobservable, "hidden in the noise." However, as the world races towards high-volume production, distribution, and consumption of digital text, information systems (IS) researchers are proving slow to start reaping the potential of analyzing textual data. There is an urgent need for methods and techniques that can meet the challenge of analyzing vast bodies of textual data. In an effort to demonstrate potential application of text-mining methods in information systems research, the dissertation presents essays that address large-scale text-based datasets' use in literature analysis and studies of system-specific behavioral outcomes. The first essay deals with identifying the research themes presented in a large body of publications on cloud computing, and the second essay demonstrates the machine-based classification of papers in leading information-systems journals. Of the behavior-focused pieces, the third essay utilizes user-generated content to illustrate system-driven viewing outcomes in the context of binge watching of television shows, and the final essay examines a large volume of content connected with a business-to-business Web portal, reporting on a study of browsing-device-linked differences in interest in marketing material.

In addition to the individual essays, the dissertation contributes to the scholarly discussion of text-mining research issues in three important ways. Firstly, it presents a conceptual framework that aids in revealing the fundamentals of text-mining research in terms of two dimensions: research objective and level of text analysis. Secondly, the four essays provide concrete demonstrations of various suitable applications of text-mining. Finally, the dissertation examines the implications of the work, highlighting specific issues and challenges pertaining to text-mining research. The findings and implications of this work should benefit IS researchers and practitioners striving to exploit large volume of textual data.

Keywords Text mining, Information Systems, Systematic Review, Topic Models, Text Classification, Word Embedding, System-driven Behaviour, Social Media

ISBN (printed) 978-952-60-8545-6

ISBN (pdf) 978-952-60-8548-7

ISSN (printed) 1799-4934

ISSN (pdf) 1799-4942

Location of publisher Helsinki

Location of printing Helsinki **Year** 2019

Pages 170

urn <http://urn.fi/URN:ISBN:978-952-60-8548-7>

Preface

Life as a Ph.D. student has been an amazing experience, a joyful ride, and above all a wonderful learning path. It all started with an aspiration to compliment my knowledge with quantitative skills and techniques. By the time of completion, doctoral education has an immense impact in developing me as a better thinker, decision maker, and especially as a better person. Above all, it has also incited a hunger to learn, and an ambition to grow as an impactful researcher. I would like to take this opportunity to express my sincere gratitude to all the wonderful people who have supported me in one way or others.

First and foremost, I would like to thank my supervisor, Associate Professor. Pekka Malo and my thesis advisor, Professor. Matti Rossi. It all started with Pekka believing in me and allowing me to pursue my interests and goals with a good balance of guidance and independence. This dissertation would not have been possible without him. I have also received tremendous support and guidance from Matti who has been indispensable in this process. In addition, I am grateful to Professor. Markku Kuula for his warm support and encouragement that gave me a lot of confidence and belief.

I would also like to take this opportunity to express my gratitude to the pre-examiners, Professor. J.P. Shim and Professor. Teero Vartiainen. Their comments and evaluations from the pre-examination have been extremely valuable and have helped me to improve the manuscript. I am greatly honored to have Professor, Oliver Müller as an opponent for the public defense. For a researcher who is following a similar path as Professor, Müller, his presence as an opponent is an invaluable experience.

Next, I would like to thank the co-authors for their significant contribution to the dissertation. It was an excellent experience co-authoring with the fabulous colleagues who are amazing both as collaborators and as friends. Aleksandre Asatiani has not only been a collaborator on multiple occasions but also a friend that I can look up to and rely upon. I have found a great colleague and collaborator in Antti Salovaara and Jani Merikivi who have always inspired and improved me as a researcher. Working with

Jussi Nykänen and Johanna Bragge was also a wonderful experience that I enjoyed a lot. I had a great learning experience with you guys, and I highly appreciate your valuable inputs.

Working as a researcher in the department was an enjoyable experience thanks to the fantastic company of Aleksandre Asatiani, Jani Merikivi, Jussi Nykänen, Oskar Ahlgren, Antti Saastamoinen, Abolfazi Keshvari, Ankur Sinha, Anton Frantsev, Tapani Rinta-Kahila, Juho-Petteri Huhtala, Saadat Ali Yawar, Venkata Marella, Philipp Back, and Nischal Guragain. You guys have been great companions, and thank you a lot for the wonderful friendship.

I have also received a great deal of support and grants from various organizations that deserve deep gratitude. I would like to express my sincere appreciation to the "HSE-Foundation" for awarding me multiple grants to support my research and conference travels. I have also received research grants from the "Paulo Foundation" and "Matti Lehti Foundation". These grants have allowed me to focus on my studies and I highly value the support that the foundations have provided over the years. The IT service team of the Aalto University School of Business and the Triton team from the computer science department has been really kind and helpful when I had technical problems. I would like to thank them for a wonderful service. I highly appreciate Merja Mäkinen who has been extremely supportive in providing necessary help and services in important work-related issues.

Last but not least, I would like to thank my parents, relatives, and friends who backed me up unconditionally. I will always be indebted to my parents who dedicated their life just to make sure that I could pursue my dream. Without their love and support, this achievement would not have been possible. I would also reserve a special appreciation for Sanjay Shrestha who was very helpful in collecting data needed for one of the essays. My Brother Bimesh Upreti has always supported me strongly and I would like to thank him for being there with me. Finally, I want to thank my wife, Rashmi Pyakurel Upreti who has always been there for me. Her love and support have allowed me to pursue my goals and without her, I would not have made it this far.

Helsinki, April 27, 2019,

Bikesh Raj Upreti

Contents

Preface	1
Contents	3
List of Publications	5
Author's Contribution	7
List of Figures	9
List of Tables	11
1. Introduction	13
1.1 Motivation	13
1.2 Text-mining research in the field of information systems	15
1.3 The research objectives	18
1.4 The conceptual framework for the research	19
1.5 The conceptual framework for the research	19
1.6 The structure of the dissertation	23
2. A Synthesizing Summary of the Essays	25
2.1 Essay I, To Reach The Clouds: Application of Topic Models to the Meta-review on Cloud Computing Literature	26
2.2 Essay II, Building Theories on Shaky Foundations? The Lack of Falsification and Correction of Knowledge in IS Research	29
2.3 Essay III, Analyzing the Ways IT Has Changed Our TV Consumption: Binge Watching and Marathon Watching' .	32
2.4 Essay IV, System-driven Browsing Outcomes in Consum- ing B2B Content: A Case of B2B Content Marketing . . .	37
3. Discussion and Conclusions	43
3.1 Implications of the research	45

3.1.1	The diversity of text: Not all text is the same . .	45
3.1.2	Human input as a fundamental element in text-mining applications	46
3.1.3	Evolution of research designs and text-mining .	47
3.2	Conclusions	48
References		51
4. Appendices		55
4.1	Appendix I	56
4.2	Appendix II	57
Publications		59

List of Publications

This thesis consists of an overview and of the following publications which are referred to in the text by their Roman numerals.

- I** Upreti, Bikesh; Asatiani, Aleksandre; and Malo, Pekka. To reach the clouds: Application of topic models to the meta-review on cloud computing literature. In *49th Hawaii International Conference on System Sciences*, 3979–3988, January 2016.
- II** Salovaara, Antti; Upreti, Bikesh Raj; Nykänen, Jussi; and Merikivi, Jani. Building theories on shaky foundations? The lack of falsification and correction of knowledge in IS research. Submitted to *European Journal of Information Systems*, 2019.
- III** Upreti, Bikesh Raj; Merikivi, Jani; Bragge, Johanna; and Malo, Pekka. Analyzing the ways IT has changed our TV consumption: Binge watching and marathon watching. In *International Conference on Information Systems*, Seoul, South Korea, December 2017.
- IV** Upreti, Bikesh. System-driven browsing outcomes in consuming B2B content: A case of B2B content marketing. , (Unpublished manuscript), .

Author's Contribution

Publication I: “To reach the clouds: Application of topic models to the meta-review on cloud computing literature”

The author of the dissertation is the first author of this publication and led the research idea's development, the collection of data, running of the experiments, result analysis, also participating in the writing of the paper.

Publication II: “Building theories on shaky foundations? The lack of falsification and correction of knowledge in IS research”

The dissertation's author is a co-author of this publication and contributed to refinement of the code book; manual coding of the data; conducting of the classification experiment; validation of the results, and preparation of the paper's data, method, and results sections.

Publication III: “Analyzing the ways IT has changed our TV consumption: Binge watching and marathon watching”

The author of the dissertation is the first author of the publication and contributed in developing the research design, collecting and processing the data, running the modeling, analyzing the results, and writing the paper.

Publication IV: “System-driven browsing outcomes in consuming B2B content: A case of B2B content marketing”

The author of the dissertation is the sole author of the fourth manuscript.

List of Figures

1.1	The conceptual framework for text-mining research . . .	22
2.1	The research design applied for the essays featured in the dissertation	25
2.2	Topics and disciplines connected with cloud-computing research	28
2.3	The binge network	36
2.4	The binge model	37
2.5	The marathon model	37
2.6	Profiles for user-viewed content from promotional channels with a) hand-held devices and b) personal computers	40
2.7	Profiles for the content viewed from sellers' channels, for a) hand-held devices and b) personal computers	41

List of Tables

2.1	A summary of the data collected	30
2.2	The candidate classifiers' performance with the test set .	32
2.3	The distribution of knowledge-correcting papers by publication	33
2.4	Content-browsing patch description for promotional channels for a) hand-held devices and b) personal computers .	40
2.5	Content patch description for users browsing sellers' own channels, for a) hand-held devices and b) personal computers	42
4.1	Description of Knowledge correcting typology	56
4.2	Keywords used in Data collections and Tweets collected	57

Part I: An Overview of the Dissertation

1. Introduction

“The written word may be man’s greatest invention. It allows us to converse with the dead, the absent, and the unborn.”

- Abraham Lincoln

1.1 Motivation

Written text has long been fundamental to preserving, communicating, and transferring information and knowledge across time and generations. Written text, as a technology for codifying information, came into existence in the early tokens used for counting and accounting, which later evolved into the form of script [20]. Over the course of recorded history, written text has witnessed a long journey from inscriptions in stone or metal, through dyes on walls and clothes, to marks on paper, and it has now entered the age of digitalization. Today, text data is created, stored, manipulated, distributed, and consumed in digital form, and the far-reaching penetration of the World Wide Web, mobile technology, and computation, in general, has guaranteed that the proliferation of already abundant textual data will continue apace for the foreseeable future. Hence, our modern age can be seen as an era of “information overload” in which the quantity of text at our disposal exceeds our processing capabilities. As the digital age progresses, we are only adding to the plethora of knowledge and information that we have accumulated – its amount is certain to grow in tandem with the upward trend in digital content and further contribute to the significance of information overload.

The availability of textual data in digital form on such a large scale has two important implications. Firstly, processing and analyzing large volumes of text manually is tedious, resource-intensive, and almost impossible in most cases. Conventional tools and techniques are of limited use in navigating a collection of text that extends to thousands or even millions of documents. Secondly, thanks to ever-improving computation

capacity and tools, large text corpora can be analyzed efficiently, a feat that just a few decades ago was only remotely achievable. Through the use of text-mining methods, interesting information and patterns that otherwise would remain unobservable and hidden can be uncovered from the data. Given the sharp growth in digital content, the future in this regard lies in the various forms of unstructured data as more and more information is created, distributed, and consumed in the form of text, video, and audio content. In light of the scale of the bodies of text available and the efforts required for collecting, processing, and analyzing that material, text analysis carried out by means of text-mining tools and methods is the way forward [33].

The roots of text-mining can be traced back to the 1958 paper "A Business Intelligence System," by Luhn [26]. That seminal work defines business intelligence as embodied in a system that "utilizes data-processing machines for auto-abstracting and auto-encoding of documents and for creating interest profiles for each of the 'action points' in an organization. Both incoming and internally generated documents are automatically abstracted, characterized by a word pattern, and sent automatically to appropriate action points." Clearly, Luhn had text-mining in mind when describing a business-intelligence system. Further, his definition of business intelligence points to the fact that even six decades ago organizations were facing a pressing need to automate text analysis and render it systematic. Later, Feldman and Dagan [15] discussed text-mining from the perspective of knowledge discovery, as a set of tools designed for extracting useful non-trivial insights from text. In a similar fashion, Hearst [22] defined text-mining as "the discovery by computer of new, previously unknown information, by automatically extracting information from different written resources." In these relatively early definitions, computer-driven automated text analysis is often referred to interchangeably as "text mining," "text data mining," "text analysis," and "text analytics." From the methodological perspective, text-mining can be considered to be a set of data-mining tools adapted to the context of unstructured textual data. Thus, we can define text-mining in summary as the suite of computer-based tools and techniques for structuring textual data for extracting patterns and meaningful information and insight.

Even though computer-mediated text analysis has been gaining momentum in recent years, the need for automating the analysis of textual material has clearly existed for quite some time now. Back in 2004, Robb [31] estimated that a large proportion of the information and knowledge within the enterprise is stored in unstructured text files. Since then, the proliferation of digital and Internet technology has further intensified the growth in unstructured data. In consequence, unstructured data easily outstrips structured data in both volume and growth. Today, the majority of information that organizations acquire is in the form of text [8] produced

as a modern organization interacts with text arising from various sources: internal reference and policy documents, interview transcripts and meeting minutes, e-mail, Web or intranet content (such as tweets and blog posts), contracts, academic publications, reviews, comments, customer feedback, and others. Added to this already diverse pool of text is material collected from external inputs, such as social media channels, discussion fora, and online portals presenting customer reviews. In addition to the text, various form of unstructured data generated from machine-to-machine communication, business transactions, biometric system, voice searching and indexing from company-specific phonic-indexing technology resides in the organizational repository.

The vast quantities of textual and other forms of unstructured data traveling through today's various information systems provide opportunities for information systems (IS) researchers to gain substantial insights into the phenomena and patterns woven within the text collected [23]. Yet, whatever the abundance of textual data or the promise it represents, the IS research domain is still far from fully realizing the potential of this form of data. Since researchers are going to be faced with large bodies of textual data increasingly often as the future unfolds, text-mining research is bound to become more a necessity than a luxury. It is in this context that I present this dissertation: a demonstration of rich text-mining applications in the field of information systems. The main contribution of this work is to provide a conceptual research framework and four illustrative essays that speak to the value of a transition toward studies utilizing text data on a large scale.

1.2 Text-mining research in the field of information systems

In the year 2002, Sebastiani [37] described text-mining as operations that uncover usage patterns and derive useful information from a large body of text data. Later, Hearst [22], One of the early contributors to the literature, defined the term "text data mining" when discussing a system capable of extracting insight from text. His term "text mining" gained popular currency in the realm of search engines [45]. Though there was little agreement as to the most suitable term or the concept in the early stages, the field was viewed as being closely related to a much established one, data-mining, natural language processing, and statistics. Text-mining can be viewed as a special case of data-mining that entails extracting useful knowledge from unstructured and semi-structured bodies of data such as textual documents [14]. We can state in summary that text-mining is focused on extracting patterns and useful information from a large body of text, which is usually in the unstructured or semi-structured form. As a research field, text-mining draws from several disciplines, with

contributions from work in such areas as natural language processing, machine learning, and statistics.

Most of the IS studies utilizing textual-form data have been carried out with a small sample of text documents subjected to manual analysis. One finds only a handful of studies with large bodies of text data in the leading information-systems publications. **Association of Information Systems (AIS)** library indexing indicates that "Competitive Intelligence and the Web", by Boncella [5], is among the first writings to address text-mining in the context of information-systems studies. However, this effort was limited to briefly highlighting text-mining methods within the Web-mining framework as a tool for analyzing a Web site's text content. A few years later, in 2006, a study by Kuechler et al. [24] became one of the earliest efforts to acknowledge the importance of computer-mediated text data, identifying a need for looking beyond "text as a unitary data type." Centered as it was on assessing effects of explicit goal statements in business-process narratives, their paper left much room for noteworthy text-mining-related applications and contributions.

With such work from the early 2000s, IS scholars began to recognize the potential of text-mining research and the emerging need for it. It was only after 2006 that text-mining research picked up momentum and IS studies started employing text-mining methods to explore research problems. Noteworthy among these early efforts is Abbasi and Chen's [1] introduction of **CyberGate**. This framework was intended for a broad range of classification-oriented tasks relying on text analysis, such as determining a typology for opinions, styles, genres, or interactions. The performance of the CyberGate framework was evaluated with 1,000 e-mail messages from the Enron email corpus.

Text-mining applications have managed to gain some traction among IS researchers as an element utilized alongside others in network analysis. For instance, a 2012 study by Chau and Xu [7] worked with a combination of unstructured text from two blog contexts and associated structured metadata to examine interaction in blogging communities. With a text corpus consisting of more than 75,000 blog posts related to Apple's iPod and 694,000+ posts connected with the Starbucks brand, they approached the text analysis mainly through term frequency, keyword matching, and sentiment analysis. In other work, Luo et al. [27] examined the impact of experts' blogs in the domain of brand perceptions and long-term brand value. Their dataset comprised upwards of 131,000 blog posts, for which sentiment classification was performed with a support vector machine (SVM), their preferred method of analysis for such text content. Their study found that the volume of material on a given brand and the sentiment expressed therein correlates positively with good consumer perceptions of that brand and negatively with views supporting competing brands. In a methodology-focused study, Guo et al. [21] developed a tool for extracting

relevant data from an intra-organization blog platform. They proposed a heuristic method based on hierarchical clustering from a similarity matrix. This system, REPEST, was benchmarked against the competing clustering techniques for 10 distinct datasets.

User-generated content, in the form of social media posts and comments posted online, has been considered to some extent in IS research. With the objective of understanding factors in the helpfulness of product reviews, Mudambi, and Schuff [29] analyzed more than 1,500 customer reviews of products posted for six items from **amazon.com**. Using word counts, as a dependent variable measured on the basis of word choice, as a proxy for review depth, the researchers found a positive association between review depth and helpfulness. In another instance, Zhang et al. [46] proposed employing a system utilizing hierarchical community-detection methods to identify closely related brand networks in a social media setting. Their research, with brand-to-brand networks in a Facebook context, spanned 2,000 brand-specific pages, featuring more than three million user posts to improve the identification of the target audience. This work was supplemented by user-sentiment analysis for ranking users in each brand community. In similar work with user-generated context, Cheng et al. [9] developed a recommendation framework taking input from the micro-blog platform Twitter. To examine information diffusion patterns in relation to an emergency such as H1N1 flu, their research applied term-frequency analysis and k -mean clustering for story detection from 35,000 tweets.

Recently, information-systems researchers have begun exploring the potential of topic models: a suite of algorithms that identifies latent themes in a collection of documents. Deng et al. [13] are among these scholars. They applied latent semantic analysis (LSA) to analyze the work of business analysts. In work along similar lines, Shi et al. [38] wrote the paper "Toward a Better Measure of Business Proximity: Topic Modeling for Industry Intelligence," which presented latent Dirichlet allocation (LDA) as an alternative approach, suitable for computing proximities between business entities from unstructured text data. Their corpus consisted of descriptions of key facts on 24,382 companies, such as their products, markets, and technologies, with each textual description being a short-to-medium-length paragraph.

Some information systems scholars have encompassed attempts to explain the workings of text-mining methods by detailing an illustrative application. One instance of this is a paper in which Mertens et al. [28] attempt to demystify the features contributing to the category in which a model places a particular document. The authors present a case of a binary Web-page classification problem for which more than 25,000 Web pages must be classified as having "adult content" or not. Using text from the Web pages to represent the page content, they demonstrate various aspects of document classification, describing each at length and rightly concluding

that the loose structuring of text data, the typically high dimensionality involved, and how the relevant features of the text are represented are critical aspects of document classification, with a profound influence on the decision ultimately made for a given document. In another demonstration, aimed at introducing topic models to IS researchers, Debortoli and colleagues [12] applied LDA to analyze 12,900 customer reviews posted on amazon.com. Their paper provides solid guidelines for researchers who are interested in learning about LDA and exploiting it in their research.

Text-mining research in the IS field can be characterized as extending to various types of textual data, among these e-mail [1], blog content [7] [27] [21], customer reviews [29] [12], and social-media content [46] [9]. However, most scholars have relied on mechanisms such as frequency metrics (counting the occurrences of particular terms), clustering algorithms, and keyword matching as the principal text-mining method. It is noteworthy also that this discipline largely confines its use of text-mining methods to serving as a small component of larger research design. A review of the literature points to a clear need for research that demonstrates the utility of standalone text-mining methods, of various types. In response, this dissertation contributes reports on four studies designed to handle textual data on a large scale by means of several text-mining methods.

1.3 The research objectives

To fulfill the main objective of demonstrating fruitful application of multiple text-mining methods in the IS research domain, the dissertation project drew together studies that represent diverse research settings and together showcase text-mining applications suited to various types of text data, several levels of analysis, and multiple research objectives. An overarching conceptual framework for text-mining research is laid out below, after which the dissertation presents the four essays, situated within the proposed framework. These essays describe studies designed to deal with large bodies of textual data in light of the framework. Academic publications, social-media feeds, and content extracted via a Web portal's data all lie on the spectrum of data sources dealt with, while the range of research objectives covers topic identification, document classification, extraction of relevant information, and analysis of documents' similarities. The scope of the research designs encompasses conducting a systematic literature review, building an appropriate set of training data, classifying documents by means of text-mining methods, processing social-media text, analyzing Web-content browsing records, and carrying out qualitative evaluation of the results. Each of the individual studies makes its own contribution to text-mining research in the IS field, while the essays together form an extensive, coherent addition to scholarship on application for numerous

forms of textual data in pursuit of multiple research aims.

1.4 The conceptual framework for the research

To fulfill the main objective of demonstrating the application of multiple text-mining methods in the IS research domain, the dissertation project drew together studies that represent diverse research settings and together showcase text-mining applications suited to various types of text data, several levels of analysis, and multiple research objectives. An overarching conceptual framework for text-mining research is laid out below, after which the dissertation presents the four essays, situated within the proposed framework. These essays describe studies designed to deal with large bodies of textual data in light of the framework. Academic publications, social-media feeds, and content extracted via a Web portal's data all lie on the spectrum of data sources dealt with, while the range of research objectives covers topic identification, document classification, extraction of relevant information and analysis of documents' similarities. The scope of the research designs encompasses conducting a systematic literature review, building an appropriate set of training data, classifying documents by means of text-mining methods, processing social-media text, analyzing Web-content browsing records, and carrying out qualitative evaluation of the results. Each of the individual studies makes its own contribution to text-mining research in the IS field, while the essays together form an extensive, coherent addition to scholarship on the application for numerous forms of textual data in pursuit of multiple research aims.

1.5 The conceptual framework for the research

The computer science domain's conceptualization of text-mining mainly follows a dichotomy between supervised and unsupervised learning. In the former, the machine learns from labeled items of text data, whereas in the latter it identifies structure from unlabeled textual data. The fundamental difference between the two methods lies in the validation of text-mining results: since a label is present in supervised text-mining tasks, the results can be evaluated against the labels, while unsupervised-learning tasks are devoid of such luxury and still requires input from human experts. Solka [39] has subdivided text-mining tasks further, into five categories (i) dimensionality reduction, (ii) clustering, (iii) topic modeling, (iv) classification, and (v) distance and similarity computing. The first three are unsupervised methods, whereas classification, being a supervised learning task, must proceed from labeled data, for learning the classification rules to apply. Finally, computation of distance and/or similarity is often carried

out in both supervised and unsupervised manner.

Social sciences literature has also discussed types of text-mining methods. Considering them in terms of the nature of the analysis performed, Roberts [32] discusses text-mining methods as tools aimed at providing structure to the text via any of three distinct analysis modes: (i) thematic text analysis, (ii) semantic text analysis, and (iii) network text analysis. Thematic text analysis concerns itself with the number of times certain themes and concepts appear in the text. Semantic analysis extends further, placing focus on understanding relationships between themes, and network analysis examines network webs among the themes present. In the context of quantitative content analysis, there are two traditional text-analysis mechanisms: substitution models and correlation models [44]. Use of a substitution model resembles document classification wherein researchers assign predefined categories to pieces of material, whereas correlation models are used for identifying the structure in the absence of a preexisting set of categories.

In most of the literature to date, text-mining methods have been explained from the perspective of the tasks for which these methods are applied. While this does provide a good overview of text-mining methods in general, it fails to address the variety of the text-mining landscape, let alone do so comprehensively. Therefore, I find it necessary to preface my presentation of the various text-mining studies by outlining a framework through which they can be situated via each text-mining method's position along two dimensions: the unit of text analysis and the objective of analysis. The analysis-unit dimension is connected with how text is represented within the application. In any text-mining application, the fundamental problem lies in finding appropriate feature representation for the text. This is connected with structuring the text data, a key part of preparing the unstructured text for further analysis. Hence, finding a structural representation for the text can be viewed as delineating the unit of analysis.

On the continuum of units of analysis, three main bands can be identified: at one end are simple word-counting methods, that also includes more sophisticated forms of dictionary-based counting and scoring; in the middle lie various forms of vector representation; and finally, there is the use of latent variables extracted from the text. In word-count- and scoring-based analysis, the analyst relies mainly on counts, matching, and scoring for either individual keywords or dictionary-based keyword sets. Next, vectorization of text resembles the document indexing method, a method familiar in the information retrieval field. A text document can be represented as a combination of vectors that each represent a feature of the text. The simplest model in this representation class is "bag of words", in which each word is a vector of word occurrences. With the final class of analysis unit, the most complex, the analyst has to extract latent variables and

themes that characterize the content. Various clustering methods, where clusters can be described as lists of words, and topic models fall into this band. Even though there exist some structural similarities in vector based representation and latent variable, the fundamental difference lies in the purpose of text transformation. In latent variable representation, text features have a basis for interpretation such that they can be interpreted as latent variables explaining the underlining concept. On the contrary, vectorization produces text features optimal for a certain task where the meaning and interpretations of these features are less of the concern.

Coupled with the above consideration in the selection and tuning of text-mining methods is the second dimension: the objective for the text analysis. One can borrow from Gregor's distinctions among the goals behind theorization [18] to explain the objectives of text-mining research: (i) description, (ii) explanation, (iii) prediction, and (iv) prescription. Text-mining research in the first category – i.e., intended for description – mostly emphasizes discovering latent features and clusters that are capable of representing patterns in the text for the descriptive and analytical purpose. Explanation-oriented text-mining research, in turn, is focused on inferring the variable of interest from the text and then considering it in combination with structured data to explain the relationship under study. Research in the third category is aimed solely at improving predictive performances (e.g., classification of documents). Finally, the goal behind prescriptive text-mining studies is to provide a better explanation or improve the theoretical grounding of text-mining research, the analysis methods or their practical application. Most contributions from the computer-science discipline stem from the last two objectives in the list, while corresponding work in the social sciences has been largely dominated by text-mining researchers pursuing the first two.

In the dissertation project, I constructed studies that showcase text-mining studies occupying various points in the space formed by the two dimensions discussed above. Figure 1.1 shows where the component essays are positioned in these terms. My demonstration of text-mining research applications extends across all three units of analysis and three of the classes of objectives: description and analysis, explanation and prediction. For the first essay, the text was conceptualized in latent topic variable terms with the objective of describing the topics addressed in the literature. The work described in the second essay was carried out at the vector level, using a "vector space model" to predict the document class. The third essay demonstrates word-level analysis that employs dictionary-based term standardization with the aim of explaining the content-consumption phenomena "binge watching" and "marathon watching". Finally, the last essay illustrates the vector level of analysis, with a study constructed to apply a "paragraph vector" approach for analyzing device-driven browsing behavior. In each of the studies, the methodological choices were informed

by the dynamics of the aforementioned dimensions: the unit of analysis and the nature of the objectives.

Figure 1.1. The conceptual framework for text-mining research

In addition to position along the dimensions of text-mining research, the four essays differ in their scope. In the latter respect, the essays featured in this dissertation can be broadly divided into two sets of applications: text-mining methods in the analysis of literature and their use in the analysis of system-driven behavioral manifestations. Traditionally, IS researchers have relied on manual techniques for analyzing literature, hand-coding a small group of sample publications; however, the rapidly expanding volume of literature implies that future researchers will need to turn to advanced tools and techniques to complement their personal expertise. Responding to this emergent need, the first two essays detail two, quite different applications of text-mining methods that are amenable to use in literature synthesis. The study reported upon in Essay I used unsupervised topic models to uncover latent themes running through the literature, whereas Essay II showcases specifically how manual coding can be expanded upon via text-mining tools. The discussion covers the entire process from creating coding rules and performing manual coding to getting text-mining tools to learn the rules and finally verifying the validity of the prediction and performing post-validation analysis.

The studies constituting the second set both involved distinguishing user behavior on the basis of system usage. This holds great potential as an alternative approach for understanding user behavior, especially with regard to digital products. While the motivation was similar, the cases differed greatly. In specific terms, the settings I selected for examining user behavior on the basis of technology use displayed considerable differ-

ences in conditions and data corpus: the third essay, with a social-media context, deals with certain differences in user behavior in bulk watching of a television show, while Essay IV, examining site-browsing history in a business-to-business (B2B) context, addresses browsing-device-linked differences in users' browsing behavior.

1.6 The structure of the dissertation

The dissertation is divided into two parts. The details of the background, research framework, and methods in the first portion are followed by description of the important results, discussion of these, and conclusions from the essays, while the second part presents the essays themselves, as itemized below. Having now provided a brief outline of the motivations and objectives for the work and specified the research framework, I will proceed to summarize the four essays, in the next chapter, placing focus primarily on the key results. The final chapter of the first portion of the thesis is dedicated to the overall discussion and conclusions. For specifics, the reader can consult the second part, in which the full essays are presented in the following order:

- I. To Reach the Clouds: Application of Topic Models to the Meta-review on Cloud Computing Literature [41]
- II. Building Theories on Shaky Foundations? The Lack of Falsification in IS Research (In review round 3, *European Journal of Information Systems*)
- III. Analyzing the Ways IT Has Changed our TV Consumption: Binge Watching and Marathon Watching [42]
- IV. System-driven Browsing Outcomes in Consuming B2B Content: A Case of B2B Content Marketing (unpublished)

2. A Synthesizing Summary of the Essays

This chapter is aimed at presenting a brief summary of the individual essays. Figure 2.1 details the study design for these elements of the dissertation with regard to the text data, level of analysis, objective, analysis method, and research scope. The figure also shows where the studies reported in the essays fit within the conceptual research framework presented in the previous chapter. That is, it illustrates the positioning described above: the first two essays are aimed at applying text-mining methods in the analysis of academic literature, whereas the other two are demonstrations of studying system-specific behavioral outcomes. The discussion below presents a summary of each essay in turn. A brief introduction to the study in question is followed by the description of the data and methods. Finally, I outline the main results presented in the essay.

Figure 2.1. The research design applied for the essays featured in the dissertation

2.1 Essay I, To Reach The Clouds: Application of Topic Models to the Meta-review on Cloud Computing Literature

With the rise of digital publication, a massive amount of literature has become accessible. Furthermore, more studies span multiple disciplines these days and, thereby, addressing a broad range of research themes in a single stroke. Analyzing and synthesizing large volumes of literature, particularly with such a broad spectrum of content orientation, is resource-intensive and time-consuming. In addition, manual analysis of a large body of literature is out of the question in most circumstances. Both factors – the multidisciplinary nature and massive volume of digital collections – render it challenging to analyze and understand a given research field’s trends and topic space. Essay I was written in response to this problem, to demonstrate the application of text-mining methods in a systematic literature review that covers a large volume of academic publications.

The context chosen is cloud-computing literature. This area’s explosive growth over the space of a single decade and its multidisciplinary roots point to cloud computing as an ideal case to demonstrate an application for a systematic literature review. In addition, some of those roots lie in IS, rendering the subject more likely to interest the reader in its own right. The main objective for the study presented in the essay was to identify cloud-computing-related topics in publications and, furthermore, analyze the orientation of these topics by parent discipline in order to map this multidisciplinary field. For these purposes, we applied LDA [3], one of the simplest probabilistic models, to pinpoint cloud-computing topics from the academic publications in the cloud computing domain.

Collection of the data: To collect the cloud-computing corpus, we relied on the **Scopus** database, because it provides good coverage of the field, indexing numerous relevant publications. We began by searching for “cloud computing” in abstracts, titles, and keywords. This search yielded 19,177 matches. The remainder of the data-collection stage consisted primarily of filtering that was designed to limit the search result to peer-reviewed publications in the English language. After a series of filtering steps, we removed duplicate and incomplete records, obtaining a final dataset consisting of 13,249 publication records for analysis. The corpus consisted of the title and abstract for each article. Our rationale for using this input instead of complete research articles is based on the assumption that authors communicate the main contribution clearly in their abstracts and titles.

Method: We chose the LDA approach because it offers a simple topic model with strong methodological underpinnings for analyzing text content of this sort. Because the first research objective was to identify the topics represented in the cloud-computing publications, this tool was employed to identify latent topics from the publication corpus. In the context of

a systematic review of literature, we use the word "topics" to refer to latent research themes uncovered from the text corpus. This simple topic model discovers topics by analyzing the co-occurrence of the words across the documents such that these topics when put together are capable of characterizing the hidden structure of the corpus, how the documents fit together as a set. The LDA model is founded on the assumption that the documents constituting any given collection possess shared elements through which a hidden topic structure runs across or binds the documents in that collection. Importantly, even though all the documents have a certain set of topics in common, every individual document displays unique proportions of topics which represent its content. To infer this hidden topic structure, LDA builds on the analysis of word co-occurrence patterns in the document collection.

There are two main components of LDA, the word topic space and document topic space. The hidden topics are iteratively constructed as a distribution over vocabularies given by the word topic space, and documents are constructed as a distribution of these topics. The topic spaces are inferred as posterior probability distributions which consequently produces two core outputs, (i) a matrix of words in which each word's topic-specific probability is determined from co-occurrence across the document collection (the topic-word matrix) and (ii) a matrix wherein each of the documents is connected with the topics represented, where topic membership is expressed in a continuous probability space (the topic-document matrix). The topic-word matrix describes the topic in terms of word-probability space whereas the document-topic matrix represents the text found in a document as a probability mixture for these topics.

Results: Working from the LDA topic model results, we identified 20 topics in the cloud-computing publications. The topics identified could be grouped into applications (education, health-care uses, mobile cloud computing, and practical applications in general), conceptualization (software architecture and conceptualization of the cloud), organizational aspects (organizations' adoption of cloud computing, service-level agreements (SLAs), and service provision), technology and efficiency (Big Data, optimization, performance, and reliability), and usage concerns (access control, security, privacy, and secure search). The higher-level grouping of topics provides insight into the concepts common to the subsidiary topics.

To characterize the cloud-computing corpus in terms of the contributing disciplines, we analyzed the disciplinary orientation of top 20 publications, based on topic probabilities, from each cloud topics. On the basis of the content, a paper could be deemed to belong to one discipline or several. Accordingly, Figure 2.2 depicts the cloud-computing topics' positioning in the space of technically, socially, and socio-technically focused disciplines. In keeping with the technology-driven nature of the field, most of the topics are found within the technical domain, with contributions derived from

mathematics, electrical engineering, and computer science.

Figure 2.2. Topics and disciplines connected with cloud-computing research

Our analysis shows that some topics extended into all three sets of disciplines, with papers on conceptualizations of the cloud, the cloud in education, cloud-technology deployment models, and practical application merging contributions from fields such as law, economics, and business. Similarly, work on mobile cloud computing, optimization of cloud solutions, models for cloud services, and applications in health care exhibited foundations in both the IS field and the technical domain. Such results reveal that ample opportunities exist for further extending cloud-computing research across disciplinary boundaries. After all, most of the cloud-computing-related topics had two contributing sets of disciplines, not three. For

instance, there remains room for studying mobile cloud computing or cloud health-care solutions from a social perspective, and scholarship on the cloud in education might benefit tremendously from technically oriented input.

2.2 Essay II, Building Theories on Shaky Foundations? The Lack of Falsification and Correction of Knowledge in IS Research

In IS studies, manual coding has often been used for classifying and categorizing the text contained in a sample of publications. However, the scope of that approach is limited to small samples, on account of the time required and the demanding nature of the manual efforts involved. Hence, the second essay presents a full-fledged demonstration of solving document classification problems. The work involved developing the codebook and proceeded to train a machine learning algorithm, then scaling from the hand-coded data to a larger document collection and validating the results.

The essay addresses the problem of estimating both the proportion and the impact of falsificationist research in the IS domain. We took the starting position that, while of unquestionable importance in advancing the research field both through critical reflection on theories and methods and via evidence-based correction of these, falsificationist studies do not receive the desired level of attention from IS researchers. The hypothesis was that the information systems as a discipline is inclined more toward research that extends knowledge than to efforts to correct. To avoid ambiguity, we apply the term “knowledge-correcting approach” for falsificationism in any of its various modes and use “knowledge-extending” to refer to other research. To substantiate our claim, we set out to identify those publications with the aim of knowledge-correction.

This essay is similar to the first in its general setting: analysis of academic publications. However, the objective, in this case, was to maximize predictive performance. To reach our goal of estimating the proportion of knowledge-correcting papers to all research publications in leading IS journals, our core method involved a binary document classification approach aimed at maximizing prediction performance. In the absence of training data, we had to identify an appropriate set of data for this use, then train and evaluate the classifiers. Only after that could we identify knowledge-correcting articles in the full dataset, using the classifiers developed, and analyze the papers identified, on the basis of bibliometric information.

Collection of the data: The data-collection process began with a search for all articles published in the leading IS journals, often referred to as the “basket of eight.” Namely, the search was restricted to *MIS Quarterly* (MISQ), *Information Systems Research* (ISR), *Journal of Management Information Systems* (JMIS), *Journal of the Association for Information*

Systems (JAIS), *Information Systems Journal* (ISJ), *European Journal of Information Systems* (EJIS), *Journal of Information Technology* (JIT), and *Journal of Strategic Information Systems* (JSIS) articles. We filtered out the papers with no abstracts, duplicate records, editorials, and letters to the editor. The analysis that followed was applied to these 5,202 articles published in leading IS journals.

Journal	Missing years	Included years	Included papers	Papers/year	% in the dataset
EJIS	1991–1994	1995–2016	671	30.5	12.9%
ISJ	1991–1993	1994–2016	421	18.3	8.1%
ISR	–	1990–2016	752	27.9	14.5%
JAIS	2000–2006	2007–2016	284	28.4	5.5%
JIT	1986	1987–2016	642	21.4	12.3%
JMIS	1984–1986	1987–2015	986	32.9	19.0%
JSIS	–	1991–2016	436	16.8	8.4%
MISQ	1977–1979	1980–2016	1009	27.3	19.4%
Sum	21 years		5201		

Table 2.1. A summary of the data collected

Method: This essay details the operational steps necessary for carrying out the text-classification problem, as outlined above. In the initial stage, we first specified the research approach of IS articles in the dichotomy of knowledge expanding and knowledge correcting. In writings intended to expand knowledge in the field, the researcher undertakes to explain, describe, and add to the existing body of knowledge. In contrast, knowledge-correcting research resonates with falsificationism in its attempts to refine that knowledge, argue for greater clarity, and stimulate debate with intent to correct. Perusing various works, we identified eight distinct categories of knowledge-correcting research, creating a typology that reflects our understanding of falsificationism. The sophisticated falsificationism applied by Imre Lakatos (1922–1974) comes closest to the resulting operational definition of knowledge-correcting research, which encompasses studies that offer attempts at falsification, report on knowledge-correction, call for falsification, and engage in critical discussion. Table 4.1 in Appendix I details the breakdown of falsification studies inclusive to our operational definition of knowledge-correcting research (in the table too, we refer to falsification as “knowledge-correcting research” for the sake of avoiding ambiguity).

Our method required us to train a supervised document classification system, so as to build a classifier that was able to identify knowledge-correcting research. Since we did not have training data to work with, we

had to create one, by means of the codebook we developed. To expedite the training phase, we selected 250 MISQ, EJIS, and EJIS articles and manually classified them. Examining the abstracts for this sample, we identified only 72 as knowledge-correcting. Although we trained SVM models on this sample, the set of training data was so small that neither the accuracy nor the stability of the model proved reliable enough for proceeding further. Accordingly, we screened 250 more potentially knowledge-correcting abstracts in light of our results. In addition, we each independently classified a further 25 abstracts, to evaluate inter-coder reliability. Upon removal of editorial pieces, we obtained the final training dataset, consisting of 519 abstracts, of which 220 had been classed as knowledge-correcting. With the training data created, we began the classification stage, which required preprocessing the text, determining the representation of features in the text, selecting and training the classifier, evaluating and fine-tuning the classifier, and performing the final classification. Performance of a classifier can be improved by carrying out preprocessing to remove the least relevant words and other “noise” from the material. In this step, we removed numbers, stopwords (such as pronouns and articles), rarely occurring words, and words consisting of three or fewer characters. Next, we formed the input-text feature space on the basis of a vector space model with a term-frequency–inverse-document-frequency, or TFIDF [35], weighting system. With this model, input text data are prepared in a matrix format wherein the rows represent the individual training documents and the columns are for the words in the respective documents. The TFIDF weight reflects the importance of the relevant word in a document.

To address our binary classification problem in a manner consistent with the evidence in the literature, we selected support vector machine (SVM) and generalized logistic regression with an added regularization term. Furthermore, for the SVM we selected three distinct models, with linear, radial, and polynomial kernel functions. Each classifier was trained, to learn the optimal parameterization, on a sample of 400 randomly selected documents with class balance. For reliable estimation, we trained all three models with tenfold cross-validation with five repetitions. Once the optimal parameters were discovered, we evaluated the models’ performance for a test dataset that had not been used in the training phase. The main objective in training with cross-validation and in evaluating the models with material external to the training set was to select a model that performs well with documents it has not encountered before.

Results: Table 2.2 presents the performance of the various classifiers for the previously unseen test set. Of the SVM models, the linear kernel-method SVM model outperformed both the radial and the polynomial one, displaying a 70% accuracy rate. With regularized regression, we were able to improve on this performance, achieving 75% accuracy, and this model emerged as the preferred one, outscored the others for most of the criteria.

Having selected this predictive model, we classified all the abstracts in our corpus to estimate the number of knowledge-correcting papers in the IS field. Initially, we found 466 papers (9% of the sample) to be knowledge-correcting in nature. We then manually checked all of the abstracts the model had classified as knowledge correcting, to validate the classification results. In this step, we found 365 falsifying papers in our corpus (7% of all publications).

Metric	SVM			Regularised logistic regression
	Linear Kernel	Radial Kernel	Polynomial Kernel	
Accuracy	0.70	0.47	0.68	0.75
Accuracy Lower	0.61	0.38	0.59	0.66
Accuracy Upper	0.78	0.56	0.76	0.82
Sensitivity	0.85	0.65	0.70	0.75
Specificity	0.67	0.43	0.68	0.75
Precision	0.34	0.19	0.30	0.38
Recall	0.96	0.86	0.92	0.94
F1	0.49	0.29	0.42	0.50
Balanced Accuracy	0.76	0.54	0.69	0.75

Table 2.2. The candidate classifiers’ performance with the test set

Table 2.3 presents the count of knowledge-correcting papers by journal and the articles’ breakdown by type. The table shows that the journals most often printed knowledge-correcting papers focused on falsification of accepted beliefs, exposition of problems, and prescription of improvements. Calls for knowledge-correcting papers was the fewest in number. Furthermore, most of the knowledge-correcting papers found in the sample addressed theory-related issues, followed by methodological research issues. By the number of publications, ISR, MISQ, and EJIS are the leading venues in publishing knowledge-correcting research.

2.3 Essay III, Analyzing the Ways IT Has Changed Our TV Consumption: Binge Watching and Marathon Watching’

Social media not only have transformed how people interact but also have gained a place among major sources of user-generated content. User-generated content shared via social media presents interesting opportunities for studying users’ behavior and preferences. In the absence of television-viewing logs, the study reported on in Essay III exploited the content itself (tweets) to examine the differences between two ways of watching television in bulk-viewing sessions: the binge-viewing and marathon modes.

Journal	Type of correction								Type of contribution		
	Fals'd belief	Prescr cnpr	Prescr impr	Exposed prob	Apost result	Disagr analysis	Debate	Call for fals	Method	Theory	Practice
EJIS	22	7	5	11	4	3	10	2	12	25	14
ISJ	7	1	2	7	3	0	0	0	6	7	5
ISR	31	15	30	12	12	0	8	0	34	40	24
JAIS	8	2	6	12	2	2	7	0	10	15	4
JIT	7	3	3	10	1	3	6	0	8	8	9
JMIS	15	15	5	6	8	0	0	0	11	19	16
JSIS	5	2	1	4	0	1	1	0	2	7	3
MISQ	22	17	17	30	11	1	12	1	33	40	26
Sum	117	62	69	92	41	10	44	3	116	161	101
Total	438*								378*		
% of Total	27%	14%	16%	21%	9%	2%	10%	1%	31%	43%	27%

A paper could be assigned to multiple classes, so the totals given the sum to more than the number of knowledge-correcting papers (438 vs. 365).

Table 2.3. The distribution of knowledge-correcting papers by publication

Watching more than one episode of a TV show in a single session is often termed "binge watching." *The Oxford dictionary* defines this as the practice of watching multiple episodes of a given TV series in immediate succession. Technological advances have enabled audiences to engage in this by such means as Internet-based platforms (e.g., Netflix) and "marathons" shown on cable television. The differences in enabling technology between these two alternatives prompted us to investigate associated differences that may emerge in viewing patterns. In Essay III, we examine user interaction with the two sets of technologies in these terms.

Considering the context of back-to-back consumption of episodes, we sought to understand system-specific outcomes connected with scheduled television and with online streaming services. Firstly, we established a distinction between the aforementioned modes of watching multiple episodes of a television program in succession, **binge watching** and **marathon watching**. The distinction can be established in terms of the differences in user autonomy afforded by the underlying systems. Driven by online streaming services, binge watching offers greater user autonomy: one can more readily choose what to watch and when to watch it. Being restricted to what is supplied by one's cable-television provider, marathon watching confers relatively limited autonomy: the user's decision is a binary one, whether to watch a given TV-show marathon or not. Using tweets collected over a span of three months, our study analyzed the impact of the underlying systems in multi-episode viewing of television shows in terms of time- and content-specific outcomes.

Collection of the data: The study was conducted with the aforementioned dataset, tweets related to multi-episode viewing. Since we lacked access to logs of television-viewing, we identified **Twitter**, one of today’s most popular social media platforms, as an alternative source of data, where the data items are users’ tweets about the viewing. The data were collected via an open query for tweets related to binge watching and marathon watching between October 30, 2014, and February 20, 2015 (covering 113 days). Using 13 keywords related to marathon and binge watching, we downloaded 661,825 tweets to a NoSQL database (using MongoDB). The keywords and search results are tabulated in table 4.2 in Appendix II. We filtered out tweets that were duplicates (promotional tweets, tweets returned for more than one keyword, and repeated posts) before moving on to the analysis.

Method: It was clear from the nature of tweet text that analyzing system-specific outcomes in multi-episode consumption clearly involved an uphill task – processing and identifying relevant tweets would not be easy. Furthermore, we aimed at achieving finer granularity in explicitly identifying both the mode of watching and the TV show in question; therefore, our approach had to extend far beyond mere counting of hashtag references. We found that the text’s informal nature and poor grammatical structure created particularly challenging obstacles.

Tweets are short pieces of text (up to 140 characters) that use free-form writing with intentional and unintentional spelling errors, along with compound words that may feature concatenation without space characters, colloquialisms, and abbreviations. In an additional hurdle, the keywords “binge” and “marathon” might be used for several other activities too, such as (for the former) eating/sleeping or (for the latter) long-distance running or watching movies back to back, not to mention that these words may be used in conjunction with various hashtags, a Keyword representing tweet content, and compound forms. The resulting complexity leads to tremendous variations in the keyword use within the tweet dataset. For instance, we found more than 500 distinct word compounds for “binge” and upwards of 600 for “marathon.” Accordingly, identifying relevant bingeing- and marathon-related tweets posed a major methodological challenge.

To overcome the linguistic complexities evident in the tweets, we defined a relevant tweet to be one containing a “marathon” or “binge” keyword and the name of a television show. The first step, finding tweets featuring the keywords, was entrusted to keyword-based search after “binge” and “marathon” were distinguished from all other forms. The second task, picking out references to a television show’s title, involved similar linguistic complexities arising from compound words, abbreviations, and embedding in long hashtags (for instance, the program *House of Cards* might be referred to via “houseofcards,” “hoc,” “hocs,” “cardshouse,” “underwoodforpresident,” “ilovehouseofcards,” “hocsbinge,” etc.). Therefore,

reliably identifying the relevant television shows' titles required extensive standardization. We prepared a mapping from more than 2,450 program titles, obtained from **IMDb**, to corresponding terms used in the tweets. The list of title-to-term mappings was prepared through manual analysis of frequent words in the tweets. Once relevant tweets could be identified, we narrowed our focus to television shows that were referred to at least 100 times in the dataset. Our final data included 186 television shows. Finally, for each of the 186, we collected particular attributes such as the program's genre, the year it began airing, its provider(s), number of seasons, and number of episodes, using **IMDb**.

Our analysis addressed two important dimensions of the multi-episode viewing outcomes: content and time. For the latter, we took the simple approach of analyzing the frequency of tweets referring to binge and marathon viewing, by day of the week. For content-driven outcomes, we simply modeled tweet counts as a function of television-show-specific attributes using likelihood estimation.

Results: Our investigation began with examining the individual TV shows' relationship to the "binge" and "marathon" keywords and to the systems that offer the respective services. For manageability, we selected the 20 shows featured most often in the tweets, the two keywords, and the seven main show-providers for our calculations of term co-occurrence strength. Figure 2.3 shows the strength of association between terms in our data, where the thickness of the connecting arrows is proportional to the strength of the association. For clarity of visualization, only co-occurrence associations above a 5% threshold are shown. Since the varying frequencies of the individual terms render co-occurrence asymmetric, the directionality of each association is indicated by the tip of the arrow. Finally, curved arrows are used to highlight co-occurrence associations that are stronger than 5% in both directions.

We can see clearly from Figure 2.3 that providers such as AMC, ABC, and FOX are closer to marathon territory whereas Netflix is closer to the binge domain. Similarly, shows such as *Awkward*, *Law & Order*, and *The Twilight Zone* are more marathon-oriented. On the other hand, *Dexter*, *House of Cards*, and *Orange Is the New Black* are among the programs that are nearer the binge domain. Users showed a preference for using the word "watch" in connection with marathon mode and "view" for binge watching. From the term-network analysis, we concluded that the marathon and binge modes clearly represent two distinct phenomena in watching of TV shows, driven by different systems.

In the next stage of analysis, we attempted to gain an understanding of content-specific outcomes as manifestations of multi-episode binges and marathon viewing. To describe the various attributes of television content, we added some of the aforementioned program-specific variables to the model: genre, IMDb rating, year of the first broadcast, number of

Figure 2.3. The binge network

seasons, episode count, and the first year of broadcast. Finally, we created two separate, mode-specific models, using estimate-based modeling to characterize the relationship between various content dimensions and the frequency of relevant tweets referring to binge watching and marathon watching. This analysis was confined to TV shows featured in more than 100 distinct tweets in our dataset.

Figures 2.4 and 2.5 graphically depicts the results from the two regression model runs – for binge watching and marathons, respectively. In the figure, the coefficients are presented in terms of Bayesian credible intervals at 95% certainty. Rather than judge by statistical significance, we find it preferable to consider the range of values associated with the degree of certainty for the relevant parameter. If the region of credibility lies on either side of the zero line, one can interpret the effect of the element in question as being either positive or negative, accordingly, while a credible interval at 0 indicates that no evidence of an effect is present.

Figure 2.4 points to TV shows with higher ratings and in the drama genre as garnering considerable interest among binge watchers, while binge watchers showed a negative inclination toward genres such as reality shows, family-oriented programming, game shows, history-based programs,

Figure 2.4. The binge model

and documentaries. Figure 2.4 highlights the following patterns among marathon watchers: these users gravitated toward lower-rated content and such genres as action, romance, and thrillers. Marathon watchers also favored shows that were still being produced.

Figure 2.5. The marathon model

We can summarize the study as yielding a characterization of two system-specific manifestations of watching TV shows in bulk. Not only do these phenomena, watching marathons of TV shows and binge watching, differ in the technical mechanisms behind them, but also we uncovered from our data substantial differences along the time and content dimensions.

2.4 Essay IV, System-driven Browsing Outcomes in Consuming B2B Content: A Case of B2B Content Marketing

Content marketing is a vital tool in the promotion and sales of B2B products. With a continuing shift from personal meetings and sales events toward digital marketing of content [10], sellers face an urgent need to

understand how users interact with digital content and consume it. When accessing this content, users rely on either hand-held devices, such as tablets and cellular phones, or personal computers. Recent developments suggest that hand-held devices are coming to dominate the landscape, favored over PCs as users' primary device for accessing the Internet [11, 36]. Further, since these two sets of browsing devices differ in characteristics, users are more than likely to exhibit differing usage accordingly. The importance of understanding device-specific browsing preferences of users can be critical, especially in B2B marketing, where success is largely driven by the effectiveness of content marketing.

The fourth essay reports on a study undertaken in this context, with the aim of distinguishing between the content-consumption pattern associated with hand-held devices and that seen with personal computers (PCs). Differences in flexibility and interface have given rise to two distinct approaches in the design of the sets of systems for browsing information on the Internet. Since the objective was to explore device-specific, browsing-system-driven patterns of content consumption, the scope of the fourth essay was restricted to description and analysis. This work considered both sellers' own channels and the content of promotional channels, accessed via a portal. The two main data components were content extracted from the Web sites and logs of users' visits to those sites.

Collection of the data: As noted above, there were two types of data sources for this essay, site content and site-browsing data. The browsing data were contributed by a leading B2B content marketer in the Nordic region. According to the marketer, the data originated from visits to its clients' Web sites and from use of promotional channels displaying paid client content. Whenever a user with a registered account visited any of the touch points, it triggered the data collection system.

The initial dataset covered content from more than three million Web sites, which together had accumulated in excess of 170 million browsing sessions. Two-thirds of the Web sites were the sellers' own channels. The dataset, from a one-year period beginning in September 2017, covered 74 separate clients and about 40,000 account-holding companies, with 13 million unique cookies.

Method: I developed a three-step approach for analyzing this large volume of Web-content data: preprocessing and cleaning, development of a suitable estimation-based content model, and visual analysis of a two-dimensional representation of users' content profile. For the model, I chose to represent the content level by applying a popular neural-network-based method for calculating text embedding, **paragraph vector**, also known as **doc2vec** [25]. This method is better equipped to capture semantic similarities between words and documents, and it also allows evaluating the two in the same content space. However, the model generated via doc2vec is still high-dimensional, and content vectors do not lend themselves to

easy interpretation. This is why I converted the doc2vec output to two-dimensional embedding. For this purpose, I chose t-Distributed Stochastic Neighbor Embedding (t-SNE) [43], an award-winning dimensionality reduction technique. Here, I chose to interpret content space in the dense regions as opposed to a two-dimensional grid space from traditional clustering solution for two important reasons. Firstly, I wanted to interpret the content space in its natural shape and structure, without limiting it to groups in a particular number of clusters, determined *a priori*. Secondly, this gives the researcher or analyst the flexibility to focus on the dense regions, homing in on the content space for which there is higher user density.

I began with filtering designed to produce an appropriate dataset for analysis in the experiment. I limited the Web-content data in the sample to English-language text and removed the browsing activity that resulted from misclicks, browsing sessions that last less than two seconds, and the sessions reflecting idle users (browsing sessions exceeding 30 minutes), as identified by the content marketer. In the next step, I extracted text tokens from the Web content. Several text-cleaning tasks were involved in this, among them tokenizing the text into terms on the basis of whitespace, removing usernames, filtering out hyperlinks, removing numbers and stopwords, and lemmatizing the tokens. After generating a list of the text tokens, I removed the Web-content entities with fewer than 15 or more than 10,000 text tokens so as to meet the requirements for the content model. In addition, I detected cases in which certain segments of text, by being repeated multiple times in a document, distorted the picture of the body of content. Such issues are difficult to spot in large datasets, on account of sheer size. To deal with such repetitive content, I applied a rule of thumb that removed Web-content entities with a unique-tokens-to-total-tokens ratio above 3.

After the filtering and cleaning, I generated three distinct content-model variants, using the GENSIM toolkit [30], implemented in Python. Within doc2vec, I estimated three variants of models; distributed bag of words (DBOW), DBOW with word vectors, and a distributed memory method. Of these models, DBOW with word vectors displayed the best performance in terms of similar words when trained for 100 epochs. Since the contents differ considerably between sellers' channels and promotional channels, I trained two separate content models accordingly. The next step involved constructing a content profile for the users by aggregating browsing records by user ID, device type, and channel type. Finally, I translated the user profile into a two-dimensional content space by using t-SNE.

Results: In keeping with the approach employed for modeling, I present the results for content-browsing in the two channel sets separately. Figure 2.6 shows the content profile for users browsing promotional channels with hand-held devices and with PCs. Since the content space is identical

between the two device types, the content profiles presented are comparable. The figure reveals that distinctive browsing patterns do emerge as an outcome of device-specific browsing. Furthermore, while users are scattered over each of the content spaces, those browsing on PCs display a slightly denser grouping.

Figure 2.6. Profiles for user-viewed content from promotional channels with a) hand-held devices and b) personal computers

To interpret the content patches presented above, I manually selected three content patches on the basis of grid space, t-SNE-generated x and y coordinates. The coordinates in t-SNE generated space are a lower-dimensionality representation of the original high-dimensionality content space. To facilitate interpretation, I described the content patches on the basis of the words close to the center of the content patches; Table 2.4 characterizes the content patches in Figure 2.6 accordingly. The table provides further confirmation that the patterns in the content space differ between hand-held-device browsing and PC-based browsing. The users browsing with hand-held devices showed interest in news, music, and airline products (patch 1); places of various kinds (patch 2); and social media and video entertainment (patch 3). In contrast, users working at PCs preferred content related to news, TV shows, and manufacturers (patch 1); music and various products (patch 2); and various people, places, and companies (patch 3).

Mobile content Browsing				Computer content Browsing			
Patch Id	t-SNE X,Y	Ten Words close to the patch center	Content Description	Patch Id	t-SNE X,Y	Ten Words close to the patch center	Content Description
Patch 1	(-10,-3) (5,12)	usatodayftw, coprosk, abduktio, onbekend, airlines product1, airlines product 2, neuralhub, sazanberk, airlines product 3, spaxxor, mobile phone dealers	News, Music, Airlines products	Patch 1	(-8,3) (-8,3)	kelly, tackitt, baptist, wdiv, kvia, holcombe, metal manufacturer, parkland, ksar, woicinski	News, TV shows, Manufacturing
Patch 2	(-3,2) (15,22)	paiha, kupu, visy, lainio, ketut, jäske, korchagin, liti, näppi, runsala	Places	Patch 2	(0,8) (5,12)	coprosk, usatodayftw, abduktio, airlines product 2, neuralhub, spaxxor, airlines product 2, airlines product 3, serbian singer, mobile phone dealers	Music and Products
Patch 3	(-3,8) (-10,2)	xgcmzgbpbe, jaiaboiz, bicane, processing plant, kiefki, brockport, puneti, hanson, jal	Social media, Entertainment	Patch 3	(8,13) (8,13)	korchagin, paiha, lippold, kupu, taxi company location, collien,näppi, manufacturing 1, swierc, construction company	Places and Persons, Companies

Table 2.4. Content-browsing patch description for promotional channels for a) hand-held devices and b) personal computers

Then, I turned to the interest expressed in content in sellers' own channels. Figure 2.7 depicts the browsing patterns for this content. Even though the shapes in the two panes show some similarity in structure, the patterns in the content space differ device-specifically. In general, both sets of users are fairly scattered, apart from those in a large dense region at the center; however, PC-users cluster more densely in the central region, and there are significantly more content points in the right-hand pane. That is, more users accessed this class of content via PCs than via hand-held devices. This indicates that the users rely heavily on PCs when accessing information directly from a seller's channel.

Figure 2.7. Profiles for the content viewed from sellers' channels, for a) hand-held devices and b) personal computers

In this analysis too, I interpreted the content space by using the grid method, wherein I manually selected the dense portions of the space. Table 2.5 describes the three selected content patches for both browsing modes: viewing content on PCs and via hand-held devices. Of the users browsing with hand-held technology, the largest group of users, found in patch 1, showed interest in content related to marketing, logistics, and energy. In addition, these users viewed content related to various products, automation, and software solutions (patch 2) and to foreign companies (patch 3), mostly ones offering outsourcing services.

As for PC-users, a large group of users, in patch 1, showed interest in airline-related products and solutions. Users in patches 2 and 3, while close to content patch 1, still demonstrated differences in interests: those in patch 2 expressed interest primarily in construction materials and services, whereas users in content patch 3 showed an interest in content related to training and education.

This essay revealed that the types of B2B service content browsed differed significantly with the browsing device: hand-held devices vs. PCs. The findings highlight the significance of analyzing and understanding users' content needs in consideration of the browsing device.

Mobile content Browsing				Computer content Browsing			
Patch Id	t-SNE X,Y	Ten Words close to the patch center	Content Description	Patch Id	t-SNE X,Y	Ten Words close to the patch center	Content Description
Patch 1	(-5,-2) (5,8)	thermal, communication, marketing, energy, installment, cargo company, research, software solution, lead, consignment	Logistics, energy, marketing	Patch 1	(-3,1) (-4,4)	orderlistsq, offerprices, serviceprices, airlineprofilers, farerulesrq, industrial control and automation company, itinreshops, piston pump, baggagelistrs, farerulesrs	Airlines products
Patch 2	(3,5) (-5,5)	coating liquid, pipe fitting products, refrigeration oil, electric automation company, softwareaccess, pressure monitor and sensor, software and service, printing and imaging product, sales and marketing firm, industrial I/O devices, radio control vechicles,	Products, amotmation and softwares	Patch 2	(1,3) (3,4)	steel producer 1, construction material supplier, office cleaning service provider, steel producer 2, fluid power industry, procaal, flame free refrigerant fittings, filter cartiridge construction, zero air generator, tube fitting products	Construction materials and services
Patch 3	(3,5) (-1,0)	submittal, Indian project management company, Candaian architectural manufacturer, Iranian IT company, Iranian networking company	Outsourcing services	Patch 3	(1,4) (-3,-1)	student, preceptorship, practicum, personbiology, educationlife, feespart, costspayment, universityyou, capayment, selinux	Training and Education

Table 2.5. Content patch description for users browsing sellers' own channels, for a) hand-held devices and b) personal computers

3. Discussion and Conclusions

This dissertation was motivated by the fact that, while the course is set to rely more and more on the ability to gain insight from unstructured data such as text, IS scholars are still far from fully exploiting the opportunities that remain locked within this challenging yet rewarding form of data. While fields such as computer science and biomedicine are starting to reap the potential of text-mining research and working with large-scale text datasets, the IS field displays a pattern seen also in the social sciences [34]: at best, haphazard application of the more advanced methods now emerging. To the best of my knowledge, this dissertation is one of the first attempts to lay out a conceptual research framework that addresses these shortcomings. The proposed framework enriches the understanding of text-mining methods and their application by conceptualizing text-mining via the dimensions of the level of analysis and the research objectives. While it aids users in assessing text-mining methods and applications, coming to a better understanding of the methods, and designing text-mining research accordingly, the framework is still conceptual in nature and requires further refinement.

Alongside that framework, the dissertation contributes four demonstrations of text-mining applications to IS research. Each essay in the dissertation demonstrates a particular research approach that can be explained along the dimensions in the proposed framework. The first addresses the aim of characterizing the research topics in cloud-computing literature. The discovered research topics still require interpretation of such layered material clearly demanded methods affording latent-level analysis. Therefore, I chose a simple topic model, LDA, for its probabilistic modeling of textual data with regard to multi-topic membership. In the study detailed in the second essay, the objective was to obtain the best predictive performance in classifying abstracts, so I relied on vector-level text analysis. These methods are well attuned to goals of optimizing prediction accuracy. The research in the third essay necessitated extracting variables from a noisy set of social-media data. The research in question required word-level analysis, using dictionary-based substitution, to extract

variables that were then used to explain the research phenomenon (preferences expressed in relation to binge viewing and marathon watching). Finally, the fourth essay too demanded careful consideration of methods. To address the objective of describing browsing-device-driven differences in content-consumption behavior of B2B users, I applied vector-level analysis, evaluating content similarity to reveal the relevant patterns and differences. For this essay, vectors were constructed to capture semantic similarities, evaluated by means of similarity scores.

The essays together demonstrate the space of research problems amenable to text-mining-based methods and selection of suitable approaches in line with the conceptual framework. Additionally, each explores a particular problem, uniquely addresses the research question, and makes its respective contributions. In detailing the study aimed at describing the landscape of topics in cloud-computing research, the first essay illustrates a text-mining-based approach to conducting a thematic review of a large body of literature. Latent Dirichlet allocation, the method used in this essay, offers the ability to analyze a large volume of literature efficiently and enables modeling of academic publications that inherit multiple topics and themes. The paper serves as useful guidance for the researcher seeking to conduct reviews of a domain that extends across boundaries between traditional disciplines. The second essay, in turn, describes the entire process of document classification, inclusive of building a set of training data from scratch. In this paper, the issues related to sampling, development of a code book, validation of the code book, the process of creating a training dataset, classification, and post-classification analysis are discussed in great detail. With its in-depth description of the full experiment procedure, Essay II serves as a solid reference for someone seeking to classify documents in the absence of a ready-to-use set of training data. Further, an approach similar to this can be exploited to generalize from a small sample of manually classified documents to a larger corpus.

The third essay, set in the context of user-generated content, demonstrates the process of extracting variables from bodies of unstructured textual data that are combined and modeled by means of structured numerical data. This essay highlights the issues that arise in consequence of the poorly structured nature of user-generated content and presents an approach of creating a dictionary to standardize the keywords from such challenging text data. Finally, the fourth essay addresses the objective of describing the Web-site content consumed by users of B2B portals and promotional channels. Because the target extended further, to demonstrate the differences in content between types of browsing device, the essay presents an approach not employed for the other three studies: one based on text analysis carried out via vector representation.

3.1 Implications of the research

In the domain of applied text-mining, this dissertation points to three important implications for researchers and practitioners alike. These implications are related primarily to the varying nature of the text data, the roles of the human and the machine in text-mining and automated analysis, and the evolution in research practices that is in progress in response to the availability of vast quantities of data.

3.1.1 The diversity of text: Not all text is the same

In general, when compared to numerical data, text data lack a proper structure. Accordingly, the term "unstructured data" often gets used for this material. Furthermore, bodies of text data exhibit substantial variations that arise from the context, culture, purpose of writing, and mode of writing [40]; text varies tremendously in nature, depending on the source generating it. One aspect of this can be viewed as a continuum. The academic text represents one extreme, where texts are written in formal structure (including formal grammatical structure), are intended for a sophisticated audience, and present a clearly intended/articulated message. At the other extreme lies user-generated text from social media, displaying weak grammatical structure, inevitable spelling errors, incomplete sentences, and online jargon that is constantly evolving. Between these extremes are text data from news articles, blogs, Web pages, discussion fora, customer feedback, and numerous other sources. The text-data entities generated by these sources vary in length, degree of formality, grammatical form, style of writing, and extent of vocabulary, to name only a few elements. While it is abundantly clear that not all text is the same, text data originating from the same sources possess similarities, while data from different sources tend to exhibit greater differences. Hence, the nature of text data can be roughly pinned to the source of the text.

This dissertation has addressed several types of textual data, from academic sources, commercial Web sites, and users of Twitter. Together, the essays demonstrate well that the nature of the text data is an important consideration, for it dictates the preprocessing and other handling required before the analysis phase can commence. In the first two studies, text from academic venues was processed in only a few steps, which involved stop-word removal and stemming. For the third essay, with a dataset composed of tweets, a manually crafted dictionary was required, for standardizing variations in terms before we could count them. Such online content, user-generated content in particular, is ambiguous and exhibits wide variations in term use. Therefore, researchers and analysts working with this type of data are often required to inject manual expertise to account for such challenges [2]. The material for the fourth essay was based on the Web

content ranging from material on B2B Web sites to the content of various promotional channels' content. Hence, its processing involved removal of usernames and embedded links, application of hefty lists of stopwords, and lemmatized tokens. Further, whenever one collects huge amounts of Web content, glitches are inevitable, on account of the Web's complexity and structural variations. The fourth essay presents guidance to an approach that addresses some of these factors by considering the ratio of unique terms to total terms for identification of poorly extracted content.

3.1.2 Human input as a fundamental element in text-mining applications

Text in its raw form is complex, is unstructured, and embodies high-dimensionality features that necessitate transposition to a simpler, low-dimension feature space before being fed in as input to the machine or empirical analysis. Text-mining methods automate the process of conversion from unstructured text into a suitable numerical structure by alleviating the need for intensive human input. Accordingly, text-mining methods offer significantly faster, more systematic, and more transparent ways to communicate methods and claims than do traditional qualitative techniques for dealing with text [6]. However, the goal with text-mining methods is to complement the qualitative analysis rather than replace it [6]. The value of human input to text-mining research in terms of expertise and knowledge must not be underestimated.

Only when the results from text-mining are interpreted with the aid of human experts with domain knowledge, the output can be presented in a readable, understandable, and usable form. Furthermore, creating resources for text-mining, such as labels, and categorizing data when no training data are available requires manual coding procedure. Creation of sentiment and other forms of dictionaries, and domain-specific resources all require substantial inputs from human experts. Finally, validating the results after completing the text analysis is of extreme importance, for guaranteeing optimal, valid results in text-mining applications [19]. This too demands human expertise.

The component essays illustrate incorporating human expertise into study designs in one form or another. Thereby, they all acknowledge the importance of human experts as a valuable input to text-mining research. Specifically, determining the right number of topics and interpreting the topics, for qualitative evaluation of the topic-model results, in the first essay utilized expert judgment. The second essay required human expertise in creating the corpus of training data and validating the prediction results. In the third essay, creating the dictionary for word substitution and standardization of words in the tweets substantial manual input. Finally, the content patches revealed in the fourth essay were highlighted by

interpretation – a human examined the dense regions in the content space.

Thus, the dissertation highlights the importance of human expertise in text-mining research. A good application of text-mining methods is a far cry from being fully automated. It still relies on some form of human expertise. Because a good text-mining application requires human expertise in building the required resources, interpreting the results, and validating them, the optimal approach to any text-mining application today involves a research design that incorporates both automated text analysis and introduction of human expertise at various levels [19].

3.1.3 Evolution of research designs and text-mining

In recent years, quantities of data have been expanding at an exponential pace, with the volume of unstructured data dwarfing that of numeric data. According to the IDC (International Data Corporation), an EMC (Egan, Marino, Curly) -backed report has estimated that by 2020 the digital universe will have grown to 40,000 exabytes, or 40 trillion gigabytes, from the 130 exabytes of in 2005 [17]. Given that unstructured data such as text, audio, and video content accounts for 95% of this [16], the key for tapping the digital world's potential lies in said data. In the business domain, the balance is tilted in even greater favor of textual data. According to a report by Merrill Lynch, more than 85% of all business information is found in various forms of unstructured data, such as e-mail messages, memos, notes from call centers and support operations, news stories, user fora, chat records, official reports, letters, survey forms, white papers, marketing material, pieces of research, presentations, and Web pages [4].

As the face of the digital sphere changes, research fields too are undergoing significant reshaping as massive quantities of data, with a huge variety of structure, become available. This massive treasure trove presents opportunities to carry out studies that were unimaginable a decade ago, but it simultaneously requires a different approach to data-collection, analysis, and research design. For instance, researchers can obtain details of users' networks, activities, opinions, etc. from platforms such as social media, blogs, feedback fora, and review sites. This entails applying an approach vastly different from the traditional collection of data. The researcher can proactively collect material and filter it, with the choices made in the data-generation process playing a key role in the relevant information obtained. The digital world serves as the setting for a vast natural experiment, from which the researcher mines data, observes patterns, and analyzes the data generated in natural setup. In this large-scale experimental environment, text-mining methods are exceedingly likely to take a more central position. After all, these methods constitute a versatile suite of tools capable of addressing many of the challenges in processing and analyzing unstructured data. For instance, analysis of audio and video

data can benefit from, among other techniques, indexing and analysis of corresponding soundtrack transcripts [16].

Reflecting such developments in tools and opportunities, this dissertation has stepped far beyond the realm of traditional qualitative text analysis, with essays that grapple with considerably larger datasets, extending to millions of items. Furthermore, the research in the dissertation project used unstructured text data in combination with structured data in various ways. For the first two studies, citation counts were considered alongside the abstracts and titles for evaluation of impact across the machine-learned feature outputs. Similarly, the third essay utilized the TV-show-specific details collected from IMDb in conjunction with the frequency of program mentions computed from the tweet corpus. In the fourth essay, I obtained the content-consumption profiles by assessing Web-site usage data jointly with the content of the pages visited. With large bodies of data growing more and more prevalent, this dissertation also contributes a timely effort to demonstrate well-designed studies that make use of large-scale textual data over a broad spectrum of research applications. In addition, it adds to scholarly reflections on evolving research designs.

3.2 Conclusions

Motivated by the IS field's snail-like response to the future before us, in which the ability to draw insight from text and other unstructured data will be vital, I have attempted to showcase some potential applications of text-mining-based research – the field can benefit greatly from this challenging yet hugely promising form of data, just as computer science, biomedicine, and other disciplines have begun to reap its rewards. To this end, I have laid out a conceptual framework of text-mining research that aids in choosing and evaluating study designs, on the basis of two dimensions: research objectives and levels of analysis. Proceeding from this framework, I presented the four essays, which represent research cases with varying combinations of analysis levels, types of textual data, and research objectives. In each case, the research questions specified in the respective essay – mainly within the context of analysis of literature and system-driven behavioral outcomes – were answered successfully.

Of these two main application areas, the dissertation has addressed the first, use of text-mining for large bodies of publication data, by demonstrating tools and techniques that are aimed at creating a better understanding of the relevant research domain. Thus far, most of the information systems researchers have been relying on traditional manual coding and categorization of a carefully selected handful of publications when conducting systematic reviews of the literature. However, text-mining tools such as topic models enable researchers to scale their work up to larger and wider

areas for the systematic review. With the first essay, we illustrated the use of topic models to describe publications on cloud computing, and Essay II describes the process of upscaling from qualitative text analysis, applied for building a set of manually coded training data, to a larger dataset, by means of text-mining tools. In the work on system-specific usage behavior, in turn, the third essay illustrated one approach to overcoming the challenges that accompany the poorly structured user-generated text, and the fourth essay brought together a massive Web-content dataset and usage data to explain the content-consumption behavior under study.

The three central implications for future attempts to apply text-mining methods are worth reiterating here. Firstly, the four studies in the dissertation project dealt with different types of textual data. Together, the essays highlight the need for considering the nature of text data (in general and with specific regard to the task at hand) in text-mining research and applications. Textual data from different sources exhibit differing properties. Also, the nature of the text-form data often determines the efforts required in preprocessing and sometimes influences the methodological considerations necessary. Secondly, the essays pinpoint the importance of human input to various aspects of text-mining applications. More often than not, the concept of text-mining is taken to be synonymous with fully automated text-analysis processes. However, at various stages in a well-designed study, text-mining research still requires human expertise and judgment. Thirdly, the various research design of the component essay also shows the evolving nature of future research where studies are designed using a variety of large-scaled data from a digital setup where data are generated without the researcher's intervention. Finally, the dissertation project, with each of its component studies involving unique considerations and conditions, illustrates that there is no "silver bullet" in text-mining research: the individual combinations of analysis level, research objectives, and type of text data imply a need for a case-specific approach.

In an age dominated by digital content, this dissertation is a timely attempt to demonstrate the application of tools and techniques that are certain to grow in importance. As the digital data repository grows, future research is almost certain to be affected, in how studies get designed, data collected, and methods applied. With the exponential growth of unstructured data in forms such as text, researchers must adapt decisively, seizing the opportunities that bigger data corpora hold. This entails a pressing need for researchers and analysts to equip themselves with tools and techniques suited to collecting, organizing, and synthesizing large volumes of textual data. Accordingly, this dissertation has presented illustrative examples wherein data are extracted from various digital platforms and subjected to analysis that employs text-mining methods. It is hoped that the contributions found in the dissertation will help carry the IS field forward. The conceptual framework for text-mining research

could assist researchers who seek to improve their understanding of text-mining applications. With the aid of this framework, researchers may become better able to consider their work along the dimensions of intended objectives and level of analysis, selecting appropriate research methods accordingly. Furthermore, the four essays add to the scholarly work on the respective research questions in their own right while also providing detailed guidance to carrying out studies in diverse research settings.

References

- [1] Ahmed Abbasi and Hsinchun Chen. Cybergate: a design framework and system for text analysis of computer-mediated communication. *Management Information Systems Quarterly*, pages 811–837, 2008.
- [2] Lawrence Ampofo, Simon Collister, Ben O’Loughlin, Andrew Chadwick, PJ Halfpenny, and PJ Procter. Text mining and social media: When quantitative meets qualitative and software meets people. *Innovations in Digital Research Methods. Thousand Oaks: Sage Publications Inc*, pages 161–192, 2015.
- [3] David M Blei, Andrew Y Ng, and Michael I Jordan. Latent dirichlet allocation. *Journal of machine Learning research*, 3(Jan):993–1022, 2003.
- [4] Robert Blumberg and Shaku Atre. The problem with unstructured data. *Dm Review*, 13(42-49):62, 2003.
- [5] Robert J Boncella. Competitive intelligence and the web. *Communications of the Association for Information Systems*, 12(1):21, 2003.
- [6] Parijat Chakrabarti and Margaret Frye. A mixed-methods framework for analyzing text data: Integrating computational techniques with qualitative methods in demography. *Demographic Research*, 37:1351–1382, 2017.
- [7] Michael Chau and Jennifer Xu. Business intelligence in blogs: Understanding consumer interactions and communities. *Management Information Systems Quarterly*, pages 1189–1216, 2012.
- [8] Hsinchun Chen, Roger HL Chiang, and Veda C Storey. Business intelligence and analytics: from big data to big impact. *Management Information Systems Quarterly*, pages 1165–1188, 2012.
- [9] Jiesi Cheng, Aaron Sun, Daning Hu, and Daniel Zeng. An information diffusion-based recommendation framework for micro-blogging. *Journal of the Association for Information Systems*, 12(7):463–486, 2011.
- [10] Angevine Christopher, Lun Plotkin Candace, and Jennifer Stanley. When b2b buyers want to go digital and when they dont, 2017. <https://www.mckinsey.com/business-functions/digital-mckinsey/our-insights/when-b2b-buyers-want-to-go-digital-and-when-they-dont>, last accessed on: 2018-06-14.
- [11] Etherington Darrell. Mobile web browsing overtakes desktop for the first time, 2016-11-01. <https://techcrunch.com/2016/11/01/mobile-internet-use-passes-desktop-for-the-first-time-study-finds/?guccounter=1>, last accessed on: 2018-08-10.

- [12] Stefan Debortoli, Oliver Müller, Iris A Junglas, and Jan vom Brocke. Text mining for information systems researchers: an annotated topic modeling tutorial. *Communications of the Association for Information Systems*, 39:7, 2016.
- [13] Xuefei Nancy Deng, Yibai Li, and Robert D Galliers. Business analytics education: A latent semantic analysis of skills, knowledge and abilities required for business versus non-business graduates. In *Proceedings of International's Conference on Information Systems*. Association for Information Systems, 2016.
- [14] Weiguo Fan, Linda Wallace, Stephanie Rich, and Zhongju Zhang. Tapping the power of text mining. *Communications of the ACM*, 49(9):76–82, 2006.
- [15] Ronen Feldman and Ido Dagan. Knowledge discovery in textual databases (kdt). In *KDD*, volume 95, pages 112–117, 1995.
- [16] Amir Gandomi and Murtaza Haider. Beyond the hype: Big data concepts, methods, and analytics. *International Journal of Information Management*, 35(2):137–144, 2015.
- [17] John Gantz and David Reinsel. The digital universe in 2020: Big data, bigger digital shadows, and biggest growth in the far east. *IDC iView: IDC Analyze the future*, 2007(2012):1–16, 2012.
- [18] Shirley Gregor. The nature of theory in information systems. *Management Information Systems Quarterly*, pages 611–642, 2006.
- [19] Justin Grimm and Brandon M Stewart. Text as data: The promise and pitfalls of automatic content analysis methods for political texts. *Political analysis*, 21(3):267–297, 2013.
- [20] Michael Gross. The evolution of writing. *Current Biology*, 22(23):R981–R984, 2012.
- [21] Xunhua Guo, Qiang Wei, Guoqing Chen, Jin Zhang, and Dandan Qiao. Extracting representative information on intra-organizational blogging platforms. *Management Information Systems Quarterly*, 41(4):1105–1127, 2017.
- [22] Marti Hearst. What is text mining. *SIMS, UC Berkeley*, 2003.
- [23] Marta Indulska, Dirk S Hovorka, and Jan Recker. Quantitative approaches to content analysis: identifying conceptual drift across publication outlets. *European Journal of Information Systems*, 21(1):49–69, 2012.
- [24] William L Kuechler and Vijay Vaishnavi. So, talk to me: The effect of explicit goals on the comprehension of business process narratives. *Management Information Systems Quarterly*, pages 961–979, 2006.
- [25] Quoc Le and Tomas Mikolov. Distributed representations of sentences and documents. In *International Conference on Machine Learning*, pages 1188–1196, 2014.
- [26] Hans Peter Luhn. A business intelligence system. *IBM Journal of Research and Development*, 2(4):314–319, 1958.
- [27] Xueming Luo, Bin Gu, Jie Zhang, and Chee Wei Phang. Expert blogs and consumer perceptions of competing brands. *Management Information Systems Quarterly*, 41(2):371–395, 2017.
- [28] David Martens and Foster Provost. Explaining data-driven document classifications. *Management Information Systems Quarterly*, 38(1):73–99, 2014.

- [29] Susan M Mudambi and David Schuff. Research note: What makes a helpful online review? a study of customer reviews on amazon. com. *Management Information Systems Quarterly*, pages 185–200, 2010.
- [30] Radim Řehůřek and Petr Sojka. Software Framework for Topic Modelling with Large Corpora. In *Proceedings of the LREC 2010 Workshop on New Challenges for NLP Frameworks*, pages 45–50, Valletta, Malta, May 2010. ELRA. <http://is.muni.cz/publication/884893/en>.
- [31] Drew Robb. Text mining tools take on unstructured data. *Computerworld*, 21, 2004.
- [32] Carl W Roberts. A conceptual framework for quantitative text analysis. *Quality and Quantity*, 34(3):259–274, 2000.
- [33] Jeremy Rose and Christian Lennerholt. Low cost text mining as a strategy for qualitative researchers. *Electronic Journal of Business Research Methods*, 15(1):2–16, 2017.
- [34] Jorge Ruiz Ruiz. Sociological discourse analysis: Methods and logic. In *Forum qualitative sozialforschung/Forum: Qualitative social research*, volume 10, 2009.
- [35] Gerard Salton and Christopher Buckley. Term-weighting approaches in automatic text retrieval. *Information processing & management*, 24(5):513–523, 1988.
- [36] Gibbs Samuel. Mobile web browsing overtakes desktop for the first time, 2016-11-12. <https://www.theguardian.com/technology/2016/nov/02/mobile-web-browsing-desktop-smartphones-tablets>, last accessed on: 2018-08-10.
- [37] Fabrizio Sebastiani. Machine learning in automated text categorization. *ACM computing surveys (CSUR)*, 34(1):1–47, 2002.
- [38] Zhan Shi, Gene Moo Lee, and Andrew B Whinston. Toward a better measure of business proximity: Topic modeling for industry intelligence. *Management Information Systems Quarterly*, 40(4), 2016.
- [39] Jeffrey L Solka et al. Text data mining: theory and methods. *Statistics Surveys*, 2:94–112, 2008.
- [40] Anna Trosborg. Text typology: Register, genre and text type. *Benjamins Translation Library*, 26:3–24, 1997.
- [41] Bikesh Raj Upreti, Aleksandre Asatiani, and Pekka Malo. To reach the clouds: Application of topic models to the meta-review on cloud computing literature. In *49th Hawaii International Conference on System Sciences (HICSS), 2016*, pages 3979–3988. IEEE, 2016.
- [42] Bikesh Raj Upreti, Jani Merikivi, Johanna Bragge, and Pekka Malo. Analyzing the ways it has changed our tv consumption: Binge watching and marathon watching. In *Proceedings of International's Conference on Information Systems*. Association for Information Systems, 2017.
- [43] Laurens van der Maaten and Geoffrey Hinton. Visualizing data using t-SNE. *Journal of machine learning research*, 9(Nov):2579–2605, 2008.
- [44] Robert Philip Weber. Measurement models for content analysis. *Quality and Quantity*, 17(2):127–149, 1983.
- [45] Ian H Witten. Text mining., 2004. <https://www.cs.waikato.ac.nz/~ihw/papers/04-IHW-Textmining.pdf>, last accessed on: 2018-06-24.

References

- [46] Kunpeng Zhang, Siddhartha Bhattacharyya, and Sudha Ram. Large-scale network analysis for online social brand advertising. *Management Information Systems Quarterly*, 40(4), 2016.

4. Appendices

4.1 Appendix I

Type	Short name*	Pattern in the abstract
<i>Type of correction</i>		
Falsification of an accepted belief	Fals'd belief	First presents a theory, method or practice as an accepted knowledge in the field, and then presents a study or an analysis whose intention was to reveal an error in it.
Prescriptive comparison	Presc cmprr	Compares theories, methods or practices with an intent of finding a winner that heretofore should be accepted while the others should be discarded or held suspect.
Prescriptive improvement	Prescr imprr	Presents a theory, method, practice with an intent of proving its superiority over other theories, methods or practices and which heretofore should be accepted while the others should be discarded or held suspect.
Exposition of a problem	Exposed prob	Presents a heretofore unpublished problem in the field.
Negative aposterioristic result	Apost result	As an outcome of the data analysis, presents a finding that disconfirmed the expected result or part of it.
Analysis of disagreements	Disagr analysis	Analyses opposing theories, methods or practices in the field.
Debate	Debate	Discusses another paper's errors or participates in an existing discussion where theories, methods or practices are presented as being in conflict.
Call for knowledge-correcting research	Call for fals	Calls for increased falsification, knowledge-correcting research or critical attitude in the field.
<i>Type of contribution</i>		
Method	Method	The knowledge-correction addresses a way of doing research or work in the field.
Theory	Theory	The knowledge-correction addresses a theory, claim, viewpoint or a belief in the field.
Practice	Practice	The knowledge-correction addresses a tradition, a general approach in academic or industry, or a philosophical or a methodological orientation.

Table 4.1. Description of Knowledge correcting typology

4.2 Appendix II

Keyword	No. of Tweets	Keyword	No. of Tweets
binge	257251	#bingewatching	4504
marathon watch	116728	binge viewing	2689
marathon watching	115189	marathon viewing	2360
TV marathon	63329	broadcast marathon	1567
binge watching	61601	binge view	506
binge watch	26016	#bingeviewing	298
bingeing	9787		
Total Number of Tweets		661825	

Table 4.2. Keywords used in Data collections and Tweets collected

ISBN 978-952-60-8545-6 (printed)
ISBN 978-952-60-8548-7 (pdf)
ISSN 1799-4934 (printed)
ISSN 1799-4942 (pdf)

Aalto University
School of Business
Department of Information and Service Management
www.aalto.fi

**BUSINESS +
ECONOMY**

**ART +
DESIGN +
ARCHITECTURE**

**SCIENCE +
TECHNOLOGY**

CROSSOVER

**DOCTORAL
DISSERTATIONS**