Numerical modeling of spray-assisted dual-fuel ignition

Heikki Kahila

Numerical modeling of spray-assisted dual-fuel ignition

Heikki Kahila

A doctoral dissertation completed for the degree of Doctor of Science (Technology) to be defended, with the permission of the Aalto University School of Engineering, at a public examination held at the lecture hall 213 (K1) of the school on the 31st of May 2019 at 12:00.

**Aalto University
School of Engineering
Department of Mechanical Engineering
Thermodynamics and Combustion Technology**

Supervising professor

Assistant Professor Ville Vuorinen, Aalto University, Finland

Thesis advisor

Doctor Ossi Kaario, Aalto University, Finland

Preliminary examiners

Professor Epaminondas Mastorakos, University of Cambridge, United Kingdom

Associate Professor Jeroen van Oijen, Eindhoven University of Technology, Netherlands

Opponent

Associate Professor Christer Fureby, Lund University, Sweden

Aalto University publication series

DOCTORAL DISSERTATIONS 106/2019

© 2019 Heikki Kahila

ISBN 978-952-60-8585-2 (printed)

ISBN 978-952-60-8586-9 (pdf)

ISSN 1799-4934 (printed)

ISSN 1799-4942 (pdf)

<http://urn.fi/URN:ISBN:978-952-60-8586-9>

Unigrafia Oy

Helsinki 2019

Finland

Author

Heikki Kahila

Name of the doctoral dissertation

Numerical modeling of spray-assisted dual-fuel ignition

Publisher School of Engineering

Unit Department of Mechanical Engineering

Series Aalto University publication series DOCTORAL DISSERTATIONS 106/2019

Field of research Energy Technology IAO15Z

Manuscript submitted 8 February 2019

Date of the defence 31 May 2019

Permission for public defence granted (date) 11 April 2019

Language English

☐ **Monograph**

☒ **Article dissertation**

☐ **Essay dissertation**

Abstract

This dissertation belongs to the field of computational physics and chemistry with a research focus on reacting fuel sprays in internal combustion engine context. Computational fluid dynamics (CFD) and chemical kinetics modeling methods are utilized to simulate turbulent reacting fluid flows in engine conditions. The dissertation comprises four journal publications targeting the modeling of dual-fuel pilot ignition system, commonly used in natural gas engines. In such an ignition concept, high-reactivity fuel (e.g. diesel) is shortly injected into a mixture of low-reactivity natural gas and air during the compression stroke. Diesel fuel autoignites and releases enough energy to initiate a premixed natural gas-air flame. Hence, the diesel spray acts similar to a large spark.

The use of natural gas as a primary fuel in engines is a contemporary topic of interest from the industrial and academic point of views. Utilization of a lean natural gas-air mixture together with modern low-temperature combustion techniques may enable reductions in emission levels. However, methane, the main component of natural gas, is a harmful greenhouse gas. Incomplete combustion due to e.g. unsuccessful ignition leads to direct methane emissions, degraded thermal efficiency and increase in fuel consumption. To avoid such complications, advanced ignition system designs have been proposed, including the dual-fuel pilot ignition.

The focus of the present work is on the analysis of mixture formation and autoignition characteristics in engine conditions. The present study is the first numerical investigation on dual-fuel pilot spray ignition problem by large-eddy simulation (LES) and finite-rate chemistry. A major effort was put on creating a highly efficient finite-rate chemistry solver by utilizing two open source libraries OpenFOAM and pyJack. The developed solver framework enabled the use of high-resolution (62.5 micrometers) grid and complex chemical mechanisms (e.g. 97 species and 997 reactions) in the simulations. The investigated spray setup corresponds to the Engine Combustion Network (ECN) Spray A configuration. ECN provides an open-access data repository and a forum for international experimental and numerical collaboration, enabling an extensive validation of numerical models in terms of a single-fuel diesel spray.

The dual-fuel simulations offer the following novel accomplishments: 1) The first published LES study on interactive physics and chemistry of the pilot spray ignition process. 2) The applied zero-, one- and three-dimensional simulations complement one another providing profound understanding on why methane prolongs diesel ignition. 3) Low- and high-temperature combustion characteristics are assessed, indicating the importance of low-temperature reactions. 4) Consistent with experiments, the connection between spray over-leaning and retarded ignition process is explained and quantified.

Keywords Dual-fuel, pilot ignition, ECN, Spray A, LES

ISBN (printed) 978-952-60-8585-2

ISBN (pdf) 978-952-60-8586-9

ISSN (printed) 1799-4934

ISSN (pdf) 1799-4942

Location of publisher Helsinki

Location of printing Helsinki **Year** 2019

Pages 191

urn <http://urn.fi/URN:ISBN:978-952-60-8586-9>

Tekijä

Heikki Kahila

Väitöskirjan nimi

Kahden polttoaineen syttymisen laskennallinen mallintaminen

Julkaisija Insinööritieteiden korkeakoulu**Yksikkö** Konetekniikan laitos**Sarja** Aalto University publication series DOCTORAL DISSERTATIONS 106/2019**Tutkimusala** Energiateknologia IA015Z**Käsikirjoituksen pvm** 08.02.2019**Väitöspäivä** 31.05.2019**Väittelyluvan myöntämispäivä** 11.04.2019**Kieli** Englanti☐ **Monografia**☒ **Artikkeliväitöskirja**☐ **Esseeväitöskirja****Tiivistelmä**

Tämä väitöskirja lukeutuu laskennallisen fysiikan ja kemian tutkimusalaan. Painopisteenä on reaktiivisten polttoainesuihkujen mallintaminen polttomottoreissa laskennallisen virtausmekaniikan ja kemian työkaluja hyödyntäen. Väitöskirja koostuu neljästä kansainvälisestä lehtijulkaisusta, jotka kaikki käsittelevät ns. sekundääripolttoaineen suoraruiskutusta maakaasumootorin sytytysjärjestelmänä. Kyseisessä menetelmässä reaktiivista diesel-polttoainetta ruiskutetaan lyhyesti moottorin palotilaan, missä se puristuuessaan syttyy ja mahdollistaa myös maakaasuilmaseoksen syttymisen. Diesel-suihku toimii siis sytytystulpan korvikkeena.

Maakaasun käyttö pääasiallisena polttoaineena polttomottoreissa on herättänyt kiinnostusta viime vuosina. Maakaasun polttaminen hyödyntäen matalan lämpötilan palamistekniikoita mahdollistaa matalampien päästötasojen saavuttamisen. Maakaasu koostuu kuitenkin suureksi osin metaanista, joka itsessään on ilmastolle haitallinen kasvihuonekaasu. Vaillinaisen palaminen kaasumootorissa johtaa välittömiin metaanipäästöihin, heikentäen moottorin hyötysuhdetta, polttoainekustannuksia sekä kokonaisvaltaisia ympäristövaikutuksia. Ongelman välttämiseksi on kehitetty vaihtoehtoisia polttoaine-ilmaseoksen sytytystekniikoita, joista yllä kuvattu kaksoispolttoainekonsepti on tämän väitöskirjan aiheena.

Tutkimuksen painopiste on ruiskutuksen mallintamisessa, polttoaineseoksen muodostumisessa sekä syttymisilmiön kartoittamisessa. Tässä työssä esitetään ensimmäinen laskennallinen malli kaksoispolttoainekonseptille käyttäen suurten pyörteiden menetelmää (LES) turbulenssin mallintamiseksi ja suoraa aikaintegrointia kemialle. Väitöskirjatyössä implementoitiin laskentamenetelmä yhdistäen kaksi modernia avoimen lähdekoodin ohjelmistoa nimeltään OpenFOAM ja pyJac. Kehitetyn laskenta-alustan avulla saavutettiin korkea paikkaresoluutio sekä laaja kemiallisten yhdisteiden määrä suhteessa aiempiin tutkimuksiin (62.5 mikrometriä, 97 yhdistettä ja 997 reaktiota). Simulaatioiden lähtökohtana on "Engine Combustion Network" (ECN) Spray A-konfiguraatio. ECN on kansainvälinen yhteistoiminnallinen organisaatio, joka mahdollistaa laajamittaisen vertailun laskennallisten ja kokeellisten mittausten välillä diesel-polttoaineen tapauksessa.

Tutkimustyön saavutuksia ovat: 1) Ensimmäinen kansainvälinen lehtijulkaisu syttymisestä kaksoispolttoainekonseptissa LES-lähestymistapaa käyttäen. 2) Toisiaan vahvistavat nolla-, yksi- ja kolmiulotteiset simulaatiot, jotka tarjoavat lisätietoa prosesseista liittyen dieselin syttymisviiveen pidentymiseen metaani-ilmaseoksissa. 3) Matalan ja korkean lämpötilan palamisen ominaisuuksien määrittäminen, joihin liittyvät matalan lämpötilan kemialliset reaktiot todettiin erityisen tärkeiksi. 4) Yhdessä kokeiden kanssa simulaatiot selittävät diesel-seoksen laihenemisen ja pidentyvän syttymisviiveen välillä olevan yhteyden.

Avainsanat diesel, metaani kaksoispolttoaine, syttyminen, ECN, Spray A, LES**ISBN (painettu)** 978-952-60-8585-2**ISBN (pdf)** 978-952-60-8586-9**ISSN (painettu)** 1799-4934**ISSN (pdf)** 1799-4942**Julkaisupaikka** Helsinki**Painopaikka** Helsinki**Vuosi** 2019**Sivumäärä** 191**urn** <http://urn.fi/URN:ISBN:978-952-60-8586-9>

Preface

The research work in this dissertation was carried out at Aalto University during the years 2015-2019. The dissertation was pre-examined by Professors Epaminondas Mastorakos and Jeroen van Oijen, whom I sincerely thank for their positive feedback. I would like to thank Professor Christer Fureby for acting my opponent in the public defense. The dissertation was financially supported by the Academy of Finland and the author acknowledges Wärtsilä Co. for academic contribution and support. The computational resources were provided by CSC–Finnish IT Center for Science Ltd.

Engine ignition problems have always been part of my life. During the years, engine sizes have changed from 2.5 to 990 cm³ and the root causes for ignition problems have varied from non-optimal fuel-air-ratio to unstable ignition sequence, induced by a broken magneto wheel on one day and a low voltage in an engine control unit on another day. Typically, these issues resulted in rough landings of my model aircraft or pushing a motorcycle in the rain.

These events did not help to solve the numerical high-performance computing problems shown in this dissertation but they probably taught some persistence and most importantly, they highlight the importance of a functioning ignition system, which is the essential topic of this dissertation.

Completing this dissertation would not have been possible alone. Hence, I would like to express my gratitude to my supervisor Professor Ville Vuorinen, who has mentored me through the academic world by teaching the fundamentals of high-quality LES, showing how to produce scientific text, how to make simplifications at right places and when to look for the smallest necessary details. My advisor, Dr. Ossi Kaario then always gave the context for our ideas and how to present them in a simple manner. Ossi, you also made my life much easier by always answering my questions on sprays and engines. Overall, I'm grateful that I contacted Prof. Martti Larmi over four years ago and that he recommended working in this research group.

During the research, profound industrial cooperation helped and motivated me to set the research targets to perspective. In particular, Lars Ola Liavåg, Jari Hyvönen and Eric Lendormy, thank you for always reminding the scales and features of practical combustion problems.

A great deal of inspiration and practical help was given by my colleague and friend Dr. Armin Wehrfritz. Many of the ideas and visualizations we discussed during those long office evenings were converted to be part of this dissertation, thank you.

Mahdi, I wonder, do we ever learn to prepare presentations in time? Probably not, but still, you are a great project partner. Thank you Dr. Karri Keskinen for shedding some light on the mysteries of turbulence but most importantly, for making the office a nice place to work at. Similarly, without Erkki, Petteri, Bulut, and Shervin, there would be no reason to come to the office.

During the past years, I have received funds from Merenkulun säätiö, Tekniikan edistämissäätiö and Väisälän Rahasto. Thank you for supporting my work.

I wish to thank all my friends and family for their constant support. In particular, I would like to thank my parents Pekka and Tyyne who have always encouraged me to reach new experiences in life and education.

Espoo, May 9, 2019,

Heikki Kahila

Contents

Preface	1
Contents	3
List of Publications	5
Author's Contribution	7
1. Introduction	9
1.1 Trends in energy production in the 2020s	9
1.2 Role of internal combustion engines in the 2020s	11
1.3 Use of natural gas and diesel in combustion engines	12
1.3.1 Conventional engine types	12
1.3.2 Dual-fuel pilot ignition system	15
1.4 Challenges in computational modeling of reacting flows	16
1.4.1 Scale separation	16
1.4.2 Turbulence modeling	17
1.4.3 Combustion chemistry modeling	18
1.5 Overall objectives	20
1.6 Outline of the dissertation	20
2. Literature review	21
2.1 Background	21
2.2 Spray research since the 1990s	22
2.3 The Engine Combustion Network (ECN)	23
2.4 Dual-fuel pilot ignition process	25
2.5 Chemical mechanisms for dual-fuel simulations	27
2.5.1 Selection of chemical mechanism	27
2.5.2 Chemical mechanisms for <i>n</i> -dodecane	28
2.6 Three-dimensional reacting spray simulations	30
2.6.1 Overview of sub-models	30
2.6.2 LES of the ECN Spray A case	32

2.7	Research gaps	33
3.	Methods	35
3.1	Governing equations	35
3.2	Discretization of the governing equations	36
3.3	Spray modeling	36
3.4	Integration of finite-rate chemistry	37
3.5	Subgrid-scale modeling	40
3.6	Role of flamelet generated manifolds in single-fuel and dual-fuel combustion	41
3.7	Simulation configuration	44
4.	Summary of Results	45
4.1	Publication I	45
4.2	Publication II	47
4.3	Publication III	49
4.4	Publication IV	51
4.5	Limitations	52
4.6	Overall conclusions	53
4.7	Suggestions for future work	53
	References	55
	Publications	71

List of Publications

This thesis consists of an overview and of the following publications which are referred to in the text by their Roman numerals.

- I** H. Kahila, A. Wehrfritz, O. Kaario, M. Ghaderi Masouleh, N. Maes, B. Somers, V. Vuorinen. Large-eddy simulation on the influence of injection pressure in reacting Spray A. *Combustion and Flame*, 191,142-159, May 2018.
- II** H. Kahila, A. Wehrfritz, O. Kaario, V. Vuorinen. Large-eddy simulation of dual-fuel ignition: Diesel spray injection into a lean methane-air mixture. *Combustion and Flame*, 199,131-151, January 2019.
- III** H. Kahila, A. Zeeshan, O. Kaario, M. Ghaderi Masouleh, B. Tekgül, M. Larmi, V. Vuorinen. A large-eddy simulation study on the influence of diesel pilot spray quantity on methane-air flame initiation. Accepted for publication in *Combustion and Flame*, May 6th 2019.
- IV** M. Ghaderi Masouleh, A. Wehrfritz, O. Kaario, H. Kahila, V. Vuorinen. Comparative study on chemical kinetic schemes for dual-fuel combustion of *n*-dodecane/methane blends. *Fuel*, 191, 62-76, March 2017.

Author's Contribution

Publication I: “Large-eddy simulation on the influence of injection pressure in reacting Spray A”

The author was responsible of carrying out the simulations and analysis of the results as well as writing major parts of the manuscript. The work was initiated by co-authors and model development was based on previous research of A. Wehrfritz. The experimental work and the related text in the manuscript were provided by co-authors from Eindhoven University of Technology.

Publication II: “Large-eddy simulation of dual-fuel ignition: Diesel spray injection into a lean methane-air mixture”

The author was responsible for the design, execution and analysis of the study. The author developed and implemented the LES-finite rate chemistry solver by utilizing two open source libraries OpenFOAM and pyJack. The article was mainly written by the author with suggestions and feedback from all the co-authors.

Publication III: “A large-eddy simulation study on the influence of diesel pilot spray quantity on methane-air flame initiation”

The author was responsible for the design, execution and analysis of the study. The article was mainly written by the author with suggestions and feedback from all the co-authors. Experimental research and the related parts of the manuscript text were provided by Z. Ahmad and M. Larimi. O. Kaario and V. Vuorinen provided several suggestions on the LES analysis and improvements on the manuscript quality.

Publication IV: “Comparative study on chemical kinetic schemes for dual-fuel combustion of *n*-dodecane/methane blends”

The author co-authored the paper and provided substantial technical assistance with the simulations, post-processing as well as theoretical analysis of the results. M. Ghaderi Masouleh was responsible on the major part of the written manuscript. The author contributed to the manuscript by providing several suggestions and improvements during the writing and proofreading process.

1. Introduction

This dissertation belongs to the field of computational physics and chemistry with focus on modeling of reacting multiphase fuel sprays in internal combustion engine conditions. The applied methods follow the modern practices in computational fluid dynamics (CFD) and chemical kinetics. The dissertation is compiled from peer-reviewed journal articles while the following chapters outline a compact introduction to the subject. The appended publications include substantially more details on the results and applied methods. In brief, injection of high-reactivity diesel fuel into a low-reactivity methane-air mixture is investigated in engine relevant conditions. Focus of the analysis is on autoignition characteristics. In this dissertation work, a short diesel spray is referred to as the pilot spray.

1.1 Trends in energy production in the 2020s

Over the past decades, combustion processes have provided a major share of the global energy supply. In 2017, global economic growth and low fossil-fuel prices led to a 2.1% higher energy demand and resulted in 1.4% growth in carbon dioxide (CO₂) emissions, reaching a historically high 32.5 Gt level [1]. However, as stated in multiple scientific references, such a global trend in anthropogenic green house gas emissions is not sustainable and will lead to global warming without any limiting actions [2–4]. International agreements pursue efforts to limit the increase in global average temperature to 1.5 °C above pre-industrial levels in this century [5].

International Energy Agency (IEA) [1] has published two projections on the future global energy sector development, denoted as the new policy scenario (NPS) and the sustainable development scenario (SDS). The NPS incorporates existing energy policies as well as an assessment of the results likely to be obtained by the announced policy intentions. The SDS outlines an integrated approach for achieving internationally agreed objectives on climate change and universal access to modern energy. Figure 1.1 demonstrates the estimated total CO₂ emission level evolution according to NPS and SDS [1]. While CO₂

Figure 1.1. Historical growth of CO₂ emissions and the estimated development according to New/Sustainable Development Policy scenarios (top). Historical and estimated electricity production by technology type in the Sustainable Development Scenario (bottom). Figure reproduced with permission: ©OECD/IEA 2018 World Energy Outlook, IEA Publishing. Licence: www.iea.org/t&c; as modified by Heikki Kahila.

levels increase mildly in the NPS, the sustainable choice yields a peak around 2017-2018 following with a steady decline.

In the world of an ever increasing energy demand, the electricity sector grows the fastest [1]. Figure 1.1 (bottom) reflects the future electricity production according to the optimistic SDS scenario, in which a clear transformation in the share of technology types is required. The rise of variable renewable sources such as hydro, wind and solar is mandatory for meeting the climate goals together with decrease in coal and oil based electricity generation. Notably, the share of natural gas (NG) remains steady in the 2020s, which is primarily driven by a high demand in China. For example, China's continuous deployment of renewable energy and transition from coal to NG retained the CO₂ emission growth in 1.7% even though China's overall economy grew nearly 7% in 2017 [1].

Natural gas consists mainly of methane ($\approx 90\%$ CH₄) and due to its low molecular carbon-hydrogen ratio (C/H), lower CO₂ emissions can be achieved compared to coal ($\sim 40\%$) and oil ($\sim 20\%$) (per energy unit) [6]. Additionally, sulfur oxide (SO_x) emissions are negligible or non-existing and considerable reductions in nitrogen oxide (NO_x) levels can be achieved with modern low-temperature combustion techniques. However, CH₄, the main component of NG, has an 85(28) times higher global warming potential relative to equivalent mass of CO₂ over a 20(100)-year time horizon [6, 7]. Hence, if there are any direct methane emissions, i.e. methane slip, due to e.g. pipe leakage or incomplete combustion, the environmental benefits of NG may be radically reduced.

Atmospheric CH₄ concentrations have risen sharply since 2006 mainly due to emissions from anthropogenic origin (60% total) [6, 8]. The energy sector accounts for 20% of the total CH₄ emissions with the upstream production/supply

responsible for most, while the downstream use of NG accounts for $\sim 20\%$ (e.g. due to incomplete combustion) [6]. As the lifetime of atmospheric CH_4 is relatively short (12 years [6]), any CH_4 emission mitigation may benefit the climate even in short-term.

1.2 Role of internal combustion engines in the 2020s

The outlook of the 2020s in energy production will be an interesting and challenging period from internal combustion engine (ICE) technology point of view. It seems that use of NG will remain as an important energy source for developing economies while use of oil is decreasing. Next, the role of ICE as a robust combustion technology type is discussed with relevance to future trends in energy and propulsion systems utilizing NG as the primary fuel.

Until recently, industry has been focusing on large ($> 300\text{MW}$) centralized coal and gas turbine-based power plants. However, lately, a growing interest towards flexible and distributed small scale solutions ($< 200\text{MW}$) has emerged, opening markets for competitive ICE manufacturers. For example, growth of new small-scale ($< 20\text{MW}$) ICE plants exceeded that of turbine-based technologies in 2013 [9].

Even though turbine-based technologies dominate the electricity production, ICEs provide cost-competitive possibilities for power grid stabilization at times when renewable sources cannot supply enough energy [1, 9, 10]. Hence, start-up times, ramping capabilities and part load efficiency become appreciated features in power generation, all being essential strengths of the ICE technology [9, 10]. Possibility to stack several engines into a larger plant enables efficient and reliable maintenance without crucial output breaks [9, 10]. The overall efficiency of an ICE plant can be increased close to 90% if the flue gases are used to co-generate heat [9, 10]. Its other benefits over conventional turbine technology are: 1) multi-fuel compatibility (gas/diesel) depending on market price with less quality requirements, 2) decreased sensitivity to ambient temperature and pressure, and 3) short construction time (less than one year) [9].

Similar to the trends in electricity generation, use of NG-based ICEs in marine transportation sector is expected to increase due to their high potential in CO_2 and SO_x savings [1]. In 2018, International Maritime Organization (IMO) set a strategy to reduce CO_2 emissions in international shipping by at least 40% by 2030 and to pursue efforts towards 70% by 2050 (on average, relative to 2008). By 2020, the sulfur content of ships' fuel will be limited to 0.5% (now 3.5%) [11]. Besides low-sulfur oil, NG is a viable option for the marine sector, depending on its worldwide availability and level of supply infrastructure in harbors [1, 6, 11]. While international seaborne transport remains the cheapest option for long-distance freight in the near future, use of NG in road vehicles is expected to remain as a niche market [6].

Low energy density of NG (40MJ m^{-3}) compared to diesel (39MJ L^{-1}) sets

Figure 1.2. Towards clean marine transportation in Baltic Sea: Viking Grace is the world's first LNG powered hybrid passenger vessel. Dual-fuel LNG/diesel engines provide primary propulsion while a rotor sail assists via the Magnus effect. Large 200 m³ LNG tanks, located outdoors at rear of the vessel, preserve the liquefied gas at -163°C temperature safely. Picture by Olli Tuominen, Ulkomatala 3/2018: printed with permission.

certain challenges for a compact fuel storage in the transport sector. Options are to either compress the gas to a pressure of ~ 200 bar, or liquefy it by cooling it to below its boiling point of -163°C (at atmospheric pressure), and store it in tanks (see Fig. 1.2). Price of liquefied natural gas (LNG) is expected to remain appealing in the upcoming decades, driving the development towards a wider LNG network with direct harbor services [6].

It seems that use of NG will remain as an important energy source and will be an option for sectors where alternatives are limited, such as marine propulsion. NG offers a less carbon intensive alternative compared to oil and coal, but given its carbon content and potential methane emissions, NG does not provide a path to full decarbonization and zero emissions. Hence, technological developments are required in a smooth transition towards cleaner options in the future.

To successfully construct a gas engine with low exhaust emissions and high overall efficiency, complete combustion of fuel is necessary. Additionally, it would be highly beneficial if an engine operator could choose between alternative fuels on the fly depending on the availability and price of the fuel. In the next section, the working principle of a dual-fuel (DF) engine concept is presented, with potential to fulfill the above prerequisites.

1.3 Use of natural gas and diesel in combustion engines

1.3.1 Conventional engine types

Conventionally, ICEs are categorized to spark-ignited (SI) and compression ignition (CI) engines. Most engines using NG belong to the former category where a homogeneous mixture of gaseous fuel and air is compressed in an

engine cylinder during the compression stroke and ignited by means of an electric discharge created by a spark plug near the top-dead-center (TDC). The spark will initiate a self-propagating turbulent premixed flame front, consuming available fuel-air charge [12].

Ability of the fuel to withstand compression before autoignition is measured by the octane number. For example, NG has a high octane number (130) compared to diesel (20), and hence, an external ignition source must be provided. In single-fuel (SF) CI engines, liquid fuel, commonly diesel, is injected with high pressure and momentum into an engine cylinder near TDC. Evaporation of liquid diesel fuel and its turbulent mixing with air lead to an autoignition under compression [12]. Continuous injection of diesel fuel leads to a growing non-premixed diffusion flame which is inherently characterized by the mixing rate of fuel and air [13]. An illustration of both SI and CI concepts is given in Fig. 1.3.

The efficiency of a combustion cycle is directly related to the designed compression ratio, which is limited by the fuel choice, fuel-air-ratio and ignition method [12, 14]. In practice, CI diesel engines have a high compression ratio yielding a high thermal efficiency compared with conventional SI engines. When the compression ratio in an SI engine exceeds a certain threshold, some parts of the premixed fuel-air mixture are undergoing a fast autoignition process instead of being consumed by the flame front. Such phenomenon is known as engine knock and may lead to degraded efficiency and structural damages due to uncontrolled pressure rise [12, 14]. In CI based diesel engines higher compression ratios can be applied because the fuel is not injected into the cylinder until ignition and subsequent heat release is required [12].

Combustion of NG in SI engines is typically taking place near stoichiometric conditions, where oxidization process ideally converts all available fuel to combustion products. One option to increase the compression ratio and efficiency is to lower the fuel-air ratio, leading to a lean, less reactive mixture. The fuel-air ratio is typically described by equivalence ratio (ϕ), which is defined as the fuel-to-oxidizer ratio, normalized by its stoichiometric value. Typically, use of mixtures with excessive air ($\phi < 1$) lead to lower fuel consumption and CO₂ emissions in engines. Additionally, in such lean combustion processes, dilution leads to a reduced peak temperature, yielding also reduction in NO_x [14].

Opportunities in thermal efficiency enhancements and emission reductions motivate engine manufacturers to develop products for lean conditions, reaching equivalence ratios below 0.5. However, there are at least three major drawbacks in such a lean combustion cycle. First, the amount of typical energy provided by the spark plug may not be sufficient to robustly ignite the mixture [14]. Second, the propagation velocity of a premixed flame front is decreased, taking longer to complete the combustion and making the flame more prone to perturbations which may induce variation between duty cycles [14]. Third, the conventional catalytic NO_x after-treatment applications lose conversion efficiency below stoichiometry [12, 14]. Next, an overview on available advanced ignition methods is given with focus on DF pilot ignition system.

(a)

(b)

Figure 1.3. Illustration of combustion types with respect to the piston scale in engine context: (a) centrally spark-ignited (I) premixed flame propagation (II) and (b) centrally injected liquid diesel spray (III) and the resulting spray diffusion flame (IV). Illustration is based on the simulation data published in Ref. [15] (a) and in Publication I (b).

1.3.2 Dual-fuel pilot ignition system

As discussed above, decrease in equivalence ratio reduces the reactivity of the fuel-air mixture. Hence, the ignition system becomes a crucial part of the engine design, as it defines the origin of turbulent flame propagation and subsequent fuel consumption. There are three major techniques to achieve ignition in lean conditions: 1) electric spark, 2) pre-chamber and 3) DF pilot ignition. Besides the aforementioned, some unconventional technologies have been recently introduced as candidates for lean combustion including plasma igniters, laser induced ignition systems and corona spark plug systems [16]. However, these technologies are complex and expensive in their present form. Next, the three major ignition techniques are briefly reviewed.

Applicability of the conventional spark system can be extended to lean conditions by introducing direct injection (DI) of gas into the cylinder, allowing some mixture stratification and knock-resistance prior to ignition [17]. However, DI of gas requires a high-fidelity injection system and is still under active development.

Pre-chamber technology refers to a system where a small amount of fuel inside a separate combustion chamber is ignited by a spark plug and the resulting exhaust gases are expanding out of multiple orifices on the sides of the pre-chamber. Such hot turbulent gas jets provide multiple and comparably very large ignition sites within the main charge and result in robust premixed flame initiation [18]. Furthermore, high velocity jets induce intensive turbulence, increasing the overall burn rates [18]. The drawback of the pre-chamber system is that in very lean conditions, auxiliary fuel injection may be needed to enrich the pre-chamber mixture, leading to a more complicated technical structure and increased role of control systems [18]. Additionally, pre-chamber ignition may increase erosion of engine parts [18].

A DF pilot ignition method refers to a concept where a relatively small quantity of high-reactivity fuel (HRF), e.g. liquid diesel fuel, is injected into an engine cylinder filled with low-reactivity fuel (LRF), e.g. premixed NG-air mixture. The high-reactivity fuel autoignites under compression and initiates a premixed flame in multiple locations (c.f. Fig. 1.4 for illustration). Similar to pre-chamber systems, high-velocity sprays induce intense turbulence levels, enhancing the premixed combustion of the main charge [19]. Typically, the contribution of pilot-fuel to the total energy is maintained below 10% [20] but on demand, a conventional diesel combustion mode (100%) can be retained [21]. Such a fuel flexibility allows utilization of the cheapest/cleanest fuel available.

The working principle and design of the DF pilot ignition system is inherently related to the modern low-temperature combustion concepts such as the homogeneous charge compression ignition (HCCI) [22, 23] and reactivity controlled compression-ignition (RCCI) [24, 25]. In particular for RCCI type engines, mixing and simultaneous combustion of both HRF and LRF is an important area to explore.

Figure 1.4. Illustration of a short diesel pilot spray igniting a premixed NG-air mixture with a subsequent generation of a self-propagating flame front. Illustration is based on simulation results obtained in Publication III.

The drawback of the pilot fuel ignition concept is related to the optimization of the injection system. Typically, the pilot fuel quantity is maintained small enough to mitigate NO_x production from diesel combustion, yet large enough to achieve a reliable ignition timing and efficient combustion of the main charge [26, 27]. In general, it has been reported that insufficient pilot ignition may lead to combustion instabilities and result in misfiring and unburned hydrocarbon (UHC) emissions (methane slip) [27, 28]. In spite of commercial utilization of DF engines, detailed understanding of the complex autoignition physics in a turbulent spray environment is not thoroughly explored. In order to enhance the fundamental understanding and to complement the small number of available experimental studies, this dissertation concerns the computational modeling of DF autoignition phenomenon in engine context.

1.4 Challenges in computational modeling of reacting flows

1.4.1 Scale separation

Turbulent combustion is encountered in a wide variety of natural and industrial processes all around our daily routines. It is a subject that is of immense practical importance, yet is at the same time lacking a comprehensive understanding. Predicting turbulent flows is a challenging task itself, but often additional complexities such as moving parts, chemical reactions, heat transfer or two-phase

fluids further complicate the engineering tasks. In practice, all the prescribed features are present in an ICE development process. Computational tools in modern engine design are constantly gaining more popularity but they are still lacking confidence in predictability, required by daily routines in industry [29].

Complexity of turbulent combustion rises from the vast scale separation in practical systems. Even without combustion, fundamental processes in viscous flows may lead to flow structures (e.g. eddies) with size differences spanning several orders of magnitude. The range of scales depends on the ratio of inertial and viscous forces within the system. Fluid velocity U , characteristic length scale of the system L and kinematic viscosity of the fluid ν define the non-dimensional Reynolds number ($Re = UL/\nu$) which characterizes fluid's response to perturbations. For flows with low Re values, the viscous forces stabilize small scale perturbations, yielding distinct streamlines for the bulk motion, i.e. laminar flow. In contrast, for high Re values, perturbations trigger instabilities, leading to complex and stochastic three dimensional fluctuations, i.e. turbulence. Following the Kolmogorov's theory on turbulence, the smallest eddy size η in a turbulent system is related to the energy dissipation rate ϵ and ν as

$$\eta = \left(\frac{\nu^3}{\epsilon} \right)^{1/4},$$

reaching values in the scale of $10 \mu\text{m}$ in low-speed engines [30].

Besides scale separation generated by turbulence, mechanical parts are designed at different scales as well. For example, engine cylinder diameter is $0.1\text{-}1 \text{ m}$, while a typical orifice diameter of a diesel fuel injector is in the scale of 10^{-4} m , producing liquid ligaments/droplets in the order of micrometer scale from a disintegrating high-velocity ($\sim 600 \text{ ms}^{-1}$) diesel spray, as illustrated in Figs. 1.3b and 1.5. In the context of diesel sprays, η may reach values below $10 \mu\text{m}$ [31, 32].

In chemically reacting flows, the reaction zone length scale, describing the regime with high oxidization activity, can be even below the smallest eddy scale. To summarize, the scale separation can easily span seven orders of magnitude in practical systems. Similarly, time scales vary greatly, from 1 s system residence time to individual chemical reaction times scales down to and below 10^{-10} s .

1.4.2 Turbulence modeling

Mathematical description of fluid flow under continuum hypothesis is given by Navier-Stokes equations, derived from Newton's laws of motion in the 1800s. The governing equations form a non-linear partial differential equation (PDE) system describing the conservation of mass, momentum and energy in the system. Non-linearity and the vast scale separation compose challenges for analytic and numerical solution approaches.

Numerical solution can be achieved by finite difference/volume/element methods, generally applied for PDEs. When discretizing the governing equations

such that all fluid length scales are resolved, the approach is referred to as direct numerical simulation (DNS). Due to the prescribed scale separation issue, the computational load of DNS is out of reach for majority of practical systems today and in the near future. Even the constantly growing potential in computational resources is not expected to change this situation without a breakthrough in processor design. Hence, to reduce the computational cost, modeling approaches for the non-linear behavior, including turbulence, have been developed.

The most widely utilized solution approach is based on the Reynolds-Averaged Navier-Stokes (RANS) equations. Within this approach, the primary variables are decomposed to a time-averaged and fluctuating parts. The mean quantities are directly computed, while the fluctuating parts, i.e. all turbulent scales, are modeled. Most RANS turbulence models have a solid theoretical and practical basis, yielding good mean flow results with low computational costs in many applications (e.g. in aerodynamics) [33]. However, predictability in more complex transient flows can be challenging.

A second modeling avenue resolves a large part of the turbulent length scale spectrum but covers the smallest scales by an additional model. The approach is denoted as large-eddy simulation (LES) and its computational cost is placed between DNS and RANS, depending on the resolution, implementation and application. LES is gaining popularity in academy and recently in some parts of industry as well, when better computational resources become available. The key difference between RANS and LES is in their ability to resolve transient structures, as illustrated in Fig. 1.5 in case of diesel spray injection.

1.4.3 Combustion chemistry modeling

In computational modeling of chemically reacting flows, the main challenge/-focus is threefold: 1) an accurate description of elementary reactions between chemical species (i.e. chemical kinetics), 2) an efficient solution of species production/consumption rates within the RANS/LES/DNS configuration, and 3) accurate treatment of the turbulence-chemistry interactions (TCI). All three aspects are crucial to achieve a realistic description of e.g. diesel spray ignition and emission formation at low temperatures.

In the field of chemistry, detailed experiments and molecular level "ab initio"

Figure 1.5. Illustration of scale resolving LES (left) and RANS (right) approaches in spray context. Figures are obtained from the work by Pei et al. [31] and reprinted with permission from Elsevier.

simulations are applied to define individual reaction rates and products for the interacting species. The rate data is carefully compiled to form specific coefficient tables, i.e. chemical mechanisms, allowing an algebraic description of the oxidation process via various reaction paths. These tables vary in size from few species and reactions for hydrogen to thousands for long hydrocarbons.

Figure 1.6 illustrates the transition towards more complex/realistic fuel surrogates with high number of elementary reactions which leads to an unsustainable growth in computational cost. As a consequence, a significant fraction of the computational power may be spent on chemistry in reacting flow simulations, depending on the desired accuracy and complexity. In case of RANS/LES approach, additional modeling effort is required to account for turbulence-chemistry interactions (TCI) at length scales not resolved by the methods. Besides chemical reactions, multicomponent mass diffusion among species may be crucial for accurate description of e.g. premixed flame propagation [34]. Without any simplifications, the computational cost of mass diffusion is in the scale of reaction rates [35].

Potential impact by computational methods in combustion optimization and emission reduction is high but greatly dependent on computational efficiency and trustworthiness of the results. Hence, as stated by R. W. Bilger, it is only with a hierarchical international validation approach that definite progress on advanced computational modeling for practical applications can be achieved [29]. Recently, steady progress on such well-defined validation procedures has been made. For example, Turbulent Non-premixed Flame (TNF) workshop [36] and the Engine Combustion Network (ECN) [37] provide a series of quantitative experiments with standards for computational comparisons. In particular, this dissertation concerns the ECN Spray A baseline case as the primary validation target condition.

Figure 1.6. Normalized mean computational evaluation time of a chemistry solution as a function of chemical mechanism size for a simple homogeneous autoignition problem. Values are obtained by the Cantera software [38].

1.5 Overall objectives

The primary objective of this thesis work is to investigate DF pilot ignition process, where diesel surrogate is injected into a premixed methane-air mixture at engine relevant conditions. The simulation setup and the validation follows the ECN Spray A baseline conditions, see Sec. 3.7. The DF configuration is achieved by modifying the Spray A case by introducing methane to the ambient mixture. The detailed literature review on DF combustion, spray modeling and chemical kinetics is provided in the next chapter, with a particular listing of specific research gaps in Sec. 2.7. The overall scientific research objectives of this dissertation are to:

1. validate the spray solver configurations against the experimental data on transient mixing, ignition delay time and flame characteristics in the baseline Spray A (single-fuel) conditions (Publication I-II).
2. investigate the ignition timing, location and the corresponding mixture state in both SF and DF configurations (Publication I-III),
3. investigate the link between diesel pilot dilution and ignition processes (Publication III),
4. identify the sensitivity of the DF ignition process on chemical mechanism and on specific elementary reactions (Publication II-IV).

In order to accomplish the above objectives, programming efforts are required to achieve fast and accurate solution of DF chemical kinetics in LES context. Hence, a reactive flow solver, based on the open-source libraries for CFD (OpenFOAM) and for chemical kinetics (pyJac), is implemented as part of this dissertation.

1.6 Outline of the dissertation

In previous sections, a rather general review on the future energy outlook and on the use of NG and diesel in ICE applications has been provided. In particular, motivation for the DF pilot ignition system design was constructed from conventional ICE technology and emission points of views.

The remainder of the dissertation is structured as follows: A detailed literature review on spray combustion in SF and DF context is given in Ch. 2, while in Ch. 3, the governing reacting flow equations and numerical models are presented.

Finally, a brief summary of the most important results is given in Ch. 4 together with concluding remarks and recommendations for future studies. It is worth noting that the details of methods or results are not repeated, but the reader is suggested to refer to the attached peer-reviewed journal publications.

2. Literature review

2.1 Background

The origin of DF pilot ignition concept dates back to 1901 when Rudolf Diesel described the essential features in his patent application [39]. Economic benefits as well as challenges in engine control were identified already in the early academic contribution by Elliot and Davis [40] (1951) who described the significance of fuel-air ratio on combustion characteristics and stability.

Since the 1970s, a series of DF studies was authored by Karim et al. who constructed the first conceptual representation of the ignition and combustion phases based on engine experiments (c.f. review by Karim [41]). Most of the recent DF combustion literature is still based on laboratory engine experiments and target on performance, efficiency and combustion stability issues [20, 27, 41–46], lacking details on ignition and premixed flame initiation. In contrast, such features are identified and well documented in high-fidelity experiments for diesel spray combustion [47–49]. Only very recently, during this thesis research, high-fidelity measurements on DF pilot ignition have emerged, underlining the importance of mixing and low-temperature chemistry [19, 50].

In order to develop a solid basis for Publication I–IV and to formulate the research scope more in detail, we begin by concentrating on diesel spray combustion experiments published in the recent years. A special focus is given on the Engine Combustion Network and its important role in detailed spray experiments. Secondly, recent advancements in the essential DF pilot ignition literature are discussed. Thirdly, we review the work on chemical mechanisms with again focus on DF applications, in particular *n*-dodecane/CH₄ mixtures. Finally, an overview on the recent numerical turbulent diesel fuel spray studies is considered. The contributions of the most elemental literature references are compiled into Table 2.2 at the end of this chapter.

2.2 Spray research since the 1990s

For decades, experimental researchers have searched for a better understanding of high-momentum fuel spray combustion [51]. New trends in quantitative high-resolution laser-based diagnostics led to a well recognized conceptual model of diesel spray combustion given by Dec [13, 52] in the late 1990s. Subsequent studies by Siebers and co-workers at Sandia National Laboratories (SNL) [47, 48, 53] in the late 1990s and early 2000s highlighted the importance of turbulent mixing, autoignition and flame stabilization in understanding the origin of emission formation. These studies provided the basis for modern spray research and establishment of the Engine Combustion Network.

In particular, the works by Siebers et al. [47, 48, 53] were based on experiments in a constant volume combustion chamber with large windows enabling optical diagnostics from multiple viewing angles [47]. In such a configuration, liquid fuel is injected into the chamber under quiescent flow conditions, and where high-pressure and high-temperature ambient conditions are achieved in a pre-burn combustion event [47]. Utilization of a large chamber avoids the intrinsic complexities found in engine experiments, including wall effects, spray impingement, transient compression, swirl and restricted optical access.

The combustion chamber experiments resulted in quantitative measurements on liquid/gaseous fuel distribution depending on fuel, injection pressure, nozzle hole diameter and ambient gas density and pressure [47]. Further investigations included detailed diagnostics of diffusion flame characteristics downstream from the injector [48, 53, 54]. The chemiluminescence imaging based on the excited state of hydroxyl (OH^*) showed that high-temperature combustion downstream from the nozzle fluctuates as a result of turbulence but has a quasisteady mean value, referred to as the flame lift-off length (FLOL), see Fig 2.1. The experiments indicated a strong link between upstream mixing, FLOL and soot formation [48, 55, 56]. The sensitivity of FLOL to ambient temperature or density was reported to be non-linear, whereas a linear trend on injection pressure was observed. However, the fundamental processes explaining the flame stabilization remained unknown.

Pickett et al. [57] provided experimental evidence on autoigniting gas pockets upstream of the FLOL. Such pockets convect downstream and merge with the primary reaction zone, pulling it closer to the injector. Fuels with shorter ignition delay time (IDT) values produced shorter FLOL values and the experimental trends could not be explained by any existing scaling laws developed for turbulent premixed flame propagation, suggesting that autoignition processes affect FLOL [57].

Developments in diagnostics, including simultaneous high-temperature chemiluminescence and Schlieren imaging, allowed Pickett et al. [58] to identify low-temperature heat-release within the spray tip volume prior to high-temperature ignition. Such phenomena were referred to as the low-temperature combustion or as the "cool-flame".

Figure 2.1. Illustration of the Spray A flame obtained by the LES modeling approach in Publication I. Liquid evaporation and turbulent mixing lead to a nearly premixed low-temperature combustion regime (high CH_2O concentration) and high-temperature diffusion flame (ground state of OH). Soot and NO_x are formed in the central high-temperature region. For reference, nozzle hole diameter is $90\mu\text{m}$ and FLOL is approximately 20 mm. Reprinted and modified with permission from Elsevier.

Idicheria et al. [59] provided quantitative information on fuel-air mixing distribution in well-characterized inert ambient conditions by imaging of Rayleigh scattering from an *n*-heptane ($n\text{-C}_7\text{H}_{16}$) spray. Observations provided evidence on downstream mixing laws being similar to gas-jets and enabled a direct comparison with numerical simulations.

While experiments started to provide quantitative measures, potential in numerical modeling was likewise recognized. However, applying simulations to supplement experiments was still restricted due to lack of comprehensive validation data, mandatory for each particular injection system and ambient conditions considered. Such a problem is still common in combustion sciences but for example, the Turbulent Non-premixed Flame (TNF) workshop [36] had already accomplished to define a series of quantitative experiments on specific atmospheric jet flames and to create a standard database for computational comparisons in the late 1990s.

2.3 The Engine Combustion Network (ECN)

In order to follow the concept behind TNF, Engine Combustion Department of SNL made the prescribed experimental spray mixing and combustion data publicly available via a web portal named as the Engine Combustion Network (ECN) [37]. First, the data archive included only data derived from SNL experiments with *n*-heptane measurements providing the standards. Quickly, in the spirit of TNF guidelines, a baseline spray case was established in 2010, denoted as "Spray A" [60].

In the early phase, international facilities including IFP Energies Nouvelles (IFPEN), Universitat Politècnica de València - CMT-Motores Térmicos (CMT), Eindhoven University of Technology (TU/e) and Spray Combustion Laboratory (SCL) at Caterpillar started to contribute in the experimental sector [61, 62].

To achieve control over the engine relevant initial/boundary conditions without extra complexities, a constant volume ¹ combustion chamber apparatus, utilized already at SNL, was chosen as the baseline approach and measurement guidelines were established for all facilities [47].

In the baseline Spray A configuration, liquid *n*-dodecane ($n\text{-C}_{12}\text{H}_{26}$) is injected with an injection pressure of 150 MPa into a combustion chamber where gas temperature of 900 K, ambient pressure of approximately 6 MPa and molar oxygen concentration of 15% are achieved after the pre-burn event. The target conditions are chosen with relevance to modern engines that use moderate exhaust gas recirculation (EGR) to achieve low-temperature combustion and minimal NO_x emissions. A more detailed list of target conditions is presented in Sec. 3.7.

A single-component diesel surrogate, *n*-dodecane, was chosen as fuel due to its long hydrocarbon structure and suitable thermophysical properties which mimic essential features of diesel spray mixing [60]. Previously, *n*-heptane had been used as a surrogate [57, 59] but its boiling and evaporation properties are less comparable to diesel and, more importantly, *n*-heptane flame produces considerably less soot with a deviating distribution compared to that in a diesel flame [63]. Hence, surrogates containing aromatics and other components were considered, leading to the choice of *n*-dodecane, for which also chemical mechanisms had been already developed.

Work during the past ten years includes new measurements on mixing, ignition and FLOL in the Spray A configuration [64–66] and investigations ensuring consistent measurement techniques among contributing facilities [61, 62]. Brief descriptions of the recent Spray A studies are compiled in Table 2.2, while the ones most relevant for this dissertation are the following: Skeen et al. [49] reported simultaneous laser-diagnostics of formaldehyde (CH_2O) and Schlieren imaging, indicating production of CH_2O upstream of the FLOL and subsequent consumption downstream. Maes et al. [67] investigated the evolution of the flame based on imaging of both the excited and ground state hydroxyl radicals (OH^*/OH), together with CH_2O visualization. Measurements of a split-injection strategy yield a more intermittent combustion during the premixed burn of the first injection, whereas the second fuel injection ignites faster [68, 69].

The recent advancements in experimental techniques have broadened the available foundation for validation of numerical models. For example, data on liquid and vapor mixture distributions, IDT, FLOL and spatial CH_2O and OH fields are used for validation in this dissertation. New experiments, supplemented by numerical investigations yield a refined understanding on diesel combustion processes. As a remark, it is noted that the present simulations results, such as those in Publication I, are largely consistent with the Dec’s conceptual model [13]. For example, Fig. 2.1, shows the low-temperature combustion regime (CH_2O) and fine turbulent diffusion flame structures (OH).

¹Constant volume at SNL, TU/e and IFPEN while constant pressure at CMT and SCL.

2.4 Dual-fuel pilot ignition process

As briefly discussed earlier, most of the recent DF combustion studies are related to experimental works on performance, efficiency and combustion stability issues in laboratory engines with the following observations: 1) The IDT of a diesel spray increases with increasing ambient methane concentration [41, 43, 46, 70]. 2) There is a trade-off relationship between UHC and NO_x emissions: with the increase of engine load and pilot quantity and the advance of pilot diesel injection timing, UHC emissions decrease but NO_x emissions increase [20, 27, 28]. 3) An insufficient pilot ignition may lead to combustion instabilities and result in misfiring and UHC emissions [27, 28, 44, 71].

Some DF engine experiments utilize simple optical diagnostics to obtain information on ignition and flame initiation [46, 72–76]. As illustrated in Fig. 2.2, spatial and temporal resolutions in most optical engine systems are rather limited and combustion dynamics is influenced by swirl and walls, leading to often qualitative conclusions. Figures are obtained from the work by Ahmad et al. [46] and were utilized in Publication III as well.

Only very recently, modern optical diagnostic techniques were utilized in DF pilot ignition experiments in a rapid compression machine (RCM). Schlatter et al. [19] (2016) utilized OH^* chemiluminescence imaging and observed high-temperature ignition at the pilot spray tip. Most recently, Srna et al. [50] (2018) provided evidence on the retarding influence of methane on early low-temperature chemistry by utilizing OH^* chemiluminescence and CH_2O laser diagnostics. The main findings of these experiments are summarized by a visual illustration in Fig. 2.3, where a comparison between a SF spray flame and a DF pilot ignition concept is presented.

According to the studies by Schlatter et al. and Srna et al. [19, 50], there are three common stages during the SF and DF autoignition processes: (I) A turbulent mixing, (II) an early heat-release due to volumetric activation of low-temperature chemistry (LTC), i.e. the first-stage ignition, and (III) a volumetric activation of high-temperature chemistry (HTC), i.e. the second-stage ignition, at

Figure 2.2. (a) A single-cylinder DF engine configuration with a two-hole injector. Natural luminosity imaging of premixed flame initiation (b) and subsequent propagation (c) at 2.97 and 7.7 CAD after TDC, respectively. The optical images are obtained from Publication III.

Figure 2.3. An artistic illustration of the comparison between a conventional single-fuel diesel spray and a dual-fuel pilot ignition process. The art work is based on the authors' numerical work on diesel sprays in Publication I (left) and DF ignition study in Publication III (right). Besides a different oxidizer composition (presence of CH_4 in DF), the key difference is a short injection duration in the DF case.

the spray tip. In case of the SF spray, the high-temperature ignition is followed by a highly luminous lifted quasi-steady diffusion flame, whereas in case of the DF pilot spray, the ignition is followed by a premixed methane-air flame initiation and its subsequent propagation in space (IV). Each of these stages is illustrated in Fig. 2.3 for a conventional diesel spray flame and for a DF pilot spray ignition.

As shown by studies in the Spray A context, within the LTC regime, diesel fuel is decomposed into various intermediate/radical species with a considerable heat release [49, 50]. Following the LTC, chemical progress leads to local high-temperature ignition pockets (i.e. kernels) around the spray tip (III), which has been observed experimentally in both SF [49] and DF configurations [19, 50, 75].

Srna et al. [50] observed in RCM experiments that both the low- and high-temperature ignition stages of diesel fuel are delayed with an increase in ambient methane concentration. For reference, a factor of ~ 1.3 delay in high-temperature ignition between a no-methane and a lean equivalence ratio $\phi_{\text{CH}_4} = 0.5$ cases was found (engine like conditions $T \approx 850\text{ K}$ and $p \approx 25\text{ bar}$ at TDC). The experimental observations indicated that a significant part of the overall delay was attributed to the inhibited low-temperature ignition chemistry.

Grochowina et al. [77] (2018) conducted reacting pilot spray experiments in combustion chamber configuration. They reported poor ignition probability for spray cases with low pilot fuel quantity and, in contrast to experiments in RCM configuration [19, 50], ignition kernels were observed near the injector in cases with low pilot quantity or low ambient temperature. Such differences in ignition

characteristics were presumably attributed to local changes in reactivity due to pilot fuel dilution process and nozzle dribbling [77].

A limited understanding of the autoignition mechanism in DF engine configurations has been noted in the literature [28, 45, 50, 78–81]. For example, Aksu et al. [45] (2016) underlined a need for detailed understanding on mixing and chemistry effects in DF split injection optimization and Nieman et al. [80] (2012) envisioned improvements to RCCI control by optimizing injection strategies.

Aside from the above studies on diesel-methane DF pilot spray ignition, there are experimental works on HCCI [22, 23] and RCCI [24, 25] concepts, where the oxidization of LRF and HRF is present. In such combustion concepts, fuel distributions are largely influenced by the fuel injection strategy, similar to pilot-fuel systems [82, 83]. Additionally, DF related work on hydrogen assisted diesel combustion [84] and swirly atmospheric burner flames with two fuels [85] have been considered in the literature.

Most numerical studies on DF pilot ignition reflect the scarce selection of experiments, targeting mainly full engine configurations by utilizing simplified zero-dimensional (0d) zonal combustion models [70, 86] or RANS computations [24, 80, 82, 87, 88]. In the RANS studies, only a little emphasis is put on combustion models, numerical accuracy, details of the pilot spray, chemical mechanism and turbulence model contribution as well as on validation aspects. Such studies lack the hierarchical validation approach, recognized by the ECN and TNF communities. A more fundamental numerical work on DF diesel-CH₄-air combustion is limited to recent few DNS studies in simplified configurations [89–92], including ignition in decaying homogeneous isotropic turbulence [90] (2016) and ignition in a turbulent mixing layer [92] (2018). The DNS studies indicate that methane consumption is initiated due to heat release and intermediate species originating from the surrogate oxidation process, leading to high-temperature ignition of rich mixtures. For further information, please see the introduction of Publication II.

2.5 Chemical mechanisms for dual-fuel simulations

2.5.1 Selection of chemical mechanism

A challenge in numerical DF combustion modeling is the choice of a chemical mechanism which should be able to cover the chemistry of both the HRF and LRF (e.g. diesel and methane). Burke et al. [93] successfully developed a chemical mechanism for mixtures of dimethyl ether (DME) and methane and validated it against various shock-tube ignition delay time experiments. It was noted that methane influences the early decomposition reactions of DME in homogeneous igniting mixtures. Other than the work by Burke et al. [93], there are no chemical mechanisms developed for diesel surrogate and methane with

experimental measurements for blended fuel mixtures.

In many numerical investigations presented in the literature, the chemical mechanism has often been constructed by merging together the corresponding pilot and primary fuel chemistry sub-mechanisms. Typically, a more compact methane chemistry is added to the existing mechanism designed for the pilot fuel [88, 94]. Huang et al. [95] developed a reduced diesel surrogate-NG mechanism by combining base *n*-heptane mechanism and *n*-butylbenzene-NG sub-mechanisms together. The authors provide validation against SF IDT and laminar flame speed data, but measurements including blended fuel mixtures are not shown.

If the chemical mechanism initially includes both HRF and LRF, it can be, in principle, applied in DF simulations. For example, certain reduced *n*-heptane (pilot fuel) mechanisms, already including methane, have shown to reproduce qualitatively the SF methane-air autoignition and laminar flame speed results close to the GRI 3.0 reference mechanism [90, 96, 97]. However, such mechanisms are not designed in the DF context, hence may not guarantee the correct interaction between long hydrocarbon radicals and high concentrations of methane (and C₁-chemistry). Such aspects are further discussed in Publication II.

2.5.2 Chemical mechanisms for *n*-dodecane

For years, *n*-heptane has been the principal diesel surrogate fuel in numerical SF diesel as well as in DF studies. As discussed earlier, it is a convenient fuel with properties close to diesel, but most importantly, already in 1998 a detailed kinetic reaction mechanism was published by Curran et al. [98]. Hence, *n*-heptane mechanisms have a rather mature status compared to e.g. *n*-dodecane which is otherwise providing better surrogate features (Spray A fuel). There are multiple chemical mechanisms describing the low- and high-temperature decomposition/oxidization chemistry of *n*-dodecane but these mechanisms are still under continuous development and their relative performance may vary considerably depending on equivalence ratio and temperature [99]. As stated by Desantes et al. [99], most *n*-dodecane mechanisms have an acceptable performance for engine simulations in terms of engine efficiency and fuel consumption but deviations from IDT experiments seem to be too high to accurately predict pollutant emissions. In particular, their capability to capture low-temperature chemistry is subject to even higher uncertainties compared to high-temperature ignition [99–101].

Two of the most detailed chemical mechanisms available for long hydrocarbons, including *n*-dodecane are (1) the mechanism for 2-methyl-alkanes up to C₂₀ and *n*-alkanes up to C₁₆ (7200 species and 31400 reactions) by Sarathy et al. [102, 103] from Lawrence Livermore National Laboratory (LLNL) and (2) the mechanism by Ranzi et al. [104] from Politecnico di Milano including up to C₁₆ alkanes and various long oxygenated hydrocarbons (451 species 17848

reactions). As discussed in Sec. 1.4, the larger the mechanism, the higher the computational cost. Hence, smaller, more compact mechanisms have been generated for reacting flow computations. Such reduced/skeletal mechanisms share the most important reactions with the detailed ones but their overall size is considerably smaller. Typically, automated species/reaction removal and chemical lumping strategies are applied with optimization of certain individual reaction rates to achieve agreement with chosen experiments. Due to elimination of redundant reactions and species, the reduced/skeletal mechanism may be bounded by a narrower operating range compared to the detailed one, resulting in e.g. poor low-temperature chemistry description.

Table 2.1 shows some mechanisms applied in the recent *n*-dodecane and ECN Spray A related studies. While the detailed mechanisms are mostly applied for fundamental combustion investigations of homogeneous mixtures or one-dimensional (1d) flames, the reduced mechanisms are utilized in multi-dimensional RANS and LES simulations. The reduced mechanisms by Yao et al. [100], Cai et al. [105] and Frassoldati et al. [106] have performed well against experimental data obtained from RCM [99] and Spray A measurements [107, 108].

In the context of the present dissertation and DF research, the capability of describing *n*-dodecane - CH₄ fuel blends by the mechanisms listed in Table 2.1 should be considered. In spite of the reduced mechanism by Cai et al. [105], CH₄ is included as a separate specie in the mechanisms. However, as shown by Ghaderi Masouleh et al. [109] (c.f. Publication IV), some of the listed mechanisms are incapable to reproduce SF methane-air IDT values. Hence, it may not be enough for DF studies that the mechanism includes CH₄ as a specie. Sensitivity of CH₄ autoignition on specific reactions is extensively studied in the past and the importance of several reaction sets is underlined [93, 110–112].

The reduced POLIMI and the Yao mechanisms are utilized and compared to each other in the DF LES studies presented in Publication II. The mechanisms were chosen due to their good performance to describe both *n*-dodecane and methane oxidization in context of autoignition as well as flame propagation. Furthermore, rationale for the choice of these chemical mechanisms in DF context is further discussed from individual reaction perspective in Publication II.

Table 2.1. Chemical mechanisms applied in Spray A studies. The fifth column (CH₄) indicates whether methane is included in the mechanism. Note, details of the reduction procedure and particular version of the detailed mechanism is given in the respective references.

Mechanism	Species	Reactions	Reduced from	CH ₄	Ref.
LLNL detailed	7200	31400	-	yes	[102, 103]
POLIMI detailed	451	17848	-	yes	[104]
Cai detailed	1692	5804	-	yes	[105]
Westbrook detailed	1282	5030	-	yes	[113]
LLNL reduced	163	887	LLNL det.	yes	[114]
Cai reduced	57	197	LLNL det.	no	[115]
POLIMI reduced	97/130	997/2395	POLIMI det.	yes	[106]
Narayanaswamy	257	1521	LLNL det.	yes	[116]
Luo	106	420	LLNL det.	yes	[117]
Wang	100	432	Westbrook det.	yes	[118]
Yao	54	269	LLNL det.	yes	[100]

2.6 Three-dimensional reacting spray simulations

2.6.1 Overview of sub-models

Early spray simulations were carried out in simple two-dimensional RANS configurations, providing mainly qualitative information on e.g. autoignition features [119, 120]. Only recently, along with the establishment of the ECN, three-dimensional simulations have emerged by using both RANS and LES approaches. Next, some of the recent modeling contributions are discussed, mostly in the context of the ECN.

The publicly available (ECN) data on quantitative *n*-heptane mixing experiments [59] gained rapid attention as high-quality reference data for simulation validation in multiple RANS studies, enabling targeted focus on IDT, FLOL and soot investigations [121–125]. The studies had produced trends comparable to experiments but uncertainties in combustion models were underlined. In particular, models showed less optimal performance in low-temperature conditions where the role of TCI evaluation becomes important, as also reported by the TNF community for atmospheric flames [126].

Two-phase sub-models are also an important part of spray combustion simulations. Typically, the liquid spray dilutes quickly in engine conditions, due to rapid atomization and evaporation. Therefore, the standard approach in RANS/LES is to utilize Lagrangian particle tracking and model the atomization process by applying a certain initial droplet size distribution, while the secondary droplet breakup is taken into account by sub-models. However, recent near-nozzle experiments by Manin et al. [127] and Crua et al. [128] raise concerns regarding the

above assumptions and may indicate a need for real-fluid models in numerical two-phase spray studies [129]. However, further investigations are needed to understand the effect of such real-fluid models on conventional spray modeling.

In many of the early reacting spray studies, the combustion models were based on direct integration of finite-rate chemistry, where a local chemistry sub-problem is solved using the respective cell values for compositions and temperature. Neglecting the subgrid-scale TCI in such simulations is denoted as a well/perfectly-stirred reactor (WSR/PSR) approach. Such a finite-rate chemistry approach is typically restricted to small reduced mechanisms due to its high computational costs (c.f. Fig. 1.6).

A more rigorous but computationally even more challenging approach is provided by the transported PDF (TPDF) method. The TPDF approach has proven to be particularly effective in accounting for TCI in spray studies using RANS [130–135]. Recently, Varna et al. [135] showed that the IDT of Spray A is insensitive to TPDF method's internal mixing model, while influence on FLOL was considerable. The results indicate a less/more important role of TCI on IDT/FLOL. Due to a high computational cost, TPDF is mostly used in RANS context, although its performance has been proven for e.g. atmospheric flames for LES as well [136]. Another advanced approach, the conditional moment closure (CMC) has been applied in both RANS [137, 138] and LES [139] spray combustion context.

Another modeling avenue is given by flamelet-based methods. In such methods, the flame structure is approximated as a set of multiple laminar flames (flamelets), which are defined in the mixture fraction space according to the chosen non-premixed/premixed configuration. Computation of the transient flamelet solution includes coupling between species and energy equations together with finite-rate chemical kinetics. Drrico et al. [140] compared the PSR approach with the multiple representative interactive flamelet (mRIF) combustion model in RANS context. While both PSR and mRIF showed similar ignition characteristics, mRIF performed better in FLOL comparison. In mRIF, a presumed probability density function (PDF) is utilized to account for TCI, as comprehensively studied in the work by Kundu et al. [141].

Besides PSR and TPDF approaches, the mRIF model is considered computationally quite expensive approach as well, since multiple flamelet problems must be interactively solved. In contrast to such an interactive technique, flamelet computations can be carried out as a pre-processing step and generate lookup-tables to reduce computational costs and target the use of larger mechanisms in the LES context. Spray combustion studies using such tabulation techniques have been carried out by e.g. Ameen and Abraham [142] in terms of the unsteady flamelet progress variable (UFPV) model (RANS), Kundu et al. [143] in terms of tabulated flamelet model, and by Bekdemir et al. [144] (LES), Tillou et al. [145] (LES) and Wehrfritz et al. [108] (LES) by the flamelet generated manifold (FGM) model. These studies show that the tabulation method can capture the ignition and flame characteristics of the complex non-premixed spray combustion process.

For further information on the FGM method, see Publication I.

2.6.2 LES of the ECN Spray A case

From the published reacting spray LES studies, there are only a few dedicated to Spray A. Gong et al. [146] utilized finite-rate chemistry with chemistry coordinated mapping (CCM) and with a uniform mesh resolution of $250\text{ }\mu\text{m}$. Similarly, Pei et al. [31] applied finite-rate chemistry and multi-zone acceleration model with a uniform $62.5\text{ }\mu\text{m}$ mesh resolution. Authors reported good agreement in IDT except at ambient temperature below 900 K. The FLOL results were noted to deviate more and the differences were attributed to features of the chemical mechanism. Soot predictions by LES presented much better agreement with experiments compared to their RANS models. In addition, the LES results indicated the possible relevance of ignition kernels as a flame stabilization mechanism and a need for multiple realizations for converged statistics was investigated as well.

Wehrfritz et al. [108] carried out Spray A LES with a uniform $62.5\text{ }\mu\text{m}$ mesh resolution and using the FGM combustion model. Comparison against experimental spatial CH_2O fields was shown and sensitivity of ignition characteristics on the choice of chemical mechanism was noted. Blomberg et al. [139] applied the CMC methodology in the split injection Spray A case obtaining good agreement with the experiments in terms of IDT and spatial appearance of CH_2O .

Recently, Hakim et al. [147] used a calibrated 2-step mechanism together with the dynamic thickened flame model to study the real gas effects and TCI on ignition by utilizing $2\text{ }\mu\text{m}$ mesh resolution near the nozzle. The simulations did not cover flame stabilization, but the authors emphasized the importance of early mixing characteristics on autoignition. Salehi et al. [148] applied sparse-Lagrangian multiple mapping conditioning model in the LES context with rather good agreement against experimental IDT and FLOL measures.

Besides the combustion model or the TCI approach, the underlying chemical mechanism can vastly influence the results. For example, Wehrfritz et al. [108] showed a consistent offset between the mechanism by Ranzi et al. [149] (130 species) and Narayanaswamy et al. [116] (257 species) within the same LES-FGM framework. Pei et al. [31] attributed their IDT overprediction at low ambient temperatures to the lack of accuracy in the chemical mechanism by Luo et al. [150] (103 species). Other examples of mechanisms applied in the LES Spray A context are the mechanism by Som et al. [151] (103 species) in the LES-CCM work by Gong et al. [146] and the mechanism by Yao et al. [152] (54 species) in the recent LES-CMC work by Blomberg et al. [139].

Recently, there have been several publications on soot and radiation properties of the Spray A flame with different model combinations [134, 153, 154]. Authors emphasize that further work is needed to improve quantitative performance of emission predictions across wide-ranging conditions. In addition to complicated spray studies, there are literature dedicated to *n*-dodecane combustion

in Spray A conditions with focus on fundamental ignition, low-temperature chemistry and flame characteristics, see e.g. [155, 156].

In spite of the recent advancements in numerical studies, models still require high-fidelity experimental data for validation and accurate description of the initial and boundary conditions. Hence, all prescribed studies have admittedly greatly benefited of the data provided by the ECN. As indicated in Table 2.2, most of the prescribed LES studies have been published during the progress of this dissertation work, highlighting the trend in international combustion research.

2.7 Research gaps

Based on the recent literature summarized in Table 2.2, there are research gaps in detailed explanation of dependence and sensitivity of DF autoignition chemistry on realistic pilot spray dynamics. In particular, the research gaps can be summarized in terms of the following open questions: 1) What is the mixture composition at the time of ignition? 2) What is the role of low-temperature chemistry prior to high-temperature ignition. 3) By what means, the LRF (methane) influences the low- and high-temperature ignition characteristics of the HRF (diesel)? 4) What is the connection between spray over-leaning and retarded ignition process? 5) What are the key requirements for a chemical mechanism in DF modeling studies?

In addition to the prescribed open questions, there are no detailed LES studies on the topic which would cover the pilot spray dynamics, mixing and complex chemistry. Hence, the present dissertation work approaches these research gaps by utilizing LES.

Table 2.2. Relevant literature on DF pilot ignition and on Spray A combustion according to research type (DF/SF and experiment/simulation). The horizontal lines point out the prescribed categories.

Reference	Year	Type	Relevance
Karim et al. [41]	2003	DF exp.	Review of engine experiments.
Dronniou et al. [75]	2014	DF exp.	Ignition near the cylinder wall.
Schlatter et al. [19]	2016	DF exp.	Chemiluminescence and Schlieren imaging in RCM
Ahmad et al. [46]	2018	DF exp.	Linear relationship between IDT and ϕ_{CH_4} .
Grochowina et al. [77]	2018	DF exp.	Ignition kernels observed near the nozzle.
Srna et al. [50]	2018	DF exp.	Evidence on methane influence on low-temperature chemistry.
Maghbouli et al. [88]	2013	DF sim.	RANS study in engine configuration.
Demosthenous et al. [90]	2016	DF sim.	DNS of <i>n</i> -heptane-CH ₄ -air ignition in isotropic homogeneous turbulence.
Jin et al. [92]	2018	DF sim.	DNS of turbulent mixing layer between DME and methane-air mixture streams.
Pickett et al. [60]	2010	SF exp.	Establishment of ECN Spray A.
Pickett et al. [64]	2011	SF exp.	Spray A liquid and vapor penetration.
Payri et al. [65]	2012	SF exp.	Fuel temperature influence on ignition and FLOL.
Bardi et al. [61, 62]	2012	SF exp.	Comparison of measurement techniques between the ECN contributors.
Benajes et al. [66]	2013	SF exp.	Spray A ignition and FLOL.
Manin et al. [127]	2014	SF exp.	Spray A near nozzle two-phase dynamics. No clear indications of droplets.
Skeen et al. [49]	2015	SF exp.	Simultaneous CH ₂ O and Schlieren imaging.
Skeen et al. [49]	2015	SF exp.	Spray A split injection.
Maes et al. [67]	2016	SF exp.	Imaging of OH [*] , OH and CH ₂ O.
Maes et al. [69]	2017	SF exp.	Spray A split injection.
Payri et al. [157]	2016	SF exp.	Influence of injector nozzle geometry on spray mixing, ignition and FLOL.
Garcia-Oliver et al. [158]	2017	SF exp.	Axial velocity measurements: self-similarity holds under reacting conditions.
Gong et al. [146]	2014	SF sim.	LES with 250 μ m resolution.
Pei et al. [131]	2015	SF sim.	RANS with TPDF method.
Pei et al. [31]	2015	SF sim.	LES with 62.5 μ m resolution and finite-rate chemistry.
Wehrfritz et al. [108]	2016	SF sim.	LES with 62.5 μ m resolution and FGM.
Hakim et al. [147]	2016	SF sim.	LES with focus on real-gas thermodynamics.
Blomberg et al. [139]	2016	SF sim.	LES of split injection.
Kundu et al. [143]	2017	SF sim.	LES with tabulated flamelet model.

3. Methods

3.1 Governing equations

As introduced in section 1.4, the Eulerian gas phase is described by the compressible Navier–Stokes equations. The LES formulation of the equation system is based on a mathematical filtering procedure, intended to decompose the variables to directly resolved and unresolved scales via cut-off parameter (grid resolution). The Favre-filtered¹ LES formulation for the continuity, momentum and energy equations is the following:

$$\frac{\partial \bar{\rho}}{\partial t} + \frac{\partial \bar{\rho} \tilde{u}_i}{\partial x_i} = \bar{S}_\rho, \quad (3.1)$$

$$\frac{\partial (\bar{\rho} \tilde{u}_i)}{\partial t} + \frac{\partial (\bar{\rho} \tilde{u}_i \tilde{u}_j)}{\partial x_j} = \frac{\partial}{\partial x_j} (-\bar{p} \delta_{ij} + \bar{\rho} \tilde{u}_i \tilde{u}_j - \bar{\rho} \tilde{u}_i \tilde{u}_j + \bar{\tau}_{ij}) + \bar{S}_{u,i}, \quad (3.2)$$

$$\frac{\partial (\bar{\rho} \tilde{Y}_k)}{\partial t} + \frac{\partial (\bar{\rho} \tilde{u}_i \tilde{Y}_k)}{\partial x_i} = \frac{\partial}{\partial x_i} \left(\bar{\rho} \tilde{u}_i \tilde{Y}_k - \bar{\rho} \tilde{u}_i \tilde{Y}_k + \bar{\rho} \tilde{D} \frac{\partial \tilde{Y}_k}{\partial x_i} \right) + \bar{S}_{Y_k} + \bar{\omega}_k, \quad (3.3)$$

$$\frac{\partial (\bar{\rho} \tilde{h}_t)}{\partial t} + \frac{\partial (\bar{\rho} \tilde{u}_j \tilde{h}_t)}{\partial x_j} = \frac{\partial \bar{p}}{\partial t} + \frac{\partial}{\partial x_j} \left(\bar{\rho} \tilde{u}_j \tilde{h}_t - \bar{\rho} \tilde{u}_j \tilde{h}_t + \frac{\bar{\lambda}}{\bar{c}_p} \frac{\partial \tilde{h}_s}{\partial x_j} \right) + \bar{S}_h + \bar{\omega}_h, \quad (3.4)$$

where $\bar{\rho}$, $\tilde{u}_i$, $\bar{p}$, $\tilde{Y}_k$, $\tilde{h}_s$, $\tilde{\tau}_{ij}$, denote the filtered density, velocity, pressure, species k , sensible enthalpy and viscous stress tensor, respectively. In particular, the overbar denotes an unweighted ensemble average, whereas the tilde ($\sim$) denotes a density-weighted ensemble average. A unity Lewis number is assumed for all species, and thus $D = \lambda/(\rho c_p)$ with c_p and λ denoting the heat capacity and thermal conductivity of the gas mixture, respectively. In Eq. (3.4) the total enthalpy $\tilde{h}_t$ is defined as a sum of the sensible enthalpy and the specific kinetic energy,

$$\tilde{h}_t = \tilde{h}_s + \frac{\tilde{u}_i \tilde{u}_i}{2}. \quad (3.5)$$

¹Specific for compressible flows, denoting density weighted filtering approach.

The viscous stress tensor is defined as

$$\overline{\tau}_{ij} = \bar{\mu} \left(\frac{\partial \tilde{u}_i}{\partial x_j} + \frac{\partial \tilde{u}_j}{\partial x_i} - \frac{2}{3} \frac{\partial \tilde{u}_k}{\partial x_k} \delta_{ij} \right), \quad (3.6)$$

where $\bar{\mu}$ is the dynamic viscosity. The source terms $\overline{S}_\rho$, $\overline{S}_{u,i}$, $\overline{S}_{Y_k}$ and $\overline{S}_h$ allow the coupling between liquid and gaseous phases with respect to mass, momentum, species and energy. The net production/consumption rate for the species k is denoted by $\overline{\omega}_k$ and the heat release rate (HRR) in Eq. (3.4) is formulated as $\overline{\omega}_h = \sum_k \Delta h_{f,k}^o \overline{\omega}_k$, where $\Delta h_{f,k}^o$ is the enthalpy of formation. Additional mechanical source terms arising from compressible Navier–Stokes are neglected in the filtered enthalpy equation. Finally, the system of equations is closed by the ideal gas law. The filtering operation introduces additional unclosed terms on the right side of Eqs. (3.2-3.4) which require modeling efforts. These are typically denoted as the subgrid-scale (SGS) terms and are further discussed in following sections.

3.2 Discretization of the governing equations

The governing equations (3.1-3.4) are solved with the finite volume method, often applied in implementations for conservation equations in multiphysics problems and complex geometries. The implementation is based on a standard open-source CFD library OpenFOAM-2.4.x [159] which enables use of unstructured meshes for domain discretization. For further information on theoretical grounds of the finite-volume method, reader is referred to a textbook by Hirsch [160] and on implementation details, dissertation work by Jasak [161]. Next, a brief overview on the applied numerical schemes is given.

Within the finite volume method, the properties of the numerical solution depend to large extent on discrete interpolation techniques applied for each individual term in Eqs. (3.1-3.4). The diffusion terms are discretized by 2nd order central schemes while the convection terms require particular attention due to the high non-linearity. Hence, the convective fluxes are interpolated by the non-linear flux limiter, developed by Jasak et al. [162]. For further information on the applied limiter parameter sensitivity, reader is referred to Publication I. The time integration is based on an implicit, three time-level, and second order accurate scheme. The pressure-velocity coupling is implemented in terms of the reacting PISO (Pressure Implicit with Splitting of Operator) algorithm [163].

3.3 Spray modeling

As discussed in literature review section, a standard practice in high-velocity spray modeling is to assume a short liquid core and rapid atomization. Hence, the Lagrangian particle tracking method is applied for the description of liquid

phase. Here, the primary breakup is implicitly considered by sampling the computational LPT parcels from the Rosin-Rammler size distribution with parameters that lead to the initial Sauter mean diameter of $6\text{ }\mu\text{m}$.

Equations of motion describing the LPT system together with model sensitivity tests considering the present implementation can be found from the work by Wehrfritz et al. [164]. Following their work, the secondary breakup is modeled by the KHRT model [165, 166] with parameters available in Ref. [167]. Heat and mass transfer between two phases are modeled according to the standard correlations by Frössling [168], Ranz and Marshall [169, 170]. It is worth noting that the LPT setup remains the same in Publications I–III.

3.4 Integration of finite-rate chemistry

While the FGM combustion model is applied in Publication I, the combustion modeling in Publications II–III is based on the direct integration of finite-rate chemistry. Here we introduce the latter approach due to its generality, but an overview of the FGM is also given later in Sec. 3.6.

The filtered chemical source terms $\bar{\omega}_k$ and $\bar{\omega}_h$ in Eqs. (3.3) and (3.4) account for the net production/consumption of species and heat, respectively. Since chemical time-scales are much smaller than fluid-dynamic ones in many practical systems, the terms introduce high stiffness to the system of equations. Therefore, an operator-splitting is performed to separate the transport of species and energy from the chemical reactions within a CFD time step [171–173].

When applying operator-splitting, change of the thermochemical composition over a CFD time step is obtained from a solution of the system of ordinary differential equations (ODE), derived from chemical kinetics [174], that is:

$$f = \frac{\partial \Phi}{\partial t} = \left\{ \frac{\partial T}{\partial t}, \frac{\partial Y_1}{\partial t}, \frac{\partial Y_2}{\partial t}, \dots, \frac{\partial Y_{N_{\text{sp}}-1}}{\partial t} \right\}^T, \quad (3.7)$$

where

$$\frac{\partial T}{\partial t} = \frac{-1}{\rho c_p} \sum_{k=1}^{N_{\text{sp}}} h_k W_k \dot{\omega}_k, \quad (3.8)$$

$$\frac{\partial Y_k}{\partial t} = \frac{W_k}{\rho} \dot{\omega}_k \quad k = 1, \dots, N_{\text{sp}} - 1, \quad (3.9)$$

where temperature T and species mass fractions are the primary variables and $\dot{\omega}_k$ is the k th species overall production rate². It is worth noting that the primary variable can be chosen to other e.g. molar fraction or concentration, but here Y_i is chosen for simplicity and to ensure a mathematically consistent state vector [175]. Following Niemeyer et al. [174], the rate of production term can be

²Note, here $\dot{\omega}_k$ is scaled by molecular weight (W_k) compared to the filtered version in Eq. (3.3).

defined as follows

$$\dot{\omega}_k = \sum_{i=1}^{N_{\text{reac}}} \nu_{ki} q_i, \quad (3.10)$$

where N_{reac} is the number of reactions, ν_{ki} is the overall stoichiometric coefficient for species k in reaction i , and q_i is the rate-of-progress for reaction i . These are defined by

$$\nu_{ki} = \nu''_{ki} - \nu'_{ki} \quad \text{and} \quad (3.11)$$

$$q_i = c_i R_i, \quad (3.12)$$

where ν''_{ki} and ν'_{ki} are the product and reactant stoichiometric coefficients (respectively) of species k in reaction i . The base rate-of-progress for the i th reversible reaction R_i is given by

$$R_i = R_{f,i} - R_{r,i}, \quad (3.13)$$

$$R_{f,i} = k_{f,i} \prod_{j=1}^{N_{\text{sp}}} [X_j]^{\nu'_{ji}}, \quad \text{and} \quad (3.14)$$

$$R_{r,i} = k_{r,i} \prod_{j=1}^{N_{\text{sp}}} [X_j]^{\nu''_{ji}}, \quad (3.15)$$

where $k_{f,i}$ and $k_{r,i}$ are the forward and reverse reaction rate coefficients for the i th reaction, respectively. The coefficient c_i accounts for the third-body/pressure modification, further defined in [174].

The forward reaction rate coefficient $k_{f,i}$ is given by the three-parameter Arrhenius expression:

$$k_{f,i} = A_i T^{\beta_i} \exp\left(-\frac{T_{a,i}}{T}\right), \quad (3.16)$$

where A_i is the pre-exponential factor, β_i is the temperature exponent, and $T_{a,i}$ is the activation temperature given by $T_{a,i} = E_{a,i}/\mathcal{R}$, where $\mathcal{R}$ is gas constant. The reverse rate coefficient is zero for irreversible reactions, while for reversible reactions, it is obtained either explicitly via reverse Arrhenius parameters or via forward rate coefficient and the equilibrium constant. In-detail derivation of e.g the third-body modifications and equilibrium constant can be found from the work by Niemeyer et al. [174].

The above stiff ODE system is solved independently in each finite volume cell by the semi-implicit Euler method (abbr. Seulex) [176]. The Seulex algorithm belongs to the class of extrapolation methods and offers an efficient and high-order (here up to 12th order) solution for stiff problems [176, 177]. The relative and absolute tolerances of the Seulex algorithm are set to $1 \cdot 10^{-6}$ and $1 \cdot 10^{-10}$, respectively, which were found sufficient in Author's tests as well as in Ref. [177]. A schematic of the solution procedure is provided in Fig. 3.1.

Figure 3.1. A schematic representation of the implementation, coupling the pyJac chemistry package and LAPACK linear algebra routines into the OpenFOAM ODE solution procedure.

Most implicit stiff ODE solvers require the computation of a system Jacobian during the integration process. Typically, the Jacobian evaluation is considered via finite difference approach which may account for a large share of the overall ODE integration cost. However, here an analytic formulation of the ODE system Jacobian is utilized, yielding considerable speed-up in the evaluation time, as illustrated in Fig. 3.2. The implementation of the analytic approach is provided by the optimized open-source *pyJac* package, including an efficient evaluation for the reaction rates in Eq. (3.10) [174]. In addition, the analytic approach yields an accurate representation of the Jacobian, enhancing the solution convergence compared to the finite difference approach when very stiff systems are considered. Furthermore, the default OpenFOAM implementation of the Seulex algorithm is modified by the Author to use optimized LAPACK routines [178] for the linear algebra operations.

After obtaining a converged integration for ODE system, the chemical source terms in Eqs. (3.3) and (3.4) are formulated as a finite difference between the initial value and the ODE solution, being only first order accurate from the operator splitting point of view [172, 179]. However, the time step used in the current LES is 80 ns, which is assumed to ensure a sufficient resolution for the operator splitting throughout the unsteady ignition problem. Similar splitting techniques with relatively small time steps have been previously applied in turbulent combustion context with successful validation against the DNS [180, 181] and experimental [182, 183] data.

For obtaining further speed-up, a computational load of the chemistry computation is dynamically distributed over all available processors using the Message Passing Interface (MPI) protocol. The dynamic load balancing (i.e. optimal load distribution) is based on the local time consumption of the ODE solver and the implementation is made by the Author.

Figure 3.2. Mean computational evaluation time of different size system Jacobians by finite differences as well as with the analytic approach provided by the pyJac package. Reproduced from work by Niemeyer et al. [174] with permission from Elsevier.

3.5 Subgrid-scale modeling

The Favre filtering results in additional unclosed terms on the right-hand side of Eqs. (3.2-3.4) that require modeling efforts. Essentially, these subgrid-scale (SGS) terms describe the dissipation of eddies at the unresolved scales. Various SGS models have been introduced in the literature and previous spray studies include e.g. dynamic Smagorinsky type models [147, 184], dynamic structure models [185, 186] and one-equation eddy models [31, 187]. In principle, models introduce explicitly additional dissipation into the system. Alternatively, such dissipation can be introduced and implicitly controlled locally by choosing a dissipative numerical scheme for the convection terms. The underlying assumption is that the numerical dissipation introduces a similar influence on the coherent scales as the physical energy dissipation at subgrid-scales. Such a modeling approach is denoted as an implicit LES (ILES) or a monotonically integrated LES (MILES) and the theoretical grounds on the similarity between the implicit and explicit approaches is discussed in Refs. [188–190]. Previously, the ILES approach has been applied to free shear flows [191, 192], supersonic jets [193, 194] and supersonic combustion [195].

The ILES approach has been applied in Publications I–III with implementation following the previous work by Wehrfritz et al. [108]. In particular, treatment of the convective terms is considered via the non-linear flux limiter, termed as the Gamma scheme [162]. The Gamma scheme requires an input parameter, k , which is chosen in order to control and maintain the spatial accuracy. According to experience from studies by Wehrfritz et al. [108, 164] and further investigations in Publication I, a value $k = 0.3$ was chosen for the momentum equation while $k = 1.0$ is chosen for the scalars to ensure a bounded

total variation diminishing solution (a low value indicates less dissipation).

The effect of turbulence-chemistry interactions (TCI) is considered with two different approaches in this dissertation. Firstly, in Publication I, a presumed-PDF method is utilized in the FGM combustion model to account for TCI (c.f. next section). Secondly, the direct integration of finite-rate chemistry approach in Publications II–III apply the first order closure hypothesis, i.e. the net reaction rate $\bar{\omega}_k \approx \omega_k(\tilde{Y}_i, \tilde{T}, \bar{p})$ is applied for the chemical source terms in Eq. (3.3-3.4). The latter "no TCI model" approach is considered under assumption that a relatively high grid resolution together with finite-rate chemistry will yield the major features of ignition chemistry in a reaction zone, broadened by intense turbulent mixing.

Recently, Pei et al. [31] applied the same first-order hypothesis (i.e. the PSR approach) in the Spray A LES context and obtained good results with a grid spacing equivalent to one used in Publications I–III. It is worth noting that spray autoignition problem has been reported to be less sensitive to SGS modeling parameters compared to e.g. flame stabilization problem [131, 135]. Hence, the work in Publications II–III is mainly focused on autoignition phenomena. Furthermore, multiple LES studies with this approach have shown a rather good agreement against experiments when a relatively high grid resolution is applied [182, 196, 197]. However, author suggests careful consideration and grid resolution sensitivity tests if the present approach is utilized in e.g. flame propagation/stabilization problems.

Further discussion and investigations on the present approach is provided in Publication II. In particular, sensitivity of IDT on mesh resolution is noted rather low and when utilizing the same chemical mechanism, the flamelet-based FGM method and the finite-rate chemistry approaches provide IDT estimates within 1% margin.

3.6 Role of flamelet generated manifolds in single-fuel and dual-fuel combustion

With relevance to Publication I, next a brief overview on the FGM model (single-fuel only) is given. In addition, restrictions of the model from DF pilot injection simulation point of view are discussed. It is worth noting that instead of FGM, integration of finite-rate chemistry is utilized in Publications II–III.

The FGM method is based on the theoretical formulation of the intrinsic low-dimensional manifold method (ILDM) [198] and relies on the assumption that a high-dimensional state space of chemical species can be largely recovered by a suitable low-dimensional manifold [199]. In practice, the low-dimensional manifold is represented by a look-up table, created from laminar flamelet solutions as a pre-processing step.

In Publication I, one-dimensional unsteady laminar counterflow diffusion (CD) flames are chosen as a canonical flamelet configuration. The CD flamelet

allows a description of autoignition and diffusion flame features as a function of mixture fraction Z , which is necessary for non-premixed spray flames. A series of flamelet solutions is computed to create a two-dimensional manifold, characterized by two control variables. Typical for non-premixed combustion models, these control variables are denoted by Z and reaction progress variable $\mathcal{Y}$, such that any thermo-chemical quantity ψ from the flamelet solution can be expressed as

$$\psi = \psi(Z, \mathcal{Y}). \quad (3.17)$$

The progress variable is defined so that it enables a monotonic description of the ignition and reaction progress within the diffusion flame. In Publication I, $\mathcal{Y}$ is defined by a linear combination of reaction products

$$\mathcal{Y} = \frac{Y_{\text{CO}_2}}{W_{\text{CO}_2}} + \frac{Y_{\text{CO}}}{W_{\text{CO}}} + \frac{Y_{\text{CH}_2\text{O}}}{W_{\text{CH}_2\text{O}}}. \quad (3.18)$$

The first onset of ignition is captured by the contribution of CH_2O and progress towards the steady flame by CO and CO_2 species.

In order to formulate a filtered version of ψ , including TCI, an assumption of statistical independence between the mixture fraction and the normalized progress variable ($\mathcal{C}$) is assumed³ [200]:

$$\tilde{\psi} = \int_0^1 \int_0^1 \psi(Z, \mathcal{C}) \beta(Z; \tilde{Z}, \widetilde{Z''^2}) \delta(\tilde{\mathcal{C}} - \mathcal{C}) d\mathcal{C} dZ, \quad (3.19)$$

where the presumed beta and delta-functions are used to approximate the mixture fraction and progress variable subgrid distributions, respectively [201]. In practice, the look-up table is extended to a third dimension by introducing mixture fraction variance ($\widetilde{Z''^2}$) as an additional control variable. The implementation of FGM includes solution of transport equations for Z and $\mathcal{Y}$ while $\widetilde{Z''^2}$ is obtained from an algebraic model [202]. Importantly, the progress of chemistry is described by the progress variable source term $\bar{\omega}_{\mathcal{Y}}$ in the respective transport equation and is sampled from the FGM look-up table according to local Z , $\mathcal{C}$ and $\widetilde{Z''^2}$ values. For further information on the theoretical and practical aspects of the FGM can be found from the earlier work by Wehrfritz et al. [108] and from Publication I.

Extending the FGM method to cover autoignition and flame initiation physics in DF pilot spray configuration would require efforts on theoretical reformulation and modifications to the prescribed implementation. Firstly, in case of two fuels, a single progress variable may not provide a unique description of chemical state at given mixture [203]. Secondly, depending on pilot injection quantity and duration, and the corresponding mixing and autoignition time scales, the pilot fuel may experience a non-premixed, premixed or partially premixed ignition and flame characteristics. Extending FGM to such mixed combustion modes has been, however, considered in literature for single-fuel cases by introducing

³See Publication I for the definition of ($\mathcal{C}$) and discussion on the underlying assumption.

additional control variables resulting in high-dimensional (> 4 dim.) manifolds [204, 205].

Furthermore, injection strategies including two or more shorter injections is constantly investigated as an option to reduce soot emissions in diesel engines [68] and to control stability in DF engines [45]. Hence, it is desired that the combustion model is able to cover both DF and sequential injection capability. In such a case, utilization of a constant strain rate boundary condition for one-dimensional transient flamelet simulations, as done in e.g. Publication I, may not be enough to capture the essential ignition characteristics.

Besides the possible prescribed issues, engine-scale simulations may require the model to account for the influence of exhaust-gas recirculation, charge compression and heat-loss effects, which can be accomplished by, again, increasing the number of control variables [204, 205]. However, increase in manifold dimensions complicate the pre-processing step and may introduce possible practical issues with memory consumption and efficient multidimensional interpolation from the non-linear manifold.

In retrospect, there may be limitations in other combustion models as well with respect to DF modeling. For example, mRIF and CMC depend directly on mixture fraction conditioning, complicating the applicability in DF mode and/or in case of multiple short pilot injections. In such cases, a two-dimensional CMC implementation may be needed as applied in Refs. [139, 206]. The TPDF approach would be able to capture the essential physics (TCI) without any modifications. This is because 1) the model computes chemistry source terms explicitly without approximations, 2) no assumption on mixing state (premixed/non-premixed) is made, and 3) no assumption on relative ratio between mixing and chemical time scale is made [132]. However, due to such a rigorous approach, the computational cost is estimated over a magnitude higher compared to e.g. mRIF and CMC models [133].

3.7 Simulation configuration

The present LES computations are carried out in a numerical configuration corresponding the ECN Spray A experiments. Liquid *n*-dodecane is injected with a 150 MPa pressure from a 90- μm diameter nozzle hole into a constant volume chamber with thermodynamical conditions presented in Table 3.1. The discretized CFD domain shares the same volume with the experimental combustion vessel at SNL [48] and a uniform 62.5 μm cell size is applied throughout the spray penetration regime.

For the numerical DF cases, the same configuration is considered, but methane is added to form a $\phi_{\text{CH}_4} = 0.5$ ambient mixture (equivalence ratio w.r.t CH_4 -air only). Other concentrations are modified such that the molar oxygen concentration is constant 15% in both cases.

Table 3.1. Common specifications for the simulation cases.

	ECN Spray A	DF cases
Injection conditions		
Fuel	<i>n</i> -C ₁₂ H ₂₆	<i>n</i> -C ₁₂ H ₂₆
Nominal nozzle diameter, <i>D</i>	90 μm	90 μm
Fuel temperature	363 K	363 K
Injection pressure	150 MPa	150 MPa
Ambient conditions		
Temperature	900 K	900 K
Density	22.8 kg/m ³	22.8 kg/m ³
O ₂ % (molar)	15.0	15.0
CO ₂ % (molar)	6.230	5.955
H ₂ O % (molar)	3.620	3.460
N ₂ % (molar)	75.150	71.835
CH ₄ % (molar)	0	3.750
ϕ_{CH_4}	0	0.5
Z_{st}	0.0435	0.0234

4. Summary of Results

The contribution of this dissertation to the field of numerical turbulent combustion research is summarized in the following sections. It is worth noting that in order to ensure a clear illustration, some figures have been modified compared to the published versions.

4.1 Publication I

In Publication I the influence of injection pressure on mixing, ignition and flame characteristics in the ECN Spray A case is considered. The performance of the LES-FGM implementation, based on an earlier work by Wehrfritz et al. [108], is investigated and potential to capture flame stabilization is considered from theoretical and practical model point of views. Three reacting LES simulations with 50, 100 and 150 MPa injection pressures were carried out. Figure 4.1 shows an overview of the igniting spray case.

The first part of Publication I is involved with validation of spray-submodels in non-reacting (0% O₂) conditions. A good agreement in liquid and vapor penetration measures was obtained for all three cases. However, comparison against experimental mean radial Z profile data indicated a more intense dilution for the simulation cases at locations farther than 20 mm downstream from the nozzle.

The reacting simulation cases were validated against IDT, FLOL and combustion vessel pressure rise. Additionally, a qualitative comparison of spatial hydroxyl field to experimental laser diagnostics was considered. The main findings of the current work on single-fuel Spray A ignition are:

1. The LES results show weaker sensitivity of IDT on injection pressure compared with experiments, see Fig. 4.2a.
2. The FLOL is predicted well for the 50 MPa case but approximately 14 % deviation is found for the 150 MPa case, see Fig. 4.2b.
3. Numerical examples show a high sensitivity of the reaction progress (FGM

model) to local mixture formation at axial locations near the FLOL, depicting the uncertainty in results.

4. Igniting gas pockets were observed near the FLOL (c.f. Fig.4.1 (I-III)), indicating that the present FGM model setup is able to capture autoignition-based flame stabilization.
5. A higher injection pressure was noted to suppress the ignition kernel formation and evolution, leading to higher FLOL values.

Figure 4.1. Time evolution for the 150 MPa case showing autoignition at spray tip and a stabilized diffusion flame structure. A zoomed view (I) shows the role of igniting gas pockets (II) and their growth (III) in the flame stabilization phenomenon.

Figure 4.2. Comparison of (a) IDT and (b) FLOL against experiments.

4.2 Publication II

In Publication II, LES with a finite-rate chemistry model was utilized for the investigation of a DF ignition process where a diesel surrogate (*n*-dodecane) spray ignites a lean methane-air mixture in engine relevant conditions. The spray setup corresponds to the ECN Spray A configuration and extensive validation was carried out in SF conditions, similar to Publication I. Prior to LES investigations, the applied chemical mechanisms were ensured to capture the essential autoignition and flame propagation features, as indicated in Fig. 4.3.

The baseline Spray A target conditions were modified to create a DF relevant model problem by adding CH_4 to the ambient oxidizer composition with a methane-air equivalence ratio of 0.5. The rest of the ECN Spray A case configuration remained unaltered. The main findings of the current work on DF spray ignition are:

1. DF ignition is a volumetric process and can be separated to three stages:
 - a) first-stage ignition, i.e. early heat release due to low-temperature chemistry,
 - b) second-stage ignition at the spray tip, i.e. activation of high-temperature chemistry and
 - c) premixed flame initiation (c.f. Fig. 4.4).
2. Ambient CH_4 influences the low- and high-temperature chemistry throughout the ignition process. Both first- and second-stage ignition processes are delayed compared to the single-fuel reference case (c.f. Fig. 4.5a).
3. The chemical mechanisms by Yao et al. (2017) and Frassoldati et al. (2015) depict the similar qualitative DF ignition process with the most deviation in time scales related to the low-temperature chemistry.
4. High-temperature ignition in LES appears in rich mixtures (c.f. Fig. 4.5b).

Figure 4.3. Comparison of chemical mechanisms in SF methane-air conditions with respect to (a) IDT at high pressures and (b) laminar flame speed in 1 bar and 300 K.

Figure 4.4. Volume rendered artistic illustration of the characteristic features of a typical spray ignition process including: liquid phase and evaporation (I), early low-temperature reactions in the rich core of the spray (II), low-temperature chemistry region (III) and the high-temperature chemistry region (IV) leading to ignition kernels (V). The colors correspond to spray fuel vapor $Z > 0.08$ (green), RO_2 (blue) and $T > 1700 \text{ K}$ (orange).

Figure 4.5. (a) LES results indicate that production of both, RO_2 (LTC) and OH (HTC) is inhibited in DF conditions compared to the SF case. (b) Production of LTC related species and high-temperature ignition appear in rich mixtures.

4.3 Publication III

Publication III is a direct continuation of the work started in Publication II, where the injection duration (t_{inj}) of the pilot fuel exceeded substantially the characteristic autoignition time scale. In Publication III, the pilot spray ignition problem is studied at a fixed mass flow rate but with a varying t_{inj} . The focus is to understand the influence of pilot quantity on spray dilution process and on low- and high-temperature chemistry. It is worth noting that there is no experimental data available for sprays with $t_{inj} < 0.5\text{ms}$ in the ECN Spray A context.

In addition to LES, experimental work on a single-cylinder laboratory DF engine was carried out by Z. Ahmad (co-author). The experimental configuration deviated from the numerical one but provided phenomenological evidence on autoignition characteristics in the context of engine applications.

The main findings of the current work on DF spray ignition are:

1. Both engine experiments and LES simulations indicate that there is a threshold value for the injection duration, below which the high-temperature IDT is considerably increased, see Fig. 4.6.
2. The onset of low-temperature chemistry (first-stage IDT) is not influenced by t_{inj} as much as the high-temperature chemistry (second-stage IDT), see Fig. 4.6b.
3. The size of the initial ignition kernel is decreased with decrease in pilot quantity. A lower volumetric growth rate is observed for initially smaller flame kernels (low pilot quantity), see Fig. 4.7.
4. The analysis implies that the sensitivity of ignition chemistry on mixing is time-dependent and connected to the end of injection.
5. Cumulative heat release is dominated by low/high-temperature chemistry at low/high t_{inj} values, see Fig. 4.8.

Summary of Results

Figure 4.6. Trends of the IDT as a function of pilot injection duration in (a) engine experiments and (b) LES cases.

Figure 4.7. 3d view at the time of ignition ($t = t_{2nd}^*$) (top row) and at $t = t_{2nd}^* + 0.13$ ms (bottom row). Translucent gray and green isosurfaces correspond to $Z = 1 \cdot 10^{-4}$ and Z_{st} , respectively. The blue isovolumes illustrate premixed flame initiation (I: $T > 1400$ K), indicating decrease in original ignition kernel size (II,III) and their respective growth rate with decrease in end-of-injection.

Figure 4.8. Relative fraction of total heat release from LTC, pre-HTC and HTC up to $t = 1.1t^*$ for all DF cases.

4.4 Publication IV

In Publication IV the DF ignition is considered from a simplified homogeneous mixture point of view. In particular, multiple zero-dimensional chemical kinetics computations were carried out, assuming constant volume and homogeneous mixture within the system. The focus was two-fold: First, the performance of detailed and reduced chemical mechanisms was compared against available experimental IDT data in both single-fuel *n*-dodecane-air and CH₄-air mixtures. Second, ignition of mixtures containing both fuels was investigated with focus on the ratio of the fuels and role of radical species. In addition to homogeneous ignition studies, impact of DF mixture on laminar flame speed was extensively investigated.

The main findings of the current work are:

1. Detailed and reduced mechanisms produce comparable results against shock-tube data obtained for *n*-dodecane-air mixtures at 20 bar pressure, see Fig. 4.9a. Larger deviations appear at higher pressures, see Publication II and Ref. [107] for further information.
2. Large deviation in predicted CH₄-air IDT values was observed for some mechanisms, see Fig. 4.9b.
3. The molar *n*-dodecane/methane ratio ($\alpha = \frac{X_{C_{12}H_{26}}}{X_{CH_4}}$) is an important parameter to characterize the influence of DF mixture state on the IDT, see Fig. 4.10.
4. Laminar flame speeds for the DF mixtures are shown to be bounded by the corresponding SF flame speeds.

Figure 4.9. Comparison of computational IDT values to available single-fuel shock-tube experiments at multiple temperature levels. Results are based on 0d homogeneous ignition problems for (a) single-fuel *n*-dodecane at stoichiometric conditions and (b) single-fuel methane-air mixtures in different high-pressure/temperature conditions (data sets 1-16)

Figure 4.10. Impact of molar *n*-dodecane/methane ratio ($\alpha = \frac{X_{C_{12}H_{26}}}{X_{CH_4}}$) on IDT characteristics as a function of temperature.

4.5 Limitations

Limitations of the present numerical work are tightly connected to the generally known uncertainties regarding the high-velocity multiphase spray, turbulence, combustion and emission modeling. Another place for improvement is the lack of high-fidelity DF experiments, which prevents quantitative comparison and generalization of the presented computational results. Next, the prescribed issues are briefly discussed.

In the present study, the modeling of liquid spray was considered according to the standard Lagrangian particle tracking approach, which requires considerable parameter tuning to achieve a fair agreement against available experimental data. Hence, large changes in injection parameters or ambient conditions may require additional efforts for obtaining the level of accuracy presented in Publications I-III.

The grid resolution influences both fuel mixing and combustion characteristics and is closely connected to performance of the chosen SGS/TCI model (ILES). Presently, the core part of the high-velocity spray jet is not resolved with resolution conventionally suggested in e.g. gas jet studies. This may pose a limited description for the early parts of the spray mixing. However, as the provided comparison against available experimental data on mixing shows, the mean trends are well captured by the present grid. Similarly, the present grid is not able to resolve the premixed flame, leading to uncertainties with respect to the use of no-model TCI approach.

To restrict the scope of the dissertation, and due to limitations of the present TCI treatment (c.f. Sec. 3.5), focus of the DF studies were targeted to ignition problems only, neglecting the subsequent premixed flame propagation. However, as indicated in literature, overall consumption of the gas-air charge is crucial

for the engine performance. Hence, for example the influence of spray induced turbulence on flame propagation would be an important area to explore but would require comparison between different TCI methods.

4.6 Overall conclusions

The main goal of this dissertation was to investigate numerically the DF pilot ignition process, where diesel surrogate is injected into a premixed methane-air mixture at engine relevant conditions. The investigations were considered by utilizing 0d, 1d and 3d simulations. The reactive pilot spray was modeled in 3d by utilizing the LES solver and finite-rate chemistry. A major effort was put on implementing a highly efficient chemistry solution solver, which was achieved by coupling two open source libraries OpenFOAM and pyJac together. Altogether there were four overall objectives, provided in Sec. 1.5.

Validation of the LES configuration was considered by comparing the simulation results with available high-fidelity experimental data from the ECN Spray A case. The LES results indicated a good overall performance against various validation measures on mixture formation, single-fuel ignition and diffusion flame characteristics (Objective 1).

The Spray A case was modified to suit DF investigations by introducing methane into the ambient mixture composition. The analysis of the DF LES results indicated that autoignition takes place in rich mixtures near the spray tip in both SF and DF configurations (Objective 2).

The autoignition chemistry was observed to be sensitive on the fraction of HRF (here, diesel surrogate). Simulation results indicate that low pilot quantities may lead to over-leaning and unsuccessful ignition (Objective 3).

The role of low-temperature chemistry in DF mixtures was observed to be important and sensitive to the choice of a chemical mechanism. A chemical mechanism comparison was carried out in this thesis work in terms of 0d, 1d and 3d simulations. The influence of ambient methane on the oxidation paths of *n*-dodecane was quantified via 0d, 1d and 3d simulations (Objective 4).

4.7 Suggestions for future work

Besides assessment of the prescribed outline of limitations, the future work could include further analyses on DF pilot sprays, numerical model development and work on efficient implementation of these models to achieve fast execution times by modern computer architectures.

As discussed above, the influence of pilot spray induced turbulence on premixed flame propagation should be quantitatively assessed. One interesting direction for further DF studies is the use of multiple short pilot injections, which could provide practical information for engine manufacturers to develop optimized

pilot ignition systems. In the present studies, soot or NO_x emissions are not considered which would be a relevant aspect in studies including pilot quantity variation and flame propagation.

Even though the chemistry is responsible for a high computational burden, the user should not sacrifice the accuracy of mixing solution by employing coarse grid resolution to make the simulation affordable. Use of high-order numerical methods could provide the needed increase in both accuracy and computational efficiency [207]. With respect to the presented cases, the assumptions made in Publications I-III on grid resolution and chosen ILES approach should be quantified in-detail with comparison to other available models.

To reduce the computational cost of finite-rate chemistry, work on ODE solver speed-up could be considered. For example, the recent study by Curtiss et al. [208] presents a second-generation version of the pyJac package, enabling an analytic sparse formulation for the Jacobian matrix of the chemistry problem. Their implementation is targeted for modern processor unit architectures (including vectorization and use of graphical processor units, GPUs) and yields speed-ups in scale of 3-20 depending on the mechanism size and problem type. In addition, sparse formulation allows the use of optimized sparse linear algebra libraries, yielding further speed-up [177, 209].

Besides enhancements in ODE solver, the number of ODE problems per time step could be restricted by using e.g. in-situ adaptive tabulation method (ISAT). In the present solver configuration, finite-rate chemistry is integrated in all chemically active cells (spray cloud), while ISAT intends to reuse an already existing ODE solution if initial conditions are similar enough. Reported speed-ups range from factor of 2 to 10 and above [210, 211], depending on combustion problem type, mechanism size and applied error tolerances.

With such efforts, utilization of LES in more practical problems with a faster turn-around time becomes possible. However, to achieve better understanding on DF pilot ignition, further work on detailed experiments and simulations is required.

References

- [1] ©OECD/IEA, International Energy Agency: World Energy Outlook 2018, 2018. doi:<https://doi.org/10.1787/weo-2018-en>.
- [2] S. Manabe, R. T. Wetherald, Thermal Equilibrium of the Atmosphere with a Given Distribution of Relative Humidity, *Journal of the Atmospheric Sciences* 24 (3) (1967) 241–259. doi:10.1175/1520-0469(1967)024<0241:TE0TAW>2.0.CO;2.
- [3] C. Parmesan, G. Yohe, A globally coherent fingerprint of climate change impacts across natural systems, *Nature* 421 (6918) (2003) 37–42. doi:10.1038/nature01286.
- [4] I. M. Held, B. J. Soden, Robust responses of the hydrological cycle to global warming, *Journal of Climate* 19 (21) (2006) 5686–5699. doi:10.1175/JCLI3990.1.
- [5] V. Masson-Delmotte, P. Zhai, H. O. Pörtner, D. Roberts, J. Skea, P. R. Shukla, A. Pirani, W. Moufouma-Okia, C. Péan, R. Pidcock, S. Connors, J. B. R. Matthews, Y. Chen, X. Zhou, M. I. Gomis, E. Lonnoy, T. Maycock, M. Tignor, T. Waterfield, IPCC, 2018: Summary for Policymakers. Global warming of 1.5 degrees Celsius., Tech. rep. (2018).
- [6] ©OECD/IEA, International Energy Agency: Outlook for Natural Gas 2017, Tech. rep. (2018). doi:<https://doi.org/10.1787/weo-2018-7-en>.
- [7] G. Myhre, D. Shindell, F.-M. F.-M. Bréon, W. Collins, J. Fuglestad, J. Huang, D. Koch, J.-F. Lamarque, D. Lee, B. Mendoza, T. Nakajima, A. Robock, G. Stephens, T. Takemura, H. Zhan, H. Zhang, Anthropogenic and Natural Radiative Forcing Supplementary Material, in: T. Stocker, D. Qin, G.-K. Plattner, J. Tignor, S. Allen, J. Boschung, A. Nauels, Y. Xia, V. Bex, P. M. Midgley (Eds.), *Climate Change 2013: The Physical Science Basis. Contribution of Working Group I to the Fifth Assessment Report of the Intergovernmental Panel on Climate Change: The Physical Science Basis.*, 2013, Ch. Supplement, pp. 1–44. doi:10.1017/CB09781107415324.018.
- [8] J. R. Worden, A. A. Bloom, S. Pandey, Z. Jiang, H. M. Worden, T. W. Walker, S. Houweling, T. Röckmann, Reduced biomass burning emissions reconcile conflicting estimates of the post-2006 atmospheric methane budget, *Nature Communications* 8 (1) (2017) 2227. doi:10.1038/s41467-017-02246-0.
- [9] ©OECD/IEA, International Energy Agency: Energy Technology Perspectives 2014, Tech. rep. (2014). doi:https://doi.org/10.1787/energy_tech-2014-en.
- [10] ©OECD/IEA, International Energy Agency: Energy Technology Perspectives 2015, Tech. rep. doi:https://doi.org/10.1787/energy_tech-2015-en.
- [11] International Maritime Organization: <http://www.imo.org> (2018).
- [12] J. B. Heywood, Internal combustion engine fundamentals, McGraw-Hill, 1988.

- [13] J. E. Dec, A Conceptual Model of DI Diesel Combustion Based on Laser-Sheet Imaging, in: SAE Technical Paper 970873, 1997. doi:10.4271/970873.
- [14] H. M. Cho, B. Q. He, Spark ignition natural gas engines – A review, *Energy Conversion and Management* 48 (2) (2007) 608–618. doi:10.1016/j.enconman.2006.05.023.
- [15] M. Ghaderi Masouleh, K. Keskinen, O. Kaario, H. Kahila, Y. M. Wright, V. Vuorinen, Flow and thermal field effects on cycle-to-cycle variation of combustion: scale-resolving simulation in a spark ignited simplified engine configuration, *Applied Energy* 230 (2018) 486–505. doi:10.1016/j.apenergy.2018.08.046.
- [16] J. Dale, Application of high energy ignition systems to engines, *Progress in Energy and Combustion Science* 23 (5-6) (1997) 379–398. doi:10.1016/S0360-1285(97)00011-7.
- [17] P. Zoldak, J. John Joseph, W. Shelley, J. Johnson, J. Naber, Characterization of Partially Stratified Direct Injection of Natural Gas for Spark-Ignited Engines, in: SAE 2015 World Congress and Exhibition, no. 2015-01-0937, 2015. doi:10.4271/2015-01-0937. Copyright.
- [18] C. E. C. Alvarez, G. E. Couto, V. R. Roso, A. B. Thiriet, R. M. Valle, A review of prechamber ignition systems as lean combustion technology for SI engines, *Applied Thermal Engineering* 128 (2018) 107–120. doi:10.1016/j.applthermaleng.2017.08.118.
- [19] S. Schlatter, B. Schneider, Y. Wright, K. Boulouchos, N-heptane micro pilot assisted methane combustion in a Rapid Compression Expansion Machine, *Fuel* 179 (2016) 339–352. doi:10.1016/j.fuel.2016.03.006.
- [20] R. Papagiannakis, D. Hountalas, C. Rakopoulos, Theoretical study of the effects of pilot fuel quantity and its injection timing on the performance and emissions of a dual fuel diesel engine, *Energy Conversion and Management* 48 (11) (2007) 2951–2961. doi:10.1016/J.ENCONMAN.2007.07.003.
- [21] B. B. Sahoo, N. Sahoo, U. K. Saha, Effect of engine parameters and type of gaseous fuel on the performance of dual-fuel gas diesel engines – A critical review, *Renewable and Sustainable Energy Reviews* 13 (6-7) (2009) 1151–1184. doi:10.1016/j.rser.2008.08.003.
- [22] X. Lü, Y. Hou, L. Zu, Z. Huang, Experimental study on the auto-ignition and combustion characteristics in the homogeneous charge compression ignition (HCCI) combustion operation with ethanol/n-heptane blend fuels by port injection, *Fuel* 85 (17-18) (2006) 2622–2631. doi:10.1016/J.FUEL.2006.05.003.
- [23] S. Khandal, N. Banapurmath, V. Gaitonde, S. Hiremath, Paradigm shift from mechanical direct injection diesel engines to advanced injection strategies of diesel homogeneous charge compression ignition (HCCI) engines- A comprehensive review, *Renewable and Sustainable Energy Reviews* 70 (2017) 369–384. doi:10.1016/j.rser.2016.11.058.
- [24] S. L. Kokjohn, R. M. Hanson, D. A. Splitter, R. D. Reitz, Fuel reactivity controlled compression ignition (RCCI): a pathway to controlled high-efficiency clean combustion, *International Journal of Engine Research* 12 (3) (2011) 209–226. doi:10.1177/1468087411401548.
- [25] R. D. Reitz, G. Duraisamy, Review of high efficiency and clean reactivity controlled compression ignition (RCCI) combustion in internal combustion engines, *Progress in Energy and Combustion Science* 46 (2015) 12–71. doi:10.1016/j.peccs.2014.05.003.

- [26] G. Abd Alla, H. Soliman, O. Badr, M. Abd Rabbo, Effect of pilot fuel quantity on the performance of a dual fuel engine, *Energy Conversion and Management* 41 (6) (2000) 559–572. doi:10.1016/S0196-8904(99)00124-7.
- [27] L. Wei, P. Geng, A review on natural gas/diesel dual fuel combustion, emissions and performance, *Fuel Processing Technology* 142 (2016) 264–278. doi:10.1016/j.fuproc.2015.09.018.
- [28] J. Liu, F. Yang, H. Wang, M. Ouyang, S. Hao, Effects of pilot fuel quantity on the emissions characteristics of a CNG/diesel dual fuel engine with optimized pilot injection timing, *Applied Energy* 110 (2013) 201–206. doi:10.1016/J.APENERGY.2013.03.024.
- [29] T. Echekki, E. Mastorakos, *Turbulent Combustion Modeling: Advances, New Trends and Perspectives*, Springer Netherland, 2010. arXiv:arXiv:1011.1669v3, doi:10.1007/978-94-007-0412-1.
- [30] M. Schmitt, C. E. Frouzakis, A. G. Tomboulides, Y. M. Wright, K. Boulouchos, Direct numerical simulation of the effect of compression on the flow, temperature and composition under engine-like conditions, *Proceedings of the Combustion Institute* 35 (3) (2015) 3069–3077. doi:10.1016/j.proci.2014.06.097.
- [31] Y. Pei, S. Som, E. Pomraning, P. K. Senecal, S. A. Skeen, J. Manin, L. M. Pickett, Large eddy simulation of a reacting spray flame with multiple realizations under compression ignition engine conditions, *Combustion and Flame* 162 (12) (2015) 4442–4455. doi:10.1016/j.combustflame.2015.08.010.
- [32] D. D. van der Voort, N. J. Dam, H. J. H. Clercx, W. van de Water, Characterization of spray-induced turbulence using fluorescence PIV, *Experiments in Fluids* 59 (7) (2018) 110. doi:10.1007/s00348-018-2561-9.
- [33] S. B. Pope, *Turbulent Flows*, Vol. 12, Cambridge University Press, 2001. doi:10.1088/0957-0233/12/11/705.
- [34] N. Peters, A. M. Kanury, *Turbulent combustion*, Cambridge University Press, 2000. doi:https://doi.org/10.1017/CB09780511612701.
- [35] T. Lu, C. K. Law, Toward accommodating realistic fuel chemistry in large-scale computations, *Progress in Energy and Combustion Science* 35 (2) (2009) 192–215. doi:10.1016/j.pecs.2008.10.002.
- [36] Turbulent Nonpremixed Flame Workshop (<https://www.sandia.gov/TNF/abstract.html>) (2018).
- [37] L. M. Pickett, ECN web page 26.06.2007 (accessed via <https://web.archive.org/web/20080919005650/http://public.ca.sandia.gov:80/ecn/cvdata/dsearch.php>) (2007).
- [38] D. Goodwin, Cantera: An object-oriented software toolkit for chemical kinetics, thermodynamics, and transport processes. Available at: <https://cantera.org>. Accessed November 2018.
- [39] R. Diesel, Patent: Method of igniting and regulating combustion for internal combustion engines. (apr 1901). doi:U5673160A.
- [40] M. A. Elliott, R. F. Davis, Dual-Fuel Combustion in Diesel Engines., *Industrial & Engineering Chemistry* 43 (12) (1951) 2854–2864. doi:10.1177/0019793916668530.
- [41] G. A. Karim, Combustion in Gas Fueled Compression: Ignition Engines of the Dual Fuel Type, *Journal of Engineering for Gas Turbines and Power* 125 (3) (2003) 827. doi:10.1115/1.1581894.

- [42] G. H. Abd Alla, H. A. Soliman, O. A. Badr, M. F. Abd Rabbo, Effect of injection timing on the performance of a dual fuel engine, *Energy Conversion and Management* 43 (2) (2002) 269–277. doi:10.1016/S0196-8904(00)00168-0.
- [43] R. G. Papagiannakis, D. T. Hountalas, Combustion and exhaust emission characteristics of a dual fuel compression ignition engine operated with pilot diesel fuel and natural gas, *Energy Conversion and Management* 45 (18-19) (2004) 2971–2987. doi:10.1016/j.enconman.2004.01.013.
- [44] S. Imran, D. R. Emberson, A. Diez, D. S. Wen, R. J. Crookes, T. Korakianitis, Natural gas fueled compression ignition engine performance and emissions maps with diesel and RME pilot fuels, *Applied Thermal Engineering* 67 (1-2) (2014) 354–365. doi:10.1016/j.apenergy.2014.02.067.
- [45] C. Aksu, N. Kawahara, K. Tsuboi, M. Kondo, E. Tomita, Extension of PREMIER combustion operation range using split micro pilot fuel injection in a dual fuel natural gas compression ignition engine: A performance-based and visual investigation, *Fuel* 185 (2016) 243–253. doi:10.1016/j.fuel.2016.07.120.
- [46] Z. Ahmad, J. Aryal, O. Ranta, O. Kaario, V. Vuorinen, An Optical Characterization of Dual-Fuel Combustion in a Heavy-Duty Diesel Engine, *SAE Technical Paper* 2018-01-02 (2018) 1–10. doi:10.4271/2018-01-0252.Abstract.
- [47] D. L. Siebers, Liquid-Phase Fuel Penetration in Diesel Sprays, in: *SAE Technical Paper* 980809, 1998. doi:10.4271/980809.
- [48] D. L. Siebers, B. Higgins, Flame Lift-Off on Direct-Injection Diesel Sprays Under Quiescent Conditions, in: *SAE Technical Paper* 2001-01-0530, 2001. arXiv:9206023, doi:10.4271/2001-01-0530.
- [49] S. A. Skeen, J. Manin, L. M. Pickett, Simultaneous formaldehyde PLIF and high-speed schlieren imaging for ignition visualization in high-pressure spray flames, *Proceedings of the Combustion Institute* 35 (3) (2015) 3167–3174. doi:10.1016/j.proci.2014.06.040.
- [50] A. Srna, M. Bolla, Y. M. Wright, K. Herrmann, R. Bombach, S. S. Pandurangi, K. Boulouchos, G. Bruneaux, Effect of methane on pilot-fuel auto-ignition in dual-fuel engines, *Proceedings of the Combustion Institute* doi:10.1016/J.PROCI.2018.06.177.
- [51] T. D. Fansler, S. E. Parrish, Spray measurement technology: A review, *Measurement Science and Technology* 26 (1) (2015) 012002. doi:10.1088/0957-0233/26/1/012002.
- [52] C. Espey, J. E. Dec, T. A. Litzinger, D. A. Santavicca, Planar laser Rayleigh scattering for quantitative vapor-fuel imaging in a diesel jet, *Combustion and Flame* 109 (1-2) (1997) 65–86. doi:10.1016/S0010-2180(96)00126-5.
- [53] B. Higgins, D. L. Siebers, Measurement of the Flame Lift-Off Location on DI Diesel Sprays Using OH Chemiluminescence, in: *SAE Technical Paper* 2001-01-0918, 2001. doi:10.4271/2001-01-0918.
- [54] D. L. Siebers, B. Higgins, L. Pickett, Flame Lift-Off on Direct-Injection Diesel Fuel Jets: Oxygen Concentration Effects, in: *SAE Technical Paper* 2002-01-0890, 2002. doi:10.4271/2002-01-0890.
- [55] L. M. Pickett, D. L. Siebers, Soot in diesel fuel jets: Effects of ambient temperature, ambient density, and injection pressure, *Combustion and Flame* 138 (1-2) (2004) 114–135. doi:10.1016/j.combustflame.2004.04.006.
- [56] L. M. Pickett, D. L. Siebers, Orifice Diameter Effects on Diesel Fuel Jet Flame Structure, *Journal of Engineering for Gas Turbines and Power* 127 (1) (2005) 187. doi:10.1115/1.1760525.

- [57] L. M. Pickett, D. L. Siebers, C. A. Idicheria, Relationship Between Ignition Processes and the Lift-Off Length of Diesel Fuel Jets, in: SAE Technical Paper 2005-01-3843, no. 724, 2005. doi:10.4271/2005-01-3843.
- [58] L. M. Pickett, S. Kook, T. C. Williams, Visualization of Diesel Spray Penetration, Cool-Flame, Ignition, High-Temperature Combustion, and Soot Formation Using High-Speed Imaging, SAE International Journal of Engines 2 (1) (2009) 2009–01–0658. doi:10.4271/2009-01-0658.
- [59] C. a. Idicheria, L. M. Pickett, Quantitative Mixing Measurements in a Vaporizing Diesel Spray by Rayleigh Imaging, in: SAE Technical Paper 2007-01-0647, Vol. 01, 2007, pp. 776–790. doi:10.4271/2007-01-0647.
- [60] L. M. Pickett, C. L. Genzale, G. Bruneaux, L. Malbec, L. Hermant, C. Christiansen, J. Schramm, Comparison of Diesel Spray Combustion in Different High-Temperature, High-Pressure Facilities, SAE International Journal of Engines 3 (2) (2010) 2010–01–2106. doi:10.4271/2010-01-2106.
- [61] M. Bardi, T. Bazyn, G. Bruneaux, J. Johnson, S. Lee, L. M. Malbec, M. Meijer, J. Naber, R. Payri, L. M. Pickett, B. Somers, Engine Combustion Network (ECN): Characterization and Comparison of Boundary Conditions for Different Combustion Vessels, Atomization and Sprays 22 (9) (2012) 777–806. doi:10.1615/AtomizSpr.2012006083.
- [62] M. Bardi, R. Payri, L. M. Malbec, G. Bruneaux, L. M. Pickett, J. Manin, T. Bazyn, C. Genzale, Engine Combustion Network: Comparison of Spray Development, Vaporization, and Combustion in Different Combustion Vessels, Atomization and Sprays 22 (10) (2012) 807–842. doi:10.1615/AtomizSpr.2013005837.
- [63] C. A. Idicheria, L. M. Pickett, Soot Formation in Diesel Combustion under High-EGR Conditions, 2005. doi:10.4271/2005-01-3834.
- [64] L. M. Pickett, J. Manin, C. L. Genzale, D. L. Siebers, M. P. B. Musculus, C. A. Idicheria, Relationship Between Diesel Fuel Spray Vapor Penetration/Dispersion and Local Fuel Mixture Fraction, SAE Int. J. Engines 4 (1) (2011) 764–799. doi:10.4271/2011-01-0686.
- [65] R. Payri, J. M. García-Oliver, M. Bardi, J. Manin, Fuel temperature influence on diesel sprays in inert and reacting conditions, Applied Thermal Engineering 35 (1) (2012) 185–195. doi:10.1016/j.applthermaleng.2011.10.027.
- [66] J. Benajes, R. Payri, M. Bardi, P. Martí-Aldaraví, Experimental characterization of diesel ignition and lift-off length using a single-hole ECN injector, Applied Thermal Engineering 58 (1-2) (2013) 554–563. doi:10.1016/j.applthermaleng.2013.04.044.
- [67] N. Maes, M. Meijer, N. Dam, B. Somers, H. Baya Toda, G. Bruneaux, S. A. Skeen, L. M. Pickett, J. Manin, Characterization of Spray A flame structure for parametric variations in ECN constant-volume vessels using chemiluminescence and laser-induced fluorescence, Combustion and Flame 174 (2016) 138–151. doi:10.1016/j.combustflame.2016.09.005.
- [68] S. Skeen, J. Manin, L. M. Pickett, Visualization of Ignition Processes in High-Pressure Sprays with Multiple Injections of n-Dodecane, SAE International Journal of Engines 8 (2) (2015) 799–2015. doi:10.4271/2015-01-0799.
- [69] N. Maes, P. Bakker, N. Dam, B. Somers, Transient Flame Development in a Constant-Volume Vessel Using a Split-Scheme Injection Strategy, SAE International Journal of Fuels and Lubricants 10 (2) (2017) 2017–01–0815. doi:10.4271/2017-01-0815.

- [70] C. S. Lee, K. H. Lee, D. S. Kim, Experimental and numerical study on the combustion characteristics of partially premixed charge compression ignition engine with dual fuel, *Fuel* 82 (5) (2003) 553–560. doi:10.1016/S0016-2361(02)00319-8.
- [71] M. S. Lounici, K. Loubar, L. Tarabet, M. Balistrrou, D. C. Niculescu, M. Tazerout, Towards improvement of natural gas-diesel dual fuel mode: An experimental investigation on performance and exhaust emissions, *Energy* 64 (2014) 200–211. doi:10.1016/j.energy.2013.10.091.
- [72] H. Saito, T. Sakurai, T. Sakonji, T. Hirashima, K. Kanno, Study on Lean Burn Gas Engine Using Pilot Oil as the Ignition Source, SAE Technical Paper 2001-01-01. doi:10.4271/2001-01-0143.
- [73] S. Schlatter, B. Schneider, Y. Wright, K. Boulouchos, Experimental Study of Ignition and Combustion Characteristics of a Diesel Pilot Spray in a Lean Premixed Methane/Air Charge using a Rapid Compression Expansion Machine, SAE Technical paper 2012-01-08. doi:10.4271/2012-01-0825.
- [74] M. Rong, X. He, H. Liu, Y. Shang, W. Zeng, X. Li, F. Liu, An Optical Investigation on the Combustion Characteristics of Gasoline-Diesel Dual-Fuel Applications, SAE Technical Paper 2014-01-13. doi:10.4271/2014-01-1310.
- [75] N. Dronniou, J. Kashdan, B. Lecointe, K. Sauve, D. Soleri, Optical Investigation of Dual-fuel CNG/Diesel Combustion Strategies to Reduce CO₂ Emissions, *SAE International Journal of Engines* 7 (2) (2014) 2014–01–1313. doi:10.4271/2014-01-1313.
- [76] X. Ma, Y. Qi, Z. Wang, H. Xu, J. Wang, An Experimental Study of EGR-Controlled Stoichiometric Dual-fuel Compression Ignition (SDCI) Combustion, SAE Technical Paper 2014-01-13. doi:10.4271/2014-01-1307.
- [77] M. Grochowina, M. Schiffner, S. Tartsch, T. Sattelmayer, Influence of Injection Parameters and Operating Conditions on Ignition and Combustion in Dual-Fuel Engines, *Journal of Engineering for Gas Turbines and Power* 140 (10) (2018) 1–10. doi:10.1115/1.4040089.
- [78] E. Tomita, Y. Harada, N. Kawahara, A. Sakane, Effect of EGR on Combustion and Exhaust Emissions in Supercharged Dual-Fuel Natural Gas Engine Ignited with Diesel Fuel, in: SAE Technical paper 2009-01-1832, 2009. doi:10.4271/2009-01-1832.
- [79] D. Lata, A. Misra, Analysis of ignition delay period of a dual fuel diesel engine with hydrogen and LPG as secondary fuels, *International Journal of Hydrogen Energy* 36 (5) (2011) 3746–3756. doi:10.1016/J.IJHYDENE.2010.12.075.
- [80] D. E. Nieman, A. B. Dempsey, R. D. Reitz, Heavy-Duty RCCI Operation Using Natural Gas and Diesel, *SAE Int. J. Engines* 5 (2) (2012) 270–285. doi:10.4271/2012-01-0379.
- [81] K. Ryu, Effects of pilot injection timing on the combustion and emissions characteristics in a diesel engine using biodiesel–CNG dual fuel, *Applied Energy* 111 (2013) 721–730. doi:10.1016/J.APENERGY.2013.05.046.
- [82] Y. Li, M. Jia, Y. Chang, Y. Liu, M. Xie, T. Wang, L. Zhou, Parametric study and optimization of a RCCI (reactivity controlled compression ignition) engine fueled with methanol and diesel, *Energy* 65 (2014) 319–332. doi:10.1016/j.energy.2013.11.059.
- [83] H. Liu, Q. Tang, Z. Yang, X. Ran, C. Geng, B. Chen, L. Feng, M. Yao, A comparative study on partially premixed combustion (PPC) and reactivity controlled compression ignition (RCCI) in an optical engine, *Proceedings of the Combustion Institute* doi:10.1016/J.PROCI.2018.06.004.

- [84] G. K. Lilik, H. Zhang, J. M. Herreros, D. C. Haworth, A. L. Boehman, Hydrogen assisted diesel combustion, *International Journal of Hydrogen Energy* 35 (9) (2010) 4382–4398. doi:10.1016/j.ijhydene.2010.01.105.
- [85] J. Sidey, E. Mastorakos, Visualisation of turbulent swirling dual-fuel flames, *Proceedings of the Combustion Institute* 36 (2) (2017) 1721–1727. doi:10.1016/j.proci.2016.08.045.
- [86] G. H. Abd Alla, H. A. Soliman, O. A. Badr, M. F. Abd Rabbo, Combustion quasi-two zone predictive model for dual fuel engines, *Energy Conversion and Management* 42 (12) (2001) 1477–1498. doi:10.1016/S0196-8904(00)00143-6.
- [87] J. Li, W. M. Yang, T. N. Goh, H. An, A. Maghbouli, Study on RCCI (reactivity controlled compression ignition) engine by means of statistical experimental design, *Energy* 78 (2014) 777–787. doi:10.1016/j.energy.2014.10.071.
- [88] A. Maghbouli, R. K. Saray, S. Shafee, J. Ghafouri, Numerical study of combustion and emission characteristics of dual-fuel engines using 3D-CFD models coupled with chemical kinetics, *Fuel* 106 (2013) 98–105. doi:10.1016/J.FUEL.2012.10.055.
- [89] A. Bhagatwala, R. Sankaran, S. Kokjohn, J. H. Chen, Numerical investigation of spontaneous flame propagation under RCCI conditions, *Combustion and Flame* 162 (9) (2015) 3412–3426. doi:10.1016/j.combustflame.2015.06.005.
- [90] E. Demosthenous, G. Borghesi, E. Mastorakos, R. S. Cant, Direct Numerical Simulations of premixed methane flame initiation by pilot n-heptane spray autoignition, *Combustion and Flame* 163 (2016) 122–137. doi:10.1016/j.combustflame.2015.09.013.
- [91] M. B. Luong, R. Sankaran, G. H. Yu, S. H. Chung, C. S. Yoo, A DNS study of the effects of injection timing on the ignition of lean PRF/air/EGR mixture with composition inhomogeneities relevant to RCCI/DDFS combustion, *Combustion and Flame* 183. doi:10.1016/j.combustflame.2017.05.023.
- [92] T. Jin, K. H. Luo, X. Wang, K. Luo, J. Fan, Dynamics of triple-flames in ignition of turbulent dual fuel mixture: A direct numerical simulation study, *Proceedings of the Combustion Institute* doi:10.1016/J.PROCI.2018.09.018.
- [93] U. Burke, K. P. Somers, P. O'Toole, C. M. Zinner, N. Marquet, G. Bourque, E. L. Petersen, W. K. Metcalfe, Z. Serinyel, H. J. Curran, An ignition delay and kinetic modeling study of methane, dimethyl ether, and their mixtures at high pressures, *Combustion and Flame* 162 (2) (2015) 315–330. doi:10.1016/j.combustflame.2014.08.014.
- [94] A. Rahimi, E. Fatehifar, R. K. Saray, Development of an optimized chemical kinetic mechanism for homogeneous charge compression ignition combustion of a fuel blend of n-heptane and natural gas using a genetic algorithm, *Proceedings of the Institution of Mechanical Engineers, Part D: Journal of Automobile Engineering* 224 (9) (2010) 1141–1159. doi:10.1243/09544070JAUT01343.
- [95] H. Huang, D. Lv, J. Zhu, Z. Zhu, Y. Chen, Y. Pan, M. Pan, Development of a new reduced diesel/natural gas mechanism for dual-fuel engine combustion and emission prediction, *Fuel* 236 (2019) 30–42. doi:10.1016/j.fuel.2018.08.161.
- [96] S. Schlatter, Experimental and Numerical Characterization of Enhanced Ignition Systems for Large Bore Gas Engines, Ph.D. thesis, ETH-Zürich (jan 2015). doi:10.3929/ETHZ-A-010410665.
- [97] Z. Wang, J. Abraham, Fundamental physics of flame development in an autoigniting dual fuel mixture, *Proceedings of the Combustion Institute* 35 (1) (2015) 1041–1048. doi:10.1016/j.proci.2014.06.079.

- [98] H. J. Curran, P. Gaffuri, W. J. Pitz, C. K. Westbrook, A comprehensive modeling study of n-heptane oxidation, *Combustion and Flame* 114 (1-2) (1998) 149–177. doi:10.1016/S0010-2180(97)00282-4.
- [99] J. M. Desantes, J. J. López, J. M. García-Oliver, D. López-Pintor, Experimental validation and analysis of seven different chemical kinetic mechanisms for n-dodecane using a Rapid Compression-Expansion Machine, *Combustion and Flame* 182 (2017) 76–89. doi:10.1016/j.combustflame.2017.04.004.
- [100] T. Yao, Y. Pei, B. Zhong, S. Som, T. Lu, K. H. Luo, A compact skeletal mechanism for n-dodecane with optimized semi-global low-temperature chemistry for diesel engine simulations, *Fuel* 191 (2017) 339–349. doi:10.1016/j.fuel.2016.11.083.
- [101] A. Frassoldati, A. Cuoci, A. Stagni, T. Faravelli, E. Ranzi, Skeletal kinetic mechanism for diesel combustion, *Combustion Theory and Modelling* 21 (1) (2017) 79–92. doi:10.1080/13647830.2016.1222082.
- [102] S. M. Sarathy, C. Yeung, C. K. Westbrook, W. J. Pitz, M. Mehl, M. J. Thomson, An experimental and kinetic modeling study of n-octane and 2-methylheptane in an opposed-flow diffusion flame, *Combustion and Flame* 158 (7) (2011) 1277–1287. doi:10.1016/j.combustflame.2010.11.008.
- [103] S. M. Sarathy, C. K. Westbrook, M. Mehl, W. J. Pitz, C. Togbe, P. Dagaut, H. Wang, M. A. Oehlschlaeger, U. Niemann, K. Seshadri, P. S. Veloo, C. Ji, F. N. Egolfopoulos, T. Lu, Comprehensive chemical kinetic modeling of the oxidation of 2-methylalkanes from C7 to C20, *Combustion and Flame* 158 (12) (2011) 2338–2357. doi:10.1016/j.combustflame.2011.05.007.
- [104] E. Ranzi, A. Frassoldati, R. Grana, A. Cuoci, T. Faravelli, A. P. Kelley, C. K. Law, Hierarchical and comparative kinetic modeling of laminar flame speeds of hydrocarbon and oxygenated fuels, *Progress in Energy and Combustion Science* 38 (4) (2012) 468–501. doi:10.1016/j.pecs.2012.03.004.
- [105] L. Cai, H. Pitsch, S. Y. Mohamed, V. Raman, J. Bugler, H. Curran, S. M. Sarathy, Optimized reaction mechanism rate rules for ignition of normal alkanes, *Combustion and Flame* 173 (2016) 468–482. doi:10.1016/j.combustflame.2016.04.022.
- [106] A. Frassoldati, G. D'Errico, T. Lucchini, A. Stagni, A. Cuoci, T. Faravelli, A. Onorati, E. Ranzi, Reduced kinetic mechanisms of diesel fuel surrogate for engine CFD simulations, *Combustion and Flame* 162 (10) (2015) 3991–4007. doi:10.1016/j.combustflame.2015.07.039.
- [107] E. R. Hawkes, "Ignition and Flame Structure", 5th workshop of the Engine Combustion Network, Detroit, USA. (2017) Available at www.sandia.gov/ecn. Accessed Jan. 2018.
- [108] A. Wehrfritz, O. Kaario, V. Vuorinen, B. Somers, Large Eddy Simulation of n-dodecane spray flames using Flamelet Generated Manifolds, *Combustion and Flame* 167 (2016) 113–131. doi:10.1016/j.combustflame.2016.02.019.
- [109] M. Ghaderi Masouleh, A. Wehrfritz, O. Kaario, H. Kahila, V. Vuorinen, Comparative study on chemical kinetic schemes for dual-fuel combustion of n-dodecane/methane blends, *Fuel* 191 (2017) 62–76. doi:10.1016/j.fuel.2016.10.114.
- [110] E. L. Petersen, D. F. Davidson, R. K. Hanson, Kinetics modeling of shock-induced ignition in low-dilution CH₄/O₂ mixtures at high pressures and intermediate temperatures, *Combustion and Flame* 117 (1-2) (1999) 272–290. doi:10.1016/S0010-2180(98)00111-4.
- [111] W. K. Metcalfe, S. M. Burke, S. S. Ahmed, H. J. Curran, A Hierarchical and Comparative Kinetic Modeling Study of C1-C2 Hydrocarbon and Oxygenated Fuels, *International Journal of Chemical Kinetics* 45 (10) (2013) 638–675. doi:10.1002/kin.20802.

- [112] D. M. Manias, E. A. Tingas, C. E. Frouzakis, K. Boulouchos, D. A. Goussis, The mechanism by which CH₂O and H₂O₂ additives affect the autoignition of CH₄/air mixtures, *Combustion and Flame* 164 (2016) 111–125. doi:10.1016/j.combustflame.2015.11.008.
- [113] C. K. Westbrook, W. J. Pitz, O. Herbinet, H. J. Curran, E. J. Silke, A comprehensive detailed chemical kinetic reaction mechanism for combustion of n-alkane hydrocarbons from n-octane to n-hexadecane, *Combustion and Flame* 156 (1) (2009) 181–199. doi:10.1016/j.combustflame.2008.07.014.
- [114] T. Lu, M. Plomer, Z. Luo, S. M. Sarathy, W. J. Pitz, S. Som, D. E. Longman, Directed Relation Graph with Expert Knowledge for Skeletal Mechanism Reduction, Tech. rep. (2011).
- [115] L. K. L. Cai, H. Pitsch, A reduced and optimized chemical mechanism for n-dodecane oxidation, in: 15th International Conference on Numerical Combustion, 2015.
- [116] K. Narayanaswamy, P. Pepiot, H. Pitsch, A chemical mechanism for low to high temperature oxidation of n-dodecane as a component of transportation fuel surrogates, *Combustion and Flame* 161 (4) (2014) 866–884. doi:10.1016/j.combustflame.2013.10.012.
- [117] Z. Luo, S. Som, S. M. Sarathy, M. Plomer, W. J. Pitz, D. E. Longman, T. Lu, Development and validation of an n-dodecane skeletal mechanism for spray combustion applications, *Combustion Theory and Modelling* 18 (2) (2014) 187–203. doi:10.1080/13647830.2013.872807.
- [118] H. Wang, Y. Ra, M. Jia, R. D. Reitz, Development of a reduced n-dodecane-PAH mechanism and its application for n-dodecane soot predictions, *Fuel* 136 (2014) 25–36. doi:10.1016/J.FUEL.2014.07.028.
- [119] F. Tao, V. I. Golovitchev, J. Chomiak, Self-Ignition and Early Combustion Process of n-Heptane Sprays Under Diluted Air Conditions: Numerical Studies Based on Detailed Chemistry, 2000. doi:10.4271/2000-01-2931.
- [120] F. Tao, J. Chomiak, Numerical Investigation of Reaction Zone Structure and Flame Liftoff of DI Diesel Sprays with Complex Chemistry, in: SAE Technical Paper, no. 2002-01-1114, 2002. doi:10.4271/2002-01-1114.
- [121] J. W. Campbell, a. D. Gosman, G. Hardy, I. M. Ag, Analysis of Premix Flame and Lift-Off in Diesel Spray Combustion using Multi-Dimensional CFD, SAE Technical Paper 2008-01-0968 1 (1) (2013) 571–590. doi:10.4271/2008-01-0968.
- [122] G. Vishwanathan, R. D. Reitz, Modeling Soot Formation Using Reduced Polycyclic Aromatic Hydrocarbon Chemistry in n-Heptane Lifted Flames With Application to Low Temperature Combustion, *Journal of Engineering for Gas Turbines and Power* 131 (3) (2009) 032801. doi:10.1115/1.3043806.
- [123] T. Lucchini, G. D'Errico, D. Ettorre, G. Ferrari, Numerical Investigation of Non-Reacting and Reacting Diesel Sprays in Constant-Volume Vessels, SAE Technical Paper 2009-01-1971 2 (1) 966–975. doi:10.4271/2009-01-1971.
- [124] J. Abraham, L. M. Pickett, Computed and Measured Fuel Vapor Distribution in a Diesel Spray, *Atomization and Sprays* 20 (3) (2010) 241–250. doi:10.1615/AtomizSpr.v20.i3.50.
- [125] G. D. Errico, D. Ettorre, T. Lucchini, M. Milano, Simplified and Detailed Chemistry Modeling of Constant-Volume Diesel Combustion Experiments, *SAE International Journal of Fuels and Lubricants* 1 (1) (2008) 452–465. doi:10.4271/2008-01-0954.

- [126] D. Veynante, L. Vervisch, Turbulent combustion modeling, *Progress in Energy and Combustion Science* 28 (3) (2002) 193–266. arXiv:arXiv:1011.1669v3, doi:10.1016/S0360-1285(01)00017-X.
- [127] J. Manin, M. Bardi, L. M. Pickett, R. N. Dahms, J. C. Oefelein, Microscopic investigation of the atomization and mixing processes of diesel sprays injected into high pressure and temperature environments, *Fuel* 134 (2014) 531–543. doi:10.1016/j.fuel.2014.05.060.
- [128] C. Crua, J. Manin, L. M. Pickett, On the transcritical mixing of fuels at diesel engine conditions, *Fuel* 208 (2017) 535–548. doi:10.1016/j.fuel.2017.06.091.
- [129] R. N. Dahms, J. C. Oefelein, On the transition between two-phase and single-phase interface dynamics in multicomponent fluids at supercritical pressures, *Physics of Fluids* 25 (9) (2013) 092103. doi:10.1063/1.4820346.
- [130] S. Bhattacharjee, D. C. Haworth, Simulations of transient n-heptane and n-dodecane spray flames under engine-relevant conditions using a transported PDF method, *Combustion and Flame* 160 (10) (2013) 2083–2102. doi:10.1016/j.combustflame.2013.05.003.
- [131] Y. Pei, E. R. Hawkes, S. Kook, G. M. Goldin, T. Lu, Modelling n-dodecane spray and combustion with the transported probability density function method, *Combustion and Flame* 162 (5) (2015) 2006–2019. doi:10.1016/j.combustflame.2014.12.019.
- [132] Y. Pei, E. R. Hawkes, M. Bolla, S. Kook, G. M. Goldin, Y. Yang, S. B. Pope, S. Som, An analysis of the structure of an n-dodecane spray flame using TPDF modelling, *Combustion and Flame* 168 (2016) 420–435. doi:10.1016/j.combustflame.2015.11.034.
- [133] M. Bolla, M. A. Chishty, E. R. Hawkes, S. Kook, Modeling combustion under engine combustion network Spray A conditions with multiple injections using the transported probability density function method, *International Journal of Engine Research* 18 (1-2) (2017) 6–14. doi:10.1177/1468087416689174.
- [134] M. Bolla, M. A. Chishty, E. R. Hawkes, Q. N. Chan, S. Kook, Influence of turbulent fluctuations on radiation heat transfer, NO and soot formation under ECN Spray A conditions, *Proceedings of the Combustion Institute* 36 (3) (2017) 3551–3558. doi:10.1016/j.proci.2016.06.173.
- [135] A. Varna, A. Wehrfritz, E. R. Hawkes, M. J. Cleary, T. Lucchini, G. D’Errico, S. Kook, Q. N. Chan, Application of a multiple mapping conditioning mixing model to ECN Spray A, *Proceedings of the Combustion Institute* doi:10.1016/J.PROCI.2018.06.007.
- [136] H. Turkeri, X. Zhao, S. B. Pope, M. Muradoglu, Large eddy simulation/probability density function simulations of the Cambridge turbulent stratified flame series, *Combustion and Flame* 199 (2019) 24–45. doi:10.1016/j.combustflame.2018.10.018.
- [137] G. Borghesi, E. Mastorakos, C. B. Devaud, R. W. Bilger, Modeling evaporation effects in conditional moment closure for spray autoignition, *Combustion Theory and Modelling* 15 (5) (2011) 725–752. doi:10.1080/13647830.2011.560282.
- [138] M. Bolla, Y. M. Wright, K. Boulouchos, G. Borghesi, E. Mastorakos, Soot formation modeling of n-heptane sprays under diesel engine conditions using the conditional moment closure approach, *Combustion Science and Technology* 185 (5) (2013) 766–793. doi:10.1080/00102202.2012.752362.
- [139] C. K. Blomberg, L. Zeugin, S. S. Pandurangi, M. Bolla, K. Boulouchos, Y. M. Wright, Modeling Split Injections of ECN “Spray A” Using a Conditional Moment Closure Combustion Model with RANS and LES, *SAE International Journal of Engines* 9 (4) (2016) 2107–2119. doi:10.4271/2016-01-2237.

- [140] G. D'Errico, T. Lucchini, F. Contino, M. Jangi, X. Bai, Comparison of well-mixed and multiple representative interactive flamelet approaches for diesel spray combustion modelling, *Combustion Theory and Modelling* 18 (1) (2014) 65–88. doi:10.1080/13647830.2013.860238.
- [141] P. Kundu, Y. Pei, M. Wang, R. Mandhapati, S. Som, Evaluation of Turbulence-Chemistry Interaction Under Diesel Engine Conditions With Multi-Flamelet RIF Model, *Atomization and Sprays* 24 (9) (2014) 779–800. doi:10.1615/AtomizSpr.2014010506.
- [142] C. Bajaj, M. Ameen, J. Abraham, Evaluation of an unsteady flamelet progress variable model for autoignition and flame lift-off in diesel jets, *Combustion Science and Technology* 185 (3) (2013) 454–472. doi:10.1080/00102202.2012.726667.
- [143] P. Kundu, M. M. Ameen, S. Som, Importance of turbulence-chemistry interactions at low temperature engine conditions, *Combustion and Flame* 183 (2017) 283–298. doi:10.1016/j.combustflame.2017.05.025.
- [144] C. Bekdemir, L. M. T. Somers, L. P. H. De Goey, J. Tillou, C. Angelberger, Predicting diesel combustion characteristics with Large-Eddy Simulations including tabulated chemical kinetics, *Proceedings of the Combustion Institute* 34 (2) (2013) 3067–3074. doi:10.1016/j.proci.2012.06.160.
- [145] J. Tillou, J.-B. Michel, C. Angelberger, C. Bekdemir, D. Veynante, Large-Eddy Simulation of Diesel Spray Combustion with Exhaust Gas Recirculation, *Oil & Gas Science and Technology – Revue d'IFP Energies nouvelles* 69 (1) (2013) 155–165. doi:10.2516/ogst/2013139.
- [146] C. Gong, M. Jangi, X. Bai, Large eddy simulation of n-dodecane spray combustion in a high pressure combustion vessel, *Applied Energy* 136 (2014) 373–381. doi:10.1016/j.apenergy.2014.09.030.
- [147] L. Hakim, G. Lacaze, J. Oefelein, Large Eddy Simulation of Autoignition Transients in a Model Diesel Injector Configuration, *SAE Technical Paper* 2016-01-0872 9 (1) (2016) 165–176. doi:10.4271/2016-01-0872.
- [148] F. Salehi, M. Cleary, A. Masri, Y. Ge, A. Klimenko, Sparse-Lagrangian MMC simulations of an n-dodecane jet at engine-relevant conditions, *Proceedings of the Combustion Institute* 36 (3) (2017) 3577–3585. doi:10.1016/J.PROCI.2016.07.074.
- [149] E. Ranzi, A. Frassoldati, A. Stagni, M. Pelucchi, A. Cuoci, T. Faravelli, Reduced kinetic schemes of complex reaction systems: Fossil and biomass-derived transportation fuels, *International Journal of Chemical Kinetics* 46 (9) (2014) 512–542. doi:10.1002/kin.20867.
- [150] Z. Luo, S. Som, S. M. Sarathy, M. Plomer, W. J. Pitz, D. E. Longman, T. Lu, Development and validation of an n-dodecane skeletal mechanism for spray combustion applications, *Combustion Theory and Modelling* 18 (2) (2014) 187–203. doi:10.1080/13647830.2013.872807.
- [151] S. Som, D. E. Longman, Z. Luo, M. Plomer, T. Lu, Longman, Luo, Plomer, Three Dimensional Simulations of Diesel Sprays Using n- Dodecane as a Surrogate, in: *Fall Technical Meeting of the Eastern States Section of the Combustion Institute*, 2011, pp. 1–14.
- [152] T. Yao, Y. Pei, B.-J. Zhong, S. Som, T. Lu, A Hybrid Mechanism for n-Dodecane Combustion with Optimized Low-Temperature Chemistry, in: *9th U. S. National Combustion Meeting*, 2015, pp. 1–10.
- [153] M. A. Chishty, M. Bolla, E. R. Hawkes, Y. Pei, S. Kook, Soot formation modelling for n-dodecane sprays using the transported PDF model, *Combustion and Flame* 192 (2018) 101–119. doi:10.1016/j.combustflame.2018.01.028.

- [154] S. F. Fernandez, C. Paul, A. Sircar, A. Imren, D. C. Haworth, S. Roy, M. F. Modest, Soot and spectral radiation modeling for high-pressure turbulent spray flames, *Combustion and Flame* 190 (2018) 402–415. doi:10.1016/j.combustflame.2017.12.016.
- [155] R. N. Dahms, G. A. Paczko, S. A. Skeen, L. M. Pickett, Understanding the ignition mechanism of high-pressure spray flames, *Proceedings of the Combustion Institute* 36 (2) (2016) 2615–2623. doi:10.1016/j.proci.2016.08.023.
- [156] A. Krisman, E. R. Hawkes, J. H. Chen, A parametric study of ignition dynamics at ECN Spray A thermochemical conditions using 2D DNS, *Proceedings of the Combustion Institute* doi:10.1016/J.PROCI.2018.08.026.
- [157] R. Payri, J. P. Viera, V. Gopalakrishnan, P. G. Szymkowicz, The effect of nozzle geometry over the evaporative spray formation for three different fuels, *Fuel* 188 (2017) 645–660. doi:10.1016/j.fuel.2016.10.064.
- [158] J. M. García-Oliver, L.-M. Malbec, H. B. Toda, G. Bruneaux, A study on the interaction between local flow and flame structure for mixing-controlled Diesel sprays, *Combustion and Flame* 179 (2017) 157–171. doi:10.1016/j.combustflame.2017.01.023.
- [159] OpenFOAM Foundation - The Open Source Computational Fluid Dynamics (CFD) Toolbox. Available at: <http://www.openfoam.org>. Accessed May 2018.
- [160] C. Hirsch, *Numerical Computation of Internal and External Flows: Fundamentals of numerical discretization*, Elsevier/Butterworth-Heinemann, 1991.
- [161] H. Jasak, *Error Analysis and Estimation for the Finite Volume Method with Applications to Fluid Flows*, Dissertation, Imperial College (1996).
- [162] H. Jasak, H. G. Weller, A. D. Gosman, High resolution NVD differencing scheme for arbitrarily unstructured meshes, *International Journal for Numerical Methods in Fluids* 31 (2) (1999) 431–449. doi:10.1002/(SICI)1097-0363(19990930)31:2<431::AID-FLD884>3.0.CO;2-T.
- [163] R. Issa, B. Ahmadi-Befrui, K. Beshay, A. Gosman, Solution of the implicitly discretised reacting flow equations by operator-splitting, *Journal of Computational Physics* 93 (2) (1991) 388–410. doi:10.1016/0021-9991(91)90191-M.
- [164] A. Wehrfritz, V. Vuorinen, O. Kaario, M. Larmi, Large Eddy Simulation of High-Velocity Fuel Sprays: Studying Mesh Resolution and Breakup Model Effects for Spray A, *Atomization and Sprays* 23 (5) (2013) 419–442. doi:10.1615/AtomizSpr.2013007342.
- [165] R. D. Reitz, Modeling Atomization Processes in High-Pressure Vaporizing Sprays, *Atomization and Spray Technology* 3 (1987) 309–337.
- [166] R. D. Reitz, J. C. Beale, Modeling Spray Atomization With the Kelvin-Helmholtz/Rayleigh-Taylor Hybrid Model, *Atomization and Sprays* 9 (6) (1999) 623–650. doi:10.1615/AtomizSpr.v9.i6.40.
- [167] A. Wehrfritz, *Large Eddy Simulation of Fuel Injection and Spray Combustion*, Ph.D. thesis, Aalto University (2016).
- [168] N. Frossling, Über die verdunstung fallender tropfen, *Geophysics* 12 (1938) 170–216.
- [169] W. E. Ranz, W. R. Marshall, Evaporation from drops, part I, *Chemical Engineering Progress* 48 (3) (1952) 141–146.
- [170] W. Ranz, W. R. Marshall, Evaporation from drops, part II, *Chemical Engineering Progress* 48 (3) (1952) 173–180.

- [171] M. S. Day, J. B. Bell, Numerical simulation of laminar reacting flows with complex chemistry, *Combustion Theory and Modelling* 4 (4) (2000) 535–556. doi:10.1088/1364-7830/4/4/309.
- [172] Z. Lu, H. Zhou, S. Li, Z. Ren, T. Lu, C. K. Law, Analysis of Operator Splitting Errors for Near-limit Flame Simulations, *Journal of Computational Physics* 335 (2017) 578–591. doi:10.1016/j.jcp.2017.01.044.
- [173] B. Sportisse, An Analysis of Operator Splitting Techniques in the Stiff Case, *Journal of Computational Physics* 161 (1) (2000) 140–168. doi:10.1006/jcph.2000.6495.
- [174] K. E. Niemeyer, N. J. Curtis, C. Sung, pyJac: Analytical Jacobian generator for chemical kinetics, *Computer Physics Communications* 215 (2017) 188–203. doi:10.1016/J.CPC.2017.02.004.
- [175] M. A. Hansen, J. C. Sutherland, On the consistency of state vectors and Jacobian matrices, *Combustion and Flame* 193 (2018) 257–271. doi:10.1016/J.COMBUSTFLAME.2018.03.017.
- [176] E. Hairer, G. Wanner, *Solving ordinary differential equations. II*, Springer-Verlag, 1996. doi:10.1007/978-3-642-05221-7.
- [177] A. Imren, D. C. Haworth, On the merits of extrapolation-based stiff ODE solvers for combustion CFD, *Combustion and Flame* 174 (2016) 1–15. doi:10.1016/j.combustflame.2016.09.018.
- [178] E. Anderson, Z. Bai, C. Bischof, S. Blackford, J. Demmel, J. Dongarra, J. Du Croz, A. Greenbaum, S. Hammarling, A. McKenney, D. Sorensen, *LAPACK Users' Guide*, 3rd Edition, Society for Industrial and Applied Mathematics, 1996.
- [179] G. Strang, On the Construction and Comparison of Difference Schemes, *SIAM Journal on Numerical Analysis* 5 (3) (1968) 506–517. doi:10.1137/0705041.
- [180] F. Qin, A. Shah, Z. Huang, L. Peng, P. Tunestal, X. Bai, Detailed numerical simulation of transient mixing and combustion of premixed methane/air mixtures in a pre-chamber/main-chamber system relevant to internal combustion engines, *Combustion and Flame* 188 (2018) 357–366. doi:10.1016/j.combustflame.2017.10.006.
- [181] J. J. Behzadi, M. Talei, M. Bolla, E. R. Hawkes, T. Lucchini, S. Kook, A Conditional Moment Closure Study of Chemical Reaction Source Terms in SCCI Combustion, *Flow Turbulence and Combustion* 100 (2018) 93–118. doi:10.1007/s10494-017-9825-y.
- [182] C. Duwig, K. Nogenmyr, C. Chan, M. J. Dunn, Large Eddy Simulations of a piloted lean premix jet flame using finite-rate chemistry, *Combustion Theory and Modelling* 15 (4) (2011) 537–568. doi:10.1080/13647830.2010.548531.
- [183] E. Fedina, C. Fureby, G. Bulat, W. Meier, Assessment of Finite Rate Chemistry Large Eddy Simulation Combustion Models, *Flow Turbulence Combust* 99 (99). doi:10.1007/s10494-017-9823-0.
- [184] G. Lacaze, A. Misdariis, A. Ruiz, J. C. Oefelein, Analysis of high-pressure Diesel fuel injection processes using LES with real-fluid thermodynamics and transport, *Proceedings of the Combustion Institute* 35 (2) (2015) 1603–1611. doi:10.1016/J.PROCI.2014.06.072.
- [185] P. K. Senecal, E. Pomraning, K. J. Richards, S. Som, An Investigation of Grid Convergence for Spray Simulations using an LES Turbulence Model, in: *SAE Technical Paper 2013-01-1083*, 2013. doi:10.4271/2013-01-1083.

- [186] A. Irannejad, A. Banaeizadeh, F. Jaber, Large eddy simulation of turbulent spray combustion, *Combustion and Flame* 162 (2) (2015) 431–450. doi:10.1016/j.combustflame.2014.07.029.
- [187] C. Gong, M. Jangi, T. Lucchini, G. D'Errico, X. S. Bai, Large eddy simulation of air entrainment and mixing in reacting and non-reacting diesel sprays, *Flow, Turbulence and Combustion* 93 (3) (2014) 385–404. doi:10.1007/s10494-014-9566-0.
- [188] F. F. Grinstein, L. G. Margolin, W. Rider, *Implicit large eddy simulation: computing turbulent fluid dynamics*, Cambridge University Press, 2007.
- [189] F. F. Grinstein, C. Fureby, On Flux-Limiting-Based Implicit Large Eddy Simulation, *Journal of Fluids Engineering* 129 (12) (2007) 1483. doi:10.1115/1.2801684.
- [190] A. Aspden, N. Nikiforakis, S. Dalziel, J. Bell, Analysis of implicit LES methods, *Communications in Applied Mathematics and Computational Science* 3 (1) (2008) 103–126. doi:10.2140/camcos.2008.3.103.
- [191] C. Fureby, F. F. Grinstein, Large Eddy Simulation of High-Reynolds-Number Free and Wall-Bounded Flows, *Journal of Computational Physics* 181 (1) (2002) 68–97. doi:10.1006/jcph.2002.7119.
- [192] C. Fureby, F. Grinstein, Monotonically integrated large eddy simulation of free shear flows, *AIAA Journal* 37 (5) (1999) 544–556. doi:10.2514/2.772.
- [193] V. Vuorinen, J. Yu, S. Tirunagari, O. Kaario, M. Larmi, C. Duwig, B. J. Boersma, Large-eddy simulation of highly underexpanded transient gas jets, *Physics of Fluids* 25 (1) (2013) 016101. doi:10.1063/1.4772192.
- [194] V. Vuorinen, A. Wehrfritz, C. Duwig, B. J. Boersma, Large-eddy simulation on the effect of injection pressure and density on fuel jet mixing in gas engines, *Fuel* 130 (2014) 241–250. doi:10.1016/j.fuel.2014.04.045.
- [195] M. Berglund, C. Fureby, LES of supersonic combustion in a scramjet engine model, *Proceedings of the Combustion Institute* 31 II (2) (2007) 2497–2504. doi:10.1016/j.proci.2006.07.074.
- [196] C. Eberle, P. Gerlinger, K. P. Geigle, M. Aigner, Toward finite-rate chemistry large-eddy simulations of sooting swirl flames, *Combustion Science and Technology* (2018) 1–24doi:10.1080/00102202.2018.1443444.
- [197] J. A. Fulton, J. R. Edwards, A. Cutler, J. McDaniel, C. Goyne, Turbulence/chemistry interactions in a ramp-stabilized supersonic hydrogen-air diffusion flame, *Combustion and Flame* 174 (2016) 152–165. doi:10.1016/J.COMBUSTFLAME.2016.09.017.
- [198] U. Maas, S. B. Pope, Simplifying chemical kinetics: Intrinsic low-dimensional manifolds in composition space, *Combustion and Flame* 88 (3-4) (1992) 239–264. doi:10.1016/0010-2180(92)90034-M.
- [199] J. van Oijen, F. Lammers, L. de Goey, Modeling of complex premixed burner systems by using flamelet-generated manifolds, *Combustion and Flame* 127 (3) (2001) 2124–2134. doi:10.1016/S0010-2180(01)00316-9.
- [200] L. Vervisch, R. Hauguel, P. Domingo, M. Rullaud, Three facets of turbulent combustion modelling: DNS of premixed V-flame, LES of lifted nonpremixed flame and RANS of jet-flame (jan 2004). doi:10.1088/1468-5248/5/1/004.
- [201] F. Bouras, A. Soudani, M. Si-Ameur, Beta-PDF approach for large-eddy simulation of non-premixed turbulent combustion, *International Review of Mechanical Engineering* 4 (3) (2010) 358–363. doi:10.1017/S0022112004008213.

- [202] C. D. Pierce, P. Moin, A dynamic model for subgrid-scale variance and dissipation rate of a conserved scalar, *Physics of Fluids* 10 (12) (1998) 3041–3044. doi:10.1063/1.869832.
- [203] M. Ihme, L. Shunn, J. Zhang, Regularization of reaction progress variable for application to flamelet-based combustion models (2012). doi:10.1016/j.jcp.2012.06.029.
- [204] A. Donini, R. J. M. Bastiaans, J. A. van Oijen, L. P. H. de Goeij, A 5-D Implementation of FGM for the Large Eddy Simulation of a Stratified Swirled Flame with Heat Loss in a Gas Turbine Combustor, *Flow, Turbulence and Combustion* (2016) 1–36doi:10.1007/s10494-016-9777-7.
- [205] J. A. van Oijen, A. Donini, R. J. M. Bastiaans, J. H. M. ten Thijs Boonkcamp, L. P. H. de Goeij, State-of-the-art in premixed combustion modeling using flamelet generated manifolds, *Progress in Energy and Combustion Science* 57 (2016) 30–74. doi:10.1016/j.peccs.2016.07.001.
- [206] B. Soriano, E. Richardson, S. Schlatter, Y. Wright, Conditional Moment Closure Modelling for Dual-Fuel Combustion Engines with Pilot-Assisted Compression Ignition, in: *SAE Technical Papers*, Vol. 2017-October, 2017. doi:10.4271/2017-01-2188.
- [207] J. C. Oefelein, Large eddy simulation of turbulent combustion processes in propulsion and power systems, *Progress in Aerospace Sciences* 42 (1) (2006) 2–37. doi:10.1016/j.paerosci.2006.02.001.
- [208] N. J. Curtis, K. E. Niemeyer, C.-J. Sung, Using SIMD and SIMT vectorization to evaluate sparse chemical kinetic Jacobian matrices and thermochemical source terms, *Combustion and Flame* 198 (2018) 186–204. doi:10.1016/J.COMBUSTFLAME.2018.09.008.
- [209] T. Dijkmans, C. M. Schietekat, K. M. Van Geem, G. B. Marin, GPU based simulation of reactive mixtures with detailed chemistry in combination with tabulation and an analytical Jacobian, *Computers and Chemical Engineering* 71 (2014) 521–531. doi:10.1016/j.compchemeng.2014.09.016.
- [210] M. A. Singer, S. B. Pope, Operator-splitting with ISAT to model reacting flow with detailed chemistry, *Combustion Theory and Modelling* 10 (2) (2006) 199–217. doi:10.1080/13647830500307501.
- [211] F. Contino, H. Jeanmart, T. Lucchini, G. D’Errico, Coupling of in situ adaptive tabulation and dynamic adaptive chemistry: An effective method for solving combustion in engine simulations, *Proceedings of the Combustion Institute* 33 (2) (2011) 3057–3064. doi:10.1016/J.PROCI.2010.08.002.

ISBN 978-952-60-8585-2 (printed)
ISBN 978-952-60-8586-9 (pdf)
ISSN 1799-4934 (printed)
ISSN 1799-4942 (pdf)

Aalto University
School of Engineering
Department of Mechanical Engineering
www.aalto.fi

**BUSINESS +
ECONOMY**

**ART +
DESIGN +
ARCHITECTURE**

**SCIENCE +
TECHNOLOGY**

CROSSOVER

**DOCTORAL
DISSERTATIONS**