Alternative Fuels and Emission Control Methods in Compression Ignition Engines

Aki Tilli

Alternative Fuels and Emission Control Methods in Compression Ignition Engines

Aki Tilli

A doctoral dissertation completed for the degree of Doctor of Science (Technology) to be defended, with the permission of the Aalto University School of Engineering, at a public examination held at the lecture hall 216 (Otakaari 4) of the school on 18 December 2019 at 12:00.

**Aalto University
School of Engineering
Department of Mechanical Engineering
Energy Conversion**

Supervising professor

Professor Martti Larmi, Aalto University, Finland

Thesis advisors

D.Sc. Teemu Sarjovaara, Neste, Finland

D.Sc. Ossi Kaario, Aalto University, Finland

Preliminary examiners

Professor Martin Tunér, Lund University, Sweden

Professor Jesper Schramm, Technical University of Denmark - DTU, Denmark

Opponent

Associate Professor Maciej Mikulski, University of Vaasa, Finland

Aalto University publication series

DOCTORAL DISSERTATIONS 232/2019

© 2019 Aki Tilli

ISBN 978-952-60-8874-7 (printed)

ISBN 978-952-60-8875-4 (pdf)

ISSN 1799-4934 (printed)

ISSN 1799-4942 (pdf)

<http://urn.fi/URN:ISBN:978-952-60-8875-4>

Unigrafia Oy

Helsinki 2019

Finland

Author
Aki Tili**Name of the doctoral dissertation**

Alternative Fuels and Emission Control Methods in Compression Ignition Engines

Publisher School of Engineering**Unit** Department of Mechanical Engineering**Series** Aalto University publication series DOCTORAL DISSERTATIONS 232/2019**Field of research** Energy Technology**Manuscript submitted** 8 October 2019**Date of the defence** 19 December 2019**Permission for public defence granted (date)** 28 October 2019**Language** English☐ **Monograph**☒ **Article dissertation**☐ **Essay dissertation****Abstract**

The focus of this doctoral thesis is on the effect of alternative diesel fuels on engine performance, emissions, and emission reduction technologies in diesel engines. The studies focused on normal engine operation, enhanced engine parameters for biofuel use, and on modern aftertreatment technologies. The research included engine experiments, simulations, and optical studies. Especially hydrotreated vegetable oil (HVO) and its blends were studied. For comparison, standard EN590 fulfilling regular diesel and its blends with traditional biodiesel (FAME) were also investigated.

FAME and HVO represent different biofuel generations. FAME is a first generation biofuel with typically small-scale production and varying product quality. It consists of oxygen-containing esters not found in pure fossil diesel. Additionally, FAME has lower energy content. The maximum amount of FAME is 7% in standard EN590. HVO is a second generation biofuel with typically large-scale production and high quality. HVO consists of paraffinic hydrocarbons - compounds found also in regular diesel. High proportions of HVO can typically be used in diesel engines without any modifications.

The first part of this thesis involves biofuels and their effects on medium-speed diesel engine performance and emissions. The biofuels were evaluated with simulations, and the effects of 100% HVO on engine performance and emissions were investigated with engine experiments. Internal exhaust gas recirculation (iEGR) and Miller timing were studied with regular diesel and HVO. The latter part of the thesis focuses on late post-injections (LPI) with 30% blends of HVO and FAME, used for diesel particulate filter (DPF) regeneration in an off-road diesel engine. During the LPI mode, exhaust gas temperature rise in the diesel oxidation catalyst (DOC), emissions, and oil dilution were investigated. Additionally, the corresponding fuel sprays were investigated in optical engines.

With 100% HVO, the compatibility, performance and emissions were first investigated with no engine parameter changes. With Miller timing and iEGR, the high ignitability lead to significant nitrogen oxide (NOx) decrease, with no fuel consumption or particulate matter (PM) emission increase. In contrast to the typical NOx-PM -trade-off, both emissions were lowered. In the LPI studies, no drawbacks were found with 30% HVO blend. 30% FAME blend resulted in worse oil dilution related to LPI's, and increased emissions during the LPI mode. No significant differences in the LPI spray lengths were measured between the fuels. Thus, the differences in the oil dilution were contributed to the distillation characteristics of the fuels.

Keywords Biofuels, diesel engine, emission reduction, HVO, FAME, biodiesel, paraffinic diesel**ISBN (printed)** 978-952-60-8874-7**ISBN (pdf)** 978-952-60-8875-4**ISSN (printed)** 1799-4934**ISSN (pdf)** 1799-4942**Location of publisher** Helsinki**Location of printing** Helsinki**Year** 2019**Pages** 167**urn** <http://urn.fi/URN:ISBN:978-952-60-8875-4>

Tekijä
Aki Tili

Väitöskirjan nimi

Vaihtoehtoiset polttoaineet ja päästöjen vähennysteknologiat puristussytytteissä moottoreissa

Julkaisija Insinööritieteiden korkeakoulu

Yksikkö Konetekniikan osasto

Sarja Aalto University publication series DOCTORAL DISSERTATIONS 232/2019

Tutkimusala Energiatekniikka

Käsikirjoituksen pvm 08.10.2019

Väitöspäivä 19.12.2019

Väittelyluvan myöntämispäivä 28.10.2019

Kieli Englanti

☐ **Monografia**

☒ **Artikkeliväitöskirja**

☐ **Esseeväitöskirja**

Tiivistelmä

Tämän väitöstutkimuksen tavoitteena on vertailla vaihtoehtoisten dieselpolttoaineiden vaikutuksia dieselmoottorien toimintaan, päästöihin ja päästöjen vähennystekniikoihin. Tutkimusmenetelminä olivat moottorikoeajot, simuloinnit sekä optiset mittaukset. Moottorikoeajoissa käytettiin tavanomaisia moottoriparametreja, biopolttoaineiden käyttöä varten muokattuja venttiilien ajoituksia, sekä nykyaikaisia jälkikäsitteilyteknologioita. Erityisesti keskityttiin vetykäsiteltyyn kasviöljyyn (HVO) ja sen sekoituksiin. Vertailua varten käytettiin standardin EN590 täyttävää dieselpolttoainetta sekä sen sekoituksia perinteisen biodieselin (FAME) kanssa.

FAME ja HVO edustavat kahta biopolttoaineiden sukupolvea. FAME:n tuotanto on yleensä pienimuotoista ja lopputuotteen laatu vaihtelee. FAME koostuu happea sisältävistä estereistä, joita ei ole puhtaassa fossiilisessa dieselissä. Sillä on lisäksi pienempi energiasisältö. FAME:a saa standardin EN 590 mukaan olla dieselpolttoaineessa enintään 7%. HVO:n tuotannon mittakaava on tyypillisesti suurempi ja lopputuotteen laatu korkea. HVO koostuu parafiinisista hiilivedyistä, joita on ainesosina myös fossiilisissa polttoaineissa. HVO:ta voidaan tyypillisesti käyttää muokkaamattomissa dieselmoottoreissa hyvin korkeissa seossuhteissa.

Ensimmäinen osa väitöskirjatutkimuksesta keskittyy biopolttoaineisiin ja niiden vaikutuksiin keskinopeassa dieselmoottorissa. Polttoaineita arvioitiin simulaatiotutkimuksilla, ja puhtaan HVO:n vaikutuksia moottorin suorituskykyyn ja päästöihin tutkittiin moottorikokein. Sisäistä pakokaasujen takaisinkierätystä (iEGR) ja Miller-ajoitusta tutkittiin tavanomaisella dieselpolttoaineella ja HVO:lla. Väitöskirjan toinen osio keskittyy dieselmoottorin hiukkassuodattimen (DPF) regeneroinnissa käytettäviin myöhäisiin jälkiriisutuksiin (LPI) 30% HVO- tai FAME -seoksilla. LPI-moodin aikana tutkittiin pakokaasujen lämpötilaa hapetuskatalysaattorissa (DOC), pakokaasupäästöjä, sekä öljynlaimenemaa. Vastaavia polttoainesuihkuja tutkittiin optisissa moottoreissa.

Puhtaalla HVO:lla tutkittiin ensin yhteensopivuutta, suorituskykyä ja päästöjä moottoriparametreja muuttamatta. Miller-ajoituksen ja iEGR:n yhdistelmällä HVO:n korkea setaaniluku johti typenoksidipäästöjen (NOx) merkittävään vähenemiseen ilman hiukkaspäästöjen (PM) tai polttoaineen kulutuksen lisääntymistä. Huomionarvoista on, että NOx- ja PM -päästöt laskivat yhtäaikaaisesti, mikä poikkeaa tyypillisestä käänteisestä korrelaatiosta. LPI -tutkimuksissa ei havaittu HVO -seokseen liittyviä ongelmia. Sen sijaan FAME -seos johti myöhäistettyjen jälkiriisutusten aiheuttaman öljynlaimenemaongelman pahenemiseen, sekä suurempiin päästöihin LPI -moodin aikana. Koska polttoainesuihkujen tunkeutumisessa ei havaittu eroja, öljynlaimenemaerojen arvioitiin johtuvan polttoaineiden erilaisista tislauksominaisuuksista.

Avainsanat Biopolttoaineet, dieselmoottori, päästöjen vähentäminen, HVO, FAME, biodiesel, parafiininen diesel, jälkikäsitteily

ISBN (painettu) 978-952-60-8874-7

ISBN (pdf) 978-952-60-8875-4

ISSN (painettu) 1799-4934

ISSN (pdf) 1799-4942

Julkaisupaikka Helsinki

Painopaikka Helsinki

Vuosi 2019

Sivumäärä 167

urn <http://urn.fi/URN:ISBN:978-952-60-8875-4>

Acknowledgements

This doctoral thesis was carried out at the Department of Mechanical Engineering (previously the Department of Energy Technology) of Aalto University, under the supervision and guidance of Professor Martti Larmi.

Financial support for the thesis came from Merenkulun säätiö, Henry Fordin Säätiö and Foundation for Aalto University Science and Technology. TEKES, Neste, Wärtsilä and Agco Power have contributed to the research projects, fuels, equipment and information that have made the research possible.

I would like to express my eternal gratitude to Professor Larmi for all the possibilities, support, guidance and understanding during my years at Aalto, and for enabling the interesting research work in his group. I would also like to thank my advisors, D.Sc. Teemu Sarjovaara and D.Sc. Ossi Kaario for their many comments, suggestions and invaluable advice on the research and the articles of this doctoral thesis.

I also owe my thanks to the project partners – especially the people at Neste, Agco Power and Wärtsilä for the long-time collaboration. I am very grateful for all the co-authors of my publications – especially Matteo Imperato, Tuomo Hulkkonen and Ossi Kaario, whose work has been crucial for this thesis.

Furthermore, I would like to thank all of my co-workers at the engine laboratory at Aalto for all the support for my research and for creating an excellent working atmosphere. Especially Olli Ranta, Otto Blomstedt and Rasmus Petinen have made the engine experiments possible with their technical expertise, work, and helpful attitude.

Thanks to my parents, for the support, understanding and a helping hand whenever it was needed. And thank you for my sanity, my friends from Veikkola, POKA, Teekkarispeksi, Värinä, Vinkkeli and Vanttera. Without the distractions and you people, I would not be who and what I am today.

And finally, I would like to thank my wife Laura, for your patience, and for each kick in the butt whenever it has been necessary. Laura, Silja and Elsa: you are the light of my life and the bedrock under my feet. You have made this possible.

Espoo, 20 November 2019
Aki Tilli

Contents

Acknowledgements.....	1
List of Abbreviations and Symbols.....	5
List of Publications	10
Authors' Contribution.....	11
1. Introduction.....	13
2. Background.....	15
2.1 Compression-ignition engines.....	15
2.2 Fuel injection system	16
2.3 Diesel combustion	17
2.4 Diesel fuel	18
2.4.1 Diesel fuel properties.....	18
2.5 Alternative fuels for diesel engines.....	21
2.5.1 Conventional biodiesel	21
2.5.2 Paraffinic diesel fuels.....	22
2.5.3 Fuel comparison	25
2.6 Emission formation in diesel engines	25
2.6.1 Nitrogen oxides.....	26
2.6.2 Particulates	27
4.1.1 Connection between NOx and PM emissions.....	28
2.6.3 Hydrocarbons	29
2.6.4 Carbon Monoxide	29
2.7 Emission Legislation	30
2.8 Aftertreatment technologies.....	31
2.8.1 Diesel Oxidation Catalyst (DOC).....	31
2.8.2 Diesel Particulate Filter (DPF)	32
2.8.3 Selective Catalytic Reduction (SCR).....	33
2.9 In-cylinder emission reduction technologies	33
2.9.1 Miller cycle.....	33
2.9.2 Exhaust gas recirculation (EGR)	35

2.9.3	Internal EGR	36
3.	Effects of Alternative Diesel Fuel Properties	37
3.1	Fuel property effects on fuel injection and fuel systems.....	38
3.2	Fuel property effects on fuel sprays and mixing	41
3.3	Fuel property effects on ignition and combustion	43
3.4	Fuel property effects on emissions and emission control.....	45
4.	Experimental Methods.....	51
4.1	The fuels studied in the research	51
4.2	The engines used in the experiments	51
4.2.1	Agco production engine	52
4.2.2	LEO2 engine.....	53
4.2.3	EVE Engine	55
4.3	Simulation models	57
4.3.1	GT-Power model	57
4.3.2	GT-Fuel model	58
5.	Summary of Publications	59
5.1	Publication 1	59
5.2	Publication 2	60
5.3	Publication 3	62
5.4	Publication 4	63
5.5	Publication 5.....	64
5.6	Publication 6	65
6.	Conclusions and Further Research	67
6.1	Summary and Conclusions	67
6.2	Suggestions for Future Work	70
	References	71

List of Abbreviations and Symbols

Al ₂ O ₃	Aluminium oxide
ASOI	After start of injection
ATR	Auto thermal reforming
BBDC	Before bottom dead centre
BDC	Bottom dead centre
BTE	Brake thermal efficiency
BTL	Biomass-to-liquids
C ₂ H ₂	Acetylene
CA°	Crank angle
CCD	Charge-coupled device
CDPF	Catalysed diesel particulate filter
CeO ₂	Cerium oxide
CEN	European Committee of Standardization
CFD	Computational fluid dynamics
CFPP	Cold filter plugging point
CH ₄	Methane
CI	Compression-ignition
CN	Cetane number
CNG	Compressed natural gas
CO	Carbon monoxide
CO ₂	Carbon dioxide
CRT	Continuously regenerating trap
CTL	Coal-to-liquids
DF	Dual-fuel

DI	Direct injection
DME	Dimethyl ether
DOC	Diesel oxidation catalyst
DPF	Diesel particulate filter
ECA	Emission control area
ECU	Electronic control unit
EEVC	Early exhaust valve closing
EGR	Exhaust gas recirculation
EHVA	Electro-hydraulic valve actuator
EN14214	International standard for FAME biodiesels
EN590	European Standard for diesel fuel
EOI	End of injection
EU	European Union
EURO I-VI	European emission standards, stages I-VI
EVE	Extreme value engine
FAEE	Fatty acid ethyl ester
FAME	Fatty acid methyl ester
FC	Fuel cell
FCC	Fluid catalytic cracking
FID	Flame ionization detector
FPGA	Field-programmable gate arrays
FSN	Filter smoke number
FT	Fischer-Tropsch
GHG	Greenhouse gas
GTL	Gas-to-liquids
H ₂	Hydrogen (molecule)
H ₂ S	Hydrogen sulphide
HBD	Hydro-generated biodiesel
HC	Hydrocarbon
HC-SCR	Hydrocarbon selective catalytic reduction
HCCI	Homogenous charge compression ignition

HCN	Hydrocyanic acid
HDRD	Hydrogenation derived renewable diesel
HEV	Hybrid-electric vehicle
HFRR	High Frequency Reciprocating Rig
HRR	Heat release rate
HVO	Hydrotreated vegetable oil
ID	Ignition delay
IEA	International Energy Agency
iEGR	Internal exhaust gas recirculation
IMO	International marine organization
IVC	Intake valve closing
LCA	Life-cycle analysis
LED	Light-emitting diode
LIVO	Late intake valve opening
LNG	Liquefied natural gas
LPG	Liquefied petroleum gas
LPI	Late post-injection
LTC	Low temperature combustion
MARPOL	International Convention for the Prevention of Pollution from Ships
MN	Methane number
NDIR	Non-dispersive infrared
NEXBTL	Paraffinic renewable diesel of Neste
N ₂	Nitrogen (molecule)
NG	Natural gas
NGV	Natural gas vehicle
NH ₃	Ammonia
NO	Nitric oxide
NO ₂	Nitrogen dioxide
NO ₃	Nitrate
NO _x	Nitrogen oxides

N ₂ O	Nitrous oxide
N ₂ O ₃	Dinitrogen trioxide
N ₂ O ₄	Dinitrogen tetroxide
N ₂ O ₅	Dinitrogen pentoxide
NVO	Negative valve overlap
OH	Hydroxyl radical
PAH	Polycyclic aromatic hydrocarbons
Pd	Palladium
PGM	Platinum group metals
PIV	Particle image velocimetry
PM	Particulate matter
Pt	Platinum
RED	Renewable Energy Directive
RGF	Residual gas fraction
Rh	Rhodium
RME	Rapeseed methyl ester
rpm	Rounds per minute, unit for engine speed
SCR	Selective catalytic reduction
SMD	Sauter mean diameter
SOC	Start of combustion
SOI	Start of injection
SO ₂	Sulphur dioxide
SO ₃	Sulphur trioxide
SO _x	Sulphur oxides
TAN	Total acid number
TBN	Total base number
TDC	Top dead centre
THC	Total hydrocarbons
Tier I-III	IMO emission standard levels I-III
WWFC	Worldwide fuel charter
ZrO ₂	Zirconium oxide

γ	Specific heat ratio
Φ	Fuel-air equivalence ratio
λ	Excess air ratio

List of Publications

This doctoral dissertation consists of a summary and the following publications, which are referred to in the text by their numerals:

- 1.** Tilli, Aki; Hulkkonen, Tuomo; Kaario, Ossi; Larmi, Martti; Sarjovaara, Teemu; Lehto, Kalle. 2018. Biofuel blend late post-injection effects on oil dilution and diesel oxidation catalyst performance. *International Journal of Engine Research*, volume 19, issue 9, pages 941-951. eISSN: 20413149 | ISSN: 14680874. doi: 10.1177/1468087417736466. JUFO class = 1.
- 2.** Hulkkonen, Tuomo; Tilli, Aki; Kaario, Ossi; Ranta, Olli; Sarjovaara, Teemu; Vuorinen, Ville; Larmi, Martti; Lehto, Kalle. 2017. Late Post-injection of Biofuel Blends in an Optical Diesel Engine: Experimental and Theoretical Discussion on the Inevitable Wall-wetting Effects on Oil Dilution. *International Journal of Engine Research*, volume 18, issue 7, pages 645-656. eISSN: 20413149 | ISSN: 14680874. doi: 10.1177/1468087416663548. JUFO class = 1.
- 3.** Imperato, Matteo; Tilli, Aki; Sarjovaara, Teemu; Larmi, Martti. 2012. Large-Bore Compression-Ignition Engines: High NO_x Reduction Achieved at Low Load with Hydro-Treated Vegetable Oil. *SAE. SAE International Journal of Fuels and Lubricants*, volume 5, issue 1, pages 225-232. eISSN: 1946-3960 | ISSN: 1946-3960. doi: 10.4271/2011-01-1956. JUFO class = 1.
- 4.** Imperato, Matteo; Tilli, Aki; Sarjovaara, Teemu; Larmi, Martti. 2012. Hydro-treated Vegetable Oil and Miller Timing in a Medium-Speed CI Engine. *SAE Technical Paper 2012-01-0862*. eISSN: 0148-7191 ISSN: 0148-7191. doi: 10.4271/2012-01-0862. JUFO class = 1.
- 5.** Kaario, Ossi; Tilli, Aki; Hillamo, Harri; Sarjovaara, Teemu; Vuorinen, Ville; Larmi, Martti. 2009. Liquid Spray Data from an Optical Medium-Speed Diesel Engine and its Comparison with CFD. *SAE Technical Paper Series 2009-01-2676*. eISSN: 0148-7191 ISSN: 0148-7191. doi: 10.4271/2009-01-2676. JUFO class = 1.
- 6.** Tilli, Aki; Kaario, Ossi; Imperato, Matteo; Larmi, Martti. 2009. Fuel Injection System Simulation with Renewable Diesel Fuels. *SAE Technical Paper Series 2009-24-0105*. eISSN: 0148-7191 ISSN: 0148-7191. doi: 10.4271/2009-24-0105. JUFO class = 1.

Authors' Contribution

Publication 1: Biofuel blend late post-injection effects on oil dilution and diesel oxidation catalyst performance.

The author has written the paper in its entirety, partly with the help of the co-authors. The author has participated in planning and executing the test runs and measurements. The data from the measurements has also been analysed and visualized by the author. The author has made the conclusions of the paper.

Publication 2: Late Post-injection of Biofuel Blends in an Optical Diesel Engine: Experimental and Theoretical Discussion on the Inevitable Wall-wetting Effects on Oil Dilution.

The author has written the basis of the background study involving DPF regeneration and oil dilution; the responsible author of the paper has edited and added to it. The author has also written the introduction of the six-cylinder test engine and its runs and the basis for the results and discussion involving the runs. The author has participated in planning and executing all the test runs and measurements. The data from the six-cylinder engine measurements has also been analysed and visualized by the author. The author has been involved in making the conclusions of the paper.

Publication 3: Large-Bore Compression-Ignition Engines: High NO_x Reduction Achieved at Low Load with Hydro-Treated Vegetable Oil.

The author has written the main parts of the literature review introducing fuel injection, fuels (HVO), fuel properties and their effects on emissions. Based on these, the author was involved in planning the test runs and making the conclusions of the paper.

Publication 4: Hydrotreated Vegetable Oil and Miller Timing in a Medium-Speed CI Engine.

The author has written the parts of the literature review introducing engine emission regulations, hydrotreated vegetable oil (HVO) and its properties affecting engine operation and especially emissions. Based on these factors, the author was involved in planning the test runs and making the conclusions of the paper.

Publication 5: Liquid Spray Data from an Optical Medium-Speed Diesel Engine and its Comparison with CFD.

The author has made the simulation model and the simulations with GT-Fuel to give fuel injection boundary conditions (fuel mass flow data) for the CFD simulations and the sensitivity analysis. The author has also written the introduction to the fuel injection 1-D simulation model and the simulations and was involved in making the conclusions.

Publication 6: Fuel Injection System Simulation with Renewable Diesel Fuels

The author is the main writer of the publication in its entirety. The author has also made the conclusions and planned and executed the simulations. The author has built the simulation models of the fuel injection system and (based on previous research) modelled the behaviour of the fuels in high temperatures and pressures with the commercial simulation program, GT-Fuel. In addition, the author also presented this work at the International Conference on Engines and Vehicles 2009 in Capri, Naples, Italy.

1. Introduction

Because of the looming climate crisis, in order to replace fossil energy, alternatives to traditional transportation energy sources are being studied, developed, and introduced to the market at an increasing rate. However, especially in long-haul heavy duty and many off-road applications, the diesel engine will most likely dominate the markets for a long time due to the range, fuel economy, reliability, and durability of the technology. This means that there is a growing demand for low-emission alternative diesel fuels, the most common being biodiesel (FAME) and paraffinic fuels: synthetic diesel or hydrotreated vegetable oil (HVO).

To reach the very low emission regulation limits of today, diesel engines need such aftertreatment technologies as diesel oxidation catalysts (DOCs), diesel particulate filters (DPFs), and selective catalytic reduction (SCR), in combination with in-cylinder emission reduction technologies, e.g. exhaust gas recirculation (EGR) and the Miller cycle. This brings about new challenges, as emission reduction technologies and fuel specifications are changing, and the use of alternative fuels is increasing. Thus, there is a need for thorough research on the combination of diesel engines, new fuels and emission reduction technologies to study the impact on the performance of the engine and its auxiliary systems, as well as the emissions. This doctoral research highlights the effect of modern biofuels in combination with diesel engine emission reduction technologies.

The focus of this doctoral thesis is on the effect of biofuels on engine performance and emissions during normal engine operation, with enhanced engine parameters for biofuel use and with modern aftertreatment technologies. The research questions in the doctoral thesis are as follows:

1. How does HVO affect diesel engine performance and emissions during typical engine operation?
2. How can low emissions be reached with HVO with no significant performance penalties in diesel engines without external aftertreatment methods?
3. How do biofuels affect late post-injection fuel sprays and required fuel injection parameters?
4. How do biofuel late post-injections affect oil dilution and DOC performance during the DPF regeneration mode in an off-road diesel engine?

The research was carried out at Aalto University's Department of Mechanical Engineering. Originally, the research was presented in the six scientific articles that comprise this thesis. The research results have given new knowledge on emissions and engine performance on engines run on alternative diesel fuels, using such emission reduction technologies as the Miller cycle and internal EGR, as well as the impact of biofuel blends on the DOC performance during the DPF regeneration cycle of an off-road diesel engine. Additionally, a part of this thesis has been the combination of optical studies, simulations and computational fluid dynamics (CFD) calculations, applied to engine research to complement the experimental measurements.

2. Background

2.1 Compression-ignition engines

The focus of this thesis is on compression ignition engines. The concept of compression-ignition (CI) engine was patented in 1892 by Rudolf Diesel. The CI engine is used in a wide variety of applications from small automobiles to ships and power plants (Majewski et al. 2006).

In Figure 1, different stages of the diesel cycle are presented. During the intake stroke (1), the retraction of the piston causes suction. The intake valves are open and fresh air flows through the valves into the cylinder. At bottom dead centre (BDC), the piston is at its lowest point, and typically, the intake valves are closed. In the compression stroke (2), the piston movement compresses the air. Thus, high pressure and temperature are achieved. If intake valve is closed earlier or later than the BDC, the pressure at the end of the stroke remains lower. This “Miller timing” technique has some positive effects and is studied in publications 3 and 4 of this thesis. Typically, the fuel injection occurs near the top dead centre (TDC) at the end of the compression stroke. Load control is realized by varying the fuel injection duration. In high injection pressures typical of Diesel engine, the fuel breaks up into tiny droplets, and the fuel jet penetrates deep into the combustion chamber. Fuel injection is simulated in publication 6 and injection parameter effects on diesel fuel sprays, and their behaviour in engine environment are modelled in publication 5 of this thesis (Heywood 1988, Van Basshuysen et al. 2004, Heisler 1995).

Figure 1. The four stages of a four-stroke diesel engine cycle. The rotation is clockwise (Van Basshuysen 2004).

In high pressure and temperature, fuel droplets vaporize quickly and mix with air. The air-fuel blend ignition occurs in parts of the fuel spray. The hot air-fuel mixture ignites after the ignition delay (ID), still close to the TDC. During the expansion stroke (3), the occurring heat release causes high pressure inside the cylinder. The pressure forces the piston to move. The reciprocating motion becomes rotational motion via a connecting rod connecting the piston to the crankshaft. During the expansion stroke, at times also very late post-injections (LPI's) may be used to induce DPF regeneration. The LPI's and their effects are studied in publications 1 and 2 of this thesis. During the exhaust stroke (4), the piston moves towards the top dead centre, and the gases remaining in the cylinder from the combustion of the fuel-air mixture are pushed out through the exhaust valve. The exhaust valve is then closed, the intake valve opened, and the process can repeat itself. Typically, the intake and exhaust valves are simultaneously open at the end of each cycle. This scavenging phase promotes the gas exchange in the cylinder. It is studied and tampered with (by diminishing the valve overlap) in publications 3 and 4 of this thesis (Heywood 1988, Van Basshuysen et al. 2004, Heisler 1995).

2.2 Fuel injection system

In the CI engines of this thesis, common rail fuel injection systems are used. In a common rail system, all the injectors of the engine are behind the same pressure system with a volume common to all injection nozzles. A single high-pressure pump holds the pressure at a pre-defined, steady and high level. Electronic control unit (ECU) operates the control valves and the injection parameters freely. The injection profile can be controlled very precisely. The high injection pressures have been shown to promote the mixing of air and fuel, and to reduce emissions. In this thesis, the rail pressure ranged from 600 bar (optical engine in publication 2) to 1400 bar (EVE engine in publications 4-5). A simulation model of the fuel injection system of EVE research engine (presented in publication 6) was used in publications 3, 4 and 5 (Pitkänen 2000, Heisler 1995).

Figure 2. Injector nozzle (Heisler 1995).

A fuel injection nozzle (Figure 2) has a number of 0,1-1 mm diameter injector holes. One injector can usually have up to ten injection holes. In the engines used in this thesis, the amount of nozzle holes was 8-9 (1 in publication 5), while the orifice diameter ranged from 0,132 mm (publications 1 and 2) to 0,36 mm (Heywood 1998, Heisler 1995).

2.3 Diesel combustion

In diesel engines, fuel is injected into the engine cylinder, where the fuel ignites in the high cylinder pressure and temperature. There are four phases of diesel combustion (see Figure 3): (1) ignition delay, (2) premixed combustion, (3) mixing controlled (diffusion) combustion, and (4) the late combustion (Heywood 1988, Guibet 1999, Challen et al. 2009, Belal et al. 2013).

Figure 3. The phases of diesel combustion and heat release rate in relation to injection timing in a diesel engine. SOI means “start of injection” and EOI “end of injection”. (Heywood 1988).

Ignition delay (ID) is defined as the time between the start of injection (SOI) and the start of combustion (SOC). During ID, due to the fuel velocity and the ambient high density, pressure and temperature, the diesel fuel breaks up into small droplets, vaporizes quickly and is mixed with ambient air. High injection pressures induce turbulence, further enhancing the mixing process. The fuel vapour goes through chemical reactions, producing the chemical species necessary for spontaneous ignition. Finally, a combustible fuel-air mixture is formed. The ID changes with the fuel properties, the injection settings and in-cylinder conditions. High ignitability (cetane number, CN), which shortens the ID phase, is a major advantage of modern high-grade diesel fuels. These high CN effects are discussed in the literature study of publication 6 of this thesis. In the experiments of this thesis (publications 3 and 4, and to some extent, publication 1), focus is on the possibilities and effects of these high CN fuels on emission reduction (Heywood 1988, Challen et al. 2009).

As the mixture reaches ignition conditions, the rate of combustion and the heat release rate (HRR) increase rapidly. This premixed combustion phase usually leads to high local in-cylinder temperatures and undesired exhaust gas emissions. The phase lasts a few crank angles (CA°), and it ends when the premixed fuel has been combusted. Therefore, as a rule of thumb, the longer the ID phase is, the higher the HRR and pressure peak are during the premixed combustion phase. The shortened ID phase (seen in publications 3 and 4 of this thesis) given by the high CN fuels lead to diminished premixed combustion phase and lower emissions (Heywood 1988, Challen et al. 2009).

The mixing-controlled combustion (diffusion combustion) is controlled by turbulent air movement and fuel spray characteristics. The combustion rate is high, as the air in the combustion chamber rapidly entrains the fuel spray. The diffusion combustion is typically the dominant phase in diesel combustion, and it can often be characterized by a second peak in the HRR curve around the end of injection (EOI) (Heywood 1988, Challen et al. 2009).

The late combustion phase starts after the EOI. The combustion rate decreases due to lower oxygen content and fuel available in the cylinder. The phase is mainly controlled by reaction kinetics. The late combustion phase is important for the engine-out emission formation process: hydrocarbon (HC) and soot emissions depend significantly on this phase. The paraffinic components (or, more precisely, the lack of other components) in alternative diesel fuels studied in this thesis play a role in diminishing the emissions in the late combustion phase. Late post-injections to regenerate DPF (discussed in publications 1-2 of this thesis) are initiated as early as possible after the late combustion phase has ended, so that the fuel will evaporate well, but not ignite (Heywood 1988, Challen et al. 2009, Tilli et al. 2010).

2.4 Diesel fuel

Fossil diesel fuel is produced in the crude oil distillation process, where the mid-length distillation fractions are suitable for diesel engines. Distillation products are further processed or are used as components of commercial diesel fuels as such. The end-product diesel fuel is a mixture of the distillates and additives. Thus, fuels with different characteristics can be produced. Standard fossil diesel fuel is composed of hundreds of different hydrocarbons that usually have 12–20 carbon atoms each. The boiling points are usually between 180 and 360 °C (distillation range). Compared with gasoline, the hydrocarbons in diesel are heavier and their boiling points are higher. Average diesel fuel consists of about 86.5 w-% carbon and 13.5 w-% hydrogen (Raiko et al. 2002, Guibet 1999, Colwell 2005, Mikkonen et al. 2007).

2.4.1 Diesel fuel properties

The most common standard used for diesel fuel quality is the European standard EN 590. Additionally, new standards (e.g. WWFC) for high-quality diesel fuels have been introduced. EN 590 determines the physical property limits the diesel fuels sold in the EU must fulfil. The latest revision for EN 590

was made in 2013. The properties of vehicle diesel fuels are divided into four classes: usability, cold operation, environmental, and storage properties (EU 2013, Raiko et al. 2002, Guibet 1999, Mikkonen et al. 2007, Colwell 2005, Neste 2016).

Chemical properties of the fuel have a direct impact on combustion and emissions from the engine. For instance, oxygen content and paraffinic nature of fuel hydrocarbons typically have positive effects. The fuel chemistry also has to be compatible with the materials of the engine. In this thesis, the focus has partially been on purely paraffinic fuels, which burn more cleanly than standard diesel fuel (publications 1-4 and 6). Oxygen-containing (ester-based) regular biodiesel has been studied and discussed in publications 1, 2 and 6 (Johansson 2012, Fanick 2001, Larsson 2007, Azimov 2008, Dec 1997, Raiko et al. 2002, Guibet 1999, Mikkonen et al. 2007).

Density of regular diesel fuel should be 820–845 kg/m³ (at 15 °C), according to standard EN 590. With alternative diesel fuels, the fuel density is often outside of this range. The density of summer class diesels is usually higher than that of winter class diesels. The volume of the fuel injected per cycle is the controlled factor in a diesel engine, and density has an effect on it and other injection parameters of the fuel. Engine type and construction of the injection system define how much effect the differences in fuel density have. Density is directly linked to the chemical fuel composition, and the paraffinic fuels studied in this thesis (publications 1-4 and 6) have lower densities than regular fossil diesel fuel. On the contrary, regular biodiesel (studied in publications 1, 2 and 6) densities are typically higher (Raiko et al. 2002, Guibet 1999, Mikkonen et al. 2007, Johansson 2012, Tilli et al. 2010, Wattrus 2013, Semião et al. 1996, Hiroyasu et al. 1990, Agarwal et al. 2012).

Heating value is the energy density of the fuel. Typical winter and summer class diesel fuel heating values are roughly the same — about 43 MJ/kg. The heating value has an effect on the power received from the engine. Alternative diesel fuel heating values may have significant differences from regular diesel. Additionally, due to fuel density differences, the energy received from a certain injected fuel volume may vary even more. Regular biodiesel has typically a slightly lower heating value, while the paraffinic fuels have higher mass-based (but lower volume-based) heating values than fossil diesel fuels. Fuel heating value differences are discussed especially in the literature study of publication 6, and the effect on DPF regeneration are discussed in publications 1 and 2 of this thesis (Raiko et al. 2002, Guibet 1999, Mikkonen et al. 2007, Tilli et al. 2010).

Viscosity is “a measure of the resistance of a fluid to deform under shear stress”. Viscosity describes the fluid flow resistance (“fluid friction”). The (kinematic) viscosity of a diesel fuel is measured at +40 °C, and it should be 2.0–4.5 mm²/s according to EN 590. A rise in temperature decreases (and a decline increases) viscosity. Viscosity has significant effects on fuel injection phenomena and fuel spray characteristics. Generally, alternative diesel fuels have viscosity deviations from fossil diesel, but usually within EN 590 limits. Regular biodiesel typically has higher viscosity than fossil diesel, which has been signif-

icant in publications 1, 2 and 6 of this thesis. Paraffinic fuels have typically slightly lower viscosities than fossil diesel on the average, which has effects in the studies of publications 1-4 and 6 of this thesis. Dimethyl ether was left out of the experimental projects in part because of its very low viscosity and the resulting effects discussed in publication 6 of this thesis (Raiko et al. 2002, Guibet 1999, Mikkonen et al. 2007, Semião et al. 1996, Wattrus 2013, Kitano et al. 2005, Tilli et al. 2010).

Cetane number (CN) describes the fuel ignitability in compression. In diesel engines, if the cetane number is high enough, the ignition delay is short and the premixed combustion phase is not dominant. The good ignitability of high CN fuels studied in this thesis (publications 1-4 and 6), usually has benefits also during the later combustion phases. In standard EN 590, the diesel fuel cetane number has been set to be at least 51. With modern alternative diesel fuels, the cetane number is usually much higher (Raiko et al. 2002, Guibet 1999, Mikkonen et al. 2007, Tilli et al. 2010, Kitano et al. 2005, Abu-Jrai et al. 2006, Lepperhoff et al. 2006, McMillian et al. 2001, Larsson et al. 2007, Azimov et al. 2007, Nishiumi et al. 2009).

Distillation area is the temperature area where the fuel evaporates if it is slowly warmed in the atmospheric pressure. Distillation characteristics affect the cold operation and fuel spray characteristics (relevant in publications 1,2 and 5 of this thesis), as well as the oil dilution and emissions performance of the fuel (studied in publications 3 and 4). Typical distilling area of summer-grade diesel fuel is 180–360 °C. Winter-grade fuels have slightly lower distillation temperatures. Alternative diesel fuel distillation characteristics may differ greatly from regular diesel. Of the fuels studied in this thesis, regular biodiesel has typically very high distillation temperatures, while with the paraffinic fuels, the distillation temperatures and the final boiling point is typically low when compared with standard diesel fuels (Raiko et al. 2002, Guibet 1999, Mikkonen et al. 2007, Tilli et al. 2010, Kitano et al. 2005, Kono 2005).

Cloud point is the lowest storage temperature of the fuel. When fuel temperature decreases, the first normal (straight chain) paraffin hydrocarbons of the fuel start to crystallize at the cloud point: the fuel starts to look cloudy. The paraffins are useful for the combustion properties of the fuel, and they keep the cetane number high, so they cannot be removed from the fuel. The solution with paraffinic fuels studied in this thesis (publications 1-4 and 6) is to use isomerized (branching) paraffins, which have better cold properties. Regular biodiesels (studied in publications 1, 2 and 6) typically have significantly higher cloud points than regular diesel (Raiko et al. 2002, Guibet 1999, Mikkonen et al. 2007, Tilli et al. 2010).

Aromatics are ring-shaped hydrocarbons whose combustion properties are usually poor. The aromatic content of diesel fuel has been limited in EU in order to reduce traffic emissions, as the fuel aromatic hydrocarbons are a major source of engine PM emissions. Around the world, the limitations are quite different and difficult to compare, since the terminology has not been standardized. In the EU, the word ‘polyaromatics’ usually refers to aromatics with two or more rings, but in Scandinavia it refers to aromatics with three or more

rings. Some polyaromatics are very toxic and carcinogenic. The alternative fuels studied in this thesis (publications 1-4 and 6) contain no aromatics (Rai-ko et al. 2002, Guibet 1999, Mikkonen et al. 2007, Tilli et al. 2010, Warnatz 2006, Johansson 2012).

Sulphur content, compressibility (bulk modulus) and vapour pressure have their effects in the engine. Regular diesel fuel sulphur content has to be below 0.001%, according to standard EN 590. In marine applications, fuels with high sulphur content are still used, causing e.g. high SO_x and particulate emissions. Regular biodiesel has low compressibility and vapour pressure. High vapour pressure and compressibility (typical of paraffinic fuels and especially DME) both promote cavitation (detected in the DME simulations of publication 6 of this thesis), which can be either beneficial or degrading to the fuel spray quality (Meier-Peter et al. 2009, Woodward 2009, Som et al. 2010, Boehmann et al. 2004).

2.5 Alternative fuels for diesel engines

Alternative fuels, especially biofuels, are developed, promoted and used to replace the fossil fuels, mainly in order to diminish the life-cycle greenhouse gas emissions of transportation. Alternative fuel properties and their effects in diesel engines are a focal point in publications 1-4 and 6 of this thesis. The European Union (EU) Renewable Energy Directive (RED), 2009/28/EC, promotes renewable energy use. According to the directive, by the year 2020, 20% of gross final energy consumption in the EU has to be renewable energy and every EU country also has an obligation to reach a minimum of 10% renewable energy in transport. RED and the Directive to reduce indirect land use change (ILUC) for biofuels and bioliquids ((EU)2015/1513) limit the biofuel raw material areas of origin, as well as the greenhouse gas (GHG) emissions produced during biofuel life cycles. Compared to the use of similar fossil fuels, for each alternative taken into account, the GHG emissions have to be reduced by at least 50% after January 2017. For biofuel production plants built after 1 January 2017, the reduction has to be at least 60% after 1 January 2018. In some cases, GHG emission saving values are given by the directive. Otherwise, it determines the calculation methods for biofuel production chain GHG emissions (EU 2009, EU 2015).

2.5.1 Conventional biodiesel

In spoken language, the term "biodiesel" is used to describe any fuel that has been produced from organic matter and whose cetane number is within diesel fuel limitations. However, in e.g. European standards, only traditional biodiesels are referred to as "biodiesel". These fuels comprise of long fatty acid chains. EN 14214 is the international standard for FAME, approved at CEN (European Committee of Standardization) on 14.2.2003. The latest update for EN 14214 was made in 2012 (Mikkonen et al. 2007, Worldwide Fuel Charter Committee 2009, EU 2012).

Biodiesels are biodegradable, and are not toxic. They contain only trace amounts sulphur or aromatics at maximum. Compared to other bio-based diesel fuels, FAME production is very simple. The feedstocks are either renewable or recycled vegetable oils or cooking oils. Life-cycle GHG emissions are typically decreased when FAME is used instead of fossil fuels. The effects on other emissions are mainly positive. Additionally, FAME can be used as a lubricity improver in fuel mixtures. However, the cold operation characteristics of FAME are worsened compared to typical diesel fuel, and the high boiling range (340–360 °C) can be problematic. Carbon build-up, engine oil dilution, corrosion, and cold smoking have been reported to increase with FAME. FAME is not compatible with long storage times, due to biodegradability and water absorbing tendency. Additionally, FAME production often competes with food production, and its feedstock availability is limited (Yamane et al. 2001, Van Gerpen et al. 2004, Knothe 2004, Nylund et al. 2008).

Thermodynamic properties of FAME resemble those of traditional diesel fuels. The biggest property differences are in chemistry and some physical properties affecting fuel spray quality, which has numerous effects in the engine. FAME sprays during late post-injections and their effects on oil dilution, as well as the effects of the low volatility of FAME on fuel exit rates from the oil have been studied in publications 1 and 2 of this thesis (Yamane et al. 2001, Knothe 2004, Lešnik et al. 2013, Liaquat et al. 2013, Singh et al. 2015, Ejim et al. 2007, Ganapathy et al. 2011).

Because of feedstock and production process variability, FAME composition and properties also vary a lot. For example, cetane number, heating value and viscosity increase as the carbon chain in the ester becomes longer. This has an effect on emissions and performance of the engine. FAME is typically used only as a blend with traditional fuels. In the EN 590 standard, FAME content in diesel blends is limited to 7% (EU 2013, Murugesan et al. 2009).

Biodiesel is produced via transesterification method from fatty acids and alcohols with acid or base catalyst. The alcohol used in biodiesel production is typically methanol. The final product is typically not a 100% biofuel, as the methanol is rarely produced from renewable sources. Other alcohols can also be used, if not as efficiently. Ethanol-based final product is called fatty acid ethyl ester (FAEE) (Yamane et al. 2001, Johansson 2012, Van Gerpen et al. 2004, Knothe 2004).

2.5.2 Paraffinic diesel fuels

Due to the fact that the traditional biodiesels do not fulfil the quality standards set for diesel fuels, production methods to produce higher-quality diesel fuels from bio-based raw materials have been developed. These fuels typically consist of paraffins and have no aromatic content. Based on the feedstock and the production process, they can be classified as either synthetic diesel fuel or hydrotreated vegetable oil. The former are produced from carbon-containing feedstocks via gasification and Fischer-Tropsch (FT) synthesis. The latter is produced from oils and fats by a hydrotreatment process (Nylund et al. 2008, Johansson 2012).

Paraffinic fuel properties are mainly close to those of fossil diesel. The differences include density, which tends to be lower than that of conventional diesel, and the mass-based heating value, which tends to be similar or slightly higher. The volumetric heating values of paraffinic fuels are lower than those of standard diesel, due to the lower density. Due to the lower density, the limits of EN 590 are usually reached with a 30% paraffinic diesel blend. No other deviations from EN 590 values are typical. Paraffin molecules are not polar and thus, the lubricity of a purely paraffinic fuel is usually low. This is easily corrected with additives. Compared to fossil diesel, paraffinic fuel cetane number is typically very high, and the boiling range low. The cold operation and distillation characteristics of paraffinic fuels depend on the carbon chain lengths and the degree of isomerization of the fuel components. Usually the distillation curve is flatter than with fossil diesel, as the hydrocarbon mixture is more homogenous. Paraffinic fuels contain no aromatics or oxygen. With the same engine configuration and injection strategy, fuel economy is usually improved with paraffinic fuels (Nylund et al. 2008, Aatola et al. 2009, Lehto et al. 2012, Tilli et al. 2010).

Paraffinic fuels decrease all regulated emissions in most cases, including NO_x, in contrast to FAME. This is beneficial as such, but also to aftertreatment systems: e.g. lower emissions decrease the required frequency of the DPF regenerations and the aging of the DOC and DPF is slowed. Also other properties of paraffinic fuels have been found to be beneficial to DPF regeneration process via late post-injections, studied in publications 1-2 on this thesis (Aatola et al. 2009, Happonen et al. 2012, Kim et al. 2014, Tilli et al. 2010, Hulkkonen et al. 2011, Lapuerta et al. 2011, Wattrus 2013, Dumitrescu et al. 2015, Derrotte et al. 2012).

Compared to conventional fuels, the high CN of the paraffinic fuels facilitates the use of different injection strategies or exhaust gas in the charge, e.g. such technologies as Miller timing and iEGR. The combination of these technologies and paraffinic diesel were studied in publications 3 and 4 of this thesis (Aatola et al. 2009, Lehto et al. 2012, Happonen et al. 2012, Kim et al. 2014, Tilli et al. 2010).

Hydrotreated vegetable oil

Hydrotreated vegetable oil (HVO) is produced from triglyceride molecules, which are bonded with hydrogen to form paraffinic hydrocarbons. Several other trade names have been adopted for HVO: renewable diesel, hydrogenation derived renewable diesel (HDRD) in the U.S. or hydro-generated biodiesel (HBD) in the Far East. The production process of HVO is based on hydrotreatment of fatty acids. The paraffins are to some extent isomerized into branched-chain paraffins (isoparaffinic hydrocarbons). The components are similar to some compounds created in the production of conventional diesel. Side products include fuel gas and biogasoline. The raw materials can be any vegetable oils or animal fats. The first refinery-scale commercial production facility for HVO was started by Neste in the summer of 2007 (Neste 2016, Nylund et al. 2008, Johansson 2012, Kuronen et al. 2007, Reinhardt et al. 2006, Mäkinen et al. 2005).

The life cycle greenhouse gas emission reductions with HVO can be considerable (up to 90%) but is highly dependent on the feedstocks, feedstock cultivation and land use changes. Compared to FAME, in HVO production process, a wider range of raw materials can be utilized. The production also enables better product optimization. HVO is studied thoroughly and compared with standard diesel fuel and FAME in publications 1-4 and 6 of this thesis (Neste 2016, Kuronen et al. 2007, Reinhardt 2006, Rantanen et al. 2005, Arvidsson et al. 2011).

Synthetic diesel

Paraffinic fuels can also be produced via raw material gasification and Fischer-Tropsch processes. The synthesis gas feed can come from natural gas ("Gas to Liquids", GTL), coal ("Coal to Liquids", CTL) or from biological masses ("Biomass to Liquids", BTL). The raw syngas typically includes many contaminants, and therefore, has to be cleaned. After purification, the carbon monoxide (CO) and hydrogen (H) of the syngas react and are liquefied in the FT reaction, forming paraffinic hydrocarbon chains. The fuel parameters can be tuned by isomerization and cracking to match the requirements. High process temperatures yield short-chained hydrocarbons, and vice versa. However, despite its promising properties and increasing market demand, the production of FT diesel is still expensive and requires further development. To make BTL production more competitive, process energy efficiency should be increased and capital costs per energy unit lowered, e.g. via integration and the scaling-up of plants (Nylund et al. 2008, Johansson 2012, Bown 2007, Boerrigter et al. 2002, Vessia 2005, Srinivas et al. 2006, Lieberz 2004, Hepola et al. 2002).

Dimethyl ether

Dimethyl ether (DME, CH_3OCH_3) is chemically stable and colourless. It is structurally the simplest ether, qualities of which can be compared with propane or butane. DME is gaseous in low temperatures and pressures: its boiling temperature is $-25\text{ }^\circ\text{C}$ in atmospheric pressure. DME is liquefied when the pressure reaches 5,1 bar at $20\text{ }^\circ\text{C}$. DME is environmental as a fuel, as it disintegrates quickly in the atmosphere (Arcoumanis et al. 2008, Nylund et al. 2008).

DME production involves either formation of DME and water from methanol, or direct synthesis from syngas. With its high CN, DME is suitable for the diesel process. Compared to conventional diesel, the DME sprays mix better with the surrounding air. The combustion is more rapid and thermal efficiency higher. The emissions overall are much lower. However, based on the findings of publication 6 DME was not included in the experimental parts of this thesis: the properties of the fuel are problematic for typical diesel engines (Arcoumanis et al. 2008, Nylund et al. 2008, Azizi et al. 2014, Yu et al. 2002, Teng et al. 2002, Hansen et al. 1995).

2.5.3 Fuel comparison

In many ways, alternative diesel fuels are better than fossil diesel in quality; but in some, they do not meet the standards and regulations. When it comes to the potential of renewable diesel fuels, the second-generation biofuels (HVO and BTL) have great potential to improve energy security and are a good option for both local pollution and climate change mitigation, if production is based on waste and direct and indirect land-use changes are minimized. The effects of first-generation fuels (FAME) are typically smaller. Fossil-based synthetic fuels (GTL and CTL) may have an effect on energy security, but should not be promoted because of their very high life-cycle GHG emissions (Nylund et al. 2008, Arvidsson et al. 2011, Hao et al. 2010, Jaramillo et al. 2008).

Table 1 compares the different renewable diesels and their production. FAME has low capital costs, but also low quality and limited feedstocks, while BTL technologies have high costs, future potential due to large feedstocks and high product quality. HVO falls in between, as the feedstocks are quite similar to those of FAME, the production refinery-scope, and the end product the same as BTL. All these renewable diesel fuels reduce (especially CO₂-) emissions, when compared with conventional diesel fuels (Bown 2007).

Table 1. Renewable diesel fuel comparison collected in publication 6 of this thesis (Bown 2007).

	FAME	HVO	BTL
Process route	Transesterification	Hydrotreatment	Gasification, FT synthesis
Feed Product	Vegetable oils	Oils, fats	Biomass
Product (type)	Fatty acid methyl esters	Paraffinic hydrocarbons	Paraffinic hydrocarbons
Product quality	Consistency and stability issues	High	High
CO₂ emissions (LCA)	1.6–2.3 kg CO ₂ / kg oil equivalent	0.5–1.5 kg CO ₂ / kg oil equivalent	0.3–1.5 kg CO ₂ / kg oil equivalent

Note: Fossil diesel fuel value is reported as 3.8 kg CO₂ / kg oil equivalent.

Production and use of FAME typically causes about 40–60 % less CO₂ emissions than conventional diesel. For HVO, the GHG reduction has been estimated to be 60–85%. With BTL, even higher CO₂ life cycle reductions can be reached at its best. However, the life-cycle CO₂ emissions of biofuels vary with the raw materials, their production methods, land use, as well as direct and indirect land use changes. In the worst-case scenario, life-cycle emissions from biofuels can be many times the typical fossil fuel GHG emissions (Bown 2008, Neste 2016, Vessia 2006, Arvidsson et al. 2011).

2.6 Emission formation in diesel engines

The regulated emissions from diesel engines are nitrogen oxides (NO_x), particulate matter (PM), unburned hydrocarbons (HC) and carbon monoxide (CO). Typically in diffusion combustion, the NO_x and PM emissions are the

most problematic. In this thesis, the focus is especially on NO_x and their reduction (publications 3-4). PM emissions (as filter smoke numbers, FSN) were also measured, but the FSN significance and differences between runs were either small (publications 3-4) or negligible (publications 1-2). In some (pre-mixed) combustion strategies, emission reduction strategies with diminished oxygen content or temperature in the cylinder (such as Miller cycle and iEGR used in publications 3 and 4) and in the case of DPF regeneration events (publications 1 and 2), the HC and CO emissions tend to rise significantly (Majewski et al. 2006, Tilli et al. 2010).

In diesel combustion, mixture formation during the ID, peak temperature, the durations of different combustion temperatures, and expansion time have significant effects on emission formation. Additionally, pollutant formation depends on the fuel components and their chemistry, several serial chemical reactions and their rates, as well as heat transfer processes. The quality and quantity of emission pollutants vary during the different combustion phases. All of these emission formation parameters are affected by the fuels and technologies studied in publications 1-4 and 6 of this thesis (Majewski et al. 2006, Tilli et al. 2010).

2.6.1 Nitrogen oxides

In this thesis, one of the focal points is nitrogen oxides, commonly abbreviated NO_x, which include the seven different compounds of nitrogen and oxygen: nitric oxide (NO), nitrogen dioxide (NO₂), nitrate (NO₃), nitrous oxide (N₂O), dinitrogen trioxide (N₂O₃), dinitrogen tetroxide (N₂O₄) and dinitrogen pentoxide (N₂O₅). Because of concerns involving environment and health, NO_x emissions are regulated in most countries. Diesel engine NO_x consists almost exclusively of NO and NO₂, as the other compounds are not formed in diesel combustion. Typically, NO constitutes 70–90% of the total NO_x amount, while the remainder is NO₂ (Van Basshuysen et al. 2004, Warnatz et al. 1999).

In diesel engines, NO_x formation is most relevant when the local temperatures in the cylinder exceed 1800 K. While most of the NO_x formation usually occurs during diffusion combustion phase, also the premixed combustion phase plays a significant role. NO_x reduction technologies, such as the iEGR and Miller cycle applied in publications 3 and 4 of this thesis, tend to diminish combustion temperature or the availability of oxygen in the combustion chamber. One hypothesis of this thesis is that with diesel fuels with good ignitability, NO_x emissions can be further reduced without problems related to ignition and combustion quality (Aoyagi et al. 1980, Donahue et al. 1994, Arcoumanis et al. 2009, Kilpinen 2010).

In diesel engines, NO_x emissions are formed in processes named Thermal NO, Prompt NO, Fuel NO, and the N₂O mechanism. The processes have a varying impact on the NO_x emissions and are affected by cylinder conditions and fuel properties. In the context of this thesis, Thermal NO plays a major role. The other processes occur in lower temperatures, and are less significant (Heywood 1988, Wenzel 2006, Warnatz et al. 1999, Miller et al. 1998).

Thermal NO is the main source of engine-out NOx emissions in diesel engines (80–95%), requiring a high temperature to be initiated. Therefore, the peak temperatures in the cylinder are very indicative of the NOx formation in the engine. Thermal NO production is typically characterized with the extended Zeldovich mechanism, which includes the following reactions:

The rate constants (k_1 , k_2 , k_3) are very temperature-dependant. The high activation energy of the equation (2.1.) is the limiting factor of the mechanism. It is initiated only in combustion zones with very high temperatures (ca. 2000 K and above). Equations (2.2) and (2.3) require lower activation energy. In typical diesel conditions (lean mixtures and high temperatures), they are much slower in the reverse direction. Thus, the N atoms from reaction (2.1) are rapidly oxidized to NO, but not vice versa (Heywood 1988, Miller et al. 1998, Warnatz et al. 1999, Wenzel 2006).

As high cylinder temperatures promote NOx formation, the heat of evaporation and specific heat capacity of the fuel and the cylinder charge, as well as the charge air temperature and the ratio of compression in the cylinder affect the NOx emissions. Another factor in NOx formation is the aromatic HC concentration of the fuel, as aromatics have high adiabatic flame temperatures. In the publications 3 and 4 of this thesis, fuels of negligible aromatic content were used with EGR and Miller cycle changing the cylinder charge heat capacity and the CR in order to decrease NOx emissions (Johansson 2012, Warnatz et al. 1999, Warnatz 2006, Tilli et al. 2010).

2.6.2 Particulates

Particulates have been defined as substances that can be filtered at 325 K from the exhaust gases. PM emissions used to be a major problem of diesel engines. Nowadays, especially in-cylinder NOx-reduction techniques (e.g. iEGR used in publications 3 and 4) increase particulate formation. Generally, non-aromatic fuels with a simple chemical structure (like the paraffinic fuels studied in this thesis) and short carbon chains (e.g. dimethyl ether) decrease PM emissions. With modern engine technology and high-quality fuels, the lubricating oil also plays a role. Low density and high CN have been shown to correlate with low PM emissions (Johansson 2012, Fanick 2001, Larsson 2007, Azimov 2008, Dec 1997, Tilli et al. 2010).

The diesel exhaust particles typically originate from the fuel impurities or are formed by incomplete combustion of hydrocarbons. Soot, composed of solid matter containing carbon, is formed from heavy hydrocarbons by polycyclic aromatic hydrocarbon (PAH) growth. PAHs exist as a fuel component in regular diesel fuel. PAH is also formed in pyrolysis reactions from other species in the high equivalence ratio parts of the fuel spray. In-cylinder soot peak values

(especially the particulate numbers) are much higher than the engine-out PM emissions. 90% of soot is oxidized in the cylinder. Moreover, the particulates grow by surface growth, coagulation and absorption mechanisms, making the PM filtering easier. Since PM emissions cause health problems and may be carcinogenic, social and environmental pressures have led to regulations with PM emission limits very close to zero. In this thesis, particulates emissions are not the main focus, but the PM emissions are observed and kept under acceptable limits by measuring and comparing the filter smoke numbers (FSN) of different engine runs in the experimental tests of this thesis. The alternative fuels studied have no PAH content, which leads to lower PM emissions (Challen et al. 2009, van Basshuysen et al. 2004, Majewski et al. 2006, Warnatz et al. 1999).

Figure 4. Local Φ – T map for NO_x and soot formation zones (Akihamo et al. 2001).

4.1.1 Connection between NO_x and PM emissions

Figure 4 represents the soot and NO_x formation areas in a local fuel-air equivalence ratio (Φ) and local combustion temperature (T) map. From this so-called “phi-T map”, one can see that soot is formed especially in rich zones ($\Phi > 2$) with moderate temperatures between 1500K and 2400K. The aim of low temperature combustion (LTC) technologies is to keep the local cylinder conditions out of the high NO_x and soot production areas seen in Figure 4. The same applies to a smaller extent to the Miller cycle and iEGR technologies studied in publications 3 and 4. NO_x formation occurs in high temperatures. Thus, to reduce both emissions, local in-cylinder temperatures should be kept low enough to avoid NO_x emissions and high enough to promote thorough combustion, while simultaneously keeping the local equivalence ratios low enough to avoid particulate emissions. To achieve these conditions, effective mixing is required. Strategies to reduce soot inside the cylinder often aim to increase the mixing rate, for example via better fuel injection profile and spray

quality by developing the fuel injection parameters. Other possibilities are optimizing the shape of the combustion chamber, or (as is the case in the tests reported in publications 1-4 of this thesis) using alternative fuels that produce less soot as such (Challen et al. 2009, Tilli et al. 2010, Warnatz et al. 1999, Akihama et al. 2001).

2.6.3 Hydrocarbons

In diesel engines, hydrocarbon (HC) emissions mainly consist of gaseous fuel that is left completely or partially unburnt. HC emissions usually result from problems in mixing, resulting in high local equivalence ratios. The overall equivalence ratio has less effect on HC emissions than mixing. In diesel engines working with high injection pressures and excess amounts of oxygen in the cylinders, HC emissions are usually low. However, very high HC emissions may occur during DPF regeneration with late post injections (studied in publications 1 and 2) if the exhaust gas temperature is low (Majewski et al. 2006, Warnatz et al. 1999, Challen et al. 2009).

Under-mixing is a major cause of HC emissions, especially at the end of injection. After the injector needle settles on the needle seat, the pressure drops and the final fuel remnant leaves the injector nozzle sac. A consequence of the low pressure is poor atomization. The very slow and large droplets mix poorly and burn only partially, because evaporation is slow and the equivalence ratios locally very high. However, over-lean conditions are also an important source of HC emissions. During the premixed combustion phase, the injected fuel mixes with an excessive amount of air, which prevents ignition. Increasing ignition delay lengthens the premixed burning phase and may thus increase HC emissions. Hydrocarbon emissions can also become important when emission reduction techniques like internal EGR or Miller timing (studied in publications 3 and 4) are used in high levels, decreasing the temperatures and increasing local equivalence ratios, which may lead to incomplete combustion and flame quenching. Additional sources for HC emissions are flame extinction near cylinder walls or in piston crevices, and fuel exiting through the exhaust valves during the scavenging phase (Warnatz et al. 1999, Tilli et al. 2010, Johansson 2012, Heywood 1988, Challen et al. 2009).

2.6.4 Carbon Monoxide

In combustion process, carbon monoxide (CO) is an intermediate species, which is usually oxidized into carbon dioxide (CO₂). CO is an odourless, colourless and very toxic gas that is flammable in high concentrations. It burns with a bright blue flame (Majewski et al. 2006).

CO emissions are a consequence of incomplete combustion in locally fuel-rich zones of the cylinder with less oxygen than is needed for complete oxidation. In these conditions, CO can only react with OH to produce CO₂. However, the OH concentration reduces rapidly with a temperature decrease, resulting in a poor CO oxidation rate during expansion. In modern diesel engines, CO emissions are usually quite low (10–500 ppm). With the typically lean mix-

tures of diesel engines, CO engine-out emissions are usually below emission regulation limits and do not represent a great concern (Warnatz et al. 1999, Challen et al. 2009).

CO emissions can become a problem with high equivalence ratio combustion techniques (like iEGR used in publications 3 and 4), as oxygen content may be locally insufficient for complete combustion. In this case, CO emissions can be prevented with an increase of in-cylinder temperatures, an extension of oxidation time, or the use of oxygen-containing fuels, such as FAME. High CO emissions may also occur during DPF regeneration with late post injections studied in publications 1-2 of this thesis, if the exhaust gas temperature is low (Schaberg 2005, Fanick 2001, Crepeau et al. 2009, Kitano et al. 2005, Tilli et al. 2010).

2.7 Emission Legislation

Emission regulation evolution has been a driving force behind the development of modern emission reduction technologies. In Europe, the EURO 1 standards for on-road vehicles were introduced in 1992. Since then, the regulations have become more stringent with every update. The current emission standard for on-road vehicles is EURO 6. Off-road vehicle emissions (relevant to the engines studied in publications 1 and 2) are regulated by separate standards, depending on the nominal power of the engine. In Europe, Stage 5 comes into force in the beginning of 2019 or 2020. The emission limits for two engine power ranges in Stage 3B, Stage 4, and Stage 5 can be seen in Table 2 (Prasad et al. 2010, EU 2007, EU 2011, EU 2004, EU 2016).

Table 2. Off-road vehicle emission regulations: Stage 3B, 4 and 5 (EU 2004, EU 2016).

Standard	Effective Date	Power range kW	CO	HC	NOx	PM
				g/kWh		
Stage 3B	Jan. 2011	130 < P < 560	3.5	0.19	2.0	0.025
	Jan. 2012	75 < P < 130	5.0	0.19	3.3	0.025
Stage 4	Jan. 2014	130 < P < 560	3.5	0.19	0.4	0.025
	Oct. 2014	75 < P < 130	5.0	0.19	0.4	0.025
Stage 5	Jan 2019	130 < P < 560	3.5	0.19	0.4	0.015
	Jan 2020	56 < P < 130	5.0	0.19	0.4	0.015

International Marine Organization (IMO) Annex VI of MARPOL 73/78 for the regulation of air pollution from ships is the legislation for maritime emissions relevant to the engine studied in publications 3-6. Tier III came into effect in 2016, and has 80% lower NOx limits than Tier I in the emission control areas (ECAs): the Baltic Sea, the North Sea and most of the North American coastal waters. The stages of emission limits apply to engines with over 130 kW maximum full-load power. The NO_x limits are calculated with weighted factors of a test cycle as functions of rated load and speed (International Standard 1996, Meier-Peter et al. 2009).

2.8 Aftertreatment technologies

A typical full-scale diesel engine aftertreatment system consists of three parts: the diesel oxidation catalyst (DOC) to remove HC and CO emissions, a diesel particulate filter (DPF) to remove soot and other particulates, and a selective catalytic reduction (SCR) system to remove NO_x emissions (see Figure 5). In this thesis, aftertreatment efficiency as such is not analysed. However, in publications 1 and 2, the focus is on late post-injections with different fuels, typically injected to be oxidized in the DOC to produce the heat, which burns off the soot (regeneration) of the DPF (Majewski et al. 2006, Reşitoğlu et al. 2015).

Figure 5. Diesel engine aftertreatment systems (Proventia).

2.8.1 Diesel Oxidation Catalyst (DOC)

Since their introduction in the 1970s, DOCs have been an important emission reduction method for diesel engines. The primary purpose of a DOC is to oxidize HC and CO. Additionally, DOCs decrease diesel PM emissions by both filtering and oxidizing HCs in the particulates. Additionally, DOCs increase the NO₂:NO ratio by oxidizing NO into NO₂. As was the case in LPI studies of this thesis (Publications 1 and 2), this NO oxidation can be inhibited by high proportions of HC or CO (whose oxidation takes precedence) entering the DOC, e.g. in the case of late post-injections. Diesel exhaust gases generally contain O₂, which is steadily consumed by the DOC (Katare et al. 2007, Irani et al. 2009, Reşitoğlu et al. 2015, Zheng et al. 2009, Wang et al. 2008, Yu and Kim 2013).

The main reactions in DOCs are:

NO₂ concentration in the NO_x is essential because a high NO₂:NO rate increases the efficiency of some aftertreatment technologies. Before DOC, the exhaust gas NO₂ portion of the NO_x is usually about 10%. In the DOC, the

$\text{NO}_2:\text{NO}$ rate typically increases rapidly towards the thermodynamic equilibrium (unless, as stated previously, HC or CO oxidation takes precedence). Full-scale oxidation of CO and HC occurs above the catalyst 'light-off' temperature. DOC efficiency varies, and depends on the exhaust gas composition and temperature, exhaust gas flow, and the catalysts used. The oxidation reactions generate heat, which can be used to regenerate the DPF downstream of the DOC. In this thesis, the effects of FAME and HVO fuel blends on the phenomena in DOC during DPF regeneration were studied in publications 1-2 (Reşitoğlu et al. 2015, Lee et al. 2008, Sampara et al. 2007).

In a DOC, a ceramic or metal honeycomb structure has surface washcoat, typically composed of metal oxides and platinum (Pt) or palladium (Pd) as catalysts. The washcoat gives high surface area and prevents catalyst sintering in high temperatures. Pt and Pd also catalyse the SO_2 oxidation to SO_3 , which reacts with water, forming sulphuric acid, which is an environmental hazard and may damage the aftertreatment system. Modern fuels used in road and off-road vehicles contain practically no sulphur. In marine applications, alternative fuels reduce or eliminate this acid formation and increase the conversion efficiency of DOC (Reşitoğlu et al. 2015, Zhu et al. 2013, Wiebenga et al. 2012, Haneda et al. 2011, Kolli et al. 2010, Wang et al. 2008, Kim et al. 2003).

2.8.2 Diesel Particulate Filter (DPF)

DPFs are used to filter particulates out of the exhaust gas. They are usually made of a silicon-containing honeycomb structure with every second channel blocked. Thus, the exhaust gas flows through the porous walls, and physical filtration occurs. DPF functioning as such is not studied in this thesis. However, the increase of PM in the filter increases also the backpressure, which has negative effects, e.g. increased fuel consumption. Removal of the PM from the DPF is called regeneration. One type of regeneration initiation method is the focus of the publications 1 and 2 of this thesis (Kuki et al. 2004, Reşitoğlu et al. 2015, Ohno et al. 2002, Tsuneyoshi et al. 2012).

DPF regeneration processes may be active or passive. In passive DPF regeneration, the soot is oxidized at the exhaust gas temperature, increased by catalytic reactions within the DPF. In a continuously regenerating trap (CRT), NO_2 oxidizes soot even at low DPF temperatures. In catalysed DPFs (CDPF), the DOC and the DPF are integrated (York et al. 2007, Allansson et al. 2002, Reşitoğlu et al. 2015, Lamharess et al. 2011).

As active regeneration is initiated, the soot of the DPF is oxidized with $T > 550\text{ }^\circ\text{C}$. The heat can be generated with e.g. an electric heater, a flame-based burner, or via HC oxidation in the DOC. The regeneration event is initiated when the filter soot load becomes too high, which can be identified via a pressure drop across the DPF. The DPF regeneration method studied in this thesis (publications 1-2) is the late post-injection (LPI), in which the post-injection timing is retarded. The late post-injected fuel should evaporate (but not ignite) in the cylinder and end up in the DOC. The fuel oxidizes in the DOC, and the temperature rises. Thus, in the DPF, situated after the DOC in the exhaust system, soot burns off. Because of low in-cylinder temperatures and pressures

during the LPI, the LPI fuel is prone to contact the cylinder walls and cause oil dilution (Lapuerta et al. 2012, Wattrus 2013, Jeguirim et al. 2005, Reşitoğlu et al. 2015).

2.8.3 Selective Catalytic Reduction (SCR)

SCR is a NO_x emission reduction technology used especially in heavy-duty vehicles, but also in modern passenger cars with diesel engines. In SCR, exhaust gas NO_x emissions are reduced with ammonia (NH₃) or hydrocarbons. The NH₃ is provided as a solution of 33% urea (NH₂)₂CO and 67% pure water. NH₃ reacts in the SCR, typically catalysed by zeolite and vanadium. The end-products of the process are water and N₂. To reach high NO_x conversion efficiencies, the NH₃ content in the SCR should be maximized. Compared to other NO_x reduction methods, regular SCR usually has the highest efficiency (over 90%). However, the need of additional liquid (urea solution) is a drawback, and ammonia slip (ammonia escaping the SCR) may become a problem; it is minimized by accurate injection of the urea solution (Majewski et al. 2006, Reşitoğlu et al. 2015, Biswas et al. 2009, Moreno-Tost et al. 2008; Hamada et al. 2012).

SCR is not in the focus of this thesis. However, a SCR system functions in temperatures between 200 and 600 °C, while the conversion efficiency peak is typically reached at 350 °C. The DPF regeneration events by LPI (studied in publications 1 and 2 of this thesis) increase the exhaust temperatures close to the upper limit, where NH₃ oxidation occurs before NO_x conversion. Additionally, NO and NO₂ are reduced in different reactions with different reaction rates, and the maximum SCR efficiency is usually reached with 1:1 NO:NO₂ ratio. Therefore, the parameters of the DOC are directly related to the efficiency of the SCR, placed downstream of the DOC in the aftertreatment system. DPF regeneration, especially initiated via LPI events may thus disrupt the functioning of the SCR due to temperature and NO:NO₂ ratio changes (Majewski et al. 2006, Reşitoğlu et al. 2015, Biswas et al. 2009, Moreno-Tost et al. 2008; Hamada et al. 2012, Way et al. 2009, Schaberg et al. 2004, Koebel et al. 2000, Chi et al. 2005, Sluder et al. 2005, Shost et al. 2008).

2.9 In-cylinder emission reduction technologies

2.9.1 Miller cycle

The Miller cycle is an over-expanded thermodynamic cycle with the goal of utilizing the pressure of the expanding gases beyond the conventional cycles and reducing the pumping losses, the compression work and the compression temperature. It is implemented by either retarding or advancing the intake valve closure (IVC). Advancing the closing timing is more common. The main advantages of early IVC compared to late IVC are reduced pumping and friction losses. In publications 3 and 4 of this thesis, Miller cycle is realized with early IVC (Sellnau et al. 2003).

lications 3 and 4 of this thesis with extreme Miller timing combined with iEGR (Musculus 2004, Kyratos 2013).

During combustion, extreme Miller rate may also cause significant in-cylinder pressure pulsations ('diesel-knock'), seen as a pressure oscillation on the typical cylinder pressure curve (see Figure 7). Because of the compression heating, the reactants enter the diffusion flame at a higher temperature, which increases the soot oxidation, resulting in shorter combustion duration. The described phenomena are more evident at a low engine load, since the proportion of premixed combustion is more relevant and the turbocharger efficiency is low, implying difficulties in achieving the target load. Advancing IVC increases the peak of premixed combustion and the pressure oscillations. As a result, NO_x reduction is not effective, a phenomenon seen in publication 3 (Kyratos et al. 2014).

Figure 7. Combustion profile at low load with an increasing Miller rate. Mil15 means IVC 15 CAD before BDC, Mil50 50 CAD. Sc60 means 60 CAD scavenging period (Publication 3).

In order to exploit the benefits of the advanced IVC and to diminish the pre-mixed combustion peak, techniques shaping the combustion profile can be used. One approach to reduce the ID is using a small early pilot injection, which reduces the ignition delay and the peak of premixed combustion (Brückner et al. 2014, Imperato et al. 2016).

2.9.2 Exhaust gas recirculation (EGR)

Exhaust Gas Recirculation is a widely used NO_x emission reduction method. The exhaust gas components CO_2 , N_2 and water are inert and have high specific heat values. In EGR, exhaust gases are brought back into the cylinder, displacing part of the charge. Consequently, combustion occurs with decreased O_2 content. The resulting equivalence ratio increase slows the combustion and lowers cylinder temperatures. Also the heat capacity increase reduces the peak temperatures. Thus, in EGR, the combination of lower oxygen content and lower local peak temperatures lead to lower NO_x formation in reaction rates.

Effects on other emissions are also numerous: even in normal diesel combustion, fuel-rich areas in the cylinder are typical, especially in the late stages of combustion and during high load operation. The increased equivalence ratios increase HC, CO and PM emissions and fuel consumption (Agarwal et al. 2011, Reşitoğlu et al. 2015, Zheng et al. 2004).

The mass percentage of the exhaust gases in the intake mixture is called the EGR ratio. Higher EGR ratios can be used with low loads. This is because of the lower exhaust gas temperatures, higher O₂ concentrations, and lower CO₂ concentrations. At high loads, the oxygen content of the exhaust gases is low, making the mixture more inert. Additionally, exhaust temperature increases. Thus, increased load increases the tendency of diesel engines with EGR to generate more smoke (Agarwal et al. 2011, Zheng et al. 2004).

2.9.3 Internal EGR

In this thesis, no traditional EGR, but internal exhaust gas recirculation (iEGR) is studied (with Miller Cycle) in publications 3 and 4. In iEGR, the exhaust gas fraction in the cylinder is increased by altering valve timing. With Miller cycle, the exhaust gas introduced into the cylinder may further reduce NO_x emissions, with a slight fuel economy penalty due to a slower combustion rate (Zannis et al. 2015, Millo et al. 2007).

In iEGR, the cylinder exhaust gas content is dependent on the valve timing, engine speed, and pressure differences over the valves. An important iEGR parameter is the residual gas fraction (RGF), the exhaust gas proportion of the total in-cylinder mass at SOC. Typically, RGF is adjusted with variable valve actuation (Fessler et al. 2004, Schwoerer et al. 2010, Kawasaki et al. 2009, Dalla Nora et al. 2015, Borgqvist et al. 2013, Gehrke et al. 2013).

Following iEGR valve timing strategies have been used to allow the exhaust gases from the exhaust manifold back into the cylinder:

Early exhaust valve closing (EEVC). The scavenging process is reduced, which increases the RGF and the in-cylinder temperatures. This strategy has been used to apply iEGR in publications 3 and 4 of this doctoral thesis (Gehrke et al. 2008, Roberts et al. 2014).

Exhaust valve re-opening during the intake stroke can improve auto-ignition and help reach the DOC light-off temperature and higher efficiencies due to better combustion phasing. The drawbacks include decreases in intake air flow and mixing (Sellnau et al. 2012; Benajes et al. 1996).

Intake valve re-opening during the exhaust stroke. The exhaust gases are pushed back into the intake manifold and flow back into the cylinder during the intake stroke. The result is an increased, colder RGF than with the re-opening of the exhaust valve, further reducing NO_x emissions while lowering CO and HC emissions (Zhang et al. 2015; Edwards et al. 1998).

Negative valve overlap (NVO) is the interval (at TDC) from an early exhaust valve closing (EEVC) to a late intake valve opening (LIVO). Compared to exhaust valve re-opening, the result is usually reduced gas exchange efficiency and a lower engine efficiency resulting from recompression heat transfer losses (Borgqvist et al. 2013).

3. Effects of Alternative Diesel Fuel Properties

The property differences of diesel fuels have numerous effects on diesel engine operation. In many cases, the alternative fuel properties give benefits as such. However, the hypothesis of this thesis is that the properties of the alternative fuels can be further utilized, especially to decrease emissions via optimizing the parameters of the engine and the emission reduction technologies. In this chapter, the properties of fuels studied in this thesis, and their effects in the engine, are considered. The fuel properties affect every stage of the fuel cycle in the engine from the storage in the tank and functioning of the fuel injection system, to fuel spray quality, mixing process, ignition, combustion, emission formation and emission reduction technologies.

In the research of this doctoral thesis, the focus is on liquid diesel biofuels with high CN. The differences in the physical properties of fossil diesel, paraffinic diesels and FAME are relatively small. This can be seen in Table 3, where the typical characteristics of the fuels are collected.

Table 3. Properties of diesel fuels. DME values are in pressures above DME vapour pressures (EU 2013, Neste 2016, Aatola et al. 2009, Rantanen et al. 2005, Boehmann et al. 2004, Nylund et al. 2008, Arcoumanis et al. 2008, Wu et al. 2003).

Fuel	HVO	GTL	FAME	Std diesel	DME	EN 590
Density@+15 °C (kg/m ³)	770–790	770–785	~880	835	667	820–845
Viscosity@+40 °C (mm ² /s)	2.0–4.0	3.2–4.5	4.5	3.1	0.21	2.0–4.5
Cetane number	70–99	73–81	51	53	>55	>51
10% distillation (°C)	260–270	260	340	200		
90% distillation (°C)	282–338	325–330	355	350		
Cloud point (°C)	–5...–34	0 ... +3	0 ... –5	–5		
Heating value (MJ/kg)	44.0	43.0	37.5	43.6	27.6	42–44
Heating value (MJ/l)	34.3	33.5	33	36.4		
Polyaromatics (wt-%)	<0.1	0	0	4	0	<8
Oxygen content (wt-%)	0	0	11	0	34.8	
Sulphur content (mg/kg)	<5	<10	<10	<10	<10	<50

The significant deviations from EN 590 are low (HVO, BTL) and high (FAME) densities, which affect the fuel spray and the energy flow through of the nozzle during injection. Density, viscosity, surface tension, and distillation temperatures are higher for FAME, and low for paraffinic fuels, while heating values are lower, especially for FAME. However, many other differences also exist,

from the apparent (e.g. chemical composition) to the inconspicuous (e.g. differences in compressibility). In the case of dimethyl ether, the fuel is gaseous in normal conditions, and the values of Table 3 have been obtained in saturated conditions. DME cetane number is high and thus, it is suitable for the diesel process, but due to the many differences with the other fuels and the resulting problems (discussed in publication 6), DME was left out of the experimental program (Semião et al. 1996, Hiroyasu et al. 1990, Ejim et al. 2007, Wattrus 2013, Kitano et al. 2005, Tilli et al. 2010, Arcoumanis et al. 2008).

3.1 Fuel property effects on fuel injection and fuel systems

The focus of publication 6 was on alternative fuel characteristics and their effects in the engine, especially the fuel injection system. The publication, comprising of a literature and simulation studies, provided a basis for the fuel choices of the later studies of this thesis.

The chemistry of the fuels is relevant to the fuel system. FAME is slightly acidic, and the fatty acids of FAME may deteriorate rubber parts of the fuel system that endure acids badly, causing leakages. Additionally, FAME is water-absorbing, and may cause corrosion in the fuel injection system and carbon build-up on the injector and the valves. This is not the case with paraffinic fuels, which are not reactive towards the materials used in a typical engine (Nylund et al. 2008, Aatola et al. 2009, Arcoumanis et al. 2008, Lehto et al. 2012, Johansson 2012, Yamane et al. 2001, Van Gerpen et al. 2004, Knothe 2004, Fanick 2001, Larsson 2007, Azimov 2008, Mikkonen et al. 2007). Additionally, FAME can cause problems in the storage, fuel tanks and injection systems because of the FAME biodegradability and tendency to gather up water. With paraffinic fuels these problems are not any worse than with regular diesel (Yamane et al. 2001, Van Gerpen et al. 2004, Knothe 2004, Nylund et al. 2008).

The cold operation characteristics of the fuel alternatives vary a lot. With FAME, the cold properties are inferior to standard diesel fuel, mainly depend on the production raw materials and are not easily corrected by additives or production process changes. Therefore, blends with high FAME content have been problematic in arctic conditions. With paraffinic fuels, the cold operation properties vary according to the fuel chemistry: in the case of long normal (straight-chain) paraffin containing fuels, the fuel becomes wax in relatively high temperatures (close to 0 degrees Celsius). However, isomerization of the paraffins and shortening the CH chains via production process changes yields a fuel with very good cold properties. A drawback is that the cetane number, density, viscosity and distillation temperatures of the fuel become lower in the process (Yamane et al. 2001, Van Gerpen et al. 2004, Knothe 2004, Nylund et al. 2008).

The different densities of the fuels lead to differences in fuel injection phenomena. The volume of the fuel injected per cycle is the controlled factor in a diesel engine. The density differences lead to differences in the injection dose (mass) and thus, engine power. The higher density of FAME leads to a higher

mass flow and the lower one of paraffinic fuels and DME leads to a lower mass flow during the injection, which is also seen in the simulation results of publication 6. For the same power, more fuel per cycle is needed, if the mass-based heating value is the same. However, the mass-based heating values are lower for diesel alternatives. When taking into account the differences in both, the densities and the heating values (seen in Table 3), in order to achieve the same energy flow, 10%, 8,5% and 6% more (in volume) of FAME, GTL and HVO have to be injected, respectively. Because of the lower heating value of DME, 1.8 times the volume of regular diesel is needed for the same power. This typically means that longer injection durations are needed (Tilli et al. 2010, Lepperhoff et al. 2006, Crepeau et al. 2009).

Generally, alternative diesel fuel viscosity differences are within the EN 590 limits. However, typically FAME viscosity is higher and paraffinic fuel viscosities lower when compared to fossil diesel. The very low viscosity of DME may cause leaks in the fuel injection system. Using additives to increase the viscosity is a possibility. However, with the required additive amounts for DME, other properties of the fuel will deteriorate (Raiko et al. 2002, Guibet 1999, Mikkonen et al. 2007, Semião et al. 1996, Kitano et al. 2005, Tilli et al. 2010, Arcoumanis et al. 2008, Azizi et al. 2014, Yu et al. 2002, Teng et al. 2002, Hansen et al. 1995).

High viscosities increase the injection pressure and therefore the mechanical stress in the injector. The volumetric flow through the injector nozzle increases as viscosity and density are decreased, which results in a higher injection velocity with paraffinic fuels and DME. The opposite applies to FAME. However, paraffinic fuel nozzle flows have been measured to resemble those of standard diesel. The high flow rates partially compensate for the lower volumetric energy density of paraffinic fuels (Lepperhoff et al. 2006, Crepeau et al. 2009, Murugesan et al. 2009, Tilli et al. 2010).

The fuel lubricity is linked to the fuel viscosity. If the viscosity is too low (2 mm²/s or below at +40 °C), the lubricity of the fuel may be too low for the fuel injection system. DME and paraffinic fuels have very low lubricity as such (due to their lack of polar molecules), which is a potential cause for wear in the injector. However, paraffinic fuels respond well to lubricating additives and even the very low lubricity of DME can be fixed with them. In contrast, FAME lubricity is high and it acts as a lubricity improver, even when the FAME content is very small (Aatola et al. 2009, Arcoumanis et al. 2008, Tilli et al. 2010, Johansson 2012, Yamane et al. 2001, Van Gerpen et al. 2004, Knothe 2004, Farnick 2001, Larsson 2007, Azimov 2008, Mikkonen et al. 2007).

Compressibility (bulk modulus) and vapour pressure have significant effects on fuel injection phenomena. Of the fuels studied in this thesis, paraffinic fuels and especially DME have high compressibility, while the regular biodiesel compressibility is lower than with regular diesel. With low compressibility, as with FAME, the rate in the rise of liquid pressure is faster and more pronounced inside the injector nozzle, leading to a higher maximum pressure. According to Publication 6 results, with FAME, the pressure pulsations inside the fuel injection system have a higher frequency and amplitude, but they die

out faster. Thus, the high bulk modulus of FAME also leads to higher stresses in the fuel injection system. The actual start of the injection (fuel leaving the nozzle, as opposed to the SOI defined by the electric signal from the ECU) occurs earlier. With higher injection pressures of common rail system, this effect has been reported to disappear. However, in Publication 6, the effect is visible (see figure 8) in the common rail fuel injection system simulations with FAME, especially when compared to DME. However, the differences seen in the injection start are in the order of 0,1-0,2 degrees CAD, which cause no relevant differences in the engine (Yamane et al. 2001, Boehmann 2004, Tilli et al. 2010, Van Gerpen et al. 2004, Knothe 2004, Nylund et al. 2008, Murugesan et al. 2009).

Figure 8. Simulated fuel injection mass flow curves. Influence of compressibility on the actual start of the injection can be seen in the augmented part of the figure; the least compressible fuel, FAME, leaves the injector nozzle first (Publication 6).

High vapour pressure promotes cavitation, defined as “the formation of bubbles in a liquid flow leading to a two-phase mixture of liquid and vapour/gas when the local pressure drops below the vapour pressure of the fluid” (Som et al. 2010). In diesel engine injectors, pressure differentials and shear stresses can reach levels that lead to cavitation, causing e.g. reduction of the injection mass flow. One of the reasons DME was left out of the experimental parts of this thesis were the cavitation caused by the very high compressibility and vapour pressures (reported in the simulations of Publication 6) in the engine. Additionally, DME compressibility changes rapidly with temperature. This may cause difficulties in the fuel pumps: the fuel amount pumped decreases as the temperature rises. This is problematic, since DME requires both a pressurized tank system and a high-pressure fuel injection (Som et al. 2010, Boehmann et al. 2004, Arcoumanis et al. 2008, Nylund et al. 2008, Azizi et al. 2014, Yu et al. 2002, Teng et al. 2002, Hansen et al. 1995).

3.2 Fuel property effects on fuel sprays and mixing

The physical properties of the diesel fuel have been found to have numerous effects on the diesel fuel spray qualities and mixing. The fuel chemical composition is directly linked to the physical properties and thus, fuel spray quality, in ways depicted in this chapter. E.g. increased carbon chain length of the fuel hydrocarbons (or, the esters, in the case of FAME) decreases density, increases viscosity and leads to higher distillation temperatures, and aromatic content increases the density and distillation temperatures. Otherwise, chemistry does not typically affect fuel sprays. However, with increased O content (like with DME or FAME), to reach thorough combustion, the amount of air and thorough mixing needed in the cylinder is decreased (Jeihuni et al. 2011, Yamane et al. 2001, Boehmann 2004, Tilli et al. 2010).

High density (e.g. that of FAME) has been found to increase fuel spray tip penetration and to decrease the spray cone angle (and thus, spray area). This leads to less effective mixing process. The effect is opposite with lower density fuels (e.g. paraffinic fuels, DME): spray tip penetration decrease and cone angle increase promote good mixing. Engine type and construction of the injection system define how much effect the differences in fuel density have (Raiko et al. 2002, Guibet 1999, Mikkonen et al. 2007, Johansson 2012, Tilli et al. 2010, Wattrus 2013, Semião et al. 1996, Hiroyasu et al. 1990, Agarwal et al. 2012, Lepperhoff et al. 2006, Crepeau et al. 2009)

Fuel viscosity effects on diesel fuel sprays are numerous. Figure 9 shows the viscosity effect on spray angle and Sauter mean diameter (SMD, average droplet size in fuel spray). Also fuel spray penetration increases with viscosity (Raiko et al. 2002, Guibet 1999, Semião et al. 1996, Wattrus 2013, Kitano et al. 2005, Tilli et al. 2010, Lepperhoff et al. 2006, Crepeau et al. 2009).

Figure 9. Fuel influence on SMD and spray angle (Kitano et al. 2005).

Thus, the spray angle is wider, the spray penetration shorter, and SMD smaller with lower viscosity. Therefore, division of droplets and the mixing process is promoted by low viscosity fuels such as GTL, HVO or DME (Yamane et al. 2001, Boehmann 2004, Nylund et al. 2008, Aatola et al. 2009, Lehto et al. 2012, Tilli et al. 2010).

Alternative diesel fuel distillation characteristics differ from regular diesel. The fuel distillation characteristics significantly affect the mixture formation after fuel injection. The low volatility, high boiling points and distillation temperatures typical of FAME lead to increased liquid fuel spray penetration and SMD, and reduce fuel spray angle and area, which leads to less effective mixing process. Vice versa, the high volatility, low distillation temperatures and final boiling points of paraffinic fuels tend to accelerate the mixing process due to rapid evaporation, and to promote spreading of the rich mixture in the combustion chamber. The liquid spray penetration of late post-injections with FAME and HVO blends has been studied experimentally in Publication 2 of this thesis. Contrary to previous studies, in these measurements (Figure 10), no significant differences between the fuels were found. The possible reasons are discussed later in this thesis (Raiko et al. 2002, Guibet 1999, Mikkonen et al. 2007, Tilli et al. 2010, Kitano et al. 2005, Kono 2005).

Figure 10. Spray tip penetrations, LPI timing 80 CAD ATDC (Publication 2).

The cavitation and bubble formation caused by e.g. high vapour pressure and compressibility, typical of DME and paraffinic fuels, can be either beneficial or degrading to the fuel spray quality, while, the high surface tension of FAME has been shown to increase SMD, and reduce fuel spray angle and area. With the lower surface tensions of paraffinic fuels, the effect is opposite (Som et al. 2010, Boehmann et al. 2004, Sou et al. 2007, Reddeman et al. 2010, Yamane et al. 2001, Knothe 2004, Ejim et al. 2007).

Cetane number has no direct link to fuel spray qualities. However, the ignition delay decreases with higher CN, which leads to shorter premixing time. Thus, the balance between premixing and diffusion mixing is shifted towards diffusion (Kitano et al. 2005, Abu-Jrai et al. 2006, Lepperhoff et al. 2006, McMillian et al. 2001, Larsson et al. 2007, Tilli et al. 2010, Azimov et al. 2007, Nishiumi et al. 2009).

3.3 Fuel property effects on ignition and combustion

The basis of the ignition and combustion of the fuel is the chemical composition. In addition to the fuel spray and mixing already discussed, the composition affects the ignition and combustion characteristics of the fuel. For example, the cetane number and heating value are higher for long HC chain fuels. Of typical fuel species, olefins and aromatics increase the fuel (gravimetric) heating value. Their adiabatic flame temperature is typically high, which promotes high local temperatures in the cylinder. Compared to paraffins, they tend not to burn as thoroughly in conditions of high equivalence ratio and low temperature. Paraffinic fuels contain no aromatics or olefins, and their combustion is stable and clean compared to the standard fuels. Moreover, the adiabatic flame temperatures of paraffins are lower. Biodiesel contains a small amount (~10%) of oxygen, which is absent in traditional diesel fuels, while the oxygen content of DME is very high. Oxygen content leads to diminished need of air in the cylinder and makes combustion in rich parts of the cylinder more thorough. Partially because of this, DME combustion is quicker and thermal efficiency better than with diesel. However, also the heating value of oxygen-containing fuels is lower (Arcoumanis et al. 2008, Nylund et al. 2008, Azizi et al. 2014, Yu et al. 2002, Teng et al. 2002, Hansen et al. 1995, Yamane et al. 2001, Boehmann 2004, Aatola et al. 2009, Lehto et al. 2012, Tilli et al. 2010).

The alternative diesel fuel heating values have differences from regular diesel. They depend on fuel chemistry, e.g. content of aromatics and oxygen, and the fuel C-H ratio. High volumetric heating value may lead to higher local peak temperatures in the cylinder. The fuels with low energy content (such as DME or FAME) require a longer injection duration, which leads to a longer and later-occurring late combustion phase in combustion-debilitating cylinder conditions (Raiko et al. 2002, Guibet 1999, Mikkonen et al. 2007, Tilli et al. 2010)

Cetane number is a very important property affecting the ignition and combustion process in the engine. In fact, much of this thesis is focused on high cetane number effects. Typically, FAME CN is quite similar to fossil diesel, while DME CN is significantly higher. Paraffinic fuels have very high cetane numbers. This affects all the phases of combustion. The effects on premixed combustion, discussed in publications 3-4, are the most significant. Low CN delays the ignition and thus, leads to an increased fuel mass in the cylinder at the time of the ignition. In the resulting strong premixed combustion phase, simultaneous ignition and combustion of the thus far injected fuel causes a peak in heat release, temperature and pressure. Vice versa, the short ignition delay resulting from high CN decreases the fuel accumulation and mixing duration before the ignition. This shortens the premixed combustion phase. The results are a decreased peak heat release rate and thus, lower maximum temperatures and pressures in the cylinder, as the simultaneous ignition and fast combustion occur with a smaller amount of premixed fuel (Raiko et al. 2002, Guibet 1999, Mikkonen et al. 2007, Tilli et al. 2010, Kitano et al. 2005, Abujrai et al. 2006, Lepperhoff et al. 2006, McMillian et al. 2001, Larsson et al. 2007, Azimov et al. 2007, Nishiumi et al. 2009). This phenomenon has been studied in publications 3-4, and can be seen in Figure 11: with HVO, the pres-

sure fluctuations occur earlier and are diminished, due to the high CN and more stable combustion process. The heat release rate also shows a lower peak, a smoother behaviour and a diminished premixed combustion phase with HVO.

Figure 11. The effect of the fuel on heat release rate and cylinder pressure (Publication 4).

With high common rail injection pressures, the ignition delay differences and thus, the premixed combustion dependency on CN is smaller. Additionally, higher CN of paraffinic fuels give better ignition, as well as more thorough and stable combustion during the later combustion phases, while not affecting the peak cylinder temperatures. However, it is difficult to differentiate the effects of high CN from those of the stable combustion and lack of aromatics in the paraffinic fuels (Raiko et al. 2002, Guibet 1999, Mikkonen et al. 2007, Tilli et al. 2010, Kitano et al. 2005, Abu-Jrai et al. 2006, Lepperhoff et al. 2006, McMillian et al. 2001, Larsson et al. 2007, Azimov et al. 2007, Nishiumi et al. 2009).

High amounts of long straight-chain paraffins give the highest CN to the fuels. However, isomerization and shorter chain lengths are required to keep cold properties acceptable. Therefore, the cetane numbers of winter-grade paraffinic fuels are lower (but still high, close to 75) than summer-grade (close to 90) (Raiko et al. 2002, Guibet 1999, Mikkonen et al. 2007, Tilli et al. 2010).

The high volatility and vapour pressure, as well as the low viscosity and density of paraffinic fuels improve fuel spray characteristics and mixing. Together with the stable and thorough combustion of the paraffins and higher CN, this leads to a higher thermal efficiency (Lepperhoff et al. 2006, Crepeau et al. 2009, Tilli et al. 2010).

3.4 Fuel property effects on emissions and emission control

In diesel combustion, mixture formation during the ID, peak temperature, as well as the durations of different combustion temperatures and the expansion have significant effects on emission formation. Additionally, pollutant formation depends on the fuel components and their chemistry, several serial chemical reactions and their rates, as well as heat transfer processes. The quality and quantity of emissions formed change during the different combustion phases. Emissions and their formation with the different fuels and cylinder conditions were investigated in publications 1, 3 and 4 of this thesis, while in publications 1, 5 and 6 the focus was on fuel injection and fuel sprays, which are directly linked to emission formation process (Majewski et al. 2006, Tilli et al. 2010).

Typically, regulated emissions decrease with paraffinic fuels. This includes also NO_x, in contrast to FAME, which decreases PM, HC and CO, but increases NO_x emissions on the average. In the Publications 1, 3 and 4 of this thesis, the emissions with alternative fuels or their mixtures with no other changes in operation were measured for reference. Compared with regular diesel, in publication 1, NO_x emissions were slightly higher with 30% blends of both HVO and FAME, and HC emissions with 30% FAME, while otherwise no significant differences were found. In publications 3 and 4, both NO_x and FSN were significantly lower with 100% HVO than with regular diesel. This is beneficial as such, but also slows the aging process of aftertreatment systems (Aatola et al. 2009, Happonen et al. 2012, Kim et al. 2014, Tilli et al. 2010, Hukkunen et al. 2011, Lapuerta et al. 2011, Wattrus 2013, Dumitrescu et al. 2015, Dornotte et al. 2012, Lešnik et al. 2013, Liaquat et al. 2013, Singh et al. 2015, Kegl 2011).

Aromatics in the fuel are directly linked to the soot emissions. Aromatic content increases the number of soot precursors in the cylinder and thus, aromatic hydrocarbons are a major source of PM emissions. Additionally the high adiabatic flame temperature of aromatics result in high local temperatures and therefore, increased NO_x emissions. Generally, non-aromatic fuels with a simple chemical structure (like the paraffinic fuels studied in publications 1-4 and 6 of this thesis) and short carbon chains (e.g. dimethyl ether simulated in publication 6) give low PM emissions. This was also seen in publications 3 and 4. On the other hand, oxygen content decreases PM, CO and HC emissions, since in high local equivalence ratio conditions, fuel O promotes thorough combustion. This is the case with FAME and DME. Due to the combination of oxygen content and lack of carbon-carbon bonds, no soot is formed in DME combustion (Johansson 2012, Fanick 2001, Larsson 2007, Azimov 2008, Dec 1997, Tilli et al. 2010).

High diesel fuel CN has been shown to correlate with decreased emissions. With low cetane number, ID is longer and with it, the fuel accumulation in the combustion chamber increased. Thus, the premixed combustion phase is more pronounced. A strong premixed combustion increases in-cylinder temperatures and the NO_x emissions, and reduces the particulate emissions. Also the advanced injection due to low compressibility typical of FAME leads to a longer ID and premixed combustion phase, increasing NO_x emissions. Vice versa,

high CN and slightly retarded injection due to high compressibility of paraffinic fuels shortens the ignition delay. The effect of compressibility was captured in publication 6 to a very small degree. The reduced premixed combustion leads to lower NO_x emissions and noise, as the maximum heat release rate and peak temperatures and pressures are lower. This effect was seen in publications 3 and 4. With short ID, the balance shifts towards higher PM emissions during the premixed combustion. However, the good ignitability usually has greater benefits during the later combustion phases, reducing PM and smoke emissions while not increasing the NO_x emissions. For common rail engines with high injection pressures, the CN and compressibility effects at the start of injection are smaller (Yamane et al. 2001, Boehmann 2004, Tilli et al. 2010, Van Gerpen et al. 2004, Knothe 2004, Nylund et al. 2008, Raiko et al. 2002, Guibet 1999, Mikkonen et al. 2007, Kitano et al. 2005, Abu-Jrai et al. 2006, Lepperhoff et al. 2006, McMillian et al. 2001, Larsson et al. 2007, Azimov et al. 2007, Nishiumi et al. 2009).

In addition to the high CN, the clean-burning paraffinic components (and the lack of other components such as aromatics) in the fuels studied in this thesis play a role in diminishing the emissions in the late combustion phase. The stable and thorough combustion (seen in figure 11 and discussed in publications 3 and 4), as well as the diminished ignition delay resulting from the high CN reduce over-leaning and have been proven to reduce unburnt emissions. With paraffinic fuels, HC and CO emissions have been shown to be reduced by up to 60–70 % from diesel fuel results (Schaberg 2000, Nishiumi et al. 2009), the reductions being higher with older engines with no common rail or electronic fuel injection control (Abu-Jrai et al. 2006, Raiko et al. 2002, Guibet 1999, Mikkonen et al. 2007, Tilli et al. 2010, Kitano et al. 2005, Lepperhoff et al. 2006, McMillian et al. 2001, Larsson et al. 2007, Azimov et al. 2007, Nishiumi et al. 2009).

As high cylinder temperatures promote NO_x formation, the fuel heat of evaporation and specific heat capacity of the cylinder charge affect the NO_x emissions. With emission reduction strategies that diminish the combustion temperature or the amount of oxygen in the cylinder, the PM, HC and CO emissions tend to rise significantly. With these technologies and diesel fuels with good ignitability, NO_x emissions can be further reduced without problems related to ignition, other emissions, or combustion quality. Compared to conventional fuels, the paraffinic fuel high ignitability and lower aromatic content permits the use of reduced in-cylinder gas temperatures or oxygen contents. The same applies to a lesser extent to FAME, which has the additional benefit of oxygen content in the fuel, which prevents incomplete combustion (Majewski et al. 2006, Johansson 2012, Warnatz et al. 1999, Aatola et al. 2009, Lehto et al. 2012, Happonen et al. 2012, Kim et al. 2014, Tilli et al. 2010, Warnatz 2006, Aoyagi et al. 1980, Donahue et al. 1994, Arcoumanis et al. 2009, Kilpinen 2010).

In the Publications 3 and 4 of this thesis, iEGR and Miller cycle were used to increase the cylinder charge heat capacity and the compression ratio in combination with fuels of negligible aromatic content to decrease NO_x emissions.

The results were promising, with 40-55% (depending on the engine load) NO_x emission reductions with no significant fuel consumption or soot emission penalties.

Lower density, viscosity, surface tension and distillation temperatures have been shown to correlate with decreased PM, HC and CO emissions. They lead to good fuel spray quality and mixing, which promote complete fuel combustion and prevent spray-wall interactions. Vice versa, the lower fuel spray quality of FAME has been concluded to increase emissions and fuel spray wall impact (Yamane et al. 2001, Knothe 2004, Lešnik et al. 2013, Liaquat et al. 2013, Singh et al. 2015, Ejim et al. 2007, Ganapathy et al. 2011, Challen et al. 2009, Raiko et al. 2002, Guibet 1999, Mikkonen et al. 2007, Kitano et al. 2005, Kono 2005, Warnatz et al. 1999, Akihama et al. 2001). Also in publications 1 and 2 of this thesis, FAME blend was found to increase both NO_x emissions and oil dilution.

Figure 12. The exhaust gas temperatures before and after the DOC and the temperature increase in the DOC during the “DPF regeneration mode” in the Agco production engine (Publication 1).

DPF regeneration-related late biofuel blend post-injections and their effects on emissions and phenomena in DOC were studied in Publications 1 and 2. The fuel properties affect the required LPI timings and quantities. First, lower PM emissions (typical of FAME and paraffinic fuels) decrease the optimum frequency of the regenerations. Additionally, with lower heating value (of e.g. FAME), the DOC reactions generate less heat, as can be seen in Figure 12. Thus, the post-injection fuel doses need to be higher to raise the temperatures to the required levels. In Publication 1, the temperature rise with B30 is even lower than expected from the heating values. This is concluded to be because of incomplete FAME oxidation in the DOC, also indicated by the higher HC and CO emissions. The result is a slightly decreased energy release (Lapuerta et al. 2011, Wattrus 2013).

The late post-injections to regenerate DPF's are initiated as early as possible after the late combustion phase has ended, so that the fuel will evaporate well, but not ignite. To prevent ignition, the LPI may have to be delayed, especially with high CN fuels. With the retarded timings, the in-cylinder temperatures and pressures are lower, and fuel spray quality decreases. On the other hand, paraffinic fuels have been found to start reacting at lower temperatures in the DOC. Paraffinic fuel spray quality has previously been found to benefit the regeneration process studied in publications 1 and 2 of this thesis (Wattrus 2013, Aatola et al. 2009, Happonen et al. 2012, Kim et al. 2014, Tilli et al. 2010, Hulkkonen et al. 2011, Lapuerta et al. 2011, Wattrus 2013, Dumitrescu et al. 2015, Dernotte et al. 2012).

In contrast, the physical properties typical of FAME deteriorate the LPI fuel spray characteristics. Thus, the fuel contact with the cylinder wall and entry into the oil has been concluded to increase. Mainly high boiling point, long carbon-chain components enter the engine oil. The low volatility and high distillation temperatures (typical of FAME and atypical of paraffinic fuels) of the fuel diluting the oil have been found to slow the exit rate (vaporization process) of the fuel from the oil. Therefore, high FAME content in the fuel has been found to increase oil dilution if DPF regeneration is realized via late post-injections (Ye et al. 2013, Lapuerta et al. 2011, Wattrus 2013, Andreae et al. 2007, Dumitrescu et al. 2015, Dernotte et al. 2012, Lešnik et al. 2013, Liaquat et al. 2013, Singh et al. 2015, Kegl 2011). However, in the publication 2 of this thesis, no significant differences in the different fuel LPI sprays were seen.

DOCs typically increase the NO₂:NO ratio by oxidizing NO into NO₂, a consequence of the combination of: a) the natural NO–NO₂ balance moving towards NO₂ as the temperature decreases, and b) the catalyzed (fast) chemical reactions in the DOC. CO and HC in the DOC potentially inhibit the NO conversion to NO₂, which can be secondary to HC oxidation in the catalyst. In Publication 1, the most significant NO–NO₂ balance change was found with HVO₃₀. With B₃₀, the relative NO₂ decrease was less pronounced. This may be explained by the inhibition discussed previously, as B₃₀ had higher HC emissions in normal mode. Moreover, the FAME oxygen promotes lower local equivalence ratios in the cylinder, which may increase NO₂ production. It is notable that the changes in NO–NO₂ ratio may reduce the NO_x conversion rate in the SCR, causing increases in NO_x emissions, or ammonia slip. In the case of DPF regeneration studied in Publications 1 and 2, also the HC and CO emissions tend to rise significantly, especially with low exhaust gas temperatures. In Publication 1, the emissions increased less with HVO blend than with the other fuels (Majewski et al. 2006, Warnatz et al. 1999, Challen et al. 2009, Olsen et al. 2010, Hirata et al. 2009, Katare et al. 2007, Irani et al. 2009, Reşitoğlu et al. 2015, Zheng et al. 2009, Wang et al. 2008, Yu et al. 2013).

Figure 13. The fuel blend distillation curves and their derivatives in publications 1 and 2.

FAME sprays during late post-injections and their effects on oil dilution, as well as the effects of the low volatility of FAME on fuel exit rates from the oil were studied in publications 1 and 2 of this thesis. In contrast to previous findings, in the experimental spray study of Publication 2, no significant differences between the fuel spray propagation of the standard diesel and fuel blends of 30% FAME or 30% HVO were found. Most probably, the fuel property differences of the blends were too small to cause detectable spray propagation differences, and in the studied case, fuel property effects on the spray were not the main cause of the differences in oil dilution. However, while there were no visible differences in the spray penetration and all the fuel blends contacted the cylinder wall, it is possible that the high surface tension, viscosity, and density, and especially the low front-end volatility (below the temperatures of exhaust gases leaving the cylinder) increased the liquid fuel amount entering the oil, and thus dilution rates. According to publication 1, the fuel exit rates from the oil had some correlation with the derivative of the back end of the distillation curve (above the temperatures of the exhaust gas leaving the cylinder), which is a measure of the evaporation rate as the temperature is increased. The FAME blend had higher evaporation rates (see Figure 13) above 330 °C, the measured exhaust temperature in publication 1 (Wattrus 2013, Aatola et al. 2009, Happonen et al. 2012, Kim et al. 2014, Tilli et al. 2010, Hulkkonen et al. 2011, Lapuerta et al. 2011, Wattrus 2013, Dumitrescu et al. 2015, Dernotte et al. 2012).

In the context of this thesis, it must be taken into account that fuel properties have strong dependencies on one another. For example, the HC chain length has numerous effects. The distillation temperatures, fuel viscosity, density and CN are usually all lower with shorter HC chains. In engine tests, it can be very difficult to conclude, which of the properties are causing the different phenomena. Changes in the HC chain length also lead to some contradictory ef-

fects. When viscosities, distillation temperatures and densities are lowered, it leads to increased mixing and evaporation and thus better combustion. However, at the same time, the CN is usually lowered, which leads to worse ignition (Tilli et al. 2010).

4. Experimental Methods

4.1 The fuels studied in the research

The focus of this doctoral thesis is on renewable diesel fuels applied in various emission-reduction technologies. The fuels and their blending ratios used in each study can be seen in Table 4. In each publication, 100% regular diesel fulfilling standard EN590 has also been used as a reference. In studies 1 and 2, all the fuels used are from the same batch and thus exhibit exactly the same properties. The same fuel batches (standard diesel and pure HVO) are also used in studies 3 and 4. The standard diesel fuel in study 5 is similar but not from the same batch. In Study 6, many different reference properties of standard diesel have been used, depending on the reference case. The final results for standard diesel in Study 6 were obtained with a fuel with properties similar to the standard diesel in Study 5. In study 6, two paraffinic diesel fuels (HVO and GTL) with slightly different properties were simulated.

Table 4. Blending ratios (in percentage) of the alternative fuels studied in the publications.

Publication	1	2	3	4	5	6
Paraffinic diesel	30	30	100	100	-	100
FAME	30	30	-	-	-	100
DME	-	-	-	-	-	100

4.2 The engines used in the experiments

The experimental studies presented in this thesis were carried out with three research engines, whose specifications can be seen in Table 5. In Publication 1, a six-cylinder production diesel engine was used, and the single cylinder optical research engine in Publication 2 was based on a similar production engine. In publications 3, 4 and 5, a single-cylinder medium-speed research engine was used, with an optical access to the cylinder in Publication 5. The fuel injection simulation model in Publication 6 was based on the single-cylinder medium-speed research engine. The setup of each engine was modified for research purposes. Specifically, the engine compression ratios, injection nozzle tips, the exhaust lines and the related aftertreatment equipment were modified. For a more correct evaluation, the effective compression ratio should be considered

slightly smaller due to crank mechanism clearances and air blow-by through the piston rings.

Table 5. Engines used in the studies and the engine specifications.

Article number	1	2	3	4	5	6
Cylinders	6	1	1	1	1	1
Cylinder diameter (mm)	111	111	200	200	200	N/A*
Stroke (mm)	145	145	280	280	280	N/A*
Compression ratio	17.0:1	17.9:1	15.0:1	15.0:1	13.0:1	N/A*
Valves	4	4	4	4		N/A*
Max. Speed (rpm)	2200	1500	900	900	900	900
Max. injection pressure (bar)	1600	1600	1400	1400	1400	1400
Injection system	CR	CR	CR	CR	CR	CR
Injector holes	8	8	9	9	1	8
Nozzle hole diameter (mm)	0.132	0.132	0.3	0.3	0.36	0.36
Gas exchange valve system	camshaft	EHVA	EHVA	EHVA	EHVA	N/A*

CR = Common rail, EHVA = Electrohydraulic valve actuator. *Not relevant in a fuel injection simulation study.

4.2.1 Agco production engine

The engine used in Publication 1 and part of Publication 2 was an Agco 8.4 litre six-cylinder off-road diesel engine approved for stage 3B emission levels. A Schenk W400 eddy-current dynamometer with a force transducer was used. The original exhaust gas aftertreatment system (DOC+SCR) of the engine was replaced with only the DOC, because solely the DOC phenomena during the LPI's was studied, not the DPF regeneration itself. The catalyst package was of typical size ($l = 5$ in, $d = 10.5$ in), containing medium PGM loading and Pt/Pd ratio. The experimental setup can be seen in Figure 14.

Figure 14. A schematic of the Agco production engine and the auxiliary system used in publications 1 and 2.

Measurements with the Agco production engine

The THC emission measurements were made with a J.U.M. VE7 analyser, using the hydrogen flame ionization detector (FID) method. O₂ was measured with a Sick Sidor analyser with a paramagnetic cell. Non-dispersive infrared (NDIR) technique was used to measure CO and CO₂, and an Ecophysics CLD 880 chemiluminescence analyser to measure the NO_x emissions. An AVL 415 smoke meter measured the filter smoke numbers (FSN), indicating the soot emissions. The fuel mass flows were measured with an AVL Fuel Meter 733. The emissions were measured after the DOC and the temperatures immediately after the cylinder, as well as at the inlet and outlet of the DOC. Additionally, oil samples were taken periodically during the test runs. Fuel contents in engine oil, viscosities, total acid numbers (TAN), and total base numbers (TBN) were analysed by a third-party laboratory.

4.2.2 LEO2 engine

The optical research engine (Figure 15) used in Publication 2 is based on a Agco Power 84 diesel engine, similar to the one used in Publication 1, converted to a single-cylinder operation mode. One of the six cylinders of the research engine is functioning, and modified for optical access. The remaining five cylinders have holes and pistons to balance the engine running.

Figure 15. The publication 2 optical engine components: A) Electrohydraulic valve actuator, B) Cylinder head, C) Dual fuel injectors, D) Piston and cylinder extension, E) Imaging system, F) Conventional fuel injection system, G) Intake boost air channels.

The research engine had the production engine cylinder head. The injector location was at the centreline of the cylinder. An electric motor with a frequency converter as a dynamometer was used with the engine, as well as an exter-

nal air compressor, capable of producing charge air pressure of 6 bars at maximum. Exhaust backpressure was adjusted with a control valve in the exhaust line. The charge air temperature was controlled with an air heater and a cooler. Fuel injection parameters were adjusted freely according to the measurement plan. The engine was equipped with an electro-hydraulic valve actuator (EH-VA) system, which gave free control over the valve timings and maximum valve lifts. Dry Teflon-based piston rings were used, as the liner was not lubricated.

The engine control and the data acquisition system were of in-house design, built on the LabVIEW CompactRIO Field-Programmable Gate Arrays (FPGA) real-time system. It was operated with a graphical user interface on a host PC. The same system was used for engine control and measurements. The engine parameters and output variables were monitored in real time.

The LEO2 engine had optical access through the piston top and cylinder liner, which allowed optical measurements (see Figure 16). An elevated cylinder liner and a piston extension gave a view from the underside of the combustion chamber through a glass piston bowl. In the studies, the borosilicate piston had a simplified piston bowl shape.

Figure 16. The optical access to the publication 2 research engine: (a) intensified camera, (b) cylinder liner, (c) mirror, (d) cylinder head, (e) piston extension or cylinder, (f) transparent glass piston and combustion chamber, and (g) LED light.

Optical measurements with the LEO2 engine

In Publication 2, fuel sprays were studied by taking pictures through the optical piston top via a mirror placed under the piston. To obtain very short exposure times and thus, freeze the spray motion, an image intensified 12-bit (4096 levels of grey) monochrome CCD camera with 1376 x 1040 pixels was used. The Mie scattering method was used for spray visualization. An external 10W Seoul SSC P7 power LED provided the light intensity needed to study the LPI spray development. The light, located above the camera lens (see Figure

16), was reflected via the mirror. The exposure time, related to the sweep time (delay) of the image intensifier, was 5 ms in the measurements. The intensifier gain was 75%. A DaVis software and a LaVision hardware system developed for optical measurements controlled the measurements and data acquisition. A calibration object with exactly known dimensions was utilized to calibrate the images for the DaVis software. The spray tip penetration was defined as the distance between the injector nozzle tip and the leading border of the liquid spray.

4.2.3 EVE Engine

Publications 3, 4 and 5 were carried out with EVE engine, a single-cylinder medium-speed CI research engine. The engine frame, the crankshaft and the main bearings of EVE engine were designed to withstand very high cylinder pressures and engine speeds. An electric motor was connected to the engine (see Figure 17). In all the experiments, 900 rpm engine speed was used.

Figure 17. Schematic of the EVE engine test bed; M: electric motor, E: single-cylinder engine (Imperato et al. 2016).

The gas exchange valve system consisted of electro-hydraulic valve actuators (EHVA). In the system, valve opening and closing timings, maximum lifts, and opening and closing slopes for intake and exhaust valves could be set with very high flexibility. The control program was based on DSpace software.

Intake pressurized air was supplied by a charge air plant that is composed of a screw compressor and three balancing reservoirs, and installed to balance the air pressure fluctuations upstream of the engine. The intake air temperature could be regulated by a heat exchanger. A throttle valve, set in the exhaust pipe before the probes for measuring the emissions and the smoke level, was used to regulate the exhaust pressures. The common-rail fuel injection system had adjustable rail pressure, injection timing and injection duration.

Measurements with the EVE engine

The measurement equipment in the EVE consisted of high frequency and low-frequency sampling devices, depending on the measured variable. Cylinder pressure was measured with a Kistler pressure transducer, sampling every 0.2 CA° and using a 20-cycle average. An Emerson Micromotion ELITE CMF100 flow meter was used for charge air measurements and the fuel mass flows before the engine were obtained with an Emerson Micromotion ELITE CMFo25 flow meter. All of the pressures and temperatures of all the fluids

involved in the tests were measured with DeltaV software with a sampling rate of 1 Hz. The emission measurement equipment and methods were similar to the ones used with Agco production engine.

Optical measurements with the EVE engine

In Publication 5, the optical spray measurements were also made with the medium-speed EVE research engine. The engine was adapted for optical measurements for this study. The optical EVE is presented in Figure 18.

Figure 18. The structural schematic of the optical EVE engine (Publication 5).

The optical access to the EVE cylinder was via quartz windows in a steel flame ring with four different window positions, of which one was used for the camera and one for the laser beam.

For optical fuel spray measurements near the TDC, the piston top design was specific to the measurements in publication 5. A large wedge shape had been cut to the piston top to ensure a view to the fuel spray (Figure 19). In the optical measurements, low load conditions were used to keep the maximum cylinder pressure at 39 bars. The optical EVE is described more thoroughly by Sarjoavaara et al. (Sarjoavaara et al. 2008).

Figure 19. The schematic view of the fuel spray near TDC (Publication 5).

A double pulse Nd:YAG laser was used as the light source in the optical measurements. A laser guide arm guided the laser beam to the sheet optics. There, the laser beam was reshaped into a thin laser sheet, aligned with a mirror so that it would cross the fuel spray in the right position. A 4M CCD cross-correlation camera, equipped with a 105mm Nikon lens, mechanical shutter and 532 nm 3nm band pass filter, was used to take images of the fuel spray. The filter blocked the combustion light from the images. Thus, only Mie scattered laser light from droplets was captured. The mechanical shutter was used to protect the second frame of PIV images from overexposure during data transfer. Images were captured via mirrors to minimize damage if the quartz window broke. Explosion covers were used to protect the laser and the camera windows.

4.3 Simulation models

Simulation models were built and used to provide information about the engine setup or to obtain results that could not be easily measured in the test runs (e.g. in-cylinder temperature). The simulation models were developed with the object-oriented GT-Power and GT-Fuel 1-D simulation programs, which are part of the GT-Suite software family.

4.3.1 GT-Power model

For publications 3 and 4, the boundary conditions, e.g. charge air and exhaust gas pressure, were produced with simulations. The GT-Power simulation model had a mathematical turbocharger (Imperato et al. 2009), transferring some of the thermal and mechanical energy from the exhaust gases to the intake side. For each valve profile, the simulations produced the boundary conditions. For the combustion chamber, the Redlich-Kwong real gas law was used. A predictive object was used to calibrate the combustion process, and the heat transfer was modelled with the classic Woschni correlation. The combus-

tion model was calibrated with cylinder pressure curves achieved from former tests.

4.3.2 GT-Fuel model

The fuel injection system model in publications 5 and 6 was made with GT-Fuel. In GT-Fuel, a flow solution developed for 3-D CFD applications reduced to one dimension is used, and an explicitly conservative finite volume solution of mass and energy is applied (Gosman, 1985, Gamma Technologies 2003, Seenikannan et al. 2008).

Figure 20. A schematic of the GT-Fuel model built for publication 6 (Publication 6).

The schematic of the fuel injector model and the injector used in publications 5 and 6 can be seen in Figure 20. Different GT-Fuel objects and templates were used to model the physical parts, properties and boundary conditions of the fuel injection system of the EVE engine. The fuels and their behaviour were referenced in their own simulation objects.

5. Summary of Publications

5.1 Publication 1

The focus of Publication 1 was on off-road diesel engine late post-injections with biofuel blends (30% FAME and 30% HVO) and their effect on engine oil dilution, DOC performance and emissions. The objectives of the study were to:

- (a) compare regular diesel, 30% HVO blend and 30% FAME blend effects on oil dilution during similar late post-injection mode engine operation;

- (b) compare the diluting fuel exit rates from oil during normal engine operation with regular diesel, 30% HVO blend and 30% FAME blend; and

- (c) monitor the emissions and temperature behaviour in the DOC during late post-injection mode operation with regular diesel, 30% HVO blend and 30% FAME blend. The engine tests were made with an off-road diesel engine under low load conditions at 1200 rpm engine speed. During the experiments, oil samples were periodically taken from the engine oil and later analysed. Emissions and temperatures before and after the DOC were also measured. The novelty of the study is based on two parts. First, similar late-post injection tests were run with blends of both HVO and FAME, giving a rare comparison with the fuels. Second, oil dilution and the fuel exit rates during normal mode without the late post-injections were measured.

The results showed the oil dilution and the DOC performance to be very similar with regular diesel and the HVO blend. In comparison, the FAME blend, the results showed increased oil dilution, as can be seen in Figure 21. Additionally, a smaller than anticipated temperature rise in the DOC, and higher emissions were observed with FAME. This indicates that the FAME blend oxidation in the DOC was not as complete as with regular diesel or HVO blend. In the fuel exit rates, the hypothesized slower exit rate of FAME was not found. On the contrary, FAME exit rate was higher than with regular diesel. The reason for this was suggested to be the low end-point of the FAME-blend distillation curves. Moreover, both the fuel entry and exit rates to and from the engine oil were concluded to be more dependent on the distillation curve derivatives in different temperature zones than the distillation temperatures themselves.

Figure 21. Fuel contents in engine oil before and during LPI mode (Publication 1).

The conclusion of the publication was that during DPF regeneration by late post-injections, FAME blends induce more oil dilution, demand an increase in late post-injection quantities and thus, result in still increased oil dilution. Therefore, they may require e.g. shorter oil change intervals, while HVO blends require no changes when compared with regular diesel.

5.2 Publication 2

Publication 2 was written side-by-side with Publication 1, with the same fuels but with different experiments and focus. Properties of late post-injection sprays were studied with regular diesel and two biofuel blends containing either 30% FAME or 30% HVO. The study focused on spray physics and spray tip penetration with selected fuel blends. The objectives of the study were to:

- (a) run a six-cylinder engine using the three test fuels in order to see how the oil is diluted in a real engine;
- (b) to mathematically characterize the wall-wetting as a function of droplet size and velocity using a single-droplet model; and
- (c) to show in an optical single cylinder engine that the post-injection leads to inevitable wall-wetting. The phenomena inside the cylinder could be quite well captured, and evidence of wall-wetting was obtained (seen Figure 22).

Three different late post-injection timings were investigated. Image sequences of the main spray flame and non-combusting late post-injection sprays were extracted. To verify oil dilution relation to the post-injections, oil samples from a six-cylinder test engine were analysed. The novelty of the study arose from (1) the first comparison of FAME and HVO blends in an optical engine, (2) strong evidence on the phenomena related to the post-injections with different engine configurations and (3) the development of a single-droplet model showing the inevitability of wall-wetting in the case studied.

Figure 22. View of phenomena in the cylinder: (a) main injection at 5 CAD ASOI, (b) atomization and evaporation before ignition, (c) ignition, (d) combustion during the main injection, (e) combustion after end of injection, (f) end of combustion, (g) late post-injection, (h) poor atomization of late post-injection and (i) cylinder wall-wetting.

Hypothesis of Publication 2 was that paraffinic fuel properties give sprays better suited for DPF regeneration in LPI conditions, and that oil dilution is diminished vs. normal diesel and FAME. However, according to the experiments, differences in the spray characteristics are not significant with the tested fuel blends, and the differences between the HVO blend and reference diesel oil dilution was insignificant. Higher oil dilution rates were observed with a fuel blend composed of 30% fatty acid methyl ester. The spray/wall interaction was thoroughly explained by introducing a theoretical/computational framework that characterizes any spray/wall interaction in terms of a phase diagram for any considered operation conditions. All the studied late post-injection timings were noted to lead to the unwanted cylinder spray/wall interaction and wall-wetting consequently diluting the engine oil: the droplet evaporation time is very long compared to the characteristic wall contact timescale in the relevant cylinder conditions. Thereby, on the average, the fuel droplets do not evaporate before the cylinder wall.

The main reason for oil dilution rate differences between fuel blends was found to be related to the volatility of the fuel fraction in the diluted engine oil. High gas density (not found in LPI conditions) and very small droplet sizes (which are, according to previous studies, typical to paraffinic fuel sprays) are required to prevent wall interactions.

5.3 Publication 3

The objective of this Publication 3 was to analyse the performance and the combustion of a large-bore medium-speed engine running with HVO at low engine load. A preliminary performance comparison between HVO and diesel was carried out, showing lower emissions for HVO as such. Because of the high HVO ignitability, it was possible to run with the advanced Miller cycle, reaching IVC up to 70 CA° BBDC and with internal exhaust gas recirculation (iEGR) up to 9% (of cylinder load mass). The iEGR technique consisted of retaining a fraction of hot exhaust gases in the combustion chamber by setting a negative gas exchange valve overlap.

Figure 23. NOx emissions in relation to fuel consumption and FSN in Miller cycle and iEGR runs, low load mode (Publication 3).

The results (see Figure 23) showed the benefits of HVO compared to diesel fuel, since fuel consumption was 5% lower with a simultaneous reduction of 3% NOx and 67% FSN. At low load, Miller timing with IVC=70 CA° BBDC increased the peak of the premixed combustion, due to the lower cylinder pressure and temperature, resulting in NOx outcomes higher than with IVC=50 CA° BBDC. In fact, the trend is monotonous: the more advanced the IVC (more Miller rate), the later the ignition occurs. However, by diluting the in-cylinder charge with a 5% exhaust gas mass (iEGR), a NOx reduction of 55%

was achieved, compared to the reference point with the same fuel consumption. In addition, soot emissions were relatively low ($FSN < 0.9$) due to the high CN and thorough combustion of the paraffinic HVO. Summing up, the use of mere Miller cycle at low engine load does not give the maximum benefits with HVO, because the ignition delay is still too long and the combustion does not proceed regularly. A small amount of exhaust gases in the combustion chamber (4-5% according to the simulations) gives the lowest NO_x, slight soot and no penalties in fuel consumption (see Figure 23). A correlation between the NO_x emissions and the combustion duration was found: if IVC is not changed, longer duration brings lower NO_x emissions. Further optimization was concluded to be possible by modifying the SOI and the injection pressure or by finding the optimum exhaust gas quantity in the combustion chamber with each Miller timing configuration.

5.4 Publication 4

Publication 4 continued the study of Publication 3. The objective was to analyse the performance and the combustion with HVO at medium load. In a preliminary comparison run, a reduction of NO_x (3%) and improvement of fuel economy (4% on a weight basis), and overall more stable combustion process with lower HRR and pressure fluctuations were achieved at the same time using HVO instead of diesel fuel. Moreover, the soot level became lower, from 0.05 to 0.02 as FSN. Advanced IVC (up to 70 CA° BBDC) and iEGR were applied running with HVO. According to the simulation results, the exhaust gas fraction in the combustion chamber was increased by a negative valve overlap and reached 10% mass.

The results showed that the Miller cycle reduced the NO_x (over 38%), while slightly improving fuel economy. The main drawback was that high charge air pressure (over 6 bar) was needed and therefore, in a real application this would require a powerful turbocharger. The highest Miller rate lengthened the ignition delay, and the peak of the premixed combustion was high, producing less stable combustion and negatively affecting the engine efficiency. Exhaust gases in the charge brought advantages in terms of combustion stability and NO_x reduction, especially when IVC=50 CA° BBDC. With IVC=70 CA° BBDC, higher fuel consumption and soot were registered with a similar NO_x level. The final results can be seen in Figure 24.

NO_x reduction of 45% was achieved with IVC=70 CA° BBDC and 4% exhaust gas mass in the charge, with a 2% penalty in fuel consumption, while almost 40% reduction was achieved with 3 % decreased fuel consumption and zero scavenging. All FSN values were below 0.1 due to the high HVO ignitability and stable paraffinic combustion.

Figure 24. NOx emissions in relation to fuel consumption and FSN in Miller cycle and iEGR runs, medium load mode (Publication 4).

5.5 Publication 5

In Publication 5, the objective was to compare experimental spray measurements made in a medium-speed optical diesel engine with CFD predictions in similar evaporating conditions. The measurements were made in an optical single-cylinder medium speed research engine with a cylinder bore of 200 mm and an engine speed of 900 rpm. The experimental spray tip penetrations, measured during the early spray development period when the spray evaporation had not yet reached the quasi-steady-state phase, were compared to CFD simulations, conducted in both a static chamber environment and in engine conditions. The fuel injection boundary conditions were produced with a 1-D simulation model of the engine fuel injection system, built in Publication 6.

Within the error margins associated with the experimental and computational data, relatively good accuracy was obtained between measured and simulated spray tip penetration: up to about 0.1 ms, the prediction and the experimental spray tip penetrations were in very good agreement. After this, the simulations overpredicted the tip penetration. It was observed that the computational spray shape was somewhat different compared to the experimental

sprays, which were wider especially near the tip area. This was evaluated to be mainly a mesh density issue. Increasing the initial opening angle in the simulations reduced the spray tip penetration, which yielded somewhat better agreement between the experimental spray tip penetration (see Figure 25).

Figure 25. The simulated fuel spray tip penetrations in engine conditions with moving piston. Initial spray opening angle is 24 degrees. The measured spray tip penetration was obtained from the running optical EVE engine (Publication 5).

Relatively good accuracy between the experiments and the modelling was also obtained for injection duration and total injected mass. However, the sensitivity analysis also showed the importance of accurate data on the fuel injection boundary. Even with a simulated fuel injection profile, large differences may occur in the final spray tip penetration. Additionally, in the experiments, the quasi steady-state phase of the fuel spray was not reached. During the quasi steady-state phase, the evaporation rate from the liquid phase is balanced by the injected mass flow rate and the liquid spray tip stays at a relatively constant location. Due to this fact, relatively large spray to spray variation was seen leading to a big error margin for the spray tip penetration.

5.6 Publication 6

In Publication 6, renewable diesel-type fuels and the compatibility of their physical properties with a single-cylinder medium-speed research diesel engine were studied. The objective of the study was to

- (a) build and validate a simulation model of the EVE research engine fuel injection system and
- (b) compare the fuels and determine whether renewable fuel properties require changes in the fuel injection system of the EVE research engine.

The study consisted of a literature study of the fuels, an introduction to the simulation model design and the simulations made, and the simulation results and summary. The fuels studied were traditional biodiesel (fatty acid methyl ester, FAME), hydrotreated vegetable oil (HVO), Fischer-Tropsch (FT) diesel fuels and dimethyl ether (DME). The raw materials, production and characteristics of the fuels were briefly introduced and their qualities and usability compared.

A relatively good fit with the experimental and simulated fuel injection doses with standard diesel fuel was achieved (see Figure 31). The simulation model gave mostly slightly larger doses, significantly so with short injection durations. This error is probably due to discharge coefficient and injection mass flow overestimation at the end of the injection: e.g. the flow decline might be slower than in reality. With injections longer than 4 ms, almost all simulated values remained within 5% limit. The relative simulation errors were larger with measurement run batch 3, at which a different nozzle, with spark eroded (not drilled) nozzle holes of the same nominal size was used.

Figure 26. Simulated and measured injection doses (Publication 6).

According to the simulations, the renewable diesel fuels function quite similarly in the fuel injection system. The main differences in the physical properties of the fuels are the densities and viscosities, having predictable effects on the fuel injection. More significant were the deviations in DME compressibility and vapour pressure, which caused cavitation in the nozzle. This, availability, the possibility of leaking due to low viscosity, the required changes to the low-pressure side of the fuel injection system (due to the gaseous nature of DME in normal conditions), and the difficult chemical properties, on their part lead to DME being left out of the later experimental program.

6. Conclusions and Further Research

6.1 Summary and Conclusions

This research focused on the most common alternative diesel fuels and their effects on both the emissions and the emission reduction methods. This was done via experimental and computational investigations with both off-road high-speed and large-bore medium-speed CI research engines.

The research has shown that the most widely used renewable diesel fuels function quite similarly in the engines (Publication 6), while having some significant effects on the emissions and functionality of emission-reduction technologies (Publications 1-4). The main differences in the physical properties of the fuels that have an effect on the emissions from the engines are fuel densities, viscosities and distillation properties. These characteristics also affect the injection event and the fuel spray, essential for fuel mixing and the possible the cylinder wall impact, which in turn causes dilution and deterioration of the engine oil, observed in publications 1 and 2.

Part of this thesis (publications 3 and 4) involved the use of the Miller cycle. The use of HVO reduced emissions as such. Moreover, the utilization of the very high cetane numbers and stable combustion properties of HVO allowed the use of very advanced IVC and internal EGR. The effect of Miller applications depends on engine load, since the in-cylinder compression temperature is generally lower as the load decreases. At high load, mixing-controlled combustion constitutes the most influential part of the process, and the Miller cycle was applied with limitations, but a NO_x reduction in the range 40%–60% was achieved at partial load with the Miller cycle, with increasing fuel consumption and smoking as NO_x was decreased. However, low in-cylinder temperature prior to combustion increased the ignition delay, which limited the possible gains in emission reduction. As a conclusion, the paraffinic fuel properties may be utilized to decrease the NO_x emissions via in-cylinder technologies further than with regular diesel. However, there are limitations, and further study is needed to optimize e.g. the fuel injection parameters.

Additionally, a part of this thesis has been the application of optical studies, combined with simulations and CFD calculations, applied to engine research. It was found that it is possible to obtain relatively good accuracy between experiments and modelling. The combined usage of an intensified CCD camera

and an external LED light source enabled investigations of liquid fuel spray properties of late post-injections despite the wetting of the transparent optical engine parts in low-temperature and low-pressure conditions. However, the sensitivity analyses also showed the importance of accurate boundary data. In Publication 5, it was found that even with a fuel injection profile from a well-verified simulation model, large differences may occur in the final spray tip penetration. There existed a relatively large error in the simulated total fuel mass, mainly attributed to the closing rate of the needle valve and to the prediction of the discharge coefficient.

According to the engine tests and oil samples, the studied regeneration mode of combustion induces oil dilution. In particular, the dilution was higher with FAME30 than with EN590 and HVO30. No significant difference between EN590 and HVO30 was observed. The numerical model, using single-droplet simulations, indicated that the droplet evaporation time is very long compared to the characteristic wall contact time, and the droplets do not evaporate before the cylinder wall. Conditions needed to evaporate the droplets before the cylinder wall require high gas density and very small droplet sizes, not attained with very late injection strategies. Correspondingly, clear cylinder wall wetting was observed during post-injection with all three studied fuels and three post-injection timings. Thus, in the optical engine (Publication 2), the differences in spray characteristics between the fuels were not found to be the major reason for the possible oil dilution rate differences. This indicates that the main reason for the oil dilution rate differences between the fuels was related to the volatility of the fuel fraction in the diluted engine oil. However, the spray measurement uncertainties were high under the unsteady engine conditions during the late post-injections, and the property differences small between the 30% fuel blends. Additionally, the image quality was not ideal for spray penetration measurements. In the spray penetration studies the spray to spray variation and thresholding of image may cause high uncertainty to results.

In Publication 5, it is pointed out that the spray did not reach the quasi steady-state phase where the liquid spray tip stays at a relatively constant location, as the evaporation rate from the liquid phase is balanced by the injected mass flow rate. Similarly, in the optical experiments of Publication 2, the quasi steady-state phase was not reached. Due to this fact, relatively large spray to spray variation was seen leading to a big error margin for the spray tip penetration. Additionally, in the usual case the fuel spray penetration is measured during the quasi steady-state period, and the results of these experiments are not comparable as such. However, as the result in Publication 2 was that the fuel spray hit the cylinder walls with every fuel, the conclusion is the same: in this case, the effect of the fuel properties on the fuel spray did not play a significant role in the oil dilution. The result brings into question some earlier hypothesis about the relationship between the spray characteristics and oil dilution.

While paraffinic fuel blend behaviour during regeneration is very similar to regular diesel, regular biodiesel blends are more prone to dilute the engine oil. Moreover, due to the lower energy content, there is a need for larger quantities

of biodiesel blend LPIs during DPF regeneration events, which will increase fuel consumption and lead to increased oil dilution. Thus, for high FAME portion fuel blends, more frequent oil changes are needed. However, in most studies, both FAME and paraffinic fuels reduce particulate emissions. This means that the interval of the regeneration events could be longer, which decreases the oil dilution, compared to regular diesel. Moreover, by optimizing the engine calibration for the biofuel blends, emissions and oil dilution could probably be reduced, as the engine parameters are based on experiences with regular diesel. Furthermore, the optimization of the LPI would be beneficial with all the fuels: the earliest possible injection timing with no ignition in the cylinder ensures the highest in-cylinder temperature and pressure during the LPIs. This increases the fuel spray quality and reduces the amount of liquid fuel contacting the cylinder walls, and therefore, oil dilution. Due to its high CN, paraffinic fuels will ignite in lower pressure and temperature, which reduces the LPI timing optimization potential.

The research questions of this thesis were:

1. How does HVO affect diesel engine performance and emissions during typical engine operation?

Answer: Depending on the engine and its parameters, HVO brings emission and fuel consumption benefits from negligible to significant. Compared to standard diesel, significantly lower fuel consumption and emissions of NO_x and PM (as FSN) were found for HVO in the reference runs of Publications 3 and 4, while no significant normal mode differences in the emissions were found in publication 1. According to the literature reviews of this thesis and its publications, also HC and CO emissions are typically reduced, especially with older engine technologies.

2. How can low emissions be reached with HVO with no significant performance penalties in diesel engines without external aftertreatment methods?

Answer: With Miller cycle and internal EGR, up to 55% lower NO_x emissions could be reached with no fuel consumption or FSN penalties. Simultaneous high load emission reductions at the range of 40% for both FSN and NO_x were found with no fuel consumption penalties. Lower emissions could probably be reached via further optimization of the valve timings and injection parameters.

3. How do biofuels affect late post-injection fuel sprays and required fuel injection parameters?

Answer: With HVO blends, no changes are required. With FAME, increased injection doses are needed, via longer injection duration or higher injection pressure, due to the lower heating value of FAME. No significant fuel spray quality differences were found between the fuel blends or fossil diesel in the measurements of publication 2.

4. How do biofuel late post-injections affect oil dilution and DOC performance during the DPF regeneration mode in an off-road diesel engine?

Answer: With HVO blend, no relevant effects when compared with regular diesel were found. With FAME blend, oil dilution and emissions were in-

creased, and the temperature rise in the DOC was lower. The need of increased injection doses with FAME was estimated to aggravate the effects.

6.2 Suggestions for Future Work

This thesis focused on certain cases of biofuel functioning in the engine and their effect on the emissions and emission reduction. However, the studies bring into light further questions relevant for the use of biofuels in engines. Further suggested research topics include:

1. 100% biofuel effects on DPF regeneration, oil dilution and late post-injection sprays. While late post-injection fuel spray differences between the 30% biofuel blends could not be seen in the studies of this thesis, the fuel physical properties have proven effect on fuel sprays, which may be significant with the 100% biofuels used in the future.
2. Fully developed fuel spray penetration with varying fuels and injection parameters in late-phase engine conditions. Finding out, whether the fuel spray impact with the cylinder wall could be avoided by parameter or fuel changes would be beneficial.
3. Similar studies with DME. DME was left out of this thesis due to its compatibility issues with the research engines. However, the issues can be quite easily resolved. DME is a very promising low emission fuel that may play a role in the future energy blend. It could be more easily synthesized from biomass than BTL, or more easily produced via power-to-gas methods than other diesel-type fuels.
4. Effects and possibilities of using FAME blended with paraffinic fuels. Both tend to decrease most emissions as such and have properties promoting ignition and combustion, especially in challenging conditions. These properties include the high cetane number and stable combustion properties of paraffinic fuels, and the oxygen content of FAME. However, FAME and paraffinic diesel fuels also have many complementing characteristics, such as high and low densities, distillation temperatures, compressibilities and viscosities, as well as the low lubricity of paraffinic fuels and the FAME tendency to increase lubricity even in low proportions.
5. Injection pressure and profile change effects on Miller cycle combined with further optimized iEGR rates and biofuels. Changing the SOI, use of pilot injection(s), or higher injection pressures should be studied to further utilize the potential of the technologies and fuels.

References

- Aatola, H.; Larmi, M.; Sarjovaara, T.; Mikkonen, S. (2009). Hydrotreated Vegetable Oil (HVO) as a Renewable Diesel Fuel: Trade-off between NO_x, Particulate Emission, and Fuel Consumption of a Heavy Duty Engine. *SAE International Journal of Engines* 1(1): 1251–1262.
- Abu-Jrai, A.; Tsolakis, A.; Theinnoi, K.; Cracknell, R.; Megaritis, A.; Wyszynski, M.; Golunski S.(2006). Effect of Gas-to-Liquid Diesel Fuels on Combustion Characteristics, Engine Emissions, and Exhaust Gas Fuel Reforming. Comparative Study. *Energy & Fuels* 20(6):2377-2384.
- Agarwal, A.; Chaudhury, V. (2012). Spray characteristics of biodiesel/blends in a high pressure constant volume spray chamber. *Exp Therm Fluid Sci* 42:212–218.
- Agarwal, D.; Singh, S. K.; Agarwal, A. K. (2011). Effect of Exhaust Gas Recirculation (EGR) on performance, emissions, deposits and durability of a constant speed compression ignition engine. *Applied Energy* 88(8):2900-2907.
- Akihama, K.; Takatori, Y.; Inagaki, K.; Sasaki, S.; Dean, A. (2001). Mechanism of the Smokeless Rich Diesel Combustion by Reducing Temperature. *SAE Technical Paper* 2001-01-0655.
- Allansson, R.; Blakeman, P.; Cooper, B.; Phillips, P.; Thoss, J.; Walker, A. (2002). The use of the continuously regenerating trap (CRTTM) to control particulate emissions: minimising the impact of sulfur poisoning. *SAE Technical Paper* 2002-01-1271.
- Al-Sarkhi, A.; Jaber, J.O.; Probert, S.D. (2006). Efficiency of a Miller engine. *Applied Energy* 83(4): 343–351.
- Antila, E.; Kaario, O.; Imperato, M.; Larmi, M. (2010). Effect of Intake Channel Design to Cylinder Charge and Initial Swirl. Society of Automotive Engineers. *SAE Technical Paper* 2010-01-0624.
- Arcoumanis, C.; Kamimoto, T. (2009). *Flow and Combustion in Reciprocating Engines*. Springer-Verlag, ISBN 978-3-540-68901-0.
- Arcoumanis, C.; Bae, C.; Crookes, R.; Kinoshita, E. (2008). The potential of di-methyl ether (DME) as an alternative fuel for compression-ignition engines: A review. *Fuel*, 87(7), 1014-1030.
- Arvidsson, R.; Persson, S.; Fröling, M.; Svanström, M. (2011). Life cycle assessment of hydrotreated vegetable oil from rape, oil palm and Jatropha. *Journal of Cleaner Production* 19:129–137.

Aoyagi, Y.; Kamimoto, T.; Matsui, Y.; Matsuoka, S. (1980). A Gas Sampling Study on the Formation Processes of Soot and NO in a DI Diesel Engine. Society of Automotive Engineers. SAE Technical Paper 800254.

Azimov, U.; Roziboyev, E.; Kim, K.; Jeong, D.; Lee, Y.; Yun, J. (2008). Investigation of Soot Formation in Diesel-GTL Fuel Blends under Quiescent Conditions. *International Journal of Automotive Technology* 9(5):523–534.

Azizi, Z.; Rezaeimanesh, M.; Tohidian, T.; Rahimpour, M. (2014). Dimethyl ether: A review of technologies and production challenges. *Chem. Eng. and Proc.* 82:150-172.

Belal, T.; Marzouk, E.; Osman, M. (2013) Investigating Diesel Engine Performance and Emissions Using CFD. *Energy and Power Engineering* 5(2):171-180.

Benajes, J.; Reyes, E.; Lujan, J. (1996). Intake Valve Pre-lift Effect on the Performance of a Turbocharged Diesel Engine. SAE Technical Paper 960950.

Beychok, M. (1973). NOX emission from fuel combustion controlled. *Oil & Gas Journal* 53–56.

Biswas, S.; Verma, V.; Schauer, J.; Sioutas, C. (2009). Chemical speciation of PM emissions from heavy-duty diesel vehicles equipped with diesel particulate filter (DPF) and selective catalytic reduction (SCR) retrofits. *Atmos Environ* 43:1917–1925.

Boehmann, A.; Morris, D.; Szybist, J.; Esen, E. (2004). The Impact of the Bulk Modulus of Diesel Fuels on Fuel Injection Timing. *Energy Fuels* 18(6):1877-1882.

Boerrigter, H.; den Uil, H.; Calis, H. (2002). Green Diesel from Biomass via Fischer-Tropsch synthesis: New Insights in Gas Cleaning and Process Design. *Pyrolysis and Gasification of Biomass and Waste, Expert Meeting, Strasbourg.*

Borgqvist, P.; Tunestal, P.; Johansson, B. (2013). Comparison of Negative Valve Overlap (NVO) and Rebreathing Valve Strategies on a Gasoline PPC Engine at Low Load and Idle Operating Conditions. SAE Technical Paper 2013-01-0902.

Bown, D. (2007). Techno-economic evaluation of emerging biodiesel production technologies. AMEC Ref. No. 14020075, AMEC London.

Brynnolf, S.; Fridell E.; Andersson, K. (2014). Environmental assessment of marine fuels: liquefied natural gas, liquefied biogas, methanol and bio-methanol. *Journal of Cleaner Production* 74: 86–95.

Brückner, C.; Kyrtatos, P.; Boulouchos, K. (2014). Extending the NO_x reduction potential with Miller valve timing using pilot fuel injection on a heavy-duty diesel engine. *SAE International Journal of Engines* 7(4):1838–1850.

Challen, B.; Baranescu, R. (2009). *Diesel Engine Reference Book*. Butterworth-Heinemann, ISBN 0-7506-2176-1.

Chi, J.; DaCosta, H. (2005). Modelling and control of a urea-SCR aftertreatment system. SAE Technical Paper 2005-01-0969.

- Chrysosakis, C.; Stahl, S. (2013). Well-To-Propeller Analysis of Alternative Fuels for Maritime Applications. CIMAC Congress, Shanghai (China). Paper No. 265.
- Codan, E.; Mathey, C. (2007). Emissions A new Challenge for Turbocharging. CIMAC Congress, Wien (Austria). Paper No. 245.
- Colwell, R. (2005). Oil Refinery Processes - A Brief Overview. Process Engineering Associates, LLC.
- Corsini, A.; Marchegiani, A.; Rispoli, F.; Sciulli, F.; Venturini, P. (2015). Vegetable Oils as Fuels in Diesel Engine. Engine Performance and Emissions. Energy Procedia 81: 942–949.
- Crepeau, G.; Gaillard, P.; van der Merwe, D. Schaberg, P. (2009) Engine Impacts and Opportunities of Various Fuels Including GTL and FAME: Toward Specific Engine Calibration? SAE Technical Paper 2009-01 -1787.
- Dalla Nora, M.; Zhao, H. (2015). High load performance and combustion analysis of a four-valve direct injection gasoline engine running in the two-stroke cycle. Applied Energy 159:117–31.
- Danish Maritime Authority (2012). North European LNG Infrastructure Project – a Feasibility Study for an LNG Filling Station Infrastructure and test of Recommendations. Copenhagen (Denmark).
- Dec, J. (1997). A Conceptual Model of DI Diesel Combustion Based on Laser Sheet Imaging. Society of Automotive Engineers. SAE Technical Paper 970873.
- Dernotte, J.; Hespel, C.; Houillé, S. (2012). Influence of fuel properties on the diesel injection process in nonvaporizing conditions, Atomization Spray 22(6):461-492.
- Di Iorio, S.; Mancaruso, E.; Sementa, P. (2015). A comprehensive analysis of the impact of biofuels on the performance and emissions from compression and spark-ignition engines. Int J Engine Res 16:680-690.
- Donahue, R.; Borman, G.; Bower, G. (1994). Cylinder-Averaged Histories of Nitrogen Oxide in a D.I. Diesel with Simulated Turbocharging. Society of Automotive Engineers. SAE Technical Paper 942046.
- Dumitrescu, C.; Polonowski, C.; Fisher, B.; Lilik, G.; Mueller, C. (2015). Diesel fuel property effects on in-cylinder liquid penetration length: impact on smoke emissions and equivalence ratio estimates at the flame lift-off length. Energ Fuel 29: 7689–7704.
- Edwards, S.; Frankle, G.; Wirbeleit, F.; Raab, A. (1998). The Potential of a Combined Miller Cycle and Internal EGR Engine for Future Heavy Duty Truck Applications. SAE Technical Paper 980180.
- Egnell, R. (1998). Combustion diagnostics by means of multizone heat release analysis and NO calculation Society of Automotive Engineers. SAE Technical Paper 981424.

Ejim, C.; Fleck, B.; Amirfazli, A. (2007). Analytical study for atomization of biodiesels and their blends in a typical injector: surface tension and viscosity effects. *Fuel* 86:1534–1544.

EU (2013). Standard EN 590:2013. Automotive fuels — Diesel — Requirements and test methods. European Committee for Standardization.

ETP (2011). Energy Technology Perspectives 2010. OECD/IEA, Paris.

EU (2004). Directive 2004/26/EC of the European Parliament and of the Council. Official Journal of the European Union.

EU (2007) Regulation (EC) No 715/2007 of the European Parliament and of the Council of 20 June 2007 on type approval of motor vehicles with respect to emissions from light passenger and commercial vehicles (Euro 5 and Euro 6) and on access to vehicle repair and maintenance information. Official Journal of the European Union.

EU (2009). Directive 2009/28/EC of the European Parliament and of the Council. Official Journal of the European Union.

EU (2011) COMMISSION REGULATION (EU) No 582/2011 implementing and amending Regulation (EC) No 595/2009 of the European Parliament and of the Council with respect to emissions from heavy duty vehicles (Euro VI) and amending Annexes I and III to Directive 2007/46/EC of the European Parliament and of the Council. Official Journal of the European Union.

EU (2012). Standard EN 14214:2012. Liquid petroleum products - Fatty acid methyl esters (FAME) for use in diesel engines and heating applications - Requirements and test methods. European Committee for Standardization.

EU (2015). Directive (EU) 2015/1513 of the European Parliament and of the Council. Official Journal of the European Union.

EU (2016) Regulation (EU) 2016/1628 of the European Parliament and of the Council of 14 September 2016 on requirements relating to gaseous and particulate pollutant emission limits and type-approval for internal combustion engines for non-road mobile machinery, amending Regulations (EU) No 1024/2012 and (EU) No 167/2013, and amending and repealing Directive 97/68/EC. Official Journal of the European Union.

Fanick, R. (2001). Comparison of Emission Characteristics of Conventional, Hydrotreated, and Fischer-Tropsch Diesel Fuels in a Heavy-Duty Diesel Engine,” SAE Technical Paper 2001-01-3519.

Flagan, C.; Seinfeld, J. (1988). Fundamentals of air pollution engineering. Prentice Hall. ISBN 0-13-332537-7.

Fessler, H.; Genova, M. (2004). An Electro-Hydraulic “Lost Motion” VVA System for a 3.0 Litre Diesel Engine. SAE Technical Paper 2004-01-3018.

GAMMA TECHNOLOGIES (2003). GT-FUEL Version 6.0 User's Manual. Gamma Technologies.

Ganapathy, T.; Gakkhar, R.; Murugesan, K. (2011). Influence of injection timing on performance, combustion and emission characteristics of Jatropha biodiesel engine, *Appl Energ* 88:4376-4386.

Gehrke, S.; Weiskirch, C.; Eilts, P. (2008). Development and Implementation of a Variable Valve Actuation System to a HD Diesel Engine. SAE Technical Paper 2008-01-1359.

Gehrke, S.; Kovács, D.; Eilts, P.; Rempel, A.; Eckert, P. (2013). Investigation of VVA-Based Exhaust Management Strategies by Means of a HD Single Cylinder Research Engine and Rapid Prototyping Systems. SAE Technical Paper 2013-01-0587.

Gosman A. (1985). Multidimensional Modelling of Cold Flows and Turbulence in Reciprocating Engines. SAE Technical Paper 850344.

Guibet, J-C (1999). Fuels and engines, volume 2. Technip. ISBN 2-7108-0754-8.

Hamada, H.; Haneda, M. (2012). A review of selective catalytic reduction of nitrogen oxides with hydrogen and carbon monoxide. *Appl Catal A* 421-422:1-13.

Haneda, M.; Sasaki, M.; Hamada, H.; Ozawa, M. (2011). Platinum-based catalyst for diesel hydrocarbon oxidation. *Chin J Catal* 32:777-781.

Hansen, J.; Joensen, F.; Sigurardottir, I.; Voss, B. (1995). Large Scale Manufacture of Dimethyl Ether – a New Alternative Diesel Fuel from Natural Gas. SAE Technical Paper 950063.

Hao, H.; Wang, H.; Song, L.; Li, X.; Ouyang, M. (2010). Energy consumption and GHG emissions of GTL fuel by LCA: Results from eight demonstration transit buses in Beijing. *Applied Energy* 87:3212-3217.

Happonen, M.; Heikkilä, J.; Murtonen, T.; Lehto, K.; Sarjovaara, T.; Larmi, M.; Virtanen, A.; Keskinen, J. (2012). Reductions in particulate and NO_x emissions by diesel engine parameter adjustments with HVO fuel. *Environ. Sci. Technol.* 46:6198-6204.

Heisler H. (1995). Advanced Engine Technology. SAE International. ISBN 978-0340568224.

Hiroyasu, H.; Arai, M. (1990). Structures of Fuel Sprays in Diesel Engines. SAE Technical Paper 900475.

Hepola, J.; Kurkela E. (2002). Energiantuotannon tehostaminen fossiiliin ja uusiutuviin polttoaineisiin perustuvassa energiantuotannossa. VTT Research Notes 2155, VTT Processes.

Heywood, J. B. (1988). Internal Combustion Engine Fundamentals. McGraw-Hill, ISBN 0-07-100499-8.

Hirata, K.; Masaki, N.; Yano, M.; Akagawa, H.; Takada, K.; Kusaka, J. 2009. Development of an improved urea selective catalytic reduction diesel particulate filter system for heavy-duty commercial vehicles. *Int J Engine Res* 10: 337–348.

Hulkkonen, T.; Hillamo, H.; Sarjovaara, T.; Larmi M. (2011). Experimental study of spray characteristics between hydrotreated vegetable oil (HVO) and crude oil based EN 590 diesel fuel. *SAE Technical Paper* 2011-24-0042.

Imperato, M.; Antila, E.; Sarjovaara, T.; Kaario, O.; Larmi, M.; Kallio, I.; Isaksson, S. (2009). NO_x Reduction in a Medium-Speed Single-Cylinder Diesel Engine using Miller Cycle with Very Advanced Valve Timing. *SAE Technical Paper* 2009-24-0112.

Imperato, M.; Kaario, O.; Sarjovaara, T.; Larmi, M. (2016). Split Injection in a Large-Bore Engine with Advanced Miller Cycle. *Applied Energy* 162:289–297.

International Standard, ISO 8178-4 (1996). Reciprocating Internal Combustion Engines – Exhaust Emission Measurement.

Irani, K.; Epling, W.; Blint, R. (2009). Effect of Hydrocarbon Species on NO Oxidation over Diesel Oxidation Catalysts. *Appl Catal B: Environ* 92:422–428.

Jaramillo, P.; Griffin, W.; Matthews, H. (2008). Comparative Analysis of the Production Costs and Life-Cycle GHG Emissions of FT Liquid Fuels from Coal and Natural Gas. *ASAP Environ. Sci. Technol.* 42 (20):7559–7565.

Jeguirim, M.; Tschamber, V.; Brilhac, J.; Ehrburger, P. (2005). Oxidation mechanism of carbon black by NO₂: effect of water vapour. *Fuel* 84:1949–1956.

Jeiouni, Y.; Pischinger, S.; Ruhkamp, L.; Koerfer, T. (2011). Relationship between Fuel Properties and Sensitivity Analysis of Non-Aromatic and Aromatic Fuels Used in a Single Cylinder Heavy Duty Diesel Engine. *SAE Technical Paper* 2011-01-0333.

Johansson, M. (2012). Fischer-Tropsch and FAME Fuels as Alternatives for Diesel Engines: an Experimental Study. Dissertation, Chalmers University of Technology. ISBN 978-91-7385-677-5.

Katare, S.; Patterson, J.; Laing P. (2007). Aged DOC is a Net Consumer of NO₂: Analyses of Vehicle, Engine Dynamometer and Reactor Data. *SAE Technical Paper* 2007-01-3984.

Kawasaki, K.; Hirota, K.; Nagata, S.; Yamane, K.; Ohtsubo, H.; Nakazono, T. (2009). Improvement of Natural-gas HCCI Combustion by Internal EGR by Means of Exhaust Valve Re-opening. *SAE Int. J. Engines* 2(2):733-739.

Kegl, B. (2011). Influence of biodiesel on engine combustion and emission characteristics, *Appl Energ* 88:1803–1812.

Kilpinen, P. (2010). Optimization of a simplified sub-model for NO emission prediction by CFD in large 4-stroke marine diesel engines. *Fuel Processing Technology* 91(2): 218–228.

- Kim, D.; Kim, S.; Oh, S.; No, S. (2014). Engine performance and emission characteristics of hydrotreated vegetable oil in light duty diesel engines. *Fuel* 125:36–43.
- Kim M.; Kim D.; Woo, S. (2003). Effect of V_2O_5 on the catalytic activity of Pt-based diesel oxidation catalyst. *Appl Catal B* 45:269–279.
- Kitano, K.; Sakata, I.; Clark, R. (2005). Effects of GTL Fuel Properties on DI Diesel Combustion. SAE Technical Paper 2005-01-3763.
- Knothe, G. (2004). Dependence of biodiesel fuel properties on the structure of fatty acid alkyl esters. National Center for Agricultural Utilization Research, USA.
- Koebel, M.; Elsener, M.; Kleemann, M. (2000). Urea-SCR: a promising technique to reduce NOx emissions from automotive diesel engines. *Catal Today* 59:335–345.
- Kolli, T.; Kanerva, T.; Huuhtanen, M.; Vippola, M.; Kallinen, K.; Kinnunen, T.; Lepistö, T.; Lahtinen, J.; Keiski, R. (2010). The activity of Pt/ Al_2O_3 diesel oxidation catalyst after sulphur and calcium treatments. *Catal Today* 154:303–307.
- Kono, N. (2005). Effects of Driving Conditions and Fuel Properties on Diesel Emissions. SAE Technical Paper 2005-01-3700.
- Kuki, T.; Miyairi, Y.; Kasai, Y.; Miyazaki, M.; Miwa, S. (2004). Study on reliability of wall-flow-type diesel particulate filter. SAE Technical Paper 2004-01-0959.
- Kuronen, M.; Mikkonen, S.; Aakko, P.; Murtonen, T. (2007). Hydrotreated vegetable oil as fuel for heavy duty diesel engines. Society of Automotive Engineers, SAE Technical Paper 2007-01-4031.
- Kyrtatos, P. (2013). The effect of prolonged ignition delay due to charge air temperature reduction on combustion in a diesel engine. Dissertation, ETH Zürich. DOI 10.3929/ethz-a-009933871
- Kyrtatos, P.; Hoyer, K.; Obrecht, P.; Boulouchos, K. (2014). Apparent effects of in-cylinder pressure oscillations and cycle-to-cycle variability on heat release rate and soot concentration under long ignition delay conditions in diesel engines. *International Journal of Engine Research* 15(3):325–337.
- Lamharess, N.; Millet, C.; Starck, L.; Jeudy, E.; Lavy, J.; Costa, P. (2011). Catalysed diesel particulate filter: study of the reactivity of soot arising from biodiesel combustion. *Catal Today* 176:219–224.
- Lapuerta, M.; Hernández, J.; Oliva, F. (2012). Strategies for active diesel particulate filter regeneration based on late injection and exhaust recirculation with different fuels. *Int J Engine Res* 15:209–221.
- Lapuerta, M.; Villajos, M.; Agudelo, J.; Boehman, A. (2011). Key properties and blending strategies of hydrotreated vegetable oil as biofuel for diesel engines. *Fuel Process Technol* 92: 2406–2411.

- Larsson, M.; Denbratt, I. (2007). An Experimental Study of Fischer-Tropsch Fuels in a Light-Duty Diesel Engine. SAE Technical Paper 2007-01-0030.
- Lee, T.; Park, J.; Kwon, S.; Lee, J.; Kim, J. (2013). Variability in operation-based NO_x emission factors with different test routes, and its effects on the real-driving emissions of light diesel vehicles. *Sci Total Environ* 461–462:377–385.
- Lepperhoff, G.; Körfer, T.; Pischinger, S.; Busch, H.; Keppeler, S.; Schaberg, P.; Schnell, M. (2006). Potential of Synthetic Fuels in Future Combustion Systems for HSDI Diesel Engines. SAE Technical paper 2006-01-0232.
- Lešnik, L.; Vajda, B.; Žunič, Z.; Škerget, L.; Kegl B. (2013). The influence of biodiesel fuel on injection characteristics, diesel engine performance, and emission formation. *Appl Energ* 111:558-570.
- Liaquat, A.; Masjukia, H.; Kalam, M.; Fazal, M.; Khan, A.; Fayaz, H.; Varman, M. (2013). Impact of palm biodiesel blend on injector deposit formation, *Appl Energ* 111:882–893.
- Lieberz, S. (2004). Biofuels in Germany - Prospects and limitations 2004. USDA Foreign Global Agriculture Information Network, Report Number: GM4048.
- Majewski, W. A.; Khair, M. K. (2006). Diesel Emissions and Their Control. SAE International. ISBN 0-7680-0674-0.
- McMillian, M. (2001). Combustion and Emission Characteristics of Fischer-Tropsch and Standard Diesel Fuel in a Single-Cylinder Diesel Engine. SAE Technical Paper 2001-01-3517.
- Meier-Peter, H.; Bernhardt, F. (2009). Compendium Marine Engineering. Seehafen Verlag, ISBN 978-3-87743-822-0.
- Mikkonen, S.; Niemi, N.; Orpana K. Polttoaineopas 2007. Neste Oil Oyj.
- Miller, R.; Davis, G.; Lavoie, G.; Newman, C.; Gardner, T. (1998). A Super-Extended Zeldovich Mechanism for NO_x Modeling and Engine Calibration. Society of Automotive Engineers. SAE Technical Paper 980781.
- Millo, F.; Gianoglio, M.; Delneri, D. (2010). Combining dual stage turbocharging with extreme Miller timings to achieve NO_x emissions reductions in marine diesel engines. CIMAC Congress, Bergen (Norway). Paper No. 210.
- Moreno-Tost, R.; Oliveira, M.; Eliche-Quesada, D.; Jiménez-Jiménez, J.; Jiménez-López, A.; Rodríguez-Castellón, E. (2008). Evaluation of Cu-PPHs as active catalysts for the SCR process to control NO_x emissions from heavy duty diesel vehicles. *Chemosphere* 72:608–615.
- Musculus, M. (2004). On the correlation between NO_x emissions and the diesel pre-mixed burn. Society of Automotive Engineers. SAE Technical Paper 2004–01-1401.

- Murugesan A., Umarani C., Subramanian R., Nedunchezian N. (2009). Bio-diesel as an alternative fuel for diesel engines-A review. *Renewable and Sustainable Energy Reviews* 13(3): 653-662
- Mäkinen, T.; Sipilä, K.; Nylund, N. (2005). Liikenteen biopolttoaineiden tuotanto- ja käyttömahdollisuudet Suomessa – taustaselvitys. VTT Processes.
- Neste (2016). Neste Renewable Diesel Handbook. Neste.
- Nishiumi, R.; Nakajima, T.; Kitano, K.; Sakata, I.; Clark, R. (2009). Improvement of DI Diesel Engine System by Utilizing GTL Fuels Characteristics. SAE Technical Paper 2009-01-1933.
- Nylund, N.; Aakko-Saksa, P.; Sipilä, K. (2008). Status and Outlook for Biofuels, Other Alternative Fuels and New Vehicles, VTT Research Notes 2426, Helsinki.
- Ohno, K.; Taoka, N.; Furuta, T.; Kudo, A.; Komori, T. (2002). Characterization of high porosity SiC-DPF. SAE Technical Paper 2002-01-0325.
- Olsen, D.; Kohls, M.; Arney G. (2010) Impact of oxidation catalysts on exhaust NO₂/NO_x ratio from lean-burn natural gas engines. *J Air Waste Manage* 60: 867–874.
- Pitkänen, J. (2000). Dieselmoottorin polttoaineen ruiskutuslaitteet. Helsinki University of Technology, Department of Mechanical Engineering, Internal Combustion Engine Laboratory. ISBN 9512248905.
- Prasad, R.; Bella, V. (2010). A review on diesel soot emission, its effect and control. *Bull Chem React Eng Catal* 5(2):69–86.
- Reddemann, M.; Mathieu, F.; Martin, D.; Kneer R. (2010). The Influence of Fuel Properties on Spray Propagation, Atomization and Evaporation. Proceedings of the 23rd Annual Conference on Liquid Atomization and Spray Systems (ILASS), Brno, Czech Republic.
- Reşitoğlu I, Kemal A, Ali K. (2015). The pollutant emissions from diesel-engine vehicles and exhaust aftertreatment systems. *Clean Technologies and Environmental Policy* 17(1):15–27.
- Raiko, R.; Saastamoinen, J.; Hupa, M.; Kurki-Suonio, I. (2002). Poltto ja palaminen. Gummerus. ISBN 9516666043.
- Rantanen, L.; Linnaila, R.; Aakko, P.; Harju, T. (2005). NExBTL – Biodiesel fuel of the second generation. SAE Technical Paper 2005-01-3771.
- Reinhardt, G.; Gärtner, S.; Helms, H.; Rettenmaier, N. (2006). Final Report - An Assessment of Energy and Greenhouse Gases of NExBTL. Institute for Energy and Environmental Research, Heidelberg GmbH, Germany.
- Roberts, L.; Magee, M.; Shaver, G.; Garg, A.; McCarthy, J.; Koeberlein, E. (2014). Modeling the impact of early exhaust valve opening on exhaust aftertreatment

thermal management and efficiency for compression ignition engines. *Int J Engine Res* 16:773–94.

Sampara, C.; Bissett, E.; Chmielewski, M.; Assanis, D. (2007). Global kinetics for platinum diesel oxidation catalysts. *Ind Eng Chem Res* 46:7993–8003.

Sarjovaara, T.; Hillamo, H.; Olenius, T.; Larmi, M. (2008). Optical in-cylinder measurements of a large-bore medium-speed diesel engine. *SAE Technical Paper* 2008-01-2477.

Schaberg, P. (2000). Comparative Emissions Performance of Sasol Fischer-Tropsch Diesel Fuel in Current and Older Technology Heavy-Duty Engines. *SAE Technical Paper* 2000-01-1912.

Schaberg, P.; Colson, J.; Higgins, S.; Thielen, D.; Anspach, B.; Brauer, J. (2004). Thermal decomposition (pyrolysis) of urea in an open reaction vessel. *Thermochem Acta* 424:131–142.

Schaberg, P. (2005). Emissions Performance of GTL Diesel Fuel and Blends with Optimized Engine Calibrations. *SAE Technical Paper* 2005-01-2187.

Schwoerer, J.; Dodi, S.; Fox, M.; Huang, S.; Yang, Z. (2004). Internal EGR Systems for NO_x Emission Reduction in Heavy-Duty Diesel Engines. *SAE Technical Paper* 2004-03-08.

Schwoerer, J.; Kumar, K.; Ruggiero, B.; Swanbon, B. (2010). Lost-Motion VVA Systems for Enabling Next Generation Diesel Engine Efficiency and After-Treatment Optimization. *SAE Technical Paper* 2010-01-1189.

Seenikannan, P.; Periasamy, V.; Nagaraj, P. (2008). A Design Strategy for Volumetric Efficiency Improvement in a Multi-Cylinder Stationary Diesel Engine and Its Validity under Transient Engine Operation. *American Journal of Applied Sciences* 5(3): 189–196.

Sellnau, M.; Rask, E. (2003). Two-Step Variable Valve Actuation for Fuel Economy, Emissions, and Performance. Society of Automotive Engineers. *SAE Technical Paper* 2003-01-0029.

Sellnau, M.; Sinnamon, J.; Hoyer, K.; Husted, H. (2012). Full-Time Gasoline Direct-Injection Compression Ignition (GDCI) for High Efficiency and Low NO_x and PM. *SAE International Journal of Engines* 5:300–14.

Semião, V.; Andrade, P.; Carvalho, M. (1996). Spray characterization: numerical prediction of Sauter mean diameter and droplet size distribution. *Fuel* 75(15):1707–1714.

Shost, M.; Noetzel, J.; Wu, M.; Sugiarto, T.; Bordewyk, T.; Fulks, G.; Fisher, G. (2008). Monitoring, feedback and control of urea SCR dosing systems for NO_x reduction: utilizing an embedded model and ammonia sensing. *SAE Technical Paper* 2008-01-1325.

- Singh, D.; Subramanian, K.; Singal, S. (2015). Emissions and fuel consumption characteristics of a heavy duty diesel engine fueled with Hydroprocessed Renewable Diesel and Biodiesel. *Appl Energ* 155:440–446.
- Sluder, S.; Storey, J.; Lewis, S.; Lewis, L. (2005). Low temperature urea decomposition and SCR performance. SAE Technical Paper 2005-01-1858.
- Som, S.; Aggarwal, S.; El-Hannouny, E.; Longman, D. (2010). Investigation of Nozzle Flow and Cavitation Characteristics in a Diesel Injector. *J. Eng. Gas Turbines Power* 132(4).
- Sou, A.; Hosokawa, S.; Tomiyana, A. (2007). Effects of cavitation in a nozzle on liquid jet atomization. *International Journal of Heat and Mass Transfer* 50:3575-3582.
- Speight, J. G. (2011). *Biofuels Handbook*. Royal Society of Chemistry. ISBN: 978-1-84973-026-6.
- Srinivas, S.; Malik, R.; Mahajani, S. Fischer-Tropsch synthesis using bio-syngas and CO₂. (2006). *Advances in Energy Research*. Department of Chemical Engineering, Indian Institute of Technology.
- Teng, H.; McCandless, J.; Schneyer, J. (2002). Viscosity and Lubricity of (Liquid) Dimethyl Ether - An Alternative Fuel for Compression-Ignition Engines. SAE Technical Paper 2002-01-0862.
- Tilli, A.; Imperato, M.; Aakko-Saksa, P.; Larmi, M.; Sarjovaara, T.; Honkanen, M. (2010). High Cetane Number Paraffinic Diesel Fuels and Emission Reduction in Engine Combustion. CIMAC Congress. Bergen. Paper N:o. 26.
- Tsuneoyoshi, K.; Yamamoto, K. (2012). A study on the cell structure and the performances of wall-flow diesel particulate filter. *Energy* 48:492–499.
- Van Basshuysen, R.; Schäfer, F. (2004). *Internal Combustion Engine Handbook*. SAE International, ISBN 0-7680-1139-6.
- Van Gerpen, J.; Shanks, B.; Pruszko, R.; Clements, D.; Knothe, G. (2004). Biodiesel Production Technology: August 2002–January 2004. National Renewable Energy Laboratory, US Dep. of Energy.
- Vessia, Ø. (2005). Biofuels from lignocellulosic material - In the Norwegian context 2010 –Technology, Potential and Costs. Project report. Norwegian University of Science and Technology.
- Wang, T.; Baek, S.; Lee, J. (2008). Kinetic parameter estimation of a diesel oxidation catalyst under actual vehicle operating conditions. *Ind Eng Chem Res* 47:2528–2537.
- Warnatz, J.; Maas, U.; Dibble, R.W. (1999). *Combustion* (2nd edition). Springer, ISBN 3-540-65228-0.

Warnatz, J. (2006). Combustion Physical and Chemical Fundamentals, Modeling and Simulation, Experiments, Pollutant Formation (4th edition), Springer-Verlag, ISBN 3540259929.

Wattrus, M. (2013). Fuel property effects on oil dilution in diesel engines. SAE Int J Fuels Lubr 6(3):794–806.

Way, P.; Viswanathan, K.; Preethi, P.; Gilb, A.; Zambon, N.; Blaisdell, J. (2009). SCR performance optimization through advancements in aftertreatment packaging. SAE Technical Paper 2009-01-0633.

Wenzel, S. (2006). Modellierung der Ruß- und NO_x-emissionen des Dieselmotors. Ph.D. Thesis. Otto-von-Guericke-Universität Magdeburg.

Wiebenga, M.; Kim, C.; Schmiege, S.; Oh, S.; Brown, D.; Kim, D.; Lee, J.; Peden, C. (2012). Deactivation mechanisms of Pt/Pd-based diesel oxidation catalysts. Catal Today 184:197–204.

Woodward, D. (2009). Pounder's Marine Diesel Engines and Gas Turbines (9th Edition). Butterworth-Heinemann, ISBN 978-0-7506-8984-7.

Worldwide Fuel Charter Committee. (2009). Biodiesel Guidelines. WWFC.

Wu, J.; Liu, Z. (2003). Viscosity of Saturated Liquid Dimethyl Ether from (227 to 343). K. J. Chem. Eng. Data. 48:426.

Yamane, K.; Ueta, A.; Shimamoto, Y. (2001). Influence of physical and chemical properties of biodiesel fuels on injection, combustion and exhaust emission characteristics in a direct injection compression ignition engine. International Journal of Engine Research 2(4):249-261.

York, A.; Ahmadinejad, M.; Watling, T.; Walker, A.; Cox, J.; Gast, J.; Blakeman, P.; Allansson, R. (2007). Modeling of the catalyzed continuously regenerating diesel particulate filter (CCR-DPF) system: model development and passive regeneration studies. SAE Technical Paper 2007-01-0043.

Yu, B.; Kim, M. (2013). Modeling the selective catalytic reduction of NO_x by ammonia over a Vanadia-based catalyst from heavy duty diesel exhaust gases. Appl Therm Eng 50:152–158.

Yu, J.; Lee, J.; Bae, C. (2002). Dimethyl Ether (DME) Spray Characteristics Compared to Diesel in a Common-Rail Fuel Injection System. SAE Technical Paper 2002-01-2898.

Zhang, X.; Wang, H.; Zheng, Z.; Reitz, R.; Yao, M. (2016). Effects of late intake valve closing (LIVC) and rebreathing valve strategies on diesel engine performance and emissions at low loads. Applied Thermal Engineering 98:310–9.

Zheng, M.; Banerjee, S. (2009). Diesel oxidation catalyst and particulate filter modeling in active-flow configurations. Appl Therm Eng 29:3021–3035.

Zheng, M.; Reader, G.; Hawley, J. (2004). Diesel engine exhaust gas recirculation – a review on advanced and novel concept. *Energy Convers. Manage.* 45:883–900.

Zhu, L.; Cheung, C.; Zhang, W.; Fang, J.; Huang, Z. (2013). Effects of ethanol–biodiesel blends and diesel oxidation catalyst (DOC) on particulate and unregulated emissions. *Fuel* 113:690–696.

ISBN 978-952-60-8874-7 (printed)
ISBN 978-952-60-8875-4 (pdf)
ISSN 1799-4934 (printed)
ISSN 1799-4942 (pdf)

Aalto University
School of Engineering
Department of Mechanical Engineering
www.aalto.fi

**BUSINESS +
ECONOMY**

**ART +
DESIGN +
ARCHITECTURE**

**SCIENCE +
TECHNOLOGY**

CROSSOVER

**DOCTORAL
DISSERTATIONS**