On the Practice of Modeling Software Variability

Mikko Raatikainen

On the Practice of Modeling Software Variability

Mikko Raatikainen

A doctoral dissertation completed for the degree of Doctor of Science (Technology) to be defended, with the permission of the Aalto University School of Science, at a public examination held at the lecture hall T2 of the school on 8 February 2019 at 12.

**Aalto University
School of Science
Department of Computer Science**

Supervising professors

Prof. Dr. Marjo Kauppinen
Aalto University, Finland

Thesis advisors

Prof. Dr. Tomi Männistö
University of Helsinki, Finland

Preliminary examiners

Lect. Dr. Jaejoon Lee
Lancaster University, United Kingdom

Assoc. Prof. Dr. Eduardo Santana de Almeida
Federal University of Bahia, Brazil

Opponents

a. Univ.-Prof. Dr. Paul Grünbacher
Johannes Kepler University, Austria

Aalto University publication series **DOCTORAL DISSERTATIONS** 10/2019

© 2019 Mikko Raatikainen. Published under CC-BY 4.0 licence.

ISBN 978-952-60-8379-7 (printed)

ISBN 978-952-60-8380-3 (pdf)

ISSN 1799-4934 (printed)

ISSN 1799-4942 (pdf)

<http://urn.fi/URN:ISBN:978-952-60-8380-3>

Unigrafia Oy
Helsinki 2019

Finland

Author

Mikko Raatikainen

Name of the doctoral dissertation

On the Practice of Modeling Software Variability

Publisher School of Science

Unit Department of Computer Science

Series Aalto University publication series DOCTORAL DISSERTATIONS 10/2019

Field of research Software engineering

Manuscript submitted 11 September 2017

Date of the defence 8 February 2019

Permission to publish granted (date) 20 November 2018

Language English

☐ **Monograph**

☒ **Article dissertation**

☐ **Essay dissertation**

Abstract

A software product line has become an established software engineering approach to developing a set of products that vary from each other but share a common set of assets and adhere to a common software architecture. Variability is a means to design the differences between the products in a software product line. Variability is the ability of a software system or an artifact to be efficiently extended, changed, customized, or configured for use in a particular context. Variability has been studied in recent years and several variability models have been proposed. However, the use especially from industry has not been addressed extensively.

This thesis addresses the problem of what kinds of models to use to represent the variability in a software product line. As the overall research approach, we applied Design Science, in which variability models are interventions in a prescription. We applied the literature review and case study as the research methods.

We study literature about the existing variability models, as well as evidence about the use of these variability models. We provide descriptive accounts of variability models in three cases in industry. On the basis of literature and a case study, we describe a set of considerations to be taken into account when representing variability.

We identified tens of different variability models. These variability models cover the activities, artifacts and phases of software engineering. We represent that several kinds of existing variability models and in-house approaches have been provided with empirical evidence about use, but no model is clearly become an established practice. The considerations explicate design decisions to be considered when using a variability model to represent the variability of an SPL, emphasizing that the applications of a variability model depend on the specific context. These considerations can also be relevant to those who develop variability models to address the needs of practice.

Keywords Variability, modeling, software product line.

ISBN (printed) 978-952-60-8379-7

ISBN (pdf) 978-952-60-8380-3

ISSN (printed) 1799-4934

ISSN (pdf) 1799-4942

Location of publisher Helsinki

Location of printing Helsinki

Year 2019

Pages 158

urn <http://urn.fi/URN:ISBN:978-952-60-8380-3>

Tekijä

Mikko Raatikainen

Väitöskirjan nimi

Ohjelmistojen varioituvuusmallituksen käytäntö

Julkaisija Perustieteiden korkeakoulu**Yksikkö** Tietotekniikan laitos**Sarja** Aalto University publication series DOCTORAL DISSERTATIONS 10/2019**Tutkimusala** Ohjelmistotuotanto**Käsikirjoituksen pvm** 11.09.2017**Väitöspäivä** 08.02.2019**Julkaisuluvan myöntämispäivä** 20.11.2018**Kieli** Englanti☐ **Monografia**☒ **Artikkeliväitöskirja**☐ **Esseeväitöskirja****Tiivistelmä**

Ohjelmistotuoteperheet ovat vakiintunut ohjelmistotuotannon kehitystapa joukolle erilaisia tuotteille, joissa uudelleenkäytetään ohjelmistoja noudattaen samaa arkkitehtuuria. Varioituvuuden avulla saavutetaan tuoteperheen tuotteiden erovaisuudet. Varioituvuus on järjestelmän tai artifaktan ominaisuus tehokkaaseen laajentamiseen, muuttamiseen, kustomointiin tai konfigurointiin tiettyä tarvetta varten. Varioituvuutta on tutkittu viime aikoina ja erityisesti erilaisia varioituvuuden mallitustapoja on esitetty. Käytöstä erityisesti teollisuudessa näyttää kuitenkin olevan vähän tutkimustuloksia.

Tämän työn tutkimusongelma käsittelee millaisia mallitustapoja tulisi käyttää tuoteperheen varioituvuuden esittämiseen. Tutkimus noudattaa konstruktiivista tutkimusmetodologiaa. Tutkimusmenetelminä käytämme kirjallisuuskatsausta ja tapaustutkimusta. Tutkimme varioituvuuden mallitustapoja kirjallisuudessa sekä niiden raportoitua käyttöä. Kuvailimme myös varioituuden mallittamista kolmessa tuoteperheessä tapaustutkimuksissa. Varioituuden mallittamiseen esitämme joukon näkökohtia jotka tulisi huomioida kirjallisuuden ja tapaustutkimusten perusteella.

Identifioimme kymmeniä erilaisia varioituvuuden mallitustapoja. Nämä mallitustavat kattavat eri ohjelmistokehityksen eri vaiheet, tekemiset ja artifaktat. Useille mallitustavoille sekä itse kehitetyille mallitustavoille on myös osoitettu käyttöä ja näin ollen arvoa käytännölle, joskaan mikään tapa ei ole vakiintunut.

Näkökohdat puolestaan esittävät päätöksiä joita varioituvuutta mallittaessa täytyy tehdä, korostaen että varioituvuuden voi mallittaa monella tapaa riippuen tilanteesta ja kontekstista. Nämä näkökulmat ovat merkittäviä myös varioituvuus mallien tutkimukselle, jotta tutkimus pystyy vastaamaan käytännön tarpeisiin.

Avainsanat Varioituvuus, mallitus, ohjelmistotuoteperhe.**ISBN (painettu)** 978-952-60-8379-7**ISBN (pdf)** 978-952-60-8380-3**ISSN (painettu)** 1799-4934**ISSN (pdf)** 1799-4942**Julkaisupaikka** Helsinki**Painopaikka** Helsinki**Vuosi** 2019**Sivumäärä** 158**urn** <http://urn.fi/URN:ISBN:978-952-60-8380-3>

Contents

Contents	1
List of Publications	3
Author's Contribution	5
1. Introduction	7
1.1 Background	7
1.2 Motivation	10
1.3 Research Problem and Questions	11
1.4 Scope	12
1.5 Structure	13
2. Research Methodology	15
2.1 Research Approach: Design Science	15
2.1.1 Overview of Design Science Approach	15
2.1.2 Application of Design Science in this Thesis	17
2.2 Literature Reviews	19
2.2.1 Overview of Literature Review Method	19
2.2.2 Tertiary Study Design (Publication I)	19
2.2.3 Literature Study Design (Publication V)	20
2.3 Case studies	22
2.3.1 Overview of Case Study Method	22
2.3.2 SPL Case Study Design (Publications II and III)	22
2.3.3 Feature Model Case Study Design (Publication IV)	23
3. Results	25
3.1 RQ1: Existing Variability Models	25
3.2 RQ2: Variability Models Used	31
3.2.1 Variability Models Used in Literature	31

3.2.2	Variability Models Used in Case Studies	33
3.3	RQ3: Considerations in Variability Models	36
4.	Discussion	39
4.1	Answer to RQ1: Existing Variability Models	39
4.2	Answer to RQ2: Variability Models Used	41
4.3	Answer to RQ3: Variability Model Considerations	42
4.4	Validity and Reliability	44
5.	Conclusions	47
	References	49
	Errata	57
	Publications	59

List of Publications

This thesis consists of an overview and of the following publications which are referred to in the text by their Roman numerals.

I Mikko Raatikainen, Juha Tiihonen, Tomi Männistö. Software Product Lines and Variability Modeling: A Tertiary Study. *The Journal of Systems and Software*, Volume 149, p. 485-510, 2019.

II Mikko Raatikainen, Timo Soininen, Tomi Männistö, and Antti Mattila. Characterizing Configurable Software Product Families and their Derivation. *Software Process Improvement and Practice*, Volume 10, Issue 1, p. 41-60, 2005.

III Varvana Myllärniemi, Mikko Raatikainen, Tomi Männistö. Inter-organisational Approach in Rapid Software Product Family Development — A Case Study. In *International Conference on Software Reuse*, Italy, p. 73-86, 2006.

IV Juha Savolainen, Mikko Raatikainen, Tomi Männistö. Eight Practical Considerations in Applying Feature Modeling for Product Lines. In *International Conference on Software Reuse*, South Korea, p. 192-206, 2011.

V Juha Tiihonen, Mikko Raatikainen, Varvana Myllärniemi, Tomi Männistö. Carrying Ideas from Knowledge-based Configuration to Software Product Lines. In *International Conference on Software Reuse*, Cyprus, p. 55-62, 2016.

Author's Contribution

Publication I: “Software Product Lines and Variability Modeling: A Tertiary Study”

Raatikainen was primarily responsible for conducting the study, including the problem statement, the study design and carrying out the study, to the reporting. The second author participated actively in the analysis and reporting of the study. The third author had a general role of supporting and commenting throughout the study.

Publication II: “Characterizing Configurable Software Product Families and their Derivation”

Raatikainen had the main responsibility for conducting the study, including study design, data collection, analysis, synthesis and reporting. The second and third author participated actively in data collection, analysis and reporting. The last author assisted in the data collection.

Publication III: “Inter-organisational Approach in Rapid Software Product Family Development — A Case Study”

Raatikainen had the primary responsibility in designing the study and he focused on the software product line. The first author focused especially on quality attribute variability. Data collection, analysis and writing was carried out together by these two first authors. The third author had a role of supporting and commenting throughout the study.

Publication IV: “Eight Practical Considerations in Applying Feature Modeling for Product Lines”

Raatikainen had a leading role in analyzing, synthesizing and reporting the results. The data is based on the long experience and industrial cases of the first author who also contributed to reporting. The third author had a role of reviewing and commenting throughout the study.

Publication V: “Carrying Ideas from Knowledge-based Configuration to Software Product Lines”

Raatikainen had the main responsibility for software variability modeling, and applying the ideas from knowledge-based configuration to software product lines. The first author had the main responsibility for knowledge-based configuration. The first author and Raatikainen had together the responsibility of writing the paper. The other authors provided comments.

1. Introduction

1.1 Background

Many software systems face a diversity of needs. The context of use, such as other systems to be integrated or to interact with, constitutes different kinds of environments. Different users have or prefer different needs for the software. Software, especially embedded software, can be running on hardware with different capabilities that require different kinds of software. Despite the differences, there is also a lot in common between different products.

To enable the commonality and diversity in software to be addressed, software product lines (SPLs), which are also synonymously called software product families, have become an established software engineering practice, as evidenced by several textbooks [86, 12, 17, 63]. The products of an SPL can be any kinds of software systems, such as embedded systems, software products, or digital services. Although what an SPL is not unambiguous, a definition of an SPL is as follows: "a set of software-intensive systems that share a common, managed set of features satisfying the specific needs of a particular market segment or mission and that are developed from a common set of core assets in a prescribed way" [17]. Another definition of an SPL is the following: "A software product line consists of a product line architecture, a set of reusable components and a set of products derived from the shared assets" [12].

In the light of these definitions of an SPL, the following essential characteristics are extracted for the purposes of this thesis. First, an SPL defines a general structure referred to as an SPL architecture that the products of an SPL adhere to. Second, within an SPL architecture, the products reuse the shared assets, such as software components or other

elements of software. The shared assets are prepared for the products of an SPL in a phase called domain engineering, while the products are realized during the application engineering phase. Third, the products are developed in a prescribed way in the application engineering phase that includes adhering to the SPL architecture and reusing the shared assets for the products. In practice, the shared assets can be, e.g., developed beforehand, or first for a specific product and then generalized for reuse in different products. Thus, the phases are conceptually different but not necessarily temporally defined. Fourth, the SPL architecture and shared assets of an SPL are targeted to a particular market segment or mission for similar products. That is, an SPL is neither about the development of a single system nor about general-purpose reuse.

As a set of products defines an SPL, the similarities within and differences between these products are essential to the characterization of an SPL and are typically associated with commonality and variability, respectively. Commonalities are often realized through reuse, so that the same artifact is used for different products in the same manner.

Variability is defined as "the ability of a software system or an artifact to be efficiently extended, changed, customized or configured for use in a particular context" [77]. The different products of an SPL are manifestations of variability, where variability is taken advantage of because of the differences it offers. The activity of realizing differences, as a part of application engineering, is referred as resolving variability, resulting in different variants. In the light of this definition, we emphasize two essential characteristics of variability. First, variability is purposefully designed ability in a system rather than changes taking place over years, such as those resulting from maintenance or evolution to introduce new features. Second, variability is related to the use of software, meaning that something essential changes that affects to the behavior of the software.

To address the phenomenon of variability, software variability management is a key activity within SPL engineering, thus forming a key characteristic distinguishing it from the development of a single system. Here, variability management means general activity to cover all activities or concerns of variability, from the identification of variability, through realization, to maintenance. Variability management is synonymous, e.g., with variability handling [24].

Within the broader context of variability management, a variability model

Figure 1.1. An example of a feature model based on the extensions of a feature model [8] in [56].

is a means and an artifact to represent the variability of software to the stakeholders. The stakeholders include internal stakeholders, such as software developers who develop the software and variability therein, managers who make the strategic decision about the software that is developed, and sales people who deal with the interface with customers, as well as external stakeholders who make the decision to buy the software and users who use the software but can also be in the role of a customer. Variability models, as understood in this thesis, cover any kinds of representations about variability. Broadly, variability models range from informal sketches or informal natural language specifications to various kinds of models using textual or graphical notations based on rigorously defined syntax and semantics. We use the term variability model to refer to any model that contains unresolved variability, thus being developed during the domain engineering phase and forming an input to the application engineering phase, when variability is resolved.

Most probably, the best known example of a variability model is a feature model [44, 45], which emerged in the 1990s, although much of the research focuses on the emergence of SPL research in the 2000s [8, 39]. An example of a simple feature model of a mobile phone is shown in Figure 1.1. A feature model conveys many of the key concepts of variability

modeling. A feature in a feature model can be seen as a characteristic of a system that is visible to the end user [44] or, more generally, a system property that is relevant to some stakeholder and is used to capture commonalities or discriminate among product variants [20]. A feature model is typically represented as a graphical diagram arranged as a set of features and relations between a parent (or compound) feature and its child features (or subfeatures) and cross-hierarchy constraints [8]. The relationships represent variabilities such as optionality, meaning that a feature can be either selected or left out, or alternatives, meaning that one of the alternatives needs to be selected.

1.2 Motivation

The years of research and practice have elevated variability modeling into a central problem area, especially within the SPL research community [15, 24]. For example, several different variability model concepts and constructs, in addition to many extensions (cf. [11]) to the aforementioned feature model, have been proposed [15]. Feature models, as an example, have been provided with extensions and formalizations already more than a decade ago [4, 9, 20, 68] and no major or fundamental changes or deficiencies have been proposed to the concepts more recently.

However, empirical research results especially from practical, industrial settings are called for variability models in particular [39, 15, 24], but also in general for SPLs [3, 52, 51, 54]. In addition, there is a call for summarizing research [3, 16]. Specifically, even though there is a lot of research about feature models [37], feature models have been provided with only a few industrial studies about use and feature model adoption is widely evidenced only in research community without actual practical or industrial applications [15, 39].

Consequently, variability models as technology [70] have matured to a phase where the focus should not be only on the variability constructs or basic research, but summaries, and the measures and characteristics of practical use, including its utility and evidence, are topical issues. Therefore, this thesis focuses on the practical use of variability models, as stated in the research problem and questions below.

1.3 Research Problem and Questions

The overall research problem of this thesis is stated as follows:

What kinds of models to use to represent variability in an SPL?

The research problem is divided into the following research questions:

- RQ1. What variability models exist?
- RQ2. What variability models are used?
- RQ3. What considerations affect variability models use?

The first research questions forms the basis of this thesis by surveying the field of variability model research. It applies a systematic literature study (Publication I). The second research question focuses on the reported empirical evidence of industrial use of variability models, rather than on research proposals. The systematic literature study Publication I and empirical experiences from case studies (Publications II and III) address the second research question. The third research question identifies the considerations affecting the use of variability models without focusing specifically any variability model per se. The third research question addresses the considerations to be taken into account in variability models by combining experience from the case study of software variability modeling (Publication IV) and the literature study of Knowledge-based configuration (Publication V). The research questions and publications addressing the research questions that are included are summarized in Table 1.1. Table 1.2 explicates the key contributions of each individual publication.

Table 1.1. What publications address each research question.

Publication	I	II	III	IV	V
RQ1	X	-	-	-	-
RQ2	X	X	X	-	-
RQ3	-	-	-	X	X

Table 1.2. The contribution of each publication to the thesis.

Publication	Contribution
Publication I	Identification of existing variability models from the literature and analysis of their evidenced use.
Publication II	Investigation and description of variability management in two companies.
Publication III	Investigation and description of variability management in a company.
Publication IV	Identification and specification of considerations in feature modeling.
Publication V	Adoption and specification of ideas from knowledge-based configuration to software variability modeling.

1.4 Scope

This thesis focuses on an SPL, which, adhering to the aforementioned definition, means a set of products that follow the same software architecture and reuse shared assets. Variability as a phenomenon is not limited to SPL but similar phenomena exist in several related domains, which, however, are not explicitly within the scope of this thesis. For example, service-oriented architectures or service-oriented computing, as well as component-based systems, often rely on composing different kinds of elements to form a larger entity such as a system and variability is evidenced by different kinds of compositions, or self-managing (self-*) or autonomous systems try to adapt themselves.

This thesis may often seem to focus on feature models. A feature model, however, is treated primarily as a widely known example of a variability model, as already elaborated in Section 1.1. In more general terms, we treat a variability model as an abstraction of software for the purpose of representing variability. Therefore, implementation or code-level techniques are not considered as variability models. That is, general-purpose programming languages such as java or C++, including extensions, are beyond the scope of the thesis. Roughly, if the constructs of a model focus on realizing algorithmic concepts, we do not consider it a variability model. However, model-driven techniques, for example, are, in contrast, considered variability models because they usually represent domain concepts, even though they can be automatically generated to executable software with the help of a generator that adds algorithmic concepts.

1.5 Structure

The rest of this thesis is structured as follows. Chapter 2 describes the research methodology in terms of the research approach, methods, and techniques. Chapter 3 summarizes the results from the publications that are included in relation to the research questions. Chapter 4 discusses the results by answering the research questions, provides a comparison with the related work, and elaborates validity and reliability. Chapter 5 draws conclusions and points out directions for future work.

2. Research Methodology

We divide the research methodology applied in this thesis into the research approach, method, and technique [41, 6, 29, 42]. In this chapter, we first present Design Science as the general research approach or intention covering the nature of the results and the criteria for results, as well as the application of Design Science in this thesis. Then the remaining sections summarize the research methods and techniques implemented in the research that was conducted and applied in the realm of Design Science. This structure is summarized in Figure 2.1.

Figure 2.1. A summary of the research methodology. 'P' refers to the publications included and the numbers in parentheses indicate the sections of this chapter.

2.1 Research Approach: Design Science

We first give an overview of a design science as research approach and then describe how the design science approach is applied in this thesis.

2.1.1 Overview of Design Science Approach

Design Science is a class of formative research where the results are innovated or brought into a specific new environment so that the results have value in the environment [29]. Thus, formative research, and Design Science, is differentiated in a taxonomy of research approaches from *formal* approaches that can be similarly innovated but are empirically void, being mainly assessed for their internal consistency [80, 43], and

research which stresses reality, referred to here as *descriptive science*, focusing on theories such as natural laws or social theories [80, 33], often being universal and for the purpose of gaining general understanding or enlightenment. Similar taxonomies exist at the level of theories [32] or classes of sciences [57]. The characterizations of software engineering research have identified formative research as a popular class of research [1, 26, 78, 28, 71, 88, 75], but it is provided with few guidelines. Design science and, e.g., its alternative Action Research are only shortly introduced in software engineering research [72]. Therefore, we adopt Design Science as covered in information systems and management research.

What is central to Design Science is the intention to obtain actionable and goal-oriented results [81, 32], which are referred to here as prescriptions. Such a prescription is also called as a design theory [83, 84, 33], a technological rule [80], a technological norm [57, 46], or even an artifact embodying a prescription [38]. More specifically, a prescription has the following underlying structure: "*if you want B in A, do X*" [80, 57, 46, 14]. In this structure, "A" describes the initial situation, "B" describes the desired goal as a conditional antecedent rather than as a norm, and "do X" is an applicable intervention. An example of prescription could be: "If you want to model variability of an information system in which the requirements are well known, use a textual feature model in order to make possible to carry out analyses". Consequently, a prescription has an underlying causal-like structure in which an intervention results in a goal. Rather than being about a naturally occurring phenomenon in which a cause has an effect, an intervention contains an artifact that is artificial for the purpose and consciously applicable to achieve a desired goal, as implied by "do X". Therefore, the design and application of an artifact in an intervention need to be specified. Typically, an intervention is a heuristic taking the form of "*something like X will help*" [80, 33, 14] or that is otherwise mutable, such as an exemplar [33].

Because of the artificial and consciously applicable characteristics, the achievement of the goal by the intervention, as well as the general criteria of science, such as truthlikeness, are insufficient in themselves in Design Science. For example, overly complexly or even hypothetically applicable interventions can be innovated that are not practically applicable. Therefore, Design Science brings in additional criteria that we refer to in short as utility [53, 38]. Broadly, utility means value to stakeholders' in

the achievement of the goal [57, 87], although more specifically, utility is a complex multi-faceted concept lacking simple measures [82, 2, 25]. Because of stakeholder-dependency, the justification of utility needs to involve empirical evidence [81], whereas non-empirical justification can only result in conclusively convincing internal validity. However, apart from restricting to involve empirical evidence, the research methods and techniques do not necessarily differ between design science and other kinds of research [59, 23, 30, 57].

2.1.2 Application of Design Science in this Thesis

The research problem of this thesis is stated in a form that seeks to find the kinds of models to represent variability. The research objective on the basis of the research problem can be expressed in a form that adheres to Design Science as the research approach:

If you want to represent variability in the context of an SPL, apply models like Xs.

The research problem treats the application of variability models to represent variability as interventions in the realm of Design Science. In so doing, Design Science provides the lenses of analysis for the structure and criteria. With respect to the structure of an intervention, on the one hand, the research problem is stated in a form that seeks to find several different kinds of variability models as possible interventions, rather than one specific variability model. On the other hand, the possible variability models in interventions are not considered as strict guidelines but are characterized by the heuristic nature of Design Science. With respect to criteria, variability models alone are insufficient but Design Science brings in the criterion of utility, which needs to be addressed. More specifically, the research problem is addressed by three more specific research questions, as detailed below and summarized in Table 2.1.

RQ1 studies possible variability models as interventions. We restrict the study to variability models proposed in the scientific literature, considering the application of each variability model as an intervention rather than innovating a new variability model. By treating the application of variability models as interventions, however, we do not insist that the studies reported in the literature adhere to Design Science. For example, the reported variability models may represent only constructs developed as solution proposals or constructs observed from practice. In fact, it is

Table 2.1. The research questions for the interventions addressed by the research methods of the publications included referred to by their Roman numerals.

The research questions for the intervention	The research methods and publications
Possible interventions (RQ1)	A survey of variability models in the literature by a tertiary study (I)
Utility of interventions (RQ2)	The use variability models as reported in the literature by a tertiary study (I) and in case studies (II and III)
The heuristic nature of interventions (RQ3)	Considerations in variability modeling by a case study (IV) and literature study (V)

even presumed that the variability models reported in the scientific literature satisfy first and foremost the general scientific criteria, such as variability can be successfully modeled using the proposed variability models, unless the results report otherwise, such as the impossibility of applying a variability model. As the research method, we apply a literature review (Publication I).

RQ2 also focuses on variability models as interventions but takes utility into account by restricting itself to those variability models that have evidence of utility. The measure of utility is, rudimentarily, evidence about industrial use. That is, the application of a specific variability model in an industrial organization manifests value. We apply a literature review (Publication I) and case studies (Publications II and III) to analyze the use of variability models. The synthesis of these studies was integrative following narrative synthesis method [18].

RQ3 addresses the heuristic nature of variability models in an intervention of Design Science. Rather than variability models being considered only as constructs to be applied as an intervention, variability modeling as an intervention is considered more holistically and generally in the context of RQ3. The research question addresses the considerations related to variability models that are not necessarily specific to one variability model but are more general considerations affecting a practical application. The research methods applied are a literature review (Publication V) and a case study (Publication IV). The synthesis of these studies was integrative following narrative synthesis method [18].

Figure 2.2. An illustration of different kinds of studies and their relationships.

2.2 Literature Reviews

We first give an overview of a literature review as a research method and then describe how the literature review method is applied in this thesis.

2.2.1 Overview of Literature Review Method

The general objective of a literature review is to constructively inform readers about the accumulated knowledge on a topic by covering the relevant literature systematically in a concept-centric manner [85]. In particular, systematic reviews (SR) have emerged as specific research methods for a literature review to summarize and synthesize primary studies following a predefined, systematic, and reliable research method [21]. The common forms of the systematic reviews in software engineering are a *systematic literature review (SLR)* [48] and a *systematic mapping study (Map)* [61] as secondary studies, and *tertiary studies* [48] (Figure 2.2). Both SLRs and Maps review primary studies that are research other than literature reviews. Tertiary studies are SRs that review existing secondary studies [48]. That is, a tertiary study is a study that treats other secondary studies, or typically only SLRs and Maps, as primary studies and is carried out by adhering to similar systematic practices to other SRs.

2.2.2 Tertiary Study Design (Publication I)

The literature review about SPL and variability in Publication I was carried out as a tertiary study. We applied a tertiary study because the fields of SPLs and variability have been subject to such extensive research that we considered it important to be characterized more broadly than what is possible with an SLR or a Map. A tertiary study provides a means to

carry out analysis for a significantly larger number of primary studies. The study includes twofold aims contributing to this thesis. The first aim is to gain an overview of different kinds of variability models (RQ1). The second aim is to find out what kinds of empirical evidence support the variability models (RQ2). We developed a protocol adhering to SR guidelines [48], as summarized below.

We include in the tertiary study SRs appearing in scientific publications. The search was carried out in two essential phases (Figure 2.3). We first applied a snowballing strategy [89] to find tertiary studies in the field of software engineering (Phase 1a) that worked as the seed for a snowballing search for SPL and variability SRs (Phase 1b). At the end of Phase 1, we applied a quasi-gold standard [92] that indicated satisfactory search results. However, we piloted additional searches and found several new SRs that led us to carry out extensive database and manual searches (Phase 2).

The data were extracted following a protocol that followed the principles used in other tertiary studies. We added specific data extraction fields for quality and evidence analysis, as well as for variability models. The analysis, complemented with cross-analysis over the research questions, allowed us to answer the research questions.

2.2.3 Literature Study Design (Publication V)

On the basis of literature, Publication V carries out a conceptual comparison of two different but seemingly disconnected fields of research, namely knowledge-based configuration and software variability management. The latter focuses especially on feature modeling. Knowledge-based configuration is a field of research that is applied, e.g., in mechanical products. Knowledge-based configuration was selected for comparison because of the similarity of the problems to be solved and the personal background knowledge and experiences of the authors. The objective was to reflect the principles of knowledge-based configuration against software variability principles, thus contributing considerations for use in software variability models, i.e., RQ3 in this thesis.

For the knowledge-based configuration literature, a search for titles and abstracts through all the special issues on configuration published in journals and the proceedings of configuration workshops since 2000 was performed to augment the already-known relevant Knowledge-based Configuration literature (cf. [79]). For the software variability modeling litera-

Figure 2.3. The search process in the tertiary study (Publication I).

ture, we selected publications that we considered seminal or widely referenced, and that we considered represent archetypical characteristics of software variability modeling, especially feature modeling. In the analysis, four concepts that contribute to the considerations in variability models were selected for more detailed comparison.

2.3 Case studies

We first give an overview of a case study as a research method and then describe how the case study method is applied in this thesis.

2.3.1 Overview of Case Study Method

The case study method has emerged within software engineering research as an increasingly popular and legitimated empirical research method, which means studying a contemporary phenomenon in its natural context [91, 66]. A case study can be divided into the phases of design and planning, data collection, and analysis [66]. The design phase defines the unit of analysis as the subject of the study that is selected purposefully rather than by sampling. The aim is to find a case that would reveal something that advances understanding about a phenomenon. The data collection phase means capturing data about a phenomenon, often relying on triangulation of, e.g., data sources and researchers so that rich data about a phenomenon are captured holistically. Analysis forms the conclusions from the rich, often at least partly qualitative, case data through several steps of, e.g., abstraction and relation.

2.3.2 SPL Case Study Design (Publications II and III)

The studies in Publications II and III were carried out as a qualitative descriptive case study in Finland. The objective of the studies was to characterize the state of practice of the SPLs in order to extract practices to advance understanding of how to develop SPLs, thus contributing to RQ2. The case studies of Case A and B were conducted first and the Fathammer case study was carried out later but all followed a similar study design [64].

Cases A and B were selected because they seemed to be potential companies that have an SPL. Fathammer was chosen because of its unique characteristics, i.e., quality attribute variability. The focus in each case

was on the SPL of the company.

The data collection was based on semi-structured interviews, the analysis of the documentation received in each case, and a validation in each company. As preparation for the interviews, we developed a set of mostly open-ended interview questions. The questions were first tested and developed further in focus group settings and in a pilot interview. In Company A and Fathammer, the interviews were carried out in one session, whereas in Company B, they were in two sessions. The total length of each interview was about half a day. At least two researchers acted as interviewers in each interviews.

The analysis was primarily based on the written transcripts of the interview. The analysis was carried out using the ATLAS.ti analysis software, in which transcripts are treated as primary documents for the analysis. The additional information was taken into account as additional primary documents or by augmenting memos. The analysis applied the principles of data coding in qualitative research [76]: on the basis of previous knowledge, a preliminary conceptual framework was developed that was then refined on the basis of, and enriched by, the data.

2.3.3 Feature Model Case Study Design (Publication IV)

Publication IV is about considerations in the practical application of feature modeling in practice. Therefore, the publication contributes to RQ3. The considerations are based on firsthand experience and observation of feature and variability modeling in different projects in several different companies by a researcher (the first author of Publication IV). In different projects, different approaches to feature modeling had been tried out and the study provides general observations rather than specific accounts. The experiences are accompanied by and reflected in experiences of more basic research about variability modeling concepts. Thus, we did not design or carry out data collection in a pre-defined manner but merely relied on experiences. The experiences were captured and analyzed by collaboratively reflecting on them, and analyzing and synthesizing them into eight considerations.

3. Results

In this chapter, we summarize the results in the publications that are included for each research question.

3.1 RQ1: Existing Variability Models

We identified variability models from 30 SRs covering 1025 primary studies out of the total of 59 SRs covering 2541 primary studies in the tertiary study (Publication I). These variability models found from the literature are listed in Table 3.1, and Tables 3.2 and 3.3 present additional and summarizing data.

In Table 3.1, the 'Variability Model' column summarizes the found variability models and the '#' column specifies how many primary studies report each variability model. The variability models are listed as presented by SRs with only minor modifications such as changes of wording. However, not all the variability models are presented clearly in SRs. For example, 'Formal' provides few details of the actual model, and 'UML' does not always differentiate which UML diagrams are covered. In addition, we omitted minor differences, such as different dialects, notations, or versions of feature modeling, such as in the case between FODA [44], FORM [45] and cardinality-based feature models [20]. 'Other' covers variability models that are not described in a clear enough manner for the specific variability model to be capable of being extracted (13 primary studies), or an SR itself lists some variability models and considers the remaining ones as *other models* without further details (40 primary studies). In addition, 'Other than features' is differentiated and is based directly on the SRs. For example, one SR [50] divides variability models into feature models (45 primary studies) and other models (22 primary studies) but it is only noted without further details that UML, architecture

Table 3.1. The variability models (Publication I).

Variability model	#	Variability model	#
Activity diagram	3	Natural language	31
ADL	3	None	6
Architecture model	23	Not specified	2
Architecture view for decisions (no details)	1	Ontology based techniques	6
Aspects-orientation	2	Orthogonal variability management	4
ATAM / Saam	5	Other	53
Attributes of components	4	Other than features	39
Attributes of features	3	OVM	13
Change scenarios	2	Profiles, e.g., tables	4
Classification of requirement sentences	3	Rules, conditions	15
Component model	5	Scenario	15
Context modeling	2	Sequence diagram	4
Covamof	2	Service models	5
CVL	1	Sets of constraints	4
Decision model	12	Source code based	11
Domain-specific language	11	Source code reorganization for variability	14
DSL	5	Structure such as component model	7
Feature mapping to elements	18	Structured natural language sentences	2
Feature model	466	Textual	19
Formal	55	Tree	5
Goal-oriented model	8	UML	59
Goals and scenarios	1	Unspecified	15
Independent of specific modeling	2	Use case	35
Koala model	2	Variability model about context combined with a feature model	1
MDE	5	Variant labels, annotations	7
Metamodels	1	X-Frames	4

models, and CVL are salient among the other models.

In Table 3.2, we present a grouping of the variability models into 14 groups. The groups emerged from the variability models by first grouping similar variability models. For example, different kinds of feature-based models were all grouped under 'FM'. Similarly, we formed generalized groups, as in the case of the 'Orthogonal' group, to which we assigned different kinds of orthogonal models, such as CVL [36] and COVAMOF [74], in addition to Orthogonal Variability Model (OVM) as presented by Pohl *et al.* [63]. We also looked for variability models that appear in several SRs and that are popular enough to represent a group of their own. For example, despite the fact that use cases can be considered a part of UML, 'Use case' formed a group of its own, while other UML-based models were grouped under 'UML'. The 'Other' group consists of the remaining isolated and unique variability models, which did not appear in more than two SRs, and models for which enough details are not given. Finally, we were looking for models, but some SRs included also source code-level techniques, such as aspects, that constitute the 'SRC' (source code) group. The 'Unspecified' group means that it remained unclear whether variability is modeled at all. These last two groups are included mainly for the sake of completeness, as the SRs originally reported them.

In addition to the variability model groups, Table 3.2 shows a short description (the 'Description' column) for each group, the number of SRs ('SRs') out of the 30 SRs reporting a variability model in which a group appears, the average support level ('Avg%'), and the number of primary studies in each a group ('#'). The support level means the percentage of primary studies in an SR that report a variability model group. The average support level is calculated as an average of those support levels of SRs that report a variability model group, i.e., are not zero.

The variability model groups in Table 3.2 can be divided into two classes. First, three groups ('FM', 'DM' and 'Orthogonal') represent dedicated variability models that are independent and propose constructs specific to variability. The 'FM' group relies on features as the main concepts and focuses primarily on the features that are relevant in the context of variability. The 'DM' group is based on models of decisions that need to be made for resolving variability. The 'Orthogonal' group provides the constructs for a dedicated variability model, e.g., by using variability points, but the variability model is not autonomous as it is always linked to the existing, so-called base models of software, such as UML diagrams. How-

Table 3.2. The groups of variability models and their description, the number of SRs reporting the group ('SRs'), the average support level percentage for the group ('%'), and the number of primary studies ('#') (Publication I).

Group	Description	SRs	Avg%	#
<i>Dedicated variability models:</i>				
FM	Feature diagrams or trees, and other feature-based models.	26	40%	488
Orthogonal	Orthogonal variability models.	9	6%	20
DM	Decision models.	5	10%	12
<i>Extensions and adaptations:</i>				
Other	Models that only a few primary studies apply in an SR and do not appear in several other SRs, or the details of the model are not given.	14	22%	156
UML	Generally, any UML diagram other than use case, including adaptations such as stereotypes.	11	12%	66
NL	Natural language, structured natural language.	8	19%	55
SA	Software architecture view-based models and component models other than UML and MDE.	8	12%	45
Formal	Formal approaches. Further details are typically not given.	7	19%	55
MDE	Model-driven engineering including domain specific languages (DSL).	7	12%	21
SRC	Source code-level techniques	6	14%	27
Unspecified	Variability model is not specified or applied.	6	15%	23
Use case	Use cases are differentiated as a group of their own from UML.	4	39%	35
Scenario	Scenario-based models	3	17%	22

Table 3.3. Variability models for different topics: The topics, the number of SRs that report variability models/the total number of SRs covering the topic, and the number of primary studies that report variability models (based on data in Publication I).

Topic	SRs	#
Requirements engineering	3 / 6	81
Design	3 / 6	49
Testing	4 / 11	129
Variability management	7 / 12	385
Quality attributes	4 / 6	170
Management	4 / 10	116
Specific SPLs	8 / 11	199
Research methods	1 / 4	97

ever, orthogonal variability models are ignorant about the base model, so any software model can be a base model. In addition, other groups, such as the 'Other' and 'Formal' groups may contain a few unique dedicated variability models. Second, the rest of the groups rely on the existing models of software that are adapted or extended with variability information. For example, variability stereotypes are specified for UML (see, e.g., [31]), or variability-specific structured natural language is used for textual requirements or in use cases [67].

In Table 3.3, we present topic categories (the 'Topic' column) in order to analyze the context of variability models in greater depth. The topic categories were formed in a bottom-up manner by grouping similar SRs and assigning each to one or more categories. First, the categories applied loosely follow the common software engineering categorization as defined, e.g., in SWEBOK [13], being representative over the life-cycle phases and activities of software development. Second, the remaining SRs were analyzed to add additional common topic categories. Table 3.3 also shows how many SRs for each topic cover variability models of the SRs addressing the topic (the 'SRs' column), as well as how many primary studies report a variability model for each topic category (the '#' column).

The results in the literature above outlined show that there is a large number of different kinds of variability models: we identified 51 unique variability models, excluding source code-based techniques for managing variability. The large variety is further evidenced by the fact that the 'Other' group is the second most popular group, appearing in 14 SRs and having the second largest average support level of, 22%, among the SRs,

and appears in 156 primary studies (Table 3.2). Only the goal-oriented model appears more than once in the 'Other' group, although some variability models in the group are not described in enough detail to be assessed in more detail. In fact, many of the models have only few supporting primary studies.

However, a feature model is clearly the most popular variability model. A feature model stands out among different variability models (Table 3.1) by having 466 supporting primary studies, while the numbers of supporting primary studies in the next largest groups, 'Other' and 'UML', are 156 and 66, respectively. Even among the different groups, the 'FM' group is mentioned in most (26/30) of the SRs (Table 3.2). Even within SRs, the 'FM' group is dominant because the support level is, on average, 40%. Four SRs study only a feature model meaning that the support level is 100%, increasing the average support level, but excluding these four SRs still results in an average support level of 29%. Although these numbers most probably include duplicate primary studies as a result of the nature a tertiary study, the 'FM' group is clearly the most popular.

In addition, UML stands out as another quite popular variability model in its own right and as a group, especially if use cases are considered as a part of UML. Although UML consists of several different diagrams, such as class and sequence diagrams, the 'UML' group is still quite strictly defined in comparison to any group other than the 'FM' group. In fact, the remaining popular groups — such as natural language and formal models without further details — are relatively general groups rather than specific models.

Apart from the 'FM' group, the dedicated variability models are not especially popular. Although the 'Orthogonal' group is addressed in 11 SRs, the average support level is low (10%). The 'DM' group is popular in early SRs but has been addressed rarely and by only few primary studies in more recent SRs, resulting in an average support level of 6% and 12 primary studies in total.

There are eight groups of extensions and adaptations and most of these groups are addressed by several SRs, and, apart from the 'Use case' group, the support level of these groups is, on average, 10-20%, with quite similar standard deviations (cf. Table 3.2). Consequently, these groups appear quite widely, even though their support level does not indicate them as being especially popular.

With respect to the context (Table 3.3), the extracted variability mod-

els cover the different topics within SPL and variability relatively extensively. Furthermore, an analysis of the support levels of variability models within each topic roughly follow the general averages in Table 3.3 and as discussed above. The 'FM' group is equally dominant for all topics as it is in general. However, there are some natural exceptions to the averages because a topic-specific model is adapted or extended to cover variability. That is, the 'SA', 'Formal', 'MDE' and 'SRC' groups, mainly consisting of realization-level artifacts, are not present in requirements engineering SRs, and the 'Use case' group is restricted to the topics of requirements engineering and testing, with a relatively high support level.

3.2 RQ2: Variability Models Used

In the following, we first summarize the findings of the tertiary study (Publication I), followed by descriptive accounts and a summary of the case studies (Publications II and III).

3.2.1 Variability Models Used in Literature

Out of the 59 SRs in the tertiary study, the variability models were extracted from 30 SRs (Section 3.1). However, the evidence for variability models in primary studies can only be extracted from nine SRs out of these 30 SRs. In terms of the primary studies, evidence was traced to 224 primary studies out of the 1025 primary studies reporting a variability model.

The evidence for different variability model groups (Publication I) is presented in Table 3.4 in terms of *evidence levels* [47, 3] differentiating between six levels of evidence. The evidence in the SRs is analyzed and presented differently, but commensurably enough to allow a mapping to the evidence levels for better comparison. The levels from the weakest (L1) to the strongest (L6) are: *L1 no evidence*; *L2 demonstration, toy example*; *L3 expert opinions, observations*; *L4 academic studies*; *L5 industrial studies*; and *L6 industrial evidence presented*.

The results from the literature show that variability models in SRs have only isolated primary studies providing empirical evidence from actual industrial use (L6). The greatest amount of evidence on the actual use of variability models in industrial context is available for the 'FM' group. Hubaux *et al.* [39], who specifically focused on finding practical applica-

Table 3.4. The number of primary studies at each level of evidence for the variability model groups (see Publication I for a visualization).

Variability model group	L1	L2	L3	L4	L5	L6
FM	4	11	2	9	14	12
DM	0	0	0	0	3	0
Formal	7	10	1	7	1	1
MDE	0	2	0	0	0	0
NL	3	13	2	4	9	0
Other	3	10	5	5	5	2
Orthogonal	0	4	0	4	0	0
SA	4	8	0	2	1	1
Scenario	0	0	0	2	4	0
SRC	0	1	0	0	3	0
UML	2	7	1	4	1	0
Unspecified	0	0	0	0	0	1
Use case	2	14	1	5	6	1

tions of feature diagrams, provide 11 out of the 12 primary studies that are classified as L6. However, two of these primary studies are about unsuccessful applications and three remain hypothetical in the sense that a feature model could have been applied in the situation. L6 support is also available for the 'Formal', 'SA', 'Use case' and 'Unspecified' groups, each of which has only one supporting primary study, and the 'Other' group, which has two supporting primary studies. Five of these are reported in one SR ([3]) and the remaining two in another SR ([52]). Consequently, three SRs reported evidence on the L6 level.

The L5 evidence level is also based on industrial studies, but these industrial studies typically mean some kind of tests or informal experiments, such as feasibility tests in an almost realistic environment at best, rather than actual use. Nevertheless, there is more evidence for L5 than for L6, and only the 'MDE' and 'Orthogonal' groups lack evidence on the L5 and L6 levels. Industrial use can also be evidenced at the L3 level by 'Expert opinions' although it is unclear whether the experts are practitioners. Evidence on the L3 level is typically even more scarce than in the case of L6. 10 out of the 12 primary studies at the L3 level are from one SR [3], which also argues for additional industrial evidence indicating that expert opinions are not based on industrial use. The remaining two instances of evidence on the L3 level appear in another SR [52].

The remaining evidence levels do not include real industrial settings. A detailed analysis comparing L2 and L4 is not meaningful because the distinction between L2 and L4 is not unambiguous between different SRs. Several SRs have primary studies without evidence (L1) but, if the number of primary studies is considered, only the 'Formal' group has significantly high support level percentages. However, the 'Formal' group can be provided with, e.g., formal semantics or proofs that have little merit at the evidence levels.

3.2.2 Variability Models Used in Case Studies

In this section, we first summarize variability modeling as descriptive accounts in the case studies reported in Publications II and III. At the end, we summarize the cases.

Case A. (Publication II)

The products of the SPL in Case A are customer-specific factory automation software. The company differentiates three types of variability. First, the vertical variability concerns about a dozen main functions, i.e., large entities of significant functionality such as software running certain tasks in a factory automatically. Second, the variability for adapting the product and its operations in the customer environment is called the horizontal variability. The horizontal variability deals with more detailed issues than the vertical variability. Third, the tailoring typically involves introducing special new interfaces to exchange data with other systems in a way that cannot be accomplished by the predesigned horizontal variability and that requires specific software to be developed. The vertical and horizontal variability are managed by setting parameters in a database without changes to the source code by the engineers of the company using a quite simple configurator developed in-house that is a dedicated tool with a graphical user interface.

Vertical variability is modeled as a stack presentation consisting of a base and stacks of the main functions (Figure 3.1). In addition, the main functions each have a detailed specification containing dozens of pages describing the main function in detail. The rules specifying how these major functions can be used to compose a product individual are given in a stack representation. The base includes a set of fundamental main functions required in all the products of the SPL. The main functions in each stack represent similar functionality, so that a main function on top

Figure 3.1. An illustration of vertical variability in the SPL of Case A. Product A is valid and Product B is invalid, violating the stack order.

of another adds, for example, more automation, functionality, or other characteristics to the main function below it in the stack. The base is always included and non-base main functions can be included in a stacked manner; that is, a main function can be included when everything below it is included too.

The horizontal variability manifests itself in a few hundred parameters. The horizontal variability is defined in the form of options, alternatives, or numerical parameters. The parameters of horizontal variability have descriptions in natural language in the configurator. These explanations specify in a few sentences the purpose of the parameter, the effects of binding the variability, what the possible values that can be selected for the binding are, and what these values mean. The descriptions are relatively short and are meant for the company’s engineers. The configurator also has some encoded rules corresponding to a model of dependencies. Thus, the configurator checks the correctness of some parameter values and their combinations, but does so only for a small subset of all parameters.

Case B (Publication II).

The products of the SPL in Company B are for medical information management. There are three types of variability, which are called selecting subproducts, referring to the main functionalities of the SPL, low-level variability to adapt a product of the SPL by setting parameters, and tailoring through additional software development.

The SPL consists of a set of about dozen such subproducts each having a specific functionality and being a well-modularized entity. Brochures documenting the details of each subproduct are used to show the main functionalities that are provided. Despite being subproducts, the subproducts

are modular elements integrated to work as one product. A product can include, in principle, any subset of the subproducts but, in practice, not all combinations are meaningful, but there are no explicit rules. However, implicitly, one of the subproducts forms the basis and is always included, and some subproducts require another subproduct to work, for example.

In addition to the above variability in selecting the main functions, detailed characteristics of a product are also customizable to the customer's preferences and environment by low-level variability. The low-level variability is realized by options, alternatives, and numeric parameters in special configuration files, without adding to or modifying the source code. The low-level variability of the SPL is bound according to customer requirements by setting hundreds or even thousands of parameter values in the configuration files. The company uses a configurator tool specifically developed for this SPL. Generating a correct configuration relies on the derivator's experience and knowledge of the SPL and subsequent testing that the configuration is operating correctly rather than rules embedded in the configurator. A product may also include tailoring through the development of new software. Tailoring includes, for example, adding a component to export data, to perform some special data handling, or to wrap an interface to other systems.

Case Fathammer (Publication III).

Fathammer has developed a technology platform called X-Forge that is a multi-device game engine that is used for different games. X-Forge alone does not result in a game that is ideal for a certain mobile device. Each game developed using X-Forge is further specialized into a number of SKUs (Stock Keeping Units), and, thus, a game corresponding to an SPL. One SKU is targeted for a specific device and localization settings, and it is distributed through a certain sales channel. The actual game development on top of X-Forge is outsourced. The device, especially the different hardware, causes a need for quality attribute variability, such as in terms of performance or memory footprint. The differences in the computing resources available on different devices might be enormous, and thus the software may need to vary its behavior in order to provide the best perceived quality on all devices.

Fathammer decided to explicitly specify some variability to outsourced development. However, it would have been infeasible to require implementation for all possible variability; this would have slowed down the

game production too much. Therefore, a verification configurations model was introduced. The game developers are given a number of separate device configurations that represent the range of existing mobile devices. These configurations specify the most critical aspects of the device, such as screen resolution and memory size. The number of verification configurations used is three. A game is developed from the start to support these configurations. This compels a game developer to identify variation points, i.e., the locations in the artifacts where the configurations differ from each other, and implement variation mechanisms for them. This is because extending existing variation points with new variants is easier than creating new variation points from scratch. However, Fathammer did not require any specific modeling of the variation points beyond implementing them. That is, variability management largely relied only on implementation-level mechanisms.

Summary of Case Studies.

Two of the cases (Case A and B) used an informal approach to model variability that was developed in-house. Both these modeled variability only at a very high level. Case A applied simple rules by the use of a stack, while in Case B the rules were implicit. However, the basic idea is very similar, so that there are around a dozen elements representing the main functionalities, some of which require and build on top of another element. Fathammer did not model variability as such but the main varying parts were informally identified. The variability was demonstrated by different variants rather than by designed variability.

All the cases manifest a significant amount of detailed variability that was not modeled comprehensively. This detailed variability was at best described practically by natural language. Cases A and B had descriptions attached to configuration parameters, while in Fathammer these were documented more informally, if at all.

3.3 RQ3: Considerations in Variability Models

The considerations in variability models are presented in Publications IV and V.

Cost-benefit. Cost-benefit refers to what is relevant to model. While technically there are no limitations on what can be modeled, the cost-efficiency of such modeling efforts remains questionable. First, construct-

ing a model itself can be laborious. Second, the understanding and use of the model can be impractical. Third, the maintenance of a model can even be the largest investment. For variability models, the needs from practice are relevant and should be taken into account rather than only concentrating on what is possible.

Stakeholders. A model can have different stakeholders because variability is a concern that can cut across the organization. Stakeholders can have different backgrounds, from technical to non-technical. For variability modeling, it is relevant to take into account the stakeholders and fitness for purpose.

Domain. A variability model can represent a problem or solution domain. A problem domain refers to what is or can be meaningful or feasible in the domain. A solution domain refers to what is, or will be, implemented taking into account, e.g., technical and business needs.

Completeness. Completeness refers to whether everything is modeled — or what and how much is, e.g., abstracted, hidden, or left out. A complete model can be complex and expensive but incomplete models ignore something. Variability is a phenomenon for which completeness becomes complex, as in the case of constraints. In practice, models are typically incomplete and primarily non-trivial things are modeled. A variability model does not require completeness per se.

Correspondence. A variability model is not standalone but needs to be related to some other model or artifact in order to be better integrated with the software development life-cycle. In order to do this, a variability model needs appropriate constructs for the relation to other artifacts or phases in software development.

Commonality. A variability model addresses variability but a decision needs to be made about how much commonality is presented. Focusing only on variability can result in the lack of a description of the essential commonalities. Too much commonality, in turn, can result in an unnecessarily large or complex model where variability is no longer the essence. A variability model, or the supporting tool, can provide different kinds of means to balance an appropriate level of commonality, e.g., by enabling information hiding or different views.

Constraints. Constraints are an essential part of a variability model. However, constraints on variability can have an influence on the model and a proper balance needs to be found. Constraints can overlap or can form a structure other than the other structures of the software. In prac-

tice, constraints introduce a new kind of relationship to software.

Separate interests. There are three separate interests even within one variability model: domain phenomena, concepts, and representation. Domain phenomena are captured as concepts with semantics and the concepts are provided with representation. There can even be multiple equivalent representations of concepts. Conceptually, these interests are separate and can be reflected in a variability model as well.

Conceptual clarity. The exact nature of concepts and relationships is the basis for conceptual clarity. If there is a significant difference, concepts should not be misused, such as through mixing *is-a* and *is-part-of* relationships. Likewise, ambiguous concepts can cause confusion, such as sometimes using cardinality (e.g., by [0,1]) and sometimes optionality. In terms of a variability model, the concepts should be made clear but also intuitive and unnecessary ambiguity should be avoided.

Type-instance. SPL engineering makes a clear distinction between domain and application engineering activities. However, variability models are not always clear about the distinction, thus being somewhat illogical. For example, the very basis of feature modeling, FODA, focuses mainly on domain analysis but application engineering concepts are not even included and considered a necessity. If it is deemed necessary, a clear separation should be realized, e.g., by a means of type-instance dichotomy.

Notation. Notation is a way to realize a variability model. There are several different notations to choose from. For a variability model, the notation should be fit for purpose.

4. Discussion

In this this chapter, we provide the answers to research questions. For each question, we first summarize the key results, then summarize the insights from the results, and finally discuss the related work. In the end of the chapter, we discuss validity and reliability.

4.1 Answer to RQ1: Existing Variability Models

The results show a large number of different kinds of variability models but many of these variability models are only supported by relatively few studies. While some of the variability models were clearly different, there are additionally many minor revisions, such as different representations or extensions of a feature model. In fact, much of the research on variability models appear to be about proposing new or revised variability models. Separating all the minor differences would result in an even larger set of variability models. However, it was possible to identify groups of similar variability models.

A feature model individually and as a group stands out clearly on its own as the most commonly appearing variability model in the literature. Using UML is another relatively clearly defined and notably popular variability model. With respect to other dedicated variability models than a feature model, different decision models and orthogonal variability models do not appear especially common. Interestingly, CVL [36], which is an orthogonal variability model and standardized by OMG [58], appears only once. Rather, many variability extensions or adaptations of existing software models are at least equally popular as these two dedicated variability models.

Practically all the phases or activities in software engineering, such as requirements engineering or detailed design, are covered by variability

models. A feature model is popular throughout the phases and activities although, e.g., use cases are notably popular for requirements engineering.

As a summary, we identified a broad set of existing variability models. The variability models cover different artifacts, activities, and phases of software engineering. Therefore, there are several variability models readily available to be selected and applied in the most, if not all situations. It is unlikely that there is no variability model capable of expressing the needed variability per se. In addition, the area of variability models is maturing. That is, a feature model as the example of the most dominant model has been formalized more than a decade ago [4, 68, 20] and no major changes have been proposed to fundamental concepts. Therefore, the practical needs and use of variability modeling in industrial settings, as well as comparative and synthesizing studies, to evidence the use and guide potential further development have become at least equally timely issues than any additional novel or adapted variability model constructs per se.

Our results are at best comparative and bear similarities to the results of the SRs focusing on variability. Chen and Ali Babar [15] study the evaluation of variability management approaches and all the approaches they found are dependent on a variability model. They identified significantly fewer models and found UML to be almost as popular as a feature model. Galster *et al.* [24] introduce five relatively abstract categories on the basis of a sample. Only one sample study per category and its central ideas are shown but the level of support is not provided beyond the sample. Consequently, a wider spectrum of variability models is captured by our study. In addition, we provide analysis with respect to different topics.

In addition, there are studies that are not as systematically conducted with respect to study selection, or do not aim to cover variability models broadly. As a result, the focus is on a more limited sample or selection of variability models. Such studies cover, e.g., a comparison of textual variability modeling languages [22], a synthesis of feature model semantics [68], a survey of feature model analysis [8], a comparison between feature and decisions models [19] and the comparison between six [73] and two [10] different variability models. These kinds of studies typically provide more details of each variability model. However, the studies do not provide an overview of the field, as SRs do, and also lack analysis with respect to different topics. Moreover, these studies often perform their analysis at

the level of constructs in variability models or abilities to cover specific phenomena, but do not focus on use, as discussed in greater depth in the next research question.

We do not claim that our study is comprehensive, but even acknowledge that there are additional variability models. For example, Clafer [5] and Delta modeling [34] are not covered in the tertiary study. However, such additional variability models likely contribute little to the exhaustiveness of variability models and would be unlikely to be notably popular.

4.2 Answer to RQ2: Variability Models Used

The literature evidences the use of variability models in industry but only scarcely: 18 primary studies are about direct research results of industrial use. A feature model has the largest number of primary studies about industrial use. However, the amount of evidence about the use of a feature model does not entirely convincingly show its wide adoption. The evidence even includes unsuccessful applications and hypothetical applications in which the latter could also be classified as expert opinions. Apart from a feature model, there is only isolated evidence about industrial use that is spread among several different kinds of models stemming from a few SRs. However, the overall amount of research about feature models is also significantly larger compared to other variability models, as argued above in RQ1. There also exists other, less direct evidence about industrial use but the evidence does not show anything convincingly different, and the amount of evidence is not significant. Thus, it is not meaningful to argue that there are large differences in industrial evidence between different variability models. The literature (Publication I) does not cover industrial use convincingly especially when one considers the amount of industrial evidence in the light of the entire amount of research on variability models covered in RQ1. That is, the reported studies do not necessarily reliably and representatively reflect industrial practice. Interestingly, what is notably absent in SRs is in-house or informal models or cases in which explicit variability modeling was not deemed to be necessary at all: such approaches are either not taken into account or do not exist or are rare.

In contrast, the results from empirical studies (Publication II and III) show the use of in-house approaches to variability modeling rather than applying an existing or research-proposed variability model. Such variability models often seem to cover variability relatively coarsely by large

modular entities related to a main functionality and, at most, by a few explicit rules. Although such models are similar to, e.g., a feature model, the models were developed in-house rather than by using any existing variability model. Moreover, low-level or even code-level techniques, such as parameters, are used extensively for more detailed variability and can be provided with descriptions but are not modeled at all, or in detail or extensively, at least to the extent that constraints would be considered.

The summary of narrative synthesis carried out to these two kinds of studies shows complementary results. Some variability models, and most of the variability model groups, as well as solutions developed in-house have been provided with evidence about their being used in a certain context. Hence, there is little uncertainty of overall applicability of the constructs. In fact, while industrial use is scarce, there is still evidence of utility. The empirical data is not sufficient to make conclusions on a basis of interpretive narrative synthesis or integrative meta-analysis of the applicable contexts or good practices for selecting and applying a variability model. More empirical evidence of successful and unsuccessful applications of variability model, the use of in-house solutions, or omitting variability models altogether by using only realization-level techniques is therefore needed. The empirical evidence could also guide the evolution of the existing variability models.

A discussed earlier, there are not many studies that focus on the use or practical applications in industrial settings. That of Hubaux *et al.* [39], which is covered in Publication I, focuses only on feature models and argues similarly to us: "few details about the usage of [feature models] were found." With respect to practical use, requirements for product derivation are surveyed but the focus is largely on expert opinions gathered from the research communities [65]. The comparative studies, such as surveys of variability models, as discussed in RQ1, have mostly surveyed the properties of the existing variability models rather than studying practical applications.

4.3 Answer to RQ3: Variability Model Considerations

We described 12 considerations in variability modeling that address the practical needs, as well as what a variability model should require and provide. The considerations are the costs-benefit balance; the stakeholders involved for the purpose; the domain of interest; the completeness of

the model; correspondence with other artifacts; the amount of commonality; the constraints of variability as an additional relationship; separate interests in a variability model; the conceptual clarity of concepts; types and instances as separate concepts differentiating domain and application engineering artifacts, and notation that is usable for the purpose.

As a summary, the considerations are design decisions that address what of the variability to model, as well as issues that need to be taken into account of so that the selected variability model is sufficient to support the needs. The considerations arise the complex nature of variability: variability, including the relationships, such as dependencies, originates from several sources; variability is a cross-cutting property designed to software through different activities, phases, levels of abstraction, and stakeholders; and variability is an aspect or quality of designed software that is somewhat orthogonal to development activities in time and space. The considerations clarify the heuristic nature of variability model use: a variability model can be applied differently or a different variability model can be applied, depending on the particular situation. That is, there is not necessarily an optimal design decisions for the considerations but the design decisions depend on the particular context as well as each offering benefits and drawbacks. Some of the considerations can be evident for a certain context without much need to take into account alternatives, thus being sometimes at least seemingly irrelevant. The considerations are not either different viewpoints or concerns that all need to be covered but decisions that need to be addressed. The listed considerations are not claimed to be a extensive list in a sense that other kinds of considerations could not exist. The considerations are theoretical propositions based on narrative synthesis that would benefit from further evaluation. The considerations are not necessarily specific for variability models only, because variability models are a subclass of software models sharing characteristics and considerations with other kinds of models.

Variability modeling, in particularly feature modeling, has been studied extensively and a variability model may appear well understood. However, the constructs alone are not sufficient and, in practice, engineers must face a number of decisions when applying a variability model. Often, these kinds of considerations that go beyond the constructs of variability models are left implicit. Besides practitioners applying a variability model for an SPL, the considerations are important in the development of variability models and in the guidelines for applying variability models.

The separation of concerns in variability models are surveyed [40] but concerns are different concurrent viewpoints rather than decisions similarly as considerations. Some considerations exist in a quite specific manner in related work, but they are often based on conceptual work. For example, correspondence has been addressed to other artifacts, such as generating source code by tools is supported [60]. The details of notation have been covered in a more general manner in modeling [55] and for product configuration [62]. The constructs are compared and provided with semantics [68] that are a means towards the conceptual clarity that we argued for.

4.4 Validity and Reliability

Validity is a measure relating to the results [35] meaning the approximate truth of an inference [69]. An issue related to validity in this thesis is the selection of Design Science as the research approach, which specified certain ontological and epistemological presumptions. Another common, archetypical formative research approach is Action Research, which primarily defines an iterative process model including researcher-practitioner interaction rather than an ontology and epistemology, or differs in its ethos [7, 81]. Therefore, Action Research was not considered relevant in this work. The alternatives for formative research are descriptive and formal approaches [32, 43]. One alternative would have been to carry out the study as a realist or pragmatic descriptive case study. Unlike a case study, Design Science as described in Section 2.1 provides us with the prescriptive structure and the criteria of utility. The case study method was possible to apply as a research method under the realm of Design Science approach. As another alternative, formal approaches were not considered feasible, because they are often empirically void and this thesis focuses on practical use.

For the validity discussion of the thesis, a more fine-grained typology of validity is applied. Construct validity refers to whether concepts are the correct representation of the intended phenomena, internal validity focuses on causal relationships, and external validity means generalizations to settings beyond those measured in the study [91, 90, 69]. Below, we discuss threats to validity within this typology.

One threat to construct validity is that the survey of variability models conducted as a tertiary study does not cover the field properly. Given the

number of studies covered, the results seem to provide a broad sample rather than all the possible variability models. Additional research proposals do exist that, however, do not seem to have been widely reported, or are recent proposals that are even still under development. Therefore, the data in our sample could change, but it seems that the change does not have a significant effect on the inference. The selection can be biased towards research proposals, lacking in industrial use and especially in-house variability models. However, such a bias is an inherent characteristic of software engineering research [27]. A threat caused by the transitive nature of a tertiary study is that a primary study can appear more than once if reported in different SRs, and errors in the secondary studies or our interpretations. To alleviate the threat, we were cautious about representativeness and, specifically, in the case of industrial use we traced the primary studies.

A threat to construct validity in Publication V is that we did not cover previous work systematically for either of the topics similarly as for Publication I. Rather, the study was carried out by relying largely on previous knowledge on the topic. We were already familiar with a large number of primary studies about software variability and feature modeling based on the tertiary study (Publication I), but analyzing all these primary studies was not considered valid or feasible. In a similar manner, we were familiar with an extensive literature on knowledge-based configuration but carried out a limited systematic search through potential papers. While a systematic review could have alleviated some of the threats, its suitability concerned us. The objective of a systematic review is to accumulate the reported empirical evidence enabling meta-analysis, while our study was an analytical and qualitative comparison of conceptual characteristics.

Threats to construct validity in the case studies pertain to the complexity of the phenomena to be captured properly [91]. To mitigate the threats in the case studies in Publications II and III, we used triangulation of data sources and researchers, and followed a well-defined case study protocol preserving the chain of evidence. However, Publication IV is less systematic in terms of the study design and realization.

A few threats to internal validity emerge from this study. First, the research problems addressed variability models as interventions and we studied the existing variability models rather than proposing our own variability model. Thus, threats to internal validity are inherited from the existing studies. Moreover, we did not make claims beyond the feasibility

that has been shown in the existing studies. Second, the considerations are characteristics of the intervention that are claimed to be often relevant, but not necessarily always explicitly relevant nor necessarily sufficient alone, in a successful variability model. Thus, the considerations are theoretical propositions based on the qualitative studies, and remain as propositions to be further evaluated.

External validity also pertains to the nature of results as theoretical propositions based on the qualitative, interpretive inference [49, 91]. With respect to the amount of evidence about the proposed variability models, we were unable to generalize beyond applicability and called for further studies to elaborate the applicable contexts of applications. Three cases from one country is also a relatively limited selection that remains a threat although allows us to generalize theoretical propositions. Similarly, the considerations are per se based on qualitative studies to be assessed in wider contexts of application.

Reliability is a measure concerning the study design and realization in order to consistently produce a valid inference [35]. Reliability is achieved by well-defined research design and traceable inference from data to conclusions [91]. In Publications I, II, and III, we applied the defined protocols and stored the data through the intermediate steps to alleviate threats. Threats to reliability exist in the studies in Publications IV and V, which do not explicate intermediate steps similarly or are not equally systematically conducted: Publication IV did not rely on pre-defined data collection and analysis techniques, and did not store data systematically, and Publication V relied on unsystematically explicated expert knowledge and expert judgments rather than systematic practices or empirical evidence as the basis for the inference. However, neither of these studies claims to be comprehensive but rather they propose a set of characteristics of the phenomena.

5. Conclusions

This thesis studied the problem "*What kinds of models to use to represent the variability in an SPL?*" The research methodology followed the Design Science approach: the applications of variability models are the *heuristic interventions* of a prescription in order to have *utility* in terms of practical value in the achievement of the desired goal of representing variability. We emphasized the use of variability models, especially in industrial settings, as an elementary form of utility, rather than studying the constructs or properties of different variability models per se. The research methods we applied were the tertiary study and a literature study method as the forms of a literature review method, as well as two different designs of the case study method. The contributions of this thesis stem from the practical and holistic application of variability models, unlike much of the existing research, which mostly focuses on variability constructs and modeling methods.

For the *variability models as interventions*, we identified from the literature tens of existing and different variability models, which cover extensively the different artifacts, activities, and phases of software engineering. The variability models are distinguishable novel variability models or variability extensions or adaptations to existing software models. However, the variability models bear similarities so that it was possible to divide them into a set of groups. The feature model stands out clearly as the most popular variability model for software engineering. There are also other commonly appearing variability models, such as the group of UML extensions and adaptations.

For the *utility of variability models*, we found out that different kinds of variability models have evidence about use, but there is no evidence that some variability models would have become an established practice. Our case studies show how variability modeling is based on in-house developed

relatively rudimentary and coarse-grained models, which are targeted to application domain experts to the representation of the variability of major functionalities. In the literature, we found out that several kinds of existing variability models have been provided with some empirical evidence about use in realistic settings. However, evidence of the industrial use of the existing variability models is too isolated to allow summarizing synthesis about what models should be used and when, as well as utility measures for and comparisons between variability models. Therefore, when selecting and using a variability model, one needs to take into account several considerations in the context.

With respect to the *heuristic nature of variability models as interventions*, we specified eight considerations. Each practitioners need to make decisions about these considerations when using a variability model to represent the variability of an SPL. The considerations emphasize how a variability model can be applied differently, depending on the particular context. The considerations address variability as a design activity and a designed ability in software that is complex, multi-faceted, and cross-cutting. These considerations can also be relevant to those who develop variability models to address the needs of practice.

There are several directions for future work. More and more detailed empirical evidence is needed for the use of variability models based on, e.g., case studies, industrial expert opinions, or surveys. This applies also to the further study and validation of the above considerations. The evidence should be more holistic meaning that rather than just describing that a variability model is applied, the evidence should include characteristics about the application, such as contexts, successes or failures, and impacts. This would facilitate future summarizing studies. We focused primarily on software product lines, but it would be interesting to study the needs and realization of variability in different application areas, or areas adopting variability modeling or software product line principles. An example is the application of variability models to help with reasoning in pervasive or self-adapting applications in which variability enables dynamic changes. Another future research topic is to study variability models for problems that are not considered primarily being about variability. An example is the application of variability models to represent incremental development. Variability does not then represent only the existing assets from which to derive a product individual, but incremental development of assets for different versions as product individuals.

References

- [1] W. R. Adrion. Research methodology in software engineering, summary of the Dagstuhl workshop on future directions in software engineering. *ACM SIGSOFT Software Engineering Notes*, 18(1):36–37, 1993.
- [2] S. Aier and C. Fischer. Criteria of progress for information systems design theories. *Information Systems and e-Business Management*, 9(1):133–172, 2011.
- [3] V. Alves, N. Niu, C. Alves, and G. Valença. Requirements engineering for software product lines: A systematic literature review. *Information and Software Technology*, 52(8):806–820, 2010.
- [4] T. Asikainen, T. Männistö, and T. Soininen. Kumbang: A domain ontology for modelling variability in software product families. *Advanced engineering informatics journal*, 21(1):23–40, 2007.
- [5] K. Bąk, Z. Diskin, M. Antkiewicz, K. Czarnecki, and A. Wąsowski. Clafer: unifying class and feature modeling. *Software & Systems Modeling*, 15(3):811–845, 2016.
- [6] R. Baskerville. What design science is not. *European Journal of Information Systems*, 17:441–443, 2008.
- [7] R. Baskerville and A. T. Wood-Harper. A critical perspective on action research as a method for information systems research. *Journal of Information Technology*, 11(3):235–246, 1996.
- [8] D. Benavides, S. Segura, and A. Ruiz-Cortes. Automated analysis of feature models 20 years later: A literature review. *Information Systems*, 35(6):615–636, 2010.
- [9] D. Benavides, P. Trinidad, and A. Ruiz Cortés. Using constraint programming to reason on feature models. In *International Conference on Software Engineering and Knowledge Engineering (SEKE)*, 2005.
- [10] T. Berger, S. She, R. Lotufo, A. Wasowski, and K. Czarnecki. A study of variability models and languages in the systems software domain. *IEEE Transactions on Software Engineering*, 39(12):1611–1640, 2013.
- [11] C.I.M. Bezerra, R.M.C. Andrade, and J.M.S. Monteiro. Measures for quality evaluation of feature models. In *International Conference on Software Reuse*, pages 282–297, 2014.

- [12] J. Bosch. *Design and Use of Software Architectures: Adapting and Evolving a Product-Line Approach*. Addison-Wesley, New York, USA, 2000.
- [13] P. Bourque and eds. R.E. Fairley. Guide to the software engineering body of knowledge version 3.0. www.swebok.org, 2014.
- [14] S. A. Carlsson. Developing information systems design knowledge: A critical realist perspective. *The Electronic Journal of Business Research Methodology*, 3(2):93–102, 2005.
- [15] L. Chen and M. Ali Babar. A systematic review of evaluation of variability management approaches in software product lines. *Information and Software Technology*, 53(4):344–362, 2011.
- [16] L. Chen, M. Ali Babar, and A. Nour. Variability management in software product lines: a systematic review. In *Software Product Line Conference (SPLC)*, pages 81–90, 2009.
- [17] P. Clements and L. M. Northrop. *Software Product Lines: Practices and Patterns*. Addison-Wesley, Boston, MA, USA, 2001.
- [18] D. S. Cruzes and T. Dybå. Research synthesis in software engineering: A tertiary study. *Information and Software Technology*, 53(5):440–455, 2011.
- [19] K. Czarnecki, P. Grünbacher, R. Rabiser, K. Schmid, and A. Wasowski. Cool features and tough decisions: A comparison of variability modeling approaches. In *International Workshop on Variability Modeling of Software-Intensive Systems*, pages 173–182, 2012.
- [20] K. Czarnecki, S. Helsen, and U. W. Eisenecker. Formalizing cardinality-based feature models and their specialization. *Software process: Improvement and practice*, 10(1):7–29, 2005.
- [21] T. Dybå, B. Kitchenham, and M. Jørgensen. Evidence-based software engineering for practitioners. *IEEE Software*, 22(1):58–65, 2005.
- [22] H. Eichelberger and K. Schmid. Mapping the design-space of textual variability modeling languages: a refined analysis. *International Journal on Software Tools for Technology Transfer*, 17(5):559–584, 2015.
- [23] C. Fischer and S. Gregor. Forms of reasoning in the design science research process. In *International Conference on Design Science Research in Information Systems and Technology*, pages 17–31, 2011.
- [24] M. Galster, D. Weyns, D. Tofan, B. Michalik, and P. Avgeriou. Variability in software systems — a systematic literature review. *IEEE Transactions on Software Engineering*, 40(3):282–306, 2014.
- [25] T. G. Gill and A. R. Hevner. A fitness-utility model for design science research. In *International Conference on Design Science Research in Information Systems and Technology*, pages 237–252, 2011.
- [26] R. L. Glass. A structure-based critique of contemporary computing research. *Journal of Systems and Software*, 28(1):3–7, 1995.
- [27] R. L. Glass, V. Ramesh, and I. Vessey. An analysis of research in computing disciplines. *Communications of the ACM*, 47(6):89–94, 2004.

- [28] R. L. Glass, I. Vessey, and V. Ramesh. Research in software engineering: an analysis of the literature. *Information and Software Technology*, 44(8):491–506, 2002.
- [29] R. L. Glass, I. Vessey, and V. Ramesh. RESRES: The story behind the paper: Research in software engineering: An analysis of the literature. *Information and Software Technology*, 51(1):68–70, 2009.
- [30] G. Goldkuhl. Design theories in information systems — a need for multi-grounding. *Journal of Information Technology Theory and Application*, 6(2):59–72, 2004.
- [31] H. Gomma. *Designing Software Product Lines with UML: From Use Cases to Pattern-Based Software Architectures*. Addison-Wesley, 2004.
- [32] S. Gregor. The nature of theory in information systems. *MIS Quarterly*, 30(3):611–642, 2006.
- [33] S. Gregor and D. Jones. The anatomy of a design theory. *Journal of the Association for Information Systems*, 8(5):312–335, 2007.
- [34] A. Haber, K. Hölldobler, C. Kolassa, M. Look, B. Rumpe, K. Müller, and I. Schaefer. Engineering delta modeling languages. In *Software Product Line Conference*, pages 22–31, 2013.
- [35] M. Hammersley. Some notes on the terms ‘validity’ and ‘reliability’. *British Educational Research Journal*, 13(1):73–81, 1987.
- [36] Ø. Haugen, A. Wasowski, and K. Czarnecki. CVL: Common variability language. In *Software Product Line Conference*, pages 277–277, 2013.
- [37] R. Heradio, H. Perez-Morago, D. Fernandez-Amoros, F J. Cabrerizo, and E. Herrera-Viedma. A bibliometric analysis of 20 years of research on software product lines. *Information and Software Technology*, 72:1–15, 2016.
- [38] A. R. Hevner, S. T. March, J. Park, and S. Ram. Design science in information systems research. *MIS Quarterly*, 28(1):75–105, 2004.
- [39] A. Hubaux, A. Classen, M. Mendonça, and P. Heymans. A preliminary review on the application of feature diagrams in practice. In *International Workshop on Variability Modelling of Software-Intensive Systems*, pages 53–59, 2010.
- [40] A. Hubaux, T.T. Tun, and P. Heymans. Separation of concerns in feature diagram languages: A systematic survey. *ACM Computing Surveys*, 45(4):51:1–51:23, 2013.
- [41] J. Iivari, R. Hirschheim, and H. K. Klein. A dynamic framework for classifying information systems development methodologies and approaches. *Journal of Management Information Systems*, 17(3):179–218, 2000-2001.
- [42] J. Iivari and J. Venable. Action research and design science research — seemingly similar but decisively dissimilar. In *European Conference on Information Systems*, pages 1642–1653, 2009.
- [43] P. Järvinen. *On research methods*. Opinaja, Tampere, Finland, 2004.

- [44] K.C. Kang, S.G. Cohen, J.A. Hess, W.E. Novak, and A.S. Peterson. Feature-oriented domain analysis (FODA) feasibility study. Technical Report CMU/SEI-90-TR-21, ADA 235785, Software Engineering Institute, 1990.
- [45] K.C. Kang, S. Kim, J. Lee, K. Kim, E. Shin, and M. Huh. FORM: A feature-oriented reuse method with domain-specific reference architectures. *Annals of Software Engineering*, 5(1):143–168, 1998.
- [46] E. Kasanen, K. Lukka, and A. Siitonen. The constructive approach in management accounting research. *Journal of Management Accounting Research*, 5:243–264, 1993.
- [47] B. Kitchenham. Procedures for performing systematic reviews. Technical report, Keele University Technical Report TR/SE-0401 and NICTA Technical Report 0400011T.1, 2004.
- [48] B. Kitchenham. Guidelines for performing systematic literature reviews in software engineering. Technical Report EBSE-2007-01 version 2.3, Keele University, 2007.
- [49] A. S. Lee and R. L. Baskerville. Generalizing generalizability in information systems research. *Information Systems Research*, 14(3):221–243, 2003.
- [50] R. E. Lopez-Herrejon, L. Linsbauer, and A. Egyed. A systematic mapping study of search-based software engineering for software product lines. *Information and Software Technology*, 61:33–51, 2015.
- [51] I.D.C.a Machado, J.D.b McGregor, Y.C.c Cavalcanti, and E.S.a De Almeida. On strategies for testing software product lines: A systematic literature review. *Information and Software Technology*, 56(10):1183–1199, 2014.
- [52] S. Mahdavi-Hezavehi, M. Galster, and P. Avgeriou. Variability in quality attributes of service-based software systems: A systematic literature review. *Information and Software Technology*, 55(2):320–343, 2013.
- [53] S. T. March and G. F. Smith. Design and natural science research on information technology. *Decision Support Systems*, 15(4):251–266, 1995.
- [54] S. Montagud, S. Abrahão, and E. Insfran. A systematic review of quality attributes and measures for software product lines. *Software Quality Journal*, 20(3-4):425–486, 2012.
- [55] D. L. Moody. The "physics" of notations: Toward a scientific basis for constructing visual notations in software engineering. *IEEE Transactions on Software Engineering*, 35(6):756–779, 2009.
- [56] V. Myllärniemi, M. Raatikainen, J. Tiihonen, and A. Felfernig. Using answer set programming for feature model representation and configuration. In *Workshop on Configuration*, pages 1–8, 2014.
- [57] I. Niiniluoto. The aim and structure of applied research. *Erkenntnis*, 38(1):1–21, 1993.
- [58] OMG. Common variability language. <http://www.omgwiki.org/variability>, 2017.

- [59] K. Peffers, T. Tuunanen, M. Rothenberger, and S. Chatterjee. A design science research methodology for information systems research. *Journal of Management Information Systems*, 24(3):45–77, 2007.
- [60] J.A. Pereira, K. Constantino, and E. Figueiredo. A systematic literature review of software product line management tools. In *International Conference on Software Reuse*, pages 73–89, 2014.
- [61] K. Petersen, R. Feldt, S. Mujtaba, and M. Mattsson. Systematic mapping studies in software engineering. In *International Conference on Evaluation and Assessment in Software Engineering*, pages 68–77, 2008.
- [62] A. Pleuss, R. Rabiser, and G. Botterweck. Visualization techniques for application in interactive product configuration. In *Software Product Line Conference, Volume 2*, pages 22:1–22:8, 2011.
- [63] K. Pohl, G. Böckle, and F. van der Linden. *Software Product Line Engineering: Foundations, Principles, and Techniques*. Springer-Verlag Berlin Heidelberg, Germany, 2005.
- [64] M. Raatikainen, T. Männistö, and Timo Soininen. CASFIS-approach for studying software product families in industry. In *Groningen Workshop on Software Variability Management: Software Product Families and Populations*, 2004.
- [65] R. Rabiser, P. Grünbacher, and D. Dhungana. Requirements for product derivation support: Results from a systematic literature review and an expert survey. *Information and Software Technology*, 52(3):324–346, 2010.
- [66] P. Runeson and M. Höst. Guidelines for conducting and reporting case study research in software engineering. *Empirical Software Engineering*, 14(2):131–164, 2009.
- [67] I. S. Santos, R. M. C. Castro Andrade, and P. A. Santos Neto. How to describe SPL variabilities in textual use cases: A systematic mapping study. In *Brazilian Symposium on Software Components, Architectures and Reuse*, pages 64–73, 2014.
- [68] P-Y. Schobbens, P. Heymans, J-C. Trigaux, and Y. Bontemps. Generic semantics of feature diagrams. *Compututer Networks*, 51(2):456–479, 2007.
- [69] W. R. Shadish, T. D. Cook, and D. T. Campbell. *Experimental and Quasi-Experimental Designs for Generalized Causal Inference*. Houghton, Mifflin, Boston, USA, 2002.
- [70] M. Shaw. What makes good research in software engineering? *International Journal on Software Tools for Technology Transfer*, 4(1):1–7, 2002.
- [71] M. Shaw. Writing good software engineering research papers. In *International Conference on Software Engineering*, pages 726–736, 2003.
- [72] F. Shull, J. Singer, and D. I.K. Sjøberg. *Guide to Advanced Empirical Software Engineering*. Springer-Verlag, New York, USA, 2007.
- [73] M. Sinnema and S. Deelstra. Classifying variability modeling techniques. *Information and Software Technology*, 49(7):717 – 739, 2007.

- [74] M. Sinnema, S. Deelstra, J. Nijhuis, and J. Bosch. COVAMOF: A framework for modeling variability in software product families. In *Software Product Line Conference*, pages 197–213, 2004.
- [75] D. I. K. Sjøberg, T. Dybå, B. C. D. Anda, and J. E. Hannay. Building theories in software engineering. In F. Shull, J. Singer, and D. I.K. Sjøberg, editors, *Guide to Advanced Empirical Software Engineering*, chapter Building Theories in Software Engineering. Springer-Verlag, New York, USA, 2008.
- [76] A. Strauss and J. Corbin. *Basics of Qualitative Research*. Sage, 2 edition, 1998.
- [77] M. Svahnberg, J. van Gurp, and J. Bosch. A taxonomy of variability realization techniques. *Software — Practice and Experience*, 35(8):705–754, 2005.
- [78] W. F. Tichy, P. Lukowicz, L. Prechelt, and E. A. Heinz. Experimental evaluation in computer science: a quantitative study. *Journal of Systems and Software*, 28(1):9–18, 1995.
- [79] J. Tiihonen. *Support for configuration of physical products and services*. Doctoral dissertation, Aalto University, 2014.
- [80] J. E. van Aken. Management research based on the paradigm of the design sciences: The quest for field-tested and grounded technological rules. *Journal of Management Studies*, 41(2):219–246, 2004.
- [81] J. E. van Aken. Management research as a design science: Articulating the research products of mode 2 knowledge production in management. *British Journal of Management*, 16(1):19–36, 2005.
- [82] J. Venable, J. Pries-Heje, and R. Baskerville. A comprehensive framework for evaluation in design science research. In *International Conference on Design Science Research in Information Systems and Technology*, pages 423–438, 2012.
- [83] J. G Walls, G. R Widmeyer, and O. A. El Sawy. Building an information system design theory for vigilant EIS. *Information Systems Research*, 3(1):36–59, 1992.
- [84] J. G Walls, G. R Widmeyer, and O. A. El Sawy. Assessing information system design theory in perspective: How useful was our 1992 initial rendition? *Journal of Information Technology Theory and Application*, 6(2):43–58, 2004.
- [85] J. Webster and R. T. Watson. Analyzing the Past to Prepare for the Future: Writing a Literature Review. *MIS Quarterly*, 26(2):13–23, 2002.
- [86] D. Weiss and C. T. R. Lai. *Software product-line engineering: a family based software development process*. Addison Wesley, Boston, MA, USA, 1999.
- [87] R. Wieringa. Design science as nested problem solving. In *International Conference on Design Science Research in Information Systems and Technology*, pages 1–12, 2009.
- [88] R. Wieringa and J. M. G. Heerkens. The methodological soundness of requirements engineering papers: a conceptual framework and two case studies. *Requirements Engineering*, 11(4):295–307, 2006.

- [89] C. Wohlin. Guidelines for snowballing in systematic literature studies and a replication in software engineering. In *International Conference on Evaluation and Assessment in Software Engineering*, pages 38:1–38:10, 2014.
- [90] C. Wohlin, P. Runeson, M. Höst, M. C. Ohlsson, B. Regnell, and A. Wesslén. *Experimentation in Software Engineering: An Introduction*. Kluwer Academic Publishers, Norwell, MA, USA, 2000.
- [91] R. K. Yin. *Case Study Research*. Sage, Thousand Oaks, CA, USA, 2. edition, 1994.
- [92] H. Zhang, M. Ali Babar, and P. Tell. Identifying relevant studies in software engineering. *Information and Software Technology*, 53(6):625 – 637, 2011.

Errata

Publication I

In the final published version, the search and the results based on the search have been updated to cover more recent years resulting in 86 SRs.

ISBN 978-952-60-8379-7 (printed)
ISBN 978-952-60-8380-3 (pdf)
ISSN 1799-4934 (printed)
ISSN 1799-4942 (pdf)

Aalto University
School of Science
Department of Computer Science
www.aalto.fi

**BUSINESS +
ECONOMY**

**ART +
DESIGN +
ARCHITECTURE**

**SCIENCE +
TECHNOLOGY**

CROSSOVER

**DOCTORAL
DISSERTATIONS**