Enabling Internet of Things Applications: An End-to-end Approach

Pranvera Kortoçi

Enabling Internet of Things Applications: An End-to-end Approach

Pranvera Kortoçi

**The public defense on 10th June 2020 at 12:00 will be
available via remote technology.**

Link: <https://aalto.zoom.us/j/67819394930>

Zoom Quick Guide: <https://www.aalto.fi/en/services/zoom-quick-guide>

A doctoral dissertation completed for the degree of Doctor of Science (Technology) to be defended, with the permission of the Aalto University School of Science, remote connection Zoom link (<https://aalto.zoom.us/j/67819394930>), on 10th June 2020 at 12:00.

**Aalto University
School of Science
Department of Computer Science**

Supervising professor

Professor Mario Di Francesco, Aalto University, Finland

Preliminary examiners

Professor Delphine Reinhardt, University of Göttingen, Germany

Professor Alhussein Abouzeid, Rensselaer Polytechnic Institute, USA

Opponent

Professor Maria Papadopoulou, University of Crete, Greece

Aalto University publication series

DOCTORAL DISSERTATIONS 88/2020

© 2020 Pranvera Kortoçi

ISBN 978-952-60-3925-1 (printed)

ISBN 978-952-60-3926-8 (pdf)

ISSN 1799-4934 (printed)

ISSN 1799-4942 (pdf)

<http://urn.fi/URN:ISBN:978-952-60-3926-8>

Images: Cover: Theeraphong/shutterstock.com,
Guppica/shutterstock.com

Unigrafia Oy
Helsinki 2020

Finland

Author

Pranvera Kortoçi

Name of the doctoral dissertation

Enabling Internet of Things Applications: An End-to-end Approach

Publisher School of Science

Unit Department of Computer Science

Series Aalto University publication series DOCTORAL DISSERTATIONS 88/2020

Field of research Computer Science

Manuscript submitted 21 January 2020

Date of the defence 10 June 2020

Permission for public defence granted (date) 27 March 2020

Language English

☐ **Monograph**

☒ **Article dissertation**

☐ **Essay dissertation**

Abstract

There is a massive amount of smart objects around us that interact with each other through Internet-based communication standards, forming the so-called Internet of Things (IoT). The scope of the IoT is quite wide and the related applications have diverse requirements in terms of security, data quality, and reliability. We consider different aspects of the IoT: taking an IoT device *securely* into use, establishing communication with an application server, and collecting as well as transmitting sensory data to remote data storage facilities (e.g., servers in the cloud). In fact, the IoT ecosystem and its immense device-generated data have given rise to several computing paradigms (e.g., cloud, edge, and fog) with different potential and means of sustaining the ever-growing IoT.

This dissertation addresses the requirements of a secure and dependable IoT by taking an end-to-end approach. First, it proposes a light-weight mechanism for the initial configuration of network and security parameters to ensure secure bootstrapping of IoT devices. We specifically target a secure as well as a user-friendly IoT: in fact, our solution requires neither human intervention nor physical access to the device, and it incurs low power expenditure. Second, this dissertation addresses challenges in data collection due to the constrained resources available on IoT devices and limited availability of wireless bandwidth. To this end, we consider people- and agent-based data collection with different types of mobility (e.g., uncontrolled, semi-controlled, and fully-controlled). In particular, we leverage the fog computing paradigm and propose a protocol to offload data opportunistically from IoT end-devices to mobile gateways with unknown and uncontrolled mobility. Moreover, we investigate the impact of incentive mechanisms to ensure user participation in the collection of sensory data. To this end, we leverage the mobile edge computing paradigm and design a smart incentive mechanism for participatory crowdsourcing systems that increases the amount of collected data and maximizes the social welfare of the system. Additionally, we propose a communication protocol for ubiquitous wireless devices to disseminate data to mobile agents with fully-controlled mobility to assist search and rescue teams during disaster scenarios. We characterize the impact of our proposed protocol in extending the battery life of the devices and thus increasing the chances of assisting the survivors. Finally, this dissertation presents a light-weight data reduction mechanism that operates at gateways and edge tiers, supporting data-intensive IoT applications. Specifically, it performs filtering and fusion on time series data, thereby reducing the amount of data transmitted to a remote data center while retaining a high recovery accuracy with respect to the original data stream.

Keywords Internet of Things, data collection protocols, cloud and fog computing

ISBN (printed) 978-952-60-3925-1

ISBN (pdf) 978-952-60-3926-8

ISSN (printed) 1799-4934

ISSN (pdf) 1799-4942

Location of publisher Helsinki

Location of printing Helsinki **Year** 2020

Pages 146

urn <http://urn.fi/URN:ISBN:978-952-60-3926-8>

Preface

The doctoral studies that led to this dissertation have been a long but truly amazing journey. There are quite a few people who made this possible. Firstly, I would like to profoundly thank my supervisor Prof. Mario Di Francesco for giving me the chance to conduct research and for creating a friendly, social, fun, and engaging work environment. Thank you for supporting me throughout all this journey, providing me with technical guidance, constructive feedback, and most importantly, for your trust. I am thankful to the pre-examiners, Prof. Delphine Reinhardt and Prof. Alhussein Abouzeid, for attentively reading my dissertation and for their insightful observations. I would also like to thank Prof. Maria Papadopouli for agreeing to be the opponent at my public defense.

Conducting research can be tough at times, but I am more than lucky to have worked with dedicated people that made research inviting and engaging. During my doctoral studies, Prof. Mung Chiang welcomed me to visit the EDGE research lab at Princeton University. Similarly, Prof. Nathalie Mitton provided a welcoming environment during my research visit at Inria research institute. I learned a lot from Prof. Jan-Erik Ekberg and the mobile security team during my industry internship with Huawei. These experiences widened my view on research and provided me with many dear memories. I am thankful to a group of great colleagues and passionate researchers – Mohit Sethi, Carlee Joe-Wong, Liang Zheng, Abbas Mehrabi, Farouk Mezghani, Liang Feng, and Sandeep Tamrakar – for their collaboration, (often remote) discussions, research ideas, and friendship.

I would like to thank the Elisa HPY Research and the Nokia Foundation for the supporting and encouraging scholarships. Likewise, I thank the Helsinki Doctoral Education Network in Information and Communications Technology (HICT) and the Networking Networking Women (N2Women) for the travel grant. I am grateful to Prof. Asokan and Prof. Tuomas Aura with whom I had interesting conversations and who always shared a piece of advice when I needed; Asokan, thank you for the honorary membership to the security group. Many people at the department and at the student services of the doctoral programme helped me immensely during my stay at Aalto: Laura Kuusisto-Noponen, Katri Seitsonen, Päivi Koivunen, Heini Vehmas, and Jaakko Kotimäki – thank you!

This journey is foremost a story of friendships. I am grateful to many friends who made me feel loved and home more than ever. Ella Nikkilä, you successfully incorporate the elements of a friend, family, around-the-clock confidant, avid proofreader, and of course, that of an adept bettor that made her way to nougat fudge – thank you for all the support and for being there for me since day one. Géraud, let's admit it, working days without links to Python and important humankind-matters would have been utterly boring; thank you for your help, kindness, and irony at its finest.

This journey is what it is because of more people: Annika Stuke, your litness is truly appreciated; Gopika Premasankar, thank you for being such a great listener and for your support; Lorenita Montoya, thank you for the language chats, Smökki times, and the cover figure. Together with Jacopo Bufalino, Marius Noreikis, Sanja Šćepanović, Heeryung Shin, and Mareike Monschein, I am so happy and grateful we share countless memories – trips, BBQs by the beach, karaoke evenings, movie nights, running ('marathon') afternoons, and Christmases spent together. Thank you all for continuing to be a source of joy and strength. And from one good place to yet another, thank you, Marc!

I would like to express my gratitude to some more people with whom I shared part of this journey. Niina Idänheimo, I admire your hard work to create a cheerful environment at work. Aila Saloranta, you welcoming me into your family means so much to me. To José Bernardo, Klaudinka Krawiecka, and Andrew Paverd, thank you for the crazy memories. Yining, Sid, Sebastian, Daniel, and Nadin – thank you for sharing happy bits of this journey. Aaro Lehtikainen, thank you for being such a big help, and for all the blueberries and Christmas cookies. Sari Mörsky, thank you for the fun flat-sharing times – your cheerfulness is addictive. To the green&fat lizard group – Antuane, Anastasiia, Matthias, Chang – I am grateful for all the good times we share; Omar Velázquez, thank you for always lending an ear and for welcoming me to your group of friends. Saani, Rina, and Yash – let there (continue to) be litness!

A special appreciation goes to my remote, yet close friends: Sameer Wagh, I cannot thank you enough for making my time at Princeton memorable, for all the help, advice, and sarcasm; Isabel and Yeohee, Princeton memories with you are very dear to me; Suzan Bayhan, your positivity is inspiring.

Mami Ruka, Lumi, Petriti, Inacuki, Valter – faleminderit për mbështetjen e vazhdueshme që më keni dhënë gjatë gjithë këtyre viteve – ju dua shumë! Iris, vizatimet e tua më bëjnë të lumtur sa herë i shoh. Ti voglio tanto bene! Amedeo Angeletti, grazie per essere una parte importante della mia famiglia e per l'ininterrotto sostegno ed incoraggiamento sin dai tempi degli studi in Italia.

Otaniemi, Espoo, May 13, 2020,

Pranvera Kortoçi

Contents

Preface	1
Contents	3
List of Publications	5
Author's Contribution	7
List of Figures	9
List of Tables	11
Abbreviations	13
1. Introduction	15
1.1 Scope and Research Questions	16
1.2 Methodology	19
1.3 Research Contributions	21
1.4 Structure of the Dissertation	23
2. Secure Bootstrapping of IoT Devices	25
2.1 Background	25
2.2 Related Work	27
2.3 The Generic Bootstrapping Architecture	28
2.4 Design Goals and Prototype Implementation	30
2.5 Conclusion	32
3. Data Collection in Large-scale IoT Systems with Uncontrolled Mobility	33
3.1 Background	33
3.2 Related Work	35
3.3 Reference Fog Architecture	36
3.4 Data Offloading Process	37
3.4.1 Adaptive Data Offloading Protocol	39

3.5	Results	39
3.6	Conclusion	41
4.	Data Collection in Large-scale IoT Systems with Semi-controlled Mobility	43
4.1	Background	43
4.2	Related Work	45
4.3	Mobile Crowdsourcing Architecture	46
4.3.1	System Model	46
4.3.2	Pricing Model of Sensory Data	47
4.4	Location-Aware Quality Data Collection	48
4.5	Results	49
4.6	Conclusion	51
5.	Data Collection in Large-scale IoT Systems with Fully-controlled Mobility	53
5.1	Background	53
5.2	Related Work	54
5.3	Multi-tier Communication	55
5.3.1	Cluster Formation	56
5.3.2	Drone-assisted Data Collection	58
5.4	Results	58
5.5	Conclusion	61
6.	Sensory Data Reduction for IoT Applications	63
6.1	Background	63
6.2	Related Work	65
6.3	Two-tier Data Reduction Method	66
6.3.1	Data Filtering at the Gateway Tier	66
6.3.2	Data Fusion at the Edge Tier	67
6.4	Results	68
6.5	Conclusion	69
7.	Conclusion	71
7.1	Future Work	72
	References	75
	Errata	85
	Publications	87

List of Publications

This thesis consists of an overview and the following publications which are referred to in the text by their Roman numerals.

- I** Mohit Sethi, Pranvera Kortoçi, Mario Di Francesco and Tuomas Aura. Secure and Low-Power Authentication for Resource-Constrained Devices. In *Proceedings of the 5th International Conference on the Internet of Things (IoT 2015)*, Seoul, pp. 30-36, ISBN: 978-1-4673-8058-4, DOI: 10.1109/IOT.2015.7356545, October 2015.
- II** Pranvera Kortoçi, Liang Zheng, Carlee Joe-Wong, Mario Di Francesco and Mung Chiang. Fog-based Data Offloading in Urban IoT Scenarios. In *Proceedings of the 38th International Conference on Computer Communications (INFOCOM 2019)*, Paris, pp. 784-792, ISBN: 978-1-7281-0515-4, DOI: 10.1109/INFOCOM.2019.8737503, April-May 2019.
- III** Pranvera Kortoçi, Abbas Mehrabi, Carlee Joe-Wong and Mario Di Francesco. Location-aware Quality Data Collection with Mobile Crowdsourcing for Time-sensitive IoT Applications. Submitted, 2020.
- IV** Farouk Mezghani, Pranvera Kortoçi, Nathalie Mitton and Mario Di Francesco. A Multi-tier Communication Scheme for Drone-assisted Disaster Recovery Scenarios. In *IEEE International Symposium on Personal, Indoor and Mobile Radio Communications (PIMRC 2019)*, Istanbul, pages 1-7, ISBN: 978-1-5386-8110-7, DOI: 10.1109/PIMRC.2019.8904140, September 2019.
- V** Liang Feng, Pranvera Kortoçi and Yong Liu. A Multi-tier Data Reduction Mechanism for IoT Sensors. In *Proceedings of the 7th International Conference on the Internet of Things (IoT 2017)*, Linz, pages 1-8, ISBN: 978-1-4503-5318-2, DOI: 10.1145/3131542.3131557, October 2017.

Author's Contribution

Publication I: “Secure and Low-Power Authentication for Resource-Constrained Devices”

The author of this dissertation designed the experimental plan, independently carried out the experimental evaluation of the prototype, analyzed the results, and wrote the article.

Publication II: “Fog-based Data Offloading in Urban IoT Scenarios”

The author of this dissertation jointly identified the problem space with the co-authors, proposed and formulated the model, designed the evaluation plan, independently implemented the simulator, analyzed the results, and wrote the article.

Publication III: “Location-aware Quality Data Collection with Mobile Crowdsourcing for Time-sensitive IoT Applications”

The author of this dissertation identified the problem space, collaboratively formulated the problem, designed the evaluation plan, independently implemented the simulator, carried out the evaluation of the proposed system, analyzed the results, and primarily wrote the article.

Publication IV: “A Multi-tier Communication Scheme for Drone-assisted Disaster Recovery Scenarios”

The author of this dissertation jointly identified the problem space with the co-authors, formulated the optimization problem, designed the evaluation plan,

Author's Contribution

provided guidance and feedback during the simulation phase, analyzed the results, and wrote the article.

Publication V: “A Multi-tier Data Reduction Mechanism for IoT Sensors”

The author of this dissertation identified the problem space, provided guidance and feedback on the evaluation of the proposed solution, and wrote the article.

List of Figures

2.1	IoT device life-cycle management.	26
2.2	Network elements of the GBA architecture.	29
2.3	GBA (a) bootstrapping and (b) usage procedures. Adapted from [67].	29
2.4	Message sequence in the prototype implementation.	31
3.1	Illustrative view of the fog computing paradigm. Adapted from [1].	36
3.2	Interactions in the reference three-tier fog network.	37
3.3	State transitions for a sensor performing collaborative offloading by role: (a) in-need and (b) helper. For the sake of readability, buffer occupancy is indicated through auxiliary variables $\alpha = L - \delta$ and $\beta = \delta + 1$. The probabilities corresponding to the top-most transitions in the diagrams realize when data is offloaded from an in-need to a helper sensor, while the probabilities at the bottom represent the event that a sensor meets a gateway.	38
3.4	(a) Drop-off as a function of the number of sensors in the network from the trace-driven simulations, (b) the CDF of the data drop-off rate, and (c) the fraction of helper sensors over time for 50 gateways.	40
4.1	The mobile crowdsourcing system in this work.	44
4.2	Main stakeholders of a mobile crowdsourcing system in this work.	45
4.3	(a) Average collected data as a function of the number of mobile users in the network for three algorithms, LQ-DCA, NL-DCA, and RL-DCA respectively, and (b) social welfare as a function of the α and β parameters [Eq.(4.1)] with 10 mobile users and 200 sensors in the network for the LQ-DCA.	50

4.4	Average (a) data collected over time, and (b) number of tasks that are either completed, (assigned but) not completed, and not assigned as a function of the task duration (i.e., $\delta = D_n - A_n$) parameter with 20 mobile users and 200 sensors in the network for the LQ-DCA.	51
5.1	A three-tier communication architecture: nodes organize themselves into clusters; in each tier, the devices use the same communication technology. The tiers are layered based on the features of these technologies, with the shortest range and the most energy-efficient one at the lowest tier. Cluster heads relay data to the upper tier, while the nodes in the highest tier communicate directly with the drone.	56
5.2	(a) Number of alive nodes over time, (b) drone hovering and flying time, and (c) energy required by a drone to complete a tour for different path planning algorithms as a function of the node density in the network.	59
6.1	High-level view of an IoT architecture and data reduction mechanisms at the gateway and edge tiers.	64
6.2	Three distance evaluation methods to find PIP points.	67
6.3	(a) Time needed to calculate the importance value T of incoming temperature data at the gateway tier, and (b) similarity between the original series and the filtered series at the gateway tier for humidity data.	68
6.4	Recovery accuracy of temperature data after performing data fusion at the edge tier.	69

List of Tables

2.1	Resource utilization of the prototype implementation.	32
3.1	Data collection schemes considered in our work.	34

Abbreviations

3GPP 3rd Generation Partnership Project

6LoWPAN IPv6 over Low power Wireless Personal Area Network

AES Advanced Encryption Standard

AKA Authenticating Key Agreement

BLE Bluetooth Low-Energy

BSF Bootstrapping Server Function

DTLS Datagram Transport Layer Security

ECC Elliptic-Curve Cryptography

GAA Generic Authentication Architecture

GBA Generic Bootstrapping Architecture

H2H Human-to-human

H2T Human-to-thing

HSS Home Subscriber Server

IoT Internet of Things

IP Internet Protocol

IPv6 Internet Protocol version 6

LoRaWAN Low Power Wide Area Network

LTE Long Term Evolution

LwM2M Lightweight Machine to Machine

MCS Mobile Crowdsourcing

Abbreviations

MEC Mobile Edge Computing

NAF Network Application Function

NB-IoT NarrowBand IoT

P2P Peer-to-peer

PIP Perceptually Important Point

PSK Pre-Shared Key

RFID Radio-frequency Identification

T2T Thing-to-thing

TEE Trusted Execution Environment

UAV Unmanned Aerial Vehicle

UE User Equipment

UICC Universal Integrated Circuit Card

1. Introduction

The Internet of Things (IoT) was first introduced to us by the MIT Auto-ID center [2] which set out the use of a radio-frequency identification (RFID) tag for physical objects, thus envisioning the Internet as made of things [26]. This shifted the traditional paradigm of simply scanning and tracking the objects toward giving them a more wide-ranging role through unique addressing schemes. That is, things could provide data upon which many applications are built. Accordingly, these smart objects form the so-called IoT by interacting with each other through Internet-based standards and a global communication infrastructure [27]. In turn, the IoT lays out a foundation for several emerging applications and services in cyber-physical systems such as intelligent transportation, smart cities, and the industrial Internet [30].

Smart objects are pervasive and ubiquitous, making them an integral part of our surroundings. They reside around us, sense and react to the environment, and report the quantities they measure. Urban environments are a particularly important application scenario for the IoT. As expected, the proliferation of the IoT has attracted considerable attention from governmental bodies, enterprises, and international standardization committees. The number of connected devices is projected to significantly increase in the coming years, with a special focus on short-range and wide-area IoT, while the laptop and mobile phone industry face only marginal increase [3] – according to a European Commission study, “the market value of the IoT in the EU is expected to exceed one trillion Euros in 2020” [4]. Moreover, the GSMA association¹ predicts that the IoT in North America will increase the number of its connections three-fold in 2025 with respect to 2017, growing faster in the industrial context (4.6x) rather than in the consumer segment (2.1x) [5]. Thus, the attention paid to IoT is truly justified by its current and future impact on several aspects of users’ lives, whether at home, work, or on the move.

IoT devices are heterogeneous and resource-constrained in terms of available energy, memory size, and computation capabilities – they include a wide variety of sensors and actuators such as smart watches, speakers, cameras, and TVs.

¹www.gsma.com

Communication technologies such as Bluetooth Low Energy (BLE) [6], Low Power Wide Area Network (LoRaWAN) [7], Sigfox [8], and NarrowBand IoT (NB-IoT) [9] have specifically targeted networks of interconnected devices with a special focus on energy consumption. These devices produce a huge amount of data that requires storage and processing. The vast variety of IoT-based applications are diverse and have different requirements in terms of data security, real-time services, and data analysis and processing [57]. Thereby, the IoT requires efficient communication solutions to sustain these ever-growing demands. To this end, different computing paradigms – cloud, edge, and fog – are leveraged in the IoT. The more traditional IoT architecture is based on cloud computing. That is, sensory data is gathered and processed in centralized data centers. The cloud offers a scalable infrastructure as well as powerful processing capabilities to address big-data storage and processing, though it incurs high latency [77]. The proliferation of the IoT and the limitations of cloud computing have emphasized the need for a new computing paradigm: edge computing [120]. Accordingly, the edge moves the processing and computation power from the cloud to the edge of the network, close to the data sources, thereby reducing the latency and lessening the burden on the access network. Similarly, the fog computing paradigm [10] creates new opportunities for the IoT. It combines the data storage and processing power of cloud computing with the low latency offered by edge computing. In fact, fog distributes the computing, storage, and networking anywhere along the cloud-to-things continuum as needed.

The IoT brings along a set of challenges, including but not limited to security, data collection (and transmission), and data reduction [96]. First, security is a primary goal for a “usable” and user-friendly IoT. In fact, the IoT is involved in many critical applications such as the exchange of goods and services in supply chain networks, thereby directly affecting the security and privacy of key stakeholders [128]. Second, data is at the core of IoT-based applications. Unsuccessful or unreliable data collection from sensors greatly hinders the applicability of the IoT in practice. Third, IoT devices produce a massive amount of sensory data which need to be transmitted to a remote server for further processing and analysis. This operation puts a high burden on the already-limited wireless resources, thereby resulting in an inefficient use of the access network. Finally, research on IoT is either highly fragmented or focuses on a single application domain or technology.

1.1 Scope and Research Questions

The research in this dissertation follows an end-to-end approach for IoT applications. Specifically, it focuses on key aspects of the communications between IoT devices that are necessary to realize IoT-based services. First, we consider how to establish a secure communication channel between an IoT device and an application server. In doing so, we address the initial configuration of smart objects

in a secure and user-friendly way. That is, we provide a mechanism to bring IoT devices into use (i.e., bootstrapping) securely that operates transparently to the user, thus requiring no human intervention. Second, we devise different data collection schemes in urban IoT scenarios, suitable for different IoT architectures (e.g., cloud, edge, and fog) and applications. We propose people-centric data collection (and offloading) protocols according to the opportunistic and participatory crowdsensing paradigms. In addition, we propose a communication and data collection protocol for the specific use case of disaster scenarios, in which mobile agents (i.e., drones) build an ad-hoc communication infrastructure to support rescue operations. Finally, we target reducing the burden of data-heavy IoT applications on the access network due to data transmission from IoT devices to a data center. To alleviate this burden, we propose a light-weight data reduction mechanism that operates at multiple tiers and considerably reduces data while retaining a high recovery accuracy.

This dissertation aims at answering the following research questions.

- *How can resource-constrained smart IoT devices be bootstrapped securely, while encountering a low power expenditure?* Smart IoT devices understand and react to the environment they reside in. However, deploying Internet-connected smart objects is challenging as they need to be correctly configured with appropriate network and security credentials. This issue is compounded by the devices' minimal input capabilities and often inaccessible locations. Hence, the opportunities for regular maintenance for installing software updates or fixing security vulnerabilities are limited. In order to enable wide-scale deployment and acceptance of these smart objects, it is thus necessary to provide a mechanism for the initial configuration – namely, *bootstrapping* – of network and security parameters without relying on human involvement. The aim is to ensure secure authentication and communication among a variety of devices and services. To this end, the security infrastructure of mobile network operators is an excellent candidate as it is scalable, dependable, and easy to use [67, 17].
- *How to efficiently offload IoT sensory data in highly dense, dynamic, and heterogeneous environments?* While urban environments are dense and dynamic, IoT devices are resource-constrained, thus making reliable data collection and scalable coordination a challenge. In fact, a long-range wireless Internet connection is either very energy hungry (as in Long Term Evolution (LTE) or WiFi) or provides only a very limited bitrate (as is the case for Narrowband IoT and LoRa) [113]. To overcome these limitations, the concept of opportunistic IoT has been introduced by applying the paradigm of delay-tolerant networking to urban scenarios [60, 22]. Though many solutions have been proposed [111, 37, 86], most of them do not capture the heterogeneity of today's dynamic urban IoT scenarios. To that end, the fog networking architecture [10] is particularly appealing, as it

captures this dynamicity by *adaptively* and *intelligently* distributing the computing, storage, and networking anywhere between the cloud and the things, as dictated by network's needs.

- *How to design efficient incentive mechanisms in mobile crowdsourcing (MCS) to induce users to collect valuable data by changing their mobility patterns?* Urban environments are an important application scenario of MCS. Effective data collection and forwarding (to a cloud server, for instance) is essential to build an efficient IoT. User participation in MCS (i.e., data collection phase) is crucial, especially as data collection incurs in energy and monetary costs, in addition to the burden for a user to modify their *planned* path [51]. Therefore, suitable MCS incentive mechanisms usually require satisfying economic principles such as truthfulness, individual rationality, efficiency (e.g., low computational complexity), as well as achieving non-negative social welfare. Key design criteria also include optimal user selection and task allocation that guarantees a target *service quality*. Therefore, the aim is to introduce an incentive-based MCS system design to *selectively* incentivize users to collect data that is *valuable* to the MCS system, while achieving a (satisfying) positive profit for all stakeholders [50, 47].
- *How can ad-hoc communication be efficiently provided during disaster scenarios?* Natural disasters (such as earthquakes, tsunamis and flooding) highly affect the existing communication infrastructure. In fact, such an infrastructure could be completely destroyed or could suffer from high access demand to its limited resources, exposing both people and rescue teams to denial of communication services. To this end, providing on-demand communication infrastructure – especially targeted to support time-sensitive rescue operations – is essential [44, 45]. This poses key questions regarding the most efficient way to establish communication in terms of time, energy, cost, and practicality. To this end, Unmanned Aerial Vehicles (UAVs) with on-board femto-cells are particularly suitable for data dissemination and alert diffusion [62, 140]. Specifically, data collection and data dissemination protocols must be tailored to realistic settings, making the energy-efficiency of such ad-hoc networks a primary concern.
- *How can the current IoT architecture enable scalable pre-processing of IoT sensory data?* IoT contributes a large volume of sensory data, given the increasing number and variety of smart devices that are already part of our lives. Indeed, the IoT's energy consumption and the burden it puts on network bandwidth, local storage, and data processing is considerable. To alleviate these effects, data must be first pre-processed prior to transmission to the cloud, for instance. This has given rise to different architectural and computing paradigms including edge, fog, and cloud [34],

to process heterogeneous and bandwidth-intensive input data [38]. Data reduction and data fusion are the main mechanisms to reduce the data generated by IoT sensors. Devising proper mechanisms and algorithms for data reduction is key to a scalable and dependable IoT. Moreover, special attention must be paid to both computational and communication requirements when such mechanisms operate at different layers of the IoT infrastructure.

This dissertation proposes novel approaches to answer these research questions. The publications in this dissertation tackle each a specific research question, as detailed next.

(i) *Initial deployment, and more specifically, bootstrapping of IoT devices.*

Publication I describes how to employ the existing 3rd Generation Partnership Project (3GPP) Generic Bootstrapping Architecture (GBA) to ensure secure authentication and communication among a variety of devices and services.

(ii) *Data collection by leveraging the power of ubiquitous smart devices (crowd).*

- Publication II devises a multi-tier data offloading protocol suitable for data-centric applications;
- Publication III formulates a social welfare maximization problem of the MCS stakeholders, subject to deadline constraints of data collection;
- Publication IV provides a collaborative data dissemination and data collection protocol that targets a fair energy consumption in an ad-hoc network during disaster scenarios.

(iii) *Data reduction for data-heavy IoT applications.* Publication V proposes a multi-tier data reduction mechanism that operates at two tiers: data filtering at the gateways and data fusion at the edge tier.

1.2 Methodology

The research in this dissertation is conducted through a combination of experimental evaluation, analytical modeling, and computer simulations.

- **Experimental evaluation.** In Publication I we provide a prototype of our proposed solution specifically designed for constrained devices. We set up an experimental testbed to evaluate the performance of the proposed solution in an Arduino Mega board connected to the Internet. We evaluate various performance metrics that highly affect the applicability of our solution to resource-constrained devices. Additionally, we repeat each experiment according to the independent replication method and

characterize the statistical significance of the obtained results through their standard deviation.

- **Analytical modeling.** We apply information theory as well as probabilistic and stochastic modeling to characterize networking and communication protocols. An analytical model of a system is expressed as a set of mathematical equations. In this context, we choose the variables of interest that directly affect our objective, then specify the relations between them as well as their range of values. The next step consists of providing an analysis of the time and computational complexity of the problem. In Publication II, Publication III, and Publication IV, the computational complexity of the problem is too high, and thus an exact solution would be impractical, especially for time-sensitive applications. Therefore, we decide upon proposing heuristic approaches to find solutions to our problems.
- **Heuristic algorithms.** The optimization problems identified in Publication II, Publication III, and Publication IV are NP-hard. This becomes a serious performance bottleneck of the proposed solution, when time and/or energy are main constraints of the system under consideration. Therefore, exact solutions to these optimization problems are not of interest – we aim at finding *suboptimal* solutions. However, prior to devising such heuristic algorithms, we first prove *theorems and/or lemmas* that provide supporting evidence to our claims and hypotheses.

When proposing a heuristic algorithm, we pay special attention to the considered use case. For instance, in Publication III we propose an *online greedy algorithm* to solve our optimization problem. In fact, exhaustive search methods are not a viable approach due to their extremely high computational complexity. Moreover, they often rely on the availability of contextual information regarding the state of (certain parameters of) the system in advance. Another example of ad-hoc design of a heuristic algorithm is shown in Publication II. We first set some conditions on the behavior of our system (e.g., the buffer occupancy of a sensor), and further proceed to show that meeting these conditions, we can derive and *guarantee* threshold values for our decision variables.

- **Computer simulations.** We evaluate the performance of the proposed models and algorithms via computer simulations, as in Publication II, Publication III, Publication IV, and Publication V. In most cases we consider an urban scenario represented by IoT sensor networks. That is, the network size is in the order of hundreds of IoT sensor devices and the geographical areas are of several square kilometers.

We chose simulation parameters that depict our IoT urban scenario as realistically as possible. We use mobility traces of people moving along streets and pedestrian paths of a real city, e.g., Helsinki. The mobility traces are derived from the Opportunistic Network Environment (ONE)

simulator [11]. The ONE is a simulation environment capable of generating node movements under different models of mobility pattern, as well as tunable parameters. These traces are then fed to a custom simulator. We implement custom Python simulators to assess the performance of the proposed algorithms based on the mobility traces obtained earlier. In all cases, we perform independent replications and report average values along with the related standard deviations, when meaningful.

1.3 Research Contributions

The contributions of five peer-reviewed publications are summarized as follows.

Publication I describes a *bootstrapping* mechanism for resource-constrained devices – that is, a mechanism to provide such devices with initial configuration of network and security parameters in order to authenticate and communicate securely with a variety of Internet services. More specifically, we rely on the existing security infrastructure of mobile operators to obtain security credentials. This infrastructure is called Generic Bootstrapping Architecture (GBA) and is defined by the 3rd Generic Bootstrapping Project (3GPP). GBA relies on the security infrastructure of mobile operators. Specifically, GBA enables to bootstrap devices whose credentials are stored in a Universal Integrated Circuit Card (UICC), yet it requires no mobile network access but only IP connectivity. Moreover, the GBA bootstrapping mechanism is suitable for resource-constrained devices as it requires no human interaction. The publication presents a secure and low-power implementation of GBA for constrained devices. In fact, we show the feasibility of leveraging the existing GBA standard without requiring any changes to it. To this end, we implement a working prototype and show that the authentication process incurs low power consumption; similarly, a GBA transaction requires even less than two seconds.

Publication II considers data offloading in highly dynamic network settings such as those of an urban environment. By contrast, IoT devices are resource-constrained, thus reliable data collection and scalable coordination becomes a challenge. We design a data offloading protocol, specifically targeting data-centric applications. We build our solution upon the fog computing paradigm, an extension of the traditional cloud. Computation, storage, communication, and management are carried out collaboratively between edge servers and end-user devices. We focus on maximizing the data offloaded to gateways before the devices (sensors) run out of storage, i.e., mitigating the *data drop-off* problem. More specifically, we consider *collaborative* data offloading among *neighboring* sensors if

the primary choice of offloading data to a gateway is not possible. We provide a mathematical analysis to model the data drop-off rates (i.e., data not successfully transmitted to a gateway) in the system. We derive our model from the state transitions of the sensors buffer occupancy over time, expressed in the form of a Markov chain. Moreover, we extend our contribution to present an *adaptive* data offloading strategy which characterizes the amount of data to be offloaded to neighboring sensors, as well as its frequency. To this end, we propose a heuristic algorithm. We then compare the results of our analytical model to those of the heuristic algorithm (trace-based simulations). The obtained results support the veracity and accuracy of our proposed models. In fact, the data drop-off rates decrease considerably compared to other baseline approaches that we consider. Specifically, the collaborative offloading process dynamically *learns* and *updates* over time its intrinsic parameters upon which data offloading is then adjusted accordingly.

Publication III analyzes Mobile Crowdsourcing (MCS) paradigms for time-sensitive IoT applications in urban scenarios. Efficient data collection and forwarding to a cloud server, for instance, is essential to build an efficient and dependable IoT. Key design criteria for MCS systems include optimal user selection and task allocation that guarantee a target service quality. The main research issues that arise in this context are the energy-efficiency as well as the realistic evaluation of the cost and revenue of the different stakeholders. Consequently, we formulate a social welfare maximization problem, defined for users to decide which sensors to visit subject to time deadline constraints. Moreover, the MCS system selectively incentivizes users to collect data that is valuable to the system itself. That is, individual sensors charge users a dynamic virtual price to collect their data. As such a problem is computationally hard, we devise a heuristic algorithm that addresses social welfare maximization as a distributed process. We evaluate our proposed algorithm via extensive simulations for a variety of mobile data collectors, task duration, and descriptive parameters that affect the social welfare. The results obtained from a real urban scenario in the city of Helsinki (Finland) show that our proposed solution drastically increases the amount of collected data and maximizes the social welfare of the system, subject to time deadlines for the data collection tasks.

Publication IV first investigates how search and rescue activities take place during the first 72 hours (referred to as the *golden relief time*) following a natural disaster such as earthquakes, tsunamis, and flooding. An operational communication infrastructure is required for efficient search and rescue operations. However, such an infrastructure is either completely destroyed or damaged, posing crucial limitations to rescue teams to assist endangered people. To this end, we leverage the ubiquitous presence

of wireless smart devices (e.g., smartphones) to assist rescue activities. We devise a multi-tier communication scheme for drone-assisted disaster scenarios to collect emergency messages in affected areas. More specifically, we propose a collaborative data collection protocol that aims at prolonging the battery life of the smart devices as well as that of the drones. Moreover, we propose efficient algorithms to control the path of the drones to collect data in the shortest time possible. Simulation results in realistic urban environments show that our proposed scheme maximizes the battery life of the smart devices, as well as minimizes the energy expenditure of the drones by means of efficient drone routes. We also demonstrate that this communication model is not restricted to a specific number of tiers, i.e., communication interfaces of smart devices.

Publication V focuses on data reduction mechanisms for IoT sensors. Depending on the specific application the IoT sensors are deployed for, their sampling rate may be high, causing fast energy and storage depletion as well as putting considerable stress on the network, if all data is transmitted to the cloud “as is”. To address these issues, we propose a multi-tier data reduction mechanism that first performs data filtering at the gateway tier, and secondly performs data fusion at the edge tier. At the gateway tier, we introduce several new techniques to extend existing algorithms to closely represent the features of a time series via a finite amount of data points. At the edge tier, we introduce a *light-weight* data fusion technique at the edge tier to fuse data from gateways, thus improving data reliability for single data sources. We evaluate the performance of our proposed data reduction and fusion technique through our custom simulator. We use real datasets that provide time-stamped topology of weather values and show that the resulting data transmitted to the cloud have a high similarity to the original data series.

1.4 Structure of the Dissertation

The rest of the dissertation is structured as follows. Chapter 2 describes the importance of providing a secure IoT to end-users, then introduces a secure and low-power bootstrapping mechanism for IoT devices. Chapter 3 presents our work on opportunistic data collection in highly dynamic and heterogeneous IoT networks. Chapter 4 similarly considers people-based data collection. However, it differs in that it provides incentives to people to increase the amount of collected data by controlling their mobility. Chapter 5 addresses data collection with mobile agents of fully-controlled mobility. It targets disaster recovery scenarios where ad-hoc networks are a necessity. Chapter 6 discusses data reduction mechanisms to support data-intensive IoT applications. Finally, chapter 7 concludes with some remarks and future development ideas. The original

Introduction

articles are presented next.

2. Secure Bootstrapping of IoT Devices

This chapter describes our work on secure and low-power authentication for resource-constrained devices. More specifically, we show how to leverage existing standards used in mobile networks to provide a scalable and dependable authentication mechanism for IoT devices. To this end, we build a prototype implementation of our proposed solution and show that it fulfills the security requirements while consuming little power and operates transparently to the user, thus requiring no human intervention.

2.1 Background

The IoT relies on the interconnection of a large number of Internet-connected devices and networks. Moreover, the communication patterns are highly heterogeneous and involve human-to-human (H2H), human-to-thing (H2T), and thing-to-thing (T2T) communications [102]. The *things* are deployed in several application domains, including but not limited to, (i) smart cities such as smart home, smart grids, public safety, and environmental monitoring, (ii) industry in agriculture, logistics, and product lifetime management, and (iii) health and well-being including medical, health care, and independent living. The vast heterogeneity and functionality of such services calls for a protocol ecosystem that allows easy integration with the Internet, as well as a unified interface for applications. Among them, Internet Protocol version 6 (IPv6) [69] is one crucial building block of the IoT.

The life of a thing starts when the device is manufactured and then proceeds through different phases: *bootstrapping*, *operational*, *de-commissioning*, and finally *end of life*. Figure 2.1 shows the life-cycle phases of an IoT device. *Bootstrapping* is the process bringing a device from non-operational to operational mode. Bootstrapping generally involves securely authenticating a device to an (application) server and establishing a channel to secure all message exchanges between them. As a result, the device becomes ready for use and a user can take ownership of it, thus being able to issue commands (control) and monitor the device. In fact, during the *operational* phase a user can query a device for the

Figure 2.1. IoT device life-cycle management.

data it has collected. In addition, maintenance operations such as software or firmware updates may take place. Moreover, the device can be de-commissioned and re-commissioned. That is, it can change ownership or simply be taken out of use because, for instance, it is faulty.

IoT devices produce highly-sensitive information. Therefore, security mechanisms that provide adequate authentication, integrity, and confidentiality are crucial. The intrinsic resource-constrained nature of IoT devices poses limits to the applicability of security protocols and bootstrapping solutions developed for other domains. Therefore, security solutions for IoT must use little memory and consume low power.

During a lifetime that spans over several years, an IoT device may require occasional maintenance such as software upgrade, reconfiguration, or even re-bootstrapping. A device might loop through these phases multiple times until it is decommissioned; that is, either the device has reached the end of its life (e.g., is defective), or it will be commissioned for another network/user. The security challenges affecting the life-cycle of a device include authentication, authorization, confidentiality, integrity, non-repudiation and availability [65]. Among these, authentication is most closely tied with bootstrapping. While bootstrapping methods can be managed, peer-to-peer (P2P), opportunistic, or hybrid methods, we will focus on the former.

The 3GPP has standardized the Generic Authentication Architecture (GAA) [17] – the security infrastructure of mobile operators – which is easy to use, dependable, and scalable. One of its components, the Generic Bootstrapping Architecture (GBA), falls under the category of managed methods, which relies on pre-established trust relations and authentication credentials and may utilize ad-hoc servers for authentication. GBA is particularly suitable for IoT devices as it provides automatic provisioning of shared keys between a device and an application server [18]. Devices whose credentials are stored in a Universal Integrated Circuit Card (UICC) may deploy GBA for bootstrapping. The same could be accomplished by using Trusted Execution Environment (TEE) and soft SIMs. Moreover, GBA requires no human interaction during the bootstrapping phase, hence, it is particularly appropriate for IoT, especially for devices that are not easily accessible.

GBA relies on the 3GPP Authenticating Key Agreement (AKA) protocol. AKA provides mutual authentication of the communicating entities and derives a

session key to protect data exchange. GBA leverages AKA to bootstrap a secure connection between an User Equipment (UE) and application server. Moreover, although GBA re-uses the credentials stored in the UICC, it requires no mobile network access but only IP connectivity to the mobile network infrastructure.

Our research aims to provide a working implementation of GBA for constrained devices under power consumption and memory constraints without sacrificing security. In fact, our implementation incorporates the minimum functionality necessary for secure authentication and requires no changes to the existing standards. To this end, we build a prototype implementation for an Arduino board and evaluate the performance of our solution in terms of resource utilization, i.e., power consumption and memory utilization.

2.2 Related Work

Authentication protocols rely on heavy cryptographic operations, thereby incurring a significant memory and computation burden on the IoT devices. The literature presents different solutions to address the limitations of existing authentication protocols for IoT scenarios, either by partially delegating computation to another entity (e.g., a delegation server), or by reducing the overhead in the authentication protocol.

The work in [43] proposes a flexible and lightweight authentication protocol based on Elliptic-Curve Cryptography (ECC) that reduces the resource requirements at the devices. That is, the heavy cryptographic processing moves from the resource-constrained device to an authentication terminal, hence mitigating the burden at the device. Similarly, [70] proposes an architecture which offloads part of the security computation task to a delegation server; the connection establishment procedure and the actual protection of the application data with the Datagram Transport Layer Security (DTLS) protocol are kept separate. By delegating the connection establishment to an external server, the corresponding public-key cryptography operations take place in the server, while the device itself needs only to implement symmetric-key cryptography to secure application data. The work in [71], instead, focuses on techniques to reduce the overhead generated during a DTLS handshake by pre-validating certificates and providing a session resumption method that minimizes transmission overheads, in addition to delegating the association establishment to other powerful devices. Likewise, [112] aims at reducing the DTLS overhead by applying compression techniques while leveraging the IPv6 over Low power Wireless Personal Area Network (6LoWPAN) standard. Our approach, by contrast, does not rely on certificates, handshake offloading, or header compression. It builds upon the existing security infrastructure of mobile operators and requires no changes to existing protocols.

Considerable research work has been carried out on secure bootstrapping of ubiquitous devices, with results presented in literature. For instance, [118]

proposes a cloud-based solution to bootstrap ubiquitous displays, that can also be applied to smart devices. However, it relies on enterprise Wifi and requires explicit actions by the user to perform the initial configuration of the devices. A GBA-solution, by contrast, requires no user interaction.

The work in [19, 63] leverages the GBA architecture to provide authentication for wireless sensor nodes. While both target the ZigBee specification, [63] specifically requires additional network elements, such as a smartphone, for the role of a gateway. Moreover, [81] provides some considerations and remarks on how to leverage GBA in resource-constrained devices. It proposes modifications to the bootstrapping procedure and suggests the use of CoAP instead of HTTP during such a process. In contrast to these solutions, ours is not tied to a specific communication technology (such as ZigBee) but only requires IP connectivity to the Internet and no additional network elements or modifications to the existing standards and infrastructure.

Considerable effort has been spent by the wireless industry on standardizing flexible protocols to manage the life-cycle of an IoT device, with special attention given to security [100]. This is exemplified by *OMA SpecWorks*¹ and its Lightweight Machine to Machine (LwM2M) protocol. LwM2M is a device management protocol, designed specifically for sensor networks in an M2M (machine-to-machine) environment². It covers the entire life-cycle of a device: bootstrapping, client registration, device management and service enablement, and information reporting [12]. The wireless community (including a wide range of companies worldwide such as ARM Pelion, AT&T IoT Solutions, Ericsson's Dynamic Digital Interaction (DDI), Huawei's OceanConnect IoT Platform, and Nokia's IMPACT IoT Platform) has contributed to the open source implementation of the LwM2M and made it available to the public. The work in [110] investigates the memory footprint of introducing LwM2M into the client side of the IoT protocol stack. Similarly, other works such as those in [123, 20] show how to efficiently implement LwM2M in the application layer of a machine-to-machine system for smoother integration of IoT services.

2.3 The Generic Bootstrapping Architecture

Our solution is built on top of the Generic Bootstrapping Architecture (GBA), which includes four major network elements: Home Subscriber Server (HSS), Bootstrapping Server Function (BSF), Network Application Function (NAF), and the User Equipment (UE) or terminal (see Figure 2.2). The HSS contains subscriber data and manages subscribers' identity, access and security; moreover, it shares a long-term key K with the UICC in the terminal. The BSF is a server, specific to the GBA architecture, that facilitates the bootstrapping procedure between an UE and an application server, namely, the NAF. GBA requires that

¹<https://www.omaspecworks.org/about/>

²<https://www.omaspecworks.org/what-is-oma-specworks/iot/lightweight-m2m-lwm2m/>

Figure 2.2. Network elements of the GBA architecture.

a NAF and a BSF must establish a secure communication link to authenticate users. Such a secure link can be established, for instance, with certificates or TLS. In fact, the 3GPP mandates no particular mechanism to establish such a secure link.

A time-limited GBA master key K_s , shared between the UE and the BSF, is generated by using the permanent secret shared between the UICC of the user and the mobile network operator. Consequently, the BSF generates a NAF-specific session key K_{s_NAF} which is then sent to the NAF. This session key allows mutual authentication and secure communication between the UE and the NAF. Figure 2.3a shows the message flow of a GBA bootstrapping process, whereas Figure 2.3b shows how a shared secret is derived to provide mutual authentication and secure communication between an UE and an application server (i.e., the NAF). The message exchange – hence the interactions between the network elements – takes place on top of different interfaces among the network elements. The message flow of a bootstrapping usage procedure consists of the following steps (Fig. 2.3b).

- An UE generates an application-specific session key K_{s_NAF} every time it attempts to access a specific application in a NAF.
- The UE sends an application request to the NAF. Such a request contains the Bootstrapping Transaction Identifier (B-TID) and an application-specific message.

Figure 2.3. GBA (a) bootstrapping and (b) usage procedures. Adapted from [67].

- The NAF uses the B-TID and its own identifier (the NAF-ID) to query the BSF.
- The BSF, in turn, queries its database upon receiving the B-TID. Moreover, it checks whether the NAF is authorized to receive application-specific keys for the given subscriber. To that end, the BSF checks the profile information of the user received from the HSS.
- If the BSF finds a matching B-TID in its database, it uses the corresponding K_s and the NAF-ID to derive the application-specific key K_{s_NAF} .
- The BSF then sends the generated K_{s_NAF} and part of the user profile concerning the specific application to the NAF.
- Finally, the NAF receives and stores the data, allowing it to communicate securely with the UE by utilizing the K_{s_NAF} key to protect their subsequent message exchange.

2.4 Design Goals and Prototype Implementation

We leverage the GBA architecture introduced in Section 2.3 as a bootstrapping solution to achieve the following set of functional requirements.

- (i) *Suitability for resource-constrained devices.* That is, the authentication process should be light-weight, and thus operate on low-end devices with limited memory as well as computing capabilities.
- (ii) *Independence from specific communication technologies.* The designed solution should not rely on a certain access network for the constrained device, but rather leverage an existing standard-compliant communication infrastructure.
- (iii) *Transparency to the user.* The authentication process should be fully automated, thus it should require no user interaction. Moreover, the software implementation should not require any additional input/output capabilities of the device, other than those needed to establish network access.
- (iv) *End-to-end security.* Both the bootstrapping process and future communications should be secure in terms of data authenticity, confidentiality, and integrity.

Our GBA implementation limits resource utilization in multiple ways. GBA relies on either HTTP Digest [14] or Pre-Shared Key (PSK) TLS [16]. In the former case, we restrict use of the HTTP stack only to the minimum amount of functionalities. We can do so due to the fact that resource constrained devices

Figure 2.4. Message sequence in the prototype implementation.

do not need an entire HTTP client library to complete a GBA authentication transaction. In fact, the messages exchanged during an authentication process can be sent directly on top of TCP, without the need of a full HTTP protocol stack. Similarly, response messages can be directly parsed from the packets received from the transport layer. As error checks are not needed, unknown packets trigger the re-start of the message exchange, thus saving computational resources. Moreover, GBA relies on standard encryption algorithms, such as the Advanced Encryption Standard (AES) [15]. We leverage the fact that many resource-constrained platforms are provided with an AES hardware engine to offload cryptographic computations. If such a hardware engine is missing, there exist software-based implementations of the AES specifically tailored for IoT devices [41]. Furthermore, our implementation removes functionalities from memory when they are not needed any more. For instance, all GBA-related code and libraries are de-allocated from memory upon successful completion of the bootstrapping procedure. In fact, only the B-TID and K_s_NAF need to be retained in the memory. This allows the freed-up memory to be re-allocated as needed for other purposes. Finally, the GBA implementation typically requires a state machine to keep track of the messages exchanged with the BSF and the NAF. However, this results in using a large amount of memory, alongside error handling. Therefore, we implement a simple hard *failover* that aborts a GBA authentication transaction in case of error to limit the memory requirements and the complexity of the system.

Figure 2.4 shows a sequence of the message flow of our implementation. We employ an Arduino Mega board³ and connect it to the Internet with an Ethernet shield. The Mega board features an 8-bit ATmega2560 microprocessor, 8 KB of RAM, 4 KB of EEPROM and 256 KB of flash memory. We use the Monsoon Power Monitor [97] to measure the power consumption of the Mega board. In order to evaluate the performance of the implemented solution, we focus on the

³<http://www.arduino.cc/en/Main/ArduinoBoardMega2560>

(i) memory utilization, (ii) execution time, and (iii) average power consumption metrics.

Parameter	Value
Program size	42,740 bytes
Data size	2,893 bytes
Average duration of one GBA transaction	$1,473.6 \pm 46.73$ ms
Average power consumption	$1,114.97 \pm 6.55$ mW

Table 2.1. Resource utilization of the prototype implementation.

Table 2.1 summarizes the resource utilization of our prototype: it shows the overall size of the program, the data size of the executable (i.e., the static data defined in the code), and the average time and power consumption of a GBA bootstrapping process. We replicated each experiment 15 times and derived the average values along with the related standard deviations. We see that both the size of the program and the data segment are well below the maximum memory sizes of the Mega board. The average duration of one GBA transaction is approximately 1.47 s; this includes the whole sequence of message exchanges shown in Figure 2.4. The power consumption of one GBA transaction is on average $1,115 \pm 6,55$ mW, which compared to the baseline (idle state) of around 1,080 mW, corresponds to a power overhead of only 45 mW.

2.5 Conclusion

This chapter presented a method to establish a secure connection between a resource-constrained device and an application server. We leveraged the GBA, a standard solution in mobile networks without the restriction of using a cellular connection, which relies on pre-configured security credentials stored in the UICC of a device. This authentication method requires no user interaction, making it particularly suitable for IoT devices, which are often installed in inaccessible places. Moreover, our prototype implementation incurs in low memory utilization and power consumption, and completes the authentication process in a short time. A promising extension of our work consists of securely bootstrapping a group of IoT devices belonging to the same user at once. However, the design of such a solution requires particular attention to correctly associating the IoT devices with their owners and not with other users nearby.

3. Data Collection in Large-scale IoT Systems with Uncontrolled Mobility

This chapter presents our work on reliable data collection in highly dynamic and heterogeneous IoT networks. Our solution is based upon the fog computing paradigm and it devises a people-based data offloading protocol specifically tailored for data-centric applications. Ideally, sensors *opportunistically* offload their data to mobile gateways with unknown and uncontrolled mobility, whenever possible; and if not, to a neighboring sensor. We aim at maximizing the data successfully relayed to a data center. In doing so, we identify network-wide parameters that characterize collaborative data offloading among sensors, and use such parameters to design a data offloading algorithm that adapts to network conditions (i.e., expected probability of a sensor to meet a gateway).

3.1 Background

The IoT ecosystem is a key enabler for a wide range of applications in urban scenarios. The IoT connects everyday objects and devices to one another and to remote data centers and services within them. The IoT is transforming businesses by providing a huge variety and amount of data to data consumers, who in turn transform the data into services [13].

Different IoT architectures – cloud, edge, and fog – treat data collection differently. Traditional IoT architectures have been developed with a well-defined scope and operational functionality in mind. For instance, cloud-based sensing models leverage the high processing capacity and low energy impact of the cloud to enable distributed data collection for offline querying [103]. Most cloud solutions are specially tailored for data-heavy and delay-tolerant applications as data is processed in powerful remote data centers with (possible) limited or no connectivity. As a result, the powerful data processing comes at the price of high latency. Therefore, cloud computing has no means to favor the ever-growing demand for real-time, low latency services. The current state of the IoT demands real-time processing of time-sensitive data. Mobile edge computing (MEC) [115], in fact, reduces the latency and lessens the burden on the backhaul links to the backbone network by performing data storage and processing locally, at the edge

of the network [79]. Similarly, the fog computing addresses the limitations of cloud computing by defining an architecture with emphasis on information processing near the end devices. In fact, the fog computing places the computation power *intelligently* anywhere along the continuum between the cloud and end devices by adapting it to prevailing network conditions [13]. That is, systems now migrate data and communication control to the edge of the network, shifting toward a *people-centric* approach as opposed to a service-centric one.

Data collection presents in different forms such as data collection for delay-tolerant or time-sensitive applications, data collection assisted either actively or passively by people, and data collection with mobile elements whose mobility is either controlled or not. These categories are not orthogonal. However, we focus on three main categories as they are the more challenging ones, especially for urban IoT applications: (i) data collection *opportunistically* assisted by people (uncontrolled mobility), (ii) data collection *actively* assisted by people (semi-controlled mobility), and (iii) data collection *actively* assisted by ad-hoc agents (controlled mobility). Table 3.1 summarizes the mobile data collection schemes we consider in our work in the scope of this dissertation.

Mobile Data Collection		
<i>People-centric</i>		<i>Agent-based</i>
Mobility Model		
<i>Uncontrolled</i>	<i>Semi-controlled (Participatory)</i>	<i>Controlled</i>

Table 3.1. Data collection schemes considered in our work.

Long-range wireless Internet connection for resource-constrained IoT devices is either energy-hungry (e.g., Long Term Evolution or WiFi) or provides low data rates (e.g., Narrowband IoT and LoRa) [113]. Such limitations have given rise to *opportunistic* IoT, by applying the paradigm of delay-tolerant networking to urban scenarios [60, 22].

Opportunistic data collection is at the core of solutions for mobile and delay-tolerant data collection [107]. That is, sensors sense phenomena around us and opportunistically offload their data to other entities whenever the opportunity arises. These mobile entities, namely gateways, are special support nodes such as cars or people carrying smartphones [107] and act as intermediate data collectors. That is, they store the data transferred by sensors and further transmit it to a remote data center for storage and analysis.

Data offloading occurs whenever a mobile gateway is within the transmission range of a sensor, e.g., a person walks by a sensor. However, the frequency of visits to sensors by mobile gateways is low in areas with low population density and limited mobility of people. As a result, sensors will soon run out of local storage as they keep storing sensory data and not be able to offload them. Therefore, offloading their data before running out of storage is crucial and requires co-operation between sensors and gateways. Two main factors

affect such co-operation: the limited computation capabilities of IoT sensors and the unpredictable mobility pattern of the gateways. With these considerations in mind, we aim to reduce the data being dropped off in the network as a result of sensors not being able to offload their data to mobile gateways, henceforth referred to as the data drop-off problem.

We propose a multi-tier data offloading protocol specially suitable for IoT urban scenarios and data-centric applications. Ideally, sensors first offload their data to a gateway whenever possible, and if not, to a *neighboring* sensor. However, this requires the sensors to make *informed* decisions whether or not to store data from neighbors based on their buffer occupancy level. That is, sensors adapt their offloading behavior to changes in gateway mobility over time. To this end, we propose an interaction scheme among network elements – sensors, gateways, and a network controller – that encounters no significant overhead. Our data offloading solution is based upon the fog architecture [13] which is particularly suitable to our problem as it *intelligently* considers the available resources on each network element.

3.2 Related Work

The IoT relies on remote data centers, such as the cloud, to process data generated by low-end IoT devices and provide services to end users. Therefore, data collection in opportunistic communication scenarios of IoT sensor networks is widely studied in the literature [127, 134]. Data collection sees many facets and varies from data collection with (i) static, unconstrained designated nodes, (ii) mobile, unconstrained designated nodes with controlled mobility, (iii) mobile, unconstrained designated nodes with uncontrolled mobility, and (iv) mobile, resource-constrained nodes with uncontrolled and unpredictable mobility. This chapter focuses on the latter as it is a clear representative of opportunistic data offloading with mobile elements with uncontrolled mobility, as well as the most non-trivial case of data offloading in urban scenarios and highly heterogeneous IoT networks in terms of resources of end-devices.

The work in [83] proposes different heuristics for data dissemination from the infrastructure to mobile end-devices under buffer constraints. However, data loss patterns due to limited sensor buffers are different from those of data offloading from end-devices to the cloud. The work in [86], in fact, proposes collaborative data offloading from mobile devices to the infrastructure to improve communication reliability. Data collection in wireless sensor networks through mobile sinks [37, 137, 92] focuses on maximizing the data collected by means of mobile sinks: while [52] assumes nodes have sufficient buffer to store all data and sink mobility is known a-priori, [89] relies on intermediate, powerful nodes to store the data which is then collected by mobile sinks. Similarly, [129] maximizes the amount of collected data by constructing a path for mobile sinks under energy constraints.

Figure 3.1. Illustrative view of the fog computing paradigm. Adapted from [1]

Other works instead focus on predicting the arrival of mobile sinks either via distributed reinforcement learning at sensor nodes [119] or by prediction framework based on temporal-difference learning [106]. Literature on mobile crowdsensing [59] is rich with studies regarding optimal deployment of mobile access points to support task-oriented sensing [74]. Similarly, [133] considers specific tasks assigned to mobile users as a function of the probability to carry out the tasks based on their mobility and deadline of the tasks.

While our work shares similarities with the literature on mobile crowdsensing, it differs on that it considers explicit *collaboration* among static sensor nodes, no prior knowledge of gateway mobility patterns, no powerful and resourceful mobile sinks, and leverage mobile users to collect sensory data due to periodic data reporting from sensors rather than task-oriented.

3.3 Reference Fog Architecture

We propose a solution to mitigate the data drop-off problem that is based on the fog networking paradigm [10]. The fog network of our solution comprises three tiers, as shown in Figure 3.2. At the bottom tier we have *IoT sensors*, wireless embedded devices with limited resources. These sensors are static and collect data from their surroundings through Bluetooth Low-Energy (BLE), a medium-range communication technology. The data is stored locally in the buffer and forwarded to other neighbors or to the intermediate tier based on available communication opportunities and sensors' buffer occupancy. The intermediate tier comprises *mobile gateways*, that is, mobile devices (e.g., smartphones carried around by people) in an urban area. These gateways receive data from sensors and forward them to the top tier located in the cloud through two radio transceivers, one for receiving data from IoT sensors and another for Internet connection, respectively. While certain sensors – located in areas with a high user mobility – encounter mobile gateways frequently, others do not. That is, some sensors offload their data to mobile gateways often, while other sensors experience full buffer occupancy and hence high data drop-off rates. It is thus

Figure 3.2. Interactions in the reference three-tier fog network.

important that sensors that are rarely in contact with a gateway get help to store (and ultimately, offload) their data by the other sensors. To this end, the *central network controller* learns about contact opportunities with gateways and *logically* divides the sensors into *in-need* and *helpers*. This is achieved as the central network controller receives status information (e.g., contact opportunities) from the gateways through which it forwards back control messages to sensors. These control messages update the in-need – helper dynamics in the network.

Sensors locally update their status as either in-need or helper sensor as a function of the probability of encountering a gateway and buffer occupancy, as well as control messages they receive from the central network controller. These control messages are two offloading parameters, ϵ and δ , and characterize the likelihood of a sensor dropping data and the number of data items a sensor offloads, respectively. The central network controller evaluates ϵ and δ by performing data analytics as described below.

3.4 Data Offloading Process

Before proceeding further, we first introduce some preliminary notation that is used throughout the rest of this chapter.

We consider a network including the set $\mathcal{S} = \{s_1, s_2, \dots, s_M\}$ of $M = |\mathcal{S}|$ static IoT sensors deployed at fixed locations, as well as the set $\mathcal{U} = \{u_1, u_2, \dots, u_N\}$ of $N = |\mathcal{U}|$ mobile gateways. Each sensor has a buffer of size B and periodically samples items of $d \ll B$ bytes each every time slot. The buffer becomes full after L time slots if no gateway is met. A sensor can transmit all the data within one time slot; a time slot is of fixed size. Sensors have no prior knowledge about the mobility patterns of the gateways. Hence, they can only estimate the buffer occupancy at time t as a function of the probability $p_m(t)$ of a sensor m to encounter any of the N gateways at time t .

The buffer occupancy b_m of sensor m transitions over time from one state to the other as shown in Figure 3.3a for an in-need sensor and Figure 3.3b for a helper sensor. *In-need*: the arrow at the top means sensor gains d bytes of data due to its sensing task, the arrow at the bottom means data is successfully offloaded to a gateway, while the reversed arrow at the top means data offloading from this in-need sensor to neighboring helper sensors when buffer is filled. *Helper*: if

Figure 3.3. State transitions for a sensor performing collaborative offloading by role: (a) in-need and (b) helper. For the sake of readability, buffer occupancy is indicated through auxiliary variables $\alpha = L - \delta$ and $\beta = \delta + 1$. The probabilities corresponding to the top-most transitions in the diagrams realize when data is offloaded from an in-need to a helper sensor, while the probabilities at the bottom represent the event that a sensor meets a gateway.

the helper sensor does not detect a gateway nearby, its buffer gains by d bytes due to its sensing task, but gains another δd bytes when any of its neighboring in-need sensors need to offload data. Based on the rich network dynamics described in Figure 3.3 – that is, the buffer occupancy states over time of in-need and helper sensors – the central network controller provides an adaptive data offloading strategy as dictated by ϵ and δ . These parameters must satisfy certain conditions. More specifically, the threshold ϵ of the data drop-off rate for a helper sensor must satisfy:

$$\epsilon < \left(1 - \frac{1}{L}\right)^{L+1}$$

while the amount of data δd offloaded to helper sensors must satisfy:

$$\delta < 1 + (L - 1) \left(1 - \frac{1}{L}\right)^{L+1}.$$

These conditions ensure that (i) helper sensors will have some available buffer to store offloaded data from in-need sensors, and that (ii) the amount of data offloaded by in-need sensors is less than the expected available buffer at any helper sensor so that the latter can accommodate the data it receives. These conditions must be met to avoid the following effects: only a few sensors would be allowed to offload their data (large ϵ); some sensors which could have stored offloaded data are designated as in-need sensors, resulting in dropped data (small ϵ); buffer overflow of the sensors (large δ); and in-need sensors being triggered to offload too much data (small δ).

Algorithm 1: Data offloading protocol run by sensor m

```

1 foreach time slot  $t$  do
2   if a gateway is in range then
3      $p_m \leftarrow (1 - \lambda/t)p_m + \lambda/t$ ;
4     transmit all data and  $p_m$  to the gateway;
5     obtain new  $\epsilon$  and  $\delta$  from the gateway;
6   else
7      $p_m \leftarrow (1 - \lambda/t)p_m$ ;
8     if  $p_m \leq 1 - \epsilon^{\frac{1}{L+1}}$  and  $b_m(t) = B$  then
9       extract and broadcast  $\delta d$  data // IN-NEED
10    else if  $p_m > 1 - \epsilon^{\frac{1}{L+1}}$  and  $b_m(t) < (L - \delta)d$  then
11      store received  $\delta d$  data // HELPER

```

3.4.1 Adaptive Data Offloading Protocol

Given ϵ and δ reported by the central network controller to the sensors through the gateways (recall Figure 3.2) as well as the (local) probability p_m of a sensor to meet any gateway, sensors run the data offloading protocol shown in Algorithm 1. Sensors offload all their data to a gateway whenever they meet one, and obtain updated ϵ and δ parameters from the central network controller as well as the probability p_m (lines 2-5). However, if a sensor meets no gateway at time slot t , it first updates the probability p_m of meeting a gateway and compares it against a threshold probability which depends on the ϵ value. If p_m is below the threshold and the buffer is full, the sensor is in-need and it broadcasts δd amount of data (lines 8-9); however, if p_m is above the threshold and the buffer can accommodate at least δd amount of data, it will store data from an in-need sensor (lines 10-11). The more frequently a sensor meets a gateway, the more data is successfully transmitted and the more accurate the network-related parameters ϵ and δ become. This clearly incurs some overhead, that could become substantial in very large networks. In such a case, it would be viable to define a tradeoff between the efficiency of offloading and the frequency of communication with the central network controller.

3.5 Results

We evaluate the performance of our proposed collaborative data offloading protocol (recall Algorithm 1) in terms of data drop-off rates in the network. We implement a custom Python simulator to assess the performance of our proposed solution against three different schemes: (i) *no offloading*: sensors do not collaborate to offload each other's data, (ii) *naive offloading*: sensors offload one

Figure 3.4. (a) Drop-off as a function of the number of sensors in the network from the trace-driven simulations, (b) the CDF of the data drop-off rate, and (c) the fraction of helper sensors over time for 50 gateways.

data item only whenever their buffer is full, and (iii) *static offloading*: sensors offload 20% of their buffer size, irrespective of network conditions (i.e., ϵ and δ). We consider a metropolitan area of 4.5 by 3.5 kilometers and vary the number of the deployed static sensors as well as the number of the mobile gateways. We generate mobility traces – through the ONE simulator v1.6.0 – based on the streets, roads, and pedestrian paths in the city of Helsinki. Pedestrians (i.e., mobile gateways) walk with a speed between 0.5 and 1.5 m/s. The transmission range of the sensors is fixed to 100 m, the buffer size of $B = 5000$, and data item of size 10. We set the initial probability a sensor m to meet any gateway n to $p_m = 0.2$.

Figure 3.4a shows the data drop-off rate as a function of the network size (i.e., number of sensors) with 50 gateways. The data drop-off rate is almost constant, irrespective of the number of sensors, in the case where sensors do not collaborate with each other (no offloading). Data drop-off rates decrease slightly with the network size for the naive and 20% static offloading, while there is a significant improvement in successful data offloading for the collaborative offloading scheme. However, the drop-off rate increases with the number of sensors. This trend is explained by the fact that gateways frequent mostly specific locations (e.g., city center, big cross intersections), while only a small fraction of sensors is located in these spots. Therefore, the number of in-need sensors increases faster compared to helpers, leaving fewer helper sensors to help more in-need neighbors. Figure 3.4b shows the cumulative distribution function (CDF) of the data drop-off rates for a network size of 50 sensors and 50 gateways. Similarly, the CDF is shown for 4 different schemes. While for the no offloading, naive, and static offloading schemes most of the sensors present

data drop-off rates of around 60%, our collaborative scheme outperforms them with a data drop-off rate of less than 20%. Figure 3.4c shows the fraction of the helper sensors as a function of simulated time for various network densities and 50 gateways. While all sensors are initialized to $p_m = 0.2$, they start reporting the actual p_m value over time to the gateways. In turn, gateways report p_m to the central network controller which then recalculates the ϵ and δ parameters. Recall that sensors change their role according to these values (refer to line 8 and line 10 in Algorithm 1). That is, the sensors *learn* and *update* their status according to network statistics, and thus execute collaborative offloading among themselves. It is worth noting that the fraction of helper sensors increases faster for lower network densities. In fact, the higher the number of sensors in the network (hence, higher sensor cardinality per cluster), the more there are in-need sensors per helper sensor. Similarly, a lower network density results in helper sensors being able to help in-need sensors without running out of buffer space.

3.6 Conclusion

This chapter showed how we leveraged the fog computing paradigm to provide a data offloading scheme for IoT sensor networks in urban scenarios. More specifically, the network consists of fixed sensors, mobile gateways of uncontrolled mobility, and a central network controller. The collaborative data offloading protocol among the sensors reduces the data drop-off in the network by relaying the data among the sensors in a multi-hop scheme until it reaches a mobile gateway. Sensors learn about their capabilities to help neighboring sensors over time, and store and transmit the data offloaded to them to a gateway. Extensive trace-driven simulations showed that our proposed solution drastically reduces the data drop-off compared to other approaches. However, we noticed that the benefits of our solution diminish in areas with limited mobility of people. Therefore, our study could be extended to investigate a support infrastructure to profitably apply our solution in such scenarios. Moreover, the communication overhead in exchanging control messages among the different elements in the considered fog network could become substantial in very large networks. As a consequence, a possible direction for future research would be to explicitly consider trading off accuracy for lower overhead. This could be accomplished, for instance, by limiting the frequency of control messages reported to the central network controller.

4. Data Collection in Large-scale IoT Systems with Semi-controlled Mobility

This chapter describes our work in providing reliable data collection for IoT applications. Our approach is based upon the opportunistic crowdsourcing paradigm with the addition of incentive mechanisms to ensure user participation. Specifically, we aim at providing a smart incentive mechanism for crowdsourcing campaigns to provide location-aware, quality data within given time deadlines set by time-sensitive IoT applications, i.e., data consumers. To this end, we propose an algorithm to maximize the collection of quality data that are relevant to data consumers with a special focus on maximizing the social welfare of the crowdsourcing system.

4.1 Background

Chapter 3 described one people-centric approach of collecting data from static sensor nodes with mobile users of uncontrolled mobility. We proposed algorithms for data offloading from sensor nodes to gateways by leveraging collaboration among static sensors to relay each other's data. Yet another approach of people-centric data collection consists of outsourcing data collection to the crowd (i.e., people equipped with mobile smart devices such as smartphones) [32], as considered in this chapter. Accordingly, the crowd senses and collects data on phenomena of interest for diverse applications such as logistics, security, entertainment, and environment [136]. In fact, data collection paradigms that leverage the ubiquitous nature of mobile devices have received great attention and are widely deployed as data consumers do not need to invest in additional infrastructure [36]. For instance, leveraging mobility for data collection is crucial in remote areas where there is no communication infrastructure or limited connectivity to it. These data collection paradigms are the basis of mobile crowdsourcing (MCS) systems and heavily rely on incentives to ensure people (user) participation. MCS falls under *participatory* sensing (recall Table 3.1) as users are explicitly incentivized to perform data collection tasks – that is, sample data from different locations at specific times. Operating a successful MCS campaign requires efficient collection and transmission of data to a remote

Figure 4.1. The mobile crowdsourcing system in this work.

data center (e.g., the cloud) for further processing. With assisted data collection, mobile crowdsourcers *actively* change their mobility pattern and collect data from specific regions of interest to data consumers [37]. To this end, the most prominent challenge in MCS data collection is to induce and incentivize users to change their mobility pattern to collect data from specific regions of interest. Typically, the data must be collected within given time deadlines and guarantee a target service quality [108, 64, 56].

Figure 4.1 shows a typical MCS system and its main stakeholders: sensor devices, the crowdsourcers, edge devices, cloud server(s), data consumers, and the MCS campaign organizer. Ensuring user participation [51] requires identifying a fair remuneration for the sensing effort of the crowd [51, 75, 64, 141]. In general, the MCS campaign must result in positive profit for all the stakeholders (shown in Figure 4.2), whose costs and benefits are intertwined among each other, thereby creating complex dynamics in the system.

Incentives must be allocated in such a way to guarantee a target service quality by optimally selecting users to perform the given tasks within a time deadline [108, 56]. While estimating the cost and revenue is rather straightforward for stakeholders like sensors, data server(s), or data consumers, that is not the case for mobile users. In fact, the (qualitative) cost of users having to change their habitual path must be expressed in quantitative terms (e.g., money). Additionally, this cost is *user-specific* as it relates to the behavior of individual users – that is, it evaluates the willingness of a user to participate in the MCS campaign. Data quality, similarly, affects a MCS campaign. Data is considered of high quality and is valuable to data consumers only if it comes from well-functioning sensors, is up-to-date (recent), and is collected from regions of interests [68, 143]. To this end, we focus on *selectively* incentivizing users to collect relevant data.

We consider collecting time- and location-dependent data, similar to [64, 143, 75]. We tie the *timeliness* and *uniqueness* of the data to the concept of *data quality* and use them interchangeably. Timeliness characterizes data collected within a given time frame, whereas uniqueness represents data that is not a duplicate of data already collected by other users. Mobile users individually

Figure 4.2. Main stakeholders of a mobile crowdsourcing system in this work.

decide whether to complete a task to collect location-aware quality data within a certain time deadline based solely on the expected profit. Specifically, sensors charge mobile users a dynamic price to collect their data. The price varies in function of the quality of the sensory data as well as the frequency of user visits to the given region of interest. We formulate the users' decision – given a set of sensor's prices for their data – of which sensors to visit (if any) as a social welfare (profit) maximization problem of the MCS system. We then propose an online algorithm that maximizes the social welfare while optimizing for the data quality and the time deadline set for the data to be collected.

4.2 Related Work

Smartphones can unravel crowdsourcing's full potential by letting users contribute to complex problem solving [32]. MCS is a distributed problem-solving model that takes advantage of the pervasive and ubiquitous nature of smartphones. Outsourcing sensory data collection to the crowd [108, 135, 76, 78] places a special focus on challenges such as optimal recruitment of mobile workers to ensure a target service and data quality. MCS inherently suffers from duplicate as well as malicious data contributed by *infected* sensors or the crowd. In these cases, addressing the truthfulness and integrity of the data becomes of uttermost importance [76], especially for data-sensitive applications. This brings to attention the challenging task of recruiting trustworthy crowdsourcers. That is, an efficient and effective MCS must ensure sufficient participants. This is achieved by providing proper incentives – usually in the form of entertainment, service, or money – to stimulate users to participate [142].

The works in [51, 75, 64, 141] focus on pricing mechanisms that ensure an adequate user participation and reduce sensor's sensing effort, i.e., their cost. This cost considers not only the effort in completing the task, but also the demand for data from data consumers. We take a similar approach and consider the cost of completing a task. While the main causes of energy consumption in MCS correspond to raw sensor data sampling, local analytics, and reporting of

sensory data [125]. In this respect, we put particular stress on the user-specific component of the cost – that is, we selectively incentivize individual users to carry out tasks based on their willingness to change their route. Moreover, we set no limit neither on the sensing tasks a user chooses (as opposed to [31]), nor on the area a user can visit as long as it complies with the service quality requirements (in contrast with [143]).

There are different options to ensure user participation. One traditional approach consists of allocating satisfactory rewards to stimulate users to participate in a MCS campaign [50, 141]. Our scheme differs from the traditional one in that it provides mobile users with expected cost and revenue evaluations prior to task completion, rather than after. Other works focus on optimizing the assignment of the tasks such that a reasonable trade-off between task quality (e.g., data collection times, task duration and spatio-temporal coverage) and task completion cost (e.g., user recruitment, data forwarding) is achieved [56]. While we focus on similar aspects of a MCS campaign, we pay special attention to complex network dynamics; they arise as a result of the time-varying price of the sensory data that accounts for changes in the users' frequency of visits to the sensors as well as the quality of the data themselves.

4.3 Mobile Crowdsourcing Architecture

We propose an online data collection algorithm that enables mobile users to collect location-aware and quality data while it maximizes the social welfare of the MCS system. The reference MCS system shown in Figure 4.1 consists of a MCS campaign organizer that resides in the cloud, edge servers, sensors, mobile users (MUs), and data consumers. MUs are people that carry personal devices such as smartphones, while data consumers are people or companies that are interested in buying sensory data, upon which they create value. Furthermore, static sensors are deployed in a large urban area; they sense physical phenomena in their surroundings and collect data correspondingly. Data collection from the environment takes place through short or medium-range technologies such as BLE; consequently, data is stored locally in sensors' buffer. Data consumers submit a request to access (i.e., buy) sensory data to the crowdsourcing platform (e.g., a cloud server).

4.3.1 System Model

Static sensors are deployed in a sensing area that consists of K regions of interest (RoIs) denoted by the set $\mathcal{R} = \{r_1, r_2, \dots, r_K\}$. In each region r_k may reside multiple sensors denoted by $S_k \subset S$, where S is the set of all sensors in the entire sensing area. The cloud server recruits N mobile users (either pedestrians or people in vehicles equipped with a personal device) denoted by the set $\mathcal{U} = \{u_1, u_2, \dots, u_N\}$; each user u_n moves within the RoIs to collect data from

sensors. We consider the set $\mathcal{E}$ of edge servers which serve a dual purpose. They allocate data collection tasks to MUs, who, in turn, report the collected data back to the nearest edge servers. One edge server covers multiple non-overlapping RoIs. A data collection round has $|T|$ time slots, with each time slot lasting for $\Delta t = 1$ second. Data consumers request the MCS organizer to access sensory data from given RoIs at specific times; such is expressed in the form (A_n, D_n) , with $0 \leq A_n \leq T$ and $A_n < D_n \leq T$, where A_n identifies the starting time and D_n the ending time that MUs must collect data from sensors.

Tasks are assigned to users that are currently available (i.e., they are not executing any other task) and agree to carry out the task based on the expected profit. Once a task is assigned to a user u_n , they then modify their route to visit *different* RoIs to collect data from the corresponding sensors starting at time slot A_n to D_n . User u_n visits RoIs in a specific sequence of descending order of expected revenue. We express the visit of a user u_n to region r at time slot t by the binary variable $x_{nr}^{(t)}$ set to 1, and 0 otherwise. Similarly, a user u_n that collects data from sensor s in region r at time slot t is expressed by the binary variable $y_{nsr}^{(t)}$ set to 1, and 0 otherwise.

A sensor s advertises the *quality level* Q_{st} of its sensory data at time t as $0 < Q_{st} \leq 1$; similarly, sensors advertise the associated reward R_{st} to be paid by an MU in exchange for such sensory data. Both MUs and sensors incur costs; these costs are related to data sampling and data transmission for sensors, and to traveling between RoIs, collecting data from sensors, and transmitting them to a nearby edge server for MUs. More specifically, a sensor spends p_s power for data sampling and $P_{st} = c_s \cdot Q_{st}$ power for transmitting the data to an MU (if user u_n collects data from sensor $s \in S_r$ at time slot t , i.e., $y_{nsr}^{(t)} = 1$). Similarly, a mobile user u_n consumes p_n power for traveling between RoIs, and $P_{nst} = c_n \cdot Q_{st}$ power for collecting data from sensor s in region r upon visiting it (i.e., $x_{nr}^{(t)} = 1$ and $y_{nsr}^{(t)} = 1$) and transmitting them to a nearby edge server. c_s and c_n are energy expenditure coefficients for the sensors and MUs correspondingly.

4.3.2 Pricing Model of Sensory Data

The data quality strongly relates to the sampling frequency of sensors as well as the timeliness of data collection by MUs and provisioning to data consumers. Moreover, data is more valuable if it has not yet been reported to data consumers by other MUs. That is, the fewer the visits to a RoI (few MUs have collected data from the given RoI), the higher the data quality.

Data quality varies over time, thereby it affects the cost and revenue of MUs and sensors during a MCS campaign, resulting in complex dynamics in the system. That is, sensors charge the MUs a time-varying price for collecting their data. This price is paid out of the price that the cloud server pays MUs. Each sensor determines the reward for its data based on the data quality Q and (historical) frequency of visits V by MUs to the RoI the sensor resides. The

time-dependent pricing model for sensor $s \in S_r$ in region r at time t is:

$$R_{st} = R_{s(t-1)} + \left(\alpha \frac{V_{r(t-1)} - \bar{V}_r^{(t-1)}}{\bar{V}_r^{(t-1)}} t + \beta \frac{Q_{st} - \bar{Q}_s^{(t)}}{\bar{Q}_s^{(t)}} \right) \cdot \Delta R \quad (4.1)$$

where ΔR is a constant incremental reward specified by the deployer; $\bar{V}_r^{(t-1)} = (\sum_{n=1}^N \sum_{t'=1}^{t-1} x_{nr}^{(t')}) / (t-1)$ is the average of the MUs visits to region r up to time slot $t-1$; and $\bar{Q}_s^{(t)} = (\sum_{t'=1}^t Q_{st'}) / t$ is the average sensory data quality of sensor s up to time slot t . The weights $0 \leq \alpha$ and $\beta \leq 1$, with $\alpha + \beta = 1$, reflect the impact of the MUs visits frequency and the sensory data quality on the price.

4.4 Location-Aware Quality Data Collection

The mobile users evaluate the expected cost and revenue prior to carrying out a task. Similarly, sensors evaluate their expected cost and revenue based on the pricing model in Equation (4.1). With this in mind – and as a direct consequence of individual rationality – MUs will only carry out tasks that yield to a positive profit ($\text{Profit}_{\text{MU}}(n) = \text{Revenue}_{\text{MU}}(n) - \text{Cost}_{\text{MU}}(n) > 0$). Similarly, the sensors will sell their data only if the payment they receive from MUs is higher than their costs ($\text{Profit}_S(s) = \text{Revenue}_S(s) - \text{Cost}_S(s) > 0$).

We formulate an optimization problem (presented in Publication III) to encourage both sensors and MUs to participate in data sampling and data collection tasks by maximizing their profits subject to delay constraints. However, as the optimization problem is NP-hard and cannot be solved efficiently, we propose an online greedy algorithm, namely, the Location-aware Quality Data Collection Algorithm (LQ-DCA), which is feasible in practice.

The LQ-DCA, depicted in Algorithm 2, builds upon the mobile edge computing (MEC) paradigm [115] to move the communication and processing tasks to the edge of the network, i.e., close to MUs. More specifically, edge servers manage the tasks for the RoIs under their coverage (see Figure 4.1). Each MU first connects to nearest edge server to receive contextual information of the RoIs such as physical distance to them, average quality level of the sensory data in the RoIs, as well as expected energy consumption of the devices in the RoIs. These information are provided to the edge servers by the local coordinators.

Each MU runs Algorithm 2 at every time slot. First, an MU computes the achievable profit and associated cost of every unvisited RoI (line 3). Recall that a demand for high data quality requires the data to be collected from unvisited RoIs. Consequently, the MU finds the region that yields to the locally-maximum social welfare (line 4). Once the MU moves to the selected RoI, it collects data for a given time period from sensors (line 9); they are ordered in decreasing order of data quality (lines 7–8). The MU then transmits the data to the nearest edge server (line 10), removes the visited RoI from the list on unvisited RoIs (line 11), updates the current time (line 12) and repeats the whole process if there is enough remaining time before the time deadline of the task D_n (line 16);

Algorithm 2: LQ-DCA for mobile user $u_n \in \mathcal{U}$ at time slot $1 \leq t \leq |T|$

```

1 Determine nearest edge server to mobile user  $u_n$ ;
2 foreach region  $r_i \in \{\mathcal{R} - \mathcal{R}_n^{(t)}\} \cap \mathcal{R}_e$  do
3   Compute  $\text{Profits}(i)$ ,  $\text{Cost}_S(i)$ ,  $\text{Profit}_{\text{MU}}(i)$  and  $\text{Cost}_{\text{MU}}(i)$ ;
4   Find the target region  $r_c$ ;
5 Move to region  $r_c$  within  $t_c$  time duration;
6 foreach time slot  $t + t_c \leq t' \leq t + t_c + \lceil t_c^c / \Delta t \rceil$  do
7   Sorted sensors in region  $r_c$  in decreasing order of their  $Q/P$  values at
   time slot  $t'$  into set  $S$ ;
8   Select first  $\lceil (m_c / \sum_j m_j) \cdot m_c \rceil, \forall j \in \mathcal{R} - \mathcal{R}_n^{(t)}$  sensors from set  $S$  such that
    $\text{Profits}(s') > 0$  and  $\text{Profit}_{\text{MU}}(n) > 0$  for each selected sensor  $s'$ ;
9   Collect data for  $\Delta t$  time from the selected sensors;
10 Transmit collected data from selected sensors in region  $r_c$  sequentially to a
   nearby edge server;
11 Remove region  $r_c$  from the set of unvisited RoIs;
12 Set current time slot to  $t_{cur} = t + \frac{Q/(d_c \cdot \bar{P}_c)}{\sum_j Q_j/(d_j \cdot \bar{P}_j)} (D_n - t)$ ;
13 Update nearby edge server;
14 if  $t_{cur} + \min\{t_r, \forall r \in \{\mathcal{R} - \mathcal{R}_n^{t_{cur}}\} \cap \mathcal{R}_e\} > D_n$  then
15   Terminate data collection by mobile user  $u_n$ ;
16 else Repeat for mobile user  $u_n$  at time slot  $t_{cur}$ ;

```

otherwise, it terminates the data collection (line 15).

4.5 Results

We employed a custom Python simulator to assess the performance of our proposed data collection scheme LQ-DCA (Algorithm 2). We consider an urban scenario of a varying number of mobiles users and 200 sensors deployed in an area of 4480 by 3500 meters. The area consists of non-overlapping RoIs of 140 by 140 meters and 24 edge servers cover subsets of such regions. The ONE simulator [11] v.1.6.0 was employed to generate mobility traces of mobile users on the roads and pedestrian paths of the city of Helsinki moving with a speed between 0.5 and 1.5 m/s. Sensors have a transmission range of 100 m and the quality of their sensory data, a direct consequence of the sampling frequency, falls in the range $[0 - 1]$. The parameters α and β [see Eq. (4.1)] are set to 0.5, unless otherwise stated. The system comprises of 300 tasks with a minimum time duration of 500 seconds (i.e., $D_n - A_n \geq 500$ s). One time slot lasts 1 second and the experiments lasted for 2 hours of simulated time.

We compare our LQ-DCA scheme with other two schemes: (i) Nearest Location Data Collection Algorithm (NL- DCA), where an MU selects to visit the region

Figure 4.3. (a) Average collected data as a function of the number of mobile users in the network for three algorithms, LQ-DCA, NL-DCA, and RL-DCA respectively, and (b) social welfare as a function of the α and β parameters [Eq.(4.1)] with 10 mobile users and 200 sensors in the network for the LQ-DCA.

with the shortest distance, and it then collects data in such a region from candidate sensors similar to LQ-DCA, and (ii) Random Location Data Collection Algorithm (RL-DCA), where an MU randomly selects to visit a region, and it then collects data in such a region from candidate sensors similarly to LQ-DCA.

Figure 4.3a shows the average data collected by all mobile users as a function of the number of MUs in the network. As expected, the amount of collected data increases with the number of MUs for the three schemes. However, our proposed LQ-DCA outperforms the NL-DCA and RL-DCA algorithms. Moreover, the NL-DCA outperforms the RL-DCA algorithm as visiting the nearest RoI results in more time available to visit a multitude of (other) RoIs, hence collect more data. Similarly, the LQ-DCA leads to higher social welfare than the other two algorithms, and more specifically, it varies with the α and β parameters, as shown in Figure 4.3b. Recall that the parameters α and β weigh the frequency of MU visits to a RoI and the quality of the sensory data, respectively. As α increases from 0.2 to 0.8 (while β decreases from 0.8 to 0.2), so does the social welfare. A first intuition would be to set a high value for the α parameter in the reward model for the sensory data [Eq.(4.1)] to increase the social welfare. However, that does not translate into collection of high quality data (low β parameter) and low price of sensory data for data consumers. In fact, data consumers – one of the main stakeholders of a MCS system (see Figure 4.2) – would incur a high monetary burden to support such a MCS system.

The time duration of the tasks, i.e., $\delta = D_n - A_n$, plays an important role on the amount of data collected. Figure 4.4a shows the average collected data as a function of δ in a network with 20 MUs and 200 sensors for the LQ-DCA. Intuitively, the amount of collected data increases with δ as MUs have more time available to visit a multitude of RoIs. Recall that the size of a RoI is 140 by 140 meters and the movement speed of MUs varies between 0.5 and 1.5 m/s. Therefore, little data is collected for values of δ comparable to the time needed to traverse a RoI. The higher the locality of the phenomena (hence, the higher

Figure 4.4. Average (a) data collected over time, and (b) number of tasks that are either completed, (assigned but) not completed, and not assigned as a function of the task duration (i.e., $\delta = D_n - A_n$) parameter with 20 mobile users and 200 sensors in the network for the LQ-DCA.

the accuracy of the data), the smaller RoI sizes are needed. Decreasing the size of the RoIs allows for shorter time duration of the tasks δ as the time to traverse a RoI decreases. That is, the minimum value of the δ parameter is a crucial design parameter of a MCS system to maximize data collection. Figure 4.4b shows the distribution of the tasks during one data collection campaign of two hours as a function of the time duration of the tasks δ for our proposed LQ-DCA. The MCS campaign consists of 300 tasks; these tasks can either be (i) assigned to an MU at time A_n (i.e., starting time of the task) and **completed** successfully by the MU, (ii) assigned to an MU but **not completed** as it is not feasible for the MU to reach a RoI within the available time, or the feasible RoI yields to negative social welfare for the system, or (iii) **not assigned** to any MU as all MUs are occupied completing other tasks. The number of completed tasks is low for tasks of short time duration δ – MUs are able to reach few feasible RoIs in terms of either time or positive social welfare. However, the majority of the tasks are assigned. That is, tasks are assigned and dropped (i.e., not completed) by MUs as soon as the feasibility of carrying out the task does not hold, making the MUs available to be assigned to other tasks. Moreover, the number of tasks assigned and dropped decreases with δ ; at the same time, the number of tasks successfully carried out increases. This is a direct consequence of MUs having a longer time available to visit feasible RoIs. Furthermore, MUs are now occupied for longer periods of time, hence being able to accept fewer tasks to carry out.

4.6 Conclusion

This chapter presented an efficient data collection scheme by semi-controlling the mobility of the data collectors through incentives. That is, we devised an incentive-based MCS scheme in which individual sensors charge mobile users a *dynamic virtual* price to collect their data. The MCS platform compensates

mobile users to collect data from sensors. Mobile users, instead, evaluate the cost and revenue relative to carrying out a task prior to accepting it. Upon accepting a data collection task, mobile users decide which sensors to visit based on the quality level of their data (i.e., task's service quality requirement) and their own cost. Sensors encode the frequency of user visits and the sensory data quality in the price they charge to dynamically incentivize a mobile user to either collect their data or not. We show through extensive simulations that our proposed scheme yields a higher amount of collected data under constraints of time and data quality, while maximizing the social welfare of the system. An interesting future development would be to refine our price model to predict the crowd churn rate based on their willingness to change path.

5. Data Collection in Large-scale IoT Systems with Fully-controlled Mobility

This chapter addresses data collection in an application-specific instance of a large-scale IoT system. In particular, it shows how to leverage the ubiquitous presence of wireless devices to assist search and rescue operations during large-scale emergencies such as disaster scenarios. Such scenarios are particularly devastating in urban environments. They endanger not only the lives of people, but also disrupt critical support infrastructure (e.g., communications, electric grid, and roads), create logistical challenges for evacuation and search and rescue operations, and finally create an environment that is unable to meet the basic survivors' needs to call for help by the usual means. In this context, we introduce a solution that includes two distinct elements. First, we provide a collaborative communication scheme for personal wireless devices to pool scarce battery life resources by using only a subset of such devices to transmit location information to data collection agents (e.g., drones). This enables devices to remain operational for a longer time, thus improving the chance of rescue. Second, we propose a matching scheme to locate survivors in a short time by deploying an ad-hoc drone-assisted communication infrastructure and optimizing the drone's path.

5.1 Background

Chapter 3 and Chapter 4 introduced people-centric data collection schemes of uncontrolled and semi-controlled mobility of the crowd, respectively. This chapter instead focuses on data collection with mobile agents of fully-controlled mobility (recall Table 3.1). This is particularly important for time-sensitive applications, as is the case of assisting victims of natural disaster scenarios as described next.

Mobile ad-hoc communication networks are deployed *on-the-fly* whenever existing communication infrastructure fails [66]. They are readily deployable, highly resilient, and sufficiently versatile to support a wide range of applications. These advantages make them uniquely suitable as contingency measures during natural disasters such as flooding, earthquakes, or tsunamis. These disasters may hit urban, dense areas and endanger the life of people as well as affect the

existing communication infrastructure [116]. This highly impacts the chances of people to communicate with each other or ask for help. In fact, the infrastructure could either reach the limit of its network capacity (i.e., bandwidth scarcity), given the high demand to access its resources, or it could be completely destroyed [45].

Failure of communication services only exacerbates the already critical situation during a disaster. In fact, the first 72 hours following a disastrous event – known as the *golden relief time* – are crucial to survivors as it is the time when most of the search and rescue activities take place [101]. Survivors carry smart devices (e.g., smartphones), which send out emergency requests. Search and rescue operations are then instructed to find a way to receive these signals. To this end, Unmanned Aerial Vehicles (UAVs) [140] are particularly suitable as they provide *on-demand* communication infrastructure by quickly and easily covering affected areas with on-board femto-cells [140, 61].

Solutions for data dissemination during disaster scenarios must be energy-efficient [91, 139]. This brings the following issues to attention: (i) the battery life of smart devices is limited, (ii) the energy supply of UAVs is limited, and (iii) the affected area could be very large. To this end, we propose a communication scheme for drone-assisted disaster recovery scenarios that specifically addresses these issues. First, we design a collaborative protocol for smart devices that organizes them in tiers. More specifically, the protocol requires smart devices to leverage the different interfaces they may have (e.g. Bluetooth, WiFi, and cellular) for energy-efficiency and extend their lifetime. That is, smart devices in proximity of each other form groups in such a way that only the leader of the group switches on the most energy-hungry interface to communicate with UAVs. Second, we propose a data collection scheme for drones to cover an affected area: we design efficient paths for the drones to visit and collect data from group leaders in a short time, thereby ensuring limited delay and extended operation time of the drones.

5.2 Related Work

UAVs are used predominantly in the military field due to their ability to operate unattended in highly dynamic and complex environments [42]. However, UAVs are now widely spread in the civil and commercial sectors as well, especially in applications for people being at high risk. Natural disasters and their aftermath requires civil authorities to assist endangered people as fast as possible. That is, assistance teams require means of constant monitoring of the situation without putting more people in danger.

Disaster scenarios demand fast and reliable ad-hoc communication infrastructure if the access network fails as a result of base stations being either damaged or destroyed [93]. UAV-assisted communication systems can quickly and easily cover an affected area to collect the data disseminated by the survivors. Cer-

tain solutions rely on opportunistic device-to-device communications to relay the data of the survivors directly to the search and rescue teams [94]. Other solutions, instead, rely on UAVs such as drones to cover an area and discover survivors [98, 44, 45]; however, these solutions require a certain level of prior organization of the rescue teams as well as efficient communication protocols among the survivor devices to prolong their battery life.

The literature has widely covered efficient placement and optimization of UAVs that cover certain disaster areas [117, 88, 87]. However, these solutions do not consider energy efficiency as their primary concern. Moreover, other solutions aim to search for a target and not provide full coverage of an area [53], while others do this by cooperating a fleet of UAVs [114]. By contrast, our solution relies on a single UAV to minimize the cooperation and synchronization cost among UAVs. In doing so, it focuses on prolonging the battery life of both mobile devices and the UAV itself.

5.3 Multi-tier Communication

The considered network in our reference architecture consists of the set $\mathcal{S} = \{s_1, s_2, \dots, s_M\}$ of $M = |\mathcal{S}|$ nodes representing survivors. Each survivor possesses a mobile device, which is equipped with the set $\mathcal{N} = \{n_1, n_2, n_3\}$ ¹ of Bluetooth, WiFi, and cellular communication interfaces, respectively. These interfaces have different transmission ranges and energy consumption profiles [94]. Accordingly, a multi-tier architecture is formed by grouping these devices into K clusters, each of which consists of devices that can reach each other directly (i.e., in a single hop) as shown in Figure 5.1. The devices (nodes) in each tier use the same communication technology and tiers are layered depending on their features: the lowest tier is the one with the most energy-efficient communication technology and the shortest communication range. Figure 5.1 shows three tiers, starting from the bottom, corresponding to the Bluetooth, WiFi, and cellular interfaces; the energy consumption c and the transmission range r of these interfaces increase from the bottom to the top tier as $c_{n_1} < c_{n_2} < c_{n_3}$ and $r_{n_1} < r_{n_2} < r_{n_3}$, respectively [95].

Each cluster elects one node as cluster head (CH) to act as a bridge between tiers, collecting data from the lower tier and relaying them upwards. At the other end, the network includes a drone that is sent *on-demand* to fly over the area affected by the disaster, providing ad-hoc cellular communication [99, 121] to the nodes in the highest tier and collecting data from them (Figure 5.1).

Our considered architecture enables energy conservation for both mobile devices and the drone. Mobile devices can preserve energy (i.e., battery power) by collaborating with each other and delegating CH nodes to switch on a more energy-hungry communication interface to relay their data to the highest tier.

¹Even though in this dissertation we consider three technologies, the reference architecture can be extended to any number of technologies as in Publication IV.

Figure 5.1. A three-tier communication architecture: nodes organize themselves into clusters; in each tier, the devices use the same communication technology. The tiers are layered based on the features of these technologies, with the shortest range and the most energy-efficient one at the lowest tier. Cluster heads relay data to the upper tier, while the nodes in the highest tier communicate directly with the drone.

Similarly, the drone visits only the nodes in the highest tier, leading to a simpler (and shorter) tour and reduced energy consumption.

5.3.1 Cluster Formation

$$\min z_{max} - z_{min} \quad (5.1)$$

$$\text{s.t. } z_{min} \leq \sum_{k \in K} x_{ik} (E_i - e_i) + y_{ik} e_i \quad \forall i \in S \quad (5.2)$$

$$\sum_{k \in K} x_{ik} (E_i - e_i) + y_{ik} e_i \leq z_{max} \quad \forall i \in S \quad (5.3)$$

$$z_{min}, z_{max} \geq 0 \quad (5.4)$$

$$x_{ik} \leq y_{ik} \quad \forall i \in S, \forall k \in K \quad (5.5)$$

$$d_{ji} y_{jk} \leq r_u x_{ik} + D(1 - x_{ik}), \quad (5.6)$$

$$\forall i, j \in S, \forall k \in K, \forall 1 \leq u < 3$$

$$\sum_{i \in S} x_{ik} = 1 \quad \forall k \in K \quad (5.7)$$

$$y_{ik} \leq \sum_{i \in S} x_{ik} \quad i \in S, k \in K \quad (5.8)$$

$$\sum_{k \in K} y_{ik} = 1 \quad \forall i \in S \quad (5.9)$$

$$x_{ik}, y_{ik} \in \{0, 1\} \quad \forall i \in S, \forall k \in K \quad (5.10)$$

Cluster formation and CH selection in each of the tiers is of uttermost importance to ensure a fair energy expenditure among the nodes. Larger clusters (i.e., clusters of greater cardinality) pose a higher burden on the CH. Collecting and relaying location data from a large number of nodes drains the battery power of the CH and shortens its life time considerably. Therefore, to mitigate the drastic energy expenditure of a CH, cluster formation should not necessarily follow the rule of “all neighbors form a cluster”.

To this end, we propose an optimization problem to form optimal clusters in the n_1 and n_2 tiers by minimizing the difference between the highest (z_{max}) and the lowest energy levels (z_{min}) of the nodes in the network, as expressed by Eq. (5.1). Clusters and corresponding CHs are updated every δ time slots to balance the energy expenditure of the nodes in the network. The energy consumption of a node depends on its role; node i consumes e_i energy if it is a member of cluster k (expressed as $y_{ik} = 1$) and E_i if the node is CH of cluster k (expressed as $x_{ik} = 1$). The constraint in Eq. (5.2) gives a lower bound for the energy expenditure of a node: node i is member ($y_{ik} = 1$) but not head ($x_{ik} = 0$) of cluster k , hence, the energy expenditure amounts to e_i . Similarly, Eq. (5.3) gives an upper bound for the energy expenditure: node i is head of cluster k and its energy expenditure amounts to E_i . Trivially, the bounds z_{min} and z_{max} must be non negative values [Eq. (5.4)]. Moreover, a node can only belong to one cluster and could be its CH [Eq. (5.5)]. Specifically, any two nodes j and i can form a cluster if the distance between them, d_{ji} , is smaller than the transmission range r_u of the interface n_u [Eq. (5.6)]. If node j is member ($y_{jk} = 1$) and node i head of cluster k ($x_{ik} = 1$), Eq. (5.6) is satisfied if the nodes are within the transmission range of each other. However, if node i is not head of cluster k , the condition in Eq. (5.6) is still satisfied for a large enough number D , as a relaxation of the first term in the expression. Eq. (5.7) and Eq. (5.8) express that a cluster can have at most one head, and that a node can belong to at most one cluster [Eq. (5.9)]. Finally, the binary decision variables in Eq. (5.10) express the status of a node as a member ($y_{jk} = 1$) or head ($x_{ik} = 1$) of cluster k , and 0 otherwise.

This optimization problem can be reduced to the maximum-cut problem, and thus is NP-complete; hence, we propose an approximate solution to the same problem. The cluster formation leverages the local connectivity of the nodes at the different tiers. The CH selection aims at achieving uniform energy expenditure at the nodes. To this end, CH selection occurs every δt time to mitigate the energy burden put on one single node. By taking turns as CHs, nodes prolong their individual lifetime, as well as that of the network. Algorithm 3 describes such a heuristic. All nodes have their Bluetooth interface on by default. In tier n_1 (Bluetooth), each CH collects data from all cluster members and switches on its n_2 (WiFi) interface. Tier n_1 CHs are then formed into clusters within tier n_2 , each of which elects a CH. These tier n_2 CHs switch on the n_3 interface and relay data from the underlying tiers to an UAV.

Algorithm 3: Dynamic CH selection at node m

```

1 Input: nodes location and  $\delta t$  (time-slot)
2 Output: switch ON/OFF interface  $n_i$ 
3 foreach  $\delta t$  do
4   //  $n_1$  communication tier;
5   activate  $n_1$  discoverable mode;
6   if node discovers  $n_1$ -neighbors then
7     diffuse 1-hop  $n_1$ -neighbors and power-budget;
8     form cluster;
9     select  $n_1$  tier CH with higher power-budget;
10    if  $n_1$  tier CH then activate  $n_2$  interface ;
11  else activate  $n_2$  interface (isolated  $n_1$ -node);
12  //  $n_2$  communication tier;
13  if  $n_1$  tier CH then
14    if node discovers  $n_2$ -neighbors then
15      diffuse 1-hop  $n_2$ -neighbors and power-budget;
16      form cluster;
17      select  $n_2$  tier CH;
18      if  $n_2$  tier CH then activate  $n_3$  interface ;
19    else activate  $n_3$  interface (isolated  $n_2$  tier CH) ;
20  else send data to CH;
21  //  $n_3$  communication tier
22  if  $n_2$  tier CH then exchange data with UAV ;

```

5.3.2 Drone-assisted Data Collection

The data relayed to the n_3 tier by the CHs is collected by drones and reported to the search and rescue teams. Initially, a drone flies over the entire disaster area and discovers all nodes in the n_3 tier that have switched on the cellular interface. We propose a solution that consists of identifying *anchor points* upon the discovery of the n_3 nodes. Anchor points can either be n_3 tier nodes or points from which a drone can reach multiple n_3 tier nodes given the cellular interface transmission range. These anchor points are given as input to a path planning algorithm that builds the shortest path that allows the drone to collect data from all nodes. This can be accomplished by formulating and solving the Traveling Salesman Problem (TSP) and its variant, the Close-Enough TSP (CETSP) [58, 54]. Our proposed solution achieves energy savings in two different ways: anchor points limit the number of locations a drone must visit, and the TSP and CETSP shorten the drone's path to visit these points.

5.4 Results

We evaluate the performance of our proposed multi-tier data relaying scheme in terms of energy expenditure and network lifetime. The disaster scenario consists of a varying number of nodes randomly distributed in an urban area of 10 by

Figure 5.2. (a) Number of alive nodes over time, (b) drone hovering and flying time, and (c) energy required by a drone to complete a tour for different path planning algorithms as a function of the node density in the network.

5 kilometers. Each survivor possesses a mobile device with Bluetooth, WiFi, and cellular interfaces. These interfaces have respective transmission ranges of 100, 200, and 500 meters and energy consumptions of 50 mW, 70 mW and 120 mW [109, 105]. The initial energy level of each node is uniformly distributed in the range [10 kJ, 20 kJ]. Finally, CHs are selected every $\delta t = 15$ minutes [90].

We compare our dynamic scheme (i.e., clusters and CHs are selected every $\delta t = 15$ minutes) against two other schemes: (i) *baseline*: there is no collaboration among nodes and every node in the network switches on all the necessary interfaces to transmit its own data to an UAV, and (ii) *static*: nodes collaborate to relay their data through the tiers. The CHs are selected based on their initial energy levels and their role as CH remains invariant until they run out of available energy and die.

Figure 5.2a shows the number of nodes remaining in the network over time for each of the three schemes. The baseline scheme involves no collaboration and, as expected, performs poorly – the nodes in the network die within a short period of time. This trend is linear with time as each node is responsible for transmitting its data to the highest tier, and must therefore switch on all the available communication interfaces. Employing a simple static scheme to reduce the energy consumption of the nodes improves outcomes considerably. In fact, a gap of around fifty (alive) nodes appears quickly and it increases with time. The decrease in the alive nodes is smoother as fewer nodes die at the same time. In fact, the static scheme nearly doubles the length of time during which there is at least one alive node in the network. Our proposed dynamic scheme results in

the highest number of alive nodes over time. In fact, most of the nodes run out of battery alone or in small groups, leading to comparable energy levels among the nodes in the network.

We now focus on the path planning of the UAV. In this case, we compare the performance of our proposed cooperative algorithms, TSP-COPE and CETSP-COPE, to the same path optimization algorithms without cooperation, TSP and CETSP. The four path planning algorithms are summarized next.

- TSP finds the optimal route that visits each node in the network. There is no cooperation among nodes to relay data.
- CETSP finds the smallest number of stops from which the drone can reach all nodes without visiting each separately, and the shortest path through these stops.
- TSP-COPE extends TSP by introducing support for cooperation among nodes. The optimal route is calculated based on the location of all nodes in the n_3 tier.
- CETSP-COPE similarly extends CETSP. The optimal route is calculated based on anchor points obtained from the n_3 tier locations.

All four schemes are implemented as additional modules to the ONE simulator v.1.6.0. We consider a scenario with different network densities. A drone flies over the disaster area with a speed of 10 m/s and it consumes 210 W for hovering and 240 W for moving [48, 25]. The drone hovers to collect data for an amount of time $t_a = \min\{t_c, t_s\}$, where $t_c = 2 \cdot |C_k|$ s, with $|C_k|$ being the cardinality of cluster k , and $t_s = 5$ s.

Figure 5.2b and Figure 5.2c illustrate the performance of the proposed path planning algorithms as well as the TSP and CETSP algorithms. The energy expenditure of a drone is due to flying and (mostly) due to hovering [39]. Our TSP-COPE and CETSP-COPE schemes decrease hovering time relative to flying time. As seen in Figure 5.2b, the hovering time remains low for all network densities. In fact, more clusters with high cardinality are formed as the network density increases; that is, a lower number of n_3 tier nodes relay the data of all the underlying tier nodes. Figure 5.2c shows the energy expenditure of a drone during one full tour with data collection as a function of network density for each scheme. The results demonstrate that our proposed CETSP-COPE scheme is effective in reducing the energy needs of the drone. Reducing its energy consumption not only decreases the cost of an *ad-hoc flying cell network* [99], but it also decreases the number of drones needed to assist a large area affected by a disaster.

5.5 Conclusion

This chapter presented an ad-hoc communication scheme particularly suitable for areas affected by disaster scenarios. We proposed a multi-tier communication scheme for survivors' devices to relay location information to search and rescue teams. This is complemented by an ad-hoc communication infrastructure consisting of drones with femto-cells on board. We proposed path planning algorithms for a drone to cover the disaster area to collect data from the survivors' devices in the shortest possible time. Our proposed solution resulted in extended lifetime of the devices in the network and considerable energy savings for the drone. Our solution could be further extended by considering a fleet of drones that fly over the disaster area at the same time to provide an even faster ad-hoc communication infrastructure for the survivors by fairly allocating certain areas to specific drones. In turn, search and rescue teams would have prompt access to the location of the survivors, allowing them to decrease the response time considerably. Therefore, relief operations can take place relatively shortly after a disaster, thereby increasing the survival chances of the people affected.

6. Sensory Data Reduction for IoT Applications

This chapter investigates data reduction mechanisms for IoT sensor networks. The chapter begins with an overview of various mechanisms that operate at different layers of the IoT architecture and their corresponding limitations. Next, it provides a hierarchical, low-complexity data reduction mechanism. We show that our proposed mechanism is not only simple to deploy but also reliably captures the representative features of the original sensory (time series) data.

6.1 Background

One main characteristic of IoT (wireless) sensor networks are the constrained resources at the sensor nodes. These constraints include memory size, energy (e.g., battery capacity), and computational capabilities. Similarly, resources available for data transmission (i.e. spectrum capacity) are also limited. These two issues go hand in hand as they pose severe limitations on storing the enormous amount of generated data and successfully transmitting it to a remote data center for further processing. This raises two questions to our attention: (i) can we make IoT sensor networks more energy efficient?, and (ii) can we reduce the amount of sensory data prior to transmitting it to a data center? While the first question is widely studied in literature and addressed via techniques such as energy harvesting and wireless charging [40], the second question requires more thoughtful consideration as to where data reduction must take place.

Data-oriented networks, such as IoT sensor networks supporting real-time applications, can particularly benefit from attention to the data transmission issue as their main asset is the data and its timeliness. Not only does their data have to reach a data center for processing, but the delay must be limited, especially for time-sensitive and critical applications. However, this imperative for fast and high-volume data transmission must be balanced with limited network capacity to avoid congestion of the wireless medium.

High energy consumption, finite storage, and limited network bandwidth all call for data reduction before transmission. In fact, up to 80% of the total energy

Figure 6.1. High-level view of an IoT architecture and data reduction mechanisms at the gateway and edge tiers.

expenditure of IoT sensor networks corresponds to the wireless data transmission [24]. Therefore, reducing the amount of data prior to transmission has significant potential for energy savings, freeing up bandwidth, and improving network efficiency [23].

Data reduction is founded on data correlation. Fundamental data aggregation techniques exploit correlations among data from various sources. These correlations can be (i) *spatial*, where sensor nodes observe phenomena located in a limited geographical area, (ii) *temporal*, where the time series data varies slowly over time, and (iii) *semantic*, where the data from various sources has the same connotation (domain). Therefore, taking advantage of datasets that exhibit spatial, temporal, or semantic correlation is at the core of data handling techniques [49]. Most common approaches for data reduction: leverage the spatial-temporal redundancy by keeping only a subset of all source nodes active [28, 84]; automatically adjust the amount of generated data by adapting the sampling rate of the nodes to the network conditions [72]; or apply data compression techniques [80, 82, 85]. The literature has addressed various data handling techniques, though most proposed solutions operate at a single level of the network architecture.

Data may be transmitted through multiple levels before reaching its destination. One instance of data generated at sensors can first be transmitted to a gateway, which in turns transmits it to the nearest edge device, which in turns transmits it to a remote data center such as the cloud, as seen in Figure 6.1. Distributing data reduction operations to the different levels of the IoT architecture helps reduce the burden placed on individual network elements, while also targeting concerns related to data resolution, sensitivity, and reliability concerns.

Data reduction is generally a lossy operation. Hence, representing the re-

duced data as closely as possible to the original one is of uttermost importance. Fundamental data reduction operations consist of reduction of dimensionality (reducing the number of features) and numerosity (reducing the number of distinct numerical values). Common approaches are data aggregation, discretization, or data compression [82]. We base our proposed solution on existing data filtering and data fusion techniques, while introducing substantial modifications. Complex data reduction techniques are not appropriate for battery-powered and memory-limited devices. To work around this limitation, we propose a data reduction scheme that operates at two tiers, namely, at the gateway and at the edge tier of the network. The scheme performs data filtering at the gateway tier and data fusion at the edge tier (see Fig. 6.1). More specifically, our solution is tailored for real-time streams of data. To achieve selection of the most representative items among all original data points in real time (despite limited computational resources), our proposed technique is light-weight in terms of computation complexity.

6.2 Related Work

Data reduction mechanisms operate during both data collection and data transmission through different types of techniques. They aim at reducing the amount of data while keeping the reduced data highly accurate, as well as minimizing the energy expenditure of IoT sensor networks [126].

Data sampling focuses on extracting the most representative points of the data set, or choosing a subset of sensors that contributes sensory data that is most significant to data consumers. For instance, only a few sensors at a time can be actively contributing with data by leveraging spatial correlation [131]. As the spatial correlation increases (i.e., the IoT sensors are placed closer and closer to each other), the fewer sensors need to be active. Similarly, the work in [33] proposes a centralized algorithm (solvable in polynomial time) to choose a small data subset to represent the vast information carried by the sensory data. The algorithm can be tuned to achieve an arbitrarily low information loss rate. Another way to achieve data reduction is by adapting the sampling rate of the sensors to network resources [73]. By doing so, a limited amount of data is streamed to a remote server.

Similar to compressing already sensed data [80], data compression prior to data acquisition [82] is equally important, especially as it directly affects the memory occupancy of the sensors. Compressed sensing, in fact, is also highly suitable for opportunistic routing networks with multi-hop schemes as it induces load balancing among the nodes [85].

Data aggregation methods such as compressed sensing and data prediction are crucial to lower the communication cost [55, 132]. For instance, the work in [138] provides a data reduction scheme based on the fog computing paradigm, where only the data that falls out of the prediction range are uploaded “as

is” from fog to cloud. Moreover, data aggregation of various sources involves complex data transformation. Therefore, centralized methods are not convenient as they require continuous communication among network entities, leading to a high communication overhead. By contrast, distributed methods aim at minimizing the messaging cost among sensor nodes [28]. In fact, methods such as clustering, multipath, and aggregate trees are commonly used [46, 84]. That is, in a data aggregation scheme, the data flows from the leaf (sensory data from a specific location) to the root of the tree (data collection element).

We base our proposed solution upon a layered IoT network architecture of sensors, gateways, router and cloud elements [104]. We reduce the amount of data transmitted to a cloud server in two tiers, at the gateway and at the edge, while maintaining a low time complexity. Moreover, our data reduction mechanism is of low computation complexity and thus suitable for resource-constrained devices and real-time data streams.

6.3 Two-tier Data Reduction Method

Our proposed data reduction scheme operates at two tiers. Details are presented below.

6.3.1 Data Filtering at the Gateway Tier

Pattern extraction from a huge amount of sensory data is at the basis of data filtering. Data time series are made of continuous and indexed data points. Extracting a pattern from such a time series amounts to selecting a subset of data points. We extract Perceptually Important Points (PIPs) to represent the original time series with high fidelity and accuracy. [122]. The PIPs are identified based on the human method of pattern recognition – that is, points that are perceptually important for identifying patterns in time series. We adapt the existing algorithm of finding PIPs [35] to continuous and dynamic streams of sensory data – the algorithm decides in real time whether to keep or discard a data point as new data arrives. Each PIP is identified as the point with the maximum (Euclidean) distance to a line drawn between two adjacent PIP points. The first PIPs are the endpoints of the time series. The process is iterated until the desired number of PIPs is chosen (see Fig. 6.2). We performed data filtering on the *Intel Lab Data*¹ dataset. We noticed that not all key features of the data are accurately captured by the existing PIP algorithm, hence we extended it as below.

Interval restriction and dynamic cache. A continuous stream of data is received in time intervals. The importance T of a point falls between 0 and 1; if T is above a certain threshold, the data point is kept; otherwise it is discarded. T strongly relates to the time interval: after a specific time

¹<http://db.csail.mit.edu/labdata/labdata.html>

Figure 6.2. Three distance evaluation methods to find PIP points.

interval has passed, the importance T of the next data point is set to 1, hence terminating the iterative process of calculating the T value of such a point. Moreover, the incoming data is stored in a *cache* while the importance T of the data points is calculated. However, a large cache size negatively affects the real-time processing capabilities of the system. We solve this by limiting the cache size to avoid a network service pause.

Weighted sequence selection. Figure 6.2 illustrates the process of identifying the PIPs. Beginning with the two endpoints, the next PIP is the one farthest from a line connecting the two initial PIPs and so on. We use Euclidean distance instead of other options such as vertical and perpendicular distance. However, the PIP algorithm yields different results as the order of calculation of the PIPs varies. For instance, an order of $S_{2,5} \rightarrow S_{3,5} \rightarrow S_{1,5} \rightarrow S_{4,5}$ and $S_{3,5} \rightarrow S_{1,5} \rightarrow S_{4,5} \rightarrow S_{2,5}$ could lead to different T values for the PIPs. We then normalize each sequence with a given weight w_k such that

$$w_k \{S_{1,n}, S_{2,n}, \dots, S_{k,n} | 1 < k < n\} \quad \text{s.t.} \quad w_k = \sqrt{T_k^2 + T_n^2}$$

where

$$\{S_{1,n}, S_{2,n}, \dots, S_{k,n} | 1 < k < n\}$$

is the sequence of the data points indexed from k to n .

6.3.2 Data Fusion at the Edge Tier

Incoming data from gateways in the first tier is sent to routers in the edge tier, which in turn send it to a remote (cloud) data center. At the edge tier we perform further data reduction by leveraging the correlation between the data of the various gateways. Data fusion is the best candidate for data reduction, as opposed to another data filtering process which would further deteriorate the accuracy of the data. We fuse the incoming data from multiple gateways according to the fusion degree that the data exhibits. The fusion degree between data incoming from two different gateways $G_i(t)$ and $G_j(t)$ is:

$$c_{ij}(t) = \exp\left(-\frac{1}{2}\|G_i(t) - G_j(t)\|\right)$$

Figure 6.3. (a) Time needed to calculate the importance value T of incoming temperature data at the gateway tier, and (b) similarity between the original series and the filtered series at the gateway tier for humidity data.

whereas the fusion degree matrix maps such a correlation for the data sources of all gateways:

$$C = \begin{bmatrix} 1 & c_{12}(t) & \dots & c_{1m}(t) \\ c_{21}(t) & 1 & \dots & c_{2m}(t) \\ \vdots & \vdots & \ddots & \vdots \\ c_{m1}(t) & c_{m2}(t) & \dots & 1 \end{bmatrix}$$

We then derive a final fusion estimation value to evaluate our data reduction scheme.

6.4 Results

We wrote a custom simulator in Python and used temperature and humidity time series datasets from the Intel Lab Data² to evaluate the performance of our scheme. In particular, we focused on the time needed to perform data filtering, data similarity after data filtering, and recovery accuracy after data filtering and data fusion. More specifically, we considered 1000 data samples per sensor and a cache size of 200 items. We considered three sources of data streams, where the first source corresponds to the dataset from Intel Lab Data and the second and third sources are obtained from the first by adding Gaussian noise with standard deviations 1 and 1.2, respectively. Figure 6.3a shows the average time to calculate the importance value T of a data point as streams of data come from gateways. Our method outperforms existing methods [104] and keeps the average computation time at around 0.18 seconds. Figure 6.3b characterizes the relation between the threshold for the T value used to decide whether a new incoming data point must be kept or discarded and the similarity between the original and the filtered time series. As seen in Figure 6.3b, reducing up to 70% ($T = 0.7$) of the original data still produces filtered data with high similarity with

²<http://db.csail.mit.edu/labdata/labdata.html>

Figure 6.4. Recovery accuracy of temperature data after performing data fusion at the edge tier.

the original data, while after this cutoff value data quality degrades drastically. Figure 6.4 shows the accuracy of recovered temperature data after performing data filtering and fusion at the gateway and at edge tiers, respectively. The recovery accuracy is around 95%, indicating that our proposed method performs well with real-time data streams.

6.5 Conclusion

This chapter presented a light-weight data reduction method for resource-constrained sensors. The proposed method operates in two stages, at the gateway and edge tiers. Simulation results based on real traces showed that the filtering method executed at the gateway tier has sufficiently low time complexity to support continuous incoming streams of data, and that the filtered data retains a high similarity for high data filtering rates. The method decides with high accuracy and as little time as 0.18 seconds whether a data point should be kept or discarded. Similarly, the data fusion method at the edge tier effectively combines the incoming data from several gateways, further reducing the amount of data requiring transmission to a remote data center, and retains a high recovery accuracy with respect to the original data stream. Future work could develop the data fusion method further by incorporating models of data prediction, thus achieving even greater efficiency.

7. Conclusion

Moti i ri mos të të gjejë vetëm një
mot më plak, po edhe një mot më
të mençur.

Fan S. Noli

The IoT has been an active research topic since the term was first coined back in the year 1999. The IoT is fundamental for an increasing number of applications and services; these include smart cities, smart grids, public safety, logistics, health care, and independent living. This vast heterogeneity of services and their corresponding requirements has given rise to important challenges that remain yet to be fully addressed to ensure a dependable IoT. This dissertation tackled some of these challenges by following an end-to-end approach, starting from taking an IoT device into use, and concluding with reliably and efficiently reporting sensory data to a remote data storage.

First, we proposed a secure bootstrapping mechanism for resource-constrained IoT devices. It specifically targets a user-friendly IoT by providing a bootstrapping mechanism that requires neither human intervention nor physical access to the device. We showed how our proposed solution incurs in very low memory, time, and energy utilization.

Second, we focused on data collection protocols suitable for applications with diverse requirements. We considered data collection with mobile elements whose mobility is either uncontrolled, semi-controlled, or fully-controlled. Specifically, we proposed an opportunistic data collection protocol for large-scale urban IoT scenarios. To this end, we leveraged the fog computing paradigm and designed a tractable data offloading protocol from sensors to mobile gateways of unknown and uncontrolled mobility. The simulation results showed that our proposed protocol increases the amount of data successfully reported to the cloud over time as the sensors *learn* to predict the expected mobility patterns of gateways. Moreover, we investigated the impact of incentives in MCS in stimulating people to collect data from regions of interest to data consumers. We proposed a smart incentive mechanism that affects the behavior of mobile data collectors over time. Our solution yields a higher amount of collected data and results in the

highest social welfare for the MCS system. We found that, to achieve an effective MCS, numerous design parameters require special attention as they trigger various trade-offs in the system. Next, we investigated data dissemination during natural disaster scenarios. The battery life of devices used to send emergency messages is very short compared to the *golden relief time* of 72 hours, within which most successful rescues take place. We devised a collaborative data dissemination protocol to extend the battery life of the devices, complemented by a data collection scheme with mobile agents of fully-controlled mobility, e.g., a drone. The drone discovers the survivors (i.e., their devices) and collects their data. We designed an optimal path for the drone to shorten the time needed to collect emergency messages, thereby increasing the survival chances of victims and reducing the energy consumption of the drone itself.

Finally, we focused on data-intensive IoT applications that put a high burden on the limited wireless bandwidth. To address this issue, we proposed a light-weight data reduction mechanism as the last mile of our end-to-end approach. It performs data filtering at the gateways and data fusion at the edge tier, thereby reducing the amount of data to be transmitted to a remote data center with minimal compromise on the data recovery accuracy with respect to the original data.

7.1 Future Work

The fast proliferation of the IoT and its massive generated data has given rise to different computing paradigms (such as the cloud, edge, and fog), and approaches to address different issues related to IoT. With IoT sustaining an increasing number of data-sensitive applications, security threats have become of uttermost importance [29, 21]. IoT must not only be secure, but also be user-friendly. That is, a user with limited to no knowledge regarding a device and the technology behind it should be able to operate the IoT device securely. We focused on a secure bootstrapping mechanism that requires no user intervention. However, often users own a multitude of devices and wish to bootstrap them all at once. Therefore, a promising extension of our work consists of securely bootstrapping IoT devices in groups; in turn, this requires first being able to associate a group of devices to the right owner (e.g., not to your neighbor).

Data collection in IoT is another prominent research topic [127]. The cloud, edge, and fog computing paradigms treat data collection differently. Cloud-based solutions leverage the high computational capabilities of the cloud and are suitable for data-heavy and delay-tolerant applications [103]. Mobile edge computing (MEC) reduces the latency by locating data storage and processing at the edge of the network [115]. Fog computing places the computation power along the continuum between the cloud and end-devices as necessary [13]. We leveraged all these paradigms to build our data collection solutions. Our purely opportunistic and people-centric data collection scheme based on the fog paradigm increased

the amount of data successfully reported to a gateway. Rural areas with little to no infrastructure could greatly benefit from our infrastructure-less solution. However, we noticed that the benefits of our solution diminish in areas with limited mobility of people. Therefore, our study could be extended to investigate the minimum infrastructure support required to profitably apply our solution in these areas. Moreover, our participatory (people-centric) data collection scheme with dynamic incentives considerably increased the amount of collected sensory data. We successfully incorporated *the human element*, i.e., the willingness of people to participate in data collection, into the incentive model. An interesting future development would be to refine our model to predict the crowd churn rates based on their willingness to change path. Additionally, our drone-based data collection scheme could be extended to support a fleet of drones so as to allocate non-overlapping areas to individual ones, thereby increasing the timeliness and efficiency of assisting survivors. Our proposed optimal path planning scheme could be applied to other ad-hoc networks with mobile elements to increase their operating agility in critical scenarios.

Finally, our real-time and light-weight data reduction scheme at the gateway and edge tiers showed encouraging results in terms of the recovery accuracy while considerably reducing the data. A possible direction for future work is to extend our scheme to incorporate more computationally-heavy methods such as machine learning [130, 124] while thoroughly identifying the costs and benefits it brings.

References

- [1] <https://www.openfogconsortium.org/what-we-do/>. Accessed: 2019-11-27.
- [2] http://autoid.mit.edu/iot_research_initiative. Accessed: 2019-08-30.
- [3] <https://www.ericsson.com/en/mobility-report/internet-of-things-forecast>. Accessed: 2019-08-30.
- [4] <https://ec.europa.eu/digital-single-market/en/internet-of-things>. Accessed: 2019-08-30.
- [5] <https://www.gsmainelligence.com/research/?file=1edb46b8f8d86187a7508bad348c3e87&download>. Accessed: 2019-08-30.
- [6] <https://www.bluetooth.com/bluetooth-technology/topology-options/>. Accessed: 2019-08-30.
- [7] <https://lora-alliance.org/about-lorawan>. Accessed: 2019-08-30.
- [8] <https://www.sigfox.com/en>. Accessed: 2019-08-30.
- [9] <https://www.3gpp.org/news-events/1733-niot>. Accessed: 2019-08-30.
- [10] https://www.iiconsortium.org/pdf/OpenFog_Reference_Architecture_2_09_17.pdf. Accessed: 2019-11-21.
- [11] <https://akeranen.github.io/the-one/>. Accessed: 2019-10-15.
- [12] http://openmobilealliance.org/RELEASE/LightweightM2M/V1_1-20180612-C/OMA-TS-LightweightM2M-Core-V1_1-20180612-C.pdf. Accessed: 2019-11-08.
- [13] <https://www.iiconsortium.org/index.htm>. Accessed: 2019-10-11.
- [14] HTTP Authentication: Basic and Digest Access Authentication. <http://tools.ietf.org/html/rfc2617>, June 1999.
- [15] Announcing the Advanced Encryption Standard (AES). <http://csrc.nist.gov/publications/fips/fips197/fips-197.pdf>, November 2001.
- [16] Pre-Shared Key Ciphersuites for Transport Layer Security (TLS). <https://tools.ietf.org/html/rfc4279>, December 2005.
- [17] 3GPP, Technical Specification Group Services and System Aspects. Generic Authentication Architecture (GAA). <http://www.3gpp.org/DynaReport/33919.htm>.
- [18] 3GPP, Technical Specification Group Services and System Aspects. Generic Bootstrapping Architecture (GBA). <http://www.3gpp.org/DynaReport/33220.htm>.

- [19] Sachin Agarwal, Christoph Peylo, Ravishankar Borgaonkar, and Jean-Pierre Seifert. Operator-based over-the-air M2M wireless sensor network security. In *The 14th International Conference on Intelligence in Next Generation Networks (ICIN 2010)*, pages 1–5, 2010.
- [20] Ala Al-Fuqaha, Abdallah Khreishah, Mohsen Guizani, Ammar Rayes, and Mehdi Mohammadi. Toward better horizontal integration among iot services. *IEEE Communications Magazine*, 53(9):72–79, 2015.
- [21] Fadele Ayotunde Alaba, Mazliza Othman, Ibrahim Abaker Targio Hashem, and Faiz Alotaibi. Internet of things security: A survey. *Journal of Network and Computer Applications*, 88:10–28, 2017.
- [22] Gianluca Aloï, Giuseppe Caliciuri, Giancarlo Fortino, Raffaele Gravina, Pasquale Pace, Wilma Russo, and Claudio Savaglio. Enabling iot interoperability through opportunistic smartphone-based mobile gateways. *Journal of Network and Computer Applications*, 81:74–84, 2017.
- [23] Mohammad Abu Alsheikh, Shaowei Lin, Dusit Niyato, and Hwee-Pink Tan. Rate-distortion balanced data compression for wireless sensor networks. *IEEE Sensors Journal*, 16(12):5072–5083, 2016.
- [24] Mohammad Abu Alsheikh, Shaowei Lin, Hwee-Pink Tan, and Dusit Niyato. Toward a robust sparse data representation for wireless sensor networks. In *2015 IEEE 40th Conference on Local Computer Networks (LCN)*, pages 117–124. IEEE, oct 2015.
- [25] Mahdi Asadpour, Bertold Van den Bergh, Domenico Giustiniano, Karin Anna Hummel, Sofie Pollin, and Bernhard Plattner. Micro aerial vehicle networks: An experimental analysis of challenges and opportunities. *IEEE Communications Magazine*, 52(7):141–149, 2014.
- [26] Kevin Ashton et al. That ‘internet of things’ thing. *RFID journal*, 22(7):97–114, 2009.
- [27] Luigi Atzori, Antonio Iera, and Giacomo Morabito. The internet of things: A survey. *Computer networks*, 54(15):2787–2805, 2010.
- [28] Boulat A Bash, John W Byers, and Jeffrey Considine. Approximately uniform random sampling in sensor networks. In *Proceedings of the 1st international workshop on Data management for sensor networks: in conjunction with VLDB 2004*, pages 32–39. ACM, 2004.
- [29] Elisa Bertino and Nayeem Islam. Botnets and internet of things security. *Computer*, (2):76–79, 2017.
- [30] Flavio Bonomi, Rodolfo Milito, Preethi Natarajan, and Jiang Zhu. Fog computing: A platform for internet of things and analytics. In *Big data and internet of things: A roadmap for smart environments*, pages 169–186. Springer, 2014.
- [31] Andrea Capponi, Claudio Fiandrino, Dzmitry Kliazovich, Pascal Bouvry, and Stefano Giordano. A cost-effective distributed framework for data collection in cloud-based mobile crowd sensing architectures. *IEEE Transactions on Sustainable Computing*, 2(1):3–16, 2017.
- [32] Georgios Chatzimilioudis, Andreas Konstantinidis, Christos Laoudias, and Demetrios Zeinalipour-Yazti. Crowdsourcing with smartphones. *IEEE Internet Computing*, 16(5):36–44, 2012.
- [33] Siyao Cheng, Zhipeng Cai, Jianzhong Li, and Hong Gao. Extracting kernel dataset from big sensory data in wireless sensor networks. *IEEE Transactions on Knowledge and Data Engineering*, 29(4):813–827, 2016.

- [34] Mung Chiang, Sangtae Ha, I Chih-Lin, Fulvio Risso, and Tao Zhang. Clarifying fog computing and networking: 10 questions and answers. *IEEE Communications Magazine*, 55(4):18–20, 2017.
- [35] F.L. Chung, Tak-Chung Fu, Robert Luk, and Vincent Ng. Flexible time series pattern matching based on perceptually important points. *International Joint Conference on Artificial Intelligence Workshop on Learning from Temporal and Spatial Data*, pages 1–7, 01 2001.
- [36] Cisco. Cisco visual networking index: Global mobile data traffic forecast update, 2017–2022. 2019.
- [37] Mario Di Francesco, Sajal K Das, and Giuseppe Anastasi. Data collection in wireless sensor networks with mobile elements: A survey. *ACM Transactions on Sensor Networks (TOSN)*, 8(1):7, 2011.
- [38] Mario Di Francesco, Na Li, Mayank Raj, and Sajal K Das. A storage infrastructure for heterogeneous and multimedia data in the internet of things. In *2012 IEEE International Conference on Green Computing and Communications*, pages 26–33. IEEE, 2012.
- [39] Carmelo Di Franco and Giorgio Buttazzo. Energy-aware coverage path planning of UAVs. In *ICARSC*, 2015.
- [40] Gabriel Martins Dias, Boris Bellalta, and Simon Oechsner. A survey about prediction-based data reduction in wireless sensor networks. *ACM Computing Surveys (CSUR)*, 49(3):58, 2016.
- [41] Shammi Didla, Aaron Ault, and Saurabh Bagchi. Optimizing AES for embedded devices and wireless sensor networks. In *Proceedings of the 4th International Conference on Testbeds and research infrastructures for the development of networks & communities*, page 4. ICST (Institute for Computer Sciences, Social-Informatics and Telecommunications Engineering), 2008.
- [42] Patrick Doherty and Piotr Rudol. A uav search and rescue scenario with human body detection and geolocalization. In *Australasian Joint Conference on Artificial Intelligence*, pages 1–13. Springer, 2007.
- [43] Norbert Druml, Manuel Menghin, Adnan Kuleta, Christian Steger, Reinhold Weiss, Holger Bock, and Josef Haid. A flexible and lightweight ecc-based authentication solution for resource constrained systems. In *The 17th Euromicro Conference on Digital System Design (DSD 2014)*, pages 372–378, 2014.
- [44] Milan Erdelj, Michał Król, and Enrico Natalizio. Wireless sensor networks and multi-uav systems for natural disaster management. *Computer Networks*, 124:72–86, 2017.
- [45] Milan Erdelj, Enrico Natalizio, Kaushik R Chowdhury, and Ian F Akyildiz. Help from the sky: Leveraging UAVs for disaster management. *IEEE Pervasive Computing*, 16(1):24–32, 2017.
- [46] Elena Fasolo, Michele Rossi, Jorg Widmer, and Michele Zorzi. In-network aggregation techniques for wireless sensor networks: a survey. *IEEE Wireless Communications*, 14(2):70–87, 2007.
- [47] Zhenni Feng, Yanmin Zhu, Qian Zhang, Lionel M Ni, and Athanasios V Vasilakos. Trac: Truthful auction for location-aware collaborative sensing in mobile crowdsourcing. In *IEEE INFOCOM 2014-IEEE Conference on Computer Communications*, pages 1231–1239. IEEE, 2014.
- [48] Azade Fotouhi, Ming Ding, and Mahbub Hassan. Dynamic base station repositioning to improve spectral efficiency of drone small cells. In *2017 IEEE 18th International Symposium on A World of Wireless, Mobile and Multimedia Networks (WoWMoM)*, pages 1–9. IEEE, 2017.

- [49] Deepak Ganesan, Deborah Estrin, and John Heidemann. Dimensions: Why do we need a new data handling architecture for sensor networks? *ACM SIGCOMM Computer Communication Review*, 33(1):143–148, 2003.
- [50] Hui Gao, Chi Harold Liu, Jian Tang, Dejun Yang, Pan Hui, and Wendong Wang. Online quality-aware incentive mechanism for mobile crowd sensing with extra bonus. *IEEE Transactions on Mobile Computing*, 2018.
- [51] Lin Gao, Fen Hou, and Jianwei Huang. Providing long-term participation incentive in participatory sensing. In *Computer Communications (INFOCOM), 2015 IEEE Conference on*, pages 2803–2811. IEEE, 2015.
- [52] Shuai Gao, Hongke Zhang, and Sajal K Das. Efficient data collection in wireless sensor networks with path-constrained mobile sinks. *IEEE Trans. on Mobile Computing*, 10(4):592–608, 2011.
- [53] Paolo Gaudiano, Eric Bonabeau, and Ben Shargel. Evolving behaviors for a swarm of unmanned air vehicles. In *Proceedings 2005 IEEE Swarm Intelligence Symposium, 2005. SIS 2005.*, pages 317–324. IEEE, 2005.
- [54] Michel Gendreau, Gilbert Laporte, and Frédéric Semet. The covering tour problem. *Operations Research*, 1997.
- [55] Edwin Prem Kumar Gilbert, Baskaran Kaliaperumal, Elijah Blessing Rajsingh, and M Lydia. Trust based data prediction, aggregation and reconstruction using compressed sensing for clustered wireless sensor networks. *Computers & Electrical Engineering*, 72:894–909, 2018.
- [56] Wei Gong, Baoxian Zhang, and Cheng Li. Task assignment in mobile crowdsensing: Present and future directions. *IEEE Network*, (99):1–8, 2018.
- [57] Jayavardhana Gubbi, Rajkumar Buyya, Slaven Marusic, and Marimuthu Palaniswami. Internet of things (iot): A vision, architectural elements, and future directions. *Future generation computer systems*, 29(7):1645–1660, 2013.
- [58] Damon J Gulczynski, Jeffrey W Heath, and Carter C Price. The close enough traveling salesman problem: A discussion of several heuristics. *Perspectives in Operations Research*, pages 271–283, 2006.
- [59] Bin Guo, Zhu Wang, Zhiwen Yu, Yu Wang, Neil Y. Yen, Runhe Huang, and Xingshe Zhou. Mobile crowd sensing and computing: The review of an emerging human-powered sensing paradigm. *ACM Computing Surveys*, 48(1):7:1–7:31, September 2015.
- [60] Bin Guo, Daqing Zhang, Zhu Wang, Zhiwen Yu, and Xingshe Zhou. Opportunistic iot: Exploring the harmonious interaction between human and the internet of things. *Journal of Network and Computer Applications*, 36(6):1531–1539, 2013.
- [61] Lav Gupta et al. Survey of important issues in UAV communication networks. *IEEE Comm. Surveys & Tutorials*, 2016.
- [62] Lav Gupta, Raj Jain, and Gabor Vaszkun. Survey of important issues in uav communication networks. *IEEE Communications Surveys & Tutorials*, 18(2):1123–1152, 2015.
- [63] Kyusuk Han, Jangseong Kim, Kwangjo Kim, and Taeshik Shon. Efficient sensor node authentication via 3GPP mobile communication networks. In *The 17th ACM Conference on Computer and Communications Security, CCS ’10*, pages 687–689, 2010.
- [64] Shibo He, Dong-Hoon Shin, Junshan Zhang, and Jiming Chen. Toward optimal allocation of location dependent tasks in crowdsensing. In *INFOCOM, 2014 Proceedings IEEE*, pages 745–753. IEEE, 2014.

- [65] Tobias Heer, Oscar Garcia-Morchon, René Hummen, Sye Loong Keoh, Sandeep S Kumar, and Klaus Wehrle. Security challenges in the ip-based internet of things. *Wireless Personal Communications*, 61(3):527–542, 2011.
- [66] Jeroen Hoebeke, Ingrid Moerman, Bart Dhoedt, and Piet Demeester. An overview of mobile ad hoc networks: applications and challenges. *Journal-Communications Network*, 3(3):60–66, 2004.
- [67] Dr. Silke Holtmanns, Valtteri Niemi, Philip Ginzboorg, Pekka Laitinen, and Prof. N. Asokan. *Cellular Authentication for Mobile and Internet Services*. Wiley Publishing, 1st edition, 2008.
- [68] Gao Hui, Harold Liu Chi, Tang Jian, Yang Dejun, Hui Pan, and Wang Wendong. Online quality-aware incentive mechanism for mobile crowd sensing with extra bonus. *IEEE Transactions on Mobile Computing*, 2018.
- [69] Christian Huitema. *IPv6: the new Internet protocol*. Prentice Hall PTR, 1998.
- [70] René Hummen, Hossein Shafagh, Shahid Raza, Thiemo Voig, and Klaus Wehrle. Delegation-based authentication and authorization for the IP-based Internet of Things. In *The 11th IEEE International Conference on Sensing, Communication, and Networking (SECON 2014)*, pages 284–292, 2014.
- [71] René Hummen, Jan H. Ziegeldorf, Hossein Shafagh, Shahid Raza, and Klaus Wehrle. Towards viable certificate-based authentication for the Internet of Things. In *The 2nd ACM Workshop on Hot Topics on Wireless Network Security and Privacy, HotWiSec '13*, pages 37–42, 2013.
- [72] Ankur Jain and Edward Y. Chang. Adaptive sampling for sensor networks. In *Proceedings of the 1st International Workshop on Data Management for Sensor Networks: In Conjunction with VLDB 2004, DMSN '04*, pages 10–16, New York, NY, USA, 2004. ACM.
- [73] Ankur Jain and Edward Y Chang. Adaptive sampling for sensor networks. In *Proceedings of the 1st international workshop on Data management for sensor networks: in conjunction with VLDB 2004*, pages 10–16. ACM, 2004.
- [74] H. Jin, H. Huang, L. Su, and K. Nahrstedt. Cost-minimizing mobile access point deployment in workflow-based mobile sensor networks. In *The 22nd Int. Conf. on Network Protocols*, pages 83–94, Oct 2014.
- [75] Haiming Jin, Lu Su, and Klara Nahrstedt. CENTURION: Incentivizing multi-requester mobile crowd sensing. In *INFOCOM 2017-IEEE Conference on Computer Communications, IEEE*, pages 1–9. IEEE, 2017.
- [76] Haiming Jin, Lu Su, and Klara Nahrstedt. Theseus: Incentivizing truth discovery in mobile crowd sensing systems. In *Proceedings of the 18th ACM International Symposium on Mobile Ad Hoc Networking and Computing*, page 1. ACM, 2017.
- [77] Anthony D JoSEP, RAnDy KATz, AnDy KonWinSKi, LEE Gunho, DAViD PATTER-Son, and ARIEL RABKin. A view of cloud computing. *Communications of the ACM*, 53(4), 2010.
- [78] Merkourios Karaliopoulos, Iordanis Koutsopoulos, and Michalis Titsias. First learn then earn: Optimizing mobile crowdsensing campaigns through data-driven user profiling. In *Proceedings of the 17th ACM International Symposium on Mobile Ad Hoc Networking and Computing*, pages 271–280. ACM, 2016.
- [79] Sami Kekki, Walter Featherstone, Yonggang Fang, Pekka Kuure, Alice Li, Anurag Ranjan, Debashish Purkayastha, Feng Jiangping, Danny Frydman, Gianluca Verin, et al. Mec in 5g networks. *ETSI white paper*, 28:1–28, 2018.

- [80] Naoto Kimura and Shahram Latifi. A survey on data compression in wireless sensor networks. In *International Conference on Information Technology: Coding and Computing (ITCC'05)-Volume II*, volume 2, pages 8–13. IEEE, 2005.
- [81] Jouni Korhonen. Applying generic bootstrapping architecture for use with constrained devices. In *Workshop on Smart Object Security*, 2012.
- [82] Shancang Li, Li Da Xu, and Xinheng Wang. Compressed sensing signal and data acquisition in wireless sensor networks and internet of things. *IEEE Transactions on Industrial Informatics*, 9(4):2177–2186, 2012.
- [83] Y. Li, M. Qian, D. Jin, P. Hui, Z. Wang, and S. Chen. Multiple mobile data offloading through disruption tolerant networks. *IEEE Transactions on Mobile Computing*, 13(7):1579–1596, July 2014.
- [84] Song Lin, Benjamin Arai, Dimitrios Gunopulos, and Gautam Das. Region sampling: Continuous adaptive sampling on sensor networks. In *2008 IEEE 24th International Conference on Data Engineering*, pages 794–803. IEEE, 2008.
- [85] Xiao-Yang Liu, Yanmin Zhu, Linghe Kong, Cong Liu, Yu Gu, Athanasios V Vasilakos, and Min-You Wu. Cdc: Compressive data collection for wireless sensor networks. *IEEE Transactions on Parallel and Distributed Systems*, 26(8):2188–2197, 2015.
- [86] Zongqing Lu, Xiao Sun, and Thomas La Porta. Cooperative data offload in opportunistic networks: From mobile devices to infrastructure. *IEEE/ACM Transactions on Networking*, 25(6):3382–3395, 2017.
- [87] Jiangbin Lyu, Yong Zeng, and Rui Zhang. Cyclical multiple access in uav-aided communications: A throughput-delay tradeoff. *IEEE Wireless Communications Letters*, 5(6):600–603, 2016.
- [88] Jiangbin Lyu, Yong Zeng, Rui Zhang, and Teng Joon Lim. Placement optimization of uav-mounted mobile base stations. *IEEE Communications Letters*, 21(3):604–607, 2016.
- [89] Guilherme Maia et al. A distributed data storage protocol for heterogeneous wireless sensor networks with mobile sinks. *Ad Hoc Networks*, 11(5):1588–1602, 2013.
- [90] Arati Manjeshwar and Dharma P Agrawal. Teen: Arouting protocol for enhanced efficiency in wireless sensor networks. In *ipdps*, volume 1, page 189, 2001.
- [91] Abraham Martín-Campillo et al. Evaluating opportunistic networks in disaster scenarios. *J. of Network and computer applications*, 2013.
- [92] Abbas Mehrabi and Kiseon Kim. Maximizing data collection throughput on a path in energy harvesting sensor networks using a mobile sink. *IEEE Transactions on Mobile Computing*, (3):690–704, 2016.
- [93] Arvind Merwaday and Ismail Guvenc. Uav assisted heterogeneous networks for public safety communications. In *2015 IEEE wireless communications and networking conference workshops (WCNCW)*, pages 329–334. IEEE, 2015.
- [94] Farouk Mezghani and Nathalie Mitton. Alternative opportunistic alert diffusion to support infrastructure failure during disasters. *Sensors*, 2017.
- [95] Farouk Mezghani and Nathalie Mitton. Benchmarking smartphone performances for cooperative disaster alert diffusion. In *Adhoc Now*, 2018.
- [96] Daniele Miorandi, Sabrina Sicari, Francesco De Pellegrini, and Imrich Chlamtac. Internet of things: Vision, applications and research challenges. *Ad hoc networks*, 10(7):1497–1516, 2012.

- [97] Monsoon Power Solutions Inc. Mobile Device Power Monitor Manual – Version 1.8. <http://msoon.github.com/powermonitor/PowerTool/doc/Power%20Monitor%20Manual.pdf>, June 2012.
- [98] Mohammad Mozaffari, Walid Saad, Mehdi Bennis, and Merouane Debbah. Drone small cells in the clouds: Design, deployment and performance analysis. In *2015 IEEE Global Communications Conference (GLOBECOM)*, pages 1–6. IEEE, 2015.
- [99] Kamesh Namuduri. When disaster strikes, flying cell towers could aid search and rescue. *IEEE Spectrum*, Aug, 2017.
- [100] Kim Thuat Nguyen, Maryline Laurent, and Nouha Oualha. Survey on secure communication protocols for the internet of things. *Ad Hoc Networks*, 32:17–31, 2015.
- [101] Sergio F Ochoa and Rodrigo Santos. Human-centric wireless sensor networks to improve information availability during urban search and rescue activities. *Information Fusion*, 22:71–84, 2015.
- [102] Se-Ra Oh and Young-Gab Kim. Security requirements analysis for the iot. In *2017 International Conference on Platform Technology and Service (PlatCon)*, pages 1–6. IEEE, 2017.
- [103] Sharief MA Oteafy and Hossam S Hassanein. IoT in the fog: A roadmap for data-centric IoT development. *IEEE Communications Magazine*, 56(3):157–163, 2018.
- [104] Apostolos Papageorgiou, Bin Cheng, and Ernő Kovacs. Real-time data reduction at the network edge of internet-of-things systems. In *2015 11th International Conference on Network and Service Management (CNSM)*, pages 284–291. IEEE, 2015.
- [105] Gian Paolo Perrucci, Frank HP Fitzek, and Jörg Widmer. Survey on energy consumption entities on the smartphone platform. In *2011 IEEE 73rd vehicular technology conference (VTC Spring)*, pages 1–6. IEEE, 2011.
- [106] R. Pozza, M. Nati, S. Georgoulas, A. Gluhak, K. Moessner, and S. Krco. CARD: Context-aware resource discovery for mobile Internet of Things scenarios. In *IEEE WoWMoM 2014*, pages 1–10, June 2014.
- [107] R. Pozza, M. Nati, S. Georgoulas, K. Moessner, and A. Gluhak. Neighbor discovery for opportunistic networking in Internet of Things scenarios: A survey. *IEEE Access*, 3:1101–1131, 2015.
- [108] Lingjun Pu, Xu Chen, Jingdong Xu, and Xiaoming Fu. Crowdlet: Optimal worker recruitment for self-organized mobile crowdsourcing. In *Computer Communications, IEEE INFOCOM 2016-The 35th Annual IEEE International Conference on*, pages 1–9. IEEE, 2016.
- [109] Guntur Dharma Putra, Azkario Rizky Pratama, Alexander Lazovik, and Marco Aiello. Comparison of energy consumption in wi-fi and bluetooth communication in a smart building. In *2017 IEEE 7th Annual Computing and Communication Workshop and Conference (CCWC)*, pages 1–6. IEEE, 2017.
- [110] Suhas Rao, Devaiah Chendanda, Chetan Deshpande, and Vishwas Lakkundi. Implementing lw2m in constrained iot devices. In *2015 IEEE Conference on Wireless Sensors (ICWiSe)*, pages 52–57. IEEE, 2015.
- [111] Bushra Rashid and Mubashir Husain Rehmani. Applications of wireless sensor networks for urban areas: A survey. *Journal of network and computer applications*, 60:192–219, 2016.

- [112] Shahid Raza, Hossein Shafagh, Kasun Hewage, René Hummen, and Thiemo Voigt. Lithe: Lightweight Secure CoAP for the Internet of Things. *IEEE Sensors Journal*, 13(10):3711–3720, 2013.
- [113] Usman Raza, Parag Kulkarni, and Mahesh Sooriyabandara. Low power wide area networks: An overview. *IEEE Communications Surveys & Tutorials*, 19(2):855–873, 2017.
- [114] Fabio Ruini, Angelo Cangelosi, and Franck Zetule. Individual and cooperative tasks performed by autonomous mav teams driven by embodied neural network controllers. In *2009 International Joint Conference on Neural Networks*, pages 2717–2724. IEEE, 2009.
- [115] Dario Sabella, Alessandro Vaillant, Pekka Kuure, Uwe Rauschenbach, and Fabio Giust. Mobile-edge computing architecture: The role of mec in the internet of things. *IEEE Consumer Electronics Magazine*, 5(4):84–91, 2016.
- [116] Toshikazu Sakano, Zubair Md Fadlullah, Thuan Ngo, Hiroki Nishiyama, Masataka Nakazawa, Fumiyuki Adachi, Nei Kato, Atsushi Takahara, Tomoaki Kumagai, Hiromichi Kasahara, et al. Disaster-resilient networking: a new vision based on movable and deployable resource units. *IEEE Network*, 27(4):40–46, 2013.
- [117] Jesús Sánchez-García, José Manuel García-Campos, SL Toral, DG Reina, and Federico Barrero. An intelligent strategy for tactical movements of UAVs in disaster scenarios. *International Journal of Distributed Sensor Networks*, 2016:18, 2016.
- [118] Mohit Sethi, Elena Oat, Mario Di Francesco, and Tuomas Aura. Secure bootstrapping of cloud-managed ubiquitous displays. In *The 2014 ACM International Joint Conference on Pervasive and Ubiquitous Computing (UbiComp 2014)*, pages 739–750, September 2014.
- [119] Kunal Shah, Mario Di Francesco, and Mohan Kumar. Distributed resource management in wireless sensor networks using reinforcement learning. *Wireless Networks*, 19(5):705–724, July 2013.
- [120] Weisong Shi, Jie Cao, Quan Zhang, Youhuizi Li, and Lanyu Xu. Edge computing: Vision and challenges. *IEEE Internet of Things Journal*, 3(5):637–646, 2016.
- [121] Ramanpreet Singh, Michael Thompson, Steffy Ann Mathews, Oghenetega Agbogidi, Kunal Bhadane, and Kamesh Namuduri. Aerial base stations for enabling cellular communications during emergency situation. In *2017 International Conference on Vision, Image and Signal Processing (ICVISP)*, pages 103–108. IEEE, 2017.
- [122] Michael J. Tarr. Visual Pattern Recognition. *Encyclopedia of psychology*, pages 1–4, 2000.
- [123] Kleanthis Thramboulidis, Danai C Vachtsevanou, and Alexandros Solanos. Cyber-physical microservices: An iot-based framework for manufacturing systems. In *2018 IEEE Industrial Cyber-Physical Systems (ICPS)*, pages 232–239. IEEE, 2018.
- [124] Chun-Wei Tsai, Chin-Feng Lai, Ming-Chao Chiang, and Laurence T Yang. Data mining for internet of things: A survey. *IEEE Communications Surveys & Tutorials*, 16(1):77–97, 2013.
- [125] Jiangtao Wang, Yasha Wang, Daqing Zhang, and Sumi Helal. Energy saving techniques in mobile crowd sensing: Current state and future opportunities. *IEEE Communications Magazine*, 56(5):164–169, 2018.

- [126] Tian Wang, Md Zakirul Alam Bhuiyan, Guojun Wang, Md Arafatur Rahman, Jie Wu, and Jiannong Cao. Big data reduction for a smart city's critical infrastructural health monitoring. *IEEE Communications Magazine*, 56(3):128–133, 2018.
- [127] Tian Wang, Lei Qiu, Guangquan Xu, Arun Kumar Sangaiah, and Anfeng Liu. Energy-efficient and trustworthy data collection protocol based on mobile fog computing in internet of things. *IEEE Transactions on Industrial Informatics*, 2019.
- [128] Rolf H Weber. Internet of things—new security and privacy challenges. *Computer law & security review*, 26(1):23–30, 2010.
- [129] Weimin Wen, Shenghui Zhao, Cuijuan Shang, and Chih-Yung Chang. EAPC: Energy-aware path construction for data collection using mobile sink in wireless sensor networks. *IEEE Sensors Journal*, 18(2):890–901, 2018.
- [130] Zhenyu Wen, Renyu Yang, Peter Garraghan, Tao Lin, Jie Xu, and Michael Rovatsos. Fog orchestration for internet of things services. *IEEE Internet Computing*, 21(2):16–24, 2017.
- [131] Rebecca Willett, Aline Martin, and Robert Nowak. Backcasting: adaptive sampling for sensor networks. In *Proceedings of the 3rd international symposium on Information processing in sensor networks*, pages 124–133. ACM, 2004.
- [132] Mou Wu, Liansheng Tan, and Naixue Xiong. Data prediction, compression, and recovery in clustered wireless sensor networks for environmental monitoring applications. *Information Sciences*, 329:800–818, 2016.
- [133] M. Xiao, J. Wu, He Huang, L. Huang, and Chang Hu. Deadline-sensitive user recruitment for mobile crowdsensing with probabilistic collaboration. In *The 24th Int. Conf. on Network Protocols*, pages 1–10, Nov 2016.
- [134] D. Xu et al. A survey of opportunistic offloading. *IEEE Comm. Surveys & Tutorials*, 20(3), 2018.
- [135] Dejun Yang, Guoliang Xue, Xi Fang, and Jian Tang. Crowdsourcing to smartphones: Incentive mechanism design for mobile phone sensing. In *Proceedings of the 18th annual international conference on Mobile computing and networking*, pages 173–184. ACM, 2012.
- [136] Dejun Yang, Guoliang Xue, Xi Fang, and Jian Tang. Incentive mechanisms for crowdsensing: Crowdsourcing with smartphones. *IEEE/ACM transactions on networking*, 24(3):1732–1744, 2015.
- [137] Shusen Yang, Usman Adeel, Yad Tahir, and Julie A McCann. Practical opportunistic data collection in wireless sensor networks with mobile sinks. *IEEE Trans. on Mobile Computing*, 16(5):1420–1433, 2017.
- [138] Tianqi Yu, Xianbin Wang, and Abdallah Shami. A novel fog computing enabled temporal data reduction scheme in iot systems. In *GLOBECOM 2017-2017 IEEE Global Communications Conference*, pages 1–5. IEEE, 2017.
- [139] Peiyan Yuan et al. Recent progress in routing protocols of mobile opportunistic networks: A clear taxonomy, analysis and evaluation. *JNCA*, 2016.
- [140] Yong Zeng, Rui Zhang, and Teng Joon Lim. Wireless communications with unmanned aerial vehicles: Opportunities and challenges. *IEEE Communications Magazine*, 54(5):36–42, 2016.
- [141] Yufeng Zhan, Yuanqing Xia, Jinhui Zhang, and Yu Wang. Incentive mechanism design in mobile opportunistic data collection with time sensitivity. *IEEE Internet of Things Journal*, 5(1):246–256, 2018.

References

- [142] Xinglin Zhang, Zheng Yang, Wei Sun, Yunhao Liu, Shaohua Tang, Kai Xing, and Xufei Mao. Incentives for mobile crowd sensing: A survey. *IEEE Communications Surveys & Tutorials*, 18(1):54–67, 2015.
- [143] Ruiting Zhou, Zongpeng Li, and Chuan Wu. A truthful online mechanism for location-aware tasks in mobile crowd sensing. *IEEE Transactions on Mobile Computing*, 2017.

Errata

Publication IV

Line 7 in Algorithm 1 should be $CH_i == m$ instead of $CH_i = m$.

Line 8 is in the same algorithm should be $ACTIVATED = FALSE$ instead of $ACTIVATED == FALSE$.

ISBN 978-952-60-3925-1 (printed)
ISBN 978-952-60-3926-8 (pdf)
ISSN 1799-4934 (printed)
ISSN 1799-4942 (pdf)

Aalto University
School of Science
Department of Computer Science
www.aalto.fi

**BUSINESS +
ECONOMY**

**ART +
DESIGN +
ARCHITECTURE**

**SCIENCE +
TECHNOLOGY**

CROSSOVER

**DOCTORAL
DISSERTATIONS**